TIBCO ActiveMatrix BusinessWorks™

Error Codes

Software Release 5.14
August 2018

Two-Second Advantage®

Important Information

SOME TIBCO SOFTWARE EMBEDS OR BUNDLES OTHER TIBCO SOFTWARE. USE OF SUCH EMBEDDED OR BUNDLED TIBCO SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED TIBCO SOFTWARE. THE EMBEDDED OR BUNDLED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER TIBCO SOFTWARE OR FOR ANY OTHER PURPOSE.

USE OF TIBCO SOFTWARE AND THIS DOCUMENT IS SUBJECT TO THE TERMS AND CONDITIONS OF A LICENSE AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED SOFTWARE LICENSE AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER LICENSE AGREEMENT WHICH IS DISPLAYED DURING DOWNLOAD OR INSTALLATION OF THE SOFTWARE (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH SOFTWARE LICENSE AGREEMENT OR CLICKWRAP END USER LICENSE AGREEMENT, THE LICENSE(S) LOCATED IN THE “LICENSE” FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

ANY SOFTWARE ITEM IDENTIFIED AS THIRD PARTY LIBRARY IS AVAILABLE UNDER SEPARATE SOFTWARE LICENSE TERMS AND IS NOT PART OF A TIBCO PRODUCT. AS SUCH, THESE SOFTWARE ITEMS ARE NOT COVERED BY THE TERMS OF YOUR AGREEMENT WITH TIBCO, INCLUDING ANY TERMS CONCERNING SUPPORT, MAINTENANCE, WARRANTIES, AND INDEMNITIES. DOWNLOAD AND USE THESE ITEMS IS SOLELY AT YOUR OWN DISCRETION AND SUBJECT TO THE LICENSE TERMS APPLICABLE TO THEM. BY PROCEEDING TO DOWNLOAD, INSTALL OR USE ANY OF THESE ITEMS, YOU ACKNOWLEDGE THE FOREGOING DISTINCTIONS BETWEEN THESE ITEMS AND TIBCO PRODUCTS.

This document contains confidential information that is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of TIBCO Software Inc.

TIBCO, Two-Second Advantage, TIBCO Hawk, TIBCO Rendezvous, TIBCO Runtime Agent, TIBCO ActiveMatrix BusinessWorks, TIBCO Administrator, TIBCO Designer, TIBCO ActiveMatrix Service Gateway, TIBCO BusinessEvents, TIBCO BusinessConnect, and TIBCO BusinessConnect Trading Community Management are either registered trademarks or trademarks of TIBCO Software Inc. in the United States and/or other countries.

Enterprise Java Beans (EJB), Java Platform Enterprise Edition (Java EE), Java 2 Platform Enterprise Edition (J2EE), and all Java-based trademarks and logos are trademarks or registered trademarks of Oracle Corporation in the U.S. and other countries.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only.

THIS SOFTWARE MAY BE AVAILABLE ON MULTIPLE OPERATING SYSTEMS. HOWEVER, NOT ALL OPERATING SYSTEM PLATFORMS FOR A SPECIFIC SOFTWARE VERSION ARE RELEASED AT THE SAME TIME. SEE THE README FILE FOR THE AVAILABILITY OF THIS SOFTWARE VERSION ON A SPECIFIC OPERATING SYSTEM PLATFORM.

THIS DOCUMENT IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. TIBCO SOFTWARE INC. MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THIS DOCUMENT AT ANY TIME.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "READ ME" FILES.

Copyright © 2001-2018 TIBCO Software Inc. ALL RIGHTS RESERVED.

Contents

Preface . . . . . **vii**

Changes from the Previous Release of this Guide viii

Related Documentation ix

TIBCO ActiveMatrix BusinessWorks Documentation ix

Other TIBCO Product Documentation x

Typographical Conventions xi

TIBCO Product Documentation and Support Services xiii

How to Access TIBCO Documentation xiii

How to Contact TIBCO Support xiii

How to Join TIBCO Community xiii

Chapter 1 Process Engine **1**

Process Engine Error Codes 2

Chapter 2 Common Errors **37**

Common Error Codes 38

Chapter 3 XPath **61**

XPath Error Codes 62

Chapter 4 ActiveEnterprise Adapter Palette **83**

ActiveEnterprise Adapter Error Codes 84

Chapter 5 File Palette **93**

File Error Codes 94

Chapter 6 FTP Palette **99**

FTP Error Codes 100

Chapter 7 General Activities Palette **107**

General Activities Error Codes 108

Chapter 8 HTTP Palette 115
HTTP Error Codes 116

Chapter 9 Java Palette 131
Java Error Codes 132

Chapter 10 JDBC Palette 153
JDBC Error Codes 154

Chapter 11 JMS Palette 165
JMS Error Codes. 166

Chapter 12 Mail Palette 183
Mail Error Codes 184

Chapter 13 Manual Work Palette 193
Manual Work Error Codes. 194

Chapter 14 Parse Palette 203
Parse Error Codes 204

Chapter 15 Rendezvous Palette 209
TIBCO Rendezvous Error Codes 210

Chapter 16 SOAP Palette 217
SOAP Error Codes 218

Chapter 17 TCP Palette 231
TCP Error Codes. 232

Chapter 18 Transaction Palette 239
Transaction Error Codes 240

Chapter 19 XML Activities Palette. 255
XML Error Codes 256

Preface

This manual lists the error codes that can be returned by TIBCO ActiveMatrix BusinessWorks.

Topics

- Changes from the Previous Release of this Guide, page viii
- Related Documentation, page ix
- Typographical Conventions, page xi
- TIBCO Product Documentation and Support Services, page xiii

Changes from the Previous Release of this Guide

There are no changes in this guide during this release.

Related Documentation

This section lists documentation resources you may find useful.

TIBCO ActiveMatrix BusinessWorks Documentation

The following documents form the TIBCO ActiveMatrix BusinessWorks documentation set:

- *TIBCO ActiveMatrix BusinessWorks Concepts* Read this manual before reading any other manual in the documentation set. This manual describes terminology and concepts of TIBCO ActiveMatrix BusinessWorks, and the other manuals in the documentation set assume you are familiar with the information in this manual.
- *TIBCO ActiveMatrix BusinessWorks Getting Started* This manual steps you through a very simple example of designing, deploying, and monitoring a TIBCO ActiveMatrix BusinessWorks process.
- *TIBCO ActiveMatrix BusinessWorks Process Design Guide* This manual describes how to create, edit, and test business processes using TIBCO ActiveMatrix BusinessWorks.
- *TIBCO ActiveMatrix BusinessWorks Palette Reference* This manual describes each of the palettes available in TIBCO ActiveMatrix BusinessWorks.
- *TIBCO ActiveMatrix BusinessWorks Administration* This manual describes how to use TIBCO Administrator to deploy, manage, and monitor TIBCO ActiveMatrix BusinessWorks processes.
- *TIBCO ActiveMatrix BusinessWorks Installation* Read this manual for information on installing one or more components of TIBCO ActiveMatrix BusinessWorks and setting up a TIBCO ActiveMatrix BusinessWorks domain.
- *TIBCO ActiveMatrix BusinessWorks Error Codes* This manual describes errors returned by TIBCO ActiveMatrix BusinessWorks.
- *TIBCO ActiveMatrix BusinessWorks Release Notes* Read the release notes for a list of new and changed features. This document also contains lists of known issues and closed issues for this release.

Other TIBCO Product Documentation

TIBCO ActiveMatrix BusinessWorks is used with other products. You may find it useful to read the documentation for the following TIBCO products:

- TIBCO Designer™ software: TIBCO Designer is an easy to use graphical user interface for design-time configuration of TIBCO applications. TIBCO Designer includes online help for each palette.
- TIBCO Administrator™ software: TIBCO Administrator is the monitoring and managing interface for new-generation TIBCO products such as TIBCO ActiveMatrix BusinessWorks.
- TIBCO Adapter software
- Third-Party Documentation

Typographical Conventions

The following typographical conventions are used in this manual.

Table 1 General Typographical Conventions

Convention	Use
ENV_NAME *TIBCO_HOME* *BW_HOME*	TIBCO products are installed into an installation environment. A product installed into an installation environment does not access components in other installation environments. Incompatible products and multiple instances of the same product must be installed into different installation environments. An installation environment consists of the following properties: • **Name** Identifies the installation environment. This name is referenced in documentation as *ENV_NAME*. On Microsoft Windows, the name is appended to the name of Windows services created by the installer and is a component of the path to the product shortcut in the Windows Start > All Programs menu. • **Path** The folder into which the product is installed. This folder is referenced in documentation as *TIBCO_HOME*. TIBCO ActiveMatrix BusinessWorks installs into a directory within a *TIBCO_HOME*. This directory is referenced in documentation as *BW_HOME*. The default value of *BW_HOME* depends on the operating system. For example on Windows systems, the default value is `C:\tibco\bw\5.12`.
`code font`	Code font identifies commands, code examples, filenames, pathnames, and output displayed in a command window. For example: Use `MyCommand` to start the foo process.
`bold code font`	Bold code font is used in the following ways: • In procedures, to indicate what a user types. For example: Type **`admin`**. • In large code samples, to indicate the parts of the sample that are of particular interest. • In command syntax, to indicate the default parameter for a command. For example, if no parameter is specified, `MyCommand` is enabled: MyCommand [**`enable`** | disable]

Table 1 General Typographical Conventions (Cont'd)

Convention	Use
italic font	Italic font is used in the following ways: • To indicate a document title. For example: See *TIBCO ActiveMatrix BusinessWorks Concepts*. • To introduce new terms For example: A portal page may contain several *portlets*. Portlets are mini-applications that run in a portal. • To indicate a variable in a command or code syntax that you must replace. For example: `MyCommand` *pathname*
Key combinations	Key name separated by a plus sign indicate keys pressed simultaneously. For example: Ctrl+C. Key names separated by a comma and space indicate keys pressed one after the other. For example: Esc, Ctrl+Q.
	The note icon indicates information that is of special interest or importance, for example, an additional action required only in certain circumstances.
	The tip icon indicates an idea that could be useful, for example, a way to apply the information provided in the current section to achieve a specific result.
	The warning icon indicates the potential for a damaging situation, for example, data loss or corruption if certain steps are taken or not taken.

TIBCO Product Documentation and Support Services

For information about this product, you can read the documentation, contact TIBCO Support, or join TIBCO Community.

How to Access TIBCO Documentation

Documentation for TIBCO products is available on the TIBCO Product Documentation website mainly in the HTML and PDF formats.

The TIBCO Product Documentation website is updated frequently and is more current than any other documentation included with the product. To access the latest documentation, visit https://docs.tibco.com.

Documentation for TIBCO ActiveMatrix BusinessWorks™ is available on the TIBCO ActiveMatrix BusinessWorks™ Product Documentation page.

How to Contact TIBCO Support

You can contact TIBCO Support in the following ways:

- For an overview of TIBCO Support, visit https://www.tibco.com/services/support.
- For accessing the Support Knowledge Base and getting personalized content about products you are interested in, visit the TIBCO Support portal at https://support.tibco.com.
- For creating a Support case, you must have a valid maintenance or support contract with TIBCO. You also need a user name and password to log in to https://support.tibco.com. If you do not have a user name, you can request one by clicking **Register** on the website.

How to Join TIBCO Community

TIBCO Community is the official channel for TIBCO customers, partners, and employee subject matter experts to share and access their collective experience. TIBCO Community offers access to Q&A forums, product wikis, and best practices. It also offers access to extensions, adapters, solution accelerators, and tools that extend and enable customers to gain full value from TIBCO products. In addition, users can submit and vote on feature requests from within the TIBCO Ideas Portal. For a free registration, go to https://community.tibco.com.

Chapter 1 Process Engine

This chapter lists error codes returned by the TIBCO ActiveMatrix BusinessWorks process engine.

Topics

- Process Engine Error Codes, page 2

Process Engine Error Codes

BWENGINE-100001: %1

Role: errorRole

Category: BW-Core

Description: used for logging generic exception, detailed message code not provided

Resolution: Depends on content of exception

BWENGINE-100002: %1

Role: errorRole

Category: BW-Core

Description: used when underlying support reported an error

Resolution: Depends on content of exception

BWENGINE-100003: %1

Role: errorRole

Category: BW-Core

Description: used for startup failures

Resolution: Depends on failure details

BWENGINE-100004: %1

Role: errorRole

Category: BW-Core

Description: used for shutdown failures

Resolution: Depends on failure details

BWENGINE-100005: Load Error

Role: errorRole

Category: BW-Core

Description: Error loading project

Resolution: Depends on failure details

BWENGINE-100006: Load Error: ref=%1, class=%2

Role: errorRole

Category: BW-Core

Description: Error loading project

Resolution: Depends on failure details

BWENGINE-100007: useSeparateThread may only be called from within the init() method

Role: errorRole

Category: BW-Core

Description: useSeparateThread may only be called from within the init() method

Resolution: Correct activity code

BWENGINE-100008: Cannot find specified Engine.Database.Configuration: %1

Role: errorRole

Category: BW-Core

Description: Cannot find specified Engine.Database.Configuration

Resolution: Re-deploy specifying correct database shared configuration

---

BWENGINE-100009: Access error for Engine.Database.Configuration: %1

Role: errorRole

Category: BW-Core

Description: Access error for Engine.Database.Configuration

Resolution:

BWENGINE-100010: Plugin agent class name not specified

Role: errorRole

Category: BW-Core

Description: Plugin agent class name not specified

Resolution: Correct plugin definition file

BWENGINE-100011: Error processing plugin agent [%1]

Role: errorRole

Category: BW-Core

Description: Error processing plugin agent

Resolution:

BWENGINE-100012: Initialization error in [%1/%2]

Role: errorRole

Category: BW-Core

Description: The activity init method detected an error

Resolution: Depends on content of "caused by" exception

BWENGINE-100013: Termination error in [%1/%2]

Role: errorRole

Category: BW-Core

Description: The activity destroy method detected an error

Resolution: Depends on content of "caused by" exception

BWENGINE-100014: process initialization failed for %1

Role: errorRole

Category: BW-Core

Description: The specified process definition could not be initialized. It is unavailable for use.

Resolution: Depends on content of "caused by" exception

BWENGINE-100015: Could not find process definition: %1

Role: errorRole

Category: BW-Core

Description: The specified process definition could not found.

Resolution: Process loading may have failed or process loading may not have been requested or may be using incorrect process reference.

BWENGINE-100016: failed to spawn called process

Role: errorRole

Category: BW-Core

Description: The Call Process activity, spawn option, failed.

Resolution:

BWENGINE-100017: failed to execute called process

Role: errorRole

Category: BW-Core

Description: The Call Process activity failed to execute called process

Resolution:

BWENGINE-100018: Process definition name not specified

Role: errorRole

Category: BW-Core

Description: Process name is required, but has not been specified

Resolution: Enter required item.

BWENGINE-100019: Can not checkpoint in middle of transaction

Role: errorRole

Category: BW-Core

Description: A checkpoint may not occur within a transaction group

Resolution: Correct process design

BWENGINE-100020: Activation error with process starter [%1]

Role: errorRole

Category: BW-Core

Description: Activation error with a process starter

Resolution: Depends on content of exception

BWENGINE-100021: Checkpoint failed

Role: errorRole

Category: BW-Core

Description: Checkpoint attempt failed

Resolution: Depends on content of exception

BWENGINE-100022: Error restarting process %1 from checkpoint

Role: errorRole

Category: BW-Core

Description: Error trying to restart process from checkpoint

Resolution: Depends on content of exception. May be that checkpoint was taken on a different version of BW.

BWENGINE-100023: Error restarting checkpoint, process definition not found: %1

Role: errorRole

Category: BW-Core

Description: Can not find the process definition needed by the checkpointed process

Resolution: Make sure same processes are deployed when restarting engine as when checkpoint was taken.

BWENGINE-100024: %1 Unable to delete checkpoint

Role: errorRole

Category: BW-Core

Description: Failed to deleted checkpoint

Resolution: Depends on content of exception. If checkpoint not deleted, job could be restarted on next engine startup.

BWENGINE-100025: Failed to get next job id block

Role: errorRole

Category: BW-Core

Description: Can not get the next block of job ids.

Resolution: Depends on content of exception

BWENGINE-100026: Error with fault tolerant setup

Role: errorRole

Category: BW-Core

Description: Error with fault tolerant setup. Engine will not start.

Resolution: Depends on content of exception

BWENGINE-100027: Notify error: group = %1, key = %2

Role: errorRole

Category: BW-Core

Description: Notify unable to complete wakeup of waiting entity

Resolution: Depends on content of exception

BWENGINE-100028: Deactivation error with process starter [%1]

Role: errorRole

Category: BW-Core

Description: Deactivation error with a process starter

Resolution: Depends on content of exception

BWENGINE-100029: Activity timed out

Role: errorRole

Category: BW-Core

Description: Activity did not complete execution within the specified time limit

Resolution:

BWENGINE-100030: Input data invalid

Role: errorRole

Category: BW-Core

Description: Activity input data validation error

Resolution:

BWENGINE-100031: Output data invalid

Role: errorRole

Category: BW-Core

Description: Activity output data validation error

Resolution:

BWENGINE-100032: Error output data invalid

Role: errorRole

Category: BW-Core

Description: Activity error output data vailidation error

Resolution:

BWENGINE-100033: Activity providing output data but none is expected

Role: errorRole

Category: BW-Core

Description: Activity has output when none was expected.

Resolution:

BWENGINE-100034: transition cycle detected in [%1/%2]

Role: errorRole

Category: BW-Core

Description: This process contains an illegal transition cycle

Resolution: This process does not allow transition cycles

BWENGINE-100035: error on exit from activity, no matching transition

Role: errorRole

Category: BW-Core

Description: No transition out of activity evaluated true. This generates an Error condition.

Resolution: Add transition or check conditions of existing transitions

---

BWENGINE-100036: error on exit from activity, too many matching transitions

Role: errorRole

Category: BW-Core

Description: Multiple transitions may not be taken when transition cycles are allowed.

Resolution: This process allows transition cycles and does not allow two transitions from any activity to be true at the same time.

BWENGINE-100037: Repository not found: %1

Role: errorRole

Category: BW-Core

Description: Can not locate specified repository

Resolution: Make sure using correct reference and server is available

---

BWENGINE-100038: Repository not specified

Role: errorRole

Category: BW-Core

Description: No repository location specified

Resolution: Specify location of repository

BWENGINE-100039: Variable name not specfied

Role: errorRole

Category: BW-Plugin

Description: Variable name to set has not been specified

Resolution: Specify variable name in configuration panel

BWENGINE-100040: Undefined variable [%1]

Role: errorRole

Category: BW-Plugin

Description: Unable to find definition for specified variable

Resolution: Please look at exception for more details

BWENGINE-100041: Mapping Error

Role: errorRole

Category: BW-Core

Description: Problem find with mapping

Resolution: Please look at mapping for more details

BWENGINE-100042: Configured Fault not found [%1]

Role: errorRole

Category: BW-Core

Description: Can not find the specified fault name

Resolution:

BWENGINE-100043: Error resolving Fault [%1]

Role: errorRole

Category: BW-Core

Description: Error encountered resolving specified fault name

Resolution:

BWENGINE-100044: File not found [%1]

Role: errorRole

Category: BW-Core

Description: Can not find specified filename

Resolution:

BWENGINE-100045: Pager can not load [%1]

Role: errorRole

Category: BW-Core

Description: Can not load the page file for the specified job

Resolution:

BWENGINE-100046: Shutdown due to startup error

Role: errorRole

Category: BW-Core

Description: Engine shutdown due to startup error

Resolution:

BWENGINE-100047: %1 Error in [%2/%3]

Role: errorRole

Category: BW-Core

Description:

Resolution:

BWENGINE-100048: Error in [%1/%2]

Role: errorRole

Category: BW-Core

Description:

Resolution:

BWENGINE-100049: Error restarting [%1], can not acquire lock [%2]

Role: errorRole

Category: BW-Core

Description: Error trying to restart process from checkpoint

Resolution: Process requires lock that is already acquired.

BWENGINE-100050: Activation error with plugin agent [%1]

Role: errorRole

Category: BW-Core

Description: Activation error with plugin agent

Resolution: Depends on content of exception

BWENGINE-100051: Unable to create trace object

Role: errorRole

Category: BW-Core

Description: Unable to create trace object

Resolution: Depends on content of exception

BWENGINE-100052: Configuration error on input type for [%1]: %2

Role: errorRole

Category: BW-Core

Description: Can not load process input type

Resolution: Depends on content of details

BWENGINE-100053: Configuration error on output type for [%1]: %2

Role: errorRole

Category: BW-Core

Description: Can not load process output type

Resolution: Depends on content of details

BWENGINE-100054: Configuration error on error output type for [%1]: %2

Role: errorRole

Category: BW-Core

Description: Can not load process error output type

Resolution: Depends on content of details

BWENGINE-100055: Configuration error on user process variables for [%1]: %2

Role: errorRole

Category: BW-Core

Description: Can not load user process variable types

Resolution: Depends on content of details

BWENGINE-100056: Loop index slot name already used: [%1]

Role: errorRole

Category: BW-Core

Description: Loop index slot name already used

Resolution: Index variable name already taken. Specify another name not already in use.

BWENGINE-100057: Invalid loop index slot name: [%1]

Role: errorRole

Category: BW-Core

Description: Invalid loop index slot name

Resolution: Specify a valid variable name

BWENGINE-100058: Accumulate output variable name already used: %1

Role: errorRole

Category: BW-Core

Description: Accumulate output variable name already used

Resolution: Accumulate variable name already taken. Specify another name not already in use.

BWENGINE-100059: Invalid accumulate output variable name: %1

Role: errorRole

Category: BW-Core

Description: Invalid accumulate output variable name

Resolution: Specify a valid variable name

BWENGINE-100060: No output to accumulate from activity: %1

Role: errorRole

Category: BW-Core

Description: No output to accumulate from activity

Resolution: Can only accumulate output from an activity that has output

---

BWENGINE-100061: Bad activity name for accumulate output: %1

Role: errorRole

Category: BW-Core

Description: Bad activity name for accumulate output

Resolution: Can only accumulate output from an activity within the group

---

BWENGINE-100062: Slot name already used: %1

Role: errorRole

Category: BW-Core

Description: Slot name already used

Resolution: Slot name already used. Specify another name not already in use.

BWENGINE-100063: Process variable schema error

Role: errorRole

Category: BW-Core

Description: The schema for a process variable had an error

Resolution: Please look at the process variables tab for more information

---

BWENGINE-100064: Process Start schema error

Role: errorRole

Category: BW-Core

Description: The Output schema for the process start had an error

Resolution: Please look at the Output Editor tab of the process start for more information

---

BWENGINE-100065: Process End schema error

Role: errorRole

Category: BW-Core

Description: The Input schema for the process end had an error

Resolution: Please look at the Input Editor tab of the process end for more information

---

BWENGINE-100066: Process Fault schema error

Role: errorRole

Category: BW-Core

Description: An process fault/error schema had an error

Resolution: Please look at the Error Schemas tab of the process end for more information

---

BWENGINE-100067: Call process input failed validation

Role: errorRole

Category: BW-Core

Description: The input data passed to the Call Process activity did not conform to the input of the called process

Resolution: Please check the input mappings for the Call Process activity

---

BWENGINE-100068: Call process results failed validation

Role: errorRole

Category: BW-Core

Description: The process that was called returned results that were not expected by the Call Process activity

Resolution: Please check the input mappings for the End activity in the process that was called

---

BWENGINE-100069: The override process [%1] expects different input than the process the Call Process activity was modeled on [%2]

Role: errorRole

Category: BW-Core

Description: The Process Name Dynamic Override option pointed, at run time, to a process with different input than the model process used to configure the activity at design time

Resolution: Please check the Process Name Dynamic Override expression in the activity configuration

---

BWENGINE-100070: The process [%1] is not a callable process

Role: errorRole

Category: BW-Core

Description: The specified process is not a callable process (it has a process starter instead)

Resolution: Please check the process names in the activity configuration

---

BWENGINE-100071: Multi-engine shared variable or lock requires engine configured to use database

Role: errorRole

Category: BW-Core

Description: Multi-engine shared variable or lock requires engine configured to use database

Resolution: Configure engine to use database

BWENGINE-100072: Undefined reference [%1]

Role: errorRole

Category: BW-Core

Description: Unable to find definition for specified reference

Resolution: Please look at exception for more details

BWENGINE-100073: Unable to parse initial value

Role: errorRole

Category: BW-Core

Description: Unable to parse initial value

Resolution: Correct error in definition of initial value

BWENGINE-100074: Persistent storage error

Role: errorRole

Category: BW-Core

Description: Problem accessing persistent storage

Resolution: Please look at exception for more details

BWENGINE-100075: Variable not set

Role: errorRole

Category: BW-Core

Description: Variable not set and has no initial value

Resolution: Set variable before use or define initial value

BWENGINE-100076: Shared variable schema error

Role: errorRole

Category: BW-Core

Description: The schema for a shared variable had an error

Resolution: Please look at exception for more details

BWENGINE-100077: Error with Transaction Manager [%1]

Role: errorRole

Category: BW-Core

Description: Error with the specified Transaction Manager

Resolution: Please look at exception for more details

BWENGINE-100078: Transaction Manager not specified

Role: errorRole

Category: BW-Core

Description: Transaction Manager not specified

Resolution: Specify transaction manager

BWENGINE-100079: Duplicate key [%1] already used by job [%2]

Role: errorRole

Category: BW-Core

Description: Another job has already registered this key

Resolution:

BWENGINE-100080: Only one duplicate key allowed per job

Role: errorRole

Category: BW-Core

Description: This job has already registered another key

Resolution:

BWENGINE-100081: XA Resource not available from [%1]

Role: errorRole

Category: BW-Core

Description: The specified event source did not provide an XA Resource

Resolution: Check event source configuration

BWENGINE-100082: Event context from [%1] not found

Role: errorRole

Category: BW-Core

Description: The specified event source did not provide an event context

Resolution: Check event source configuration

BWENGINE-100083: Checkpoint verify failed

Role: errorRole

Category: BW-Core

Description: Attempt to verify checkpoint failed

Resolution: Depends on content of exception

BWENGINE-100084: Transaction rollback error

Role: errorRole

Category: BW-Core

Description: Exception thrown during transaction rollback

Resolution: Depends on content of exception

BWENGINE-100085: Configuration error, checkpoint can not join transaction

Role: errorRole

Category: BW-Core

Description: Configuration error, checkpoint can not join transaction

Resolution: Correct configuration

BWENGINE-100086: Engine commands are not enabled

Role: errorRole

Category: BW-Plugin

Description: Engine commands are not enabled so Engine Command activity can not be used

Resolution: Enable engine commands

BWENGINE-100087: Error invoking engine command [%1]

Role: errorRole

Category: BW-Plugin

Description: Error invoking specified engine command

Resolution: Please look at exception for more details

BWENGINE-100088: Library alias undefined [%1]

Role: errorRole

Category: BW-Core

Description: Cannot resolve library alias

Resolution: Provide valid library path for this alias

BWENGINE-100089: Library not found for alias [%1], path [%2]

Role: errorRole

Category: BW-Core

Description: Can not find library for specifed alias

Resolution: Provide valid library path for this alias

BWENGINE-100090: Invalid library file type for alias [%1], path [%2]

Role: errorRole

Category: BW-Core

Description: Library for this alias has invalid file type

Resolution: Provide valid library path for this alias

BWENGINE-100091: Library error for alias [%1], path [%2]

Role: errorRole

Category: BW-Core

Description: Library error for this alias

Resolution: Please look at exception for more details

BWENGINE-100092: Can not checkpoint in middle of a critical section

Role: errorRole

Category: BW-Core

Description: A checkpoint may not occur within a critical section group

Resolution: Correct process design

BWENGINE-100093: Required Lock object not specified

Role: errorRole

Category: BW-Core

Description: A multi-group critical section requires a lock object

Resolution: Configure a lock object

BWENGINE-100094: Process id [%1] not found

Role: errorRole

Category: BW-Core

Description: No process found with matching process id

Resolution: Use existing process id

BWENGINE-100095: Fault to catch has not been specified

Role: errorRole

Category: BW-Core

Description: Specify fault or select all

Resolution:

BWENGINE-100096: Duplicate catch activities [%1] [%2]

Role: errorRole

Category: BW-Core

Description: More than one catch activity with the same configuration

Resolution: Reconfigure catch activities so that they don't conflict with each other

---

BWENGINE-100097: Can not create/access pager directory [%1]

Role: errorRole

Category: BW-Core

Description: Problem encountered creating or accessing the pager directory

Resolution: Check available file space and permissions

BWENGINE-100100: Transition condition XPath has an error

Role: errorRole

Category: BW-Core

Description:

Resolution: Please look at the transition for more details

BWENGINE-100101: Loop over expression error

Role: errorRole

Category: BW-Core

Description:

Resolution: Please look at the group for more details

BWENGINE-100102: Repeat condition expression error

Role: errorRole

Category: BW-Core

Description:

Resolution: Please look at the group for more details

BWENGINE-100103: Error condition expression error

Role: errorRole

Category: BW-Core

Description:

Resolution: Please look at the group for more details

BWENGINE-100104: Variable [%1] has not been initialized

Role: errorRole

Category: BW-Plugin

Description: Tried to use variable contents that has not been initialized

Resolution: Initialize variable before using contents

BWENGINE-100105: Join failure exception

Role: errorRole

Category: BW-Plugin

Description: Join condition false and join exception not suppressed

Resolution: May be desired result. If not, redesign process definition accordingly.

BWENGINE-100106: Join condition error

Role: errorRole

Category: BW-Plugin

Description: Join condition XPATH expression has an error

Resolution: Correct join condition

BWENGINE-200001: Partition [%1] not loaded

Role: warnRole

Category: BW-Core

Description: Partition listed to load has not been loaded

Resolution:

BWENGINE-200002: no path from start to this point

Role: warnRole

Category: BW-Core

Description: This point can not be reached

Resolution:

BWENGINE-200003: Mapping Warning

Role: warnRole

Category: BW-Core

Description: Potential problem find with mapping

Resolution: Please look at mapping for more details

BWENGINE-200004: Checkpoint not included with transaction

Role: warnRole

Category: BW-Core

Description: Checkpoint taken before commit. Restart could happen before or after commit.

Resolution: Reconfigure checkpoint database configuration

BWENGINE-200005: Join condition warning

Role: errorRole

Category: BW-Plugin

Description: Join condition XPATH expression has a warning

Resolution: Verify join condition

BWENGINE-300001: Process Engine %1

Role: infoRole

Category: BW-Core

Description: process engine versionn

Resolution:

BWENGINE-300002: Engine %1 started

Role: infoRole

Category: BW-Core

Description: engine started

Resolution:

BWENGINE-300003: Engine %1 started in backup mode

Role: infoRole

Category: BW-Core

Description: Indicates the named engine has been started FT backup mode

Resolution:

BWENGINE-300004: Engine %1 %2

Role: infoRole

Category: BW-Core

Description: Fault Tolerant actions

Resolution:

BWENGINE-300006: Engine %1 terminating

Role: infoRole

Category: BW-Core

Description: engine terminating

Resolution:

BWENGINE-300007: Process Started

Role: infoRole

Category: BW-Core

Description: A new process has been started

Resolution:

BWENGINE-300008: Process started tracking=%1

Role: infoRole

Category: BW-Core

Description: A new process has been started with associated tracking info

Resolution:

BWENGINE-300009: BW Plugins: %1

Role: infoRole

Category: BW-Core

Description: BW plugins.jar version

Resolution:

BWENGINE-300010: XML Support: %1

Role: infoRole

Category: BW-Core

Description: TIBCOXML version

Resolution:

BWENGINE-300011: Java version: %1 %2

Role: infoRole

Category: BW-Core

Description: Java VM name and version

Resolution:

BWENGINE-300012: OS version: %1 %2 %3

Role: infoRole

Category: BW-Core

Description: OS arch, name and version

Resolution:

BWENGINE-300013: Tibrv string encoding: %1

Role: infoRole

Category: BW-Core

Description: Tibrv string encoding

Resolution:

BWENGINE-300014: Starting delayed shutdown, max-delay=[%1], wait-for-checkpoints=[%2]

Role: infoRole

Category: BW-Core

Description: Processing delayed shutdown command

Resolution:

BWENGINE-300015: Statistics collection started, recording to [%1]

Role: infoRole

Category: BW-Core

Description: Starting activity statistics collection and recording to specified file

Resolution:

BWENGINE-300016: Statistics collection stopped

Role: infoRole

Category: BW-Core

Description: Stopping activity statistics collection and recording

Resolution:

BWENGINE-300017: Restarting [%1] for process [%2]

Role: infoRole

Category: BW-Core

Description: Restarting process instance from checkpoint

Resolution:

BWENGINE-300018: Found [%1] checkpoint(s) to be restarted

Role: infoRole

Category: BW-Core

Description: Shows number of checkpoints available to be restarted

Resolution:

BWENGINE-300019: Found [%1] checkpoint(s) auto restart NOT selected

Role: infoRole

Category: BW-Core

Description: Shows number of checkpoints available, but not to be auto restarted

Resolution:

BWENGINE-300020: Found [%1] recoverable checkpoint(s) preserved after process faulted

Role: infoRole

Category: BW-Core

Description: Shows number of checkpoints preserved after process terminated with a fault

Resolution:

BWENGINE-300021: Resource [%1] changed its state from [%2] to [%3].

Role: infoRole

Category: BW-Core

Description: Resource state change information

Resolution:

BW-EXT-LOG-100000: %1

Role: errorRole

Category: LOG4J

Description: Error message logged by third party application or java code using LOG4J api

Resolution: Refer to your third party application or java code

---

BW-EXT-LOG-100001: %1

Role: errorRole

Category: LOG4J

Description: Fatal error message logged by third party application or java code using LOG4J api

Resolution: Refer to your third party application or java code

---

BW-EXT-LOG-100002: Unable to write the message logged by third party application or java code to TIBCO BusinessWorks log file. %1

Role: errorRole

Category: LOG4J

Description: Error occurred while trying to forward the message logged by third party application or java code to TIBCO BusinessWorks log file

Resolution:

BW-EXT-LOG-200000: %1

Role: warnRole

Category: LOG4J

Description: Warning message logged by third party application or java code using LOG4J api

Resolution: Refer to your third party application or java code

---

BW-EXT-LOG-300000: %1

Role: infoRole

Category: LOG4J

Description: Info message logged by third party application or java code using LOG4J api

Resolution: Refer to your third party application or java code

---

BW-EXT-LOG-300001: %1

Role: infoRole

Category: LOG4J

Description: Message logged by third party application or java code using LOG4J api

Resolution: Refer to your third party application or java code

---

BW-EXT-LOG-300002: %1

Role: debugRole

Category: LOG4J

Description: Debug message logged by third party application or java code using LOG4J api

Resolution: Refer to your third party application or java code

---

Chapter 2 Common Errors

Some error codes are common across activities within different palettes. This chapter describes these errors.

Topics

- Common Error Codes, page 38

Common Error Codes

BW-COMMON-100001: Configuration error in field [%1]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value

Resolution: Please update the cofiguration data

BW-COMMON-100002: Configuration error in field [%1] expecting a valid [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the cofiguration data for the field with value of the indicated type

---

BW-COMMON-100003: Configuration error in field [%1] expecting a value between [%2] and [%3]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the cofiguration data

BW-COMMON-100004: Configuration error in field [%1] the value must be non empty

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the cofiguration data

BW-COMMON-100005: Configuration error in field [%1] the value must be a valid [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the cofiguration data

BW-COMMON-100006: Configuration error in field [%1] the value must be a valid URI

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid URI

Resolution: Please specify a valid URI

BW-COMMON-100007: Configuration error in field [%1] the value must be a valid URL

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid URL

Resolution: Please specify a valid URL

BW-COMMON-100008: Configuration error in field [%1] the value must be a valid hostname

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid hostname

Resolution: Please specify a valid hostname

BW-COMMON-100009: Configuration error in field [%1] the value must be a valid port number

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid port number

Resolution: Please specify a valid port number

BW-COMMON-100010: Configuration error in field [%1] the value must be a valid number

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid number

Resolution: Please specify a valid number

BW-COMMON-100011: Configuration error in field [%1] the value must be a valid timeout value

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid timeout value

Resolution: Please specify a valid number between 1 and 32000

BW-COMMON-100012: Configuration error in field [%1] the value must be a valid NCName

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid NCName type from XML specification

Resolution: Please specify a valid NCName

BW-COMMON-100013: Configuration error in field [%1] the value must be a valid XPath expression

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid XPath expression

Resolution: Please specify a valid XPath

BW-COMMON-100014: Configuration error in field [%1] the value must be a valid java classname

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid Class name

Resolution: Please specify a valid Java Class name

BW-COMMON-100015: Configuration error in field [%1] the value must be a valid file name

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid file name

Resolution: Please specify a valid file name

BW-COMMON-100016: Configuration error in field [%1] the value must be a valid directory name

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid directory name

Resolution: Please specify a valid directory name

BW-COMMON-100017: Configuration error in field [%1] the value must be a valid event source name

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid event source name

Resolution: Please specify a valid event source name

BW-COMMON-100018: Configuration error in field [%1] the value must be a valid event source name of type [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid event source name of the specified kind

Resolution: Please specify a valid event source name of the specified kind

---

BW-COMMON-100019: Configuration error in field [%1] the value must be a valid floating point number

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid floating point number

Resolution: Please specify a valid floating point number

BW-COMMON-100020: Configuration error in field [%1] the value must be a valid double number

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid double

Resolution: Please specify a valid double

BW-COMMON-100021: Configuration error in field [%1] the value must be a valid encoding

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid encoding

Resolution: Please specify a valid encoding

BW-COMMON-100022: Configuration error in field [%1] the specified encoding [%2] not supported

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid encoding

Resolution: Please specify a valid encoding

BW-COMMON-100023: Configuration error in field [%1] the value must be a valid namespace URI

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid namespace URI

Resolution: Please specify a valid namespace URI

BW-COMMON-100024: Configuration error in field [%1] the value must be a valid schema element

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid schema element

Resolution: Please specify a valid schema element

BW-COMMON-100025: Configuration error in field [%1] the value must be a valid schema type

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid schema type

Resolution: Please specify a valid schema type

BW-COMMON-100026: Configuration error in field [%1] the value must be a valid HTTP connection resource

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid HTTP connection

Resolution: Please specify a valid HTTP Connection resource

BW-COMMON-100027: Configuration error in field [%1] the value must be a valid TIBRV connection resource

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid TIBRV connection

Resolution: Please specify a valid TIBRV Connection resource

BW-COMMON-100028: Configuration error in field [%1] the value must be a valid JDBC connection resource

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid JDBC connection

Resolution: Please specify a valid JDBC Connection resource

BW-COMMON-100029: Configuration error in field [%1] the value must be a valid JMS connection resource

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid JMS connection

Resolution: Please specify a valid JMS Connection resource

BW-COMMON-100030: Configuration error in field [%1] the value must be a valid IC Server connection

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid IC Server connection

Resolution: Please specify a valid IC Server Connection resource

---

BW-COMMON-100031: Configuration error in field [%1] the value must be a valid WSDL message QName

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid WSDL message QName

Resolution: Please specify a valid WSDL message QName

BW-COMMON-100032: Configuration error in field [%1] the value must be a valid WSDL portType QName

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid WSDL portType QName

Resolution: Please specify a valid WSDL portType QName

BW-COMMON-100033: Configuration error in field [%1] the value must be a valid WSDL Service QName

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid WSDL Service QName

Resolution: Please specify a valid WSDL Service QName

BW-COMMON-100034: Configuration error in field [%1] the value must be a valid WSDL Port Name in service [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid WSDL Port Name

Resolution: Please specify a valid WSDL Port Name

BW-COMMON-100035: Configuration error in field [%1] the value must be a valid WSDL Operation Name in portType [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid WSDL Operation Name

Resolution: Please specify a valid WSDL Operation Name

BW-COMMON-100036: Configuration error in field [%1] the value must be a valid proxy resource

Role: errorRole

Category: BW_Plugins

Description: Please make sure that the specified field is a valid HTTP Proxy Name

Resolution: Please specify a valid HTTP Proxy Resource Name

BW-COMMON-100037: The server certificate [%1] not found

Role: errorRole

Category: BW_Plugins

Description: The certificate path is invalid

Resolution: Please specify the valid certificate file

BW-COMMON-100038: An exception is received [%1]

Role: errorRole

Category: BW_Plugins

Description: Unexpected error

Resolution: Please contact TIBCO support

BW-COMMON-100039: Error initializing TIBCrypt [%1]

Role: errorRole

Category: BW_Plugins

Description: Unexpected error

Resolution: Please contact TIBCO support

BW-COMMON-100040: The client key [%1] not found

Role: errorRole

Category: BW_Plugins

Description: The key file path may be invalid

Resolution: Please specify the valid key file

BW-COMMON-100041: Server certificate is invalid

Role: errorRole

Category: BW_Plugins

Description: The specified certificate is invalid

Resolution: Please specify the valid certificate

BW-COMMON-100042: Configuration error in field [%1] the specified transport is not supported

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid transport type

Resolution: Please contact TIBCO support to get a list of transport protocols supported for this activity

---

BW-COMMON-100043: Configuration error. [%1]

Role: errorRole

Category: BW_Plugins

Description: Activity is not configured correctly

Resolution: Please check that the activity is configured correctly

---

BW-COMMON-100044: Inline schema error. [%1]

Role: errorRole

Category: BW_Plugins

Description: There was an error resolving an inline schema, or there was an error with a reference from the inline to another schema resource.

Resolution: Please check the inline schema definition for errors. The error may not be in the inline schema itself, but in a schema resource that is used by the inline schema.

BW-COMMON-100045: Configuration error in field [%1] the value must be a valid WSDL Operation Name in port [%2] in service [%3]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid WSDL Operation Name

Resolution: Please specify a valid WSDL Operation Name

BW-COMMON-100046: Configuration error in field [%1] the value must be a positive integer number

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid positive integer number

Resolution: Please specify a valid positive integer number

BW-COMMON-100047: Configuration error: The metadate schema defined for the activity [%1] cannot be locked

Role: errorRole

Category: BW-Plugin

Description: The metadate schema defined for an activity cannot be locked

Resolution: Please look at exception for more details

BW-COMMON-100300: The partner [%1] doesn't implement the specified operation [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the interface implemented by the partner does define the specified operation

Resolution: Please specify a valid operation name

BW-COMMON-100301: Partner is not specified

Role: errorRole

Category: BW-Plugin

Description: Please specify a partner

Resolution: Check the configuration and make sure that a partner is specified

---

BW-COMMON-100302: Operation is not specified

Role: errorRole

Category: BW-Plugin

Description: Please specify an operation

Resolution: Check the configuration and make sure that an operation is specified

---

BW-COMMON-100303: Service is not specified

Role: errorRole

Category: BW-Plugin

Description: Please specify a service

Resolution: Check the configuration and make sure that a service is specified

---

BW-COMMON-100304: Port is not specified

Role: errorRole

Category: BW-Plugin

Description: Please specify a port

Resolution: Check the configuration and make sure that a port is specified

---

BW-COMMON-100305: The service name [%1] is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid service name

Resolution: Check the configuration and make sure that the service has a valid name

---

BW-COMMON-100306: The port name [%1] is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid port name

Resolution: Check the configuration and make sure that the port has a valid name

---

BW-COMMON-100307: The operation name [%1] is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid operation name

Resolution: Check the configuration and make sure that the operation has a valid name

---

BW-COMMON-100308: The binding type [%1] is not supported

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid binding

Resolution: Check the configuration and make sure that the binding is valid

---

BW-COMMON-100309: The namespace of the service is not specified

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid namespace

Resolution: Check the configuration and make sure that the namespace of the service is specified

---

BW-COMMON-100310: The namespace of the service [%1] is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid namespace

Resolution: Check the configuration and make sure that the namespace of the service is valid

---

BW-COMMON-100311: The namespace of the port [%1] is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid namespace

Resolution: Check the configuration and make sure that the namespace of the port is valid

---

BW-COMMON-100312: The port [%1] doesn't have a binding or the binding associated with it is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid binding

Resolution: Check the WSDL file and make sure that the port has a valid binding

---

BW-COMMON-100313: The port [%1] doesn't have a PortType or the PortType associated with it is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid PortType

Resolution: Check the WSDL file and make sure that the port has a valid PortType

---

BW-COMMON-100314: The NOTIFICATION MEP is not supported

Role: errorRole

Category: BW-Plugin

Description: Please specify either a REQUEST-RESPONSE or a ONE-WAY operation

Resolution: Check the style of the operation and make sure it is either REQUEST-RESPONSE or ONE_WAY

BW-COMMON-100315: The SOLICIT-RESPONSE MEP is not supported

Role: errorRole

Category: BW-Plugin

Description: Please specify either a REQUEST-RESPONSE or a ONE-WAY operation

Resolution: Check the style of the operation and make sure it is either REQUEST-RESPONSE or ONE_WAY

BW-COMMON-100316: The Partner [%1] is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid partner name

Resolution: Check the configuration and make sure that a valid partner name is specified

---

BW-COMMON-100317: Either the Partner [%1] or the Operation [%2] is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid partner name and a valid operation name

Resolution: Check the configuration and make sure that both a valid partner and a valid operation are specified

---

BW-COMMON-100318: The Event Source is not specified

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid event source name

Resolution: Check the configuration and make sure that a valid event source name is specified

---

BW-COMMON-100319: The Event Source [%1] is not valid

Role: errorRole

Category: BW-Plugin

Description: Please specify a valid event source name

Resolution: Check the configuration and make sure that a valid event source name is specified

---

BW-COMMON-100320: A Reply activity cannot be used to reply to the selected Event Source. The operation implemented is a ONE-WAY operation

Role: errorRole

Category: BW-Plugin

Description: A Reply activity can be used only when the operation implemented by the selected Event Source has a REQUEST-RESPONSE message exchange pattern

Resolution: Please remove the Reply activity or associate it with a different Event Source

---

BW-COMMON-100501: Unexpected value [%1] in the field [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value

Resolution: Please update the cofiguration data

BW-COMMON-100502: Input data error in field [%1] expecting a valid [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the input data

BW-COMMON-100503: Input data error in field [%1] expecting a value between [%2] and [%3]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the cofiguration data

BW-COMMON-100504: Input data error in field [%1] because [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value

Resolution: Please update the cofiguration data

BW-COMMON-100505: Input data error. [%1]

Role: errorRole

Category: BW-Plugin

Description: Activity received incorrect value for the field(s) in the input tab.

Resolution: Reconfigure the TIBCO BusinessWorks process that contains this activity to provide the correct value for the input field(s).

BW-COMMON-100601: Output data error in field [%1]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value

Resolution: Please update the cofiguration data

BW-COMMON-100602: Output data error in field [%1] expecting a valid [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the output data

BW-COMMON-100603: Output data error in field [%1] expecting a value between [%2] and [%3]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the cofiguration data

BW-COMMON-100604: Output data error in field [%1] because [%2]

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value

Resolution: Please update the cofiguration data

BW-COMMON-100605: Output data error in field [%1] value cannot be null

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the output data

BW-COMMON-100606: Output data error in field [%1] value is not serializable

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field has a valid value as indicated

Resolution: Please update the output data

BW-COMMON-101001: Error while serializing [%1] message [%2]

Role: errorRole

Category: BW_Plugin

Description: Error while serializing the message

Resolution: Please Contact TIBCO Support

BW-COMMON-101002: Error while deserializing [%1] message [%2]

Role: errorRole

Category: BW_Plugin

Description: Error while deserializing the message

Resolution: Please Contact TIBCO Support

BW-COMMON-101003: [%1] operation timed out

Role: errorRole

Category: BW_Plugin

Description: Timeout error while waiting for reply

Resolution: Please check the remote server or increse the timeout value

---

BW-COMMON-101004: Internal error occurred. [%1]

Role: errorRole

Category: BW-Plugin

Description: Internal error has occured in the activity.

Resolution: Please contact TIBCO support

BW-COMMON-101005: Internal error occurred. Class=[%1], Method=[%2], Cause=[%3]

Role: errorRole

Category: BW-Plugin

Description: Internal error has occured in the activity.

Resolution: Please contact TIBCO support

BW-COMMON-101006: Unable to get value for the global variable [%1]

Role: errorRole

Category: BW_Plugin

Description: Unable to get value for the specified global variable

Resolution: Make sure that the specified global variable is defined.

BW-COMMON-101007: Unable to get value for the global variable [%1] because [%2]

Role: errorRole

Category: BW_Plugin

Description: Unable to get value for the specified global variable

Resolution: Make sure that the specified global variable is defined.

BW-COMMON-101008: The global variable [%1] is not defined

Role: errorRole

Category: BW_Plugin

Description: Unable to get value for the specified global variable

Resolution: Make sure that the specified global variable is defined.

BW-MIME-100000: Configuration error in field [%1] the value if present, must be a valid directory name; the directory needs to have read/write permission

Role: errorRole

Category: BW-Plugin

Description: Please make sure that the specified field is a valid directory name (the field can be empty) with the necessary read/write permission

Resolution: Please specify a valid directory name (the field can be empty) with the necessary read/write permission

---

Chapter 3 XPath

This chapter describes error codes that are returned due to errors in XPath expressions.

Topics

- XPath Error Codes, page 62

XPath Error Codes

XPATH-100001: Null Content

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100002: Expected non-repeating, got repeating

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100003: Expected more than 1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100004: Exceeds maximum occurrence

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100005: Unexpected %1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100006: No functions in namespace:%1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100010: Cannot resolve prefix:%1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100011: Cannot resolve function without prefix.

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100012: No such function.

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100013: Expected 1 argument

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100014: Expected %1 arguments

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100015: Expected at least 1 argument

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100016: Expected at least %1 arguments

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100017: Expected %1 or %2 arguments

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100020: Expected a node-set

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100021: No matching %1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100022: Variable not defined

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100030: Interpreted as a double, rounded to: %1. Use a string constant for arbitrary precision.

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100031: Unterminated escape character. Use & for ampersand.

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100032: XPath indexes are 1 based.

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100100: Variable '%1' already defined in this template

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100101: Illegal variable name

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100110: The substituted type '%1' is not a sub-type of the element's type

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100111: Cannot load the schema for the type substitution

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100112: No such type in schema for the type substitution

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100113: Element is abstract and cannot appear in a valid document

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100114: Type is abstract and cannot appear in a valid document

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100115: This element is not allowed to be nil

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100116: Cannot load the schema for the element

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100117: Unexpected output, no such element in the schema

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100118: Unexpected output, no such element in the current context

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100119: Multiple schemas with namespace '%1' found, and no import to disambiguate

between them.

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100120: No formula expected on structure

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100130: Group-by required for for-each-group

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100131: Group-by must be the first child of for-each-group

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100132: Only 1 Group-by allowed for a for-each-group

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100140: Unexpected output, '%1'

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100141: Unexpected output, '%1'; exceeds maximum occurrence

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100142: Unexpected text output

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100143: Unexpected output, '%1'; got namepsace '%2', expected namespace '%3'

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100150: Value required for '%1'

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100151: Element '%1' required

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100152: Not all required components of '%1' are complete

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100153: The output generated inside '%1' is incomplete

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100154: The output generated inside '%1' is not valid

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100155: Missing preceding output terms

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100190: Components inside of '%1' contain errors

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100200: Change namespace to %1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100202: Rename to %1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100203: Move to: %1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100204: Move to before: %1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100210: Copy-of incompatible; names match, but content differs

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100300: Formula has errors

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100301: Marker must be filled in

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100400: A 'when' statement cannot appear after an 'otherwise'

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100401: Only 1 'otherwise' statement is allowed in a 'choose'

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100402: Only 'when' and 'otherwise' can appear under 'choose'

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100410: All 'sort' statements must appear before anything else

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100420: Can generate more than the expected output of '%1'

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100421: The 'sort' statement must appear directly inside a 'for-each' or 'apply-templates' statement

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100500: Expected %1

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100501: Unexpected

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100502: Unexpected end of xpath

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100503: a variable name

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-100600: Coercion error: '%1' (check coercion list)

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-200001: Possibly invalid conversion from %1 to %2

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200002: Always true

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200003: Converting a constant string to a boolean, always true

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200004: Will be converted as if by boolean(), recommend comparing to string

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200005: Will be converted as if by boolean(), recommend converting to a number

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200006: Always false

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200010: position() is relative to inside the filter; equivalent to 'true()' in this usage.

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200100: Statement contains no children; has no effect

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200101: Output is required, so the surrounding 'if' is not required

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200102: Input is not optional, so the surrounding 'if' is not required

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200103: Input is not a node set, so the surrounding 'if' is not recommended

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200110: Simplify to an xsi:nil attribute constant

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200120: The input and this element are both nillable, set to copy-nil

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200121: This element is not nillable

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200122: This input element is not nillable

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200200: The referenced schema component has an error: %1

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-200300: The term %1 is required but not generated in all cases of the choose

Role: warningRole

Category: BW-Core

Description:

Resolution:

XPATH-300001: Converted by %1

Role: infoRole

Category: BW-Core

Description:

Resolution:

XPATH-300100: Optimize by computing '%1' out of the predicate

Role: infoRole

Category: BW-Core

Description:

Resolution:

XPATH-301000: For element '%1', source schema has namespace '%2', the target has namespace '%3'

Role: infoRole

Category: BW-Core

Description:

Resolution:

XPATH-301001: Source schema has name '%1', target has name '%2'

Role: infoRole

Category: BW-Core

Description:

Resolution:

XPATH-301002: Source schema has '%1', target has '%2'

Role: infoRole

Category: BW-Core

Description:

Resolution:

XPATH-400001: The statement 'stylesheet' cannot appear here

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-400101: Expected output '%1' before this

Role: errorRole

Category: BW-Core

Description:

Resolution:

XPATH-400102: Expected output '%1' at end of this

Role: errorRole

Category: BW-Core

Description:

Resolution:

Chapter 4 ActiveEnterprise Adapter Palette

This chapter describes error codes that can be returned by activities in the ActiveEnterprise Adapter palette.

Topics

- ActiveEnterprise Adapter Error Codes, page 84

ActiveEnterprise Adapter Error Codes

BW-AE-100000: Cannot create Transport

Role: errorRole

Category: BW_Plugin

Description: Cannot create Transport

Resolution: Please Contact TIBCO Support

BW-AE-100001: Error in sending message

Role: errorRole

Category: BW_Plugin

Description: Error in sending message

Resolution: Please Contact TIBCO Support

BW-AE-100002: Error serializing the message

Role: errorRole

Category: BW_Plugin

Description: Error serializing the message

Resolution: Please Contact TIBCO Support

BW-AE-100003: Error in sending request

Role: errorRole

Category: BW_Plugin

Description: Error in sending request

Resolution: Please Contact TIBCO Support

BW-AE-100004: Error in processing event: %1

Role: errorRole

Category: BW_Plugin

Description: Error in processing event

Resolution: Please Contact TIBCO Support

BW-AE-100005: Cannot create TibrvQueue: %1

Role: errorRole

Category: BW_Plugin

Description: Cannot create TibrvQueue

Resolution: Please Contact TIBCO Support

BW-AE-100006: Cannot create rvEventContext: %1

Role: errorRole

Category: BW_Plugin

Description: Cannot create rvEventContext

Resolution: Please Contact TIBCO Support

BW-AE-100007: Cannot create reply listener for subject: %1

Role: errorRole

Category: BW_Plugin

Description: Cannot create reply listener, for subject: %1

Resolution: Please Contact TIBCO Support

BW-AE-100008: Cannot activate TIBRV listener for subject: %1

Role: errorRole

Category: BW_Plugin

Description: Cannot activate TIBRV listener for subject: %1

Resolution: Please Contact TIBCO Support

BW-AE-100009: Error in sending reply

Role: errorRole

Category: BW_Plugin

Description: Error in sending reply

Resolution: Please Contact TIBCO Support

BW-AE-100010: Error in confirming the message

Role: errorRole

Category: BW_Plugin

Description: Error in sending reply

Resolution: Please Contact TIBCO Support

BW-AE-100011: RPC Server returned error message.

Role: errorRole

Category: BW_Plugin

Description: RPC Server returned error message.

Resolution: Please check the RPC exception data for more information

---

BW-AE-100012: Error while serializing the message.

Role: errorRole

Category: BW_Plugin

Description: Error while serializing the message

Resolution: Please Contact TIBCO Support

BW-AE-100013: Error while deserializing the message.

Role: errorRole

Category: BW_Plugin

Description: Error while deserializing the message

Resolution: Please Contact TIBCO Support

BW-AE-100014: Timeout waiting for reply.

Role: errorRole

Category: BW_Plugin

Description: Timeout waiting for reply

Resolution: Please Contact TIBCO Support

BW-AE-100015: Subject used in the Transport of the Activity is different from the Adapter Service.

Role: errorRole

Category: BW_Plugin

Description: Subject used in the Transport of the Activity is different from the Adapter Service

Resolution: Please Contact TIBCO Support

BW-AE-100016: RV Service used in the Transport of the Activity is different from the Adapter Service.

Role: errorRole

Category: BW_Plugin

Description: RV Service used in the Transport of the Activity is different from the Adapter Service

Resolution: Please Contact TIBCO Support

BW-AE-100017: RV Network used in the Transport of the Activity is different from the Adapter Service.

Role: errorRole

Category: BW_Plugin

Description: RV Network used in the Transport of the Activity is different from the Adapter Service

Resolution: Please Contact TIBCO Support

BW-AE-100018: RV Daemon used in the Transport of the Activity is different from the Adapter Service.

Role: errorRole

Category: BW_Plugin

Description: RV Daemon used in the Transport of the Activity is different from the Adapter Service

Resolution: Please Contact TIBCO Support

BW-AE-100019: JMS Topic used in the Transport of the Activity is different from the Adapter Service.

Role: errorRole

Category: BW_Plugin

Description: JMS Topic used in the Transport of the Activity is different from the Adapter Service

Resolution: Please Contact TIBCO Support

BW-AE-100020: JMS Queue used in the Transport of the Activity is different from the Adapter Service.

Role: errorRole

Category: BW_Plugin

Description: JMS Queue used in the Transport of the Activity is different from the Adapter Service

Resolution: Please Contact TIBCO Support

BW-AE-100021: The Adapter Service being connected to may use a SSL option different from the BW Activity.

Role: errorRole

Category: BW_Plugin

Description: The Adapter Service being connected to may use a SSL option different from the BW Activity.

Resolution: Please Contact TIBCO Support

BW-AE-100022: The Adapter Service being connected to may use a different JMS URL from the BW Activity.

Role: errorRole

Category: BW_Plugin

Description: The Adapter Service being connected to may use a different JMS URL from the BW Activity.

Resolution: Please Contact TIBCO Support

BW-AE-100023: RV Subject is a required field.

Role: errorRole

Category: BW_Plugin

Description: RV Subject is a required field.

Resolution: Please Contact TIBCO Support

BW-AE-100024: JMS Topic is a required field.

Role: errorRole

Category: BW_Plugin

Description: JMS Topic is a required field.

Resolution: Please Contact TIBCO Support

BW-AE-100025: JMS Queue is a required field.

Role: errorRole

Category: BW_Plugin

Description: JMS Queue is a required field.

Resolution: Please Contact TIBCO Support

BW-AE-100026: JMS Url is a required field.

Role: errorRole

Category: BW_Plugin

Description: JMS Url is a required field.

Resolution: Please Contact TIBCO Support

BW-AE-100027: AE metadata loading error: class %1 not found.

Role: errorRole

Category: BW_Plugin

Description: AE metadata loading error: class %1 not found.

Resolution: Please Contact TIBCO Support

BW-AE-100028: Failed to load request metadata for operation %1 in class %2.

Role: errorRole

Category: BW_Plugin

Description: Failed to load request metadata for operation %1 in class %2.

Resolution: Please Contact TIBCO Support

BW-AE-100029: Can't load the ProcessStarter %1.

Role: errorRole

Category: BW_Plugin

Description: Can't load the ProcessStarter %1.

Resolution: Please Contact TIBCO Support

BW-AE-100030: AE plugin configuration error: %1

Role: errorRole

Category: BW-Plugin

Description: AE plugin configuration error. Details provided

Resolution: Please Contact TIBCO Support

Chapter 5 File Palette

This chapter describes error codes that can be returned by activities in the File palette.

Topics

- File Error Codes, page 94

File Error Codes

BW-FILE-100000: File name [%1] is not valid

Role: errorRole

Category: BW_Plugin

Description: The file name is not valid

Resolution: Correct the filename or the mapping used to create the file name

---

BW-FILE-100001: File [%1] was not found

Role: errorRole

Category: BW_Plugin

Description: The file was not found

Resolution: Correct the filename or the mapping used to create the file name

---

BW-FILE-100002: File [%1] already exists

Role: errorRole

Category: BW_Plugin

Description: The file already exists

Resolution: Correct the filename or the mapping used to create the file name

---

BW-FILE-100003: An IO exception occurred while trying to write to the file [%1]

Role: errorRole

Category: BW_Plugin

Description: An IO exception occurred while trying to write to the file

Resolution: System error

BW-FILE-100004: File [%1] cannot be created

Role: errorRole

Category: BW_Plugin

Description: File cannot be created

Resolution: System error

BW-FILE-100005: Cannot read the binary content for the file [%1]

Role: errorRole

Category: BW_Plugin

Description: Unable to get the file content in binary form

Resolution: System error

BW-FILE-100006: Cannot read the string content for the file [%1]

Role: errorRole

Category: BW_Plugin

Description: Unable to get the file content in string form

Resolution: System error

BW-FILE-100007: The encoding [%1] is not valid

Role: errorRole

Category: BW_Plugin

Description: The encoding is not valid

Resolution: Check the encoding to make sure it is supported

BW-FILE-100008: The content provided is not base 64 binary

Role: errorRole

Category: BW_Plugin

Description: The file was not found

Resolution: Check the input data

BW-FILE-100009: Cannot rename the file [%1] to [%2]

Role: errorRole

Category: BW_Plugin

Description: Cannot rename the file

Resolution: System error

BW-FILE-100010: Cannot rename the file [%1] to [%2]. The destination file exists and its type is different then the type of the source file

Role: errorRole

Category: BW_Plugin

Description: Cannot rename the file]. The destination file exists and its type is different then the type of the source file

Resolution: Check input data

BW-FILE-100011: This activity cannot be used to move a directory

Role: errorRole

Category: BW_Plugin

Description: This activity cannot be used to move a directory

Resolution: See the documentation of the File Rename Activity

---

BW-FILE-100012: Cannot remove the file [%1]

Role: errorRole

Category: BW_Plugin

Description: Cannot remove the file

Resolution: System error

BW-FILE-100013: An IO exception occurred while trying to create the file [%1]

Role: errorRole

Category: BW_Plugin

Description: An IO exception occurred while trying to create the file

Resolution: System error

BW-FILE-100014: You cannot overwrite the following file [%1] to file [%2] if the overwrite flag is not selected.

Role: errorRole

Category: BW_Plugin

Description:

Resolution: May need to set Overwrite property on activity Configuration

---

BW-FILE-100015: You cannot copy a directory [%1] to an existing file [%2]

Role: errorRole

Category: BW_Plugin

Description: You cannot copy a directory to an existing file

Resolution: Change from file path

BW-FILE-100016: You cannot copy multiple files [%1] to an existing file [%2]

Role: errorRole

Category: BW_Plugin

Description: You cannot copy mutiple files to an existing file

Resolution: Change from file path

BW-FILE-100017: Cannot create missing path [%1]

Role: errorRole

Category: BW_Plugin

Description: Cannot create missing path

Resolution: May need to set Create Missing Dirs property on activity Configuration

---

BW-FILE-100018: Cannot copy file [%1] to file [%2]

Role: errorRole

Category: BW_Plugin

Description: Cannot copy file

Resolution: System Error

Chapter 6 FTP Palette

This chapter describes error codes that can be returned by activities in the FTP palette.

Topics

- FTP Error Codes, page 100

FTP Error Codes

BW-FTP-100000: FTP connection is required.

Role: errorRole

Category: BW_Plugin

Description: FTP connection is required.

Resolution: Please Contact TIBCO Support

BW-FTP-100001: Cannot perform FTP Operation: %1. Error Info: %2

Role: errorRole

Category: BW_Plugin

Description: Cannot perform FTP Operation: %1. Error Info: %2

Resolution: Please Contact TIBCO Support

BW-FTP-100002: Cannot establish FTP connection when performing FTP function: %1. Error Info: %2

Role: errorRole

Category: BW_Plugin

Description: Cannot establish FTP connection when performing FTP function: %1. Error Info: %2

Resolution: Please Contact TIBCO Support

BW-FTP-100003: File %1 already exists.

Role: errorRole

Category: BW_Plugin

Description: File %1 already exists.

Resolution: Please Contact TIBCO Support

BW-FTP-100004: Error in PUT or MPUT command. See Error Tab for details.

Role: errorRole

Category: BW_Plugin

Description: Error in PUT or MPUT command. See Error Tab for details.

Resolution: Please Contact TIBCO Support

BW-FTP-100005: Error in GET or MGET command. See Error Tab for details.

Role: errorRole

Category: BW_Plugin

Description: Error in GET or MGET command. See Error Tab for details.

Resolution: Please Contact TIBCO Support

BW-FTP-100006: FTP Connection Succeeded. Target System: %1.

Role: infoRole

Category: BW_Plugin

Description: FTP Connection Succeeded. Target System: %1.

Resolution: Please Contact TIBCO Support

BW-FTP-100007: Client is not initialized: %1.

Role: errorRole

Category: BW-Plugin

Description: Client is not initialized: %1.

Resolution: Please Contact TIBCO Support

BW-FTP-100008: Connection timeout.

Role: errorRole

Category: BW-Plugin

Description: Connection timeout.

Resolution: Please Contact TIBCO Support

BW-FTP-100009: Local file specified cannot be found.

Role: errorRole

Category: BW-Plugin

Description: Local file specified cannot be found.

Resolution: Please Contact TIBCO Support

BW-FTP-100010: Global variable %1 not defined.

Role: errorRole

Category: BW-Plugin

Description: Global variable %1 not defined.

Resolution: Please Contact TIBCO Support

BW-FTP-100011: Unexpected reply code. Returned Code: %1 Expected Code: %2.

Role: errorRole

Category: BW-Plugin

Description: Unexpected reply code. Returned Code: %1. Expected Code: %2.

Resolution: Please Contact TIBCO Support

BW-FTP-100012: Invalid user name or password

Role: errorRole

Category: BW-Plugin

Description: Invalid user name or password

Resolution: Please Contact TIBCO Support

BW-FTP-100013: Error in executing remote command: %1

Role: errorRole

Category: BW-Plugin

Description: Error in executing remote command: %1

Resolution: Please Contact TIBCO Support

BW-FTP-100014: Connection reference is missing.

Role: errorRole

Category: BW-Plugin

Description: Connection reference is missing.

Resolution: Please Contact TIBCO Support

BW-FTP-100015: Cannot access firewall.

Role: errorRole

Category: BW-Plugin

Description: Cannot access firewall.

Resolution: Please Contact TIBCO Support

BW-FTP-100016: Field %1 is required.

Role: errorRole

Category: BW-Plugin

Description: Field %1 is required.

Resolution: Please Contact TIBCO Support

BW-FTP-100017: FTP Connection Test Failed. Validate Host Name: %1.

Role: errorRole

Category: BW-Plugin

Description: FTP Connection Test Failed. Validate Host Name: %1.

Resolution: Please Contact TIBCO Support

BW-FTP-100018: FTP Connection Test Failed. Error: %1.

Role: errorRole

Category: BW-Plugin

Description: FTP Connection Test Failed. Error: %1.

Resolution: Please Contact TIBCO Support

BW-FTP-100019: File %1 does not exist.

Role: errorRole

Category: BW-Plugin

Description: File %1 does not exist.

Resolution: Please Contact TIBCO Support

BW-FTP-100020: Trusted Certificate location not specified in SSL Configuration

Role: errorRole

Category: BW-Plugin

Description: Trusted Certificate location not specified in SSL Configuration

Resolution: Please Contact TIBCO Support

BW-FTP-100021: Error compiling trusted certificate. Reason : %1

Role: errorRole

Category: BW-Plugin

Description: Error compiling trusted certificate. Reason : %1

Resolution: Please Contact TIBCO Support

BW-FTP-100022: Error compiling client identity. Reason : %1

Role: errorRole

Category: BW-Plugin

Description: Error compiling client identity. Reason : %1

Resolution: Please Contact TIBCO Support

BW-FTP-100023: Error creating SSL client. Reason : %1

Role: errorRole

Category: BW-Plugin

Description: Error creating SSL client. Reason : %1

Resolution: Please Contact TIBCO Support

BW-FTP-100024: Error creating secure socket. Reason : %1

Role: errorRole

Category: BW-Plugin

Description: Error creating secure socket. Reason : %1

Resolution: Please Contact TIBCO Support

BW-FTP-100025: Error establishing active data socket. Reason : %1

Role: errorRole

Category: BW-Plugin

Description: Error establishing active data socket. Reason : %1

Resolution: Please Contact TIBCO Support

BW-FTP-100026: Error changing remote working directory. Reason : input is null

Role: errorRole

Category: BW-Plugin

Description: Error changing remote working directory. Reason : input is null

Resolution: Please Contact TIBCO Support

BW-FTP-100027: Error doing mget. Reason: mget is not supported for FTP via Proxy

Role: errorRole

Category: BW-Plugin

Description: Error doing mget. Reason: mget is not supported for FTP via Proxy

Resolution: Please Contact TIBCO Support

Chapter 7 General Activities Palette

This chapter describes error codes that can be returned by activities in the General Activities palette.

Topics

- General Activities Error Codes, page 108

General Activities Error Codes

BW-GENERAL-100001: Notify Configuration not specified

Role: errorRole

Category: BW-Plugin

Description: Notify Configuration not specified

Resolution: Please specify shared configuration

BW-GENERAL-100002: Unable to construct notification data for wait/receive activity

Role: errorRole

Category: BW-Plugin

Description: Unexpected internal error occurs. Unable to construct notification data for wait/receive activity

Resolution: Please contact TIBCO support

BW-GENERAL-100003: Unable to lock schema for notify input

Role: errorRole

Category: BW-Plugin

Description: Unable to lock schema for otify input

Resolution: Please look at exception for more details

BW-GENERAL-100004: Internal schema error occurs

Role: errorRole

Category: BW-Plugin

Description: Internal schema error occurs

Resolution: Please look at exception for more details

BW-GENERAL-100005: Unable to resolve shared configuration reference for [%1]

Role: errorRole

Category: BW-Plugin

Description: Unable to resolve shared configuration reference for [%1]

Resolution: Please look at exception for more details

BW-GENERAL-202001: Cannot cancel wait on group [%1] key [%2]

Role: warnRole

Category: BW-Plugin

Description: Cannot cancel wait on group [%1] key [%2]

Resolution: Please look at exception for more details

BW-GENERAL-202002: Receive error notification in [%1]

Role: warnRole

Category: BW-Plugin

Description: Receive error notification in [%1]

Resolution: Please look at exception for more details

BW-GENERAL-202003: Error occurs after getting notification data in [%1]

Role: warnRole

Category: BW-Plugin

Description: Error occurs after getting notification data in [%1]

Resolution: Please look at exception for more details

BW-GENERAL-202004: Wait for notification failed for [%1], set inactive

Role: warnRole

Category: BW-Plugin

Description: Wait for notification failed for [%1], set inactive

Resolution: Please look at exception for more details

BW-GENERAL-202005: Wait thread internal error for [%1], set inactive

Role: warnRole

Category: BW-Plugin

Description: Wait thread internal error for [%1], set inactive

Resolution: Please look at exception for more details

BW-JNDI-100001: Configuration Test Failed. %1

Role: errorRole

Category: BW_Plugin

Description: Unable to establish connection to the server.

Resolution: Please correct the error stated in the exception message and retry.

BW-JNDI-100002: Configuration Test Failed. Exception [%1] occurred.

Role: errorRole

Category: BW_Plugin

Description: Unable to establish connection to the server. Exception occurred

Resolution: Please correct the error stated in the exception message and retry.

BW-JNDI-100003: The JNDI Configuration reference [%1] not found

Role: errorRole

Category: BW_Plugin

Description: Unable to obtain the specified JNDI Configuration shared resource reference

Resolution: Please correct the error and retry.

BW-JNDI-100004: The JNDI Configuration reference [%1] not found in repository

Role: errorRole

Category: BW_Plugin

Description: The repository does not contain the specified JNDI Configuration shared resource reference

Resolution: Please correct the error and retry.

BW-JNDI-100005: The JNDI Configuration reference [%1] contains incorrect field values.

Role: errorRole

Category: BW_Plugin

Description: The JNDI Configuration shared resource referenced contains invalid field values.

Resolution: Please correct the error and retry.

BW-JNDI-100006: Exception occurred while trying to obtain the JNDI Configuration reference [%1]: %2

Role: errorRole

Category: BW_Plugin

Description: Unable to obtain the JNDI Configuration shared resource reference

Resolution: Please correct the error and retry.

BW-JTAUT-400000: %1

Role: debugRole

Category: BW_Plugin

Description: Debug Trace Message

Resolution: None

BW-CMD-100001: Error executing external command %1: %2.

Role: errorRole

Category: BW_Plugin

Description: Error executing external command %1: %2.

Resolution: Check command value in configuration and input.

BW-CMD-100002: Error accessing file or directory %1: %2. Check file or directory name and permissions.

Role: errorRole

Category: BW_Plugin

Description: Error accessing file or directory %1: %2. Check file or directory name and permissions.

Resolution: Ensure that output file has write permissions for user running engine and that sufficient disk space is available for writing output file. Ensure that working directory exists and is accessible for user running engine.

BW-CMD-100003: No command specified.

Role: errorRole

Category: BW_Plugin

Description: No command specified.

Resolution: Provide a command in configuration or input.

BW-TIMER-100000: Invalid start time [%1], correct format is [%2]

Role: errorRole

Category: BW_Plugin

Description: The format of the start time must conform to the standard format.

Resolution: Update the global variable to use the correct format.

Chapter 8 HTTP Palette

This chapter describes error codes that can be returned by activities in the HTTP palette.

Topics

- HTTP Error Codes, page 116

HTTP Error Codes

BW-HTTP-100000: The Http Server replied with a 4XX status code

Role: errorRole

Category: BW_Plugin

Description: The request contains bad syntax or cannot be fulfilled

Resolution: Correct the configuration (input data) of the Http Request activity

---

BW-HTTP-100001: The Http Server replied with a 5XX status code

Role: errorRole

Category: BW_Plugin

Description: The server failed to fulfill an apparently valid request

Resolution: See the documentation

BW-HTTP-100100: An exception was thrown while trying to initialize the Http client

Role: errorRole

Category: BW_Plugin

Description: An exception was thrown while trying to initialize the Http client

Resolution: System exception

BW-HTTP-100102: An exception occurred while trying to initialize the Http server

Role: errorRole

Category: BW_Plugin

Description: An exception occurred while trying to initialize the Http server

Resolution: System exception

BW-HTTP-100103: There are more than one Http event sources registered on [%1]

Role: errorRole

Category: BW_Plugin

Description: There are more than one Http event sources registered on a specific port

Resolution: Make sure there is no more than one Http event source (signal-in activity) that use a specific Http Connection Shared Resource.

BW-HTTP-100104: The trusted CA store was not specified

Role: errorRole

Category: BW_Plugin

Description: The trusted CA store was not specified

Resolution: Make sure the trusted CA store is specified

BW-HTTP-100105: An exception occurred while trying to build the input class.

Role: errorRole

Category: BW_Plugin

Description: A schema specific exception occurred while trying to build the input class.

Resolution: System error

BW-HTTP-100106: An exception occurred while trying to build the output class.

Role: errorRole

Category: BW_Plugin

Description: A schema specific exception occurred while trying to build the output class.

Resolution: System error

BW-HTTP-100107: A repository exception was thrown while trying to load the identity.

Role: errorRole

Category: BW_Plugin

Description: A repository exception was thrown while trying to load the identity.

Resolution: Make sure the file that contains the private key can be read.

BW-HTTP-100108: A security exception was thrown while trying to load the identity.

Role: errorRole

Category: BW_Plugin

Description: A security exception was thrown while trying to load the identity.

Resolution: Make sure the format of the file that contains the private key is supported.

BW-HTTP-100109: An IO exception whas thrown while trying to load the identity.

Role: errorRole

Category: BW_Plugin

Description: An IO exception whas thrown while trying to load the identity.

Resolution: Make sure the file that contains the private key exists and is readable.

BW-HTTP-100110: An IO exception whas thrown while trying to load the trusted CA store.

Role: errorRole

Category: BW_Plugin

Description: An IO exception whas thrown while trying to load the trusted CA store.

Resolution: Make sure the certificates that are stored in the trusted CA store are valid. See the documentation.

BW-HTTP-100111: A security exception whas thrown while trying to load the trusted CA store.

Role: errorRole

Category: BW_Plugin

Description: A security exception whas thrown while trying to load the trusted CA store.

Resolution: Make sure the certificates that are stored in the trusted CA store are valid. See the documentation.

BW-HTTP-100112: A CertificateException whas thrown while trying to load a particular certificate from the trusted CA store.

Role: errorRole

Category: BW_Plugin

Description: A CertificateException whas thrown while trying to load a particular certificate from the trusted CA store.

Resolution: Make sure the certificates that are stored in the trusted CA store are valid. See the documentation.

BW-HTTP-100113: The Identity [%1] is not valid.

Role: errorRole

Category: BW_Plugin

Description: The Identity [%1] is not valid.

Resolution: See the documentation

BW-HTTP-100114: The Identity is not specified

Role: errorRole

Category: BW_Plugin

Description: The Identity is not specified

Resolution: Make sure the Identity name is specified

BW-HTTP-100115: A security exception was thrown while trying to initialize the HTTPS server

Role: errorRole

Category: BW_Plugin

Description: A security exception was thrown while trying to initialize the HTTPS server

Resolution: System error

BW-HTTP-100116: A lifecycle exception was thrown while trying to initialize the Tomcat server

Role: errorRole

Category: BW_Plugin

Description: A lifecycle exception was thrown while trying to initialize the Tomcat server

Resolution: System error

BW-HTTP-100117: An IO exception was thrown while trying to create the web server file structure

Role: errorRole

Category: BW_Plugin

Description: An IO exception was thrown while trying to create the web server file structure

Resolution: System error

BW-HTTP-100118: An exception was thrown while trying to load the proxy's identity

Role: errorRole

Category: BW_Plugin

Description: An exception was thrown while trying to load the proxy's identity

Resolution: System error.

BW-HTTP-100119: An exception was thrown while trying to load the proxy

Role: errorRole

Category: BW_Plugin

Description: An exception was thrown while trying to load the proxy

Resolution: System error.

BW-HTTP-100120: An exception was thrown while trying to load the identity used for basic Http authentication

Role: errorRole

Category: BW_Plugin

Description: An exception was thrown while trying to load the identity used for basic Http authentication

Resolution: System error.

BW-HTTP-100121: An exception occurred while trying to initialize the Http server: %1

Role: errorRole

Category: BW_Plugin

Description: An exception occurred while trying to initialize the Http server

Resolution: System exception

BW-HTTP-100123: The Identity on the Proxy Connection is not valid

Role: errorRole

Category: BW_Plugin

Description: The Identity on the Proxy Connection is not valid. Please use a UsernamePassword Identity

Resolution: Correct the Identity

BW-HTTP-100124: The Identity for the basic authentication was not specified

Role: errorRole

Category: BW_Plugin

Description: The Identity for the basic authentication was not specified

Resolution: Make sure the Identity name is specified

BW-HTTP-100125: The Identity [%1] cannot be referenced in this context

Role: errorRole

Category: BW_Plugin

Description: The Identity [%1] cannot be referenced in this context

Resolution: See the documentation

BW-HTTP-100126: The Parameter Name [%1] is not valid

Role: errorRole

Category: BW_Plugin

Description: The Parameter Name [%1] is not valid

Resolution: Fix the name of the parameter

BW-HTTP-100127: The Parameter Name [%1] is already specified

Role: errorRole

Category: BW_Plugin

Description: The Parameter Name [%1] is already specified

Resolution: Remove one of the parameters

BW-HTTP-100128: The HTTP Connection Resource is not specified

Role: errorRole

Category: BW_Plugin

Description: The HTTP Connection Resource is not specified

Resolution: Specify an HTTP Connection Resource

BW-HTTP-100129

Role: errorRole

Category: BW_Plugin

Description: Identity for Kerberos authentication was not specified.

Resolution: Create the Identity resource with the username and password, and map it to the HTTP Send Request activity.

BW-HTTP-100130

Role: errorRole

Category: BW_Plugin

Description: An exception was thrown while trying to load the identity used for Kerberos HTTP authentication

Resolution: Resolve the identity resource mapping if the resource is mapped incorrectly.

BW-HTTP-100201: A POST Method cannot send parameters if the message body is specified

Role: errorRole

Category: BW_Plugin

Description: A POST Method cannot send parameters if the message body is specified

Resolution: Correct the input data.

BW-HTTP-100202: A GET Method doesn't have a message body

Role: errorRole

Category: BW_Plugin

Description: A GET Method doesn't have a message body

Resolution: Correct the input data. Make sure that the message body is not specified for a GET request

---

BW-HTTP-100203: Invalid endpoint URL. The host name is not specified

Role: errorRole

Category: BW_Plugin

Description: Invalid endpoint URL. The host name is not specified

Resolution: Correct either the configuration or the input data. Make sure that the host name is specified.

BW-HTTP-100204: Invalid endpoint URL

Role: errorRole

Category: BW_Plugin

Description: Invalid endpoint URL

Resolution: Correct either the configuration or the input data.

BW-HTTP-100205: Invalid input data. The encoding is not supported

Role: errorRole

Category: BW_Plugin

Description: Invalid input data. The encoding is not supported

Resolution: Correct the input data. Make sure the encoding is supported. See the documentation.

BW-HTTP-100206: The http method [%1] is not valid

Role: errorRole

Category: BW_Plugin

Description: The specified HTTP method is not valid

Resolution: Correct the input data. Make sure that the HTTP method is valid

---

BW-HTTP-100207: The status line [%1] is not valid

Role: errorRole

Category: BW_Plugin

Description: The status line is not valid. The right format is X Y Z, where X - the HTTP version, Y - the status code, Z - the reason phrase

Resolution: See the documentation

BW-HTTP-100208: An exception was thrown while trying to url-encode the data

Role: errorRole

Category: BW_Plugin

Description: An exception was thrown while trying to url-encode the data.

Resolution: See the documentation

BW-HTTP-100209: Attachment not supported for HTTP method %1. Only HTTP 'POST' can send attachments

Role: errorRole

Category: BW_Plugin

Description: Attachment not supported for HTTP method %1. Only HTTP 'POST' can send attachments

Resolution: See the documentation

BW-HTTP-100210: Error serializing attachment data, Cause: %1

Role: errorRole

Category: BW_Plugin

Description: Error serializing attachment data, Cause: %1

Resolution: See the documentation

BW-HTTP-100299: The input data is not valid

Role: errorRole

Category: BW_Plugin

Description: The input data is not valid

Resolution: See the documentation

BW-HTTP-100300: An IOException was thrown while trying to execute the Http method

Role: errorRole

Category: BW_Plugin

Description: An IOException was thrown while trying to execute the Http method

Resolution: System exception

BW-HTTP-100301: An exception was thrown while trying to execute the Http method. The Reason-code is [%1]

Role: errorRole

Category: BW_Plugin

Description: An exception was thrown while trying to execute the Http method.

Resolution: System exception

BW-HTTP-100302: An IOException was thrown while trying to read the response

Role: errorRole

Category: BW_Plugin

Description: An IOException was thrown while trying to read the response

Resolution: System exception

BW-HTTP-100303: An IOException was thrown while trying to send the response

Role: errorRole

Category: BW_Plugin

Description: An IOException was thrown while trying to send the response

Resolution: System exception

BW-HTTP-100304: An Exception was thrown while trying to send the response

Role: errorRole

Category: BW_Plugin

Description: An Exception was thrown while trying to send the response

Resolution: System exception

BW-HTTP-100305: An exception was thrown while trying to send the Http request

Role: errorRole

Category: BW_Plugin

Description: An exception was thrown while trying to send the Http request

Resolution: System exception

BW-HTTP-100400: The incoming Http message cannot be deserialized

Role: errorRole

Category: BW_Plugin

Description: The incoming Http message cannot be deserialized

Resolution: There is probabily an error on the Http client that invokes this service

---

BW-HTTP-100500: Using the following HTTP minProcessors/maxProcessors [host=%1 port=%2]: %3/%4

Role: infoRole

Category: BW_Plugin

Description: Using the following HTTP minProcessors/maxProcessors [host=%1 port=%2]: %3/%4

Resolution:

BW-HTTP-100600: For better MIME Multipart support, consider Upgrading Configuration

Role: warnRole

Category: BW_Plugin

Description: For better MIME Multipart support, consider Upgrading Configuration

Resolution:

BW-HTTP-100801:

Role: errorRole

Category: BW_Plugin

Description: Krb conf file is not specified

Resolution: Provide the correct file path.

BW-HTTP-100802:

Role: errorRole

Category: BW_Plugin

Description: Login conf file is not specified

Resolution: Provide the correct file path.

Chapter 9 Java Palette

This chapter describes error codes that can be returned by activities in the Java palette.

Topics

- Java Error Codes, page 132

Java Error Codes

BW-JAVA-100000: The activity was not compiled

Role: errorRole

Category: BW_Plugin

Description: The activity was not compiled

Resolution: Compile the activity in Designer.

BW-JAVA-100001: While executing [%1] encountered [%2] : [%3]

Role: errorRole

Category: BW_Plugin

Description: Exception encountered while invoking a method on the activity

Resolution: Inspect the Java source for this activity for a possible cause.

BW-JAVA-100002: The Java compiler is not in the classpath. Add tools.jar to the classpath.

Role: errorRole

Category: BW_Plugin

Description: The Java compiler is not in the classpath. Add tools.jar to the classpath.

Resolution: Add tools.jar to the classpath.

BW-JAVA-100003: The Java compile of [%1] failed with message: [%2]

Role: errorRole

Category: BW_Plugin

Description: The Java compiler encountered an error in the activity Java code.

Resolution: Examine the error and fix the issue in the Java code.

BW-JAVA-100004: The Java code is missing a required comment: [%1]

Role: errorRole

Category: BW_Plugin

Description: The activity uses embedded comments to auto generate code. One of them is missing.

Resolution: Update the code to remove any unbalanced comment delimiters and recompile.

BW-JAVA-100005: The [javaCode] property is missing from the .tra file

Role: errorRole

Category: BW_Plugin

Description: The activity could not determine a suitable temporary directory.

Resolution: add java.property.javaCode=[directory] in the designer.tra and bwengine.tra files.

BW-JAVA-100006: Cannot delete the [%1] Java source file.

Role: errorRole

Category: BW_Plugin

Description: Source files are written to the local file system for the compiler to access. The given file already exists and is write protected.

Resolution: Remove the Java source file from the local file system so that the activity may write a new copy.

BW-JAVA-100007: Cannot write the [%1] Java source file: [%2]

Role: errorRole

Category: BW_Plugin

Description: Source files are written to the local file system for the compiler to access. There was an error writing the given file to the file system.

Resolution: Examine the temporary directory for sufficient space to write files.

BW-JAVA-100011: Activity input schema creation error. Exception [%1] occurred while trying to create input schema. %2

Role: errorRole

Category: BW_Plugin

Description: The Java plugin activity is not able create schema for the activity's input tab. Exception occurred

Resolution: Please correct the error and retry.

BW-JAVA-100012: Activity output schema creation error. Exception [%1] occurred while trying to create output schema. %2

Role: errorRole

Category: BW_Plugin

Description: The Java plugin activity is not able create schema for the activity's output tab. Exception occurred

Resolution: Please correct the error and retry.

BW-JAVA-100013: Activity input data conversion error. Exception [%1] occurred while trying to render the activity input data. %2

Role: errorRole

Category: BW_Plugin

Description: This activity is not able to convert the input data.

Resolution: Please Contact TIBCO Support

BW-JAVA-100014: Activity output data conversion error. Exception [%1] occurred while trying to create the activity output data. %2

Role: errorRole

Category: BW_Plugin

Description: This activity is not able to create the output data.

Resolution: Please Contact TIBCO Support

BW-JAVA-000015: Activity initialization error: %1

Role: errorRole

Category: BW_Plugin

Description: Error occurred while initializing the activity.

Resolution: Please Contact TIBCO Support

BW-JAVA-100016: Unable to obtain information for the Java class [%1]. Exception [%2] occurred. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred while trying to obtain information for the declared Java class.

Resolution: Please correct the error stated in the exception message and retry.

BW-JAVA-100017: The Java class [%1] is not found in the classpath. ClassNotFoundException occurred. %2

Role: errorRole

Category: BW_Plugin

Description: ClassNotFoundException occurred while trying to access the specified Java class.

Resolution: Please verify that the specified class file is contained in the classpath.

BW-JAVA-100018: The Java class [%1] cannot be instantiated. Exception [%2] occurred. %3

Role: errorRole

Category: BW_Plugin

Description: Unable to create an instance of the specified Java class.

Resolution: Please correct the error stated in the exception message and retry.

BW-JAVA-100019: Input data error. The activity received an incorrect value for the method parameters. IllegalArgumentException occurred while trying to construct an instance of the Java class [%1]: %2

Role: errorRole

Category: BW_Plugin

Description: The activity received a incorrect value for the method parameter element that is in the activity input tab. IllegalArgumentException occurred while trying to construct the specified Java class.

Resolution: Verify that the correct values are provided for the method parameter elements that are in the activity input tab.

BW-JAVA-100020: Unable to construct an instance of the Java class [%1]. Exception [%2] occurred. %3

Role: errorRole

Category: BW_Plugin

Description: Unable to create an instance of the Java class. Exception occurred while trying to create an instance of the Java class.

Resolution: Please correct the error stated in the exception message and retry.

BW-JAVA-100021: The constructor for the Java class [%1] raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the Java class constructor.

Resolution: The exception was raised by the constructor of the declared Java class. Please refer to the Java class implementation for details.

BW-JAVA-100022: Configuration error. The Java class [%1] is an abstract class. It is not permitted to create an instance of an abstract Java class.

Role: errorRole

Category: BW_Plugin

Description: The selected class is an abstract Java class.

Resolution: Make sure that the selected class is not an abstract Java class

---

BW-JAVA-100023: Configuration error. The Java class [%1] is an interface. It is not permitted to create an instance of a Java interface.

Role: errorRole

Category: BW_Plugin

Description: The selected class is a Java interface.

Resolution: Make sure that the selected class is not a Java interface

---

BW-JAVA-100024: Configuration error. The Java class [%1] is not serializable. If the selected Java class is cached by the activity then the class must be a subtype of the interface 'java.io.Serializable'.

Role: errorRole

Category: BW_Plugin

Description: The declared Java class is not serializable. If the user has selected the option to cache the declared Java class then the class must be a subtype of the interface 'java.io.Serializable'.

Resolution: Make sure that the selected class is a subtype of the interface 'java.io.Serializable'

BW-JAVA-100025: Configuration error. The method [%1] returns a Java class [%2] that is not serializable. The Java class returned by the selected method must be a subtype of the interface 'java.io.Serializable'.

Role: errorRole

Category: BW_Plugin

Description: Invalid method return type. If the selected method must returns a Java class then the class must be a subtype of the interface 'java.io.Serializable'.

Resolution: Make sure that the selected method returns a serializable Java class

---

BW-JAVA-100026: Unable to obtain information for the method [%1] from the class [%2]. NoSuchMethodException occurred. %3

Role: errorRole

Category: BW_Plugin

Description: The method name is not contained in the declared Java class.

Resolution: It is possible that the declared Java class has been modified since the last configuration of this activity. Please reconfigure this activity or verify that the declared Java class has not changed since the last configuration.

BW-JAVA-100027: Unable to obtain information for the cleanup method [%1] from the class [%2]. NoSuchMethodException occurred. %3

Role: errorRole

Category: BW_Plugin

Description: The cleanup method name is not contained in the declared Java class.

Resolution: It is possible that declared Java class has been modified since the last configuration of this activity. Please reconfigure this activity or verify that the declared Java class has not changed since the last configuration.

BW-JAVA-100028: Unable to obtain information for method [%1] from the class [%2]. SecurityException occurred. %3

Role: errorRole

Category: BW_Plugin

Description: SecurityException occurred while trying to get method information from the declared Java class.

Resolution: Please correct the error and retry.

BW-JAVA-100029: Unable to obtain information for method [%1] from the class [%2]. ClassNotFoundException occurred. %3

Role: errorRole

Category: BW_Plugin

Description: ClassNotFoundException occurred while trying to get method information from the declared Java class.

Resolution: Please verify that the specified class file is contained in the classpath.

BW-JAVA-100030: Unable to obtain information for method [%1] from the class [%2]. Exception occurred. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred while trying to get method information from the declared Java class.

Resolution: Please correct the error and retry.

BW-JAVA-100031: Input data error. The activity received an incorrect value for the method parameters. IllegalArgumentException occurred while trying to invoke the method [%1]: %2

Role: errorRole

Category: BW_Plugin

Description: The activity received a incorrect value for the method parameter element that is in the activity input tab. IllegalArgumentException occurred while trying to invoke the Java method.

Resolution: Verify that the correct values are provided for the method parameter elements that are in the activity input tab.

BW-JAVA-100032: Input data error. The activity received an incorrect Java object for the declared Java class [%1]. The activity expected an instance of the Java class [%2], but received an instance of the Java class [%3]: %4

Role: errorRole

Category: BW_Plugin

Description: The activity received a incorrect value for the declared class element that is in the activity input tab.

Resolution: Possible causes for this error are: (1). Incorrect object reference was specified for the declared Java class. Verify that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. (2). The classpath refers to a incorrect declared class or the Java jar file. Verify that the classpath refers to the correct declared class.

BW-JAVA-100033: Input data error. The activity received an incorrect Java object for the declared Java class [%1]. The Java object received is not compatible with the Java object expected by this activity. The activity expects an instance of the Java class [%2]: %3

Role: errorRole

Category: BW_Plugin

Description: The activity received a incorrect value for the declared class element that is in the activity input tab.

Resolution: Possible causes for this error are: (1). Incorrect object reference was specified for the declared Java class. Verify that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. (2). The classpath refers to a incorrect declared class or the Java jar file. Verify that the classpath refers to the correct declared class.

BW-JAVA-100034: Input data error. The activity received 'null' value for the for the declared Java class. The activity expected an instance of the class [%1], but received a 'null'.

Role: errorRole

Category: BW_Plugin

Description: The activity received a null value for the declared class element that is in the activity input tab

Resolution: Possible causes for this error are: (1). Incorrect object reference was specified for the declared Java class. Verify that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. (2). The preceding activity that provides the input value for this activity produced a null for its output.

BW-JAVA-100035: Unable to invoke the method [%1]. Exception [%2] occurred. %3

Role: errorRole

Category: BW_Plugin

Description: Unable to invoke the user specified method of the Java class. Exception occurred while trying to invoke the method.

Resolution: Please correct the error stated in the exception message and retry.

BW-JAVA-100036: Unable to invoke the cleanup method [%1]. Exception [%2] occurred. %3

Role: errorRole

Category: BW_Plugin

Description: Unable to invoke the cleanup method for the Java class. Exception occurred while trying to invoke the method.

Resolution: Please correct the error stated in the exception message and retry.

BW-JAVA-100037: The method [%1] raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the specified method.

Resolution: The exception was raised by the method of the specified Java class. Please refer to the declared class implementation for details.

BW-JAVA-100038: The cleanup method [%1] raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the cleanup method.

Resolution: The exception was raised by the method of the specified Java class. Please refer to the declared class implementation for details.

BW-JAVA-100039: Exception occurred while trying to obtain the JavaSchema [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Unable to get the JavaSchema activity referenced by this activity

Resolution: Please correct the error and retry.

BW-JAVA-100040: The JavaSchema [%1] referenced by this activity is not found in repository.

Role: errorRole

Category: BW_Plugin

Description: The repository does not contain the JavaSchema activity referenced by this activity.

Resolution: Please correct the error and retry.

BW-JAVA-100041: The JavaSchema [%1] referenced by this activity contains invalid field values.

Role: errorRole

Category: BW_Plugin

Description: The JavaSchema activity referenced by this activity contains invalid field values.

Resolution: Please correct the error and retry.

BW-JAVA-100042: Input data error. The activity received 'null' value for the declared Java class. The activity expected instance of class [%1], but received a 'null'.

Role: errorRole

Category: BW_Plugin

Description: The activity received a null value for the declared Java class element that is in the activity input tab

Resolution: Possible causes for this error are: (1). Incorrect object reference was specified for the declared class. Verify that the correct Java object reference is provided for the declared class element shown in the input tab of this activity. (2). The preceding activity that provides the input value for this activity produced a null for its output.

BW-JAVA-100043: Input data error. The activity received incorrect Java object for the declared Java class. The activity expected instance of a class [%1], but received instance of a class [%2].

Role: errorRole

Category: BW_Plugin

Description: The activity received a incorrect value for the declared Java class element that is in the activity input tab.

Resolution: Possible causes for this error are: (1). Incorrect object reference was specified for the declared class. Verify that the correct Java object reference is provided for the declared class element shown in the input tab of this activity. (2). The classpath refers to a incorrect the declared class or the Java jar file. Verify that the classpath refers to the correct declared Java class.

BW-JAVA-100044: Configuration error. The Java class [%1] does not contain a default constructor or a constructor with no arguments. The selected Java class must have a default constructor if the user has selected the option to construct the declared class by the activity.

Role: errorRole

Category: BW_Plugin

Description: The user has selected the option to construct the declared class by the activity. This option is available in the

Resolution: Select a Java class that contain a default constructor

---

BW-JAVA-100045: Data Conversion error: %1

Role: errorRole

Category: BW_Plugin

Description: Unable to convert data from XML to Java or Java to XML.

Resolution: Certain Java data types are not supported by the BusinessWorks conversion mechanism. Please verify that unsupported data types are not utilized or referenced in your Java class.

BW-JAVA-100046: Data Conversion error. Exception occurred while trying to convert Java object to XML data. %1

Role: errorRole

Category: BW_Plugin

Description: Unable to convert the Java object to an XML data

Resolution: Certain Java data types are not supported by the Java to XML conversion mechanism. Please verify that unsupported data types are not utilized or referenced in your Java class.

BW-JAVA-100047: Data Conversion error. Exception occurred while trying to convert XML data to Java object. %1

Role: errorRole

Category: BW_Plugin

Description: Unable to convert the XML data to Java object

Resolution: Certain Java data types are not supported by the XML to Java conversion mechanism. Please verify that unsupported data types are not utilized or referenced in your Java class.

BW-JAVA-100048: Unable to generate schema for the Java class [%1]. Exception [%2] occurred. %3

Role: errorRole

Category: BW_Plugin

Description: Error occurred while trying to generate schema for the declared Java class.

Resolution: Please correct the error and retry.

BW-JAVA-100049: Configuration error. The Java class [%1] is not serializable. For XML to Java conversion operations the selected Java class must be a subtype of the interface 'java.io.Serializable'.

Role: errorRole

Category: BW_Plugin

Description: The selected class must be serializable for XML to Java conversion operation

Resolution: Select a class that is serializable

BW-JAVA-100050: Configuration error. The Java class [%1] does not contain a default constructor or a constructor with no arguments. For XML to Java conversion operation the selected Java class must have a default constructor.

Role: errorRole

Category: BW_Plugin

Description: The selected Java class does not contain a constructor with zero arguments

Resolution: Select a Java class that contain a default constructor

---

BW-JAVA-100051: Configuration error. The Java class [%1] contains unsupported data type. %2

Role: errorRole

Category: BW_Plugin

Description: The declared Java class contains unsupported data type.

Resolution: Certain Java data types are not supported by the XML to Java or Java to XML conversion mechanism. Please verify that unsupported data types are not utilized or referenced in your Java class.

BW-JAVA-100052: Missing the schema for the Java class [%1].

Role: errorRole

Category: BW_Plugin

Description: A schema could not be located the specified Java class.

Resolution: Please attempt to generate the schema.

BW-JAVA-100053: A schema for the JavaSchema resource [%1] with the namespace [%2] could not be found.

Role: errorRole

Category: BW_Plugin

Description: A schema could not be located the specified namespace.

Resolution: Please examine the JavaSchema resource and attempt to regenerate the schema.

BW-JAVA-100054: At runtime the TIBCO BusinessWorks activity will not be able to access the method [%1] of the class [%2]. The class or the superclass [%3] that implements the method is not declared as a public class.

Role: errorRole

Category: BW_Plugin

Description: The declared class modifier must be public.

Resolution: Please verfiy that the Java class that implements the selected method is declared public

---

BW-JAVA-100055: At runtime the TIBCO BusinessWorks activity will not be able to access the method [%1] of the class or interface [%2]. The interface [%3] that defines the method is not declared as a public interface.

Role: errorRole

Category: BW_Plugin

Description: The declared inteface modifier must be public.

Resolution: Please verfiy that the Java Inteface that proclaims the selected method is declared public

---

BW-JAVA-100056: Configuration error. The Java class [%1] does not contain a default constructor or a constructor with no arguments. For XML to Java conversion operations, the [%2] Java class must be comprised only of classes with default constructors.

Role: errorRole

Category: BW_Plugin

Description: All classes comprising the [%2] Java class must contain a constructor with zero arguments

Resolution: Select a Java class comprised only of classes with default constructors

---

BW-JAVA-100057: Configuration error. The Java class [%1] is is not declared as a public class. It is not permitted to create an instance of an non-public class.

Role: errorRole

Category: BW_Plugin

Description: The declared class modifier must be public.

Resolution: Make sure that the selected Java class is declared as a public class

---

BW-JAVA-100058: Exception occurred while trying to obtain the Java Global Instance resource reference [%1]: %2

Role: errorRole

Category: BW_Plugin

Description: Unable to get the Java Global Instance resource referenced by this activity

Resolution: Please correct the error and retry.

BW-JAVA-100059: The Java Global Instance resource [%1] referenced by this activity is not found in the repository.

Role: errorRole

Category: BW_Plugin

Description: The repository does not contain the Java Global Instance resource referenced by this activity.

Resolution: Please correct the error and retry.

BW-JAVA-100060: The Java Global Instance resource [%1] referenced by this activity contains invalid field values.

Role: errorRole

Category: BW_Plugin

Description: The Java Global Instance resource referenced by this activity contains invalid field values.

Resolution: Please correct the error and retry.

BW-JAVA-100061: Configuration error. The Java class name specified in this JavaMethod activity does not match the Java class name specified in the Java Global Instance resource [%1].

Role: errorRole

Category: BW_Plugin

Description: The Java Global Instance resource referenced by this JavaMethod activity contains different Java class name then the Java class name specified in the JavaMethod activity

Resolution: Please reconfigure the JavaMethod activity.

BW-JAVA-100062: Configuration error. The library specified in this JavaMethod activity does not match the library specified in the Java Global Instance resource [%1].

Role: errorRole

Category: BW_Plugin

Description: The Java Global Instance resource referenced by this JavaMethod activity contains different library value then the library value specified in the JavaMethod activity

Resolution: Please reconfigure the JavaMethod activity.

BW-JAVA-100063: Runtime error. Illegal onEvent(Object output)/onError(Throwable error) method call. OnEvent/OnError method must not be called in the init method or during the initialization phase.

Role: errorRole

Category: BW_Plugin

Description: The onEvent(Object output) method must never be called in the init() method. The BW engine is in the middle of initializing the Java Event Source activity.

Resolution: Please remove the onEvent(Object output) method call in the init method.

BW-JAVA-100064: Runtime error. Unable to generate notification events.

Role: errorRole

Category: BW_Plugin

Description: The error occurs when the JavaProcessStarter is unable to generate notification data due un-availability of a resource.

Resolution: Please check the JavaProcessStarter component for resource errors.

BW-JAVA-100065: Runtime error. The output type defined by the getOutputObjectType() does not match with the type that is passed in to onEvent(Object object).

Role: errorRole

Category: BW_Plugin

Description: This exception is thrown if the getOutputObjectType() method defines the type of the output object that is not the same as object type passed to onEvent(Object object) method in case of "Convert Output Object To XML" flag being set.

Resolution: Please make sure that object passed to onEvent(Object output) method is of the same type as that which is returned by getOutputObjectType().

Chapter 10 JDBC Palette

This chapter describes error codes that can be returned by activities in the JDBC palette.

Topics

- JDBC Error Codes, page 154

JDBC Error Codes

BW-JDBC-100000: Failed to find or create the JDBC driver : %1

Role: errorRole

Category: BW-Plugin

Description: Failed to find or create the JDBC driver

Resolution: Check the CLASSPATH and/or JDBC driver specification

BW-JDBC-100001: Missing SQL statement

Role: errorRole

Category: BW-Plugin

Description: Missing SQL statement

Resolution: Specify the SQL statement

BW-JDBC-100002: Some or all of the prepared parameters do not have data types specified

Role: errorRole

Category: BW-Plugin

Description: Some or all of the prepared parameters do not have data types specified

Resolution: Make sure all the prepared parameters have data types specified

BW-JDBC-100003: A JDBC driver that supports metadata access is required

Role: errorRole

Category: BW-Plugin

Description: A JDBC driver that supports metadata access is required

Resolution: Use a JDBC driver which allows metadata access

BW-JDBC-100004: This is not a valid SQL type: %1

Role: errorRole

Category: BW-Plugin

Description: Data type specified is not a valid SQL type

Resolution: Specify a valid SQL data type

BW-JDBC-100005: You must select a JDBC Connection shared configuration resource

Role: errorRole

Category: BW-Plugin

Description: You must select a JDBC Connection shared configuration resource

Resolution: Select a JDBC Connection shared configuration resource

---

BW-JDBC-100006: Cannot find shared JDBC configuration: %1

Role: errorRole

Category: BW-Plugin

Description: Cannot find shared JDBC configuration

Resolution: Please Contact TIBCO Support

BW-JDBC-100007: Cannot find TIbase.jar in the classpath

Role: errorRole

Category: BW-Plugin

Description: Cannot find TIbase.jar in the classpath

Resolution: Please Contact TIBCO Support

BW-JDBC-100008: Improper SQL statement used. %1

Role: errorRole

Category: BW-Plugin

Description: Improper SQL statement used. Details provided

Resolution: Correct and provide proper SQL statement

BW-JDBC-100009: Cannot load JDBC Driver: %1

Role: errorRole

Category: BW-Plugin

Description: Cannot load specified JDBC Driver

Resolution: Please Contact TIBCO Support

BW-JDBC-100010: Duplicate field name found '%1', please modify the query and create unique aliases for duplicate fields

Role: errorRole

Category: BW-Plugin

Description: Duplicate field name found, please modify the query and create unique aliases for duplicate fields

Resolution: Modify the query and create unique aliases for duplicate fields

---

BW-JDBC-100011: At least one parameter must have a value

Role: errorRole

Category: BW-Plugin

Description: At least one parameter must have a value

Resolution: Set a value for any parameter

BW-JDBC-100012: %1 is not a valid timezone. Please either choose a timezone from the list provided in the Constants tab or refer to the list of valid timezones in the documentation

Role: errorRole

Category: BW-Plugin

Description: Invalid timezone specified. Please either choose a timezone from the list provided in the Constants tab or refer to the list of valid timezones in the documentation

Resolution: Please either choose a timezone from the list provided in the Constants tab or refer to the list of valid timezones in the documentation

---

BW-JDBC-100013: JDBC plugin initialization failed: %1

Role: errorRole

Category: BW-Plugin

Description: JDBC plugin initialization failed. Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100014: JDBC error reported: (SQLState = %1) - %2

Role: errorRole

Category: BW-Plugin

Description: JDBC error reported. Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100015: JDBC plugin evaluation error: %1

Role: errorRole

Category: BW-Plugin

Description: JDBC plugin evaluation error. Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100016: No JDBC connection available

Role: errorRole

Category: BW-Plugin

Description: No JDBC connection available

Resolution: Please Contact TIBCO Support

BW-JDBC-100017: Failed to create input and/or output schema(s): %1

Role: errorRole

Category: BW-Plugin

Description: Failed to create input and/or output schema(s). Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100018: %1 input parameters declared in the SQL statement but no input parameters provided

Role: errorRole

Category: BW-Plugin

Description: Some input parameters declared in the SQL statement but no corresponding input parameters provided

Resolution: Provide input parameters declared in the SQL statement

---

BW-JDBC-100019: Unexpected number of input parameters. %1 declared in the SQL statement but %2 input parameters provided

Role: errorRole

Category: BW-Plugin

Description: Number of input parameters declared in the SQL statement does not match number of input parameters provided

Resolution: Make sure the number of input parameters declared in the SQL statement match number of input parameters provided

---

BW-JDBC-100020: Unexpected input parameters. No input parameter declared in the SQL statement but %1 input parameters provided

Role: errorRole

Category: BW-Plugin

Description: There is no input parameter declared in the SQL statement but some input parameters provided

Resolution: Remove all the input parameter provided

BW-JDBC-100021: JDBC plugin configuration error: %1

Role: errorRole

Category: BW-Plugin

Description: JDBC plugin configuration error. Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100022: Global variable %1 not defined

Role: errorRole

Category: BW-Plugin

Description: Specified global variable not defined

Resolution: Define such global variable

BW-JDBC-100023: JDBC activity timed out

Role: errorRole

Category: BW-Plugin

Description: JDBC activity timed out

Resolution: Please Contact TIBCO Support

BW-JDBC-100024: Invalid procedure name specified. %1

Role: errorRole

Category: BW-Plugin

Description: Invalid procedure name specified. Details provided

Resolution: Provide a valid stored procedure name

BW-JDBC-100025: Unable to obfuscate password. %1

Role: errorRole

Category: BW-Plugin

Description: Unable to obfuscate password. Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100026: Unable to deobfuscate password. %1

Role: errorRole

Category: BW-Plugin

Description: Unable to deobfuscate password. Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100027: %1 is not a valid SQL statement. It does not generate any output schema. Please press 'Fetch' button to (re)fetch output schema or correct the SQL statement

Role: errorRole

Category: BW-Plugin

Description: Invalid SQL statement specified. It does not generate any output schema. Please press 'Fetch' button to (re)fetch output schema or correct the SQL statement

Resolution: Please press 'Fetch' button to (re)fetch output schema or correct the SQL statement

---

BW-JDBC-100028: Invalid procedure name specified. It can not be null

Role: errorRole

Category: BW-Plugin

Description: Invalid procedure name specified. It can not be null

Resolution: Provide a valid stored procedure name

BW-JDBC-100029: The JNDI Configuration reference [%1] not found

Role: errorRole

Category: BW-Plugin

Description: The JNDI Configuration reference specified not found

Resolution: Provide a valid JNDI Configuration reference

BW-JDBC-100030: The JNDI Configuration reference [%1] not found in repository

Role: errorRole

Category: BW-Plugin

Description: The JNDI Configuration reference specified not found in repository

Resolution: Provide a valid JNDI Configuration reference

BW-JDBC-100031: The JNDI Configuration reference [%1] contains incorrect field values

Role: errorRole

Category: BW-Plugin

Description: The JNDI Configuration reference specified contains incorrect field values

Resolution: Check and correct specified JNDI Configuration reference

---

BW-JDBC-100032: Exception occurred while trying to obtain the JNDI Configuration reference [%1]: %2

Role: errorRole

Category: BW-Plugin

Description: Exception occurred while trying to obtain the JNDI Configuration reference. Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100033: Configuration Test Failed. %1

Role: errorRole

Category: BW-Plugin

Description: Configuration Test Failed. Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100034: Configuration Test Failed. Exception [%1] occurred.

Role: errorRole

Category: BW-Plugin

Description: Configuration Test Failed. Exception occurred. Details provided

Resolution: Please Contact TIBCO Support

BW-JDBC-100035: Invalid object looked up, must be either DataSource or XADataSource: %1

Role: errorRole

Category: BW-Plugin

Description: Invalid object looked up, must be either DataSource or XADataSource. JNDI lookup name provided

Resolution: Make sure JNDI lookup name bound to either DataSource or XADataSource object

---

BW-JDBC-100036: JNDI look up failed, object is null: %1

Role: errorRole

Category: BW-Plugin

Description: JNDI look up failed, object is null. JNDI lookup name provided

Resolution: Make sure JNDI look up returns not null object

BW-JDBC-100037: Batch updates failed on update number: %1

Role: errorRole

Category: BW-Plugin

Description: Batch updates failed on provided update numbers

Resolution: Resolve these individual updates

BW-JDBC-100038: Can't participlate in this transaction group. Correct JDBC Connection type or enable [Override Transaction Behavior]

Role: errorRole

Category: BW-Plugin

Description: Can't participlate in this transaction group. Correct JDBC Connection type or enable [Override Transaction Behavior]

Resolution: Correct JDBC Connection type or enable [Override Transaction Behavior]

BW-JDBC-100039: JDBC Connection Login timed out

Role: errorRole

Category: BW-Plugin

Description: JDBC Connection Login timed out

Resolution: Increase login timeout

BW-JDBC-100040: Invalid timeout value [%1]. The value must be an integer greater than or equal to '0'

Role: errorRole

Category: BW-Plugin

Description: Invalid timeout value specified. The value must be an integer greater than or equal to '0'

Resolution: Set timeout to an integer greater than or equal to '0'

Chapter 11 JMS Palette

This chapter describes error codes that can be returned by activities in the JMS palette.

Topics

- JMS Error Codes, page 166

JMS Error Codes

BW-JMS-100000: Invalid configuration data: JMS connection reference is not specified.

Role: errorRole

Category: BW-Plugin

Description: JMS connection reference is not specified in configuration data.

Resolution: Specify a valid JMS connection reference in activity configuration.

BW-JMS-100002: Invalid configuration data: specfied connection reference not found in repository.[%1]

Role: errorRole

Category: BW-Plugin

Description: The specified JMS connection reference is not found in repository. [%1-connection reference].

Resolution: Make sure that the connection reference specified in activity configuration refers to a valid shared JMS connection.

BW-JMS-100003: Invalid configuration data: JNDI context URL is not specified.[%1]

Role: errorRole

Category: BW-Plugin

Description: JNDI context URL is not specified in the shared JMS connection. [%1-shared connection data].

Resolution: Specify a valid JNDI context URL in the specified shared JMS connection.

BW-JMS-100004: Invalid configuration data: JNDI initial context factory is not specified.[%1]

Role: errorRole

Category: BW-Plugin

Description: JNDI initial context factory is not specified in the shared JMS connection. [%1-shared connection data].

Resolution: Specify a valid JNDI initial context factory in the specified shared JMS connection.

BW-JMS-100005: Could not create connection with JMS server.[%1]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a connection with JMS server[%1-connection key data].

Resolution: Look at the exception for more information.

BW-JMS-100006: Could not create a session to receive messages.[%1]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a session to receive messages [%1-configuration data].

Resolution: Look at the exception for more information.

BW-JMS-100007: Could not create a reply session/producer.[%1]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a reply producer [%1-configuration data].

Resolution: Look at the exception for more information.

BW-JMS-100008: JNDI lookup of queue name [%1] failed.

Role: errorRole

Category: BW-Plugin

Description: JNDI lookup of queue name [%1] failed.

Resolution: Look at the exception for more information. Make sure that the queue has been setup in your JMS provider

---

BW-JMS-100009: Cannot retrieve queue with name [%1].

Role: errorRole

Category: BW-Plugin

Description: Cannot retrieve queue with name [%1].

Resolution: Make sure that the queue has been setup in your JMS provider.

BW-JMS-100010: Error creating JNDI initial context [%1].

Role: errorRole

Category: BW-Plugin

Description: Cannot create JNDI initial context [%1 - connection key data].

Resolution: Look at the exception for more information.

BW-JMS-100011: JNDI lookup of topic name [%1] failed.

Role: errorRole

Category: BW-Plugin

Description: JNDI lookup of topic name [%1] failed.

Resolution: Look at the exception for more information. Make sure that the topic has been setup in your JMS provider

---

BW-JMS-100012: Cannot retrieve topic with name [%1].

Role: errorRole

Category: BW-Plugin

Description: Cannot retrieve topic with name [%1].

Resolution: Make sure that the topic has been setup in your JMS provider.

BW-JMS-100013: Error creating dynamic queue with name [%1].

Role: errorRole

Category: BW-Plugin

Description: Error creating dynamic queue with name [%1].

Resolution: Look at the exception for more information. Also refer to your JMS provider documentation.

BW-JMS-100014: Error creating dynamic topic with name [%1].

Role: errorRole

Category: BW-Plugin

Description: Error creating dynamic topic with name [%1].

Resolution: Look at the exception for more information. Also refer to your JMS provider documentation.

BW-JMS-100015: Could not create queue message receiver.[%1]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a queue receiver [%1-configuration data].

Resolution: Look at the exception for more information.

BW-JMS-100016: Could not create queue message receiver.[%1]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a queue receiver [%1-Destination].

Resolution: Look at the exception for more information.

BW-JMS-100017: Could not create durable topic message subsriber.[%1]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a durable topic message subsriber.[%1-configuration data].

Resolution: Look at the exception for more information.

BW-JMS-100018: Could not create topic message subsriber.[%1]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a topic message subsriber.[%1-configuration data].

Resolution: Look at the exception for more information.

BW-JMS-100019: Could not create topic message subsriber.[%1]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a topic message subsriber.[%1-Destination].

Resolution: Look at the exception for more information.

BW-JMS-100020: There was an error when attempting to receive a message.

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to receive a message.

Resolution: Look at the exception for more information.

BW-JMS-100021: There was an error in onMessage callback for a received message of type [%1].

Role: errorRole

Category: BW-Plugin

Description: There was an error in onMessage callback for a received message of type [%1].

Resolution: Look at the exception for more information.

BW-JMS-100022: Received a message of type [%1] but configured to receive messages of type [%2].

Role: errorRole

Category: BW-Plugin

Description: The message type of received message does not match the configured message type.

Resolution: Make sure that the JMS message type is configured correctly in the activity configuration.

BW-JMS-100023: There was an error while parsing the reply message.

Role: errorRole

Category: BW-Plugin

Description: There was an error while parsing the reply message.

Resolution: Look at the exception for more information.

BW-JMS-100024: There was an error when attempting to confirm a message.

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to confirm a message.

Resolution: Look at the exception for more information.

BW-JMS-100026: JMS message type [%1] is not valid.

Role: errorRole

Category: BW-Plugin

Description: JMS message type [%1] is not valid.

Resolution: Internal error.

BW-JMS-100027: Error creating temporary queue for reply.

Role: errorRole

Category: BW-Plugin

Description: Error creating temporary queue topic for reply.

Resolution: Look at the exception for more information.

BW-JMS-100028: Error creating temporary topic for reply.

Role: errorRole

Category: BW-Plugin

Description: Error creating temporary topic for reply.

Resolution: Look at the exception for more information.

BW-JMS-100029: Could not create a reply receiver.[Destination=%1]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a reply receiver.[Destination=%1].

Resolution: Look at the exception for more information.

BW-JMS-100030: There was an error when attempting to send a request message.

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to send a request message.

Resolution: Look at the exception for more information.

BW-JMS-100031: There was an unexpected error.

Role: errorRole

Category: BW-Plugin

Description: There was an unexpected error.

Resolution: Look at the exception for more information.

BW-JMS-100032: There was an unexpected error.

Role: errorRole

Category: BW-Plugin

Description: There was an unexpected error.

Resolution: Look at the exception for more information.

BW-JMS-100033: Unkown state in request/reply processing [%1].

Role: errorRole

Category: BW-Plugin

Description: There was an unexpected error [%1-closure].

Resolution: Look at the exception for more information.

BW-JMS-100034: There was an error while cancelling.

Role: errorRole

Category: BW-Plugin

Description: There was an error while cancelling.

Resolution: Look at the exception for more information.

BW-JMS-100035: Received a null reply message.

Role: errorRole

Category: BW-Plugin

Description: Received a null reply message.

Resolution: Look at the exception for more information.

BW-JMS-100036: Could not create a session to send request messages.[ConnectionKey=%1, Transacted=%2, AckMode=%3]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a session to send request messages [ConnectionKey=%1, Transacted=%2, AckMode=%3].

Resolution: Look at the exception for more information.

BW-JMS-100037: Could not create a session to receive reply messages.[ConnectionKey=%1, Transacted=%2, AckMode=%3]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a session to send reply messages [ConnectionKey=%1, Transacted=%2, AckMode=%3].

Resolution: Look at the exception for more information.

BW-JMS-100038: Could not create a session to send messages.[ConnectionKey=%1, Transacted=%2, AckMode=%3]

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to create a session to send messages [ConnectionKey=%1, Transacted=%2, AckMode=%3].

Resolution: Look at the exception for more information.

BW-JMS-100039: There was an unexpected error while sending a message.

Role: errorRole

Category: BW-Plugin

Description: There was an unexpected error while sending a message.

Resolution: Look at the exception for more information.

BW-JMS-100040: There was an unexpected error while sending a reply.

Role: errorRole

Category: BW-Plugin

Description: There was an unexpected error while sending a reply.

Resolution: Look at the exception for more information.

BW-JMS-100041: There was an internal error when attempting setReady.

Role: errorRole

Category: BW-Plugin

Description: There was an internal error when attempting setReady.

Resolution: Look at the exception for more information.

BW-JMS-100042: There was an error while sending a message.

Role: errorRole

Category: BW-Plugin

Description: There was an error while sending a message.

Resolution: Look at the exception for more information.

BW-JMS-100043: There was an error while parsing a message.

Role: errorRole

Category: BW-Plugin

Description: There was an error while parsing a message.

Resolution: Look at the exception for more information.

BW-JMS-100044: There was an error while parsing the JMS schema.

Role: errorRole

Category: BW-Plugin

Description: There was an error while parsing the JMS schema.

Resolution: This is an internal error.

BW-JMS-100045: There was an error while parsing the JMS schema.

Role: errorRole

Category: BW-Plugin

Description: There was an error while parsing the JMS schema.

Resolution: This is an internal error.

BW-JMS-100046: There was an error while parsing the JMS schema.

Role: errorRole

Category: BW-Plugin

Description: There was an error while parsing the JMS schema.

Resolution: This is an internal error.

BW-JMS-100047: There was an error while parsing data to build a message: attributes are not allowed.

Role: errorRole

Category: BW-Plugin

Description: There was an error while parsing data to build a messag: attributes are not allowed.

Resolution: This is an internal error.

BW-JMS-100048: There was an error while parsing data to build a message: mixed text not allowed.

Role: errorRole

Category: BW-Plugin

Description: There was an error while parsing data to build a messag: mixed text not allowed.

Resolution: This is an internal error.

BW-JMS-100049: JMS message priority [%1] in input bind is not valid.

Role: errorRole

Category: BW-Plugin

Description: JMS message priority [%1] in input bind is not valid.

Resolution: A valid JMS message priority must be a number between 0 and 9 (inclusive).

BW-JMS-100050: Invalid JMS Application Properties [%1].

Role: errorRole

Category: BW-Plugin

Description: JMS application properties are not valid. See [%1-exception] for more details.

Resolution: Verify that JMS application properties are correct. This can be done by using 'validate for deployment' feature of the Designer.

BW-JMS-100051: Invalid message body schema specified [%1] [%2].

Role: errorRole

Category: BW-Plugin

Description: The schema [%1] to define message body is not valid. See [%2-exception] for more details.

Resolution: Check the message body schema specified.

BW-JMS-100052: Invalid JMS message type specified [%1].

Role: errorRole

Category: BW-Plugin

Description: The JMS message type [%1] is not valid.

Resolution: Pick a valid JMS message type.

BW-JMS-100053: An internal error occured while processing configuration data [%1].

Role: errorRole

Category: BW-Plugin

Description: An internal error occured while processing configuration data. See [%1-exception] for more details.

Resolution: Check the exception for more details.

BW-JMS-100054: Invalid input data.

Role: errorRole

Category: BW-Plugin

Description: Input data is invalid. See the exception for more details.

Resolution: Check activity input data.

BW-JMS-100055: Error creating JMS message.

Role: errorRole

Category: BW-Plugin

Description: There was an error while creating a JMS message. See the exception for more details.

Resolution: Check activity input data. See the exception for more details.

BW-JMS-100056: Invalid configuration data: message body schema is not specified.

Role: errorRole

Category: BW-Plugin

Description: Invalid configuration data: no schema specified for message body.

Resolution: Specify a schema to represent the message body in the 'Input Editor' or 'Output Editor' tab.

BW-JMS-100057: Invalid configuration data: destination %1 name is not specified.

Role: errorRole

Category: BW-Plugin

Description: Invalid configuration data: destination name is not specified.

Resolution: Specify name of the topic/queue destination in 'Configuration' tab.

BW-JMS-100058: Invalid configuration data: reply to is not specified.

Role: errorRole

Category: BW-Plugin

Description: Invalid configuration data: reply to is not specified.

Resolution: Pick the reply target in 'Configuration' tab.

BW-JMS-100059: Cannot create connection factory in a provider-specific way.

Role: errorRole

Category: BW-Plugin

Description: Cannot create connection factory in a provider-specific way. Use JNDI lookup instead.

Resolution: Please use TIBCO Enterprise for JMS. Otherwise use JNDI to lookup connection factory.

BW-JMS-100060: Invalid configuration data: message body schema is not specified in 'Input Editor' tab.

Role: errorRole

Category: BW-Plugin

Description: Invalid configuration data: no schema specified for the request message body in 'Input Editor' tab.

Resolution: Specify a schema to represent the request message body in the 'Input Editor' tab.

BW-JMS-100061: Invalid configuration data: message body schema is not specified in 'Output Editor' tab.

Role: errorRole

Category: BW-Plugin

Description: Invalid configuration data: no schema specified for the reply message body in 'Output Editor' tab.

Resolution: Specify a schema to represent the reply message body in the 'Output Editor' tab.

BW-JMS-100062: Invalid message body schema specified in 'Input Editor' tab [%1] [%2].

Role: errorRole

Category: BW-Plugin

Description: The schema [%1] to define the request message body in 'Input Editor' tab is not valid. See [%2-exception] for more details.

Resolution: Check the request message body schema specified in 'Input Editor' tab.

BW-JMS-100063: Invalid message body schema specified in 'Output Editor' tab [%1] [%2].

Role: errorRole

Category: BW-Plugin

Description: The schema [%1] to define the reply message body in 'Output Editor' tab is not valid. See [%2-exception] for more details.

Resolution: Check the reply message body schema specified in 'Output Editor' tab.

BW-JMS-100064: Could not decrypt password.[%1].

Role: errorRole

Category: BW-Plugin

Description: There was an error while decrypting a password. See [%1-exception] for more details.

Resolution: Make sure that the password stored in the repository is not in clear text.

BW-JMS-100065: Can't create XAResource.Check if the ConnectionFactory [%1] is XA enabled.

Role: errorRole

Category: BW-Plugin

Description: Can't create XAResource.Check if the ConnectionFactory [%1] is XA enabled.

Resolution: Check if the ConnectionFactory [%1] is XA enabled.

BW-JMS-100066: JNDI lookup failed for queue with name [%1].

Role: errorRole

Category: BW-Plugin

Description: JNDI lookup failed for queue with name [%1].

Resolution: Look at the exception for more information. Also refer to your JMS provider documentation.

Chapter 12 Mail Palette

This chapter describes error codes that can be returned by activities in the Mail palette.

Topics

- Mail Error Codes, page 184

Mail Error Codes

BW-MAIL-100001: Invalid input data: mail server host not specified

Role: errorRole

Category: BW-Plugin

Description: Host name of mail server is not specified.

Resolution: Specify a valid mail server host in configuration.

BW-MAIL-100002: Invalid input data: username not specified.

Role: errorRole

Category: BW-Plugin

Description: Username for mail server account is not specified

Resolution: Specify a valid user name in configuration.

BW-MAIL-100003: Invalid input data: password not specified.

Role: errorRole

Category: BW-Plugin

Description: Password for mail server account is not specified.

Resolution: Specify a valid password in configuration.

BW-MAIL-100004: Invalid input data: Null input data.

Role: errorRole

Category: BW-Plugin

Description: Input data is null.

Resolution: Check activity input data.

BW-MAIL-100005: Invalid input data: Error parsing input data.

Role: errorRole

Category: BW-Plugin

Description: Input data is invalid.

Resolution: Check activity input data.

BW-MAIL-100006: Invalid input data: Unequal number of attachment names and attachment data.

Role: errorRole

Category: BW-Plugin

Description: Number of attachment names and attachment data specified in the input are unequal.

Resolution: Check attachment input data.

BW-MAIL-100007: Invalid input data: Both the comma and semicolon cannot be used at same time to separate addresses.

Role: errorRole

Category: BW-Plugin

Description: Both the comma and semicolon cannot be used at same time to separate addresses.

Resolution: Use either comma or semicolon for separating addresses.

BW-MAIL-100008: Mail provider for protocol [%1] not found. Make sure that the provider jar is in java classpath.

Role: errorRole

Category: BW-Plugin

Description: Could not initialize the mail provider for specified protocol: [mail protocol].

Resolution: Make sure that the mail provider jar file is in java classpath.

BW-MAIL-100009: Error connecting to the mail server using connection parameters: [%1].

Role: errorRole

Category: BW-Plugin

Description: Could not establish connection to the mail server using sepecifed parameters: [parameters].

Resolution: Check configuration data.

BW-MAIL-100010: The default mail folder was not found on mail server.

Role: errorRole

Category: BW-Plugin

Description: The default mail folder was not found on mail server.

Resolution: Check mail server setup.

BW-MAIL-100011: The INBOX mail folder was not found on mail server.

Role: errorRole

Category: BW-Plugin

Description: The INBOX mail folder was not found on mail server.

Resolution: Check mail server setup.

BW-MAIL-100012: Error getting folder on mail server.

Role: errorRole

Category: BW-Plugin

Description: Error getting folder on mail server.

Resolution: Check mail server setup.

BW-MAIL-100013: Error closing mail server connection.

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting close connection with mail server.

Resolution: Look at the exception for more information.

BW-MAIL-100014: Error while polling mail server: cannot open INBOX folder.

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to open connection with mail server.

Resolution: Look at the exception for more information.

BW-MAIL-100015: Error while polling mail server: cannot close INBOX folder.

Role: errorRole

Category: BW-Plugin

Description: There was an error when attempting to close connection with mail server.

Resolution: Look at the exception for more information.

BW-MAIL-100016: Unexpected error while polling mail server.

Role: errorRole

Category: BW-Plugin

Description: There was an unexpected error while retrieving mails.

Resolution: Look at the exception for more information.

BW-MAIL-100017: Error parsing received mail.

Role: errorRole

Category: BW-Plugin

Description: There was an error while parsing a new mail message received.

Resolution: Look at the exception for more information.

BW-MAIL-100018: Error building mail message.

Role: errorRole

Category: BW-Plugin

Description: There was an error while building a mail message to send.

Resolution: Look at the exception for more information.

BW-MAIL-100019: Error sending mail message.

Role: errorRole

Category: BW-Plugin

Description: Error sending mail message. Cause: %1

Resolution: Look at the exception for more information.

BW-MAIL-100020: Error connecting to the mail server - unknown host; connection parameters: [%1].

Role: errorRole

Category: BW-Plugin

Description: Could not establish connection to the mail server - specified host is unknown: [%1 - connection parameters].

Resolution: Specify a valid mail server host in configuration or check your network connections and setup.

BW-MAIL-100021: Error connecting to the mail server - connect exception; connection parameters: [%1].

Role: errorRole

Category: BW-Plugin

Description: Could not establish connection to the mail server - connect exception: [%1 - connection parameters].

Resolution: Verify that your mail server is running or check your network connections.

BW-MAIL-100022: An internal error occured while processing configuration data [%1].

Role: errorRole

Category: BW-Plugin

Description: An internal error occured while processing configuration data. See [%1-exception] for more details.

Resolution: Check the exception for more details.

BW-MAIL-100023: Invalid polling interval [%1] [%2].

Role: errorRole

Category: BW-Plugin

Description: Specified polling interval [%1] is not valid. See [%2-exception] for more details.

Resolution: Specify a valid polling interval.

BW-MAIL-100024: Could not resolve mail server host name [%1].

Role: errorRole

Category: BW-Plugin

Description: The specified host name of mail server [%1] cannot be resolved.

Resolution: Use a valid mail server host name. If the host name is valid, make sure the network naming (DNS) is properly setup.

BW-MAIL-100025: Could not decrypt password [%1].

Role: errorRole

Category: BW-Plugin

Description: There was an error while decrypting a password. See [%1-exception] for more details.

Resolution: Make sure that the password stored in the repository is not in clear text.

BW-MAIL-100026: Could not connect to mail server - invalid username in field [%1] and/or invalid password in field [%2].

Role: errorRole

Category: BW-Plugin

Description: Got authentication error while connecting to mail server.

Resolution: Make sure that the username and password are correct.

BW-MAIL-100027: %1 Start time = %2 End time= %3 Processing time= %4

Role: infoRole

Category: BW-Plugin

Description: %1 Start time = %2 End time= %3 Processing time= %4

Resolution: none

BW-MAIL-100028: %1 Processing times: %2

Role: infoRole

Category: BW-Plugin

Description: %1 Processing times: %2

Resolution: none

BW-MAIL-100029: Using POP3 Provider from %1

Role: infoRole

Category: BW-Plugin

Description: Using POP3 Provider from %1

Resolution: none

BW-MAIL-100030: Username can not be null when Authentication is on

Role: errorRole

Category: BW-Plugin

Description: Username can not be null when Authentication is on

Resolution: Make sure that the username and password are correct.

BW-MAIL-100031: Password can not be null when Authentication is on

Role: errorRole

Category: BW-Plugin

Description: Password can not be null when Authentication is on

Resolution: Make sure that the username and password are correct.

BW-MAIL-100032: Mail is already deleted, Receive Mail activity has 'Delete Mail' turned on

Role: errorRole

Category: BW-Plugin

Description: Mail is already deleted, Receive Mail activity has 'Delete Mail' turned on

Resolution: Either turn off 'Delete Mail' in Mail Receiver or do not use Confirm activity

---

BW-MAIL-100033: Error building mail message. Cause: %1

Role: errorRole

Category: BW-Plugin

Description: There was an error while building a mail message to send.

Resolution: Look at the exception for more information.

Chapter 13 Manual Work Palette

This chapter describes error codes that can be returned by activities in the Manual Work palette.

Topics

- Manual Work Error Codes, page 194

Manual Work Error Codes

BW-Inconcert-100000: Server Connection Reference not set.

Role: errorRole

Category: BW-Plugin

Description: Server Connection Reference not set.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100001: Cannot find shared connection resource: %1.

Role: errorRole

Category: BW-Plugin

Description: Cannot find shared connection resource: %1.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100002: Work details reference not set.

Role: errorRole

Category: BW-Plugin

Description: Work details reference not set.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100003: Fail to get event manager.

Role: errorRole

Category: BW-Plugin

Description: Fail to get event manager.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100004: Work ID need to be set. Check your input tab to make sure that work ID binded is valid

Role: errorRole

Category: BW-Plugin

Description: Work ID need to be set. Check your input tab to make sure that work ID binded is valid

Resolution: Please Contact TIBCO Support

BW-Inconcert-100005: The inconcert user pool selected is empty.

Role: errorRole

Category: BW-Plugin

Description: The inconcert user pool selected is empty.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100006: Cannot connect to IC Server.

Role: errorRole

Category: BW-Plugin

Description: Cannot connect to IC Server.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100007: Exception caught in assign task activity. Exception Message: %1

Role: errorRole

Category: BW-Plugin

Description: Exception caught in assign task activity.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100008: Cannot find work details reference: %1.

Role: errorRole

Category: BW-Plugin

Description: Cannot find work details reference: %1.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100009: The server %1 is not configured correctly. Run the batch registry script "mkpcattr.btg" before proceeding.

Role: errorRole

Category: BW-Plugin

Description: The server %1 is not configured correctly. Run the batch registry script "mkpcattr.btg" before proceeding.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100010: Failed to locate the ICPLUGIN server %1.

Role: errorRole

Category: BW-Plugin

Description: Failed to locate the ICPLUGIN server %1

Resolution: Please Contact TIBCO Support

BW-Inconcert-100011: JNI libraries required to interact with Ic Server are missing.

Role: errorRole

Category: BW-Plugin

Description: JNI libraries required to interact with Ic Server are missing.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100012: Cannot generate workflow server list.

Role: errorRole

Category: BW-Plugin

Description: Cannot generate workflow server list.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100013: Timed out waiting for response.

Role: errorRole

Category: BW-Plugin

Description: Timed out waiting for response.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100014: Error in EventManager: %1.

Role: errorRole

Category: BW-Plugin

Description: Error in EventManager: %1.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100015: Encountered %1 for field %2 when expecting %3.

Role: errorRole

Category: BW-Plugin

Description: Encountered %1 for field %2 when expecting %3.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100016: Work Resource cannot be found %1.

Role: errorRole

Category: BW-Plugin

Description: Work Resource cannot be found %1.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100017: Field %1 is already defined in parent schema %2.

Role: errorRole

Category: BW-Plugin

Description: Field %1 is already defined in parent schema %2.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100018: Test Workflow connection

Role: infoRole

Category: connection

Description: Test Workflow connection

Resolution: Please Contact TIBCO Support

BW-Inconcert-100019: Connected to Workflow Server %1.

Role: infoRole

Category: connection

Description: Connected to Workflow Server %1.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100020: The "Extended Details" does not support "Document" fields. All the "Document" fields are ignored.

Role: infoRole

Category: connection

Description: The "Extended Details" does not support "Document" fields. All the "Document" fields are ignored.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100021: Failed to connect to Workflow Server "%1".

Role: errorRole

Category: BW-Plugin

Description: Failed to connect to Workflow Server "%1".

Resolution: Please Contact TIBCO Support

BW-Inconcert-100022: Error while handling response timeout

Role: errorRole

Category: BW-Plugin

Description: Error while handling response timeout

Resolution: Please Contact TIBCO Support

BW-Inconcert-100023: Exception caught in query docuement activity. Exception message: %1

Role: errorRole

Category: BW-Plugin

Description: Exception caught in query document activity.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100024: Exception caught in work status activity. Exception message: %1

Role: errorRole

Category: BW-Plugin

Description: Exception caught in work status activity.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100025: Exception caught in work action activity. Exception message: %1

Role: errorRole

Category: BW-Plugin

Description: Exception caught in work action activity.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100026: Error caught in wait work activity. Exception message: %1

Role: errorRole

Category: BW-Plugin

Description: Exception caught in wait work activity.

Resolution: Please Contact TIBCO Support

BW-Inconcert-100027: Reserved word cannot be used in schema:%1

Role: errorRole

Category: BW-Plugin

Description: Reserved word cannot be used in schema:%1

Resolution: Please Contact TIBCO Support

BW-Inconcert-100028: Schema Validation Error

Role: errorRole

Category: BW-Plugin

Description: Schema Validation Error

Resolution: Please Contact TIBCO Support

BW-Inconcert-100029: Work Name need to be set. Check your input tab to make sure that work Name binded is valid

Role: errorRole

Category: BW-Plugin

Description: Work Name need to be set. Check your input tab to make sure that work Name binded is valid

Resolution: Please Contact TIBCO Support

BW-Inconcert-100030: Assign Pool is not set.

Role: errorRole

Category: BW-Plugin

Description: Assign Pool is not set.

Resolution: Please Contact TIBCO Support

Chapter 14 Parse Palette

This chapter describes error codes that can be returned by activities in the Parse palette.

Topics

- Parse Error Codes, page 204

Parse Error Codes

BW-PARSE-100000: Cannot find data format schema resource: %1.

Role: errorRole

Category: BW-Plugin

Description: Cannot find data format schema resource: %1.

Resolution: Please Contact TIBCO Support

BW-PARSE-100001: Cannot create schema from data format schema.

Role: errorRole

Category: BW-Plugin

Description: Cannot create schema from data format schema.

Resolution: Please Contact TIBCO Support

BW-PARSE-100002: Exception in parse eval: %1.

Role: errorRole

Category: BW-Plugin

Description: Exception in parse eval: %1.

Resolution: Please Contact TIBCO Support

BW-PARSE-100003: Line length needs to be

Role: errorRole

Category: BW-Plugin

Description: Line length needs to be

Resolution: Please Contact TIBCO Support

BW-PARSE-100004: Hit EOF on row %1 field %2 spanning columns %3 to %4 .... last row contents was: '%5'

Role: errorRole

Category: BW-Plugin

Description: Hit EOF on row %1 field %2 spanning columns %3 to %4 .... last row contents was: '%5'

Resolution: Please Contact TIBCO Support

BW-PARSE-100005: Input type is not specified.

Role: errorRole

Category: BW-Plugin

Description: Input type is not specified.

Resolution: Please Contact TIBCO Support

BW-PARSE-100006: Please specify the Input type field.

Role: errorRole

Category: BW-Plugin

Description: Please specified the Input type field.

Resolution: Please Contact TIBCO Support

BW-PARSE-100007: Data format resource not specified.

Role: errorRole

Category: BW-Plugin

Description: Data format resource not specified.

Resolution: Please Contact TIBCO Support

BW-PARSE-100008: Please specify the data format resource.

Role: errorRole

Category: BW-Plugin

Description: Please specified the data format resource.

Resolution: Please Contact TIBCO Support

BW-PARSE-100009: File %1 cannot be opened using encoding method %2

Role: errorRole

Category: BW-Plugin

Description: File %1 cannot be opened using encoding method %2

Resolution: Please Contact TIBCO Support

BW-PARSE-100010: %1 must be specified if %2 is selected.

Role: errorRole

Category: BW-Plugin

Description: %1 must be specified if %2 is selected.

Resolution: Please Contact TIBCO Support

BW-PARSE-100011: Format Type must be selected.

Role: errorRole

Category: BW-Plugin

Description: Format Type must be selected.

Resolution: Please Contact TIBCO Support

BW-PARSE-100012: Line is too long. Specified Line Delimiter may not match file content.

Role: errorRole

Category: BW-Plugin

Description: Line is too long. Specified Line Delimiter may not match file content.

Resolution: Please check your input values.

BW-PARSE-100013: There are not enough data for the number of required fields in a row.

Role: errorRole

Category: BW-Plugin

Description: There are not enough data for the number of required fields in a row.

Resolution: Please check your input values.

Chapter 15 Rendezvous Palette

This chapter describes error codes that can be returned by activities in the Rendezvous palette.

Topics

- TIBCO Rendezvous Error Codes, page 210

TIBCO Rendezvous Error Codes

BW-TIBRV-100000: Cannot create Transport

Role: errorRole

Category: BW-Plugin

Description: Cannot create Transport

Resolution: Please check the transport configuration

BW-TIBRV-100001: Error in sending message

Role: errorRole

Category: BW-Plugin

Description: Error in sending message

Resolution: Please Contact TIBCO Support

BW-TIBRV-100002: Error serializing the message

Role: errorRole

Category: BW-Plugin

Description: Error serializing the message

Resolution: Please Contact TIBCO Support

BW-TIBRV-100003: Error in sending request

Role: errorRole

Category: BW-Plugin

Description: Error in sending request

Resolution: Please Contact TIBCO Support

BW-TIBRV-100004: Error in processing event: [%1]

Role: errorRole

Category: BW-Plugin

Description: Error in processing event

Resolution: Please Contact TIBCO Support

BW-TIBRV-100005: Cannot create TibrvQueue: [%1]

Role: errorRole

Category: BW-Plugin

Description: Cannot create TibrvQueue

Resolution: Please Contact TIBCO Support

BW-TIBRV-100006: Cannot create rvEventContext: [%1]

Role: errorRole

Category: BW-Plugin

Description: Cannot create rvEventContext

Resolution: Please Contact TIBCO Support

BW-TIBRV-100007: Cannot create reply listener for subject: [%1]

Role: errorRole

Category: BW-Plugin

Description: Cannot create reply listener, for subject: [%1]

Resolution: Please Contact TIBCO Support

BW-TIBRV-100008: Cannot activate TIBRV listener for subject: [%1]

Role: errorRole

Category: BW-Plugin

Description: Cannot activate TIBRV listener for subject: [%1]

Resolution: Please Contact TIBCO Support

BW-TIBRV-100009: Error in sending reply

Role: errorRole

Category: BW-Plugin

Description: Error in sending reply

Resolution: Please Contact TIBCO Support

BW-TIBRV-100010: Reply For-field not set in reply activity

Role: errorRole

Category: BW-Plugin

Description: Reply For-field not set in reply activity

Resolution: Please set the needed field in the activity

BW-TIBRV-100011: Cannot reply to [%1]: activity not found in process

Role: errorRole

Category: BW-Plugin

Description: Cannot reply to configured eventsource. It is not found in process

Resolution: Make sure to have RV-EventSource in the process to which the reply-activity needs to reply

---

BW-TIBRV-100012: Transport parameter not specified

Role: errorRole

Category: BW-Plugin

Description: Configure a valid transport reference on the Activity/EventSource

Resolution: Configure a valid transport reference on the Activity/EventSource

---

BW-TIBRV-100013: Subject parameter not specified

Role: errorRole

Category: BW-Plugin

Description: Configure a valid subject-name on the Activity/EventSource

Resolution: Configure a valid subject-name on the Activity/EventSource

---

BW-TIBRV-100014: Daemon Certificate not specified

Role: errorRole

Category: BW-Plugin

Description: Configure a valid daemon certificate in SSL configuration

Resolution: Configure a valid daemon certificate in SSL configuration

---

BW-TIBRV-100015: Identity not specified

Role: errorRole

Category: BW-Plugin

Description: Configure a valid identity in SSL configuration

Resolution: Configure a valid identity in SSL configuration

BW-TIBRV-100016: [%1]

Role: errorRole

Category: BW-Plugin

Description: The exception will give information for the problem encountered.

Resolution: The exception will give information for the problem encountered.

BW-TIBRV-100017: Reply Subject is not specified.

Role: errorRole

Category: BW-Plugin

Description: Specify the reply subject in the configuration/inputdata.

Resolution: Specify the reply subject in the configuration/inputdata.

BW-TIBRV-100018: CM Name is not specified. If omitted, a unique, non-reusable name will be generated for the duration of the transport.

Role: errorRole

Category: BW-Plugin

Description: CM Name is not specified. If omitted, a unique, non-reusable name will be generated for the duration of the transport.

Resolution: CM Name is not specified. If omitted, a unique, non-reusable name will be generated for the duration of the transport.

BW-TIBRV-100019: Specified Global-Variable is not found for [%1].

Role: errorRole

Category: BW-Plugin

Description: Specified Global-Variable is not found for the attribute.

Resolution: Please specify the initialized Globle-Variable.

BW-TIBRV-100020: Scheduler Weight of 0 is not allowed with the Worker Complete Time

Role: errorRole

Category: BW-Plugin

Description: Scheduler Weight of 0 is not allowed with the Worker Complete Time

Resolution: Please refer to the documentation for correct combination of values

---

BW-TIBRV-100021: Reply not Specified

Role: errorRole

Category: BW-Plugin

Description: Specify the input schema for the Rendezvous Reply activity.

Resolution: Specify the input schema for the Rendezvous Reply activity.

BW-TIBRV-200001: Rendezvous Subscriber/Wait for Rendezvous Message-exception setting certified output field: [%1], Event-Source-Name: [%2].

Role: warnRole

Category: BW-Plugin

Description: Rendezvous Subscriber/Wait for Rendezvous Message-exception setting certified output field.

Resolution:

BW-TIBRV-200002: Transport selected for the Rendezvous Subscriber/Wait for Rendezvous Message does not support confirm.

Role: warnRole

Category: BW-Plugin

Description: Transport selected for the Rendezvous Subscriber/Wait for Rendezvous Message does not support confirm.

Resolution:

BW-ADVISORY-100000: Advisory listening queue caught exception: %1

Role: errorRole

Category: BW-Plugin

Description: Advisory listening queue caught exception. Exception detail provided

Resolution: Please Contact TIBCO Support

BW-ADVISORY-300000: Advisory: %1

Role: infoRole

Category: BW-Plugin

Description: Advisory provided

Resolution: N/A

BW-ADVISORY-300001: Advisory info: %1

Role: infoRole

Category: BW-Plugin

Description: Advisory information provided

Resolution: N/A

Chapter 16 SOAP Palette

This chapter describes error codes that can be returned by activities in the SOAP palette.

Topics

- SOAP Error Codes, page 218

SOAP Error Codes

SOAPPLUGIN-100001: Unable to create Transport

Role: errorRole

Category: BW_Plugins

Description: Error initializing the transport

Resolution: Please check the transport configuration

SOAPPLUGIN-100002: SOAP Envelope is invalid

Role: errorRole

Category: BW_Plugins

Description: The request or response enevelope received from the remote host is invalid

Resolution: Please verify the SOAP envelope

SOAPPLUGIN-100003: Unable to serialize the SOAP envelope

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please check the input data to this activity and the make sure that it is consistent with the WSDL description

---

SOAPPLUGIN-100004: Unable to deserialize the SOAP envelope

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please check the input data to this activity and the make sure that it is consistent with the WSDL description

---

SOAPPLUGIN-100005: Unable to process the SOAP envelope

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please check the input data to this activity and the WSDL description

---

SOAPPLUGIN-100006: The SOAP processor could not be instantiated

Role: errorRole

Category: BW_Plugins

Description: This is an internal error

Resolution: Please contact TIBCO support

SOAPPLUGIN-100007: The SOAP service is invalid

Role: errorRole

Category: BW_Plugins

Description: This is an internal error

Resolution: Please contact TIBCO support

SOAPPLUGIN-100008: SOAP Envelope has no data

Role: errorRole

Category: BW_Plugins

Description: The request or response message received from the remote server is invalid

Resolution: Please make sure the endpoint is a valid soap 1.1 server

---

SOAPPLUGIN-100009: Error parsing SOAP message

Role: errorRole

Category: BW_Plugins

Description: The request or response message received from the remote server is invalid

Resolution: Please make sure the endpoint is a valid soap 1.1 server

---

SOAPPLUGIN-100010: Error while adding xsi:type attribute

Role: errorRole

Category: BW_Plugins

Description: Internal error

Resolution: Please make sure that you are using the supported schema flavor

---

SOAPPLUGIN-100011: Part accessor for the message-part not found in the soap envelope

Role: errorRole

Category: BW_Plugins

Description: The request or response message received from the remote server is invalid

Resolution: Please check the input data to this activity and the make sure that it is consistent with the WSDL description

---

SOAPPLUGIN-100012: Unable to send soap reply message

Role: errorRole

Category: BW_Plugins

Description: The remote server may have closed the connection or there is an internal exception

Resolution: Please correct the connection error

SOAPPLUGIN-100014: Unable to send reply or fault message. Please check the operation type

Role: errorRole

Category: BW_Plugins

Description: The specified operation may not throw a soap fault or send soap reply

Resolution: Please make sure that you have an operation which allows reply and fault messages

---

SOAPPLUGIN-100016: Unable to convert a soap fault message to activity output

Role: errorRole

Category: BW_Plugins

Description: This is an internal error occurs when the soap request activity is not initialized

Resolution: Please contact TIBCO support

SOAPPLUGIN-100017: Unable to initialize the URL resolvers for builtin services

Role: errorRole

Category: BW_Plugins

Description: This is an internal error

Resolution: Please contact TIBCO support

SOAPPLUGIN-100018: Unable to get the specified resource

Role: errorRole

Category: BW_Plugins

Description: The resource URL or filter may be invalid or there is no resolver for the kind of URL specified

Resolution: Please specify the correct URL

SOAPPLUGIN-100019: A security error while trying to load the certficiate [%1]

Role: errorRole

Category: BW_Plugins

Description: The certificate path may be invalid or the certificate type is unsupported

Resolution: Please specify the correct path

SOAPPLUGIN-100020: An IO error occurred while trying to load the certificate [%1]

Role: errorRole

Category: BW_Plugins

Description: The certificate path may be invalid or the certificate type is unsupported

Resolution: Please specify the correct path

SOAPPLUGIN-100021: An IO error while trying send soap message [%1]

Role: errorRole

Category: BW_Plugins

Description: SOAP Driver could not send the message

Resolution: Please make sure that you have specified the correct endpoint infomation

---

SOAPPLUGIN-100022: An IO error while loading client key [%1]

Role: errorRole

Category: BW_Plugins

Description: The client key path may be invalid or the KEY type is unsupported

Resolution: Please specify the correct path

SOAPPLUGIN-100023: Soap fault message is received

Role: errorRole

Category: BW_Plugins

Description: Fault Details element provides more informaiton

Resolution: Remote server has responded with a soap fault message, it is usually thrown when the input data is invalid or soap server doesn't support the version of the saop message or mandatory soap headers are not specified

---

SOAPPLUGIN-100024: HTTP error [%1] Message Received

Role: errorRole

Category: BW_Plugins

Description: Please refer to the HTTP specifications for more information about the error code

Resolution:

SOAPPLUGIN-100025: Input data error. Resource path [%1] is invalid

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please correct the resource path in the retrieve resources activity

---

SOAPPLUGIN-100026: Input data error. Resource filter [%1] is invalid

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify the correct resource filter wsdl, wsil or xsd

---

SOAPPLUGIN-100027: Message part accessor not found in part [%1]

Role: errorRole

Category: BW_Plugins

Description: The request or response message received from the remote server is invalid

Resolution: Please check the input data to this activity and the make sure that it is consistent with the WSDL description

---

SOAPPLUGIN-100028: Data not found for resource [%1] using filter [%2]

Role: errorRole

Category: BW_Plugins

Description: The supported filters are wsdl, wsil or xsd. For other filters resourceData may not available as ascii

Resolution: Please correct the resource path in the retrieve resources activity

---

SOAPPLUGIN-100032: Duplicate soapAction value [%1]

Role: errorRole

Category: BW_Plugins

Description: The soapAction value must be unique accross all Soap Event Sources to correctly dispatch the soap messages

Resolution: Please check other SOAP Event Source activities and make sure that the soapAction is not duplicated

---

SOAPPLUGIN-100033: Duplicate WSDL Target Namespace value [%1]

Role: errorRole

Category: BW_Plugins

Description: The Target Namespace specified on advanced tab must be unique accross all Soap Event Sources

Resolution: Please check other SOAP Event Source activities and make sure that the Target Namespace is not duplicated

---

SOAPPLUGIN-100034: Configuration Error. The specified operation name [%1] not found in portType [%2]

Role: errorRole

Category: BW_Plugins

Description: The operation name is invalid

Resolution: Please ensure that the WSDL file has the specified operation name

---

SOAPPLUGIN-100035: Configuration Error. Transport is not specified for this service

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify a HTTP or HTTPS transport using HTTP Connection resource

---

SOAPPLUGIN-100036: Configuration Error. SoapAction is not specified for this service

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify a non null SoapAction

SOAPPLUGIN-100037: Configuration Error. Operation style is invalid

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify document or rpc

SOAPPLUGIN-100038: Configuration Error. Use attribute is invalid

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify literal or encoded

SOAPPLUGIN-100039: Configuration Error. The specified operation name [%1] not found in port [%2] in service [%3]

Role: errorRole

Category: BW_Plugins

Description: The operation name is invalid

Resolution: Please ensure that the WSDL file has the specified operation name

---

SOAPPLUGIN-100040: Configuration Error. The message part [%1] is defined using 'element' attribute instead of 'type'

Role: errorRole

Category: BW_Plugins

Description: Soap encoding rules require the message part to be defined with type attribute

Resolution: Please modify the WSDL message definition to use schema type

---

SOAPPLUGIN-100041: Configuration Error. Only one message part can be defined using 'type' attribute for document style services in literal encoding

Role: errorRole

Category: BW_Plugins

Description: Document Literal encoding rules require only one message part to be defined with type attribute

Resolution: Please modify the WSDL message definition

SOAPPLUGIN-100042: Configuration Error. All Parts must be defined using either 'type' or 'element'

Role: errorRole

Category: BW_Plugins

Description: Mixing type and element attributes for the message parts is not permitted

Resolution: Please modify the WSDL message definition

SOAPPLUGIN-100043: Configuration Error. Multiple %1 parts defined using same name are not supported

Role: errorRole

Category: BW_Plugins

Description: Local names for two or more parts is same

Resolution: Please modify the headers configuration

SOAPPLUGIN-100044: Runtime error in SOAP service: %1

Role: errorRole

Category: BW_Plugins

Description: This is an internal error

Resolution: Please contact TIBCO support

SOAPPLUGIN-100045: Runtime error in SOAP client: %1

Role: errorRole

Category: BW_Plugins

Description: This is an internal error

Resolution: Please contact TIBCO support

SOAPPLUGIN-100046: Unable to serialize the MIME envelope. Please make sure that mimePart content (binaryContent|textContent|fileName) is consistent with content-type

Role: errorRole

Category: BW_Plugins

Description: Unable to serialize the MIME envelope. Please make sure that mimePart content (binaryContent | textContent | fileName) is consistent with content-type

Resolution: Please make sure that mimePart content (binaryContent | textContent | fileName) is consistent with content-type

---

SOAPPLUGIN-100047: Unable to dispatch the SOAP message to a Service. The URL/SoapAction specified in the incoming message was invalid.

Role: errorRole

Category: BW_Plugins

Description: Unable to dispatch the SOAP message to a Service. The URL/SoapAction specified in the incoming message was invalid.

Resolution: Please make sure that the client is using an up to date WSDL file

---

SOAPPLUGIN-100048: An exception with the following message was thrown while deserializing/processing the incoming SOAP message: [% 1]

Role: errorRole

Category: BW_Plugins

Description: An exception was thrown while deserializing/processing the incoming SOAP message.

Resolution: Please make sure that the client is using an up to date WSDL file

---

SOAPPLUGIN-100049: The system cannot find the file specified

Role: errorRole

Category: BW_Plugins

Description: The system cannot find the file specified

Resolution: Please make sure that the specified file exists on the system

---

SOAPPLUGIN-100501: A java exception has occured. [%1]

Role: errorRole

Category: BW_Plugins

Description: The configuration or input data of the activity might have caused this error

Resolution: Please correct the errors

SOAPPLUGIN-100502: Illegal Argument exception has occured. [%1]

Role: errorRole

Category: BW_Plugins

Description: The configuration or input data of the activity might have caused this error

Resolution: Please correct the errors

SOAPPLUGIN-100503: A java exception has occured while constructing the WSDL file. [%1]

Role: errorRole

Category: BW_Plugins

Description: The configuration or input data of the activity might have caused this error

Resolution: Please correct the errors

SOAPPLUGIN-100504: IO exception has occured. [%1]

Role: errorRole

Category: BW_Plugins

Description: The configuration or input data of the activity might have caused this error

Resolution: Please correct the errors

SOAPPLUGIN-100505: Unable to create WSDL file due to insufficient configuration

Role: errorRole

Category: BW_Plugins

Description: Provide values for all the mandatroty configuration fields marked in the bold font

Resolution: Please correct the errors

Chapter 17 TCP Palette

This chapter describes error codes that can be returned by activities in the TCP palette.

Topics

- TCP Error Codes, page 232

TCP Error Codes

BW-TCP-100001: Cannot start TCP Receiver on Host '%1', Port '%2'. Reason: %3

Role: errorRole

Category: BW_Plugin

Description: Cannot create Server Socket on %1:%2. Reason: %3

Resolution: Please correct the error and retry.

BW-TCP-100002: 'TCP connection' field is required.

Role: errorRole

Category: BW_Plugin

Description: 'TCP connection' field is required.

Resolution: Please correct the error and retry.

BW-TCP-100003: Invalid Port; port must be numeric. Error: %1

Role: errorRole

Category: BW_Plugin

Description: Invalid Port; port must be numeric. Error: %1

Resolution: Please correct the error and retry.

BW-TCP-100004: No value specified for the 'data' input field.

Role: errorRole

Category: BW_Plugin

Description: No value specified for the 'data' input field.

Resolution: Please correct the error and retry.

BW-TCP-100005: Cannot process TCP request. Reason: %1

Role: errorRole

Category: BW_Plugin

Description: Cannot process TCP request. Reason: %1

Resolution: Please correct the error and retry.

BW-TCP-100006: Error reading TCP data. Reason: %1

Role: errorRole

Category: BW_Plugin

Description: Error reading TCP data. Reason: %1

Resolution: Please correct the error and retry.

BW-TCP-100007: Unknown separator type: %1.

Role: errorRole

Category: BW_Plugin

Description: Unknown separator type: %1.

Resolution: Please correct the error and retry.

BW-TCP-100008: Error opening TCP Connection. Reason: %1.

Role: errorRole

Category: BW_Plugin

Description: Error opening TCP Connection. Reason: %1.

Resolution: Please correct the error and retry.

BW-TCP-100009: Error opening TCP Connection. Reason: Host '%1' unknown

Role: errorRole

Category: BW_Plugin

Description: Error opening TCP Connection. Reason: Host '%1' unknown

Resolution: Please correct the error and retry.

BW-TCP-100010: Error reading data. Reason: Bytes to read can not be zero

Role: errorRole

Category: BW_Plugin

Description: Error reading data. Reason: Bytes to read can not be zero

Resolution: Please correct the error and retry.

BW-TCP-100011: Error reading data. Reason: Stream has no data, end of stream reached.

Role: errorRole

Category: BW_Plugin

Description: Error reading data. Reason: Stream has no data, end of stream reached.

Resolution: Please correct the error and retry.

BW-TCP-100012: Exception reading data. Separator '%1' not found in data after reading %2 bytes. Reason: %3

Role: errorRole

Category: BW_Plugin

Description: Exception reading data. Separator '%1' not found in data after reading %2 bytes. Reason: %3

Resolution: Please correct the error and retry.

BW-TCP-100013: Exception closing TCP Connection. Reason: %1

Role: errorRole

Category: BW_Plugin

Description: Exception closing TCP Connection. Reason: %1

Resolution: Please correct the error and retry.

BW-TCP-100014: Could not read from TCP connection. The input connection is either invalid or closed.

Role: errorRole

Category: BW_Plugin

Description: Could not read from TCP connection. The input connection is either invalid or closed.

Resolution: Please correct the error and retry.

BW-TCP-100015: Could not write to TCP connection. The input connection is either invalid or closed.

Role: errorRole

Category: BW_Plugin

Description: Could not write to TCP connection. The input connection is either invalid or closed.

Resolution: Please correct the error and retry.

BW-TCP-100016: Can not start TCP Receiver on Host='%1',Port='%2'. Another TCP Receiver is already running with the same configuration.

Role: errorRole

Category: BW_Plugin

Description: Can not start TCP Receiver on Host='%1',Port='%2'. Another TCP Receiver is already running with the same configuration.

Resolution: Please correct the error and retry.

BW-TCP-100017: Error closing TCP connection. Reason: No connection is available which matches the input connection key

Role: errorRole

Category: BW_Plugin

Description: Error closing TCP connection. Reason: No connection is available which matches the input connection key

Resolution: Please correct the error and retry.

BW-TCP-100018: Error writing data. Reason: %1

Role: errorRole

Category: BW_Plugin

Description: Error writing data. Reason: %1

Resolution: Please correct the error and retry.

BW-TCP-100019: Error writing data. Reason: Bytes to write can not be zero

Role: errorRole

Category: BW_Plugin

Description: Error writing data. Reason: Bytes to write can not be zero

Resolution: Please correct the error and retry.

BW-TCP-100020: Error in configuring field '%1'. Pl. specify comma separated byte values e.g. "0x0A,0x05,0x0c". For valid string representation of byte values, refer to the Javadoc for decode(String nm) method of class java.lang.Byte

Role: errorRole

Category: BW_Plugin

Description: Error in configuring field '%1'. Pl. specify comma separated byte values e.g. "0x0A,0x05,0x0c". For valid string representation of byte values, refer to the Javadoc for decode(String nm) method of class java.lang.Byte

Resolution: Please correct the error and retry.

BW-TCP-100021: Timeout while reading TCP data

Role: errorRole

Category: BW_Plugin

Description: Timeout while reading TCP data

Resolution: Please correct the error and retry.

Chapter 18 Transaction Palette

This chapter describes error codes that can be returned by activities in the Transaction palette.

Topics

- Transaction Error Codes, page 240

Transaction Error Codes

BW-TRANS-100001: Initialization Error. %1

Role: errorRole

Category: BW_Plugin

Description:

Resolution:

BW-TRANS-100002: Get transaction status error. %1

Role: errorRole

Category: BW_Plugin

Description: Exception occurred while trying to obtain the status of the transaction from the transaction manager.

Resolution:

BW-TRANS-100003: Transaction setRollbackOnly error. %1

Role: errorRole

Category: BW_Plugin

Description: Exception occurred while trying to mark the transaction for rollback only

Resolution:

BW-TRANS-100004: Unable to obtain the status of the transaction. Exception [%1] occurred. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred while trying to obtain the status of the transaction.

Resolution:

BW-TRANS-100005: Unable to set the transaction for rollback only. Exception [%1] occurred. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred while trying to set the transaction for rollback only

Resolution:

BW-TRANS-400000: %1

Role: debugRole

Category: BW_Plugin

Description: Debug Trace Message

Resolution: None

BW-JTATM-100001: Transaction Manager Initialization Error. %1

Role: errorRole

Category: BW_Plugin

Description:

Resolution:

BW-JTATM-100002: Unable to obtain the status of the transaction. The method 'UserTransaction.getStatus' raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method 'javax.transaction.UserTransaction.getStatus()'.

Resolution:

BW-JTATM-100003: Unable to set the transaction for rollback only. The method 'UserTransaction.setRollbackOnly' raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method 'javax.transaction.UserTransaction.setRollbackOnly()'.

Resolution:

BW-JTATM-100004: Transaction begin error. The method 'UserTransaction.begin' raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method 'javax.transaction.UserTransaction.begin()'

Resolution: Please correct the error stated in the exception message and retry

---

BW-JTATM-100005: Transaction commit error. The method 'UserTransaction.commit' raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method 'javax.transaction.UserTransaction.commit()'

Resolution: Please correct the error stated in the exception message and retry

---

BW-JTATM-100006: Transaction rollback error. The method 'UserTransaction.rollback' raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method 'javax.transaction.UserTransaction.rollback()'

Resolution: Please correct the error stated in the exception message and retry

---

BW-JTATM-100007: Unable to set timeout for transaction. The method 'UserTransaction.setTransactionTimeout' raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method 'javax.transaction.UserTransaction.setTransactionTimeout()'

Resolution: Please correct the error stated in the exception message and retry

---

BW-JTATM-100008: Unable resume the transaction. The method 'resume' of the JTATM raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method 'resume'.

Resolution:

BW-JTATM-100009: Unable suspend the transaction. The method 'suspend' of the JTATM raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method 'suspend'.

Resolution:

BW-JTATM-100010: XAResource registration error. The method 'registerResource' of the JTATM raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred when trying register XAResource with the Transaction Manager

Resolution:

BW-JTATM-100011: Unable to enlist XAResource with the transaction object. The method 'enlistResource' of the JTATM raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred when trying enlist XAResource with the transaction object

Resolution:

BW-JTATM-100012: Unable to delist XAResource from the transaction object. The method 'delistResource' of the JTATM raised exception [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred when trying delist XAResource from the transaction context

Resolution:

BW-JTATM-100013: The JTA UserTransaction Configuration reference [%1] specified for the Transaction Group contains incorrect field values.

Role: errorRole

Category: BW_Plugin

Description: The JTA UserTransaction Configuration activity referenced by this Transaction group contains invalid field values.

Resolution: Please correct the error and retry.

BW-JTATM-100014: Connection Test Failed. %1

Role: errorRole

Category: BW_Plugin

Description: Unable to establish connection to the server.

Resolution: Please correct the error stated in the exception message and retry.

BW-JTATM-100015: Connection Test Failed. Exception [%1] occurred.

Role: errorRole

Category: BW_Plugin

Description: Unable to establish connection to the server. Exception occurred

Resolution: Please correct the error stated in the exception message and retry.

BW-JTATM-100016: Java class [%1] not found in the classpath. ClassNotFoundException occurred. %2

Role: errorRole

Category: BW_Plugin

Description: ClassNotFoundException occurred while trying to access the specified Java class.

Resolution: Please verify that the specified class file is contained in the classpath.

BW-JTATM-100017: Error occurred while trying to obtain the JNDI Configuration shared resource reference [%1]: %2

Role: errorRole

Category: BW_Plugin

Description: Unable to get the shared JNDI Configuration resource referenced by the JTA UserTransaction Configuration

Resolution: Please correct the error and retry.

BW-JTATM-100018: Unable to create an instance of 'javax.naming.InitialContext'. NamingException occurred. %1

Role: errorRole

Category: BW_Plugin

Description: Exception of type 'javax.naming.NamingException' occurred while trying to construct an instance of 'javax.naming.InitialContext'.

Resolution: Please correct the specified NamingException and retry.

BW-JTATM-100019: Unable to create an instance of 'javax.naming.InitialContext'. Exception [%1] occurred. %2

Role: errorRole

Category: BW_Plugin

Description: Exception occurred while trying to construct an instance of 'javax.naming.InitialContext'.

Resolution: Please correct the error stated in the exception message and retry.

BW-JTATM-100020: Unable to obtain UserTransaction object for the JNDI name [%1]. NamingException occurred. %2

Role: errorRole

Category: BW_Plugin

Description: Exception of type 'javax.naming.NamingException' occurred on invocation of the method 'javax.naming.InitialContext.lookup(..)'

Resolution: Please correct the specified NamingException and retry.

BW-JTATM-100021: Unable to obtain the UserTransaction object for the JNDI name [%1]. Exception [%2] occurred. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method 'javax.naming.InitialContext.lookup(..)'

Resolution: Please correct the specified NamingException and retry.

BW-JTATM-400000: %1

Role: debugRole

Category: BW_Plugin

Description: Debug Trace Message

Resolution: None

BW-XATM-100001: Transaction Manager Initialization Error. The method 'init' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description:

Resolution:

BW-XATM-100002: Unable to obtain the status of the transaction. The method 'getStatus' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the Transaction Manager's getStatus method

Resolution:

BW-XATM-100003: Unable to set the transaction for rollback only. The method 'setRollbackOnly' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the Transaction Manager's setRollbackOnly method.

Resolution:

BW-XATM-100004: Transaction begin error. The method 'begin' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the Transaction Manager's begin method

Resolution: Please correct the error stated in the exception message and retry

---

BW-XATM-100005: Transaction commit error. The method 'commit' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the Transaction Manager's commit method

Resolution: Please correct the error stated in the exception message and retry

---

BW-XATM-100006: Transaction rollback error. The method 'rollback' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the TransactionManager's rollback method

Resolution: Please correct the error stated in the exception message and retry

---

BW-XATM-100007: Unable to set timeout for transaction. The method 'setTransactionTimeout' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the Transaction Manager's setTransactionTimeout method

Resolution: Please correct the error stated in the exception message and retry

---

BW-XATM-100008: Unable resume the transaction. The method 'resume' of the [%1] Transaction Manager's exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the TransactionManager's resume method

Resolution:

BW-XATM-100009: Unable suspend the transaction. The method 'suspend' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the Transaction Manager's suspend method

Resolution:

BW-XATM-100010: XAResource registration error. The method 'registerResource' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred when trying register XAResource with the Transaction Manager

Resolution:

BW-XATM-100011: Unable to enlist XAResource with the transaction object. The method 'enlistResource' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred when trying enlist XAResource with the transaction object

Resolution:

BW-XATM-100012: Unable to delist XAResource from the transaction object. The method 'delistResource' of the [%1] Transaction Manager raised exception [%2]. %3

Role: errorRole

Category: BW_Plugin

Description: Exception occurred when trying delist XAResource from the transaction object

Resolution:

BW-XATM-100013: The XA TransactionManager Configuration reference [%1] specified for the Transaction Group contains incorrect field values.

Role: errorRole

Category: BW_Plugin

Description: The XA TransactionManager Configuration activity referenced by this Transaction group contains invalid field values.

Resolution: Please correct the error and retry.

BW-XATM-100014: The XA TransactionManager Configuration reference [%1] not found

Role: errorRole

Category: BW_Plugin

Description: Unable to obtain the specified XA TransactionManager Configuration shared resource reference

Resolution: Please correct the error and retry.

BW-XATM-100015: The XA TransactionManager Configuration reference [%1] not found in repository

Role: errorRole

Category: BW_Plugin

Description: The repository does not contain the specified XA TransactionManager Configuration shared resource reference

Resolution: Please correct the error and retry.

BW-XATM-100016: Exception occurred while trying to obtain the XA TransactionManager Configuration reference [%1]: %2

Role: errorRole

Category: BW_Plugin

Description: Unable to obtain the XA TransactionManager Configuration shared resource reference

Resolution: Please correct the error and retry.

BW-XATM-100017: Method [%1] of the [%2] Transaction Manager raised exception [%3]. %4

Role: errorRole

Category: BW_Plugin

Description: Exception occurred on invocation of the method of the Transaction Manager

Resolution: Please correct the error stated in the exception message and retry

---

BW-XATM-100018: Invalid [%1] Transaction Manager reference (XATransactionManager.m_tm == null).

Role: errorRole

Category: BW_Plugin

Description: XA Transaction Manager reference contains invalid value.

Resolution: Make sure the method "XATransactionManager.setTransactionManager" is called after constructing the custom TransactionManager in the method "XATransactionManager.init".

BW-XATM-100019: ClassNotFoundException occurred during initialization of the [%1] transaction manager. The classpath does not contain the required [%2] transaction manager's class or jar files. %3

Role: errorRole

Category: BW_Plugin

Description: ClassNotFoundException occurred while trying to access the transaction manager's Java class.

Resolution: Please verify that the required transaction manger's java jar or class file is contained in the classpath.

BW-XATM-300001: %1 object store directory: %2

Role: infoRole

Category: BW_Plugin

Description: Location of the transaction manager object store directory

Resolution:

BW-XATM-400000: %1

Role: debugRole

Category: BW_Plugin

Description: Debug Trace Message

Resolution: None

Chapter 19 XML Activities Palette

This chapter describes error codes that can be returned by activities in the XML Activities palette.

Topics

- XML Error Codes, page 256

XML Error Codes

BW-XML-000000: Internal error occurred. Class=%1, Method=%2, Reason=%3

Role: errorRole

Category: BW_Plugin

Description: Internal error occurred

Resolution: Please Contact TIBCO Support

BW-XML-100001: Activity configuration error. %1

Role: errorRole

Category: BW_Plugin

Description: This activity is not configured correctly

Resolution: Please correct the error and retry.

BW-XML-100002: Unable to get value for the global variable [%1]. %2

Role: errorRole

Category: BW_Plugin

Description: Unable to get value for the specified global variable

Resolution: Make sure that the specified global variable is defined.

BW-XML-100003: Invalid global variable. The global variable [%1] may not have been defined.

Role: errorRole

Category: BW_Plugin

Description: Unable to get value for the specified global variable

Resolution: Make sure that the specified global variable is defined.

BW-XML-100004: An error occurred while serializing the XML: %1

Role: errorRole

Category: BW_Plugin

Description: An error occuring while serializing the XML.

Resolution: Please correct.

BW-XML-100005: An error occurred while parsing: %1.

Role: errorRole

Category: BW_Plugin

Description: Error occurred while parsing.

Resolution: Examine input for validity..

BW-XML-100006: The [%1] occurred during XSLT transformation: %2

Role: errorRole

Category: BW_Plugin

Description: Error occurred during XSLT transformation.

Resolution: Examine input for validity..

BW-XML-100007: No stylesheet for XSLT transformation

Role: errorRole

Category: BW_Plugin

Description: No stylesheet for XSLT transformation

Resolution: Examine input for validity..

BW-XML-100008: The selected encoding [%1] is not valid.

Role: errorRole

Category: BW_Plugin

Description: The selected encoding is invalid.

Resolution: Please use a valid encoding.

BW-XML-100009: Encoding error occurred: %1.

Role: errorRole

Category: BW_Plugin

Description: Error occurred while encoding.

Resolution: Please ensure that selected encoding is legal.

BW-XML-100010: The encoded bytes content is empty.

Role: errorRole

Category: BW_Plugin

Description: Content cannot be empty.

Resolution: Please ensure that the content is not empty.

BW-XML-100011: [%1]

Role: errorRole

Category: BW_Plugin

Description: ?.

Resolution: ?

BW-XML-100012: The input document's root element [%1] does not match the desired output's root element [%2].

Role: errorRole

Category: BW_Plugin

Description: The output type doesn't match the root of the input document.

Resolution: Either modify the incoming document or change the output mapping to accurately reflect that docuement's contents.

BW-XML-100501: Using the old XML render code

Role: infoRole

Category: BW_Plugin

Description: Using the old XML render code

Resolution:

BW-XML-100502: Using the optimized XML render code

Role: infoRole

Category: BW_Plugin

Description: Using the optimized XML render code

Resolution: