



TIBCO ActiveMatrix BusinessWorks™

Error Codes

Version 5.16.1 | February 2025

Contents

Contents	2
Process Engine Error Codes	4
Common Error Codes	36
XPath Error Codes	59
ActiveEnterprise Adapter Error Codes	81
File Error Codes	89
FTP Error Codes	94
General Activities Error Codes	101
HTTP Error Codes	107
Java Error Codes	121
JDBC Error Codes	140
JMS Error Codes	151
Mail Error Codes	168
Manual Work Error Codes	177
Parse Error Codes	185
TIBCO Rendezvous Error Codes	189
SOAP Error Codes	196

TCP Error Codes	209
Transaction Error Codes	215
XML Error Codes	229
TIBCO Product Documentation and Support Services	233
Legal and Third-Party Notices	236

Process Engine Error Codes

This section lists error codes returned by the TIBCO ActiveMatrix BusinessWorks™ process engine.

BWENGINE-100001: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Used for logging generic exception, detailed message code not provided.
- **Resolution:** Depends on content of exception.

BWENGINE-100002: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Used when underlying support reported an error.
- **Resolution:** Depends on content of exception.

BWENGINE-100003: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Used for startup failures.
- **Resolution:** Depends on failure details.

BWENGINE-100004: %1

- **Role:** errorRole
- **Category:** BW-Core

- **Description:** Used for shutdown failures.
- **Resolution:** Depends on failure details.

BWENGINE-100005: Load Error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Error loading project.
- **Resolution:** Depends on failure details.

BWENGINE-100006: Load Error: ref=%1, class=%2

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Error loading project.
- **Resolution:** Depends on failure details.

BWENGINE-100007: UseSeparateThread may only be called from within the init() method

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** UseSeparateThread may only be called from within the init() method.
- **Resolution:** Correct activity code.

BWENGINE-100008: Cannot find specified Engine.Database.Configuration: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Cannot find specified Engine.Database.Configuration.
- **Resolution:** Re-deploy specifying correct database shared configuration.

BWENGINE-100009: Access error for Engine.Database.Configuration: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Access error for Engine.Database.Configuration
- **Resolution:**

BWENGINE-100010: Plugin agent class name not specified

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Plugin agent class name not specified.
- **Resolution:** Correct plugin definition file.

BWENGINE-100011: Error processing plugin agent [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Error processing plugin agent.
- **Resolution:**

BWENGINE-100012: Initialization error in [%1/%2]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The activity init method detected an error.
- **Resolution:** Depends on content of "caused by" exception.

BWENGINE-100013: Termination error in [%1/%2]

- **Role:** errorRole
- **Category:** BW-Core

- **Description:** The activity destroy method detected an error.
- **Resolution:** Depends on content of "caused by" exception.

BWENGINE-100014: process initialization failed for %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The specified process definition could not be initialized. It is unavailable for use.
- **Resolution:** Depends on content of "caused by" exception.

BWENGINE-100015: Could not find process definition: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The specified process definition could not found.
- **Resolution:** Process loading may have failed or process loading may not have been requested or may be using incorrect process reference.

BWENGINE-100016: failed to spawn called process

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The Call Process activity, spawn option, failed.
- **Resolution:**

BWENGINE-100017: failed to execute called process

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The Call Process activity failed to execute called process.
- **Resolution:**

BWENGINE-100018: Process definition name not specified

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Process name is required, but has not been specified.
- **Resolution:** Enter required item.

BWENGINE-100019: Can not checkpoint in middle of transaction

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** A checkpoint may not occur within a transaction group.
- **Resolution:** Correct process design.

BWENGINE-100020: Activation error with process starter [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Activation error with a process starter.
- **Resolution:** Depends on content of exception.

BWENGINE-100021: Checkpoint failed

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Checkpoint attempt failed.
- **Resolution:** Depends on content of exception.

BWENGINE-100022: Error restarting process %1 from checkpoint

- **Role:** errorRole
- **Category:** BW-Core

- **Description:** Error trying to restart process from checkpoint.
- **Resolution:** Depends on content of exception. May be that checkpoint was taken on a different version of ActiveMatrix BusinessWorks™.

BWENGINE-100023: Error restarting checkpoint, process definition not found: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not find the process definition needed by the checkpointed process.
- **Resolution:** Make sure same processes are deployed when restarting engine as when checkpoint was taken.

BWENGINE-100024: %1 Unable to delete checkpoint

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Failed to delete checkpoint.
- **Resolution:** Depends on content of exception. If checkpoint not deleted, job could be restarted on next engine startup.

BWENGINE-100025: Failed to get next job id block

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not get the next block of job ids.
- **Resolution:** Depends on content of exception.

BWENGINE-100026: Error with fault tolerant setup

- **Role:** errorRole
- **Category:** BW-Core

- **Description:** Error with fault tolerant setup. Engine will not start.
- **Resolution:** Depends on content of exception.

BWENGINE-100027: Notify error: group = %1, key = %2

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Notify unable to complete wakeup of waiting entity.
- **Resolution:** Depends on content of exception.

BWENGINE-100028: Deactivation error with process starter [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Deactivation error with a process starter.
- **Resolution:** Depends on content of exception.

BWENGINE-100029: Activity timed out

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Activity did not complete execution within the specified time limit.
- **Resolution:**

BWENGINE-100030: Input data invalid

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Activity input data validation error.
- **Resolution:**

BWENGINE-100031: Output data invalid

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Activity output data validation error.
- **Resolution:**

BWENGINE-100032: Error output data invalid

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Activity error output data validation error.
- **Resolution:**

BWENGINE-100033: Activity providing output data but none is expected

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Activity has output when none was expected.
- **Resolution:**

BWENGINE-100034: Transition cycle detected in [%1/%2]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** This process contains an illegal transition cycle.
- **Resolution:** This process does not allow transition cycles.

BWENGINE-100035: Error on exit from activity, no matching transition

- **Role:** errorRole
- **Category:** BW-Core

- **Description:** No transition out of activity evaluated true. This generates an Error condition.
- **Resolution:** Add transition or check conditions of existing transitions.

BWENGINE-100036: Error on exit from activity, too many matching transitions

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Multiple transitions may not be taken when transition cycles are allowed.
- **Resolution:** This process allows transition cycles and does not allow two transitions from any activity to be true at the same time.

BWENGINE-100037: Repository not found: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not locate specified repository.
- **Resolution:** Make sure using correct reference and server is available.

BWENGINE-100038: Repository not specified

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** No repository location specified.
- **Resolution:** Specify location of repository.

BWENGINE-100039: Variable name not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Variable name to set has not been specified.

- **Resolution:** Specify variable name in configuration panel.

BWENGINE-100040: Undefined variable [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Unable to find definition for specified variable.
- **Resolution:** Please look at exception for more details.

BWENGINE-100041: Mapping Error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Problem found with mapping.
- **Resolution:** Please look at mapping for more details.

BWENGINE-100042: Configured Fault not found [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not find the specified fault name.
- **Resolution:**

BWENGINE-100043: Error resolving Fault [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Error encountered resolving specified fault name.
- **Resolution:**

BWENGINE-100044: File not found [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not find specified file name.
- **Resolution:**

BWENGINE-100045: Pager can not load [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not load the page file for the specified job.
- **Resolution:**

BWENGINE-100046: Shutdown due to startup error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Engine shutdown due to startup error.
- **Resolution:**

BWENGINE-100047: %1 Error in [%2/%3]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

BWENGINE-100048: Error in [%1/%2]

- **Role:** errorRole
- **Category:** BW-Core

- **Description:**
- **Resolution:**

BWENGINE-100049: Error restarting [%1], can not acquire lock [%2]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Error trying to restart process from checkpoint.
- **Resolution:** Process requires lock that is already acquired.

BWENGINE-100050: Activation error with plugin agent [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Activation error with plugin agent.
- **Resolution:** Depends on content of exception.

BWENGINE-100051: Unable to create trace object

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Unable to create trace object.
- **Resolution:** Depends on content of exception.

BWENGINE-100052: Configuration error on input type for [%1]: %2

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not load process input type.
- **Resolution:** Depends on content of details.

BWENGINE-100053: Configuration error on output type for [%1]: %2

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not load process output type.
- **Resolution:** Depends on content of details.

BWENGINE-100054: Configuration error on error output type for [%1]: %2

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not load process error output type.
- **Resolution:** Depends on content of details.

BWENGINE-100055: Configuration error on user process variables for [%1]: %2

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not load user process variable types.
- **Resolution:** Depends on content of details.

BWENGINE-100056: Loop index slot name already used: [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Loop index slot name already used.
- **Resolution:** Index variable name already taken. Specify another name not already in use.

BWENGINE-100057: Invalid loop index slot name: [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Invalid loop index slot name.
- **Resolution:** Specify a valid variable name.

BWENGINE-100058: Accumulate output variable name already used: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Accumulate output variable name already used.
- **Resolution:** Accumulate variable name already taken. Specify another name not already in use.

BWENGINE-100059: Invalid accumulate output variable name: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Invalid accumulate output variable name.
- **Resolution:** Specify a valid variable name.

BWENGINE-100060: No output to accumulate from activity: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** No output to accumulate from activity.
- **Resolution:** Can only accumulate output from an activity that has output.

BWENGINE-100061: Bad activity name for accumulate output: %1

- **Role:** errorRole
- **Category:** BW-Core

- **Description:** Bad activity name for accumulate output.
- **Resolution:** Can only accumulate output from an activity within the group.

BWENGINE-100062: Slot name already used: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Slot name already used.
- **Resolution:** Slot name already used. Specify another name not already in use.

BWENGINE-100063: Process variable schema error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The schema for a process variable had an error.
- **Resolution:** Please look at the process variables tab for more information.

BWENGINE-100064: Process Start schema error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The Output schema for the process start had an error.
- **Resolution:** Please look at the Output Editor tab of the process start for more information.

BWENGINE-100065: Process End schema error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The Input schema for the process end had an error.
- **Resolution:** Please look at the Input Editor tab of the process end for more information.

BWENGINE-100066: Process Fault schema error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** An process fault/error schema had an error.
- **Resolution:** Please look at the Error Schemas tab of the process end for more information.

BWENGINE-100067: Call process input failed validation

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The input data passed to the Call Process activity did not conform to the input of the called process.
- **Resolution:** Please check the input mappings for the Call Process activity.

BWENGINE-100068: Call process results failed validation

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The process that was called returned results that were not expected by the Call Process activity.
- **Resolution:** Please check the input mappings for the End activity in the process that was called.

BWENGINE-100069: The override process [%1] expects different input than the process the Call Process activity was modeled on [%2]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The Process Name Dynamic Override option pointed, at run time, to a process with different input than the model process used to configure the activity at design time.

- **Resolution:** Please check the Process Name Dynamic Override expression in the activity configuration.

BWENGINE-100070: The process [%1] is not a callable process

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The specified process is not a callable process (it has a process starter instead).
- **Resolution:** Please check the process names in the activity configuration.

BWENGINE-100071: Multi-engine shared variable or lock requires engine configured to use database

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Multi-engine shared variable or lock requires engine configured to use database.
- **Resolution:** Configure engine to use database.

BWENGINE-100072: Undefined reference [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Unable to find definition for specified reference.
- **Resolution:** Please look at exception for more details.

BWENGINE-100073: Unable to parse initial value

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Unable to parse initial value.
- **Resolution:** Correct error in definition of initial value.

BWENGINE-100074: Persistent storage error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Problem accessing persistent storage.
- **Resolution:** Please look at exception for more details.

BWENGINE-100075: Variable not set

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Variable not set and has no initial value.
- **Resolution:** Set variable before use or define initial value.

BWENGINE-100076: Shared variable schema error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The schema for a shared variable had an error.
- **Resolution:** Please look at exception for more details.

BWENGINE-100077: Error with Transaction Manager [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Error with the specified Transaction Manager.
- **Resolution:** Please look at exception for more details.

BWENGINE-100078: Transaction Manager not specified

- **Role:** errorRole
- **Category:** BW-Core

- **Description:** Transaction Manager not specified.
- **Resolution:** Specify transaction manager.

BWENGINE-100079: Duplicate key [%1] already used by job [%2]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Another job has already registered this key.
- **Resolution:**

BWENGINE-100080: Only one duplicate key allowed per job

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** This job has already registered another key.
- **Resolution:**

BWENGINE-100081: XA Resource not available from [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The specified event source did not provide an XA Resource.
- **Resolution:** Check event source configuration.

BWENGINE-100082: Event context from [%1] not found

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** The specified event source did not provide an event context.
- **Resolution:** Check event source configuration.

BWENGINE-100083: Checkpoint verify failed

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Attempt to verify checkpoint failed.
- **Resolution:** Depends on content of exception.

BWENGINE-100084: Transaction rollback error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Exception thrown during transaction rollback.
- **Resolution:** Depends on content of exception.

BWENGINE-100085: Configuration error, checkpoint can not join transaction

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Configuration error, checkpoint can not join transaction.
- **Resolution:** Correct the configuration.

BWENGINE-100086: Engine commands are not enabled

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Engine commands are not enabled so Engine Command activity can not be used.
- **Resolution:** Enable engine commands.

BWENGINE-100087: Error invoking engine command [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error invoking specified engine command.
- **Resolution:** Please look at exception for more details.

BWENGINE-100088: Library alias undefined [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Cannot resolve library alias.
- **Resolution:** Provide valid library path for this alias.

BWENGINE-100089: Library not found for alias [%1], path [%2]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Can not find library for specified alias.
- **Resolution:** Provide valid library path for this alias.

BWENGINE-100090: Invalid library file type for alias [%1], path [%2]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Library for this alias has invalid file type.
- **Resolution:** Provide valid library path for this alias.

BWENGINE-100091: Library error for alias [%1], path [%2]

- **Role:** errorRole
- **Category:** BW-Core

- **Description:** Library error for this alias.
- **Resolution:** Please look at exception for more details.

BWENGINE-100092: Can not checkpoint in middle of a critical section

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** A checkpoint may not occur within a critical section group.
- **Resolution:** Correct process design.

BWENGINE-100093: Required Lock object not specified

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** A multi-group critical section requires a lock object.
- **Resolution:** Configure a lock object.

BWENGINE-100094: Process id [%1] not found

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** No process found with matching process id.
- **Resolution:** Use existing process id.

BWENGINE-100095: Fault to catch has not been specified

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Specify fault or select all.
- **Resolution:**

BWENGINE-100096: Duplicate catch activities [%1] [%2]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** More than one catch activity with the same configuration.
- **Resolution:** Reconfigure catch activities so that they don't conflict with each other.

BWENGINE-100097: Can not create/access pager directory [%1]

- **Role:** errorRole
- **Category:** BW-Core
- **Description:** Problem encountered creating or accessing the pager directory.
- **Resolution:** Check available file space and permissions.

BWENGINE-100100: Transition condition XPath has an error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:** Please look at the transition for more details.

BWENGINE-100101: Loop over expression error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:** Please look at the group for more details.

BWENGINE-100102: Repeat condition expression error

- **Role:** errorRole
- **Category:** BW-Core

- **Description:**
- **Resolution:** Please look at the group for more details.

BWENGINE-100103: Error condition expression error

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:** Please look at the group for more details.

BWENGINE-100104: Variable [%1] has not been initialized

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Tried to use variable contents that has not been initialized.
- **Resolution:** Initialize variable before using contents.

BWENGINE-100105: Join failure exception

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Join condition false and join exception not suppressed.
- **Resolution:** May be desired result. If not, redesign process definition accordingly.

BWENGINE-100106: Join condition error

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Join condition XPATH expression has an error.
- **Resolution:** Correct join condition.

BWENGINE-200001: Partition [%1] not loaded

- **Role:** warnRole
- **Category:** BW-Core
- **Description:** Partition listed to load has not been loaded.
- **Resolution:**

BWENGINE-200002: No path from start to this point

- **Role:** warnRole
- **Category:** BW-Core
- **Description:** This point can not be reached.
- **Resolution:**

BWENGINE-200003: Mapping Warning

- **Role:** warnRole
- **Category:** BW-Core
- **Description:** Potential problem find with mapping.
- **Resolution:** Please look at mapping for more details.

BWENGINE-200004: Checkpoint not included with transaction

- **Role:** warnRole
- **Category:** BW-Core
- **Description:** Checkpoint taken before commit. Restart could happen before or after commit.
- **Resolution:** Reconfigure checkpoint database configuration.

BWENGINE-200005: Join condition warning

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Join condition XPATH expression has a warning.
- **Resolution:** Verify join condition.

BWENGINE-300001: Process Engine %1

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Process engine version.
- **Resolution:**

BWENGINE-300002: Engine %1 started

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Engine started.
- **Resolution:**

BWENGINE-300003: Engine %1 started in backup mode

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Indicates the named engine has been started FT backup mode.
- **Resolution:**

BWENGINE-300004: Engine %1 %2

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Fault Tolerant actions.
- **Resolution:**

BWENGINE-300006: Engine %1 terminating

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Engine terminating.
- **Resolution:**

BWENGINE-300007: Process Started

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** A new process has been started.
- **Resolution:**

BWENGINE-300008: Process started tracking=%1

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** A new process has been started with associated tracking info.
- **Resolution:**

BWENGINE-300009: BW Plugins: %1

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** BW plugins.jar version.
- **Resolution:**

BWENGINE-300010: XML Support: %1

- **Role:** infoRole
- **Category:** BW-Core

- **Description:** TIBCOXML version
- **Resolution:**

BWENGINE-300011: Java version: %1 %2

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Java VM name and version.
- **Resolution:**

BWENGINE-300012: OS version: %1 %2 %3

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** OS arch, name and version.
- **Resolution:**

BWENGINE-300013: Tibrv string encoding: %1

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Tibrv string encoding.
- **Resolution:**

BWENGINE-300014: Starting delayed shutdown, max-delay=[%1], wait-for-checkpoints=[%2]

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Processing delayed shutdown command.
- **Resolution:**

BWENGINE-300015: Statistics collection started, recording to [%1]

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Starting activity statistics collection and recording to specified file.
- **Resolution:**

BWENGINE-300016: Statistics collection stopped

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Stopping activity statistics collection and recording.
- **Resolution:**

BWENGINE-300017: Restarting [%1] for process [%2]

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Restarting process instance from checkpoint.
- **Resolution:**

BWENGINE-300018: Found [%1] checkpoint(s) to be restarted

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Shows number of checkpoints available to be restarted.
- **Resolution:**

BWENGINE-300019: Found [%1] checkpoint(s) auto restart NOT selected

- **Role:** infoRole
- **Category:** BW-Core

- **Description:** Shows number of checkpoints available, but not to be auto restarted.
- **Resolution:**

BWENGINE-300020: Found [%1] recoverable checkpoint(s) preserved after process faulted

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Shows number of checkpoints preserved after process terminated with a fault.
- **Resolution:**

BWENGINE-300021: Resource [%1] changed its state from [%2] to [%3].

- **Role:** infoRole
- **Category:** BW-Core
- **Description:** Resource state change information.
- **Resolution:**

BW-EXT-LOG-100000: %1

- **Role:** errorRole
- **Category:** LOG4J
- **Description:** Error message logged by third party application or java code using LOG4J api.
- **Resolution:** Refer to your third party application or java code.

BW-EXT-LOG-100001: %1

- **Role:** errorRole
- **Category:** LOG4J
- **Description:** Fatal error message logged by third party application or java code using

LOG4J api.

- **Resolution:** Refer to your third party application or java code.

BW-EXT-LOG-100002: Unable to write the message logged by third party application or java code to TIBCO BusinessWorks log file. %1

- **Role:** errorRole
- **Category:** LOG4J
- **Description:** Error occurred while trying to forward the message logged by third party application or java code to TIBCO BusinessWorks log file.
- **Resolution:**

BW-EXT-LOG-200000: %1

- **Role:** warnRole
- **Category:** LOG4J
- **Description:** Warning message logged by third party application or java code using LOG4J api.
- **Resolution:** Refer to your third party application or java code.

BW-EXT-LOG-300000: %1

- **Role:** infoRole
- **Category:** LOG4J
- **Description:** Info message logged by third party application or java code using LOG4J api.
- **Resolution:** Refer to your third party application or java code.

BW-EXT-LOG-300001: %1

- **Role:** infoRole
- **Category:** LOG4J
- **Description:** Message logged by third party application or java code using LOG4J

api.

- **Resolution:** Refer to your third party application or java code.

BW-EXT-LOG-300002: %1

- **Role:** debugRole
- **Category:** LOG4J
- **Description:** Debug message logged by third party application or java code using LOG4J api.
- **Resolution:** Refer to your third party application or java code.

Common Error Codes

Some error codes are common across activities within different palettes. This section describes these errors.

BW-COMMON-100001: Configuration error in field [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value.
- **Resolution:** Please update the configuration data.

BW-COMMON-100002: Configuration error in field [%1] expecting a valid [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the configuration data for the field with value of the indicated type.

BW-COMMON-100003: Configuration error in field [%1] expecting a value between [%2] and [%3]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the configuration data.

BW-COMMON-100004: Configuration error in field [%1] the value must be non empty

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the configuration data.

BW-COMMON-100005: Configuration error in field [%1] the value must be a valid [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the configuration data.

BW-COMMON-100006: Configuration error in field [%1] the value must be a valid URI

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid URI.
- **Resolution:** Please specify a valid URI.

BW-COMMON-100007: Configuration error in field [%1] the value must be a valid URL

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid URL.
- **Resolution:** Please specify a valid URL.

BW-COMMON-100008: Configuration error in field [%1] the value must be a valid hostname

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid hostname.
- **Resolution:** Please specify a valid hostname.

BW-COMMON-100009: Configuration error in field [%1] the value must be a valid port number

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid port number.
- **Resolution:** Please specify a valid port number.

BW-COMMON-100010: Configuration error in field [%1] the value must be a valid number

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid number.
- **Resolution:** Please specify a valid number.

BW-COMMON-100011: Configuration error in field [%1] the value must be a valid timeout value

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid timeout value.
- **Resolution:** Please specify a valid number between 1 and 32000.

BW-COMMON-100012: Configuration error in field [%1] the value must be a valid NCName

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid NCName type from XML specification.
- **Resolution:** Please specify a valid NCName.

BW-COMMON-100013: Configuration error in field [%1] the value must be a valid XPath expression

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid XPath expression.
- **Resolution:** Please specify a valid XPath.

BW-COMMON-100014: Configuration error in field [%1] the value must be a valid java classname

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid Class name.
- **Resolution:** Please specify a valid Java Class name.

BW-COMMON-100015: Configuration error in field [%1] the value must be a valid file name

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid file name.
- **Resolution:** Please specify a valid file name.

BW-COMMON-100016: Configuration error in field [%1] the value must be a valid directory name

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid directory name.
- **Resolution:** Please specify a valid directory name.

BW-COMMON-100017: Configuration error in field [%1] the value must be a valid event source name

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid event source name.
- **Resolution:** Please specify a valid event source name.

BW-COMMON-100018: Configuration error in field [%1] the value must be a valid event source name of type [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid event source name of the specified kind.
- **Resolution:** Please specify a valid event source name of the specified kind.

BW-COMMON-100019: Configuration error in field [%1] the value must be a valid floating point number

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid floating point number.

- **Resolution:** Please specify a valid floating point number.

BW-COMMON-100020: Configuration error in field [%1] the value must be a valid double number

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid double.
- **Resolution:** Please specify a valid double.

BW-COMMON-100021: Configuration error in field [%1] the value must be a valid encoding

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid encoding.
- **Resolution:** Please specify a valid encoding.

BW-COMMON-100022: Configuration error in field [%1] the specified encoding [%2] not supported

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid encoding.
- **Resolution:** Please specify a valid encoding.

BW-COMMON-100023: Configuration error in field [%1] the value must be a valid namespace URI

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid namespace URI.

- **Resolution:** Please specify a valid namespace URI.

BW-COMMON-100024: Configuration error in field [%1] the value must be a valid schema element

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid schema element.
- **Resolution:** Please specify a valid schema element.

BW-COMMON-100025: Configuration error in field [%1] the value must be a valid schema type

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid schema type.
- **Resolution:** Please specify a valid schema type.

BW-COMMON-100026: Configuration error in field [%1] the value must be a valid HTTP connection resource

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid HTTP connection.
- **Resolution:** Please specify a valid HTTP Connection resource.

BW-COMMON-100027: Configuration error in field [%1] the value must be a valid TIBRV connection resource

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid TIBRV connection.

- **Resolution:** Please specify a valid TIBRV Connection resource.

BW-COMMON-100028: Configuration error in field [%1] the value must be a valid JDBC connection resource

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid JDBC connection.
- **Resolution:** Please specify a valid JDBC Connection resource.

BW-COMMON-100029: Configuration error in field [%1] the value must be a valid JMS connection resource

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid JMS connection.
- **Resolution:** Please specify a valid JMS Connection resource.

BW-COMMON-100030: Configuration error in field [%1] the value must be a valid IC Server connection

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid IC Server connection.
- **Resolution:** Please specify a valid IC Server Connection resource.

BW-COMMON-100031: Configuration error in field [%1] the value must be a valid WSDL message QName

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid WSDL message

QName.

- **Resolution:** Please specify a valid WSDL message QName.

BW-COMMON-100032: Configuration error in field [%1] the value must be a valid WSDL portType QName

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid WSDL portType QName.
- **Resolution:** Please specify a valid WSDL portType QName.

BW-COMMON-100033: Configuration error in field [%1] the value must be a valid WSDL Service QName

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid WSDL Service QName.
- **Resolution:** Please specify a valid WSDL Service QName.

BW-COMMON-100034: Configuration error in field [%1] the value must be a valid WSDL Port Name in service [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid WSDL Port Name.
- **Resolution:** Please specify a valid WSDL Port Name.

BW-COMMON-100035: Configuration error in field [%1] the value must be a valid WSDL Operation Name in portType [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid WSDL Operation Name.
- **Resolution:** Please specify a valid WSDL Operation Name.

BW-COMMON-100036: Configuration error in field [%1] the value must be a valid proxy resource

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** Please make sure that the specified field is a valid HTTP Proxy Name.
- **Resolution:** Please specify a valid HTTP Proxy Resource Name.

BW-COMMON-100037: The server certificate [%1] not found

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The certificate path is invalid.
- **Resolution:** Please specify the valid certificate file.

BW-COMMON-100038: An exception is received [%1]

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** Unexpected error.
- **Resolution:** Please contact TIBCO support.

BW-COMMON-100039: Error initializing TIBCrypt [%1]

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** Unexpected error.
- **Resolution:** Please contact TIBCO support.

BW-COMMON-100040: The client key [%1] not found

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The key file path may be invalid.
- **Resolution:** Please specify the valid key file.

BW-COMMON-100041: Server certificate is invalid

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The specified certificate is invalid.
- **Resolution:** Please specify the valid certificate.

BW-COMMON-100042: Configuration error in field [%1] the specified transport is not supported

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid transport type.
- **Resolution:** Please contact TIBCO support to get a list of transport protocols supported for this activity.

BW-COMMON-100043: Configuration error. [%1]

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** Activity is not configured correctly.
- **Resolution:** Please check that the activity is configured correctly.

BW-COMMON-100044: Inline schema error. [%1]

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** There was an error resolving an inline schema, or there was an error with a reference from the inline to another schema resource.
- **Resolution:** Please check the inline schema definition for errors. The error may not be in the inline schema itself, but in a schema resource that is used by the inline schema.

BW-COMMON-100045: Configuration error in field [%1] the value must be a valid WSDL Operation Name in port [%2] in service [%3]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid WSDL Operation Name.
- **Resolution:** Please specify a valid WSDL Operation Name.

BW-COMMON-100046: Configuration error in field [%1] the value must be a positive integer number

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid positive integer number.

- **Resolution:** Please specify a valid positive integer number.

BW-COMMON-100047: Configuration error: The metadata schema defined for the activity [%1] cannot be locked

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The metadata schema defined for an activity cannot be locked.
- **Resolution:** Please look at exception for more details.

BW-COMMON-100300: The partner [%1] doesn't implement the specified operation [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the interface implemented by the partner does define the specified operation.
- **Resolution:** Please specify a valid operation name.

BW-COMMON-100301: Partner is not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a partner.
- **Resolution:** Check the configuration and make sure that a partner is specified.

BW-COMMON-100302: Operation is not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify an operation.
- **Resolution:** Check the configuration and make sure that an operation is specified.

BW-COMMON-100303: Service is not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a service.
- **Resolution:** Check the configuration and make sure that a service is specified.

BW-COMMON-100304: Port is not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a port.
- **Resolution:** Check the configuration and make sure that a port is specified.

BW-COMMON-100305: The service name [%1] is not valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid service name.
- **Resolution:** Check the configuration and make sure that the service has a valid name.

BW-COMMON-100306: The port name [%1] is not valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid port name.
- **Resolution:** Check the configuration and make sure that the port has a valid name.

BW-COMMON-100307: The operation name [%1] is not valid

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Please specify a valid operation name.
- **Resolution:** Check the configuration and make sure that the operation has a valid name.

BW-COMMON-100308: The binding type [%1] is not supported

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid binding.
- **Resolution:** Check the configuration and make sure that the binding is valid.

BW-COMMON-100309: The namespace of the service is not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid namespace.
- **Resolution:** Check the configuration and make sure that the namespace of the service is specified.

BW-COMMON-100310: The namespace of the service [%1] is not valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid namespace.
- **Resolution:** Check the configuration and make sure that the namespace of the service is valid.

BW-COMMON-100311: The namespace of the port [%1] is not valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid namespace.
- **Resolution:** Check the configuration and make sure that the namespace of the port

is valid.

BW-COMMON-100312: The port [%1] doesn't have a binding or the binding associated with it is not valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid binding.
- **Resolution:** Check the WSDL file and make sure that the port has a valid binding.

BW-COMMON-100313: The port [%1] doesn't have a PortType or the PortType associated with it is not valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid PortType.
- **Resolution:** Check the WSDL file and make sure that the port has a valid PortType.

BW-COMMON-100314: The NOTIFICATION MEP is not supported

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify either a REQUEST-RESPONSE or a ONE-WAY operation.
- **Resolution:** Check the style of the operation and make sure it is either REQUEST-RESPONSE or ONE_WAY.

BW-COMMON-100315: The SOLICIT-RESPONSE MEP is not supported

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify either a REQUEST-RESPONSE or a ONE-WAY operation.
- **Resolution:** Check the style of the operation and make sure it is either REQUEST-

RESPONSE or ONE_WAY.

BW-COMMON-100316: The Partner [%1] is not valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid partner name.
- **Resolution:** Check the configuration and make sure that a valid partner name is specified.

BW-COMMON-100317: Either the Partner [%1] or the Operation [%2] is not valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid partner name and a valid operation name.
- **Resolution:** Check the configuration and make sure that both a valid partner and a valid operation are specified.

BW-COMMON-100318: The Event Source is not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid event source name.
- **Resolution:** Check the configuration and make sure that a valid event source name is specified.

BW-COMMON-100319: The Event Source [%1] is not valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specify a valid event source name.
- **Resolution:** Check the configuration and make sure that a valid event source name

is specified.

BW-COMMON-100320: A Reply activity cannot be used to reply to the selected Event Source. The operation implemented is a ONE-WAY operation

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** A Reply activity can be used only when the operation implemented by the selected Event Source has a REQUEST-RESPONSE message exchange pattern.
- **Resolution:** Please remove the Reply activity or associate it with a different Event Source.

BW-COMMON-100501: Unexpected value [%1] in the field [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value.
- **Resolution:** Please update the configuration data.

BW-COMMON-100502: Input data error in field [%1] expecting a valid [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the input data.

BW-COMMON-100503: Input data error in field [%1] expecting a value between [%2] and [%3]

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the configuration data.

BW-COMMON-100504: Input data error in field [%1] because [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value.
- **Resolution:** Please update the configuration data.

BW-COMMON-100505: Input data error. [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Activity received incorrect value for the field(s) in the input tab.
- **Resolution:** Reconfigure the ActiveMatrix BusinessWorks process that contains this activity to provide the correct value for the input field(s).

BW-COMMON-100601: Output data error in field [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value.
- **Resolution:** Please update the configuration data.

BW-COMMON-100602: Output data error in field [%1] expecting a valid [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the output data.

BW-COMMON-100603: Output data error in field [%1] expecting a value between [%2] and [%3]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the configuration data.

BW-COMMON-100604: Output data error in field [%1] because [%2]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value.
- **Resolution:** Please update the configuration data.

BW-COMMON-100605: Output data error in field [%1] value cannot be null

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the output data.

BW-COMMON-100606: Output data error in field [%1] value is not serializable

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field has a valid value as indicated.
- **Resolution:** Please update the output data.

BW-COMMON-101001: Error while serializing [%1] message [%2]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error while serializing the message.
- **Resolution:** Please contact TIBCO Support.

BW-COMMON-101002: Error while deserializing [%1] message [%2]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error while deserializing the message.
- **Resolution:** Please contact TIBCO Support.

BW-COMMON-101003: [%1] operation timed out

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Timeout error while waiting for reply.
- **Resolution:** Please check the remote server or increase the timeout value.

BW-COMMON-101004: Internal error occurred. [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Internal error has occurred in the activity.
- **Resolution:** Please contact TIBCO Support.

BW-COMMON-101005: Internal error occurred. Class=[%1], Method=[%2], Cause=[%3]

- **Role:** errorRole

- **Category:** BW-Plugin
- **Description:** Internal error has occurred in the activity.
- **Resolution:** Please contact TIBCO Support.

BW-COMMON-101006: Unable to get value for the global variable [%1]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get value for the specified global variable.
- **Resolution:** Make sure that the specified global variable is defined.

BW-COMMON-101007: Unable to get value for the global variable [%1] because [%2]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get value for the specified global variable.
- **Resolution:** Make sure that the specified global variable is defined.

BW-COMMON-101008: The global variable [%1] is not defined

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get value for the specified global variable.
- **Resolution:** Make sure that the specified global variable is defined.

BW-MIME-100000: Configuration error in field [%1] the value if present, must be a valid directory name; the directory needs to have read/write permission

- **Role:** errorRole

- **Category:** BW-Plugin
- **Description:** Please make sure that the specified field is a valid directory name (the field can be empty) with the necessary read/write permission.
- **Resolution:** Please specify a valid directory name (the field can be empty) with the necessary read/write permission.

XPath Error Codes

This section describes error codes that are returned due to errors in XPath expressions.

XPATH-100001: Null Content

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100002: Expected non-repeating, got repeating

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100003: Expected more than 1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100004: Exceeds maximum occurrence

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**

- **Resolution:**

XPATH-100005: Unexpected %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100006: No functions in namespace:%1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100010: Cannot resolve prefix:%1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100011: Cannot resolve function without prefix.

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100012: No such function.

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100013: Expected 1 argument

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100014: Expected %1 arguments

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100015: Expected at least 1 argument

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100016: Expected at least %1 arguments

- **Role:** errorRole
- **Category:** BW-Core

- **Description:**
- **Resolution:**

XPATH-100017: Expected %1 or %2 arguments

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100020: Expected a node-set

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100021: No matching %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100022: Variable not defined

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100030: Interpreted as a double, rounded to: %1. Use a string constant for arbitrary precision.

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100031: Unterminated escape character. Use & for ampersand.

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100032: XPath indexes are 1 based.

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100100: Variable '%1' already defined in this template

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100101: Illegal variable name

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100110: The substituted type '%1' is not a sub-type of the element's type

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100111: Cannot load the schema for the type substitution

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100112: No such type in schema for the type substitution

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100113: Element is abstract and cannot appear in a valid document

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100114: Type is abstract and cannot appear in a valid document

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100115: This element is not allowed to be nil

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100116: Cannot load the schema for the element

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100117: Unexpected output, no such element in the schema

- **Role:** errorRole

- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100118: Unexpected output, no such element in the current context

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100119: Multiple schemas with namespace '%1' found, and no import to disambiguate between them.

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100120: No formula expected on structure

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100130: Group-by required for for-each-group

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**

- **Resolution:**

XPATH-100131: Group-by must be the first child of for-each-group

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100132: Only 1 Group-by allowed for a for-each-group

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100140: Unexpected output, '%1'

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100141: Unexpected output, '%1'; exceeds maximum occurrence

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100142: Unexpected text output

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100143: Unexpected output, '%1'; got namespace '%2', expected namespace '%3'

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100150: Value required for '%1'

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100151: Element '%1' required

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100152: Not all required components of '%1' are complete

- **Role:** errorRole

- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100153: The output generated inside '%1' is incomplete

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100154: The output generated inside '%1' is not valid

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100155: Missing preceding output terms

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100190: Components inside of '%1' contain errors

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100200: Change namespace to %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100202: Rename to %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100203: Move to: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100204: Move to before: %1

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100210: Copy-of incompatible; names match, but content differs

- **Role:** errorRole
- **Category:** BW-Core

- **Description:**
- **Resolution:**

XPATH-100300: Formula has errors

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100301: Marker must be filled in

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100400: A 'when' statement cannot appear after an 'otherwise'

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100401: Only 1 'otherwise' statement is allowed in a 'choose'

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100402: Only 'when' and 'otherwise' can appear under 'choose'

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100410: All 'sort' statements must appear before anything else

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100420: Can generate more than the expected output of '%1'

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100421: The 'sort' statement must appear directly inside a 'for-each' or 'apply-templates' statement

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100500: Expected %1

- **Role:** errorRole

- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100501: Unexpected

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100502: Unexpected end of xpath

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100503: A variable name

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-100600: Coercion error: '%1' (check coercion list)

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200001: Possibly invalid conversion from %1 to %2

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200002: Always true

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200003: Converting a constant string to a boolean, always true

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200004: Will be converted as if by boolean(), recommend comparing to string

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200005: Will be converted as if by boolean(), recommend converting to a number

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200006: Always false

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200010: position() is relative to inside the filter; equivalent to 'true()' in this usage.

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200100: Statement contains no children; has no effect

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200101: Output is required, so the surrounding 'if' is not required

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200102: Input is not optional, so the surrounding 'if' is not required

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200103: Input is not a node set, so the surrounding 'if' is not recommended

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200110: Simplify to an xsi:nil attribute constant

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200120: The input and this element are both nillable, set to copy-nil

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200121: This element is not nillable

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200122: This input element is not nillable

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200200: The referenced schema component has an error: %1

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-200300: The term %1 is required but not generated in all cases of the choose

- **Role:** warningRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-300001: Converted by %1

- **Role:** infoRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-300100: Optimize by computing '%1' out of the predicate

- **Role:** infoRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-301000: For element '%1', source schema has namespace '%2', the target has namespace '%3'

- **Role:** infoRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-301001: Source schema has name '%1', target has name '%2'

- **Role:** infoRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-301002: Source schema has '%1', target has '%2'

- **Role:** infoRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-400001: The statement 'stylesheet' cannot appear here

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-400101: Expected output '%1' before this

- **Role:** errorRole
- **Category:** BW-Core
- **Description:**
- **Resolution:**

XPATH-400102: Expected output '%1' at end of this

- **Role:** errorRole
- **Category:** BW-Core

- **Description:**
- **Resolution:**

ActiveEnterprise Adapter Error Codes

This section describes error codes that can be returned by activities in the ActiveEnterprise Adapter palette.

BW-AE-100000: Cannot create Transport

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot create Transport.
- **Resolution:** Please Contact TIBCO Support.

BW-AE-100001: Error in sending message

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error in sending message.
- **Resolution:** Please Contact TIBCO Support.

BW-AE-100002: Error serializing the message

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error serializing the message.
- **Resolution:** Please Contact TIBCO Support.

BW-AE-100003: Error in sending request

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** Error in sending request.
- **Resolution:** Please Contact TIBCO Support.

BW-AE-100004: Error in processing event: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error in processing event.
- **Resolution:** Please Contact TIBCO Support.

BW-AE-100005: Cannot create TibrvQueue: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot create TibrvQueue.
- **Resolution:** Please Contact TIBCO Support.

BW-AE-100006: Cannot create rvEventContext: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot create rvEventContext.
- **Resolution:** Please Contact TIBCO Support.

BW-AE-100007: Cannot create reply listener for subject: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot create reply listener, for subject: %1.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100008: Cannot activate TIBRV listener for subject: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot activate TIBRV listener for subject: %1.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100009: Error in sending reply

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error in sending reply.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100010: Error in confirming the message

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error in sending reply.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100011: RPC Server returned error message.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** RPC Server returned error message.
- **Resolution:** Please check the RPC exception data for more information.

BW-AE-100012: Error while serializing the message.

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** Error while serializing the message.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100013: Error while deserializing the message.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error while deserializing the message.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100014: Timeout waiting for reply.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Timeout waiting for reply.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100015: Subject used in the Transport of the Activity is different from the Adapter Service.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Subject used in the Transport of the Activity is different from the Adapter Service.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100016: RV Service used in the Transport of the Activity is different from the Adapter Service.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** RV Service used in the Transport of the Activity is different from the

Adapter Service.

- **Resolution:** Please contact TIBCO Support.

BW-AE-100017: RV Network used in the Transport of the Activity is different from the Adapter Service.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** RV Network used in the Transport of the Activity is different from the Adapter Service.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100018: RV Daemon used in the Transport of the Activity is different from the Adapter Service.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** RV Daemon used in the Transport of the Activity is different from the Adapter Service.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100019: JMS Topic used in the Transport of the Activity is different from the Adapter Service.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** JMS Topic used in the Transport of the Activity is different from the Adapter Service.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100020: JMS Queue used in the Transport of the Activity is different from the Adapter Service.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** JMS Queue used in the Transport of the Activity is different from the Adapter Service.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100021: The Adapter Service being connected to may use a SSL option different from the BW Activity.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Adapter Service being connected to may use a SSL option different from the BW Activity.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100022: The Adapter Service being connected to may use a different JMS URL from the BW Activity.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Adapter Service being connected to may use a different JMS URL from the BW Activity.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100023: RV Subject is a required field.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** RV Subject is a required field.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100024: JMS Topic is a required field.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** JMS Topic is a required field.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100025: JMS Queue is a required field.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** JMS Queue is a required field.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100026: JMS URL is a required field.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** JMS URL is a required field.
- **Resolution:** Please Contact TIBCO Support.

BW-AE-100027: AE metadata loading error: class %1 not found.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** AE metadata loading error: class %1 not found.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100028: Failed to load request metadata for operation %1 in class %2.

- **Role:** errorRole

- **Category:** BW_Plugin
- **Description:** Failed to load request metadata for operation %1 in class %2.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100029: Can't load the ProcessStarter %1.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Can't load the ProcessStarter %1.
- **Resolution:** Please contact TIBCO Support.

BW-AE-100030: AE plugin configuration error: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** AE plugin configuration error. Details provided.
- **Resolution:** Please contact TIBCO Support.

File Error Codes

This section describes error codes that can be returned by activities in the File palette.

BW-FILE-100000: File name [%1] is not valid

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The file name is not valid.
- **Resolution:** Correct the file name or the mapping used to create the file name.

BW-FILE-100001: File [%1] was not found

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The file was not found.
- **Resolution:** Correct the file name or the mapping used to create the file name.

BW-FILE-100002: File [%1] already exists

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The file already exists.
- **Resolution:** Correct the file name or the mapping used to create the file name.

BW-FILE-100003: An IO exception occurred while trying to write to the file [%1]

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** An IO exception occurred while trying to write to the file.
- **Resolution:** System error

BW-FILE-100004: File [%1] cannot be created

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** File cannot be created.
- **Resolution:** System error

BW-FILE-100005: Cannot read the binary content for the file [%1]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get the file content in binary form.
- **Resolution:** System error

BW-FILE-100006: Cannot read the string content for the file [%1]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get the file content in string form.
- **Resolution:** System error

BW-FILE-100007: The encoding [%1] is not valid

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The encoding is not valid.
- **Resolution:** Check the encoding to make sure it is supported.

BW-FILE-100008: The content provided is not base 64 binary

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The file was not found.
- **Resolution:** Check the input data.

BW-FILE-100009: Cannot rename the file [%1] to [%2]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot rename the file.
- **Resolution:** System error

BW-FILE-100010: Cannot rename the file [%1] to [%2]. The destination file exists and its type is different than the type of the source file

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot rename the file. The destination file exists and its type is different than the type of the source file.
- **Resolution:** Check input data.

BW-FILE-100011: This activity cannot be used to move a directory

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** This activity cannot be used to move a directory.
- **Resolution:** See the documentation of the File Rename Activity.

BW-FILE-100012: Cannot remove the file [%1]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot remove the file.
- **Resolution:** System error

BW-FILE-100013: An IO exception occurred while trying to create the file [%1]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An IO exception occurred while trying to create the file.
- **Resolution:** System error

BW-FILE-100014: You cannot overwrite the following file [%1] to file [%2] if the overwrite flag is not selected.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:**
- **Resolution:** May need to set Overwrite property on activity Configuration.

BW-FILE-100015: You cannot copy a directory [%1] to an existing file [%2]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** You cannot copy a directory to an existing file.
- **Resolution:** Change from file path.

BW-FILE-100016: You cannot copy multiple files [%1] to an existing file [%2]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** You cannot copy multiple files to an existing file.
- **Resolution:** Change from file path.

BW-FILE-100017: Cannot create missing path [%1]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot create missing path.
- **Resolution:** May need to set Create Missing Dirs property on activity Configuration.

BW-FILE-100018: Cannot copy file [%1] to file [%2]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot copy file.
- **Resolution:** System Error

FTP Error Codes

This section describes error codes that can be returned by activities in the FTP palette.

BW-FTP-100000: FTP connection is required.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** FTP connection is required.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100001: Cannot perform FTP Operation: %1. Error Info: %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot perform FTP Operation: %1. Error Info: %2.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100002: Cannot establish FTP connection when performing FTP function: %1. Error Info: %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot establish FTP connection when performing FTP function: %1. Error Info: %2.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100003: File %1 already exists.

- **Role:** errorRole

- **Category:** BW_Plugin
- **Description:** File %1 already exists.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100004: Error in PUT or MPUT command. See Error Tab for details.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error in PUT or MPUT command. See Error Tab for details.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100005: Error in GET or MGET command. See Error Tab for details.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error in GET or MGET command. See Error Tab for details.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100006: FTP Connection Succeeded. Target System: %1.

- **Role:** infoRole
- **Category:** BW_Plugin
- **Description:** FTP Connection Succeeded. Target System: %1.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100007: Client is not initialized: %1.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Client is not initialized: %1.

- **Resolution:** Please contact TIBCO Support.

BW-FTP-100008: Connection timeout.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Connection timeout.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100009: Local file specified cannot be found.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Local file specified cannot be found.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100010: Global variable %1 not defined.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Global variable %1 not defined.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100011: Unexpected reply code. Returned Code: %1 Expected Code: %2.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Unexpected reply code. Returned Code: %1. Expected Code: %2.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100012: Invalid user name or password

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid user name or password.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100013: Error in executing remote command: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error in executing remote command: %1.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100014: Connection reference is missing.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Connection reference is missing.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100015: Cannot access firewall.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot access firewall.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100016: Field %1 is required.

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Field %1 is required.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100017: FTP Connection Test Failed. Validate Host Name: %1.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** FTP Connection Test Failed. Validate Host Name: %1.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100018: FTP Connection Test Failed. Error: %1.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** FTP Connection Test Failed. Error: %1.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100019: File %1 does not exist.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** File %1 does not exist.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100020: Trusted Certificate location not specified in SSL Configuration

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Trusted Certificate location not specified in SSL Configuration.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100021: Error compiling trusted certificate. Reason: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error compiling trusted certificate. Reason: %1.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100022: Error compiling client identity. Reason: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error compiling client identity. Reason: %1
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100023: Error creating SSL client. Reason: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error creating SSL client. Reason: %1.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100024: Error creating secure socket. Reason: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error creating secure socket. Reason: %1.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100025: Error establishing active data socket. Reason: %1

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Error establishing active data socket. Reason: %1.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100026: Error changing remote working directory. Reason: input is null

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error changing remote working directory. Reason: input is null.
- **Resolution:** Please contact TIBCO Support.

BW-FTP-100027: Error doing mget. Reason: mget is not supported for FTP via Proxy

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error doing mget. Reason: mget is not supported for FTP via Proxy.
- **Resolution:** Please contact TIBCO Support.

General Activities Error Codes

This section describes error codes that can be returned by activities in the General Activities palette.

BW-GENERAL-100001: Notify Configuration not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Notify Configuration not specified.
- **Resolution:** Please specify shared configuration.

BW-GENERAL-100002: Unable to construct notification data for wait/receive activity

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Unexpected internal error occurs. Unable to construct notification data for wait/receive activity.
- **Resolution:** Please contact TIBCO Support.

BW-GENERAL-100003: Unable to lock schema for notify input

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Unable to lock schema for notify input.
- **Resolution:** Please look at exception for more details.

BW-GENERAL-100004: Internal schema error occurs

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Internal schema error occurs.
- **Resolution:** Please look at exception for more details.

BW-GENERAL-100005: Unable to resolve shared configuration reference for [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Unable to resolve shared configuration reference for [%1].
- **Resolution:** Please look at exception for more details.

BW-GENERAL-202001: Cannot cancel wait on group [%1] key [%2]

- **Role:** warnRole
- **Category:** BW-Plugin
- **Description:** Cannot cancel wait on group [%1] key [%2].
- **Resolution:** Please look at exception for more details.

BW-GENERAL-202002: Receive error notification in [%1]

- **Role:** warnRole
- **Category:** BW-Plugin
- **Description:** Receive error notification in [%1].
- **Resolution:** Please look at exception for more details.

BW-GENERAL-202003: Error occurs after getting notification data in [%1]

- **Role:** warnRole

- **Category:** BW-Plugin
- **Description:** Error occurs after getting notification data in [%1].
- **Resolution:** Please look at exception for more details.

BW-GENERAL-202004: Wait for notification failed for [%1], set inactive

- **Role:** warnRole
- **Category:** BW-Plugin
- **Description:** Wait for notification failed for [%1], set inactive.
- **Resolution:** Please look at exception for more details.

BW-GENERAL-202005: Wait thread internal error for [%1], set inactive

- **Role:** warnRole
- **Category:** BW-Plugin
- **Description:** Wait thread internal error for [%1], set inactive.
- **Resolution:** Please look at exception for more details.

BW-JNDI-100001: Configuration Test Failed. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to establish connection to the server.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JNDI-100002: Configuration Test Failed. Exception [%1] occurred.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to establish connection to the server. Exception occurred.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JNDI-100003: The JNDI Configuration reference [%1] not found

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to obtain the specified JNDI Configuration shared resource reference.
- **Resolution:** Please correct the error and retry.

BW-JNDI-100004: The JNDI Configuration reference [%1] not found in repository

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The repository does not contain the specified JNDI Configuration shared resource reference.
- **Resolution:** Please correct the error and retry.

BW-JNDI-100005: The JNDI Configuration reference [%1] contains incorrect field values.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The JNDI Configuration shared resource referenced contains invalid field values.
- **Resolution:** Please correct the error and retry.

BW-JNDI-100006: Exception occurred while trying to obtain the JNDI Configuration reference [%1]: %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to obtain the JNDI Configuration shared resource reference.
- **Resolution:** Please correct the error and retry.

BW-JTAUT-400000: %1

- **Role:** debugRole
- **Category:** BW_Plugin
- **Description:** Debug Trace Message
- **Resolution:** None

BW-CMD-100001: Error executing external command %1: %2.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error executing external command %1: %2.
- **Resolution:** Check command value in configuration and input.

BW-CMD-100002: Error accessing file or directory %1: %2. Check file or directory name and permissions.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error accessing file or directory %1: %2. Check file or directory name and permissions.
- **Resolution:** Ensure that output file has write permissions for user running engine and that sufficient disk space is available for writing output file. Ensure that working directory exists and is accessible for user running engine.

BW-CMD-100003: No command specified.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** No command specified.
- **Resolution:** Provide a command in configuration or input.

BW-TIMER-100000: Invalid start time [%1], correct format is [%2]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The format of the start time must conform to the standard format.
- **Resolution:** Update the global variable to use the correct format.

HTTP Error Codes

This section describes error codes that can be returned by activities in the HTTP palette.

BW-HTTP-100000: The HTTP Server replied with a 4XX status code

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The request contains bad syntax or cannot be fulfilled.
- **Resolution:** Correct the configuration (input data) of the HTTP Request activity.

BW-HTTP-100001: The HTTP Server replied with a 5XX status code

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The server failed to fulfill an apparently valid request.
- **Resolution:** See the documentation.

BW-HTTP-100100: An exception was thrown while trying to initialize the HTTP client

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An exception was thrown while trying to initialize the HTTP client.
- **Resolution:** System exception.

BW-HTTP-100102: An exception occurred while trying to initialize the HTTP server

- **Role:** errorRole

- **Category:** BW_Plugin
- **Description:** An exception occurred while trying to initialize the HTTP server.
- **Resolution:** System exception.

BW-HTTP-100103: There are more than one HTTP event sources registered on [%1]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** There are more than one HTTP event sources registered on a specific port.
- **Resolution:** Make sure there is no more than one HTTP event source (signal-in activity) that use a specific HTTP Connection Shared Resource.

BW-HTTP-100104: The trusted CA store was not specified

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The trusted CA store was not specified.
- **Resolution:** Make sure the trusted CA store is specified.

BW-HTTP-100105: An exception occurred while trying to build the input class.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A schema specific exception occurred while trying to build the input class.
- **Resolution:** System error.

BW-HTTP-100106: An exception occurred while trying to build the output class.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A schema specific exception occurred while trying to build the output class.
- **Resolution:** System error.

BW-HTTP-100107: A repository exception was thrown while trying to load the identity.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A repository exception was thrown while trying to load the identity.
- **Resolution:** Make sure the file that contains the private key can be read.

BW-HTTP-100108: A security exception was thrown while trying to load the identity.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A security exception was thrown while trying to load the identity.
- **Resolution:** Make sure the format of the file that contains the private key is supported.

BW-HTTP-100109: An IO exception was thrown while trying to load the identity.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An IO exception was thrown while trying to load the identity.

- **Resolution:** Make sure the file that contains the private key exists and is readable.

BW-HTTP-100110: An IO exception was thrown while trying to load the trusted CA store.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An IO exception was thrown while trying to load the trusted CA store.
- **Resolution:** Make sure the certificates that are stored in the trusted CA store are valid. See the documentation.

BW-HTTP-100111: A security exception was thrown while trying to load the trusted CA store.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A security exception was thrown while trying to load the trusted CA store.
- **Resolution:** Make sure the certificates that are stored in the trusted CA store are valid. See the documentation.

BW-HTTP-100112: A CertificateException was thrown while trying to load a particular certificate from the trusted CA store.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A CertificateException was thrown while trying to load a particular certificate from the trusted CA store.
- **Resolution:** Make sure the certificates that are stored in the trusted CA store are valid. See the documentation.

BW-HTTP-100113: The Identity [%1] is not valid.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Identity [%1] is not valid.
- **Resolution:** See the documentation.

BW-HTTP-100114: The Identity is not specified

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Identity is not specified.
- **Resolution:** Make sure the Identity name is specified.

BW-HTTP-100115: A security exception was thrown while trying to initialize the HTTPS server

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A security exception was thrown while trying to initialize the HTTPS server.
- **Resolution:** System error.

BW-HTTP-100116: A lifecycle exception was thrown while trying to initialize the Tomcat server

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A lifecycle exception was thrown while trying to initialize the Tomcat server.
- **Resolution:** System error.

BW-HTTP-100117: An IO exception was thrown while trying to create the web server file structure

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An IO exception was thrown while trying to create the web server file structure.
- **Resolution:** System error.

BW-HTTP-100118: An exception was thrown while trying to load the proxy's identity

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An exception was thrown while trying to load the proxy's identity.
- **Resolution:** System error.

BW-HTTP-100119: An exception was thrown while trying to load the proxy

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An exception was thrown while trying to load the proxy.
- **Resolution:** System error.

BW-HTTP-100120: An exception was thrown while trying to load the identity used for basic HTTP authentication

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An exception was thrown while trying to load the identity used for basic HTTP authentication.

- **Resolution:** System error.

BW-HTTP-100121: An exception occurred while trying to initialize the HTTP server: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An exception occurred while trying to initialize the HTTP server.
- **Resolution:** System exception.

BW-HTTP-100123: The Identity on the Proxy Connection is not valid

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Identity on the Proxy Connection is not valid. Please use a UsernamePassword Identity.
- **Resolution:** Correct the Identity.

BW-HTTP-100124: The Identity for the basic authentication was not specified

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Identity for the basic authentication was not specified.
- **Resolution:** Make sure the Identity name is specified.

BW-HTTP-100125: The Identity [%1] cannot be referenced in this context

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Identity [%1] cannot be referenced in this context.

- **Resolution:** See the documentation.

BW-HTTP-100126: The Parameter Name [%1] is not valid

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Parameter Name [%1] is not valid.
- **Resolution:** Fix the name of the parameter.

BW-HTTP-100127: The Parameter Name [%1] is already specified

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Parameter Name [%1] is already specified.
- **Resolution:** Remove one of the parameters.

BW-HTTP-100128: The HTTP Connection Resource is not specified

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The HTTP Connection Resource is not specified.
- **Resolution:** Specify an HTTP Connection Resource.

BW-HTTP-100129

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Identity for Kerberos authentication was not specified.
- **Resolution:** Create the Identity resource with the username and password, and map it to the HTTP Send Request activity.

BW-HTTP-100130

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An exception was thrown while trying to load the identity used for Kerberos HTTP authentication.
- **Resolution:** Resolve the identity resource mapping if the resource is mapped incorrectly.

BW-HTTP-100201: A POST Method cannot send parameters if the message body is specified

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A POST Method cannot send parameters if the message body is specified.
- **Resolution:** Correct the input data.

BW-HTTP-100202: A GET Method doesn't have a message body

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A GET Method doesn't have a message body.
- **Resolution:** Correct the input data. Make sure that the message body is not specified for a GET request.

BW-HTTP-100203: Invalid endpoint URL. The host name is not specified.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Invalid endpoint URL. The host name is not specified.
- **Resolution:** Correct either the configuration or the input data. Make sure that the

host name is specified.

BW-HTTP-100204: Invalid endpoint URL

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Invalid endpoint URL.
- **Resolution:** Correct either the configuration or the input data.

BW-HTTP-100205: Invalid input data. The encoding is not supported.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Invalid input data. The encoding is not supported.
- **Resolution:** Correct the input data. Make sure the encoding is supported. See the documentation.

BW-HTTP-100206: The HTTP method [%1] is not valid

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The specified HTTP method is not valid.
- **Resolution:** Correct the input data. Make sure that the HTTP method is valid.

BW-HTTP-100207: The status line [%1] is not valid

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The status line is not valid. The right format is X Y Z, where X - the HTTP version, Y - the status code, Z - the reason phrase.
- **Resolution:** See the documentation.

BW-HTTP-100208: An exception was thrown while trying to url-encode the data

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An exception was thrown while trying to url-encode the data.
- **Resolution:** See the documentation.

BW-HTTP-100209: Attachment not supported for HTTP method %1. Only HTTP 'POST' can send attachments.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Attachment not supported for HTTP method %1. Only HTTP 'POST' can send attachments.
- **Resolution:** See the documentation.

BW-HTTP-100210: Error serializing attachment data, Cause: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error serializing attachment data, Cause: %1.
- **Resolution:** See the documentation.

BW-HTTP-100299: The input data is not valid

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The input data is not valid.
- **Resolution:** See the documentation.

BW-HTTP-100300: An IOException was thrown while trying to execute the HTTP method

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An IOException was thrown while trying to execute the HTTP method.
- **Resolution:** System exception.

BW-HTTP-100301: An exception was thrown while trying to execute the HTTP method. The Reason-code is [%1].

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An exception was thrown while trying to execute the HTTP method.
- **Resolution:** System exception.

BW-HTTP-100302: An IOException was thrown while trying to read the response

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An IOException was thrown while trying to read the response.
- **Resolution:** System exception.

BW-HTTP-100303: An IOException was thrown while trying to send the response

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An IOException was thrown while trying to send the response.
- **Resolution:** System exception.

BW-HTTP-100304: An Exception was thrown while trying to send the response

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An Exception was thrown while trying to send the response.
- **Resolution:** System exception.

BW-HTTP-100305: An exception was thrown while trying to send the HTTP request

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An exception was thrown while trying to send the HTTP request.
- **Resolution:** System exception.

BW-HTTP-100400: The incoming HTTP message cannot be deserialized

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The incoming HTTP message cannot be deserialized.
- **Resolution:** There is probably an error on the HTTP client that invokes this service.

BW-HTTP-100500: Using the following HTTP minProcessors/maxProcessors [host=%1 port=%2]: %3/%4

- **Role:** infoRole
- **Category:** BW_Plugin
- **Description:** Using the following HTTP minProcessors/maxProcessors [host=%1 port=%2]: %3/%4.
- **Resolution:**

BW-HTTP-100600: For better MIME Multipart support, consider Upgrading Configuration

- **Role:** warnRole
- **Category:** BW_Plugin
- **Description:** For better MIME Multipart support, consider Upgrading Configuration.
- **Resolution:**

BW-HTTP-100801:

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Krb conf file is not specified.
- **Resolution:** Provide the correct file path.

BW-HTTP-100802:

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Login conf file is not specified.
- **Resolution:** Provide the correct file path.

Java Error Codes

This section describes error codes that can be returned by activities in the Java palette.

BW-JAVA-100000: The activity was not compiled

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The activity was not compiled.
- **Resolution:** Compile the activity in Designer.

BW-JAVA-100001: While executing [%1] encountered [%2] : [%3]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception encountered while invoking a method on the activity.
- **Resolution:** Inspect the Java source for this activity for a possible cause.

BW-JAVA-100002: The Java compiler is not in the classpath. Add tools.jar to the classpath.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Java compiler is not in the classpath. Add tools.jar to the classpath.
- **Resolution:** Add tools.jar to the classpath.

BW-JAVA-100003: The Java compile of [%1] failed with message: [%2]

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** The Java compiler encountered an error in the activity Java code.
- **Resolution:** Examine the error and fix the issue in the Java code.

BW-JAVA-100004: The Java code is missing a required comment: [%1]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The activity uses embedded comments to auto generate code. One of them is missing.
- **Resolution:** Update the code to remove any unbalanced comment delimiters and recompile.

BW-JAVA-100005: The [javaCode] property is missing from the .tra file

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The activity could not determine a suitable temporary directory.
- **Resolution:** add java.property.javaCode=[directory] in the designer.tra and bwengine.tra files.

BW-JAVA-100006: Cannot delete the [%1] Java source file.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Source files are written to the local file system for the compiler to access. The given file already exists and is write protected.
- **Resolution:** Remove the Java source file from the local file system so that the activity may write a new copy.

BW-JAVA-100007: Cannot write the [%1] Java source file: [%2]

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** Source files are written to the local file system for the compiler to access. There was an error writing the given file to the file system.
- **Resolution:** Examine the temporary directory for sufficient space to write files.

BW-JAVA-100011: Activity input schema creation error. Exception [%1] occurred while trying to create input schema. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Java plugin activity is not able create schema for the activity's input tab. Exception occurred.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100012: Activity output schema creation error. Exception [%1] occurred while trying to create output schema. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Java plugin activity is not able create schema for the activity's output tab. Exception occurred.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100013: Activity input data conversion error. Exception [%1] occurred while trying to render the activity input data. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** This activity is not able to convert the input data.
- **Resolution:** Please Contact TIBCO Support.

BW-JAVA-100014: Activity output data conversion error. Exception [%1] occurred while trying to create the activity output data. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** This activity is not able to create the output data.
- **Resolution:** Please Contact TIBCO Support.

BW-JAVA-000015: Activity initialization error: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error occurred while initializing the activity.
- **Resolution:** Please Contact TIBCO Support.

BW-JAVA-100016: Unable to obtain information for the Java class [%1]. Exception [%2] occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred while trying to obtain information for the declared Java class.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JAVA-100017: The Java class [%1] is not found in the classpath. ClassNotFoundException occurred. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** ClassNotFoundException occurred while trying to access the specified Java class.
- **Resolution:** Please verify that the specified class file is contained in the classpath.

BW-JAVA-100018: The Java class [%1] cannot be instantiated. Exception [%2] occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to create an instance of the specified Java class.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JAVA-100019: Input data error. The activity received an incorrect value for the method parameters. IllegalArgumentException occurred while trying to construct an instance of the Java class [%1]: %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The activity received a incorrect value for the method parameter element that is in the activity input tab. IllegalArgumentException occurred while trying to construct the specified Java class.
- **Resolution:** Verify that the correct values are provided for the method parameter elements that are in the activity input tab.

BW-JAVA-100020: Unable to construct an instance of the Java class [%1]. Exception [%2] occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to create an instance of the Java class. Exception occurred while trying to create an instance of the Java class.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JAVA-100021: The constructor for the Java class [%1] raised exception [%2]. %3

- **Role:** errorRole

- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the Java class constructor.
- **Resolution:** The exception was raised by the constructor of the declared Java class. Please refer to the Java class implementation for details.

BW-JAVA-100022: Configuration error. The Java class [%1] is an abstract class. It is not permitted to create an instance of an abstract Java class.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The selected class is an abstract Java class.
- **Resolution:** Make sure that the selected class is not an abstract Java class.

BW-JAVA-100023: Configuration error. The Java class [%1] is an interface. It is not permitted to create an instance of a Java interface.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The selected class is a Java interface.
- **Resolution:** Make sure that the selected class is not a Java interface.

BW-JAVA-100024: Configuration error. The Java class [%1] is not serializable. If the selected Java class is cached by the activity then the class must be a subtype of the interface 'java.io.Serializable'.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The declared Java class is not serializable. If the user has selected the option to cache the declared Java class then the class must be a subtype of the interface 'java.io.Serializable'.
- **Resolution:** Make sure that the selected class is a subtype of the interface 'java.io.Serializable'.

BW-JAVA-100025: Configuration error. The method [%1] returns a Java class [%2] that is not serializable. The Java class returned by the selected method must be a subtype of the interface 'java.io.Serializable'.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Invalid method return type. If the selected method must returns a Java class then the class must be a subtype of the interface 'java.io.Serializable'.
- **Resolution:** Make sure that the selected method returns a serializable Java class.

BW-JAVA-100026: Unable to obtain information for the method [%1] from the class [%2]. NoSuchMethodException occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The method name is not contained in the declared Java class.
- **Resolution:** It is possible that the declared Java class has been modified since the last configuration of this activity. Please reconfigure this activity or verify that the declared Java class has not changed since the last configuration.

BW-JAVA-100027: Unable to obtain information for the cleanup method [%1] from the class [%2]. NoSuchMethodException occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The cleanup method name is not contained in the declared Java class.
- **Resolution:** It is possible that declared Java class has been modified since the last configuration of this activity. Please reconfigure this activity or verify that the declared Java class has not changed since the last configuration.

BW-JAVA-100028: Unable to obtain information for method [%1] from the class [%2]. SecurityException occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** SecurityException occurred while trying to get method information from the declared Java class.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100029: Unable to obtain information for method [%1] from the class [%2]. ClassNotFoundException occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** ClassNotFoundException occurred while trying to get method information from the declared Java class.
- **Resolution:** Please verify that the specified class file is contained in the classpath.

BW-JAVA-100030: Unable to obtain information for method [%1] from the class [%2]. Exception occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred while trying to get method information from the declared Java class.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100031: Input data error. The activity received an incorrect value for the method parameters. IllegalArgumentException occurred while trying to invoke the method [%1]: %2

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** The activity received a incorrect value for the method parameter element that is in the activity input tab. IllegalArgumentException occurred while trying to invoke the Java method.
- **Resolution:** Verify that the correct values are provided for the method parameter elements that are in the activity input tab.

BW-JAVA-100032: Input data error. The activity received an incorrect Java object for the declared Java class [%1]. The activity expected an instance of the Java class [%2], but received an instance of the Java class [%3]: %4

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The activity received a incorrect value for the declared class element that is in the activity input tab.
- **Resolution:** Possible causes for this error are: (1). Incorrect object reference was specified for the declared Java class. Verify that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. (2). The classpath refers to a incorrect declared class or the Java jar file. Verify that the classpath refers to the correct declared class.

BW-JAVA-100033: Input data error. The activity received an incorrect Java object for the declared Java class [%1]. The Java object received is not compatible with the Java object expected by this activity. The activity expects an instance of the Java class [%2]: %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The activity received a incorrect value for the declared class element that is in the activity input tab.
- **Resolution:** Possible causes for this error are: (1). Incorrect object reference was specified for the declared Java class. Verify that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. (2). The classpath refers to a incorrect declared class or the Java jar file. Verify that

the classpath refers to the correct declared class.

BW-JAVA-100034: Input data error. The activity received 'null' value for the for the declared Java class. The activity expected an instance of the class [%1], but received a 'null'.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The activity received a null value for the declared class element that is in the activity input tab.
- **Resolution:** Possible causes for this error are: (1). Incorrect object reference was specified for the declared Java class. Verify that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. (2). The preceding activity that provides the input value for this activity produced a null for its output.

BW-JAVA-100035: Unable to invoke the method [%1]. Exception [%2] occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to invoke the user specified method of the Java class. Exception occurred while trying to invoke the method.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JAVA-100036: Unable to invoke the cleanup method [%1]. Exception [%2] occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to invoke the cleanup method for the Java class. Exception occurred while trying to invoke the method.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JAVA-100037: The method [%1] raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the specified method.
- **Resolution:** The exception was raised by the method of the specified Java class. Please refer to the declared class implementation for details.

BW-JAVA-100038: The cleanup method [%1] raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the cleanup method.
- **Resolution:** The exception was raised by the method of the specified Java class. Please refer to the declared class implementation for details.

BW-JAVA-100039: Exception occurred while trying to obtain the JavaSchema [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get the **JavaSchema** activity referenced by this activity.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100040: The JavaSchema [%1] referenced by this activity is not found in repository.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The repository does not contain the JavaSchema activity referenced by this activity.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100041: The JavaSchema [%1] referenced by this activity contains invalid field values.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The JavaSchema activity referenced by this activity contains invalid field values.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100042: Input data error. The activity received 'null' value for the declared Java class. The activity expected instance of class [%1], but received a 'null'.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The activity received a null value for the declared Java class element that is in the activity input tab.
- **Resolution:** Possible causes for this error are: (1). Incorrect object reference was specified for the declared class. Verify that the correct Java object reference is provided for the declared class element shown in the input tab of this activity. (2). The preceding activity that provides the input value for this activity produced a null for its output.

BW-JAVA-100043: Input data error. The activity received incorrect Java object for the declared Java class. The activity expected instance of a class [%1], but received instance of a class [%2].

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The activity received an incorrect value for the declared Java class element that is in the activity input tab.
- **Resolution:** Possible causes for this error are: (1). Incorrect object reference was specified for the declared class. Verify that the correct Java object reference is

provided for the declared class element shown in the input tab of this activity. (2). The classpath refers to a incorrect the declared class or the Java jar file. Verify that the classpath refers to the correct declared Java class.

BW-JAVA-100044: Configuration error. The Java class [%1] does not contain a default constructor or a constructor with no arguments. The selected Java class must have a default constructor if the user has selected the option to construct the declared class by the activity.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The user has selected the option to construct the declared class by the activity.
- **Resolution:** Select a Java class that contain a default constructor.

BW-JAVA-100045: Data Conversion error: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to convert data from XML to Java or Java to XML.
- **Resolution:** Certain Java data types are not supported by the BusinessWorks conversion mechanism. Please verify that unsupported data types are not utilized or referenced in your Java class.

BW-JAVA-100046: Data Conversion error. Exception occurred while trying to convert Java object to XML data. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to convert the Java object to an XML data.
- **Resolution:** Certain Java data types are not supported by the Java to XML conversion mechanism. Please verify that unsupported data types are not utilized or referenced in your Java class.

BW-JAVA-100047: Data Conversion error. Exception occurred while trying to convert XML data to Java object. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to convert the XML data to Java object.
- **Resolution:** Certain Java data types are not supported by the XML to Java conversion mechanism. Please verify that unsupported data types are not utilized or referenced in your Java class.

BW-JAVA-100048: Unable to generate schema for the Java class [%1]. Exception [%2] occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error occurred while trying to generate schema for the declared Java class.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100049: Configuration error. The Java class [%1] is not serializable. For XML to Java conversion operations the selected Java class must be a subtype of the interface 'java.io.Serializable'.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The selected class must be serializable for XML to Java conversion operation.
- **Resolution:** Select a class that is serializable.

BW-JAVA-100050: Configuration error. The Java class [%1] does not contain a default constructor or a constructor with no arguments. For XML to Java conversion operation the selected Java class must have a default constructor.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The selected Java class does not contain a constructor with zero arguments.
- **Resolution:** Select a Java class that contain a default constructor.

BW-JAVA-100051: Configuration error. The Java class [%1] contains unsupported data type. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The declared Java class contains unsupported data type.
- **Resolution:** Certain Java data types are not supported by the XML to Java or Java to XML conversion mechanism. Please verify that unsupported data types are not utilized or referenced in your Java class.

BW-JAVA-100052: Missing the schema for the Java class [%1].

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** A schema could not be located the specified Java class.
- **Resolution:** Please attempt to generate the schema.

BW-JAVA-100053: A schema for the JavaSchema resource [%1] with the namespace [%2] could not be found.

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** A schema could not be located the specified namespace.
- **Resolution:** Please examine the JavaSchema resource and attempt to regenerate the schema.

BW-JAVA-100054: At runtime the TIBCO BusinessWorks activity will not be able to access the method [%1] of the class [%2]. The class or the superclass [%3] that implements the method is not declared as a public class.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The declared class modifier must be public.
- **Resolution:** Please verify that the Java class that implements the selected method is declared public.

BW-JAVA-100055: At runtime the TIBCO BusinessWorks activity will not be able to access the method [%1] of the class or interface [%2]. The interface [%3] that defines the method is not declared as a public interface.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The declared interface modifier must be public.
- **Resolution:** Please verify that the Java Interface that proclaims the selected method is declared public.

BW-JAVA-100056: Configuration error. The Java class [%1] does not contain a default constructor or a constructor with no arguments. For XML to Java conversion operations, the [%2] Java class must be comprised only of classes with default constructors.

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** All classes comprising the [%2] Java class must contain a constructor with zero arguments.
- **Resolution:** Select a Java class comprised only of classes with default constructors.

BW-JAVA-100057: Configuration error. The Java class [%1] is is not declared as a public class. It is not permitted to create an instance of an non-public class.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The declared class modifier must be public.
- **Resolution:** Make sure that the selected Java class is declared as a public class.

BW-JAVA-100058: Exception occurred while trying to obtain the Java Global Instance resource reference [%1]: %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get the **Java Global Instance** resource referenced by this activity.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100059: The Java Global Instance resource [%1] referenced by this activity is not found in the repository.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The repository does not contain the **Java Global Instance** resource referenced by this activity.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100060: The Java Global Instance resource [%1] referenced by this activity contains invalid field values.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The **Java Global Instance** resource referenced by this activity contains invalid field values.
- **Resolution:** Please correct the error and retry.

BW-JAVA-100061: Configuration error. The Java class name specified in this JavaMethod activity does not match the Java class name specified in the Java Global Instance resource [%1].

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Java Global Instance resource referenced by this **JavaMethod** activity contains different Java class name then the Java class name specified in the **JavaMethod** activity.
- **Resolution:** Please reconfigure the **JavaMethod** activity.

BW-JAVA-100062: Configuration error. The library specified in this JavaMethod activity does not match the library specified in the Java Global Instance resource [%1].

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The Java Global Instance resource referenced by this **JavaMethod** activity contains different library value then the library value specified in the **JavaMethod** activity.
- **Resolution:** Please reconfigure the **JavaMethod** activity.

BW-JAVA-100063: Runtime error. Illegal onEvent(Object output)/onError (Throwable error) method call. OnEvent/OnError method must not be called in the init method or during the initialization phase.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The onEvent(Object output) method must never be called in the init() method. The BW engine is in the middle of initializing the Java Event Source activity.
- **Resolution:** Please remove the onEvent(Object output) method call in the init method.

BW-JAVA-100064: Runtime error. Unable to generate notification events.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The error occurs when the JavaProcessStarter is unable to generate notification data due un-availability of a resource.
- **Resolution:** Please check the JavaProcessStarter component for resource errors.

BW-JAVA-100065: Runtime error. The output type defined by the getOutputObjectType() does not match with the type that is passed in to onEvent(Object object).

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** This exception is thrown if the getOutputObjectType() method defines the type of the output object that is not the same as object type passed to onEvent (Object object) method in case of "Convert Output Object To XML" flag being set.
- **Resolution:** Please make sure that object passed to onEvent(Object output) method is of the same type as that which is returned by getOutputObjectType().

JDBC Error Codes

This section describes error codes that can be returned by activities in the JDBC palette.

BW-JDBC-100000: Failed to find or create the JDBC driver : %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Failed to find or create the JDBC driver.
- **Resolution:** Check the CLASSPATH and/or JDBC driver specification.

BW-JDBC-100001: Missing SQL statement

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Missing SQL statement.
- **Resolution:** Specify the SQL statement.

BW-JDBC-100002: Some or all of the prepared parameters do not have data types specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Some or all of the prepared parameters do not have data types specified.
- **Resolution:** Make sure all the prepared parameters have data types specified.

BW-JDBC-100003: A JDBC driver that supports metadata access is required

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** A JDBC driver that supports metadata access is required.
- **Resolution:** Use a JDBC driver which allows metadata access.

BW-JDBC-100004: This is not a valid SQL type: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Data type specified is not a valid SQL type.
- **Resolution:** Specify a valid SQL data type.

BW-JDBC-100005: You must select a JDBC Connection shared configuration resource

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** You must select a JDBC Connection shared configuration resource.
- **Resolution:** Select a JDBC Connection shared configuration resource.

BW-JDBC-100006: Cannot find shared JDBC configuration: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot find shared JDBC configuration.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100007: Cannot find Tlbase.jar in the classpath

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot find Tlbase.jar in the classpath.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100008: Improper SQL statement used. %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Improper SQL statement used. Details provided.
- **Resolution:** Correct and provide proper SQL statement.

BW-JDBC-100009: Cannot load JDBC Driver: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot load specified JDBC Driver.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100010: Duplicate field name found '%1', please modify the query and create unique aliases for duplicate fields

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Duplicate field name found, please modify the query and create unique aliases for duplicate fields.
- **Resolution:** Modify the query and create unique aliases for duplicate fields.

BW-JDBC-100011: At least one parameter must have a value

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** At least one parameter must have a value.
- **Resolution:** Set a value for any parameter.

BW-JDBC-100012: %1 is not a valid timezone. Please either choose a timezone from the list provided in the Constants tab or refer to the list of valid timezones in the documentation

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid timezone specified. Please either choose a timezone from the list provided in the Constants tab or refer to the list of valid timezones in the documentation.
- **Resolution:** Please either choose a timezone from the list provided in the Constants tab or refer to the list of valid timezones in the documentation.

BW-JDBC-100013: JDBC plugin initialization failed: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JDBC plugin initialization failed. Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100014: JDBC error reported: (SQLState = %1) - %2

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JDBC error reported. Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100015: JDBC plugin evaluation error: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JDBC plugin evaluation error. Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100016: No JDBC connection available

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** No JDBC connection available.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100017: Failed to create input and/or output schema(s): %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Failed to create input and/or output schema(s). Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100018: %1 input parameters declared in the SQL statement but no input parameters provided

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Some input parameters declared in the SQL statement but no corresponding input parameters provided.
- **Resolution:** Provide input parameters declared in the SQL statement.

BW-JDBC-100019: Unexpected number of input parameters. %1 declared in the SQL statement but %2 input parameters provided

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Number of input parameters declared in the SQL statement does not match number of input parameters provided.
- **Resolution:** Make sure the number of input parameters declared in the SQL statement match number of input parameters provided.

BW-JDBC-100020: Unexpected input parameters. No input parameter declared in the SQL statement but %1 input parameters provided

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There is no input parameter declared in the SQL statement but some input parameters provided.
- **Resolution:** Remove all the input parameter provided.

BW-JDBC-100021: JDBC plugin configuration error: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JDBC plugin configuration error. Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100022: Global variable %1 not defined

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Specified global variable not defined.
- **Resolution:** Define such global variable.

BW-JDBC-100023: JDBC activity timed out

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JDBC activity timed out.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100024: Invalid procedure name specified. %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid procedure name specified. Details provided.
- **Resolution:** Provide a valid stored procedure name.

BW-JDBC-100025: Unable to obfuscate password. %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Unable to obfuscate password. Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100026: Unable to deobfuscate password. %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Unable to deobfuscate password. Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100027: %1 is not a valid SQL statement. It does not generate any output schema. Please press 'Fetch' button to (re)fetch output schema or correct the SQL statement

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid SQL statement specified. It does not generate any output schema. Please press 'Fetch' button to (re)fetch output schema or correct the SQL statement.
- **Resolution:** Please press 'Fetch' button to (re)fetch output schema or correct the SQL statement.

BW-JDBC-100028: Invalid procedure name specified. It can not be null

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid procedure name specified. It can not be null.
- **Resolution:** Provide a valid stored procedure name.

BW-JDBC-100029: The JNDI Configuration reference [%1] not found

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The JNDI Configuration reference specified not found.
- **Resolution:** Provide a valid JNDI Configuration reference.

BW-JDBC-100030: The JNDI Configuration reference [%1] not found in repository

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The JNDI Configuration reference specified not found in repository.
- **Resolution:** Provide a valid JNDI Configuration reference.

BW-JDBC-100031: The JNDI Configuration reference [%1] contains incorrect field values

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The JNDI Configuration reference specified contains incorrect field values
- **Resolution:** Check and correct specified JNDI Configuration reference.

BW-JDBC-100032: Exception occurred while trying to obtain the JNDI Configuration reference [%1]: %2

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Exception occurred while trying to obtain the JNDI Configuration reference. Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100033: Configuration Test Failed. %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Configuration Test Failed. Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100034: Configuration Test Failed. Exception [%1] occurred.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Configuration Test Failed. Exception occurred. Details provided.
- **Resolution:** Please Contact TIBCO Support.

BW-JDBC-100035: Invalid object looked up, must be either DataSource or XADataSource: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid object looked up, must be either DataSource or XADataSource. JNDI lookup name provided.
- **Resolution:** Make sure JNDI lookup name bound to either DataSource or XADataSource object.

BW-JDBC-100036: JNDI look up failed, object is null: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JNDI look up failed, object is null. JNDI lookup name provided.
- **Resolution:** Make sure JNDI look up returns not null object.

BW-JDBC-100037: Batch updates failed on update number: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Batch updates failed on provided update numbers.
- **Resolution:** Resolve these individual updates.

BW-JDBC-100038: Can't participate in this transaction group. Correct JDBC Connection type or enable [Override Transaction Behavior]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Can't participate in this transaction group. Correct JDBC Connection type or enable [Override Transaction Behavior].
- **Resolution:** Correct JDBC Connection type or enable [Override Transaction

Behavior].

BW-JDBC-100039: JDBC Connection Login timed out

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JDBC Connection Login timed out.
- **Resolution:** Increase login timeout.

BW-JDBC-100040: Invalid timeout value [%1]. The value must be an integer greater than or equal to '0'

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid timeout value specified. The value must be an integer greater than or equal to '0'.
- **Resolution:** Set timeout to an integer greater than or equal to '0'.

JMS Error Codes

This section describes error codes that can be returned by activities in the JMS palette.

BW-JMS-100000: Invalid configuration data: JMS connection reference is not specified.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JMS connection reference is not specified in configuration data.
- **Resolution:** Specify a valid JMS connection reference in activity configuration.

BW-JMS-100002: Invalid configuration data: specified connection reference not found in repository.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The specified JMS connection reference is not found in repository. [%1-connection reference].
- **Resolution:** Make sure that the connection reference specified in activity configuration refers to a valid shared JMS connection.

BW-JMS-100003: Invalid configuration data: JNDI context URL is not specified.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JNDI context URL is not specified in the shared JMS connection. [%1-shared connection data].
- **Resolution:** Specify a valid JNDI context URL in the specified shared JMS

connection.

BW-JMS-100004: Invalid configuration data: JNDI initial context factory is not specified.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JNDI initial context factory is not specified in the shared JMS connection. [%1-shared connection data].
- **Resolution:** Specify a valid JNDI initial context factory in the specified shared JMS connection.

BW-JMS-100005: Could not create connection with JMS server.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a connection with JMS server[%1-connection key data].
- **Resolution:** Look at the exception for more information.

BW-JMS-100006: Could not create a session to receive messages.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a session to receive messages [%1-configuration data].
- **Resolution:** Look at the exception for more information.

BW-JMS-100007: Could not create a reply session/producer.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a reply producer [%1-

configuration data].

- **Resolution:** Look at the exception for more information.

BW-JMS-100008: JNDI lookup of queue name [%1] failed.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JNDI lookup of queue name [%1] failed.
- **Resolution:** Look at the exception for more information. Make sure that the queue has been setup in your JMS provider.

BW-JMS-100009: Cannot retrieve queue with name [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot retrieve queue with name [%1].
- **Resolution:** Make sure that the queue has been setup in your JMS provider.

BW-JMS-100010: Error creating JNDI initial context [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot create JNDI initial context [%1 - connection key data].
- **Resolution:** Look at the exception for more information.

BW-JMS-100011: JNDI lookup of topic name [%1] failed.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JNDI lookup of topic name [%1] failed.
- **Resolution:** Look at the exception for more information. Make sure that the topic has been setup in your JMS provider.

BW-JMS-100012: Cannot retrieve topic with name [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot retrieve topic with name [%1].
- **Resolution:** Make sure that the topic has been setup in your JMS provider.

BW-JMS-100013: Error creating dynamic queue with name [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error creating dynamic queue with name [%1].
- **Resolution:** Look at the exception for more information. Also refer to your JMS provider documentation.

BW-JMS-100014: Error creating dynamic topic with name [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error creating dynamic topic with name [%1].
- **Resolution:** Look at the exception for more information. Also refer to your JMS provider documentation.

BW-JMS-100015: Could not create queue message receiver.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a queue receiver [%1-configuration data].
- **Resolution:** Look at the exception for more information.

BW-JMS-100016: Could not create queue message receiver.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a queue receiver [%1-Destination].
- **Resolution:** Look at the exception for more information.

BW-JMS-100017: Could not create durable topic message subscriber.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a durable topic message subscriber.[%1-configuration data].
- **Resolution:** Look at the exception for more information.

BW-JMS-100018: Could not create topic message subscriber.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a topic message subscriber.[%1-configuration data].
- **Resolution:** Look at the exception for more information.

BW-JMS-100019: Could not create topic message subscriber.[%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a topic message subscriber.[%1-Destination].
- **Resolution:** Look at the exception for more information.

BW-JMS-100020: There was an error when attempting to receive a message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to receive a message.
- **Resolution:** Look at the exception for more information.

BW-JMS-100021: There was an error in onMessage callback for a received message of type [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error in onMessage callback for a received message of type [%1].
- **Resolution:** Look at the exception for more information.

BW-JMS-100022: Received a message of type [%1] but configured to receive messages of type [%2].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The message type of received message does not match the configured message type.
- **Resolution:** Make sure that the JMS message type is configured correctly in the activity configuration.

BW-JMS-100023: There was an error while parsing the reply message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while parsing the reply message.
- **Resolution:** Look at the exception for more information.

BW-JMS-100024: There was an error when attempting to confirm a message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to confirm a message.
- **Resolution:** Look at the exception for more information.

BW-JMS-100026: JMS message type [%1] is not valid.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JMS message type [%1] is not valid.
- **Resolution:** Internal error.

BW-JMS-100027: Error creating temporary queue for reply.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error creating temporary queue topic for reply.
- **Resolution:** Look at the exception for more information.

BW-JMS-100028: Error creating temporary topic for reply.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error creating temporary topic for reply.
- **Resolution:** Look at the exception for more information.

BW-JMS-100029: Could not create a reply receiver.[Destination=%1]

- **Role:** errorRole

- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a reply receiver. [Destination=%1].
- **Resolution:** Look at the exception for more information.

BW-JMS-100030: There was an error when attempting to send a request message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to send a request message.
- **Resolution:** Look at the exception for more information.

BW-JMS-100031: There was an unexpected error.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an unexpected error.
- **Resolution:** Look at the exception for more information.

BW-JMS-100032: There was an unexpected error.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an unexpected error.
- **Resolution:** Look at the exception for more information.

BW-JMS-100033: Unkown state in request/reply processing [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an unexpected error [%1-closure].

- **Resolution:** Look at the exception for more information.

BW-JMS-100034: There was an error while cancelling.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while cancelling.
- **Resolution:** Look at the exception for more information.

BW-JMS-100035: Received a null reply message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Received a null reply message.
- **Resolution:** Look at the exception for more information.

**BW-JMS-100036: Could not create a session to send request messages.
[ConnectionKey=%1, Transacted=%2, AckMode=%3]**

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a session to send request messages [ConnectionKey=%1, Transacted=%2, AckMode=%3].
- **Resolution:** Look at the exception for more information.

**BW-JMS-100037: Could not create a session to receive reply messages.
[ConnectionKey=%1, Transacted=%2, AckMode=%3]**

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a session to send reply messages [ConnectionKey=%1, Transacted=%2, AckMode=%3].

- **Resolution:** Look at the exception for more information.

BW-JMS-100038: Could not create a session to send messages.

[ConnectionKey=%1, Transacted=%2, AckMode=%3]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to create a session to send messages [ConnectionKey=%1, Transacted=%2, AckMode=%3].
- **Resolution:** Look at the exception for more information.

BW-JMS-100039: There was an unexpected error while sending a message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an unexpected error while sending a message.
- **Resolution:** Look at the exception for more information.

BW-JMS-100040: There was an unexpected error while sending a reply.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an unexpected error while sending a reply.
- **Resolution:** Look at the exception for more information.

BW-JMS-100041: There was an internal error when attempting setReady.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an internal error when attempting setReady.
- **Resolution:** Look at the exception for more information.

BW-JMS-100042: There was an error while sending a message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while sending a message.
- **Resolution:** Look at the exception for more information.

BW-JMS-100043: There was an error while parsing a message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while parsing a message.
- **Resolution:** Look at the exception for more information.

BW-JMS-100044: There was an error while parsing the JMS schema.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while parsing the JMS schema.
- **Resolution:** This is an internal error.

BW-JMS-100045: There was an error while parsing the JMS schema.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while parsing the JMS schema.
- **Resolution:** This is an internal error.

BW-JMS-100046: There was an error while parsing the JMS schema.

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** There was an error while parsing the JMS schema.
- **Resolution:** This is an internal error.

BW-JMS-100047: There was an error while parsing data to build a message: attributes are not allowed.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while parsing data to build a message: attributes are not allowed.
- **Resolution:** This is an internal error.

BW-JMS-100048: There was an error while parsing data to build a message: mixed text not allowed.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while parsing data to build a message: mixed text not allowed.
- **Resolution:** This is an internal error.

BW-JMS-100049: JMS message priority [%1] in input bind is not valid.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JMS message priority [%1] in input bind is not valid.
- **Resolution:** A valid JMS message priority must be a number between 0 and 9 (inclusive).

BW-JMS-100050: Invalid JMS Application Properties [%1].

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** JMS application properties are not valid. See [%1-exception] for more details.
- **Resolution:** Verify that JMS application properties are correct. This can be done by using 'validate for deployment' feature of the Designer.

BW-JMS-100051: Invalid message body schema specified [%1] [%2].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The schema [%1] to define message body is not valid. See [%2-exception] for more details.
- **Resolution:** Check the message body schema specified.

BW-JMS-100052: Invalid JMS message type specified [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The JMS message type [%1] is not valid.
- **Resolution:** Pick a valid JMS message type.

BW-JMS-100053: An internal error occurred while processing configuration data [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** An internal error occurred while processing configuration data. See [%1-exception] for more details.
- **Resolution:** Check the exception for more details.

BW-JMS-100054: Invalid input data.

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Input data is invalid. See the exception for more details.
- **Resolution:** Check activity input data.

BW-JMS-100055: Error creating JMS message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while creating a JMS message. See the exception for more details.
- **Resolution:** Check activity input data. See the exception for more details.

BW-JMS-100056: Invalid configuration data: message body schema is not specified.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid configuration data: no schema specified for message body.
- **Resolution:** Specify a schema to represent the message body in the **Input Editor** or **Output Editor** tab.

BW-JMS-100057: Invalid configuration data: destination %1 name is not specified.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid configuration data: destination name is not specified.
- **Resolution:** Specify name of the topic or queue destination in **Configuration** tab.

BW-JMS-100058: Invalid configuration data: reply to is not specified.

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Invalid configuration data: reply to is not specified.
- **Resolution:** Pick the reply target in **Configuration** tab.

BW-JMS-100059: Cannot create connection factory in a provider-specific way.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot create connection factory in a provider-specific way. Use JNDI lookup instead.
- **Resolution:** Please use TIBCO Enterprise for JMS. Otherwise use JNDI to lookup connection factory.

BW-JMS-100060: Invalid configuration data: message body schema is not specified in 'Input Editor' tab.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid configuration data: no schema specified for the request message body in **Input Editor** tab.
- **Resolution:** Specify a schema to represent the request message body in the **Input Editor** tab.

BW-JMS-100061: Invalid configuration data: message body schema is not specified in 'Output Editor' tab.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Invalid configuration data: no schema specified for the reply message body in the **Output Editor** tab.
- **Resolution:** Specify a schema to represent the reply message body in the **Output Editor** tab.

BW-JMS-100062: Invalid message body schema specified in 'Input Editor' tab [%1] [%2].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The schema [%1] to define the request message body in **Input Editor** tab is not valid. See [%2-exception] for more details.
- **Resolution:** Check the request message body schema specified in **Input Editor** tab.

BW-JMS-100063: Invalid message body schema specified in 'Output Editor' tab [%1] [%2].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The schema [%1] to define the reply message body in the **Output Editor** tab is not valid. See [%2-exception] for more details.
- **Resolution:** Check the reply message body schema specified in the **Output Editor** tab.

BW-JMS-100064: Could not decrypt password.[%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while decrypting a password. See [%1-exception] for more details.
- **Resolution:** Make sure that the password stored in the repository is not in clear text.

BW-JMS-100065: Can't create XAResource.Check if the ConnectionFactory [%1] is XA enabled.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Can't create XAResource.Check if the ConnectionFactory [%1] is XA

enabled.

- **Resolution:** Check if the ConnectionFactory [%1] is XA enabled.

BW-JMS-100066: JNDI lookup failed for queue with name [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JNDI lookup failed for queue with name [%1].
- **Resolution:** Look at the exception for more information. Also refer to your JMS provider documentation.

Mail Error Codes

This section describes error codes that can be returned by activities in the Mail palette.

BW-MAIL-100001: Invalid input data: mail server host not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Host name of mail server is not specified.
- **Resolution:** Specify a valid mail server host in configuration.

BW-MAIL-100002: Invalid input data: username not specified.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Username for mail server account is not specified.
- **Resolution:** Specify a valid user name in configuration.

BW-MAIL-100003: Invalid input data: password not specified.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Password for mail server account is not specified.
- **Resolution:** Specify a valid password in configuration.

BW-MAIL-100004: Invalid input data: Null input data.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Input data is null.

- **Resolution:** Check activity input data.

BW-MAIL-100005: Invalid input data: Error parsing input data.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Input data is invalid.
- **Resolution:** Check activity input data.

BW-MAIL-100006: Invalid input data: Unequal number of attachment names and attachment data.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Number of attachment names and attachment data specified in the input are unequal.
- **Resolution:** Check attachment input data.

BW-MAIL-100007: Invalid input data: Both the comma and semicolon cannot be used at same time to separate addresses.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Both the comma and semicolon cannot be used at same time to separate addresses.
- **Resolution:** Use either comma or semicolon for separating addresses.

BW-MAIL-100008: Mail provider for protocol [%1] not found. Make sure that the provider jar is in java classpath.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Could not initialize the mail provider for specified protocol: [mail

protocol].

- **Resolution:** Make sure that the mail provider jar file is in java classpath.

BW-MAIL-100009: Error connecting to the mail server using connection parameters: [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Could not establish connection to the mail server using sepecified parameters: [parameters].
- **Resolution:** Check configuration data.

BW-MAIL-100010: The default mail folder was not found on mail server.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The default mail folder was not found on mail server.
- **Resolution:** Check mail server setup.

BW-MAIL-100011: The INBOX mail folder was not found on mail server.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The INBOX mail folder was not found on mail server.
- **Resolution:** Check mail server setup.

BW-MAIL-100012: Error getting folder on mail server.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error getting folder on mail server.
- **Resolution:** Check mail server setup.

BW-MAIL-100013: Error closing mail server connection.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting close connection with mail server.
- **Resolution:** Look at the exception for more information.

BW-MAIL-100014: Error while polling mail server: cannot open INBOX folder.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to open connection with mail server.
- **Resolution:** Look at the exception for more information.

BW-MAIL-100015: Error while polling mail server: cannot close INBOX folder.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error when attempting to close connection with mail server.
- **Resolution:** Look at the exception for more information.

BW-MAIL-100016: Unexpected error while polling mail server.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an unexpected error while retrieving mails.
- **Resolution:** Look at the exception for more information.

BW-MAIL-100017: Error parsing received mail.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while parsing a new mail message received.
- **Resolution:** Look at the exception for more information.

BW-MAIL-100018: Error building mail message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while building a mail message to send.
- **Resolution:** Look at the exception for more information.

BW-MAIL-100019: Error sending mail message.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error sending mail message. Cause: %1.
- **Resolution:** Look at the exception for more information.

BW-MAIL-100020: Error connecting to the mail server - unknown host; connection parameters: [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Could not establish connection to the mail server - specified host is unknown: [%1 - connection parameters].
- **Resolution:** Specify a valid mail server host in configuration or check your network connections and setup.

BW-MAIL-100021: Error connecting to the mail server - connect exception; connection parameters: [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Could not establish connection to the mail server - connect exception: [%1 - connection parameters].
- **Resolution:** Verify that your mail server is running or check your network connections.

BW-MAIL-100022: An internal error occurred while processing configuration data [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** An internal error occurred while processing configuration data. See [%1-exception] for more details.
- **Resolution:** Check the exception for more details.

BW-MAIL-100023: Invalid polling interval [%1] [%2].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Specified polling interval [%1] is not valid. See [%2-exception] for more details.
- **Resolution:** Specify a valid polling interval.

BW-MAIL-100024: Could not resolve mail server host name [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The specified host name of mail server [%1] cannot be resolved.
- **Resolution:** Use a valid mail server host name. If the host name is valid, make sure

the network naming (DNS) is properly setup.

BW-MAIL-100025: Could not decrypt password [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while decrypting a password. See [%1-exception] for more details.
- **Resolution:** Make sure that the password stored in the repository is not in clear text.

BW-MAIL-100026: Could not connect to mail server - invalid username in field [%1] and/or invalid password in field [%2].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Got authentication error while connecting to mail server.
- **Resolution:** Make sure that the username and password are correct.

BW-MAIL-100027: %1 Start time = %2 End time= %3 Processing time= %4

- **Role:** infoRole
- **Category:** BW-Plugin
- **Description:** %1 Start time = %2 End time= %3 Processing time= %4
- **Resolution:** none

BW-MAIL-100028: %1 Processing times: %2

- **Role:** infoRole
- **Category:** BW-Plugin
- **Description:** %1 Processing times: %2
- **Resolution:** none

BW-MAIL-100029: Using POP3 Provider from %1

- **Role:** infoRole
- **Category:** BW-Plugin
- **Description:** Using POP3 Provider from %1
- **Resolution:** none

BW-MAIL-100030: Username can not be null when Authentication is on

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Username can not be null when Authentication is on.
- **Resolution:** Make sure that the username and password are correct.

BW-MAIL-100031: Password can not be null when Authentication is on

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Password can not be null when Authentication is on.
- **Resolution:** Make sure that the username and password are correct.

BW-MAIL-100032: Mail is already deleted, Receive Mail activity has 'Delete Mail' turned on

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Mail is already deleted, Receive Mail activity has **Delete Mail** turned on.
- **Resolution:** Either turn off **Delete Mail** in Mail Receiver or do not use **Confirm** activity.

BW-MAIL-100033: Error building mail message. Cause: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There was an error while building a mail message to send.
- **Resolution:** Look at the exception for more information.

Manual Work Error Codes

This section describes error codes that can be returned by activities in the Manual Work palette.

BW-Inconcert-100000: Server Connection Reference not set.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Server Connection Reference not set.
- **Resolution:** Please Contact TIBCO Support

BW-Inconcert-100001: Cannot find shared connection resource: %1.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot find shared connection resource: %1.
- **Resolution:** Please Contact TIBCO Support

BW-Inconcert-100002: Work details reference not set.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Work details reference not set.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100003: Fail to get event manager.

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Fail to get event manager.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100004: Work ID need to be set. Check your input tab to make sure that work ID binded is valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Work ID need to be set. Check your input tab to make sure that work ID binded is valid.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100005: The inconcert user pool selected is empty.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The inconcert user pool selected is empty.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100006: Cannot connect to IC Server.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot connect to IC Server.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100007: Exception caught in assign task activity. Exception Message: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Exception caught in assign task activity.

- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100008: Cannot find work details reference: %1.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot find work details reference: %1.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100009: The server %1 is not configured correctly. Run the batch registry script "mkpcattr.btg" before proceeding.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The server %1 is not configured correctly. Run the batch registry script "mkpcattr.btg" before proceeding.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100010: Failed to locate the ICPLUGIN server %1.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Failed to locate the ICPLUGIN server %1.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100011: JNI libraries required to interact with Ic Server are missing.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** JNI libraries required to interact with Ic Server are missing.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100012: Cannot generate workflow server list.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot generate workflow server list.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100013: Timed out waiting for response.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Timed out waiting for response.
- **Resolution:** Please Contact TIBCO Support

BW-Inconcert-100014: Error in EventManager: %1.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error in EventManager: %1.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100015: Encountered %1 for field %2 when expecting %3.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Encountered %1 for field %2 when expecting %3.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100016: Work Resource cannot be found %1.

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Work Resource cannot be found %1.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100017: Field %1 is already defined in parent schema %2.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Field %1 is already defined in parent schema %2.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100018: Test Workflow connection

- **Role:** infoRole
- **Category:** connection
- **Description:** Test Workflow connection.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100019: Connected to Workflow Server %1.

- **Role:** infoRole
- **Category:** connection
- **Description:** Connected to Workflow Server %1.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100020: The "Extended Details" does not support "Document" fields. All the "Document" fields are ignored.

- **Role:** infoRole
- **Category:** connection
- **Description:** The "Extended Details" does not support "Document" fields. All the "Document" fields are ignored.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100021: Failed to connect to Workflow Server "%1".

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Failed to connect to Workflow Server "%1".
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100022: Error while handling response timeout

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error while handling response timeout.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100023: Exception caught in query document activity.

Exception message: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Exception caught in query document activity.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100024: Exception caught in work status activity.

Exception message: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Exception caught in work status activity.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100025: Exception caught in work action activity.

Exception message: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Exception caught in work action activity.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100026: Error caught in wait work activity. Exception message: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Exception caught in wait work activity.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100027: Reserved word cannot be used in schema:%1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Reserved word cannot be used in schema:%1.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100028: Schema Validation Error

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Schema Validation Error.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100029: Work Name need to be set. Check your input tab to make sure that work Name binded is valid

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Work Name need to be set. Check your input tab to make sure that work Name binded is valid.
- **Resolution:** Please Contact TIBCO Support.

BW-Inconcert-100030: Assign Pool is not set.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Assign Pool is not set.
- **Resolution:** Please Contact TIBCO Support.

Parse Error Codes

This section describes error codes that can be returned by activities in the Parse palette.

BW-PARSE-100000: Cannot find data format schema resource: %1.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot find data format schema resource: %1.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100001: Cannot create schema from data format schema.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot create schema from data format schema.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100002: Exception in parse eval: %1.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Exception in parse eval: %1.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100003: Line length needs to be

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Line length needs to be

- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100004: Hit EOF on row %1 field %2 spanning columns %3 to %4 last row contents was: '%5'

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Hit EOF on row %1 field %2 spanning columns %3 to %4 last row contents was: '%5'
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100005: Input type is not specified.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Input type is not specified.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100006: Please specify the Input type field.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specified the Input type field.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100007: Data format resource not specified.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Data format resource not specified.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100008: Please specify the data format resource.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Please specified the data format resource.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100009: File %1 cannot be opened using encoding method %2

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** File %1 cannot be opened using encoding method %2.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100010: %1 must be specified if %2 is selected.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** %1 must be specified if %2 is selected.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100011: Format Type must be selected.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Format Type must be selected.
- **Resolution:** Please Contact TIBCO Support.

BW-PARSE-100012: Line is too long. Specified Line Delimiter may not match file content.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Line is too long. Specified Line Delimiter may not match file content.
- **Resolution:** Please check your input values.

BW-PARSE-100013: There are not enough data for the number of required fields in a row.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** There are not enough data for the number of required fields in a row.
- **Resolution:** Please check your input values.

TIBCO Rendezvous Error Codes

This section describes error codes that can be returned by activities in the Rendezvous palette.

BW-TIBRV-100000: Cannot create Transport

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot create Transport.
- **Resolution:** Please check the transport configuration.

BW-TIBRV-100001: Error in sending message

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error in sending message.
- **Resolution:** Please Contact TIBCO Support.

BW-TIBRV-100002: Error serializing the message

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error serializing the message.
- **Resolution:** Please Contact TIBCO Support.

BW-TIBRV-100003: Error in sending request

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Error in sending request.
- **Resolution:** Please Contact TIBCO Support.

BW-TIBRV-100004: Error in processing event: [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error in processing event.
- **Resolution:** Please Contact TIBCO Support.

BW-TIBRV-100005: Cannot create TibrvQueue: [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot create TibrvQueue.
- **Resolution:** Please Contact TIBCO Support.

BW-TIBRV-100006: Cannot create rvEventContext: [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot create rvEventContext.
- **Resolution:** Please Contact TIBCO Support.

BW-TIBRV-100007: Cannot create reply listener for subject: [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot create reply listener, for subject: [%1].
- **Resolution:** Please Contact TIBCO Support.

BW-TIBRV-100008: Cannot activate TIBRV listener for subject: [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot activate TIBRV listener for subject: [%1].
- **Resolution:** Please Contact TIBCO Support.

BW-TIBRV-100009: Error in sending reply

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Error in sending reply.
- **Resolution:** Please Contact TIBCO Support.

BW-TIBRV-100010: Reply For-field not set in reply activity

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The **Reply For** field not set in the **Reply** activity.
- **Resolution:** Please set the needed field in the activity.

BW-TIBRV-100011: Cannot reply to [%1]: activity not found in process

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Cannot reply to configured eventsources. It is not found in process.
- **Resolution:** Make sure to have RV-EventSource in the process to which the reply-activity needs to reply.

BW-TIBRV-100012: Transport parameter not specified

- **Role:** errorRole
- **Category:** BW-Plugin

- **Description:** Configure a valid transport reference on the Activity/EventSource.
- **Resolution:** Configure a valid transport reference on the Activity/EventSource.

BW-TIBRV-100013: Subject parameter not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Configure a valid subject-name on the Activity/EventSource.
- **Resolution:** Configure a valid subject-name on the Activity/EventSource.

BW-TIBRV-100014: Daemon Certificate not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Configure a valid daemon certificate in SSL configuration.
- **Resolution:** Configure a valid daemon certificate in SSL configuration.

BW-TIBRV-100015: Identity not specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Configure a valid identity in SSL configuration.
- **Resolution:** Configure a valid identity in SSL configuration.

BW-TIBRV-100016: [%1]

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** The exception will give information for the problem encountered.
- **Resolution:** The exception will give information for the problem encountered.

BW-TIBRV-100017: Reply Subject is not specified.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Specify the reply subject in the configuration/inputdata.
- **Resolution:** Specify the reply subject in the configuration/inputdata.

BW-TIBRV-100018: CM Name is not specified. If omitted, a unique, non-reusable name will be generated for the duration of the transport.

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** CM Name is not specified. If omitted, a unique, non-reusable name will be generated for the duration of the transport.
- **Resolution:** CM Name is not specified. If omitted, a unique, non-reusable name will be generated for the duration of the transport.

BW-TIBRV-100019: Specified Global-Variable is not found for [%1].

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Specified Global-Variable is not found for the attribute.
- **Resolution:** Please specify the initialized Globle-Variable.

BW-TIBRV-100020: Scheduler Weight of 0 is not allowed with the Worker Complete Time

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Scheduler Weight of 0 is not allowed with the Worker Complete Time.
- **Resolution:** Please refer to the documentation for correct combination of values.

BW-TIBRV-100021: Reply not Specified

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Specify the input schema for the **Rendezvous Reply** activity.
- **Resolution:** Specify the input schema for the **Rendezvous Reply** activity.

BW-TIBRV-200001: Rendezvous Subscriber/Wait for Rendezvous Message-exception setting certified output field: [%1], Event-Source-Name: [%2].

- **Role:** warnRole
- **Category:** BW-Plugin
- **Description:** Rendezvous Subscriber or Wait for Rendezvous Message-exception setting certified output field.
- **Resolution:**

BW-TIBRV-200002: Transport selected for the Rendezvous Subscriber/Wait for Rendezvous Message does not support confirm.

- **Role:** warnRole
- **Category:** BW-Plugin
- **Description:** Transport selected for the Rendezvous Subscriber/Wait for Rendezvous Message does not support confirm.
- **Resolution:**

BW-ADVISORY-100000: Advisory listening queue caught exception: %1

- **Role:** errorRole
- **Category:** BW-Plugin
- **Description:** Advisory listening queue caught exception. Exception detail provided.

- **Resolution:** Please Contact TIBCO Support.

BW-ADVISORY-300000: Advisory: %1

- **Role:** infoRole
- **Category:** BW-Plugin
- **Description:** Advisory provided
- **Resolution:** N/A

BW-ADVISORY-300001: Advisory info: %1

- **Role:** infoRole
- **Category:** BW-Plugin
- **Description:** Advisory information provided
- **Resolution:** N/A

SOAP Error Codes

This section describes error codes that can be returned by activities in the SOAP palette.

SOAPPLUGIN-100001: Unable to create Transport

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** Error initializing the transport.
- **Resolution:** Please check the transport configuration.

SOAPPLUGIN-100002: SOAP Envelope is invalid

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The request or response envelope received from the remote host is invalid.
- **Resolution:** Please verify the SOAP envelope.

SOAPPLUGIN-100003: Unable to serialize the SOAP envelope

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:**
- **Resolution:** Please check the input data to this activity and make sure that it is consistent with the WSDL description.

SOAPPLUGIN-100004: Unable to deserialize the SOAP envelope

- **Role:** errorRole
- **Category:** BW_Plugins

- **Description:**
- **Resolution:** Please check the input data to this activity and the make sure that it is consistent with the WSDL description.

SOAPPLUGIN-100005: Unable to process the SOAP envelope

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:**
- **Resolution:** Please check the input data to this activity and the WSDL description.

SOAPPLUGIN-100006: The SOAP processor could not be instantiated

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** This is an internal error.
- **Resolution:** Please contact TIBCO support.

SOAPPLUGIN-100007: The SOAP service is invalid

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** This is an internal error.
- **Resolution:** Please contact TIBCO support.

SOAPPLUGIN-100008: SOAP Envelope has no data

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The request or response message received from the remote server is invalid.
- **Resolution:** Please make sure the endpoint is a valid soap 1.1 server.

SOAPPLUGIN-100009: Error parsing SOAP message

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The request or response message received from the remote server is invalid.
- **Resolution:** Please make sure the endpoint is a valid soap 1.1 server.

SOAPPLUGIN-100010: Error while adding xsi:type attribute

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** Internal error.
- **Resolution:** Please make sure that you are using the supported schema flavor.

SOAPPLUGIN-100011: Part accessor for the message-part not found in the soap envelope

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The request or response message received from the remote server is invalid.
- **Resolution:** Please check the input data to this activity and the make sure that it is consistent with the WSDL description.

SOAPPLUGIN-100012: Unable to send soap reply message

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The remote server may have closed the connection or there is an internal exception.
- **Resolution:** Please correct the connection error.

SOAPPLUGIN-100014: Unable to send reply or fault message. Please check the operation type

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The specified operation may not throw a soap fault or send soap reply.
- **Resolution:** Please make sure that you have an operation which allows reply and fault messages.

SOAPPLUGIN-100016: Unable to convert a soap fault message to activity output

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** This is an internal error occurs when the soap request activity is not initialized.
- **Resolution:** Please contact TIBCO support.

SOAPPLUGIN-100017: Unable to initialize the URL resolvers for builtin services

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** This is an internal error.
- **Resolution:** Please contact TIBCO support.

SOAPPLUGIN-100018: Unable to get the specified resource

- **Role:** errorRole
- **Category:** BW_Plugins
- **Description:** The resource URL or filter may be invalid or there is no resolver for the kind of URL specified.
- **Resolution:** Please specify the correct URL.

SOAPPLUGIN-100019: A security error while trying to load the certificate [%1]

Role: errorRole

Category: BW_Plugins

Description: The certificate path may be invalid or the certificate type is unsupported

Resolution: Please specify the correct path

SOAPPLUGIN-100020: An IO error occurred while trying to load the certificate [%1]

Role: errorRole

Category: BW_Plugins

Description: The certificate path may be invalid or the certificate type is unsupported

Resolution: Please specify the correct path

SOAPPLUGIN-100021: An IO error while trying send soap message [%1]

Role: errorRole

Category: BW_Plugins

Description: SOAP Driver could not send the message

Resolution: Please make sure that you have specified the correct endpoint information

SOAPPLUGIN-100022: An IO error while loading client key [%1]

Role: errorRole

Category: BW_Plugins

Description: The client key path may be invalid or the KEY type is unsupported

Resolution: Please specify the correct path

SOAPPLUGIN-100023: Soap fault message is received

Role: errorRole

Category: BW_Plugins

Description: Fault Details element provides more information

Resolution: Remote server has responded with a soap fault message, it is usually thrown when the input data is invalid or soap server doesn't support the version of the soap message or mandatory soap headers are not specified

SOAPPLUGIN-100024: HTTP error [%1] Message Received

Role: errorRole

Category: BW_Plugins

Description: Please refer to the HTTP specifications for more information about the error code

Resolution:

SOAPPLUGIN-100025: Input data error. Resource path [%1] is invalid

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please correct the resource path in the retrieve resources activity

SOAPPLUGIN-100026: Input data error. Resource filter [%1] is invalid

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify the correct resource filter wsdl, wsil or xsd

SOAPPLUGIN-100027: Message part accessor not found in part [%1]

Role: errorRole

Category: BW_Plugins

Description: The request or response message received from the remote server is invalid

Resolution: Please check the input data to this activity and the make sure that it is consistent with the WSDL description

SOAPPLUGIN-100028: Data not found for resource [%1] using filter [%2]

Role: errorRole

Category: BW_Plugins

Description: The supported filters are wsdl, wsil or xsd. For other filters resourceData may not available as ascii

Resolution: Please correct the resource path in the retrieve resources activity

SOAPPLUGIN-100032: Duplicate soapAction value [%1]

Role: errorRole

Category: BW_Plugins

Description: The soapAction value must be unique accross all Soap Event Sources to correctly dispatch the soap messages

Resolution: Please check other SOAP Event Source activities and make sure that the soapAction is not duplicated

SOAPPLUGIN-100033: Duplicate WSDL Target Namespace value [%1]

Role: errorRole

Category: BW_Plugins

Description: The Target Namespace specified on advanced tab must be unique accross all Soap Event Sources

Resolution: Please check other SOAP Event Source activities and make sure that the Target Namespace is not duplicated

SOAPPLUGIN-100034: Configuration Error. The specified operation name [%1] not found in portType [%2]

Role: errorRole

Category: BW_Plugins

Description: The operation name is invalid

Resolution: Please ensure that the WSDL file has the specified operation name

SOAPPLUGIN-100035: Configuration Error. Transport is not specified for this service

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify a HTTP or HTTPS transport using HTTP Connection resource

SOAPPLUGIN-100036: Configuration Error. SoapAction is not specified for this service

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify a non null SoapAction

SOAPPLUGIN-100037: Configuration Error. Operation style is invalid

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify document or rpc

SOAPPLUGIN-100038: Configuration Error. Use attribute is invalid

Role: errorRole

Category: BW_Plugins

Description:

Resolution: Please specify literal or encoded

SOAPPLUGIN-100039: Configuration Error. The specified operation name [%1] not found in port [%2] in service [%3]

Role: errorRole

Category: BW_Plugins

Description: The operation name is invalid

Resolution: Please ensure that the WSDL file has the specified operation name

SOAPPLUGIN-100040: Configuration Error. The message part [%1] is defined using 'element' attribute instead of 'type'

Role: errorRole

Category: BW_Plugins

Description: Soap encoding rules require the message part to be defined with type attribute

Resolution: Please modify the WSDL message definition to use schema type

SOAPPLUGIN-100041: Configuration Error. Only one message part can be defined using 'type' attribute for document style services in literal encoding

Role: errorRole

Category: BW_Plugins

Description: Document Literal encoding rules require only one message part to be defined with type attribute

Resolution: Please modify the WSDL message definition

SOAPPLUGIN-100042: Configuration Error. All Parts must be defined using either 'type' or 'element'

Role: errorRole

Category: BW_Plugins

Description: Mixing type and element attributes for the message parts is not permitted

Resolution: Please modify the WSDL message definition

SOAPPLUGIN-100043: Configuration Error. Multiple %1 parts defined using same name are not supported

Role: errorRole

Category: BW_Plugins

Description: Local names for two or more parts is same

Resolution: Please modify the headers configuration

SOAPPLUGIN-100044: Runtime error in SOAP service: %1

Role: errorRole

Category: BW_Plugins

Description: This is an internal error

Resolution: Please contact TIBCO support

SOAPPLUGIN-100045: Runtime error in SOAP client: %1

Role: errorRole

Category: BW_Plugins

Description: This is an internal error

Resolution: Please contact TIBCO support

SOAPPLUGIN-100046: Unable to serialize the MIME envelope. Please make sure that mimePart content (binaryContent|textContent|fileName) is consistent with content-type

Role: errorRole

Category: BW_Plugins

Description: Unable to serialize the MIME envelope. Please make sure that mimeType content (binaryContent|textContent|fileName) is consistent with content-type

Resolution: Please make sure that mimeType content (binaryContent|textContent|fileName) is consistent with content-type

SOAPPLUGIN-100047: Unable to dispatch the SOAP message to a Service. The URL/SoapAction specified in the incoming message was invalid.

Role: errorRole

Category: BW_Plugins

Description: Unable to dispatch the SOAP message to a Service. The URL/SoapAction specified in the incoming message was invalid.

Resolution: Please make sure that the client is using an up to date WSDL file

SOAPPLUGIN-100048: An exception with the following message was thrown while deserializing/processing the incoming SOAP message: [%1]

Role: errorRole

Category: BW_Plugins

Description: An exception was thrown while deserializing/processing the incoming SOAP message.

Resolution: Please make sure that the client is using an up to date WSDL file

SOAPPLUGIN-100049: The system cannot find the file specified

Role: errorRole

Category: BW_Plugins

Description: The system cannot find the file specified

Resolution: Please make sure that the specified file exists on the system

SOAPPLUGIN-100501: A java exception has occurred. [%1]

Role: errorRole

Category: BW_Plugins

Description: The configuration or input data of the activity might have caused this error

Resolution: Please correct the errors

SOAPPLUGIN-100502: Illegal Argument exception has occurred. [%1]

Role: errorRole

Category: BW_Plugins

Description: The configuration or input data of the activity might have caused this error

Resolution: Please correct the errors

SOAPPLUGIN-100503: A java exception has occurred while constructing the WSDL file. [%1]

Role: errorRole

Category: BW_Plugins

Description: The configuration or input data of the activity might have caused this error

Resolution: Please correct the errors

SOAPPLUGIN-100504: IO exception has occurred. [%1]

Role: errorRole

Category: BW_Plugins

Description: The configuration or input data of the activity might have caused this error

Resolution: Please correct the errors

SOAPPLUGIN-100505: Unable to create WSDL file due to insufficient configuration

Role: errorRole

Category: BW_Plugins

Description: Provide values for all the mandatory configuration fields marked in the bold font

Resolution: Please correct the errors

TCP Error Codes

This section describes error codes that can be returned by activities in the TCP palette.

BW-TCP-100001: Cannot start TCP Receiver on Host '%1', Port '%2'. Reason: %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot create Server Socket on %1:%2. Reason: %3
- **Resolution:** Please correct the error and retry.

BW-TCP-100002: 'TCP connection' field is required.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** **TCP connection** field is required.
- **Resolution:** Please correct the error and retry.

BW-TCP-100003: Invalid Port; port must be numeric. Error: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Invalid Port; port must be numeric. Error: %1
- **Resolution:** Please correct the error and retry.

BW-TCP-100004: No value specified for the 'data' input field.

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** No value specified for the 'data' input field.
- **Resolution:** Please correct the error and retry.

BW-TCP-100005: Cannot process TCP request. Reason: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Cannot process TCP request. Reason: %1
- **Resolution:** Please correct the error and retry.

BW-TCP-100006: Error reading TCP data. Reason: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error reading TCP data. Reason: %1
- **Resolution:** Please correct the error and retry.

BW-TCP-100007: Unknown separator type: %1.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unknown separator type: %1.
- **Resolution:** Please correct the error and retry.

BW-TCP-100008: Error opening TCP Connection. Reason: %1.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error opening TCP Connection. Reason: %1.
- **Resolution:** Please correct the error and retry.

BW-TCP-100009: Error opening TCP Connection. Reason: Host '%1' unknown

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error opening TCP Connection. Reason: Host '%1' unknown
- **Resolution:** Please correct the error and retry.

BW-TCP-100010: Error reading data. Reason: Bytes to read can not be zero

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error reading data. Reason: Bytes to read can not be zero
- **Resolution:** Please correct the error and retry.

BW-TCP-100011: Error reading data. Reason: Stream has no data, end of stream reached.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error reading data. Reason: Stream has no data, end of stream reached.
- **Resolution:** Please correct the error and retry.

BW-TCP-100012: Exception reading data. Separator '%1' not found in data after reading %2 bytes. Reason: %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception reading data. Separator '%1' not found in data after reading %2 bytes. Reason: %3
- **Resolution:** Please correct the error and retry.

BW-TCP-100013: Exception closing TCP Connection. Reason: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception closing TCP Connection. Reason: %1
- **Resolution:** Please correct the error and retry.

BW-TCP-100014: Could not read from TCP connection. The input connection is either invalid or closed.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Could not read from TCP connection. The input connection is either invalid or closed.
- **Resolution:** Please correct the error and retry.

BW-TCP-100015: Could not write to TCP connection. The input connection is either invalid or closed.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Could not write to TCP connection. The input connection is either invalid or closed.
- **Resolution:** Please correct the error and retry.

BW-TCP-100016: Can not start TCP Receiver on Host='%1',Port='%2'. Another TCP Receiver is already running with the same configuration.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Can not start TCP Receiver on Host='%1',Port='%2'. Another TCP Receiver is already running with the same configuration.
- **Resolution:** Please correct the error and retry.

BW-TCP-100017: Error closing TCP connection. Reason: No connection is available which matches the input connection key

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error closing TCP connection. Reason: No connection is available which matches the input connection key
- **Resolution:** Please correct the error and retry.

BW-TCP-100018: Error writing data. Reason: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error writing data. Reason: %1
- **Resolution:** Please correct the error and retry.

BW-TCP-100019: Error writing data. Reason: Bytes to write can not be zero

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error writing data. Reason: Bytes to write can not be zero
- **Resolution:** Please correct the error and retry.

BW-TCP-100020: Error in configuring field '%1'. Pl. specify comma separated byte values e.g. "0x0A,0x05,0x0c". For valid string representation of byte values, refer to the Javadoc for decode(String nm) method of class java.lang.Byte

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error in configuring field '%1'. Pl. specify comma separated byte values

e.g. "0x0A,0x05,0x0c". For valid string representation of byte values, refer to the Javadoc for `decode(String nm)` method of class `java.lang.Byte`

- **Resolution:** Please correct the error and retry.

BW-TCP-100021: Timeout while reading TCP data

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Timeout while reading TCP data
- **Resolution:** Please correct the error and retry.

Transaction Error Codes

This section describes error codes that can be returned by activities in the Transaction palette.

BW-TRANS-100001: Initialization Error. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:**
- **Resolution:**

BW-TRANS-100002: Get transaction status error. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred while trying to obtain the status of the transaction from the transaction manager.
- **Resolution:**

BW-TRANS-100003: Transaction setRollbackOnly error. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred while trying to mark the transaction for rollback only
- **Resolution:**

BW-TRANS-100004: Unable to obtain the status of the transaction.

Exception [%1] occurred. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred while trying to obtain the status of the transaction.
- **Resolution:**

BW-TRANS-100005: Unable to set the transaction for rollback only.

Exception [%1] occurred. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred while trying to set the transaction for rollback only
- **Resolution:**

BW-TRANS-400000: %1

- **Role:** debugRole
- **Category:** BW_Plugin
- **Description:** Debug Trace Message
- **Resolution:** None

BW-JTATM-100001: Transaction Manager Initialization Error. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:**
- **Resolution:**

BW-JTATM-100002: Unable to obtain the status of the transaction. The method 'UserTransaction.getStatus' raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method 'javax.transaction.UserTransaction.getStatus()'.
- **Resolution:**

BW-JTATM-100003: Unable to set the transaction for rollback only. The method 'UserTransaction.setRollbackOnly' raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method 'javax.transaction.UserTransaction.setRollbackOnly()'.
- **Resolution:**

BW-JTATM-100004: Transaction begin error. The method 'UserTransaction.begin' raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method 'javax.transaction.UserTransaction.begin()'.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JTATM-100005: Transaction commit error. The method 'UserTransaction.commit' raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method

`'javax.transaction.UserTransaction.commit()'`

- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JTATM-100006: Transaction rollback error. The method 'UserTransaction.rollback' raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method `'javax.transaction.UserTransaction.rollback()'`
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JTATM-100007: Unable to set timeout for transaction. The method 'UserTransaction.setTransactionTimeout' raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method `'javax.transaction.UserTransaction.setTransactionTimeout()'`
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JTATM-100008: Unable resume the transaction. The method 'resume' of the JTATM raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method 'resume'.
- **Resolution:**

BW-JTATM-100009: Unable suspend the transaction. The method 'suspend' of the JTATM raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method 'suspend'.
- **Resolution:**

BW-JTATM-100010: XAResource registration error. The method 'registerResource' of the JTATM raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred when trying register XAResource with the Transaction Manager
- **Resolution:**

BW-JTATM-100011: Unable to enlist XAResource with the transaction object. The method 'enlistResource' of the JTATM raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred when trying enlist XAResource with the transaction object
- **Resolution:**

BW-JTATM-100012: Unable to delist XAResource from the transaction object. The method 'delistResource' of the JTATM raised exception [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** Exception occurred when trying delist XAResource from the transaction context
- **Resolution:**

BW-JTATM-100013: The JTA UserTransaction Configuration reference [%1] specified for the Transaction Group contains incorrect field values.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The JTA UserTransaction Configuration activity referenced by this Transaction group contains invalid field values.
- **Resolution:** Please correct the error and retry.

BW-JTATM-100014: Connection Test Failed. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to establish connection to the server.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JTATM-100015: Connection Test Failed. Exception [%1] occurred.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to establish connection to the server. Exception occurred
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JTATM-100016: Java class [%1] not found in the classpath. ClassNotFoundException occurred. %2

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** ClassNotFoundException occurred while trying to access the specified Java class.
- **Resolution:** Please verify that the specified class file is contained in the classpath.

BW-JTATM-100017: Error occurred while trying to obtain the JNDI Configuration shared resource reference [%1]: %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get the shared JNDI Configuration resource referenced by the JTA UserTransaction Configuration
- **Resolution:** Please correct the error and retry.

BW-JTATM-100018: Unable to create an instance of 'javax.naming.InitialContext'. NamingException occurred. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception of type 'javax.naming.NamingException' occurred while trying to construct an instance of 'javax.naming.InitialContext'.
- **Resolution:** Please correct the specified NamingException and retry.

BW-JTATM-100019: Unable to create an instance of 'javax.naming.InitialContext'. Exception [%1] occurred. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred while trying to construct an instance of 'javax.naming.InitialContext'.
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-JTATM-100020: Unable to obtain UserTransaction object for the JNDI name [%1]. NamingException occurred. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception of type 'javax.naming.NamingException' occurred on invocation of the method 'javax.naming.InitialContext.lookup(..)'
- **Resolution:** Please correct the specified NamingException and retry.

BW-JTATM-100021: Unable to obtain the UserTransaction object for the JNDI name [%1]. Exception [%2] occurred. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method 'javax.naming.InitialContext.lookup(..)'
- **Resolution:** Please correct the specified NamingException and retry.

BW-JTATM-400000: %1

- **Role:** debugRole
- **Category:** BW_Plugin
- **Description:** Debug Trace Message
- **Resolution:** None

BW-XATM-100001: Transaction Manager Initialization Error. The method 'init' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:**

- **Resolution:**

BW-XATM-100002: Unable to obtain the status of the transaction. The method 'getStatus' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the Transaction Manager's getStatus method
- **Resolution:**

BW-XATM-100003: Unable to set the transaction for rollback only. The method 'setRollbackOnly' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the Transaction Manager's setRollbackOnly method.
- **Resolution:**

BW-XATM-100004: Transaction begin error. The method 'begin' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the Transaction Manager's begin method
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-XATM-100005: Transaction commit error. The method 'commit' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the Transaction Manager's commit method
- **Resolution:** Please correct the error stated in the exception message and retry.
- BW-XATM-100006: Transaction rollback error. The method 'rollback' of the [%1] Transaction Manager raised exception [%2]. %3
- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the TransactionManager's rollback method
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-XATM-100007: Unable to set timeout for transaction. The method 'setTransactionTimeout' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the Transaction Manager's setTransactionTimeout method
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-XATM-100008: Unable resume the transaction. The method 'resume' of the [%1] Transaction Manager's exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the TransactionManager's resume

method.

- **Resolution:**

BW-XATM-100009: Unable suspend the transaction. The method 'suspend' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the Transaction Manager's suspend method.
- **Resolution:**

BW-XATM-100010: XAResource registration error. The method 'registerResource' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred when trying register XAResource with the Transaction Manager
- **Resolution:**

BW-XATM-100011: Unable to enlist XAResource with the transaction object. The method 'enlistResource' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred when trying enlist XAResource with the transaction object
- **Resolution:**

BW-XATM-100012: Unable to delist XAResource from the transaction object. The method 'delistResource' of the [%1] Transaction Manager raised exception [%2]. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred when trying delist XAResource from the transaction object
- **Resolution:**

BW-XATM-100013: The XA TransactionManager Configuration reference [%1] specified for the Transaction Group contains incorrect field values.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The XA TransactionManager Configuration activity referenced by this Transaction group contains invalid field values.
- **Resolution:** Please correct the error and retry.

BW-XATM-100014: The XA TransactionManager Configuration reference [%1] not found

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to obtain the specified XA TransactionManager Configuration shared resource reference
- **Resolution:** Please correct the error and retry.

BW-XATM-100015: The XA TransactionManager Configuration reference [%1] not found in repository

- **Role:** errorRole
- **Category:** BW_Plugin

- **Description:** The repository does not contain the specified XA TransactionManager Configuration shared resource reference
- **Resolution:** Please correct the error and retry.

BW-XATM-100016: Exception occurred while trying to obtain the XA TransactionManager Configuration reference [%1]: %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to obtain the XA TransactionManager Configuration shared resource reference
- **Resolution:** Please correct the error and retry.

BW-XATM-100017: Method [%1] of the [%2] Transaction Manager raised exception [%3]. %4

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Exception occurred on invocation of the method of the Transaction Manager
- **Resolution:** Please correct the error stated in the exception message and retry.

BW-XATM-100018: Invalid [%1] Transaction Manager reference (XATransactionManager.m_tm == null).

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** XA Transaction Manager reference contains invalid value.
- **Resolution:** Make sure the method "XATransactionManager.setTransactionManager" is called after constructing the custom TransactionManager in the method "XATransactionManager.init".

BW-XATM-100019: ClassNotFoundException occurred during initialization of the [%1] transaction manager. The classpath does not contain the required [%2] transaction manager's class or jar files. %3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** ClassNotFoundException occurred while trying to access the transaction manager's Java class.
- **Resolution:** Please verify that the required transaction manger's java jar or class file is contained in the classpath.

BW-XATM-300001: %1 object store directory: %2

- **Role:** infoRole
- **Category:** BW_Plugin
- **Description:** Location of the transaction manager object store directory
- **Resolution:**

BW-XATM-400000: %1

- **Role:** debugRole
- **Category:** BW_Plugin
- **Description:** Debug Trace Message
- **Resolution:** None

XML Error Codes

This section describes error codes that can be returned by activities in the XML Activities palette.

BW-XML-000000: Internal error occurred. Class=%1, Method=%2, Reason=%3

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Internal error occurred
- **Resolution:** Please Contact TIBCO Support.

BW-XML-100001: Activity configuration error. %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** This activity is not configured correctly
- **Resolution:** Please correct the error and retry.

BW-XML-100002: Unable to get value for the global variable [%1]. %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get value for the specified global variable
- **Resolution:** Make sure that the specified global variable is defined.

BW-XML-100003: Invalid global variable. The global variable [%1] may not have been defined.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Unable to get value for the specified global variable
- **Resolution:** Make sure that the specified global variable is defined.

BW-XML-100004: An error occurred while serializing the XML: %1

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** An error occurring while serializing the XML.
- **Resolution:** Please correct.

BW-XML-100005: An error occurred while parsing: %1.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error occurred while parsing.
- **Resolution:** Examine input for validity.

BW-XML-100006: The [%1] occurred during XSLT transformation: %2

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error occurred during XSLT transformation.
- **Resolution:** Examine input for validity.

BW-XML-100007: No stylesheet for XSLT transformation

- **Role:** errorRole

- **Category:** BW_Plugin
- **Description:** No stylesheet for XSLT transformation
- **Resolution:** Examine input for validity.

BW-XML-100008: The selected encoding [%1] is not valid.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The selected encoding is invalid.
- **Resolution:** Please use a valid encoding.

BW-XML-100009: Encoding error occurred: %1.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Error occurred while encoding.
- **Resolution:** Please ensure that selected encoding is legal.

BW-XML-100010: The encoded bytes content is empty.

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** Content cannot be empty.
- **Resolution:** Please ensure that the content is not empty.

BW-XML-100011: [%1]

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:**
- **Resolution:**

BW-XML-100012: The input document's root element [%1] does not match the desired output's root element [%2].

- **Role:** errorRole
- **Category:** BW_Plugin
- **Description:** The output type doesn't match the root of the input document.
- **Resolution:** Either modify the incoming document or change the output mapping to accurately reflect that document's contents.

BW-XML-100501: Using the old XML render code

- **Role:** infoRole
- **Category:** BW_Plugin
- **Description:** Using the old XML render code
- **Resolution:**

BW-XML-100502: Using the optimized XML render code

- **Role:** infoRole
- **Category:** BW_Plugin
- **Description:** Using the optimized XML render code
- **Resolution:**

TIBCO Product Documentation and Support Services

For information about this product, you can read the documentation, contact TIBCO Support, and join TIBCO Community.

How to Access TIBCO Documentation

Documentation for TIBCO products is available on the [Product Documentation website](#), mainly in HTML and PDF formats.

The [Product Documentation website](#) is updated frequently and is more current than any other documentation included with the product.

Product-Specific Documentation

The following documentation for this product is available on the [TIBCO ActiveMatrix BusinessWorks™ Product Documentation](#) page:

- *TIBCO ActiveMatrix BusinessWorks™ Release Notes*
- *TIBCO ActiveMatrix BusinessWorks™ Administration*
- *TIBCO ActiveMatrix BusinessWorks™ Concepts*
- *TIBCO ActiveMatrix BusinessWorks™ Error Codes*
- *TIBCO ActiveMatrix BusinessWorks™ Getting Started*
- *TIBCO ActiveMatrix BusinessWorks™ Installation*
- *TIBCO ActiveMatrix BusinessWorks™ Palette Reference*
- *TIBCO ActiveMatrix BusinessWorks™ Process Design*

To directly access documentation for this product, double-click the following file:

`TIBCO_HOME/release_notes/TIB_<productID>_version_docinfo.html`

where *TIBCO_HOME* is the top-level directory in which TIBCO products are installed. On Windows, the default *TIBCO_HOME* is C:\tibco. On UNIX systems, the default *TIBCO_HOME* is /opt/tibco.

Other TIBCO Product Documentation

When working with ActiveMatrix BusinessWorks, you may find it useful to read the documentation of the following TIBCO products:

- TIBCO Designer™: *TIBCO Designer is an easy to use graphical user interface for design-time configuration of TIBCO applications. TIBCO Designer includes online help for each palette.*
- TIBCO Runtime Agent™: *TRA supplies a number of TIBCO and third-party libraries used by ActiveMatrix BusinessWorks.*
- TIBCO Administrator™: *TIBCO Administrator is the monitoring and managing interface for new-generation TIBCO products such as ActiveMatrix BusinessWorks.*
- TIBCO Rendezvous® : *TIBCO Rendezvous software uses messages to enable distributed application programs to communicate across a wide variety of hardware platforms and programming languages.*

How to Access Related Third-Party Documentation

When working with ActiveMatrix BusinessWorks, you may find it useful to read the documentation of the following third-party products:

How to Contact Support for TIBCO Products

You can contact the Support team in the following ways:

- To access the Support Knowledge Base and getting personalized content about products you are interested in, visit our [product Support website](#).
- To create a Support case, you must have a valid maintenance or support contract with a Cloud Software Group entity. You also need a username and password to log in to the [product Support website](#). If you do not have a username, you can request one by clicking **Register** on the website.

How to Join TIBCO Community

TIBCO Community is the official channel for TIBCO customers, partners, and employee subject matter experts to share and access their collective experience. TIBCO Community offers access to Q&A forums, product wikis, and best practices. It also offers access to extensions, adapters, solution accelerators, and tools that extend and enable customers to gain full value from TIBCO products. In addition, users can submit and vote on feature requests from within the [TIBCO Ideas Portal](#). For a free registration, go to [TIBCO Community](#).

Legal and Third-Party Notices

SOME CLOUD SOFTWARE GROUP, INC. (“CLOUD SG”) SOFTWARE AND CLOUD SERVICES EMBED, BUNDLE, OR OTHERWISE INCLUDE OTHER SOFTWARE, INCLUDING OTHER CLOUD SG SOFTWARE (COLLECTIVELY, “INCLUDED SOFTWARE”). USE OF INCLUDED SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED CLOUD SG SOFTWARE AND/OR CLOUD SERVICES. THE INCLUDED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER CLOUD SG SOFTWARE AND/OR CLOUD SERVICES OR FOR ANY OTHER PURPOSE.

USE OF CLOUD SG SOFTWARE AND CLOUD SERVICES IS SUBJECT TO THE TERMS AND CONDITIONS OF AN AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER AGREEMENT WHICH IS DISPLAYED WHEN ACCESSING, DOWNLOADING, OR INSTALLING THE SOFTWARE OR CLOUD SERVICES (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH LICENSE AGREEMENT OR CLICKWRAP END USER AGREEMENT, THE LICENSE(S) LOCATED IN THE “LICENSE” FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE SAME TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of Cloud Software Group, Inc.

TIBCO, the TIBCO logo, the TIBCO O logo, and are either registered trademarks or trademarks of Cloud Software Group, Inc. in the United States and/or other countries.

Java and all Java based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only. You acknowledge that all rights to these third party marks are the exclusive property of their respective owners. Please refer to Cloud SG’s Third Party Trademark Notices (<https://www.cloud.com/legal>) for more information.

This document includes fonts that are licensed under the SIL Open Font License, Version 1.1, which is available at: <https://scripts.sil.org/OFL>

Copyright (c) Paul D. Hunt, with Reserved Font Name Source Sans Pro and Source Code Pro.

Cloud SG software may be available on multiple operating systems. However, not all operating system platforms for a specific software version are released at the same time. See the “readme” file for the availability of a specific version of Cloud SG software on a specific operating system platform.

THIS DOCUMENT IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. CLOUD SG MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S), THE PROGRAM(S), AND/OR THE SERVICES DESCRIBED IN THIS DOCUMENT AT ANY TIME WITHOUT NOTICE.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "README" FILES.

This and other products of Cloud SG may be covered by registered patents. For details, please refer to the Virtual Patent Marking document located at <https://www.cloud.com/legal>.

Copyright © 2001-2025. Cloud Software Group, Inc. All Rights Reserved.