



# **TIBCO ActiveMatrix® Service Grid**

## Spring Component Development

Version 3.4.3 | February 2025

# Contents

---

<b>Contents</b>	<b>2</b>
<b>Spring Components</b>	<b>4</b>
Creating a Spring Component	4
Updating a Spring Component	5
Component Feature Dependencies	5
Spring Component Reference	7
<b>Spring Component Implementations</b>	<b>10</b>
Spring Bean Configuration Files	11
Data Binding	13
Generating XML Data Binding Classes	14
Data Binding Classes for Abstract and Concrete WSDL Files	15
XML Data Binding Reference	16
Opening a Spring Component Implementation	19
Opening a Spring Bean Implementation	19
Generating a Spring Component Implementation	20
Regenerating a Spring Component Implementation	22
Generate Spring Component Implementation Reference	24
Life Cycle Events	28
Component Context	30
Accessing a Property	30
Accessing a Resource	31
Accessing a Hibernate Resource	32
Accessing a JDBC Resource	34
Accessing JMS Resources	35
Accessing LDAP Connections	37
Accessing SMTP Connections	39

Accessing a Teneo Resource .....	40
Invoking an HTTP Request .....	42
Post Example .....	43
Invoking a Reference Operation .....	49
Error Handling .....	50
Example WSDL File .....	51
SOAPException Reference .....	57
Context Parameters .....	59
Working with Context Parameters .....	63
Endpoint References .....	67
Retrieving an Endpoint Reference .....	67
Creating an Endpoint Reference .....	68
Referencing an External Spring Application .....	70
<b>Custom Features .....</b>	<b>73</b>
Bundles and Plug-in Projects .....	74
Configuring Dependencies on External Java Classes .....	77
Versions .....	79
<b>Default XML to Java Mapping .....</b>	<b>81</b>
<b>TIBCO Documentation and Support Services .....</b>	<b>88</b>
<b>Legal and Third-Party Notices .....</b>	<b>90</b>

# Spring Components

---



Spring components integrate Spring Beans into the TIBCO ActiveMatrix platform.

A Spring component is very similar to Java component, but its implementation can consist of more than one Java class. The classes are specified in a Spring Bean configuration file. Each Spring Bean corresponds to a Java class. In Spring components, each service, reference, and property is associated with a Bean (as opposed to all being associated with the same Java class in the case of Java components).

## Creating a Spring Component

You can create a Spring component by using a wizard or by using a manual procedure.

Choose an option and follow the relevant procedure.

Control	Procedure
Wizard	<ol style="list-style-type: none"><li>1. Create an SOA project selecting the <b>SOA Project from WSDL</b> project type.</li><li>2. In the Component Details page of the wizard, specify <b>Spring</b> for the component implementation type.</li><li>3. Specify code generation details as described in <a href="#">Generate Spring Component Implementation Reference</a></li></ol>
Manual	<ol style="list-style-type: none"><li>1. Create an SOA project of any type.</li><li>2. Open the composite created in the project.</li><li>3.<ul style="list-style-type: none"><li>• Click the Spring icon  in the Palette and click the canvas.</li><li>• Click the canvas and click the Spring icon  in the pop-up toolbar.</li></ul></li><li>4. Generate the Spring implementation as described in <a href="#">Generating a Spring Component Implementation</a></li></ol>

A Spring component is added to the canvas and its implementation is configured.

# Updating a Spring Component

You typically update a component after you have configured its implementation. You can perform the update from the canvas or from the Problems view.

The procedure depends on the control you want to use.

Control	Procedure
Canvas	1. Right-click the component and select <b>Refresh from Implementation</b> .
Canvas	1. Right-click a component and select <b>Quick Fixes &gt; Update Component from Implementation</b> .
Problems View	<ol style="list-style-type: none"><li>1. In the Problems view, right-click an error of the form The component "<i>ComponentName</i>" is out of sync with its implementation and select <b>Quick Fix</b>.</li><li>2. In the Quick Fix dialog, select <b>Update Component from Implementation</b>.</li><li>3. Click <b>Finish</b>.</li></ol>

All the changes made to the component since the implementation was generated are discarded and the component is refreshed from the implementation.

## Component Feature Dependencies


When a component implementation is dependent on a shared library, the feature containing the dependency must be specified in the component's Feature Dependencies table.

By default, a component is configured to depend on the custom features containing:

- The component implementation
- External libraries reference by the component implementation

In both cases, the default version range is set to "[1.0.0.qualifier,1.0.0.qualifier)".

## Dependencies



If the *qualifier* component of a version is set to "qualifier" when you create a DAA, TIBCO Business Studio replaces "qualifier" with a generated qualifier that defaults to a timestamp. The effect is that the application requires that the version of the features installed on a node be a perfect match to a version that includes a timestamp.

## External Library Dependencies

It is not possible to know the value of the version's qualifier component for the feature containing an external library when you package the composite. Therefore, if you are using an external library, you should "relax" the version range of the feature containing the library. For example, change the range from "[1.0.0.qualifier,1.0.0.qualifier]" to "[1.0.0,2.0.0)" as shown in the following screenshot.

### Relaxed Feature Dependency



# Spring Component Reference

Field	Description
Project	<p>The name of the Spring plug-in project to contain the implementation.</p> <p>Default: <code>com.sample.spring</code>.</p>
Bean Configuration File	<p>The path to the Spring Bean configuration file relative to the Spring plug-in project.</p> <p>Default: <code>config-compositeName-componentName/compositeName_componentName_beans.xml</code>.</p>
Thread Context Class Loader Type	<p>Configures the value returned by the call <code>Thread.currentThread().getContextClassLoader()</code> inside a Java implementation class (once it is instantiated):</p> <ul style="list-style-type: none"> <li>• <code>component</code> - The thread context class loader is the class loader of the component configured on the composite.</li> <li>• <code>bundle</code> - The thread context class loader is the class loader of the bundle (that is, plug-in) that contains the application context/Spring Beans XML file.</li> <li>• <code>none</code> - A null thread context class loader.</li> </ul> <p>Default:</p>
Field	Description
Compute Component Dependencies	<p>Indicate whether to TIBCO Business Studio - BPM Edition should compute the component bundle dependencies. When a component is deployed on a node, ActiveMatrix Service Grid generates a component bundle. When checked, the component implementation bundles required by the component bundle are computed and identified when you package the composite. When unchecked, the Implementation Dependency and Compute Feature Dependencies fields display and you can manually specify the dependencies.</p> <p>Default:</p>

Field	Description
	<ul style="list-style-type: none"> <li>• New projects - checked.</li> <li>• Legacy projects - unchecked.</li> </ul>
Implementation Dependency	<p>Type of the dependency of the component bundle on the component implementation.</p> <ul style="list-style-type: none"> <li>• Require Bundle - The bundle containing the component implementation is declared as a required bundle. When selected, the <b>Bundle Name</b> field appears.</li> <li>• Import Package - The package exported by the component implementation is declared as an imported package. When selected, the <b>Import Package</b> field displays.</li> </ul> <p>Default:</p> <ul style="list-style-type: none"> <li>• New projects - Require Bundle.</li> <li>• Legacy projects - Import Package.</li> </ul>
Bundle Name	<p>Symbolic name of the bundle containing the component implementation.</p> <p>Default: The bundle in which the component implementation class is present.</p>
Import Package	<p>Name of the package containing the component implementation.</p> <p>Default: The package in which the component implementation class is present.</p>
Version Range	<p>Versions of the bundle or package that satisfy the component bundle's dependency. When specifying a range for a bundle, you can require an exact match to a version that includes a build qualifier. In contrast, the range for a package is inexact.</p> <p>Default:</p> <ul style="list-style-type: none"> <li>• Bundle - [1.0.0.qualifier,1.0.0.qualifier].</li> <li>• Package - [1.0.0, 2.0.0).</li> </ul>



Field	Description
Compute Feature Dependencies	Indicate whether to compute the features on which the component bundle depends. When unchecked the Feature Dependencies table displays. Default: <ul style="list-style-type: none"><li>• New projects - checked.</li><li>• Legacy projects - unchecked.</li></ul>
Preview	A link that when clicked displays a dialog containing a list of the features on which the component bundle depends.

Field	Description
Compute Feature Dependencies	Indicate whether to compute the features on which the component bundle depends. When unchecked the Feature Dependencies table displays. Default: <ul style="list-style-type: none"><li>• New projects - checked.</li><li>• Legacy projects - unchecked.</li></ul>
Preview	A link that when clicked displays a dialog containing a list of the features on which the component bundle depends.

# Spring Component Implementations

---

A Spring component implementation consists of the abstract and concrete classes that represent the component and the Spring Bean configuration file.

The abstract class defines service method signatures, reference fields and accessor methods, and property fields and accessor methods. The concrete class contains the implementations of the service methods. Spring component implementations are stored in Spring projects.


## Declaring Dependencies on Packages

Normally, if you import packages and do not add them to the manifest, TIBCO Business Studio displays an error. However, if you import any of the `javax.xml.*` or `org.ietf.jgss` packages and do not declare the import in the manifest, TIBCO Business Studio does not display an error because TIBCO Business Studio - BPM Edition resolves those packages from the configured JRE. If you then deploy the application without the declaration in the manifest, the application does not run. Hence, you must ensure that you import `javax.xml` or `org.ietf.jgss` packages in the manifest file.


For example, if you imported the following classes:

```
import javax.xml.XMLConstants;  
import javax.xml.transform.TransformerFactory;
```

The corresponding import packages in the manifest should be:



**i Note:** Each subpackage of `javax.xml` may have a different version:



A screenshot of a Java IDE showing a list of subpackages under the `javax.xml` package. Each entry is preceded by a small icon of a folder with a grid pattern. The list includes the following packages and versions:

- `javax.xml (1.3.0)`
- `javax.xml.bind (2.1.0)`
- `javax.xml.bind.annotation (2.1.0)`
- `javax.xml.bind.annotation.adapters (2.1.0)`
- `javax.xml.bind.attachment (2.1.0)`
- `javax.xml.bind.helpers (2.1.0)`
- `javax.xml.bind.util (2.1.0)`
- `javax.xml.crypto`
- `javax.xml.crypto.dom`
- `javax.xml.crypto.dsig`
- `javax.xml.crypto.dsig.dom`
- `javax.xml.crypto.dsig.keyinfo`
- `javax.xml.crypto.dsig.spec`
- `javax.xml.datatype (1.3.0)`
- `javax.xml.namespace (1.1.0)`
- `javax.xml.parsers (1.3.0)`

## Spring Bean Configuration Files

When you generate the implementation for a Spring component, TIBCO Business Studio - BPM Edition generates the Spring Bean configuration file containing information to access the services, references, and properties of the component.

**i Note:** The only changes you should make to a generated Spring Bean configuration file are to import existing Spring Beans.

## Limitations

Spring Bean configuration files:

- Do not support the `sca:composite` tag (that is, it does not support exposing the Spring application context as a composite).
- Do not support application context XML locations (and their resolution) such as inside JARs or directories.
- Include TIBCO Business Studio - BPM Edition tags, such as `tibco:service-metadata`, are added for supporting TIBCO ActiveMatrix design-time metadata.

The following XML snippets illustrate the contents of a Spring Bean configuration file for a Spring component with a HelloWorld service, Date Manager reference, and a SpringGreeting property.

## Define Namespace

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns="http://www.springframework.org/schema/beans"
xmlns:context="http://www.springframework.org/schema/context"
xmlns:sca="http://www.springframework.org/schema/sca"
xmlns:tibco="http://xsd.tns.tibco.com/2008/amf/extension/spring"
xsi:schemaLocation="http://xsd.tns.tibco.com/2008/amf/extension/spring
http://xsd.tns.tibco.com/schema/sca/tibco-ext-spring-sca.xsd
http://www.springframework.org/schema/sca
http://www.osoa.org/xmlns/sca/1.0/spring-sca.xsd
http://www.springframework.org/schema/context
http://www.springframework.org/schema/context/spring-context.xsd
http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans.xsd">
```

## Bean Definition

```
<bean id="HelloWorldPTBean" class="com.tibco.ns.hello.HelloWorldPTImpl"
destroy-method="destroy" init-method="init">
  <property name="springGreeting" ref="SpringGreeting" />
</bean>
```

## Component Services

Component services are declared in an SCA service tag and tibco:service-metadata tag. For example:

```
<sca:service name="HelloWorldPT" target="HelloWorldPTBean"
type="com.tibco.ns.hello.HelloWorldPT" />
<tibco:service-metadata name="HelloWorldPT"
wsdl-location="/jv.helloworld4.svcs/Service
Descriptors/HelloWorld2.wsdl"
wsdl-interface="http://ns.tibco.com/hello/#HelloWorldPT" />
```

## Component References

The component references are declared in an SCA reference tag and `tibco:reference-metadata` tag. For example:

```
<sca:reference name="DateManagerPT"
type="com.tibco.ns.date.DateManagerPT" />
<tibco:reference-metadata name="DateManagerPT"
    target="HelloWorldPTBean" wsdl-location="/jv.helloworld4.svcs/Service
Descriptors/DateManager.wsdl"
    wsdl-interface="http://ns.tibco.com/date/#DateManagerPT" />
```

## Component Properties

Component properties are declared in an SCA property tag. For example:

```
<sca:property id="SpringGreeting" name="SpringGreeting"
type="java.lang.String" />
</beans>
```

# Data Binding

Data binding is the process of converting objects described in an XML document to Java objects and vice versa. You can generate data binding classes directly from a WSDL or schema document or while generating a Java or Spring component implementation.

TIBCO Business Studio - BPM Edition supports two data binding technologies: [JAXB](#) and [XMLBeans](#). The default mapping of WSDL and XSD schema elements to Java programming language elements is described in [Default XML to Java Mapping](#).

## Data Binding Configuration Files

You can change the mapping of XML elements to Java objects by specifying mapping constraints in a data binding configuration file. Each data binding technology has its own configuration file format: XMLBeans XSDCONFIG or JAXB XJB. See the XMLBeans and JAXB specifications for the formats of their configuration files.

For example, the following XMLBeans configuration file maps the target namespace `http://ns.tibco.com/Hello/` to the package `com.sample.othername.hello` and specifies

suffixes, prefixes, and name replacements for generated classes.

```
<xb:config
  xmlns:xb="http://xml.apache.org/xmlbeans/2004/02/xbean/config"
  xmlns:ct="http://ns.tibco.com/Hello/">

  <xb:namespace uri="http://ns.tibco.com/Hello/ http://someurihere.com">
    <xb:package>com.sample.othername.hello</xb:package>
  </xb:namespace>

  <!--
    The ##any value is used to indicate "all URIs".
    The <prefix> tag is used to prepend to top-level Java type names
    generated in the specified namespace.
    The <suffix> tag is used to append to top-level Java types names
    generated in the specified namespace.
    The <prefix> and <suffix> are not used for inner Java types.
  -->

  <xb:namespace uri="##any">
    <xb:prefix>Xml</xb:prefix>
    <xb:suffix>BeanClass</xb:suffix>
  </xb:namespace>

  <!-- The <qname> tag specifies a Java class name for a qualified name
  -->
  <xb:qname name="ct:HelloResponse" javaname="TheHelloResponse" />

</xb:config>
```

## Generating XML Data Binding Classes

You can generate XML data binding classes for you SOA project from the Project Explorer. When you complete the process, a JAR file and optional schema document are created. Steps 1 through 3 are optional. They are recommended if you want to share the data binding classes between more than one SOA project.

### Procedure

1. Create a SOA project. In the Asset Type Selection screen, clear the **TIBCO SOA Platform** checkbox.

2. Click **Finish**.

In the Project Explorer, an SOA project is created containing only the Service Descriptors special folder.

3. Import or create WSDL and schema documents in the Service Descriptors folder.

4. In the Project Explorer, right-click a WSDL or schema document and select **Generate XML Data Bindings**.

The XML Data Binding Classes dialog displays.

5. Configure the XML data binding type, Beans, and interface JAR file properties as described in [XML Data Binding Reference](#).

6. Click **Finish**.

A JAR file containing the XML data binding classes for each WSDL and schema document is created in the specified location unless you click the Use this JAR for All Data Bindings link.

## Data Binding Classes for Abstract and Concrete WSDL Files

Using an abstract WSDL and its generated concrete WSDL in services and references of the same component requires special consideration if the WSDL contains an embedded schema. When a concrete WSDL file is generated from an abstract WSDL file that has an embedded schema, the resulting concrete WSDL file also contains the same embedded schema. When you generate data binding classes for both WSDL files, the code generator generates duplicate classes for the embedded schema.

The impact of this is two-fold:

- Generating the data binding classes for the abstract and concrete WSDL files into a single JAR is not supported.
- When you generate the data binding classes for the two WSDL files into different bean JARs, both JARs contain the same classes.

For correct operation, you must manually remove one of the resulting bean JARs from the bundle containing the bean JARs as follows:

1. Open the component implementation bundle's manifest in the Manifest Editor.

2. Click the Runtime tab, and delete one of the JARs containing the duplicate bean classes from the Classpath area.
3. Save the manifest.

To avoid having to manually edit the manifest, the recommended method for using abstract and concrete WSDL files in the same composite is to use only abstract WSDL files for the component services and references and use the concrete WSDL only for the corresponding promoted references as follows:

1. Delete the wire between component references and promoted references.
2. Configure the component reference with the abstract WSDL.
3. Configure the promoted reference with the concrete WSDL.
4. Wire the component reference to the promoted reference using the Wire tool in the Palette.

## XML Data Binding Reference

Field	Description
Type	<p>The type of the data binding being generated: XMLBeans or JAXB.</p> <p>If a JAR file already exists for the contract selected in the Contracts list, and you choose a binding type different than the one that exists in the JAR file or the contract has changed since the JAR file was generated, the <b>Overwrite Existing JAR</b> checkbox is selected.</p> <p>Default: XMLBeans.</p> <div><b>Note:</b> Generating implementations for two or more components in the same Java plug-in project using different binding types is not supported.</div>
Contracts	A list of WSDL and schema files for which XML data binding classes are generated.
JAR Type	The type of JAR file being generated: Beans or Interface.



Field	Description
Source File	The path to the source file containing the selected contract.
JAR File	<p>The path to the generated JAR file.</p> <p>Default: When generating a component implementation:</p> <ul style="list-style-type: none"> <li>Beans - <i>projectName</i>/<i>libs</i>/<i>contractFileName</i>.wsdl.jar</li> <li>Interface - <i>projectName</i>/<i>libs</i>/<i>contractFileName</i>.wsdl_interface.jar</li> </ul> <p>where <i>contractFileName</i> is the name of the file containing the contract selected in the Contracts list and <i>projectName</i> is the name of the project containing the component implementation.</p> <p>When generating from a contract file:</p> <ul style="list-style-type: none"> <li>Beans - <i>projectName</i>.libs/<i>libs</i>/<i>contractFileName</i>.wsdl.jar</li> <li>Interface - <i>projectName</i>.libs/<i>libs</i>/<i>contractFileName</i>.wsdl_interface.jar</li> </ul> <p>where <i>contractFileName</i> is the name of the file containing the contract selected in the Contracts list and <i>projectName</i> is the name of the project containing the contract file.</p>
Use this JAR for All Data Bindings	Indicate that all data binding classes should be generated into the JAR file specified in the JAR File field. You must generate all data binding classes into a single JAR file whenever there are cyclical references between schema files.
Set JAR Folder	<p>Invokes a dialog where you can set the folder to contain generated JAR files:</p> <ul style="list-style-type: none"> <li>All Generated JARs - All JAR files are generated in the same folder as the destination of the currently selected JAR.</li> <li>New Generated JARs - Only newly generated JAR files are generated in the same folder as the destination of the currently selected JAR file.</li> </ul>

Field	Description
	<p><b>Note:</b> Setting the JAR folder affects only the JAR files generated by the wizard. It has no effect outside the wizard nor on subsequent wizard runs.</p> <p>Default: All Generated JARs.</p>
JAR Status	<p>The status of the JAR file containing the classes generated for the selected contract:</p> <ul style="list-style-type: none"> <li>• JAR is non-existent and is generated. - The JAR file does not exist.</li> <li>• Different binding type. JAR must be overwritten. - The value of the Type field is different than the type of the data binding classes in the JAR file.</li> <li>• JAR exists and is overwritten. - The JAR file exists and the <b>Overwrite Existing JAR</b> checkbox is selected.</li> <li>• JAR exists and is preserved. - The JAR file exists and the <b>Overwrite Existing JAR</b> checkbox is clear.</li> <li>• JAR is outdated and is overwritten. - The selected contract has changed since the JAR file was generated and the <b>Overwrite Existing JAR</b> checkbox is selected, so the JAR file is generated.</li> <li>• JAR is outdated and is preserved. - The selected contract has changed since the JAR file was generated and the <b>Overwrite Existing JAR</b> checkbox is clear, so the JAR file is not generated.</li> </ul>
Overwrite Existing JAR	<p>Enabled only when the JAR file exists. When checked, the JAR file is regenerated. When unchecked, the existing file is reused and is not modified.</p>
<b>Advanced</b>	
Export Data Binding Packages	<p>Indicate that all packages of classes generated into the same plug-in as the component implementation should be exported in the component's implementation plug-in manifest using the Export-Package directive. This allows you to reuse data binding JAR files generated into the same plug-in as the component implementation. However, this is not the recommended</p>

Field	Description
	<p>approach for data binding library sharing. Instead, you should generate data binding JAR files into a separate plug-in project.</p> <p>Default: Unchecked.</p>
Use Configuration File	<p>Indicate that the specified data binding configuration file should be used when generating JAR files. When you select the checkbox, the text field is enabled.</p> <p>Default: Unchecked.</p>

## Opening a Spring Component Implementation

You can open a Spring component implementation from the canvas or from the Problem view.

Choose an initial control and follow the relevant procedure.

Control	Procedure
Canvas	Double-click the component.
Canvas	Right-click the component and select <b>Open Implementation</b> .
Problems View	Right-click the implementation file and select <b>Open With &gt; XML Editor</b> .

The Spring bean configuration file opens in the XML editor.

## Opening a Spring Bean Implementation

After you have opened a Spring Component implementation, you can open a Spring bean implementation file.

## Before you begin

Open a Spring component implementation. See [Opening a Spring Component Implementation](#).

## Procedure

1. Open a Spring component implementation.
2. In the Spring bean configuration file, press the **Ctrl** key and click the `class` attribute in the bean element.

The bean implementation file opens in a Java editor.

# Generating a Spring Component Implementation

You can generate a spring component implementation from the Property view, canvas, or Problems view. The wizard steps you through the implementation.

## Procedure

1. Choose an initial control and follow the relevant procedure.



Control	Procedure
Properties View	<ol style="list-style-type: none"><li>a. In the Validation Report area on the General tab of the component's Property View, click the <b>fix</b> link.</li><li>b. Select <b>Generate Spring Implementation</b>.</li></ol>
Canvas	<ol style="list-style-type: none"><li>a. Right-click the component and select <b>Quick Fixes &gt; Generate Spring Implementation</b>.</li></ol>
Canvas	<ol style="list-style-type: none"><li>a. Right-click the component and select <b>Generate Spring Implementation</b>.</li></ol>

Control	Procedure
Problems View	<ol style="list-style-type: none"> <li>In the Problems view, right-click an error of the form Component "<i>ComponentName</i>" is not configured and select <b>Quick Fixes</b>.</li> <li>In the Quick Fix dialog, click <b>Generate Spring Implementation</b>.</li> <li>Click <b>Finish</b>.</li> </ol>

The Create Spring Bean dialog displays.

- Configure the project, source, and bean definition file details in the [Code Generation Details](#) screen.
- If the component has a service or reference, choose a data binding option and follow the appropriate procedure:

Data Binding Option	Procedure
Accept Defaults	A JAR containing XMLBeans data binding classes with the default options is generated.
Configure	<ol style="list-style-type: none"> <li>Click <b>Next</b>.</li> <li>Configure the data binding type and Beans and interface JAR properties.</li> </ol>

- If the component has a reference and more than one service, click .
- Choose the bean to contain the reference element, click **OK**, and click **Next**.
- If the component has a property and more than one service, click .

The Bean Selection dialog displays.

- Choose the bean to contain the property element, click **OK**, and click **Next**.
- Click **Finish**.

**i Note:** When you add a reference or property to a Spring component and then generate the implementation, TIBCO Business Studio - BPM Edition displays warnings about a referenced bean not being found in the Problems view. You can ignore the warning.

## Result

The following objects are generated:

- A Java plug-in project containing abstract and concrete implementation classes, interface, and data binding classes.
- The [Spring bean XML configuration file](#). If the composite name is *compositeName* and component name is *componentName*, the bean XML configuration file is named *compositeName\_componentName\_beans.xml* and is located in the plug-in project under the folder *config-compositeName\_componentName*.
- A custom feature file that references the Java plug-in in the Deployment Artifacts special folder in the SOA project.
- Abstract and concrete implementation classes are also generated. If the implementation class is named *ImplClass*, the abstract implementation class is named *AbstractImplClass*. Additional code is generated based on the component elements as follows:
  - Service - An interface. If the port type is named *PortType*, the interface is named *PortType*. The clause `implementsPortType` is added to the abstract class.
  - Reference - Field and accessor methods are added to the abstract class.
  - Property - Field and accessor methods are added to the abstract class.

# Regenerating a Spring Component Implementation

You should regenerate the component implementation after you add a service, reference, or property to the component or to recreate the data binding classes created by a previous version of TIBCO Business Studio - BPM Edition. The regeneration recreates the abstract class, but it does not change or remove any code from the implementation class.

## Before you begin

The implementation must have been originally generated by TIBCO Business Studio - BPM Edition.

It is possible that the implementation class has errors after regeneration (for example when the reference has been removed and the implementation is using the reference).

If the implementation was generated with a previous version of TIBCO Business Studio - BPM Edition, a dialog displays asking if you want to delete legacy JARs. Legacy JARs are named *PortType-timestamp-service-beans.jar* and *PortType-timestamp-service-interface.jar*.

## Procedure

1. Choose an initial control and follow the relevant procedure.

Control	Procedure
Canvas	a. Right-click the component and select <b>Regenerate Spring Implementation</b> .
Canvas	a. Right-click a component and select <b>Quick Fixes &gt; Update Spring Configuration</b> .
Properties View	a. In the Validation Report area on the General tab of the component's Properties view click the <b>fix</b> link. b. Select <b>Update Spring Configuration</b> .
Problems View	a. In the Problems view, right-click an error of the form The component "componentName" is out of sync with its implementation and select <b>Quick Fix</b> . b. In the Quick Fix dialog, select <b>Update Spring Configuration</b> . c. Click <b>Finish</b> .

The Spring implementation and bean configuration XML file are updated.

2. Decide how you want to handle legacy JARs and follow the appropriate procedure.

Legacy JARs	Procedure
Delete	a. Click <b>Yes</b> .
Retain	a. Open the META-INF/Manifest.MF file in the component implementation's Java plug-in project. b. Delete the legacy JARs from the Bundle-ClassPath property. c. If the preceding step failed, right-click the Java project and select <b>PDE Tools &gt; Update classpath</b> . d. If necessary, remove legacy JARs from the build properties file in the component implementation's Java plug-in project. e. Delete the legacy JARs from the project. f. Fix compilation errors if any.

The implementation is updated to match the component.

## Generate Spring Component Implementation Reference

### Code Generation Details

Field	Description
Project	The name of the Spring plug-in project to contain the implementation. Default: <code>com.sample.spring</code> .
Source Folder	The name of the source folder in the plug-in project. Default: <code>src</code> .



Field	Description
Bean Configuration File	<p>The path to the Spring Bean configuration file relative to the Spring plug-in project.</p> <p>Default: <code>config-compositeName-componentName/compositeName_componentName_beans.xml</code>.</p>

## XML Data Binding Classes

Field	Description
Type	<p>The type of the data binding being generated: XMLBeans or JAXB.</p> <p>If a JAR file already exists for the contract selected in the Contracts list, and you choose a binding type different than the one that exists in the JAR file or the contract has changed since the JAR file was generated, the <b>Overwrite Existing JAR</b> checkbox is selected.</p> <p>Default: XMLBeans.</p> <div> <p><b>Note:</b> Generating implementations for two or more components in the same Java plug-in project using different binding types is not supported.</p> </div>
Contracts	A list of WSDL and schema files for which XML data binding classes is generated.
JAR Type	The type of JAR file being generated: Beans or Interface.
Source File	The path to the source file containing the selected contract.
JAR File	<p>The path to the generated JAR file.</p> <p>Default: When generating a component implementation:</p> <ul style="list-style-type: none"> <li>Beans - <code>projectName/libs/contractFileName.wsdl.jar</code></li> <li>Interface - <code>projectName/libs/contractFileName.wsdl_interface.jar</code></li> </ul>

Field	Description
	<p>where <i>contractFileName</i> is the name of the file containing the contract selected in the Contracts list and <i>projectName</i> is the name of the project containing the component implementation.</p> <p>When generating from a contract file:</p> <ul style="list-style-type: none"> <li>• Beans - <i>projectName.libs/libs/contractFileName.wsdl.jar</i></li> <li>• Interface - <i>projectName.libs/libs/contractFileName.wsdl_interface.jar</i></li> </ul> <p>where <i>contractFileName</i> is the name of the file containing the contract selected in the Contracts list and <i>projectName</i> is the name of the project containing the contract file.</p>
Use this JAR for All Data Bindings	Indicate that all data binding classes should be generated into the JAR file specified in the JAR File field. You must generate all data binding classes into a single JAR file whenever there are cyclical references between schema files.
Set JAR Folder	<p>Invokes a dialog where you can set the folder to contain generated JAR files:</p> <ul style="list-style-type: none"> <li>• All Generated JARs - All JAR files are generated in the same folder as the destination of the currently selected JAR.</li> <li>• New Generated JARs - Only newly generated JAR files are generated in the same folder as the destination of the currently selected JAR file.</li> </ul> <p><b>Note:</b> Setting the JAR folder affects only the JAR files generated by the wizard. It has no effect outside the wizard nor on subsequent wizard runs.</p> <p>Default: All Generated JARs.</p>
JAR Status	<p>The status of the JAR file containing the classes generated for the selected contract:</p> <ul style="list-style-type: none"> <li>• JAR is non-existent and is generated. - The JAR file does not exist.</li> <li>• Different binding type. JAR must be overwritten. - The value of the</li> </ul>

Field	Description
	<p>Type field is different than the type of the data binding classes in the JAR file.</p> <ul style="list-style-type: none"> <li>JAR exists and is overwritten. - The JAR file exists and the <b>Overwrite Existing JAR</b> checkbox is selected.</li> <li>JAR exists and is preserved. - The JAR file exists and the <b>Overwrite Existing JAR</b> checkbox is clear.</li> <li>JAR is outdated and is overwritten. - The selected contract has changed since the JAR file was generated and the <b>Overwrite Existing JAR</b> checkbox is selected, so the JAR file is generated.</li> <li>JAR is outdated and is preserved. - The selected contract has changed since the JAR file was generated and the <b>Overwrite Existing JAR</b> checkbox is clear, so the JAR file is not generated.</li> </ul>
Overwrite Existing JAR	<p>Enabled only when the JAR file exists.</p> <p>When selected, the JAR file is regenerated.</p> <p>When clear, the existing file is reused and is not modified.</p>
<b>Advanced</b>	
Export Data Binding Packages	<p>Indicate that all packages of classes generated into the same plug-in as the component implementation should be exported in the component's implementation plug-in manifest using the Export-Package directive. This allows you to reuse data binding JAR files generated into the same plug-in as the component implementation. However, this is not the recommended approach for data binding library sharing. Instead, you should generate data binding JAR files into a separate plug-in project.</p> <p>Default: Unchecked.</p>
Use Configuration File	<p>Indicate that the specified data binding configuration file should be used when generating JAR files. When you select the checkbox, the text field is enabled.</p> <p>Default: Unchecked.</p>

## New Bean Definition

Field	Description
Service Name	Read-only. The name of the service for which the bean is being generated.
Bean ID	The name of the generated bean. Default: <i>serviceNameBean</i> .
Package	The name of the package of the implementation class.
Class	The name of the class of the implementation. Default: <i>serviceNameImpl</i> . If no service is defined on the component, the default class name is <i>componentName</i> .
Use Default Location for Superclass	Indicate whether to generate the superclass of the implementation class in the same package as the implementation class and name the class <i>AbstractComponentName</i> . When unchecked, the Superclass Package and Superclass fields are enabled. Default: Checked.
Superclass Package	The name of the package of the abstract superclass of the implementation class. Default: <i>com.sample.projectName</i> .
Superclass	The name of the abstract superclass of the implementation class. Default: <i>AbstractComponentName</i> .

## Life Cycle Events

The ActiveMatrix runtime exposes component life cycle events—Init and Destroy—to component implementations.

Methods annotated with @Init and @Destroy are invoked when the life cycle events trigger. The following table describes the meaning of each event and how component

implementations can handle each event.

#### *Life Cycle Events*

Event	When Invoked
Init	<p>When the application containing the component or the component is started.</p> <p>When this event is triggered all the component's properties, references, and resources have been initialized.</p> <p>The method invoked when this event is triggered is typically used to validate component configuration and open connection to resources.</p>
Destroy	<p>When the application containing the component or the component is stopped.</p> <div><b>Note:</b> If you open connections to resources in a method that is invoked by an Init event you must close the connections to the resources in the method that is invoked by a Destroy event.</div>

When TIBCO Business Studio - BPM Edition generates a Java or Spring component implementation, it automatically adds the appropriately annotated initialization and destruction methods:

```
org.osoa.sca.annotations.Init;
org.osoa.sca.annotations.Destroy;
@Init
public void init()
{
    // Component initialization code.
    // All properties are initialized and references are injected.
}
@Destroy
public void destroy()
{
    // Component disposal code.
    // All properties are disposed.
}
```

You can customize these methods to perform application-specific initialization and cleanup.

## Component Context

A *component context* provides access to the context in which a component executes. The context includes the component's name and containing application name, the node on which it executes, the host managing the node, context parameters available to the component, the component's work area, and so on.

To access the component context, add the following declarations to a Java or Spring component implementation:

```
import org.osoa.sca.annotations.Context;
import
com.tibco.amf.platform.runtime.extension.context.ComponentContext;
@Context
public ComponentContext componentContext;
```

These declarations are automatically added to the abstract component implementation when a context parameter is defined for the component. The TIBCO ActiveMatrix platform injects the component context object into the component implementation.

If a component implementation wants to create a file, it should do so in the work area assigned to each component. The TIBCO ActiveMatrix platform ensures that these files are deleted when the component is undeployed. Work areas are backed up during node upgrade. A component implementation can retrieve its work area through the component context's `getWorkArea()` method which returns the `java.io.File` object that represents the work area folder for that component.

## Accessing a Property

When you generate a Java or Spring component implementation after adding a property to the component, TIBCO Business Studio - BPM Edition adds properties and methods to the component's abstract implementation class:

The following items are added.

- SCA property annotation import
- A field that represents the property
- Accessor methods

The TIBCO ActiveMatrix platform injects the property object into the component implementation.

For example, if you add a property named `greeting` of type `String` to a component, the following code is added:

```
org.osoa.sca.annotations.Property;
private String greeting;

@property(name = "greeting")
public void setGreeting(String greeting)
{
    this.greeting = greeting;
}

public String getGreeting()
{
    return greeting;
}
```

To reference the property invoke the accessor methods. For example:

```
resp.setHelloResponse(getGreeting() + " " + name + "! "
+ "The current time is " + time + ".");
```

## Accessing a Resource

You can access a resource with an accessor method that is part of the component implementation.

### Procedure

1. Add a property of the resource type to the component.
2. Generate or regenerate the component implementation. TIBCO Business Studio - BPM Edition adds imports, fields, and resource accessor methods to the component's abstract implementation class. When the component is instantiated, the TIBCO ActiveMatrix platform injects the resource object into the component implementation.
3. Access the resource using the generated accessor methods.
4. After you are finished with the resource and any objects retrieved from the resource,

close the objects.

## Accessing a Hibernate Resource

You can access a Hibernate resource from the Hibernate session that is associated with the session factory

If you create a property named sessionFactory of type Hibernate Resource Template, TIBCO Business Studio - BPM Edition adds the following to the abstract implementation class:

```
import org.osoa.sca.annotations.Property;
import
com.tibco.amf.sharedresource.runtime.core.hibernate.sharedresource.Proxy
SessionFactory;

private ProxySessionFactory sessionFactory;

    @Property(name = "sessionFactory")
    public void setSessionFactory(ProxySessionFactory sessionFactory)
    {
        this.sessionFactory = sessionFactory;
    }

    public ProxySessionFactory getSessionFactory()
    {
        return sessionFactory;
    }
```

### Procedure

1. Retrieve the proxy session factory using the generated getSessionFactory method.
2. Register the model class using the session factory addClass method.
3. Retrieve the Hibernate session from the session factory using the openSession method.
4. Retrieve a transaction from the session.
5. Create a query.
6. Execute the query.
7. Save the session.



8. Commit the transaction.
9. Close the session.
10. When the component is destroyed, unregister the model class using the `removeClass` method.

```
import org.hibernate.Query;
import org.hibernate.Session;
import org.hibernate.Transaction;
...
    final Session session = getSessionFactory().openSession();
    try
    {
        /**
         * Begin a transaction before performing any queries.
         * Closing the session cleans up the transaction.
         */
        Transaction tx = session.beginTransaction();
        final Query query = session.createQuery("UPDATE ...");
        ...
        int result = query.executeUpdate();
        if (result == 0)
        {
            ...
            session.save(report);
        }
        tx.commit();
    } finally
    {
        session.close();
    }
    ...

    @Init
    public void init()
    {
        if (getSessionFactory() == null)
        {
            throw new IllegalStateException("Failed to inject
ProxySessionFactory");
        }

        /** Register the ModelClass model class on SessionFactory */
        getSessionFactory().addClass(ModelClass.class);

        try
```

```

{
    // Initializes database data.
    initializeDBData();
    } catch (Throwable th) {
        ...
    }
}
...
@Destroy
public void destroy()
{
    if (getSessionFactory() != null)
    {
        /**
         * Unregister the ModelClass model class from SessionFactory
         */
        sessionFactory().removeClass(ModelClass.class);
    }
}
}

```

## Accessing a JDBC Resource

If you create a property named `jdbcr` of type JDBC Resource Template, TIBCO Business Studio - BPM Edition adds the following to the abstract implementation class:

```

import org.osoa.sca.annotations.Property;
import javax.sql.DataSource;

private DataSource jdbcr;

@Property(name = "jdbcr")
public void setDbr(DataSource jdbcr) {
    this.jdbcr = jdbcr;
}

public DataSource getJdbcr() {
    return jdbcr;
}

```

### Procedure

1. Invoke the accessor methods in your component implementation.

```

import javax.sql.DataSource;
DataSource ds = getJdbc();
Connection connection = null;

try {
    connection = ds.getConnection();
    ensureTablesExist(connection);

    Statement stmt = connection.createStatement();
    ResultSet rs = stmt.executeQuery(sqlString);
    PhoneEntryType entry = null;

    while(rs.next()) {
        entry = resp.addNewOut();
        entry.setEntryId(rs.getString("id"));
        entry.setFirstName(rs.getString("firstName"));
        entry.setLastName(rs.getString("lastName"));
        entry.setPhone(rs.getString("phone"));
    }

} catch(SQLException e) {
    e.printStackTrace();
} finally {
    try{
        connection.close();
    }catch(Exception e){};
    ...
}

```

## Accessing JMS Resources

To access JMS resources, create JMS Connection Factory and JMS Destination properties. If you create a property named `connectionFactory` of type JMS Connection Factory and a property named `destination` of type JMS Destination, TIBCO Business Studio - BPM Edition adds the following to the abstract implementation class:

```

import javax.jms.ConnectionFactory;
import javax.jms.Destination;

private ConnectionFactory connectionFactory;

@property(name = "connectionFactory")

```

```

    public void setConnectionFactory(ConnectionFactory connectionFactory) {
        this.connectionFactory = connectionFactory;
    }

    public ConnectionFactory getConnectionFactory() {
        return connectionFactory;
    }

    private Destination destination;

    @Property(name = "destination")
    public void setDestination(Destination destination) {
        this.destination = destination;
    }

    public Destination getDestination() {
        return destination;
    }

```

## Procedure

1. Invoke the accessor methods in your component implementation.

```

import javax.jms.Connection;
import javax.jms.Destination;
import javax.jms.JMSEException;

import javax.jms.MessageProducer;
import javax.jms.Session;
import javax.jms.TextMessage;

@Init
public void init() throws JMSEException {
    connection = getConnectionFactory().createConnection();
    connection.start();
    session = connection.createSession(false, Session.AUTO_ACKNOWLEDGE);
    System.out.println(session);
}

@Destroy
public void destroy() throws JMSEException {
    session.close();
    connection.stop();
    connection.close();
}

```

```

        private String doPublish(String input ) throws JMSException {
            MessageProducer producer = session.createProducer(getDestination());
            TextMessage message = session.createTextMessage("Input from SOAP
Request :" + input );
            producer.send(message);
            String msg_id = message.getJMSMessageID();
            return msg_id;
        }

```

## Accessing LDAP Connections

If you create a property named `ldapr` of type LDAP Connection Resource Template, TIBCO Business Studio - BPM Edition adds the following to the abstract implementation class:

```

import org.osoa.sca.annotations.Property;
import javax.naming.ldap.LdapContext;

private LdapContext ldapr;

@Property(name = "ldapr")
public void setLdap(LdapContext ldapr) {
    this.ldapr = ldapr;
}

public LdapContext getLdap() {
    return ldapr;
}

```

### Procedure

1. To update the resource:

```

...
        Attributes attr = new BasicAttributes(true);
        Attribute objFact = new BasicAttribute("objectclass");
        objFact.add("top");
        objFact.add("person");
        objFact.add("uidObject");
        objFact.add("organizationalPerson");

```

```

        attr.put(objFact);
        attr.put("uid", uid);
        attr.put("cn", commonName);
        attr.put("sn", surname);
        attr.put("userPassword", password);
        Name name = new LdapName("uid=" + uid +
        ",ou=People,dc=tibco,dc=com");
        getLdapr().createSubcontext(name, attr);
        ...
        public void destroy() {
            try {
                getLdapContext().close();
            } catch (NamingException e) {
                e.printStackTrace();
            }
        }
    }

```

## 2. To query the resource:

```

    ...
    StringBuffer sb = new StringBuffer();
    NamingEnumeration<SearchResult> results = null;
    try {
        SearchControls controls = new SearchControls();
        controls.setSearchScope(SearchControls.SUBTREE_SCOPE);
        MessageFormat format = new MessageFormat("&(uid={0})"
        (objectclass=*))");
        String format2 = format.format(new Object[] { uid });
        results = getLdapr().search("uid=" + uid +
        ",ou=People,dc=tibco,dc=com",
        format2,controls);

        while (results.hasMore()) {
            SearchResult searchResult = (SearchResult) results.next();
            Attributes attributes = searchResult.getAttributes();
            NamingEnumeration<? extends Attribute> enumeration =
            attributes.getAll();
            for (; enumeration.hasMoreElements();) {
                Attribute object = (Attribute) enumeration.next();
                sb.append(object.toString());
                sb.append('\n');
                if (logger.isInfoEnabled()) {
                    logger.info(object.toString() );
                }
            }
        }
    }

```

```

        }
    }

    } catch (NameNotFoundException e) {
        ...
    } catch (NamingException e) {
        ...
    }

    return sb.toString();
    ...

```

## Accessing SMTP Connections

If you create a property named `smtpr` of type SMTP Resource Template, TIBCO Business Studio - BPM Edition adds the following to the abstract implementation class:

```

import org.osoa.sca.annotations.Property;
import javax.mail.Session;

private Session smtpr;

@Property(name = "smtpr")
public void setSmtpr(Session smtpr) {
    this.smtpr = smtpr;
}

public Session getSmtpr() {
    return smtpr;
}

```

Invoke the accessor methods in your component implementation.

```

import javax.mail.Message;
import javax.mail.MessagingException;
import javax.mail.Session;
import javax.mail.Transport;
...
    Transport transport = null;
    try{
        Session session = getSmtpr();
        transport = session.getTransport();
    }
}

```

```

        Message message = new MimeMessage(session);
        message.setFrom(new InternetAddress(mailFrom));
        InternetAddress dests[] = new InternetAddress[]{ new
InternetAddress(mailTo) };
        message.setRecipients(Message.RecipientType.TO, dests);
        message.setSubject(subject);

        message.setDataHandler(new DataHandler(new ByteArrayDataSource(
            requestContent, "text/plain")));
        transport.connect();
        transport.sendMessage(message, dests);
        } catch (Exception exp) {
            ...
        }
        return false;
    } finally {
        if (transport != null)
            try {
                transport.close();
            } catch (MessagingException e) {
                e.printStackTrace();
            }
    }
}
return true;
...

```

## Accessing a Teneo Resource

If you create a property named `sessionFactory` of type `Teneo Resource Template`, TIBCO Business Studio - BPM Edition adds the following to the abstract implementation class:

```

import org.osoa.sca.annotations.Property;
import
com.tibco.amf.sharedresource.runtime.core.teneo.sharedresource.TeneoSess
ionFactory;

private TeneoSessionFactory sessionFactory;

@Property(name = "sessionFactory")
public void setSessionFactory(TeneoSessionFactory sessionFactory) {
    this.sessionFactory = sessionFactory;
}

```



```

public TeneoSessionFactory getSessionFactory() {
    return sessionFactory;
}

```

Invoke the accessor methods in your component implementation.

```

...
import org.hibernate.Query;
import org.hibernate.Session;
import org.hibernate.Transaction;
Session session = null;
Transaction tx = null;
try {
    session = getSessionFactory().openSession();
    tx = session.beginTransaction();
    Query q = session.createQuery("...");
    User user = (User)q.uniqueResult();
    Trip trip = ...;
    ...
    id = (Long) session.save(trip);
    user.getTrips().add(trip);
    session.save(user);
}
catch (Throwable th) {
    error = true;
    result = "failed: " + th.getMessage();
    th.printStackTrace();
}
finally {
    if (tx != null) {
        if (error) {
            try {
                tx.rollback();
            }
            catch (Throwable th) {
                th.printStackTrace();
            }
        }
        else {
            try {
                tx.commit();
            }
            catch (Throwable th) {
                th.printStackTrace();
            }
        }
    }
}

```

```

        }
        if (session != null) {
            try {
                session.close();
            }
            catch (Throwable th) {
                th.printStackTrace();
            }
        }
    }
    ...

```

## Invoking an HTTP Request

You can use an HTTP client resource to invoke HTTP requests from component implementations. A POST example illustrates this.

### Procedure

1. Add a property of type HTTP Client Resource Template to the component.

When you regenerate the implementation, TIBCO Business Studio - BPM Edition adds an HTTP client connection factory property to the abstraction implementation class. For a property named `httpClientConnectionFactory`, TIBCO Business Studio - BPM Edition adds the following:

```

import

com.tibco.amf.sharedresource.runtime.core.http.httpclient.HttpClientConnectionFactory;

private HttpClientConnectionFactory httpClientConnectionFactory;

public void setHttpClientConnectionFactory(
    HttpClientConnectionFactory httpClientConnectionFactory) {
    this.httpClientConnectionFactory = httpClientConnectionFactory;
}

/**
 * @return Returns the HttpClientConnectionFactory
 */

```

```

        public HttpClientConnectionFactory getHttpClientConnectionFactory() {
            return httpConnectionFactory;
        }

```

2. Retrieve an HTTP client object from the connection factory.
3. Invoke HTTP methods on the HTTP client object.

## Post Example

The following example demonstrates how to invoke an HTTP Post request using an HTTP client object retrieved from the HTTP client connection factory or using an HTTP connection:

```

import org.apache.http.HttpClientConnection;
import org.apache.http.HttpEntity;
import org.apache.http.HttpException;
import org.apache.http.HttpHost;
import org.apache.http.HttpResponse;
import org.apache.http.client.ClientProtocolException;
import org.apache.http.client.methods.HttpPost;
import org.apache.http.entity.InputStreamEntity;
import org.apache.http.protocol.BasicHttpContext;
import org.apache.http.protocol.BasicHttpProcessor;
import org.apache.http.protocol.ExecutionContext;
import org.apache.http.protocol.HttpRequestExecutor;
import org.apache.http.protocol.RequestConnControl;
import org.apache.http.protocol.RequestContent;
import org.apache.http.protocol.RequestExpectContinue;
import org.apache.http.protocol.RequestTargetHost;
import org.apache.http.protocol.RequestUserAgent;

    public GetQuoteResponseDocument getQuote
(GetQuoteDocument parameters) {
        String symbol = parameters.getGetQuote().getSymbol();
        String value = ERROR_MSG;
        try
        {
            /**
             * Two ways of using HTTP client API, randomly selected at runtime:
             * a) HTTP Client
             * b) HTTP Connection
             */

```

```

        if(random.nextBoolean()){
            value = getQuoteUsingHttpClient(getHttpClientConnectionFactory(),
symbol.trim());
        }else{
            value = getQuoteUsingHttpConnection(getHttpClientConnectionFactory(),
symbol.trim());
        }
    } catch (Exception e) {
        if(logger.isEnabled()){
            logger.error(ERROR_MSG,e);
        }
    }

    GetQuoteResponseDocument responseDoc =
GetQuoteResponseDocument.Factory.newInstance();
    responseDoc.addNewGetQuoteResponse().setGetQuoteResult(value);
    return responseDoc;
}

/**
 * Processes the request using HTTPClient API
 */
private String getQuoteUsingHttpClient(HttpClientConnectionFactory
connectionFactory,
String symbol) throws HttpException, ClientProtocolException,
IOException {
    String responseString = ERROR_MSG;
    String message = getContent(symbol);
    byte[] bytes = message.getBytes();

    /** HTTPClient provides a facade to a number of special purpose
handler or strategy
    * implementations responsible for handling of a particular
aspect of
    * the HTTP protocol such as redirect or authentication handling or
    * making decision about connection persistence and keep alive
duration.
    * This allows you to selectively replace the default
implementation
    * of those aspects with custom, application-specific ones.
    */
    HttpClientWrapper httpClient = connectionFactory.getHttpClient();
    HttpHost configuration = connectionFactory.getHostConfiguration();

    /**
    * Construct the request URL

```

```

    */
    String url = configuration.getSchemeName() + "://" +
configuration.getHostName()+":"+
    configuration.getPort() + "/stockquote.asmx";

    /**
    * Prepare request object and its header for HTTP Post request
    */
    HttpPost httpPost = new HttpPost(url);
    httpPost.setHeader("Content-Type", "text/xml; charset=utf-8");
    httpPost.setHeader("SOAPAction",
"http://www.webserviceX.NET/GetQuote");

    /**
    * Sets the Entity to handle content management.
    */
    ByteArrayInputStream instream = new ByteArrayInputStream(bytes);
    InputStreamEntity e2 = new InputStreamEntity(instream, -1);
    httpPost.setEntity(e2);

    /**
    * Execute the POST URL using HttpClientWrapper which takes care of
    * connection management other functionality internally.
    */
    HttpResponse response = httpClient.execute(httpPost);
    /**
    * Get the response Entity which holds the response content from
    HttpResponse.
    */
    HttpEntity resEntity = response.getEntity();

    //Reads the response
    responseString = getResponseString(resEntity);
    if (resEntity != null) {
    /**
    * The Method consumeContent() is called to indicate that the
content of this entity
    * is no longer required. All entity implementations are expected
to
    * release all allocated resources as a result of this method
    * invocation.
    */
        resEntity.consumeContent();
    }

    return responseString;

```

```

    }

    /**
     * Processes the request using HTTPConnection API
     */
    private String getQuoteUsingHttpConnection
    (HttpClientConnectionFactory connectionFactory, String symbol) throws
    HttpException, IOException {

        String responseString = ERROR_MSG;
        String message = getContent(symbol);
        byte[] bytes = message.getBytes();

        HttpClientConnection httpClientConnection =
        connectionFactory.getHttpConnection();
        HttpHost configuration = connectionFactory.getHostConfiguration();

        /**
         * Construct the request URL
         */
        String url = configuration.getSchemeName() + "://" +
        configuration.getHostHostName() + ":" +
        configuration.getPort() + "/stockquote.asmx";

        try {

            /**
             * Prepare request object and its header for HTTP Post request
             */
            HttpPost httpPost = new HttpPost(url);
            httpPost.setHeader("Content-Type", "text/xml; charset=utf-8");
            httpPost.setHeader("SOAPAction",
            "http://www.webserviceX.NET/GetQuote");

            /**
             * Sets the Entity to handle content management.
             */
            ByteArrayInputStream instream = new ByteArrayInputStream(bytes);
            InputStreamEntity e2 = new InputStreamEntity(instream, -1);
            httpPost.setEntity(e2);

            /**
             * Set HTTP params on Post request object
             */
            httpPost.setParams(connectionFactory.getHttpParams());

```

```

    /** HttpContext represents execution state of an HTTP process.
    * It is a structure that can be used to map an attribute name
    * to an attribute value. Internally HTTP context implementations
    * are usually backed by a HashMap.
    */
    BasicHttpContext basicHttpContext = new BasicHttpContext(null);
    // Populate the execution context
    basicHttpContext.setAttribute(ExecutionContext.HTTP_
CONNECTION,httpClientConnection);
    basicHttpContext.setAttribute(ExecutionContext.HTTP_TARGET_
HOST,connectionFactory.
    getHostConfiguration());
    basicHttpContext.setAttribute(ExecutionContext.HTTP_REQUEST,
httpPost);

    /** HTTP protocol processor is a collection of protocol interceptors
that
    * implements the Chain of Responsibility pattern, where each
individual
    * protocol interceptor is expected to work on a particular
aspect of the HTTP
    * protocol for which the interceptor is responsible.
    */
    BasicHttpProcessor httpProcessor = new BasicHttpProcessor();
    // Required request interceptors
    httpProcessor.addInterceptor(new RequestContent());
    httpProcessor.addInterceptor(new RequestTargetHost());
    // Recommended request interceptors
    httpProcessor.addInterceptor(new RequestConnControl());
    httpProcessor.addInterceptor(new RequestUserAgent());
    httpProcessor.addInterceptor(new RequestExpectContinue());

    /** HttpRequestExecutor is a client side HTTP protocol handler
based on the
    * blocking I/O model that implements the essential requirements
of the HTTP
    * protocol for the client side message processing
    */
    HttpRequestExecutor httpexecutor = new HttpRequestExecutor();

    // Prepare request
    httpexecutor.preProcess(httpPost, httpProcessor, basicHttpContext);
    // Execute request and get a response
    HttpResponse response = httpexecutor.execute

```

```

(httpPost,httpClientConnection,
    basicHttpContext);
// Finalize response
httpexecutor.postProcess(response, httpProcessor, basicHttpContext);
HttpEntity resEntity = response.getEntity();

//Reads the response
responseString = getResponseString(resEntity);
if (resEntity != null) {
/**
 * The Method consumeContent() is called to indicate that the
content of this entity
 * is no longer required. All entity implementations are expected
to
 * release all allocated resources as a result of this method
 * invocation.
 */
    resEntity.consumeContent();
}
} finally {
    httpClientConnection.close();
}
return responseString;
}

/**
 * Reads and returns the string content from response Entity
 */
private String getResponseString(HttpEntity resEntity)
    throws IOException {
    if (resEntity != null) {
        InputStream content = resEntity.getContent();
        byte[] cbytes = new byte[new Long(1000).intValue()];
        int x = -1;
        StringBuilder sb = new StringBuilder();
        while ((x = content.read(cbytes)) != -1) {
            String reponseContent = new String(cbytes);
            sb.append(reponseContent);
        }
        return getValue(sb.toString().trim());
    }
    return ERROR_MSG;
}

/**
 * Returns the request content.

```



```

    * @param symbol
    * @return
    */
    private String getContent(String symbol) {
        return "<soapenv:Envelope
xmlns:soapenv=\"http://schemas.xmlsoap.org/soap/envelope/\"
    + \"xmlns:web=\"http://www.webserviceX.NET/\">\"
        + \"<soapenv:Header/>\"
        + \"<soapenv:Body>\"
        + \"<web:GetQuote>\"
        + \"<web:symbol>\"+symbol+\"</web:symbol>\"
        + \"</web:GetQuote>\"
        + \"</soapenv:Body>\"
        + \"</soapenv:Envelope>\";
    }

```

## Invoking a Reference Operation

When you add a reference to a Spring component, TIBCO Business Studio - BPM Edition adds the following field and accessor methods to the abstract component implementation. TIBCO ActiveMatrix injects the referenced object into the component implementation.

TIBCO Business Studio - BPM Edition adds the following elements to the abstract component implementation:

- SCA reference annotation import
- A field that declares the referenced object
- Accessor methods

The TIBCO ActiveMatrix platform injects the referenced object into the component implementation. For example, if you add a reference to port type `DateManagerPT`, the following code is added:

```

import org.osoa.sca.annotations.Reference;
@Reference(name = "DateManagerPT")
public void setDateManagerPT(DateManagerPT DateManagerPT) {
    this.DateManagerPT = DateManagerPT;
}

public DateManagerPT getDateManagerPT() {
    return this.DateManagerPT;
}

```

**i Note:** When you pass an XMLBeans document object to a reference invocation, the object is passed by reference. Since the state of an object is not guaranteed across reference invocations, you cannot access the object after the reference invocation. If you need to access the object after the invocation, make a deep copy of the object using the copy method before you invoke the reference. For example, if you needed to access the req object after the call to `getCurrentTime`, make a deep copy of req as follows:

```
TimeRequestDocument req =
    TimeRequestDocument.Factory.newInstance();
req.setTimeRequest("America/Los_Angeles");
TimeRequestDocument reqcopy = (TimeRequestDocument)req.copy();
TimeResponseDocument time = getDateManagerPT().getCurrentTime
    (req);
System.out.println("The time in " + reqcopy.getTimeRequest() +
    " is " +
    time.getTimeResponse());
```

Add the statement `getportType().operation`. If the reference is configured for dynamic wiring, you must define a method to create an endpoint reference (see [Creating an Endpoint Reference](#)) and call the method before invoking the reference object. For information on wiring, see "Static and Dynamic Wiring" in *TIBCO ActiveMatrix® Service Grid Composite Development*.

The following code snippet demonstrates how to invoke the `getCurrentTime` operation on the reference configured for dynamic wiring with port type `DateManagerPT`:

```
setEPR(targetURI);
String time = currentTime.getTimeResponse();

resp.setHelloResponse(getJavaGreeting() + " " + name + "! "
    + "The current time is " + time + ".");
return resp;
```

## Error Handling

In service-oriented applications, SOAP clients expect a fault message to be returned when an error occurs during processing. A *fault message* is a SOAP message

A fault message has the following subelements:

Subelement	Description
faultcode	A code that identifies the fault.
faultstring	An explanation of the fault.
faultactor	Information about what caused the fault to occur.
detail	Application-specific information about the fault.

Fault messages defined in the WSDL file are called *declared faults*. Fault messages that are not defined in the WSDL file are called *undeclared faults*. The process for generating a fault message is implementation dependent and typically depends on whether the fault is declared or not.

## Declared Faults

When you add a service to a Spring component TIBCO Business Studio - BPM Edition generates a fault exception class for each fault declared in the WSDL file that defines the service's port type.

## Example WSDL File

The following WSDL fragment shows the `getWeather` operation with two declared faults: `orderFault` and `orderFault2`. The detail element for the `orderFault` message contains a `ZipCodeFault` element. The detail element for the `orderFault2` message contains a `CityFault` element.

```
<wsdl:types>
  <schema xmlns="http://www.w3.org/2001/XMLSchema"
    xmlns:tns="http://www.example.org/weatherschema"
    targetNamespace="http://www.example.org/weatherschema"
    elementFormDefault="unqualified"
    attributeFormDefault="unqualified">
    <complexType name="WeatherRequestType">
      <sequence>
        <element name="city" type="string"/>
        <element name="state" type="string"/>
        <element name="zip" type="string"/>
      </sequence>
    </complexType>
  </schema>
</wsdl:types>
```

```

        </sequence>
    </complexType>
    <complexType name="WeatherResponseType">
        <sequence>
            <element name="high" type="float"/>
            <element name="low" type="float"/>
            <element name="forecast" type="string"/>
        </sequence>
    </complexType>

    <element name="WeatherRequest" type="tns:WeatherRequestType"/>
    <element name="WeatherResponse" type="tns:WeatherResponseType"/>
    <element name="ZipCodeFault" type="string"/>
    <element name="CityFault" type="string" />
</schema>
</wsdl:types>
<wsdl:message name="invalidZipCodeFault">
    <wsdl:part name="error" element="ns0:ZipCodeFault"/>
</wsdl:message>
<wsdl:message name="invalidCityFault">
    <wsdl:part name="error" element="ns0:CityFault" />
</wsdl:message>
<wsdl:portType name="WeatherReportPT">
    <wsdl:operation name="GetWeather">
        <wsdl:input message="tns:GetWeatherRequest"/>
        <wsdl:output message="tns:GetWeatherResponse"/>
        <wsdl:fault name="orderFault" message="tns:invalidZipCodeFault"/>
        <wsdl:fault name="orderFault2" message="tns:invalidCityFault" />
    </wsdl:operation>
</wsdl:portType>

```

## Code Generation

When TIBCO Business Studio - BPM Edition generates the Spring component implementation `invalidCityFault` and `invalidZipCodeFault` are mapped to the exceptions:

```

public class InvalidCityFaultException extends java.lang.Exception
public class InvalidZipCodeFaultException extends java.lang.Exception

```

and a throws clause containing the generated exceptions is added to the `getWeather` method.

To generate the `invalidCityFault` fault message while processing the `getWeather` method, throw `InvalidCityFaultException`. The `faultcode` and `faultactor` subelements

of the SOAP fault element are predefined as:

Subelement	Content
faultcode	SOAP-ENV:Server
faultactor	DefaultRole

## Setting Fault Message Subelements

To customize the values of the `faultstring` and `detail` subelements:

1. Create a string object and set it to an informative message. The message is mapped to the SOAP message's `faultstring` element.
2. Create a fault document and set the appropriate fault property of the document to the reason for the error. The reason is mapped to the SOAP message `detail` element.
3. Create a fault message exception that contains the message and fault document.

For example, if the `city` element of the request is not set correctly, configure and throw the fault message exception as follows:

```
public WeatherResponseDocument getWeather(WeatherRequestDocument
getWeatherRequest)
    throws org.example.www.WeatherService.InvalidCityFaultException,
           org.example.www.WeatherService.InvalidCityFaultException {
    WeatherRequestType weatherRequest = getWeatherRequest.getWeather();
    if (weatherRequest.getCity() == null || weatherRequest.getCity().equals
("")) {
        CityFaultDocument cityFaultDocument =
CityFaultDocument.Factory.newInstance();

        XmlString msg = XmlString.Factory.newInstance();
        msg.setStringValue("Error processing getWeather.");
        // set detail
        cityFaultDocument.setCityFault("Invalid city for zipcode" +
weatherRequest.getZip());
        // set faultstring
        InvalidCityFaultException invalidCityFaultException =
new InvalidCityFaultException(msg.getStringValue(),
cityFaultDocument);
        throw invalidCityFaultException;
    }
}
```

```
    ...
}
```

which would generate the following SOAP fault message if `getCity` does not return a valid value:

```
<SOAP-ENV:Envelope xmlns:SOAP-
ENV="http://schemas.xmlsoap.org/soap/envelope/">
<SOAP-ENV:Body>
<SOAP-ENV:Fault>
<faultcode>SOAP-ENV:Server</faultcode>
<faultstring>Error processing getWeather.</faultstring>
<faultactor>DefaultRole</faultactor>
<detail>
<CityFault xmlns="http://www.example.org/weatherschema">
  Invalid city for zipcode 95070.</CityFault>
</detail>
</SOAP-ENV:Fault>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

A consumer invoking `getWeather` should handle the exception as follows:

```
public WeatherResponseDocument getWeather(WeatherRequestDocument
getWeatherRequest) {
    try {
        return getWeatherReportPT().getWeather(getWeatherRequest);
    }
    catch(Exception e) {
        if (e instanceof InvalidCityFaultException)
            throw (InvalidCityFaultException)e;
        else{
            System.out.println("Error occurred.");
            throw new RuntimeException(e.getMessage(),e);
        }
    }
    ...
}
```

## Undeclared Faults

When an undeclared fault occurs, the TIBCO ActiveMatrix runtime returns a SOAP fault with the following subelements:

Subelement	Content
faultcode	SOAP-ENV:Server
faultstring	java.lang.RuntimeException
faultactor	DefaultRole
detail	A stack trace indicating where the exception occurred.

If a runtime exception occurs while processing `getWeather`, the following SOAP fault would be generated:

```
<SOAP-ENV:Envelope xmlns:SOAP-
ENV="http://schemas.xmlsoap.org/soap/envelope/">
<SOAP-ENV:Body>
  <SOAP-ENV:Fault>
    <faultcode>SOAP-ENV:Server</faultcode>
    <faultstring>java.lang.RuntimeException: Undeclared
fault....</faultstring>
    <faultactor>DefaultRole</faultactor>
    <detail>
      <tibco:myFaultDetail xmlns:tibco="http://tibcouri/">
        org.osoa.sca.ServiceRuntimeException: java.lang.RuntimeException:
Undeclared fault....
        at
com.tibco.amf.platform.runtime.componentframework.internal.proxies.
ProxyInvocationHandler.invoke(ProxyInvocationHandler.java:473)
        at $Proxy21.invoke(Unknown Source)
        at
com.tibco.amf.binding.soap.runtime.transport.http.SoapHttpInboundEndpoin
t.
        processHttpPost(SoapHttpInboundEndpoint.java:250)
        at
com.tibco.amf.binding.soap.runtime.transport.http.SoapHttpServer.doPost(
SoapHttpServer.java:103)
        ...
        Caused by: java.lang.RuntimeException: Undeclared fault....
        at com.sample.faultservice.Component1.getWeather
(Component1.java:50)
        at sun.reflect.NativeMethodAccessorImpl.invoke0(Native Method)
        at sun.reflect.NativeMethodAccessorImpl.invoke
(NativeMethodAccessorImpl.java:39)
```

```

        at sun.reflect.DelegatingMethodAccessorImpl.invoke
(DelegatingMethodAccessorImpl.java:25)
        at java.lang.reflect.Method.invoke(Method.java:585)
        at
com.tibco.amf.platform.runtime.componentframework.internal.proxies.
    ProxyInvocationHandler.invoke(ProxyInvocationHandler.java:426)
    ... 20 more
    </tibco:myFaultDetail>
</detail>
</SOAP-ENV:Fault>
</SOAP-ENV:Body>
</SOAP-ENV:Envelope>

```

To specify SOAP fault subelements for undeclared faults, convert the runtime exception into a `com.tibco.amf.platform.runtime.extension.SOAPException` class. The following code fragment illustrates how to modify the subelements of the SOAP fault:

```

import com.tibco.amf.platform.runtime.extension.exception.SOAPException;
import com.tibco.amf.platform.runtime.extension.exception.SOAPDetail;
import com.tibco.amf.platform.runtime.extension.exception.SOAPCode;
import java.net.URI;
import org.w3c.dom.Element;
import org.w3c.dom.Node;
...
    URI role = null;
    try {
        role = new URI("http://soapexception.role");
    } catch (URISyntaxException e) {
        e.printStackTrace();
    }
    WeatherRequestType weatherRequest =
getWeatherRequest.getWeatherRequest();
    Node domNode = weatherRequest.getDomNode();
    //Set the original request as the fault detail
    SOAPDetail<Element> soapDetail = new SOAPDetail<Element>
(Element.class, (Element)domNode);
    SOAPCode soapCode = new SOAPCode(new QName("fault code"));

    SOAPException soapException = new SOAPException(soapCode, "reason",
role, soapDetail);
    throw soapException;
...

```

The following example illustrates how to catch the `SOAPException` exception returned by an invocation of a referenced service:



```

public WeatherResponseDocument getWeather(WeatherRequestDocument
getWeatherRequest)
    throws org.example.www.WeatherService.InvalidZipCodeFaultException {
    try {
        return getWeatherReportPT().getWeather(getWeatherRequest);
    } catch (InvalidZipCodeFaultException e) {
        System.out.println("====InvalidZipcodeFaultException====");
        throw e;
    } catch (Exception e) {
        System.out.println("====Runtime Exception====");
        if (e instanceof ServiceRuntimeException) {
            ServiceRuntimeException sre = (ServiceRuntimeException) e;
            Throwable cause = sre.getCause();
            if (cause instanceof SOAPException) {
                SOAPException soapex = (SOAPException) cause;
                if (soapex.getCode() != null) {
                    System.out.println("Fault code: " + soapex.getCode().toString());
                }
                if (soapex.getRole() != null) {
                    System.out.println("Fault role: " + soapex.getRole().toString());
                }
                throw soapex;
            }
        }
        throw new RuntimeException(e);
    }
    ...
    return null;
}

```

## SOAPException Reference

SOAPException has SOAPCode and SOAPDetail in its parameter list. All three are discussed below.

```

public SOAPException(final SOAPCode code, final String[] reason, final
URI node, final URI role, final SOAPDetail<T> detail)

```

The parameters of type SOAPXXX map to subelements of SOAP faults. Some of the parameters are for future use.

Parameter	Description
code	Intended for use by software to provide an algorithmic mechanism for

Parameter	Description
	identifying the fault.
reason	Provides a human readable explanation of the fault.
node	A URI that identifies the SOAP node that generated the fault. Its absence implies that the first recipient of the message generated the fault.
role	A URI identifying the source of the fault within the message path.
detail	Carries application-specific error information related to the Body element. It must not be used to carry information about error information belonging to header entries. Detailed error information belonging to header entries must be carried within header entries.

```
public SOAPCode(final QName codeValue, final SOAPCode
                subcode)
```

The type of the code parameter of `SOAPException`. The structure of the code parameter is hierarchical. The top-level code is a base fault and must be understood by all SOAP nodes. Nested codeValues are application-specific, and represent further elaboration or refinement of the base fault.

Parameter	Description
codeValue	The QName that identifies the code for the fault.
subcode	An optional subcode. Each child subcode element has a mandatory codeValue and an optional subcode subelement to support application-specific codes.

```
public SOAPDetail(final Class<T> detailType, final T detail)
```

The type of the detail parameter of `SOAPException`.

Parameter	Description
detailType	Type of the detailed data provided to the exception.
detail	Detail data provided to the exception. For example: <code>SOAPDetail&lt;Element&gt;</code> <code>soapDetail = new SOAPDetail&lt;Element&gt;(Element.class,</code> <code>(Element)domNode);</code>

## Context Parameters

A *context parameter* is a key-value pair passed to a service operation invocation. The values are populated by bindings, which map transport and binding headers to context parameters. Context parameters allow component developers to access transport and binding metadata that could affect the execution of an operation but which is not passed in the input, output, and fault messages defined by an abstract WSDL file.

A service may be supported on multiple types of transport bindings; each binding protocol specifies its own headers. For example, HTTP supports a body and headers that specify metadata that can be mapped to context parameters. The SOAP similarly defines a body and headers that are different than HTTP headers. The JMS protocol defines headers and allows developers to define application-specific properties. Typically, a client invoking a service sets some headers. For example, browsers usually set the HTTP Locale and Referrer headers.

Component implementations can read and set the values of context parameters and the values can be used to control service operation logic. The operation behavior thus changes according to the metadata. For example, consider a service that pays the agent that referred a customer to a website. To track the referrer on a SOAP/HTTP binding, you would specify a mapping from the HTTP Referrer header to a context parameter. If the service has a JMS binding, you would specify a mapping from a JMS message property named `referencedBy` to the same context parameter. When the incoming message is SOAP/HTTP, the HTTP Referrer header is copied into the context parameter and when a JMS message arrives, the `referencedBy` property is copied into the context parameter. The following table lists the header sources for each binding type.

*Header Source*

Binding Type	Header Source
SOAP/HTTP	HTTP Transport Header, HTTP Context, TCP Context, SOAP Header, SOAP Fault
SOAP/JMS	JMS Header, JMS Application Properties, SOAP Fault, SOAP Header
JMS	JMS Header, JMS Application Properties



**Note:** In the TIBCO ActiveMatrix platform, the context parameter key `com.tibco.security.userinformation` is used to communicate security context. It can be retrieved by a component from `requestContext`. However, when invoking a reference this context parameter may be overwritten by a policy agent before the SOAP binding maps it to a HTTP Transport Header or JMS application property. Therefore, you cannot set this context parameter in a component before invoking a reference.

The following sections list the headers available in each header source. The tables in each section list which headers are available in service or reference bindings.

- From: XXX Binding To: Context applies to inbound messages received on either a service ("in" part of "in-out" MEP) or a reference ("out|fault" part of "in-out" MEP)
- From: Context To: XXX Binding applies to outbound messages sent from either a service ("out|fault" part of "in-out" MEP) or a reference ("in" part of "in-out" MEP)

## HTTP Context

From: SOAP/HTTP Binding (WS-A = OFF)	To: Context
Service	HTTP-Method, HTTP-FileSpec, HTTP-Version
Reference	HTTP-Status-Code, HTTP-Status-Message

<b>From: SOAP/HTTP Binding (WS-A = ON)    To: Context</b>	
Service	HTTP-Method, HTTP-FileSpec, HTTP-Version
Reference	None

## TCP Context

<b>From: SOAP/HTTP Binding    To: Context</b>	
Service	Local-TCP-Host, Local-TCP-Port, Remote-TCP-Host, Remote-TCP-Port
Reference	None

## SOAP Fault

<b>From: SOAP Binding (For Declared Faults)    To: Context</b>	
Service	None
Reference	Role, Code

<b>From: Context    To: SOAP Binding (For Declared Faults)</b>	
Service	Role, Code
Reference	None

## JMS Header

From: SOAP/JMS Binding	To: Context
Service	JMSCorrelationID, JMSDeliveryMode, JMSMessageID, JMSType
Reference	None
From: Context	To: SOAP/JMS Binding
Service	None
Reference	JMSCorrelationID, JMSDeliveryMode, JMSType

For information on how to create context parameters, see *TIBCO ActiveMatrix® Service Grid Composite Development*.

The first time you add a context parameter to a service or reference wired to a Spring component, an error badge is added to the Spring component and the error is reported in the Problems view. When you resolve the error by updating the implementation, the following is added to the abstract component implementation:

```
import org.osoa.sca.annotations.Context;
import
com.tibco.amf.platform.runtime.extension.context.ComponentContext;
/**
 *      Use this property to access the context parameters.
 *      Context parameters for this component are:
 *      parameterName : DIRECTION
 */
@Context
public ComponentContext componentContext;
```

For each successive parameter, no error badge is added to the component. To update the list of context parameters in the comment, update the component implementation.

Methods defined on `ComponentContext` allow you to retrieve and set a `RequestContext`, which in turn has methods for retrieving and setting the context parameters.

## Working with Context Parameters

You can retrieve a context parameter from a request or from a response, and set a context parameter in a request or a response.

### Retrieving a Context Parameter from a Request

#### Procedure

1. Retrieve the request context:

```
import
com.tibco.amf.platform.runtime.extension.context.RequestContext;
RequestContext requestContext =
(RequestContext)componentContext.getRequestContext();
```

2. Retrieve the parameter from the request context:

```
requestContext.getParameter(parameterName, Type.class);
```

where Type can take the values String, Integer, Long, Boolean, Map, QName, and URI.

### Setting a Context Parameter in a Request

#### Procedure

1. Create a mutable request context:

```
import
com.tibco.amf.platform.runtime.extension.context.MutableRequestCont
ext;
MutableRequestContext mutableRequestContext = componentContext.
createMutableRequestContext();
```

2. Set a parameter on the mutable request context:

```
mutableRequestContext.setParameter(parameterName,
```

```
Type.class,parameterValue);
```

3. Set the request context on the component's context to the mutable request context:

```
componentContext.setRequestContext(mutableRequestContext);
```

4. Invoke a reference.

**i Note:** The `componentContext.getRequestContext()` function returns the request context that corresponds to the last remotable service invocation whereas `componentContext.setContext()` assigns the context that gets used for the next downstream service invocation. For example, in the following case, `curCtx` does not equal to `newCtx` but equals to `oldCtx`.

```
RequestContext oldCtx =
(RequestContext)componentContext.getRequestContext();
MutableRequestContext newCtx =
componentContext.createMutableRequestContext();
componentContext.setRequestContext(newCtx);
RequestContext curCtx =
(RequestContext)componentContext.getRequestContext();
```

## Retrieving a Context Parameter from a Response

### Procedure

1. Retrieve a callback context from the mutable request context:

```
import
com.tibco.amf.platform.runtime.extension.context.CallbackContext;
                                CallbackContext callbackContext
=mutableRequestContext.getCallbackContext();
```

2. Retrieve a parameter from the callback context:

```
callbackContext.getParameter(parameterName, Type.class);
```



## Setting a Context Parameter in a Response

### Procedure

1. Retrieve a mutable callback context from the original request context:

```
import
com.tibco.amf.platform.runtime.extension.context.MutableCallbackContext;

MutableCallbackContext mutableCallbackContext =
(MutableCallbackContext)requestContext.getCallbackContext();
```

2. Set a parameter on the mutable callback context:

```
mutableCallbackContext.setParameter(parameterName,
                                   Type.class, parameterValue);
```

## Distributed File System Example

A distributed file system component manages files based on the host address of the machine on which the file was created. The address is tracked in a context parameter named `httpHost`:

Name	Operations	Direction	Type	Definition
httpHost	prepareFragmentedWrite,write	Input	Basic	string

The file system component is invoked by SOAP clients through a service with a SOAP binding and by a web application component.

- If a request comes through the SOAP binding, the context parameter is mapped to the TCP remote host header by the SOAP binding:

Context Parameter	Direction	Header Source	Header Name
httpHost	INPUT	TCP	remoteHost

- If the request originates from the web application, the parameter value is retrieved from the HTTP request and manually set by the servlet implementing the web application component:

```
String host = req.getRemoteHost();
MutableRequestContext mutableRequestContext =
componentContext.createMutableRequestContext();
mutableRequestContext.setParameter("httpHost", String.class, host);
componentContext.setRequestContext(mutableRequestContext);
```

The file system component retrieves the value of the context parameter as follows:


```
RequestContext requestContext = componentContext.getRequestContext();
String host requestContext.getParameter("httpHost", String.class);
```

## Dynamic Binding Example

Application logic can depend on the value of the application and service name. In particular, the application logic may be used to dynamically determine the target of a reference invocation (also referred to as wire by implementation) in a mediation flow. The following example illustrates how to retrieve the application and service name in a Spring component that invokes a mediation component service, and set context parameters with that data:

```
String appName = componentContext.getApplicationName();
String svcname = componentContext.getRequestContext().getServiceName();
MutableRequestContext mutableRequestContext
=componentContext.createMutableRequestContext();
mutableRequestContext.setParameter("ServiceName",
java.lang.String.class,svcname);
mutableRequestContext.setParameter("ApplicationName",
java.lang.String.class, appName);
componentContext.setRequestContext(mutableRequestContext);
```

The context parameters are then mapped in the mediation flow's Set Dynamic Reference task property sheet as follows:



# Endpoint References

If WS-Addressing is enabled on a SOAP binding, endpoint references are accessible from within Spring component implementations. For information on enabling WS-Addressing and endpoint references, see "WS-Addressing" in *TIBCO ActiveMatrix® Service Grid Composite Development*.

## Retrieving an Endpoint Reference

### Before you begin

Enable the SOAP binding that delivers the message to the Spring component for WS-Addressing to use reference parameters.

### Procedure

1. Import context, endpoint reference, request context, wildcard extension, and URI class definitions:

```
import
com.tibco.amf.platform.runtime.extension.context.ComponentContext;
import
com.tibco.amf.platform.runtime.extension.context.EndpointReference;
import
com.tibco.amf.platform.runtime.extension.context.RequestContext;
import
com.tibco.amf.platform.runtime.extension.context.WildCardExtension;
import java.net.URI;
```

2. Declare the component context:

```
@Context
public ComponentContext componentContext;
```

3. Retrieve the request context:

```
RequestContext requestContext =
(RequestContext)componentContext.getRequestContext();
```

4. Retrieve the endpoint reference:

```
EndpointReference<Element> endpointReference =
    requestContext.getEndpointReference(Element.class);
```

5. Optionally retrieve the URI and reference parameters from the endpoint reference:

```
URI uri = endpointReference.getAddress().getURI();
WildcardExtension<Element> refElements =
    endpointReference.getReferenceParameters();
```

## Creating an Endpoint Reference

### Before you begin

Enable the SOAP binding that delivers the message to the Spring component for WS-Addressing to use reference parameters.

You must set an endpoint reference object before invoking a reference that is dynamically wired to a service.

### Procedure

1. Import context, endpoint reference, and URI class definitions:

```
import org.osoa.sca.annotations.Context;
import
com.tibco.amf.platform.runtime.extension.context.ComponentContext;
import
com.tibco.amf.platform.runtime.extension.context.EndpointReference;
import
com.tibco.amf.platform.runtime.extension.context.MutableRequestCont
ext;
import
com.tibco.amf.platform.runtime.extension.support.ElementEndpointRef
erence;
import
com.tibco.amf.platform.runtime.extension.support.ElementWildcardExt
ension;
```

2. Declare the component context:

```
@Context
public ComponentContext context;
```

3. Create an endpoint reference:

```
EndpointReference<Element> epr = new ElementEndpointReference
(targetURI);
```

4. Optionally create and set a list of parameters. For example:

```
String property1= "<property1 " + "xmlns=\"" + WSQName +
"\>value1</property1>";
String property2= "<property2 " + "xmlns=\"" + WSQName +
"\>value2</property2>";
List<Element> elements = Arrays.asList(
    DOMUtils.getDOMNode(property1).getDocumentElement(),
    DOMUtils.getDOMNode(property2).getDocumentElement());
ElementWildcardExtension refParams = new
ElementWildcardExtension(null, elements);
epr.setReferenceParameters(refParams);
```

5. Create a mutable request context object:

```
MutableRequestContext mctxt =
(MutableRequestContext)context.createMutableRequestContext();
```

6. Set the endpoint reference of the mutable context object:

```
mctxt.setEndpointReference(epr);
```

7. Set the request context of the component context to the mutable request context:

```
context.setRequestContext(mctxt);
```

```
import org.osoa.sca.annotations.Context;
import
com.tibco.amf.platform.runtime.extension.context.ComponentContext;
import
com.tibco.amf.platform.runtime.extension.context.EndpointReference;
import
com.tibco.amf.platform.runtime.extension.context.MutableRequestContext;
```

```

import
com.tibco.amf.platform.runtime.extension.support.ElementEndpointReferenc
e;
import
com.tibco.amf.platform.runtime.extension.support.ElementWildcardExtensio
n;
import java.net.URI;
import java.util.List;
import java.util.Arrays;
@Context
public ComponentContext context;
public static final String WSQName = "com.ws.base";
private void setEPR(URI targetURI) {
    EndpointReference<Element> epr = new ElementEndpointReference
(targetURI);

    String property1= "<property1 " + "xmlns=\"" + WSQName +
"\>value1</property1>";
    String property2= "<property2 " + "xmlns=\"" + WSQName +
"\>value2</property2>";
    List<Element> elements = Arrays.asList(
        DOMUtils.getDOMNode(property1).getDocumentElement(),
        DOMUtils.getDOMNode(property2).getDocumentElement());
    ElementWildcardExtension refParams = new ElementWildcardExtension
(null, elements);
    epr.setReferenceParameters(refParams);

    MutableRequestContext mctxt = (MutableRequestContext)
context.createMutableRequestContext();
    mctxt.setEndpointReference(epr);
    context.setRequestContext(mctxt);
}

```

## Referencing an External Spring Application

### Procedure

1. Import the external Spring application into the workspace as a plug-in project.
  - a. Create a new plug-in project using the **Plug-in Development > Plug-in from existing JAR archives**.
  - b. In the JAR selection screen, click **Add External** and select the external Spring

application JAR file.

- c. Enter the plug-in properties and clear the **Unzip the JAR archives into the project** checkbox.
2. Edit the external Spring application to export the packages referenced by the Spring component implementation.
  - a. Expand the META-INF directory of the external Spring application plug-in project.
  - b. Double-click MANIFEST.MF.
  - c. In the Manifest editor, click the **Runtime** tab.
  - d. In the Exported Packages area, click **Add** and select the **Show non Java Packages** checkbox.
  - e. Select the library JAR file and click **OK** to add it.
3. Configure dependencies as described in [Configuring Dependencies on External Java Classes](#).
4. Edit the Spring Bean configuration file:
  - a. Add the `import` statement to the bean definition that points to the location of the external Spring application configuration file:

```
<import resource="classpath:/location_of_external_springbean.xml">
```

- b. Add the property tags from the external Spring application to the bean definition:

```
<property name="propertyName" ref="BeanId_External">
```

5. Edit the Spring component's implementation class to delegate calls to the external Spring application's classes.

The following example illustrates how to delegate calls from class `HelloWorldPTImpl` to the external Spring class `MyLegacyJavaClass`:

```
public class HelloWorldPTImpl extends AbstractHelloWorldPTImpl {
    /**
     * Initialization of ReuseLegacySpringComponent component.
```

```

    */
    private MyLegacyJavaClass legacyBean;
    public void init() {
        // Component initialization code.
        // All properties are initialized and references are injected.
        if(this.legacyBean !=null){
            System.out.println( "Legacy Bean Initilized...");
            System.out.println( this.legacyBean.sayHello("World"));
        } else {
            throw new IllegalStateException("Injected bean is null");
        }
    }
    /**
    * Disposal of ReuseLegacySpringComponent component.
    */
    @Destroy
    public void destroy() {
        // Component disposal code.
        // All properties are disposed.
    }
    /**
    * Implementation of the WSDL operation: sayHello      */
    public HelloResponseDocument sayHello(HelloRequestDocument
    firstName) {
        HelloResponseDocument
        hrd=HelloResponseDocument.Factory.newInstance();
        hrd.setHelloResponse(getLegacyBean().sayHello(
            firstName.getHelloRequest()).toString());
        return hrd;
    }
    public MyLegacyJavaClass getLegacyBean() {
        return legacyBean;
    }
    public void setLegacyBean(MyLegacyJavaClass legacyBean) {
        this.legacyBean = legacyBean;
    }
}

```



# Custom Features

---

A *feature* is a software package that contains plug-ins, which in turn contain component implementations and libraries. A feature is identified by an ID, a multi-part version, and its dependencies on other features. There are two types of features: system and shared library.

System features are part of a TIBCO ActiveMatrix product or contain the drivers that are installed using TIBCO Configuration Tool. Shared library features contain component implementations and libraries. When you create a distributed application archive containing a composite, you can package the composite's required features in the application archive or you can package the features as a standalone distributed application archive.

When you upload a distributed application archive containing a composite in Administrator you can optionally import the features contained in the archive into the Administrator software repository. When you deploy an application, the Administrator automatically distributes the features (and any features that it depends on) to the host that manages the nodes on which the application is distributed and installs the features on those nodes. You can also manually install features on the other nodes managed by that host.

## Version Numbers

A version number is a multicomponent number of the form *major.minor.service.qualifier*. Changes in the value of each component reflect different types of changes in the versioned object:

- *major* - Reflects breaking changes to the interface.
- *minor* - Reflects non-breaking changes in an externally visible way. Examples of externally visible changes include binary compatible changes, significant performance changes, major code rework, and so on.
- *service* - Reflects changes that are not visible in the interface. For example, a bug has been fixed in the code, documentation has changed, compiler settings have changed, and so on.
- *qualifier* - Identifies when and where the object was built or packaged.

When you create an object in TIBCO Business Studio - BPM Edition, the version is set to

"1.0.0.qualifier". If the *qualifier* component of a version is set to "qualifier" when you create a DAA, TIBCO Business Studio - BPM Edition replaces "qualifier" with a generated qualifier that defaults to a timestamp. You can customize the format of the generated qualifier by specifying a qualifier replacement.

## Version Ranges

Some fields require you to specify a version range. For example, a feature may have a dependency on a range of versions of another feature. A *version range* is an interval specified as: *bracket**lower limit*, *upper limit**bracket*, where *bracket* can be "[" or "]", which denotes an inclusive end of the range or "(" or ")", which denotes an exclusive end of the range. If one end of the range is to be included and the other excluded, the range can contain a square bracket with a round bracket.

There are three common use cases:

- A strict version range, such as [1.0.0,1.0.0], denotes version 1.0.0 and only that version.
- A half-open range, such as [1.0.0,2.0.0), which has an inclusive lower limit and an exclusive upper limit, denotes version 1.0.0 and any later version, up to, but not including, version 2.0.0.
- An unbounded open range expressed as a single number such as 2.0.0, which is equivalent to the range [2.0.0, *infinity*), denotes version 2.0.0 and any later version.

A custom feature named *compositeName.customfeature.id* containing the component implementation plug-in is created automatically when you generate a component implementation. The custom feature file is stored in the `Deployment Artifacts` folder of the SOA project.

## Bundles and Plug-in Projects

A *bundle* is an OSGI mechanism for grouping Java classes into a modular, sharable unit. In TIBCO Business Studio - BPM Edition, a plug-in project implements a bundle.

Plug-in properties, including the packages it exports and the objects on which it depends, are described in the plug-in manifest. The manifest file is located in *plug-inFolderName*META-INF/MANIFEST.MF. The default editor for the file is a manifest editor which displays OSGi headers in property sheets and in the MANIFEST.MF source view. The following table summarizes the best practices you should follow when configuring plug-ins.

*Plug-in Project Best Practices*

Property	Manifest Editor UI	OSGi Header in Source View	Best Practice
Unique Identifier	<b>Overview &gt; ID</b>	Bundle-SymbolicName	Give the plug-in a symbolic name that follows Java package name conventions. That is, <code>com.companyName.pluginName</code> .
Version	<b>Overview &gt; Version</b>	Bundle-Version	Follow the recommendations in <a href="#">Versions</a> .
Display Name	<b>Overview &gt; Name</b>	Bundle-Name	Give the plug-in an appropriate, descriptive display name.
Dependencies	<b>Dependencies &gt;</b>  <b>Imported Packages</b>  <b>Required Plug-ins</b>	Import-Package  Require-Bundle	<ul style="list-style-type: none"> <li>Express dependencies based on the contents of the plug-in: <ul style="list-style-type: none"> <li>For plug-ins that you create or if you want tight control of the dependency, specify the dependency as a required bundle. You can (but are not required to) indicate a perfect match to a specific plug-in and build. For example, when TIBCO Business Studio - BPM Edition generates a component implementation, the component's dependency on the plug-in containing the component implementation is expressed as <code>[1.0.0.qualifier,1.0.0.qualifier]</code>.</li> </ul> </li> </ul>

Property	Manifest Editor UI	OSGi Header in Source View	Best Practice
			<ul style="list-style-type: none"> <li>◦ For third-party plug-ins, specify the dependency as an imported package. To allow packages to be upgraded without requiring plug-ins dependent on those packages to be upgraded, specify package dependency ranges of the form <code>[x.y.z,x+1.0.0)</code>. That is, up to, but not including the next major version. For example, <code>[2.3.0, 3.0.0)</code>.</li> <li>• Minimize or eliminate optional imports.</li> </ul>
Exported Packages	<b>Runtime &gt; Exported Packages</b>	Export-Package	<ul style="list-style-type: none"> <li>• Export only those packages imported by other plug-ins.</li> <li>• Put classes that are not exported in packages that are not exported.</li> <li>• Specify versions of all exported packages.</li> <li>• Import all exported packages, with a range floor of the exported package version, and a range ceiling of the next major version exclusive, per the range definition above.</li> <li>• If the classes in the exported packages use other classes (for example, they extend classes from another package or the classes appear in method signatures) add</li> </ul>

Property	Manifest Editor UI	OSGi Header in Source View	Best Practice
			the uses directive to the export package definition.

## Configuring Dependencies on External Java Classes

Java and Spring component implementations can use Java classes contained in a library plug-in project in the same workspace as the component implementation. You must configure the dependency in both the component implementation and component.


### Procedure

1. Expand the META-INF directory of plug-in project containing the component implementation.
2. Double-click MANIFEST.MF.  
The manifest opens in the manifest editor.
3. Click the **Dependencies** tab.
4. Follow the appropriate procedure based on the [dependency](#) type.

Dependency Type	Procedure
Plug-in	<ol style="list-style-type: none"> <li>a. Click <b>Add</b> to the right of the Required Plug-ins table.</li> <li>b. Select the plug-in containing the referenced class.</li> <li>c. Click <b>OK</b>.</li> </ol> <p>For example, if you reference a temperature conversion plug-in in a Spring component implementation, add tempconversion.jv as a required plug-in:</p>

## Dependency Type


## Procedure



### Package

- Click **Add** to the right of the Imported Packages table.
- Click the referenced package.
- Click **OK**.

For example, if you reference a logging class in a Spring component implementation, add `org.slf4j` as an imported package:



- If the library plug-in is packaged and deployed separately from the component implementation:
  - Open the composite.
  - Click the Spring component.
  - In the Properties view, click the **Implementation** tab.
  - Clear the **Package Implementation Bundle with Application** and **Compute Feature Dependencies** checkboxes.

The Features Dependencies table displays.

- e. In the Feature Dependencies table, click the feature that contains the library plug-in.
- f. Relax value of the version as described in [External Library Dependencies](#).

## Versions

A *version* is a property that controls how an object is treated at installation or deployment. Versions are specified in TIBCO Business Studio - BPM Edition and cannot be modified in Administrator.

The following objects have versions:

- Composites and application templates.
- Components - During application upgrade, Administrator compares component versions to determine whether the component needs to be upgraded.
- Features
- Plug-ins
- Packages

## Version Numbers

A version number is a multicomponent number of the form *major.minor.service.qualifier*. Changes in the value of each component reflect different types of changes in the versioned object:

- *major* - Reflects breaking changes to the interface.
- *minor* - Reflects non-breaking changes in an externally visible way. Examples of externally visible changes include binary compatible changes, significant performance changes, major code rework, and so on.
- *service* - Reflects changes that are not visible in the interface. For example, a bug has been fixed in the code, documentation has changed, compiler settings have changed, and so on.
- *qualifier* - Identifies when and where the object was built or packaged.

When you create an object in TIBCO Business Studio - BPM Edition, the version is set to

"1.0.0.qualifier". If the *qualifier* component of a version is set to "qualifier" when you create a DAA, TIBCO Business Studio - BPM Edition replaces "qualifier" with a generated qualifier that defaults to a timestamp. You can customize the format of the generated qualifier by specifying a qualifier replacement.

## Version Ranges

Some fields require you to specify a version range. For example, a feature may have a dependency on a range of versions of another feature. A *version range* is an interval specified as: *bracket**lower limit*, *upper limit**bracket*, where *bracket* can be “[” or “]”, which denotes an inclusive end of the range or “(” or “)”, which denotes an exclusive end of the range. If one end of the range is to be included and the other excluded, the range can contain a square bracket with a round bracket.

There are three common use cases:

- A strict version range, such as [1.0.0,1.0.0], denotes version 1.0.0 and only that version.
- A half-open range, such as [1.0.0,2.0.0), which has an inclusive lower limit and an exclusive upper limit, denotes version 1.0.0 and any later version, up to, but not including, version 2.0.0.
- An unbounded open range expressed as a single number such as 2.0.0, which is equivalent to the range [2.0.0, *infinity*), denotes version 2.0.0 and any later version.



# Default XML to Java Mapping

---

When you generate a Spring component implementation or XML data binding classes, TIBCO Business Studio - BPM Edition maps WSDL and XSD schema elements to Java programming language elements.

The following sections describe the default mappings of WSDL definitions, types, portType, operation, message, part, and fault elements to Java.

**i Note:** Generating implementations for two or more components in the same Java plug-in project using different binding types is not supported.

**i Note:** The payload for a xsd:gMonth datatype is converted incorrectly if you use JAXB data binding.

## wsdl:definitions

The `wsdl:definitions` element's `targetNamespace` attribute is mapped to a Java package. By default, for a target namespace whose structure is: `http://rootPart/subPart`, the order of the elements in the root part of the target namespace are reversed in the package name. Subparts appearing after the root part separated by slashes are appended to the root part with a period (.). For example, the namespace `http://ns.tibco.com/StockQuote` becomes the package `com.tibco.ns.stockQuote`. If the first character of a namespace identifier is invalid, the preprocessor prepends an underscore `_` in front of the identifier.

## wsdl:portType

A `wsdl:portType` element is mapped to a Java interface. The name of the interface is the value of the `name` attribute of the corresponding `wsdl:portType` element.

The generated interface contains Java methods mapped from the `wsdl:operation` subelements of the `wsdl:portType` element. Since WSDL 1.1 does not support port type inheritance, each generated interface contains methods for all the operations in the corresponding port type.

## wsdl:operation

Each `wsdl:operation` element is mapped to a Java method in the corresponding Java interface. The `name` attribute of the `wsdl:operation` element determines the name of the generated method. If the `wsdl:operation` element contains a `wsdl:fault` message, the fault is mapped to a Java exception that appears in the `throws` clause of the generated method. See also [wsdl:fault](#).

## wsdl:output, wsdl:input, and wsdl:part

The `name` attribute of the `part` element of the `wsdl:output` message is mapped to the return type of the generated Java method according to the XML data binding type as follows:

- JAXB - *name*
- XMLBeans - *nameDocument*

The method for accessing components of request parameters and defining response objects depends on the type of data binding you choose.

### JAXB

The `type` or `element` attribute of the `part` element of the `wsdl:input` message is mapped to the type of the input parameter of the generated Java method. The `name` attribute of the `part` element of the `wsdl:input` message is mapped to the name of an input parameter of the generated Java method. You can directly access components of a request parameter as follows:

```
public AddPhoneResponse addPhone(AddPhoneRequest addPhoneParameters) {
    ...
    String firstName = addPhoneParameters.getFirstName();
    String lastName = addPhoneParameters.getLastName();
    String phone = addPhoneParameters.getPhone();
}
```

To create a response object or a complex object defined in the WSDL document:

1. Import `packageName.ObjectFactory`, where *packageName* is the package name generated from the WSDL document namespace.
2. Create an instance of `ObjectFactory`.
3. Create an object of type *Type* with the `createType` method.

For example:

```

import com.tibco.ns.hello.phonebook.ObjectFactory;
import com.tibco.ns.hello.phonebook.GetPhoneResponse;
...
ObjectFactory objectFactory = new ObjectFactory();
GetPhoneResponse phoneResponse = objectFactory.createGetPhoneResponse();

try{
    ...
    PhoneEntryType entry = objectFactory.createPhoneEntryType();
    while(rs.next()){
        entry.setEntryId(rs.getString("id"));
        entry.setFirstName(rs.getString("firstName"));
        entry.setLastName(rs.getString("lastName"));
        entry.setPhone(rs.getString("phone"));
    }
}catch(SQLException e){
    ...
}
return phoneResponse;

```

**i Note:** When implementing a JAXB-based Spring component service, users typically form a response object in their service method, populate it with some response data, and return it from the method. Such a returned object is then marshaled into an XML (DOM) payload by the platform. While the platform code is marshaling this payload, if the user code manipulates the contents of the same object, the JAXB marshaller throws a `java.util.ConcurrentModificationException`. Make sure the contents of the response object returned from the service method are not modified by multiple threads.

## XMLBeans

There are two ways to specify the type of a message part: indirectly through an `element` attribute that is defined in the `wsdl:types` element or directly with a `type` attribute. If you use XMLBeans binding, the generated Java code depends on how you specify the types of message parts.

When you define the types of the parts through the `element` attribute classes named *ElementNameDocument*, where *ElementName* is the input and output message type element name with the first letter capitalized, are generated. The generated Java method accepts a document type named *ElementNameDocument*. The generated method returns a document

type similarly named according to the element that specifies the type of the output message part.

In the following WSDL document, the types of the message parts are defined through an element attribute:

```
<wsdl:definitions
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:tns="http://ns.tibco.com/StockQuote/"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
  targetNamespace="http://ns.tibco.com/StockQuote/">
  <wsdl:types>
    <xs:schema xmlns:xs="http://www.w3.org/2001/XMLSchema"
      attributeFormDefault="unqualified"
      elementFormDefault="qualified"
      targetNamespace="http://ns.tibco.com/StockQuote/">
      <xs:element name="symbol" type="xs:string"/>
      <xs:element name="quote" type="xs:float"/>
    </xs:schema>
  </wsdl:types>
  <wsdl:message name="OperationRequest">
    <wsdl:part name="stockQuoteRequest" element="tns:symbol"/>
  </wsdl:message>
  <wsdl:message name="OperationResponse">
    <wsdl:part name="stockQuoteResponse" element="tns:quote"/>
  </wsdl:message>
  <wsdl:portType name="StockPT">
    <wsdl:operation name="getQuote">
      <wsdl:input message="tns:OperationRequest"/>
      <wsdl:output message="tns:OperationResponse"/>
    </wsdl:operation>
  </wsdl:portType>
</wsdl:definitions>
```

The following code fragment shows the generated Java class implementation:

```
import com.tibco.stockQuote.SymbolDocument;
import com.tibco.stockQuote.QuoteDocument;

public class StockQuoteServiceImpl extends AbstractStockQuoteServiceImpl
{
  public QuoteDocument getQuote(SymbolDocument stockQuoteRequest)
  {
    String sym = stockQuoteRequest.getSymbol();
    float quote = quoteLookup(sym);
  }
}
```

```

        QuoteDocument response = QuoteDocument.Factory.newInstance();
        response.setQuote(quote);
        return response;
    }
}

```

The relationships between the message part, message part type, message type element, and document type are:

Message Part	Type	Element	Document Type
stockQuoteRequest	xs:string	tns:symbol	SymbolDocument
stockQuoteResponse	xs:float	tns:quote	QuoteDocument

The value of the request message part is retrieved from the document using bean-style accessors. In the example, the stock symbol is retrieved from the `SymbolDocument` object with the `getSymbol` method.

You create a response document, of type `QuoteDocument`, by calling the `newInstance` method of the document factory class. Finally, you set the value of the response message part by calling the `setQuote` method on the response document.

In the following WSDL document, the types of the message parts are specified through a `type` attribute:

```

<wsdl:definitions
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:tns="http://ns.tibco.com/StockQuote/"
  xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
  name="Untitled" targetNamespace="http://ns.tibco.com/StockQuote/">
  <wsdl:message name="OperationRequest">
    <wsdl:part name="symbol" type="xs:string"/>
  </wsdl:message>
  <wsdl:message name="OperationResponse">
    <wsdl:part name="quote" type="xs:float"/>
  </wsdl:message>
  <wsdl:portType name="StockPT">
    <wsdl:operation name="getQuote">
      <wsdl:input message="tns:OperationRequest"/>
      <wsdl:output message="tns:OperationResponse"/>
    </wsdl:operation>
  </wsdl:portType>

```

```

        </wsdl:operation>
    </wsdl:portType>
</wsdl:definitions>

```

For this WSDL document, the generated Java code references the message parts directly, instead of through documents. However, the types of the message parts are XMLBeans types, which means that you must use the XMLBeans API to access the XML data bound to Java objects and convert between XMLBeans types and native Java types in your method implementation. To perform this conversion, you use `[get|set]TypeValue` methods, where *Type* is the native Java type. Like the document types described earlier, you create XMLBeans objects by calling the `newInstance` method of the type's Factory class.

```

import org.apache.xmlbeans.XmlFloat;
import org.apache.xmlbeans.XmlString;

public class StockQuoteServiceImpl extends AbstractStockQuoteServiceImpl
{
    public XmlFloat getQuote(XmlString symbol){
        float quote = quoteLookup(symbol.getStringValue());
        XmlFloat resp = XmlFloat.Factory.newInstance();
        resp.setFloatValue(quote);
        return resp;
    }
}

```

## wsdl:fault

A `wsdl:fault` element is mapped to a Java exception. The generated exception class extends the class `java.lang.Exception`. The name of the exception is formed by concatenating the name attribute of the `wsdl:message` referenced by the `wsdl:fault` element with `Exception`. For the following WSDL fragment, the exception class would be named `GetCurrentTimeFaultMsgException`.

```

<schema>
...
<element name="CurrentTimeFault" type="string"/>
...
</schema>
<wsdl:message name="getCurrentTimeFaultMsg">
    <wsdl:part element="tns:getCurrentTimeFault" name="faultInfo"/>

```

```
</wsdl:message>
<wsdl:portType name="DateManagerPT">
  <wsdl:operation name="getCurrentTime">
    <wsdl:input message="tns:OperationRequest"/>
    <wsdl:output message="tns:OperationResponse"/>
    <wsdl:fault message="ns0:getCurrentTimeFaultMsg" name="faultMsg"/>
  </wsdl:operation>
</wsdl:portType>
```

## XMLBeans

A fault object named *faultDocument* is generated, where *fault* is the type of the fault message's part. For the preceding WSDL fragment, the fault object would be named *GetCurrentTimeFaultDocument*.

# TIBCO Documentation and Support Services

---

For information about this product, you can read the documentation, contact TIBCO Support, and join TIBCO Community.

## How to Access TIBCO Documentation

Documentation for TIBCO products is available on the [Product Documentation website](#), mainly in HTML and PDF formats.

The [Product Documentation website](#) is updated frequently and is more current than any other documentation included with the product.

## Product-Specific Documentation

The documentation for this product is available on the [TIBCO ActiveMatrix® Service Grid Product Documentation](#) page.

## How to Contact Support for TIBCO Products

You can contact the Support team in the following ways:

- To access the Support Knowledge Base and getting personalized content about products you are interested in, visit our [product Support website](#).
- To create a Support case, you must have a valid maintenance or support contract with a Cloud Software Group entity. You also need a username and password to log in to the [product Support website](#). If you do not have a username, you can request one by clicking **Register** on the website.

## How to Join TIBCO Community

TIBCO Community is the official channel for TIBCO customers, partners, and employee subject matter experts to share and access their collective experience. TIBCO Community offers access to Q&A forums, product wikis, and best practices. It also offers access to extensions, adapters, solution accelerators, and tools that extend and enable customers to gain full value from TIBCO products. In addition, users can submit and vote on feature



requests from within the [TIBCO Ideas Portal](#). For a free registration, go to [TIBCO Community](#).

# Legal and Third-Party Notices

---

SOME CLOUD SOFTWARE GROUP, INC. (“CLOUD SG”) SOFTWARE AND CLOUD SERVICES EMBED, BUNDLE, OR OTHERWISE INCLUDE OTHER SOFTWARE, INCLUDING OTHER CLOUD SG SOFTWARE (COLLECTIVELY, “INCLUDED SOFTWARE”). USE OF INCLUDED SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED CLOUD SG SOFTWARE AND/OR CLOUD SERVICES. THE INCLUDED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER CLOUD SG SOFTWARE AND/OR CLOUD SERVICES OR FOR ANY OTHER PURPOSE.

USE OF CLOUD SG SOFTWARE AND CLOUD SERVICES IS SUBJECT TO THE TERMS AND CONDITIONS OF AN AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER AGREEMENT WHICH IS DISPLAYED WHEN ACCESSING, DOWNLOADING, OR INSTALLING THE SOFTWARE OR CLOUD SERVICES (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH LICENSE AGREEMENT OR CLICKWRAP END USER AGREEMENT, THE LICENSE(S) LOCATED IN THE “LICENSE” FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE SAME TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of Cloud Software Group, Inc.

TIBCO, the TIBCO logo, the TIBCO O logo, ActiveMatrix, Business Studio, Enterprise Message Service, and Hawk are either registered trademarks or trademarks of Cloud Software Group, Inc. in the United States and/or other countries.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only. You acknowledge that all rights to these third party marks are the exclusive property of their respective owners. Please refer to Cloud SG’s Third Party Trademark Notices (<https://www.cloud.com/legal>) for more information.

This document includes fonts that are licensed under the SIL Open Font License, Version 1.1, which is available at: <https://scripts.sil.org/OFL>

Copyright (c) Paul D. Hunt, with Reserved Font Name Source Sans Pro and Source Code Pro.

Cloud SG software may be available on multiple operating systems. However, not all operating system platforms for a specific software version are released at the same time. See the “readme” file for the availability of a specific version of Cloud SG software on a specific operating system platform.

THIS DOCUMENT IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. CLOUD SG MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S), THE PROGRAM(S), AND/OR THE SERVICES DESCRIBED IN THIS DOCUMENT AT ANY TIME WITHOUT NOTICE.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "README" FILES.

This and other products of Cloud SG may be covered by registered patents. For details, please refer to the Virtual Patent Marking document located at <https://www.tibco.com/patents>.

Copyright © 2010-2025. Cloud Software Group, Inc. All Rights Reserved.