



TIBCO BusinessConnect™ Container Edition

Installation and Deployment

*Version 1.2.0
October 2022*



Contents

Contents	2
Installation Overview	3
Installation Requirements	4
System Requirements	4
Required TIBCO Products	5
Required Third-Party Products	6
BusinessConnect Container Edition Migration	8
Migrating from Release 6.4.x or 7.x	8
Migrating from Release 1.0.0, 1.1.0, or 1.1.1	10
BusinessConnect Container Edition Dockerfiles and Scripts	12
Dockerfiles and Scripts	12
Configuration files	13
Deploying BusinessConnect Container Edition Application	14
Building BusinessConnect Container Edition Component's Docker Images	14
Deploying BusinessConnect Container Edition Component's Docker Images	16
Uninstalling BusinessConnect Container Edition	22
Viewing Container Logs	23
TIBCO Documentation and Support Services	24
Legal and Third-Party Notices	26

Installation Overview


TIBCO BusinessConnect™ Container Edition is the containerized edition of TIBCO BusinessConnect™, TIBCO's leading enterprise B2B gateway.

BusinessConnect™ Container Edition does not have TIBCO Universal Installer. It contains Dockerfiles, scripts, and configuration files with preloaded settings to build and deploy Docker images of each component either on Docker or Kubernetes platform.

Installation Requirements

Before you install and deploy the application, ensure that your system meets all the hardware and software requirements. For more information about the hardware and software requirements, supported platforms, versions, and the required patches, see the product *Readme* file.

The *Readme* file can be obtained either on the [TIBCO Product Documentation](#) website or from the [TIBCO eDelivery](#) website with the product software.

 **Note:** To access the [TIBCO eDelivery](#) website, you need a user name and password. If you did not receive a user name and password, contact [TIBCO Support](#).

System Requirements

Platform

The supported platforms are as follows:

- CentOS 7.7 64-bit on x86-64
- Red Hat Enterprise Linux Server 8.x 64-bit on x86-64
- Ubuntu Server 18.04 64-bit on x86-64

Disk Space

The minimum disk space requirement is 10 GB.

System Memory

The minimum system memory requirement is 8 GB.

Required TIBCO Products

The following table lists the required and optional TIBCO products:



Note: The following software products are distributed and installed separately from this product. See the *Readme* file for the supported versions.

Software	Description
TIBCO® AuditSafe	<p>Required.</p> <p>TIBCO AuditSafe is used to securely post and store audit events generated by your business processes, and retrieve those events later.</p> <p>You must deploy and run TIBCO AuditSafe to post audit logs from BusinessConnect Container Edition.</p>
TIBCO Enterprise Message Service™	<p>Required.</p> <p>Enterprise Message Service™ is used as the notification and messaging backbone for BusinessConnect Container Edition. It is also used for internal communication between the Interior Server and Poller Server, and Interior Server and Gateway Server.</p> <p>BusinessConnect Container Edition and Enterprise Message Service can be installed on the same machine or on different machines in the same environment.</p> <p>BusinessConnect Container Edition license does not include Enterprise Message Service software. You must separately obtain an Enterprise Message Service license or another supported JMS product.</p>
TIBCO BusinessConnect™ Container Edition – Services Plug-in	<p>Optional.</p> <p>BusinessConnect™ Container Edition – Services Plug-in is an easy-to-use data transfer protocol, which you can use to securely exchange data over the internet.</p> <p>Trading partners managed by BusinessConnect Container Edition can quickly and efficiently be configured to exchange documents securely with the BusinessConnect Container Edition host using this plug-in,</p>

Software	Description
	without the overhead of interpreting the document contents.
TIBCO BusinessConnect™ Container Edition EDI Protocol powered by Instream®	Optional. BusinessConnect™ Container Edition EDI Protocol powered by Instream is the TIBCO B2B solution for transferring Electronic Data Interchange (EDI) documents between trading partners. It can be used for all EDI integration scenarios, including connecting directly to trading partners and connecting to value added networks (VANs).
TIBCO BusinessConnect™ Container Edition – RosettaNet Protocol	Optional. BusinessConnect™ Container Edition – RosettaNet Protocol is the TIBCO implementation of RosettaNet. It acts as a plug-in to BusinessConnect Container Edition and uses business process models that conform to the RosettaNet Partner Interface Process standard, which enables you to conduct e-business transactions with your trading partners using RosettaNet. BusinessConnect Container Edition – RosettaNet Protocol implements the RNIF 1.1 and RNIF 2.0 standards. It supports all PIPs listed as approved standards on the <i>RosettaNet website</i> .

Required Third-Party Products

The following table lists the required third-party products:

i Note: When you obtain third-party software or services, it is your responsibility to ensure you understand the license terms associated with such third-party software or services and comply with such terms. See the product *Readme* file for the supported versions.

Software	Description
Docker	Docker provides a way to securely run applications isolated in a container,

Software	Description
	<p>packaged with all its dependencies and libraries. Your application can run in any environment as all the dependencies are already present in the image of the application.</p> <p>You must install Docker to build the Docker images. For more information about Docker installation and initial setup based on your operating system, see <i>Docker Documentation</i>.</p>
Elasticsearch	<p>Elasticsearch is a distributed, open source search and analytics engine for all types of data, including textual, numerical, geospatial, structured, and unstructured. The Elasticsearch REST APIs support structured queries, full text queries, and complex queries that combine the two.</p> <p>TIBCO recommends that you install Elasticsearch 7.6 or later. For more information, see <i>ElasticSearch Documentation</i>.</p>
kubectrl	<p>Kubernetes provides many advantages such as scaling, high-availability, and recovery. You must install Kubectl to deploy BusinessConnect Container Edition on the Kubernetes cluster. For more information, see <i>Kubernetes Documentation</i>.</p>
Kubernetes cluster	<p>You must set up a Kubernetes cluster to deploy and run the BusinessConnect Container Edition services.</p> <div> <p>Note: To run the application in a Kubernetes cluster on a cloud platform, you must have an active account on that cloud platform.</p> </div>
MySQL	<div> <p>Note: You need to create one database for BusinessConnect Container Edition and one for AUS. If the AUS database is already created while installing TASEE, only create one database for BusinessConnect Container Edition.</p> </div>
Oracle	<p>You can install one of the supported database services to facilitate the storage, retrieval, modification, and deletion of data in conjunction with various data-processing operations.</p> <p>For more information, see <i>Database Documentation</i>.</p>

BusinessConnect Container Edition Migration

To migrate from earlier versions to TIBCO BusinessConnect™ Container Edition 1.2.0, perform the following steps.

Migrating from Release 6.4.x or 7.x

To migrate from TIBCO BusinessConnect™ 6.4.x or 7.x to BusinessConnect™ Container Edition 1.2.0, complete the following steps:

Exporting the Old Configuration

Perform the following steps to export the existing BusinessConnect™ 6.4.x or 7.x configuration by using the TIBCO Administrator GUI:

Procedure

1. Log in to TIBCO Administrator. Click **BusinessConnect** in the left panel, and then click **Manage** in the right panel.
2. In the Management area of the Manage Installation dialog box, click **Export**.
3. (Optional) You can also set a password to protect the exported data. In the Configuration Data Export dialog box, click **Set**.
4. Click **Export** to export the existing configuration. Do not exit until the export process is successfully completed.
5. Click **Download**.

You are prompted to confirm that you want to download the *InstallationName.csx* file and to specify where the file is to be saved. The exported configuration is secure and can be imported into BusinessConnect Container Edition as explained in the following steps.

Installing and Configuring TIBCO BusinessConnect™ Container Edition 1.2.0

To install BusinessConnect Container Edition 1.2.0 and appropriate protocols, perform the following steps:

1. Install TIBCO BusinessConnect™ Container Edition 1.2.0. For more information, see *TIBCO BusinessConnect™ Container Edition Installation and Deployment* guide.
2. Install the appropriate protocols. For more information, see the documentation of each protocol.
3. To perform migration from TIBCO BusinessConnect 6.4.x or 7.x to TIBCO BusinessConnect™ Container Edition 1.2.0, the systems must contain an identical set of protocols.
4. Configure the BusinessConnect Container Edition installation. This operation upgrades the configuration store database schemas. For more information, see *TIBCO BusinessConnect™ Container Edition Installation and Deployment* guide.

Importing the Old Configuration to Trigger Migration

To import the saved old installation, perform the following steps:

1. Log in into the TIBCO BusinessConnect Container Edition UI.
2. In **System Settings**, click **Installation Properties** under the General tab.
3. On the Installation Properties page, click **Import Configuration**.
4. In the right panel, click **Upload file**, navigate to the location where the .csx file is saved and upload the file. Provide password (if any).
5. Click **Start Importing** and wait for the import process to complete.



Important: Do not exit this process while data is being imported. If the data import process is interrupted for any reason, the system might be left in an unpredictable state. In this case, you have to recreate the installation and perform a new import operation.

i Note: If you wish to migrate from one BusinessConnect Container Edition to the other, export the .bcce file by using the **Export BCCE configuration** option in the Installation Properties page and follow the importing procedure.

Migrating from Release 1.0.0, 1.1.0, or 1.1.1

To migrate from TIBCO BusinessConnect Container Edition 1.0.0, 1.1.0, or 1.1.1 to TIBCO BusinessConnect Container Edition 1.2.0, complete the following steps:

Exporting the Old Configuration

Perform the following steps to export the existing TIBCO BusinessConnect Container Edition 1.0.0, 1.1.0, or 1.1.1 configuration by using the TIBCO Admin UI:

1. In the Admin UI, navigate to **System Settings > General > Installation** Properties.
2. On the Installation Properties page, click **Export BCCE configuration**.
3. In the Export Configuration Data dialog box, click **Export**.
Setting the password is optional.
4. Click **Export** and wait for the export process to complete.
5. After the export process is completed, click **Download**, and save the exported .bcce file to a desired location.

The exported configuration is secure and can be imported into BusinessConnect Container Edition as explained in the following steps.

Installing and Configuring TIBCO BusinessConnect™ Container Edition 1.2.0

To install TIBCO BusinessConnect™ Container Edition 1.2.0 and appropriate protocols, perform the following steps:


1. Install TIBCO BusinessConnect™ Container Edition 1.2.0. For more information, see *TIBCO BusinessConnect™ Container Edition Installation and Deployment* guide.

2. Install the appropriate protocols. For more information, see the documentation of each protocol.
3. To migrate from TIBCO BusinessConnect Container Edition 1.0.0, 1.1.0, or 1.1.1 to TIBCO BusinessConnect™ Container Edition 1.2.0, the systems must contain an identical set of protocols.
4. Configure the TIBCO BusinessConnect™ Container Edition installation. This operation upgrades the configuration store database schemas. For more information, see *TIBCO BusinessConnect™ Container Edition Installation and Deployment* guide.

Importing the Old Configuration to Trigger Migration

To import the saved old configuration, perform the following steps:

1. Log in to the TIBCO BusinessConnect Container Edition UI.
2. In **System Settings**, click **Installation Properties** under the **General** tab.
3. On the Installation Properties page, click **Import Configuration**.
4. In the right panel, click **Upload file**, navigate to the location where the .bcce file is saved and upload the file. Provide password (if any).
5. Click **Start Importing** and wait for the import process to complete.

 **Important:** Do not exit this process while data is being imported. If the data import process is interrupted for any reason, the system might be left in an unpredictable state. In this case, you have to recreate the installation and perform a new import operation.

BusinessConnect Container Edition

Dockerfiles and Scripts

BusinessConnect Container Edition installation and deployment package provide all the necessary Dockerfiles, scripts, and configuration files to install, deploy, and uninstall all the BusinessConnect Container Edition services or deployments.

Dockerfiles and Scripts

A Dockerfile is simply a text-based script of instructions that is used to create a container image.

File	Description
build-images.sh	Creates the BusinessConnect Container Edition Docker images and push the images to the Docker repository
deploy-bcce.sh	Deploys the BusinessConnect Container Edition services onto the Kubernetes cluster
remove-bcce-services.sh	Deletes all the BusinessConnect Container Edition services and deployments
apply_secret_cert.sh	Creates the Kubernetes secret bcce-gs-config for two key/cert files
apply_secret_docker_login.sh	Creates the Kubernetes secret Docker-registry for Docker login
apply_secret_log4j2.sh	Creates the Kubernetes secret log4j2 with the log4j2.xml
apply_secret_log4j2_json.sh	Creates the Kubernetes secret log4j2_json with the log4j2.json

Configuration files

A configuration file (config file) is used to configure the parameters, settings, and preferences.

File	Description
configuration.properties	Contains all the properties that user has to set to build the BusinessConnect Container Edition's Docker images and deploy to the Kubernetes cluster
credentials.properties	Default file to create the Kubernetes credentials secret.
deployment.properties	Contains all the properties that user has to set to deploy the BusinessConnect Container Edition's Docker images to the Kubernetes cluster
log4j2.xml	Default XML file to create the Kubernetes log4j2 secret. You can also change logger levels for all servers except Admin Server using this file.
log4j2.json	Default JSON file to create the Kubernetes log4j2_json secret

Deploying BusinessConnect Container Edition Application

Before you begin

Ensure that you have the infrastructure and other requirements listed in [Installation Requirements](#).

To deploy and run BusinessConnect Container Edition components on Docker or Kubernetes platform, perform the steps described in the following sections.

- [Building BusinessConnect Container Edition Component's Docker Images](#)
- [Deploying BusinessConnect Container Edition Component's Docker Images](#)

Building BusinessConnect Container Edition Component's Docker Images

To run the BusinessConnect Container Edition components on Docker or Kubernetes platform, you must first build the Docker images for the components and applications.

Before you begin

1. Install the required protocols, such as, EZComm, RosettaNet, or EDI (X12 and Gateway). Any number of supported protocols can be installed. For installing a protocol, refer to protocol's *Installation document*.
2. From [TIBCO eDelivery](#), download the TIB_bcce_<version>.tar.gz installation and deployment package.
3. Extract the contents of the package to a local directory.
4. For initial setup and additional technical details, see the *README* file located in the bcce-1.2.0 > images > scripts directory.

Procedure

1. Navigate to the `<folder>/bcce-1.2.0/images/config` directory.
2. Open the `configuration.properties` file and configure the properties listed in the following table.

Property	Description
docker_repository = <code><docker_registry_ip>:<docker_registry_port></code>	<code><docker_registry_ip></code> is the IP address and <code><docker_registry_port></code> is the port of the machine to which you want to push the Docker images
docker_username	Specify the user name required to log in to Docker
download_dir = <code><download_dir></code>	<code><download_dir></code> is the directory path where you want to download all the JAR files

3. Save and close the `configuration.properties` file.
4. Navigate to the `<folder>/bcce-1.2.0/images/scripts` directory.
5. Run the following command:

```
./build-images.sh
```

6. Follow the command-line interface instructions, review the license agreement, and enter `y` to accept it.
7. When prompted:

```
Do you want to push the BCCE docker images to <docker_registry_ip>:<docker_registry_port>?
If not, the BCCE docker images will still be built at local.
(y/n)
```

Enter `y` to build the Docker images.

Result

The BusinessConnect Container Edition component's Docker images are built and pushed to the Docker repository.

Deploying BusinessConnect Container Edition Component's Docker Images

To deploy the BusinessConnect Container Edition component's Docker images on the Docker or Kubernetes platform, perform the following steps.

Before you begin

1. For initial setup and additional technical details, see the *README* file located in the `bcce-1.2.0 > deployment > scripts` directory.

Important: Before you deploy Docker images, if you are using MySQL 5.7.x or later versions; then in the `my.ini` file under `[mysqld]` section, you must add `skip_ssl` and set `max_allowed_packet` to 500M.

Procedure

1. Navigate to the `<folder>/bcce-<version>/deployment/config` directory.
2. Open the `deployment.properties` file and configure the properties listed in the following table.

Property	Description
<code>docker_repository=<docker_registry_ip>:<docker_registry_port></code>	<code><docker_registry_ip></code> is the IP address and <code><docker_registry_port></code> is the port of the machine from which you want to pull the Docker images from.
<code>docker_username</code>	Specify the user name required to log in to Docker.
<code>host_ip=<host_ip></code>	<code><host_ip></code> is the IP address of the host machine, host name, or Kubernetes cluster.

Property	Description
gstoken_unzip =<gstoken_unzip>	<gstoken_unzip> is the directory path where you should extract the contents of GSToken.zip file.
Database properties	
database_url =jdbc:mysql://<database_machine_ip>:3306/auditsafe?useSSL=false\\&allowPublicKeyRetrieval=true for MySQL database	<database_machine_ip> is the IP address of the machine where the database resides.
database_url =jdbc:oracle:thin:@<machine_ip>:1521:<serv_id> for Oracle Database	<machine_ip> is the IP address of the machine where the database resides. <serv_id> is the service identifier for oracle instance.
database_username =<username>	<username> is the name of the user accessing the database.
database_password =<password>	<password> is the password to access the database.
database_driver =com.mysql.cj.jdbc.Driver for MySQL database database_driver =oracle.jdbc.OracleDriver for Oracle Database	Configure the database driver property accordingly.
Optional mount_path =<nfs_path>	<nfs_path> is the path for Poller Server and Interior Server to monitor or get the files mount_path.

Property	Description
	Note: You need to install and configure a working NFS for this feature to work.
Optional mount_path2 =<nfs_path>/<folders>	Path for Interior Server to store the large EDI files. Note: The value of mount_path2 should be different from the value of mount_path .

3. Configure additional properties that are specific to Kubernetes services: Amazon Elastic Kubernetes Service (AWS EKS), Azure Kubernetes Service (AKS), or Google Cloud Kubernetes Engine (GKE).
4. Save and close the `deployment.properties` file.
5. To deploy the BusinessConnect Container Edition component's Docker images, run one of the following commands depending on the platform:
 - **Kubernetes:** Navigate to the `<folder>/bcce-<version>/deployment/scripts` directory and run the following command:

```
./deploy-bcce.sh
```

- **Docker:** Navigate to the `<folder>/bcce-<version>/deployment/samples/docker-scripts` directory and run the following command:

```
./docker-run-bcce-all.sh
```

6. Follow the command-line interface instructions, review the license agreement, and enter `y` to accept it.
7. This step is applicable only if you want to deploy BusinessConnect Container Edition services on Kubernetes, otherwise skip this step.

When prompted:

```
Which Kubernetes environment do you want to deploy TIBCO BCCE
services?
```

1. Native Kubernetes
2. AWS EKS
3. Azure AKS
4. Google Cloud GKE
- q. Quit

Enter 1, 2, 3, 4, or q.

8. When prompted:

```
Do you want to deploy TIBCO BCCE Server services?
```

1. ConfigStore Management Server
 2. Admin Server
- (y/n)

Enter y to deploy ConfigStore Management Server and Admin Server.

9. Perform the following steps to configure JMS Server settings; before you deploy Poller Server and Interior Server.

- a. Log in to the BusinessConnect Container Edition application using the URL:
http://<host_ip>:<as_port>.



Tip: Use the <host_ip> and <as_port> that you have set in the deployment.properties file.

- b. Go to System Settings > General, click **Internal Messaging (JMS)**.



Note: For more information on how to configure Private Process JMS, Intercomponent JMS, or Intercomponent DMZ-JMS, see the “Configuring JMS Settings” topic in *TIBCO BusinessConnect™ Container Edition Administration Guide*.

- c. Click **Private Process JMS**, select or enter information in all the mandatory


fields, and click **Save**.

- d. Click **Intercomponent JMS**, select or enter information in all the mandatory fields, and click **Save**.
- e. Optional: To use different JMS between Gateway Server and Interior Server, click **Intercomponent DMZ-JMS (Optional)**, select or enter information in all the mandatory fields, and click **Save**.

10. On the command-line interface, when prompted:

```
Do you want to deploy TIBCO BCCE Server services?
3. Poller Server
4. Interior Server
Please make sure the JMS Server settings are done properly from the
BCCE Admin UI.
Otherwise, the Poller Server and Interior Server won't work.
(y/n)
```

Enter y to deploy Poller Server and Interior Server.

11. Perform the following steps to download the GSToken.zip file; before you deploy Gateway Server.
 - a. Go to System Settings > Transport Protocols > Inbound Protocols.
 - b. Select the **HTTP** check box and click **Save**.
 - c. Click **Configure Service** of **HTTP** and click **Add** .
 - d. Enter **Gateway Service Name**, select HTTP from the **Gateway Service Type** list and click **Proceed**.



Tip: Default **Gateway Service Name** is set to http in the deployment.properties file. To use another **Gateway Service Name**, set `<service name>` for `gs_services=HTTP:<service name>` in the deployment.properties file.

- e. Select the **Enable** check box to enable the Gateway Service and configure the **Ports**, **Advanced**, and **Credentials** tabs. For more information on how to

configure these tabs, see the “Configuring Gateway Services (HTTP)” topic in *TIBCO BusinessConnect™ Container Edition Administration Guide*.

- f. On the Admin UI, go to System Settings tile > General, click **Installation Properties**.
- g. Click **Export GS configuration** to download the GSToken.zip file, which contains intercomProps, hostKey, and peerCert files that are required to deploy Gateway Server.
- h. Extract the contents of GSToken.zip to the **<gstoken_unzip>** directory.



Tip: Use the **<gstoken_unzip>** that you have set in the deployment.properties file.

12. On the command-line interface, when prompted:

```
Do you want to deploy TIBCO BCCE Gateway Server services?  
Please make sure that you have downloaded the GSToken.zip from  
Admin UI, extracted it  
in a folder and set the property gstoken_unzip in the  
deployment.properties file.  
Otherwise, the Gateway Server won't work.  
(y/n)
```

Enter y to deploy Gateway Server.

Result

You have deployed all the components of the BusinessConnect Container Edition application.

What to do next

Configure the Outbound Email poller to receive an email in the event of a forgotten password.

Uninstalling BusinessConnect Container Edition

To uninstall BusinessConnect Container Edition, perform the following steps:

Procedure

1. To remove all the BusinessConnect Container Edition services or deployments, run one of the following commands depending on the platform:

- **Kubernetes:** Navigate to the `<folder>/bcce-<version>/deployment/scripts` directory and run the following command:

```
./remove_bcce_services.sh
```

- **Docker:** Navigate to the `<folder>/bcce-<version>/deployment/samples/docker-scripts` directory and run the following command:

```
./stop_bcce_containers.sh
```

2. Delete all the Docker images.

What to do next

Delete the database that you have set up for BusinessConnect Container Edition.

Viewing Container Logs

All the BusinessConnect Container Edition component containers publish their logs on the standard output device.

Procedure

1. To view logs of a particular container, run one of the following commands depending on the platform:

- **Kubernetes:**

```
kubectl logs <container_id> -n <k8s_namespace>
```

Where *<k8s_namespace>* is Kubernetes namespace that you have set in the `deployment.properties` file.



Note: If *<k8s_namespace>* is not set, then its default value is *bcce*.



Tip: To follow logs use `--follow`.

- **Docker:**

```
docker logs <container_id>
```

TIBCO Documentation and Support Services

For information about this product, you can read the documentation, contact TIBCO Support, and join TIBCO Community.

How to Access TIBCO Documentation

Documentation for TIBCO products is available on the [TIBCO Product Documentation](#) website, mainly in HTML and PDF formats.

The [TIBCO Product Documentation](#) website is updated frequently and is more current than any other documentation included with the product.

Product-Specific Documentation

The following documentation for TIBCO BusinessConnect™ Container Edition is available on the [TIBCO BusinessConnect™ Container Edition](#) page.

- *TIBCO BusinessConnect™ Container Edition Release Notes*
- *TIBCO BusinessConnect™ Container Edition Installation and Deployment*
- *TIBCO BusinessConnect™ Container Edition Concepts*
- *TIBCO BusinessConnect™ Container Edition Trading Partner Management*
- *TIBCO BusinessConnect™ Container Edition Administration*
- *TIBCO BusinessConnect™ Container Edition Security Guidelines*

How to Contact TIBCO Support

Get an overview of [TIBCO Support](#). You can contact TIBCO Support in the following ways:

- For accessing the Support Knowledge Base and getting personalized content about products you are interested in, visit the [TIBCO Support](#) website.
- For creating a Support case, you must have a valid maintenance or support contract with TIBCO. You also need a user name and password to log in to [TIBCO Support](#) website. If you do not have a user name, you can request one by clicking **Register** on

the website.

How to Join TIBCO Community

TIBCO Community is the official channel for TIBCO customers, partners, and employee subject matter experts to share and access their collective experience. TIBCO Community offers access to Q&A forums, product wikis, and best practices. It also offers access to extensions, adapters, solution accelerators, and tools that extend and enable customers to gain full value from TIBCO products. In addition, users can submit and vote on feature requests from within the [TIBCO Ideas Portal](#). For a free registration, go to [TIBCO Community](#).

Legal and Third-Party Notices

SOME TIBCO SOFTWARE EMBEDS OR BUNDLES OTHER TIBCO SOFTWARE. USE OF SUCH EMBEDDED OR BUNDLED TIBCO SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED TIBCO SOFTWARE. THE EMBEDDED OR BUNDLED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER TIBCO SOFTWARE OR FOR ANY OTHER PURPOSE.

USE OF TIBCO SOFTWARE AND THIS DOCUMENT IS SUBJECT TO THE TERMS AND CONDITIONS OF A LICENSE AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED SOFTWARE LICENSE AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER LICENSE AGREEMENT WHICH IS DISPLAYED DURING DOWNLOAD OR INSTALLATION OF THE SOFTWARE (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH SOFTWARE LICENSE AGREEMENT OR CLICKWRAP END USER LICENSE AGREEMENT, THE LICENSE(S) LOCATED IN THE “LICENSE” FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of TIBCO Software Inc.

TIBCO, the TIBCO logo, the TIBCO O logo, TIB, ActiveMatrix BusinessWorks, BusinessConnect, BusinessConnect Container Edition, and Enterprise Message Service are either registered trademarks or trademarks of TIBCO Software Inc. in the United States and/or other countries.

Java and all Java based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

This document includes fonts that are licensed under the SIL Open Font License, Version 1.1, which is available at: <https://scripts.sil.org/OFL>

Copyright (c) Paul D. Hunt, with Reserved Font Name Source Sans Pro and Source Code Pro.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only.

This software may be available on multiple operating systems. However, not all operating system platforms for a specific software version are released at the same time. See the readme file for the availability of this software version on a specific operating system platform.

THIS DOCUMENT IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. TIBCO SOFTWARE INC. MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THIS DOCUMENT AT ANY TIME.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "READ ME" FILES.

This and other products of TIBCO Software Inc. may be covered by registered patents. Please refer to TIBCO's Virtual Patent Marking document (<https://www.tibco.com/patents>) for details.

Copyright © 2001-2022. TIBCO Software Inc. All Rights Reserved.