



TIBCO BusinessWorks™ Container Edition

Error Codes

Version 2.10.0 | December 2024

Contents

Contents	2
Message Codes Naming Convention	4
Bindings	6
SOAP Binding Error Codes	6
REST Binding Error Codes	18
Core	23
Engine Error Codes	23
Design Time Error Codes	87
Palettes	89
File Palette Error Codes	89
FTP Palette Error Codes	92
General Palette Error Codes	94
HTTP Palette Error Codes	96
Java Palette Error Codes	100
JDBC Palette Error Codes	107
JMS Palette Error Codes	112
Mail Palette Error Codes	115
Parse Palette Error Codes	119
Rendezvous Palette Error Codes	125
TCP Palette Error Codes	128
XML Palette Error Codes	131
Shared Resources	134
Shared Resource Framework Error Codes	134
Data Format Error Codes	136

FTP Connection Error Codes	136
HTTP Client Error Codes	137
HTTP Connector Error Codes	137
Java Global Instance Error Codes	140
JMS Connection Error Codes	142
JDBC Connection Error Codes	143
JNDI Configuration Error Codes	146
Proxy Configuration Error Codes	146
SMTP Resource Error Codes	147
TCP Connection	148
TIBCO Documentation and Support Services	149
Legal and Third-Party Notices	151

Message Codes Naming Convention

Product execution errors, warnings, and information are reported through detailed log messages that can help trace the cause of the issue. These messages follow a naming convention that indicates the component and log level for each message. The log levels allow you to capture different granularity of messages for different loggers.

Messages returned by the software consist of a code and an associated message.

The message code consists of two parts, a *component ID* and a 6-digit number, separated by a hyphen (-). The *component ID* indicates the component that reported the message and the 6-digit number is a numerical range that indicates the logger level.

The following table lists the component IDs and their descriptions.

Component Id	Description
BX	BusinessWorks Container Edition Engine Layer
PVM	BusinessWorks Container Edition Engine Layer
TIBCO-BW-BINDING-REST	BusinessWorks Container Edition REST Binding
TIBCO-BW-BINDING-SOAP	BusinessWorks Container Edition SOAP Binding
TIBCO-BW-CORE	BusinessWorks Container Edition Engine Layer
TIBCO-BW-FRWK	BusinessWorks Container Edition Framework
TIBCO-BW-PALETTE	BusinessWorks Container Edition Palette layer
TIBCO-BW-PALETTE- <i><Palette Name></i>	BusinessWorks Container Edition Palette specific activity
TIBCO-BW-SR	BusinessWorks Container Edition Shared Resource API layer

TIBCO-BW-SR- <i><UniqueName></i>	BusinessWorks Container Edition specific Shared Resource
TIBCO-BW-STATS	BusinessWorks Container Edition Stats Collector
TIBCO-THOR-FRWK	Thor Framework

i **Note:** The Engine layers with component IDs BX and PVM do not follow this convention.

The message describes the issue. Sometimes, the message can contain parameters shown as $\{N\}$, where N is an integer.

Bindings

This section describes the error messages that can be reported by the SOAP and REST Binding types.

SOAP Binding Error Codes

This section describes the error messages that can be reported by the SOAP Binding.

Error Codes	Error Message	Error Resolution
TIBCO-BW-BINDING-SOAP-001010	SOAP BindingFactory is initialized with incorrect BindingConfiguration for the SOAP Service Binding.	This is an internal resolution message. The resolution is not required.
TIBCO-BW-BINDING-SOAP-001020	Failed to obtain the HTTP Connector resource for SoapServiceBinding [{0}], Application [{1}]: {2}	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-001030	Failed to obtain the HTTP Connector resource for SoapServiceBinding [{0}], Application [{1}]: {2}	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-001031	SOAP BindingFactory is initialized with incorrect BindingConfiguration for the SOAP Reference Binding.	This is an internal resolution message. The resolution is not required.
TIBCO-BW-BINDING-	Failed to parse binding meta data file [{0}] in bundle [{1}] due to exception [{2}].	Ensure that the xml file contents are valid and well

Error Codes	Error Message	Error Resolution
SOAP-001040		formed.
TIBCO-BW-BINDING-SOAP-001050	Failed to process File [{0}] in bundle [{1}]. BindingName is not specified.	Ensure that the 'name' attribute of the service element contains a unique Binding Name.
TIBCO-BW-BINDING-SOAP-001060	Failed to process File [{0}] in bundle [{1}]. A Binding with name [{2}] is already registered.	Ensure that Binding Name of the SOAP Interceptor is unique and it does not match with any Binding Name (service/reference) in the Application Module
TIBCO-BW-BINDING-SOAP-001070	Failed to deploy the SOAP Interceptor Module [{0}], due to exception [{1}]. Root exception message is [{2}].	Ensure that the SOAP Interceptor deployed follows the Axis2 Module protocol.
TIBCO-BW-BINDING-SOAP-001080	Failed to initialize SOAP Binding. Binding Name is not specified.	BW_SOAP_BINDING_NAME_MISSING_ERROR.resolution = Make sure all Bindings in the application Module have a Name.
TIBCO-BW-BINDING-SOAP-001081	Failed to initialize SOAP Binding. Binding Name is not specified for port [{0}].	Make sure the Binding in the application Module has a Name.
TIBCO-BW-BINDING-SOAP-001090	Failed to initialize SOAP Binding. Application Name is not available.	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBCO-BW-BINDING-SOAP-001100	Failed to initialize SOAP Binding. Application Version is not available.	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-001130	Failed to locate WSDL definition for port type [{0}].	Ensure that a WSDL exist with port type [{0}] in the application module.
TIBCO-BW-BINDING-SOAP-001140	MEP [{0}] is not supported. Review the WSDL definition for Port type [{1}].	Ensure that the MEP definition for Port type [{1}] is either IN-OUT OR IN-ONLY
TIBCO-BW-BINDING-SOAP-001150	Failed to recognize the MEP for Port type [{0}].	Ensure that the MEP definition for Port type [{0}] is either IN-OUT OR IN-ONLY
TIBCO-BW-BINDING-SOAP-001160	Failed to find message receiver for MEP [{0}] for port type [{1}].	Ensure that the MEP definition for Port type [{1}] is either IN-OUT OR IN-ONLY
TIBCO-BW-BINDING-SOAP-001170	SOAP Binding [{1}] for portType [{0}] is missing Transport Configuration.	Ensure that the SOAP Binding [{1}] for port type [{0}] is configured with a Transport.
TIBCO-BW-BINDING-SOAP-001180	Operation Configuration for Operation [{0}], Port Type [{1}], SOAP Binding [{2}] is missing. Ensure that SOAP Binding [{2}] is in sync with WSDL	Ensure that SOAP Binding [{2}] is in sync with WSDL.
TIBCO-BW-	Failed to initialize SOAP Service Binding [{0}].	This is an internal product

Error Codes	Error Message	Error Resolution
BINDING-SOAP-001110	Promoted Name for the Binding is missing.	error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-001120	Failed to initialize SOAP Reference Binding [{0}]. Promoted Name for the Binding is missing.	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-001130	Failed to load WSDL definition for namespace [{0}].	Make sure the WSDL with namespace [{0}] exists in the application module.
TIBCO-BW-BINDING-SOAP-500009	Malformed MIME Message received. Failed to parse the attachments in the received message for Operation [{0}], SoapBinding [{1}], Application [{2};{3}]. Ignoring the attachments from the SOAP Message.	Ensure that the MIME Message is well formed with correct mime boundaries.
TIBCO-BW-BINDING-SOAP-500010	Failed to create SoapServiceBinding [{0}], Application [{1};{2}] due to exception [{3}]	This is an internal resolution message. The resolution is not required.
TIBCO-BW-BINDING-SOAP-500011	Unable to parse model version of the SOAP Binding.	Ensure that the SOAP Model version in .bwm file is of format [0-9].[0-9].[0-9]
TIBCO-BW-BINDING-SOAP-500020	Failed to initialize SoapServiceBinding [{0}], Application [{1};{2}] due to exception [{3}]	Ensure that the configuration and context mapping, if any, done on SoapServiceBinding [{0}] are correct.
TIBCO-BW-	Failed to add transport dependency for	Ensure that the

Error Codes	Error Message	Error Resolution
BINDING-SOAP-500030	SoapServiceBinding [{0}], Application [{1}:{2}]	SoapServiceBinding [{0}] is configured with a Shared Transport Resource.
TIBCO-BW-BINDING-SOAP-500040	Failed to initialize SoapServiceBinding [{0}]. A Service Endpoint URI [{1}] is already registered	Ensure that each SOAP/HTTP service has unique URL.
TIBCO-BW-BINDING-SOAP-500050	Failed to initialize SoapServiceBinding [{0}]. The operation [{1}] with soapaction [{2}] is already registered for destination [{3}] with Message Style [{4}].	Ensure that the combination of Soap Action and MessageStyle:Destination should be unique.
TIBCO-BW-BINDING-SOAP-500060	Failed to send SOAP Fault message to the consumer of the service for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Root Exception message: {5}	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-500070	Failed to process Reply message for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Sending Undeclared Fault message to the consumer of this service. Root Exception message: [{5}]	Ensure that the Binding configuration and Context Configuration, if any, done on SoapServiceBinding [{1}] are correct.
TIBCO-BW-BINDING-SOAP-500080	Error occurred while processing Service Request messages Context Information for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Root Exception message: {5}	Ensure that the Context Mapping done on SoapServiceBinding [{1}] are correct.
TIBCO-BW-BINDING-SOAP-500090	Error occurred while processing Service Request message for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Root Exception	Ensure that the Message part configuration and header configuration, if any, done on SoapServiceBinding [{1}] are

Error Codes	Error Message	Error Resolution
	message: {5}	correct.
TIBCO-BW-BINDING-SOAP-500100	Error occurred while processing Service Request message for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Sending Undeclared Fault message to the consumer of this service. Root Exception message: {5}	Ensure that the Message part configuration and header configuration, if any, done on SoapServiceBinding [{1}] are correct.
TIBCO-BW-BINDING-SOAP-500105	Error occurred while processing Service Request message for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Root Exception message: {5}	Ensure that the Message part configuration and header configuration, if any, done on SoapServiceBinding [{1}] are correct.
TIBCO-BW-BINDING-SOAP-500110	Failed to process Declared Fault Message for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Sending Undeclared Fault message to the consumer of this service. Root Exception message: {5}.	Ensure that the Context Mapping and configuration done on SoapServiceBinding [{1}] are correct.
TIBCO-BW-BINDING-SOAP-500120	The BusinessWorks ProcessService implementation failed to complete the request for the Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] and returned exception [{4}]. Sending Undeclared Fault message to the consumer of this service. Root Exception message: {5}.	Ensure that the BW Process construct is correct.
TIBCO-BW-BINDING-SOAP-500130	Unable to populate SOAP Binding Configuration due to exception [{1}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-	An Error occurred while cleaning up the SOAP	This is an internal product

Error Codes	Error Message	Error Resolution
BINDING-SOAP-500131	Binding Configuration Resources due to an exception [{1}]	error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-500140	An interrupted fault occurred while waiting for the Service Request message to be processed for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]. Sending Undeclared Fault message to the consumer of this service. Root Exception message: {5}	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-500150	Failed to start SoapServiceBinding [{0}], Application [{1}:{2}] due to an exception [{3}]	Ensure that the Transport Configuration done on SoapServiceBinding [{0}] are correct.
TIBCO-BW-BINDING-SOAP-500160	Failed to stop SoapServiceBinding [{0}], Application [{1}:{2}] due to an exception [{3}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-500170	Error occurred while processing Service Request messages Context information for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]. Sending Undeclared Fault message to the consumer of this service. Root Exception message: {5}	Ensure that the Context Mapping and configuration done on SoapServiceBinding [{1}] are correct.
TIBCO-BW-BINDING-SOAP-500190	Failed to start JMS transport primitive for SoapServiceBinding [{0}], Application [{1}:{2}] due to an exception [{3}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-	Failed to stop JMS transport primitive for	This is an internal product

Error Codes	Error Message	Error Resolution
BINDING-SOAP-500200	SoapServiceBinding [{0}], Application [{1}:{2}] due to an exception [{3}]	error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-500210	Failed to Initialize JMS transport primitive for SoapServiceBinding [{0}], Application [{1}:{2}] due to an exception [{3}]	Ensure that the transport configuration done on SoapServiceBinding [{0}] are correct.
TIBCO-BW-BINDING-SOAP-500230	Failed to read incoming JMS raw message due to an exception [{0}];	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-500240	Failed to create JMS Reply Handler for SoapServiceBinding [{0}], Application [{1}:{2}] due to an exception [{3}]	Ensure that the transport configuration done on SoapServiceBinding [{0}] are correct.
TIBCO-BW-BINDING-SOAP-500250	Failed to process service request message for SoapServiceBinding [{0}], Application [{1}:{2}] due to an exception [{3}]. Root exception message: [{4}]	Ensure that the Service Provider is sending a correct SOAP Envelope.
TIBCO-BW-BINDING-SOAP-500260	Failed to send Service Reply message for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-500270	Failed to acknowledge Service Request message for Operation [{0}], SoapServiceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-	Failed to authenticate Request message for Operation [{0}], SoapServiceBinding [{1}],	Check if the identity resource referenced in the HTTP Client

Error Codes	Error Message	Error Resolution
SOAP-500280	Application [{2};{3}] due to an exception [{4}].	resource contains username and password.
TIBCO-BW-BINDING-SOAP-500281	Failed to authenticate Request message for Operation [{0}], SoapServiceBinding [{1}], Application [{2};{3}]. Username and Password is not set.	Check if the identity resource referenced in the HTTP Client resource contains username and password.
TIBCO-BW-BINDING-SOAP-500290	Failed to authenticate Request message for Operation [{0}], SoapServiceBinding [{1}], Application [{2};{3}] due to an exception [{4}].	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-500300	Malformed SOAP Request message received for Operation [{0}], SoapServiceBinding [{1}], Application [{2};{3}]. Root Exception message: [{5}]	Check if the SOAP Request Message is well formed.
TIBCO-BW-BINDING-SOAP-550010	Failed to create SoapReferenceBinding [{0}], Application [{1};{2}] due to an exception [{3}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-550020	Failed to create SoapReferenceEndpoint [{0}] due to an exception [{1}]	Ensure that configurations done on Reference Binding [{0}] are correct.
TIBCO-BW-BINDING-SOAP-550030	Failed to initialize SoapReferenceBinding [{0}], Application [{1};{2}] due to an exception [{3}]	Ensure that the Binding and Transport configuration on SoapReferenceBinding [{0}] are correct.
TIBCO-BW-BINDING-SOAP-	Failed to add transport dependency for SoapReferenceBinding [{0}], Application [{1};{2}]	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
550040	Failed to destroy SoapReferenceBinding [{0}], Application [{1}:{2}] due to an exception [{3}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-550050	Failed to release transport resources for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-550060	Received Declared Fault. Failed to release transport resources for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-550070	Unable to receive response from the service provider for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-BINDING-SOAP-550090	Received SOAP Fault from the service provider of the Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}]. SOAP Fault received: [{4}]	This is an internal message sent to the framework for server error. The resolution is not required.
TIBCO-BW-BINDING-SOAP-550100	Received SOAP Fault from the service provider of the Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}]. SOAP Fault received: [{4}]	This is an internal message sent to the framework for client error. The resolution is not required.
TIBCO-BW-BINDING-SOAP-550101	Error occurred while processing the declared fault message from the service provider of the Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	Ensure that the declared fault send back by the Service Provider is valid and well formed SOAP Fault.

Error Codes	Error Message	Error Resolution
TIBCO-BW-BINDING-SOAP-550120	Error occurred while processing reply message from the service provider of the Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	Ensure that Message Part and Header Configuration done on SoapReferenceBinding [{1}] are correct.
TIBCO-BW-BINDING-SOAP-550121	SOAPEnvelope must contain a body element, which is either first or second child element of the SOAPEnvelope.	Ensure that Service Provider has send a valid SOAP Envelope.
TIBCO-BW-BINDING-SOAP-550130	Error occurred while processing reply message attachments from the service provider of the Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	Ensure that Context configuration and Mapping for the attachment done on SoapReferenceBinding [{1}] is correct.
TIBCO-BW-BINDING-SOAP-550140	Failed to Initialize JMS transport primitive for SoapReferenceBinding [{0}], Application [{1}:{2}] due to an exception [{3}]	Ensure that the Transport Sender configurations are correct.
TIBCO-BW-BINDING-SOAP-550170	Failed to send Reference Request message for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	Ensure that the Message Configuration done on SoapReferenceBinding [{1}] are correct.
TIBCO-BW-BINDING-SOAP-550180	Failed to process reply message from the service provider of the Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to an exception [{4}]	Ensure that the Message Configuration done on SoapReferenceBinding [{1}] are correct
TIBCO-BW-BINDING-SOAP-550190	Failed to update the HTTP Transport configurations before sending the Reference Request message for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to an exception [{4}].	Ensure that the port number configuration for SoapReferenceBinding [{1}] is valid

Error Codes	Error Message	Error Resolution
TIBCO-BW-BINDING-SOAP-550210	Failed to create the HTTP Client required for sending the Reference Request message for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to exception [{4}]	Ensure that the Endpoint URL is in correct format.
TIBCO-BW-BINDING-SOAP-550220	Failed to serialize JMS transport message due to exception [{1}].	Ensure that the configuration done on Reference Binding is correct.
TIBCO-BW-BINDING-SOAP-550230	Failed to convert JMS message to string due to exception [{1}].	Ensure that the configuration done on Reference Binding is correct.
TIBCO-BW-BINDING-SOAP-550240	Failed to create Endpoint URL for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to exception [{4}]	Ensure that the Endpoint URI configuration on SOAPReferenceBinding [{1}] is correct.
TIBCO-BW-BINDING-SOAP-555000	Unable to receive response from the service provider for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Message Received: [{5}]	Ensure that the Service Provider is available.
TIBCO-BW-BINDING-SOAP-555010	Unable to receive response from the service provider for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Message Received: [{5}]	Ensure that the HTTP Client configurations are configured as per service provider requirements.
TIBCO-BW-BINDING-SOAP-555020	Unable to receive response from the service provider for Operation [{0}], SoapReferenceBinding [{1}], Application [{2}:{3}] due to exception [{4}]. Message Received: [{5}]	Ensure that the HTTP Client configurations are configured as per service provider requirements.

Error Codes	Error Message	Error Resolution
	[[5]]	
TIBCO-BW-BINDING-SOAP-555030	Unable to send request the service provider for Operation [[0]], SoapReferenceBinding [[1]], Application [[2]:{3}] due to exception [[4]]. Message Received: [[5]]	Ensure that the HTTP Client configurations are configured as per service provider requirements.
TIBCO-BW-BINDING-SOAP-555040	Unable to send request the service provider for Operation [[0]], SoapReferenceBinding [[1]], Application [[2]:{3}] due to exception [[4]]. Message Received: [[5]]	Ensure that the COOKIE format is correct.

REST Binding Error Codes

This section lists the error messages that can be reported by the REST Binding.

Error Codes	Error Message	Error Resolution
TIBCO-BW-BINDING-REST-200001	Creating REST Resource with the HTTP Connector Name [[0]] at Resource Path: [[1]]	This is a debug message and the resolution is not applicable.
TIBCO-BW-BINDING-REST-200002	Creating REST Resource for conflicting path spec	This is a debug message and the resolution is not applicable.
TIBCO-BW-BINDING-REST-200003	Adding REST operation [[0]] with the HTTP Method[[1]] for [[2]] at resource path [[3]]	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
TIBCO-BW-BINDING-REST-200004	Request Received for Operation [{0}]	This is a debug message and the resolution is not applicable.
TIBCO-BW-BINDING-REST-200005	Invoking BW Endpoint [{0}] for Operation [{1}]	This is a debug message and the resolution is not applicable.
TIBCO-BW-BINDING-REST-200006	BW Endpoint [{0}] for Operation [{1}] has been invoked. Waiting for Reply to be generated	This is a debug message and the resolution is not applicable.
TIBCO-BW-BINDING-REST-200007	Response generated. Responding to request	This is a debug message and the resolution is not applicable.
TIBCO-BW-BINDING-REST-200008	Payload for Request is [{0}]	This is a debug message and the resolution is not applicable.
TIBCO-BW-BINDING-REST-200009	Creating XML Message for JSON Message. Element details - targetnamespace [{0}] and name is [{1}]	This is a debug message and the resolution is not applicable.
TIBCO-BW-BINDING-REST-200010	Destroying REST Binding with pathspec [{0}] and binding name [{1}]	This is a debug message and the resolution is not applicable.
TIBCO-BW-	JSON-> XML Conversion Result: \n {0}	This is a debug message and the

Error Codes	Error Message	Error Resolution
BINDING-REST-200011		resolution is not applicable.
TIBCO-BW-BINDING-REST-200012	REST Binding Authentication is enabled. Trying to authenticate using the Authorization Header of the request	This is a debug message and the resolution is not applicable.
TIBCO-BW-BINDING-REST-400001	Expected JSON Content-Type. Got XML Instead. Replying with error to client	The Client needs to be notified to use the right Content-Type Header or the binding configuration can be changed to allow multiple content-types
TIBCO-BW-BINDING-REST-400002	Expected XML Content-Type. Got JSON Instead. Replying with error to client	The Client needs to be notified to use the right Content-Type Header or the binding configuration can be changed to allow multiple content-types
TIBCO-BW-BINDING-REST-500001	Binding Configuration is not for a REST Service Binding	Check configuration of the REST binding
TIBCO-BW-BINDING-REST-500002	NO_RESOURCE_URL_SPECIFIED = No relative resource url specified to deploy REST Resource	Check configuration of the REST binding for the value of the Resource URL field.
TIBCO-BW-BINDING-REST-500003	Unable to create REST resource for binding [{0}]. Reason - Unable to stop conflicting binding [{1}].	Check both binding configurations specified in the error message for the Resource URL fields

Error Codes	Error Message	Error Resolution
TIBCO-BW-BINDING-REST-500004	Error Occurred while trying to create Jersey REST Resource for binding [{1}]	Check configuration of the REST binding specified in the error message
TIBCO-BW-BINDING-REST-500004	Unable to start REST Binding with name [{0}]	Check configuration of the REST binding specified in the error message
TIBCO-BW-BINDING-REST-500005	Unable to stop REST Binding with name [{0}]	Check configuration of the REST binding specified in the error message
TIBCO-BW-BINDING-REST-500006	Error Occurred while parsing and creating the HTTP Headers. Responding to client with error message.	Invalid values were sent by the client in the HTTP headers.
TIBCO-BW-BINDING-REST-500007	Error Occurred while creating Parameters Part. Responding to client with error message.	Invalid values were passed for the Parameters element. Check the client request and the configuration of the REST Binding.
TIBCO-BW-BINDING-REST-500008	Error Occurred while creating User Part. Responding to client with error message.	Invalid values were passed for the Parameters element. Check the client request and the configuration of the REST Binding.
TIBCO-BW-BINDING-REST-500009	The HTTP Connector failed to deploy the REST Service Binding. Check the exception thrown by the HTTP Connector for possible configuration issues.	Check the HTTP Connector exception for possible reasons of failure. For example, Some of them could be related to

Error Codes	Error Message	Error Resolution
TIBCO-BW-BINDING-REST-500010	The HTTP Connector [{0}] shared resource could not be retrieved. Check the REST Binding configuration or the logs if the HTTP Connector could not be started.	overlapping context paths or an address in use.
TIBCO-BW-BINDING-REST-500011	The HTTP Connector [{0}] shared resource could not be retrieved. Check the REST Binding configuration or the logs if the HTTP Connector could not be started.	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-BINDING-REST-500012	AUTHENTICATION_FAILED = Authentication failed for client request. A 401 status code has been sent to the client with the realm as [{0}].	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-BINDING-REST-500013	WSDL_CACHE_NOT_FOUND = An error occurred while trying to retrieve the WSDL/XSD's for the REST binding [{0}]. Check the underlying exception thrown by the WSDL/XSD Cache for the root cause.	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-BINDING-REST-000001	No WSDL Operation found. Revalidate the application module and try deploying again.	This is an internal product error. Contact TIBCO Support.

Core

This section lists the error codes returned by the core components such as runtime.

Engine Error Codes

This section describes the error messages that can be reported by the Engine layers.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 00000 1	{0}	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00001 0	BWActivityManager Registration Error. The BWActivityManager argument provided to the BWEEngine is null.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00001 2	Failed to initialize BWEEngine. The BWEEngine was initialized without a logger object.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00001 8	Failed to initialize BWEEngine. While registering BWActivityBridge, the BWEEngine encountered an exception [{0}].	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 00002 0	Failed to initialize BWEngine. The BWActivityManager was not registered correctly with the BWEngine.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00002 2	Failed to initialize BWEngine. The BW Crypto service was not registered correctly with the BWEngine.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00002 4	Failed to initialize BWEngine. The BW Custom XPath Function Manager service was not registered correctly with the BWEngine.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00002 6	Failed to enable BW Debugger. The BWEngine has not been initialized.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00002 8	The BW Debugger is already enabled state and it cannot be enabled again.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00003 0	Unable to disable BW Debugger. The BWEngine has not been initialized.	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 00003 2	Attempt to disable the BW Debugger encountered an exception [{0}]	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00003 4	Unable to enable BW Event Publisher. The BWEngine has not been initialized.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00003 6	BWEngine configuration data does not contain a AppNode name.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00003 8	BWEngine configuration data does not contain a AppSpace name.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00004 0	BWEngine configuration data does not contain Domain name.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00005 2	The operation [{0}] is not supported for the BX Non-Executable Module. ModuleName={0}, ModuleVersion={1}	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 00005 4	The operation <code>{{0}}</code> is not supported for the BX Executable Module. <code>ModuleName={1}</code> , <code>ModuleVersion={2}</code>	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00005 6	The operation <code>{{0}}</code> is not supported for the BW Job Shared Variable.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00005 7	Unable to obtain EngineManagement. The BWEngine has not been initialized.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00005 8	Unable to obtain EngineManagement due to an exception <code>{{0}}</code>	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00005 9	The BX operation <code>{{0}}</code> failed due to an exception <code>{{1}}</code> .	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00010 2	Invalid 'BWModuleHandle'. The BW Module represented by this handle has been already uninstalled or the handle has been already destroyed.	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 00010 4	Unable to obtain process templates referenced by the BW Module, the BWEngine encountered an exception. ModuleName[{}], ModuleVersion [{}], Exception[{}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00011 6	Unable to obtain GenXDM SchemaComponentCache for the BW Module [{}]. The operation [{}] returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00011 8	Unable to obtain GenXDM SchemaComponentCache for the BW Module [{}]. The operation [{}] returned an exception [{}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00012 0	Unable to obtain GenXDM SchemaComponentCache for the BW Module [{}:{}] due to an exception [{}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00012 2	Unable to obtain "BundleContext" for BW Module [{}:{}]. The operation [{}] returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00012 4	Unable to obtain "BundleContext" for BW Module [{}:{}] due to an exception [{}].	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 00012 6	Unable to obtain ServiceReference for the cache service [{0}]. The operation "BundleContext.getServiceReference" for BW Module [{1}:{2}] returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00012 8	Unable to obtain ServiceReference for the cache service [{0}]. The operation "BundleContext.getServiceReference" for the BW Module [{1}:{2}] returned an exception [{3}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00013 0	Unable to obtain XSD cache service [{0}] for the BW Module [{1}:{2}]. The operation [{3}] returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00013 1	Unable to obtain XSD cache service [{0}] for the BW Module [{1}:{2}]. The operation [{3}] returned an exception [{4}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00013 2	Unable to obtain WSDL cache service [{0}] for the BW Module [{1}:{2}]. The operation [{3}] returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00013	Unable to obtain WSDL cache service [{0}] for the BW Module [{1}:{2}]. The operation [{3}] returned an exception [{4}].	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
3	<p>TIBC O-BW- CORE- 00013 4</p> <p>Unable to obtain WSDL ModuleCache from the WSDLCacheService for the WSDL namespace [{0}], locationURI [{1}] that is associated with the BW Module [{2}:{3}], DeploymentUnit [{4}:{5}]. The operation [{6}] returned "null".</p>	<p>This is an internal product error. Contact TIBCO Support.</p>
5	<p>TIBC O-BW- CORE- 00013 5</p> <p>Unable to obtain WSDL ModuleCache from the WSDLCacheService for the WSDL namespace [{0}], locationURI [{1}] that is associated with the BW Module [{2}:{3}], DeploymentUnit [{4}:{5}]. Encountered an exception [{6}]</p>	<p>This is an internal product error. Contact TIBCO Support.</p>
6	<p>TIBC O-BW- CORE- 00013 6</p> <p>Unable to obtain BxWSDLResolver for the WSDL namespace [{0}], Location [{1}] that is associated with the BW Module [{2}:{3}], DeploymentUnit [{4}:{5}] due to an exception [{6}]</p>	<p>This is an internal product error. Contact TIBCO Support.</p>
7	<p>TIBC O-BW- CORE- 00013 7</p> <p>Unable to obtain the GenXDM WSDL Module for the WSDL namespace [{0}] that is associated with the BW Module [{1}:{2}], DeploymentUnit [{3}:{4}]. The operation "{5}" returned an exception [{6}].</p>	<p>This is an internal product error. Contact TIBCO Support.</p>

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 00013 8	Unable to obtain the GenXDM WSDL Module for the WSDL namespace [{0}] that is associated with the BW Module [{1}:{2}], DeploymentUnit [{3}:{4}]. The operation "{5}" returned "null". Ensure that the BW Module [{6}] is dependent on a BW shared module, which contains the WSDL file for this WSDL namespace. Or the BW Module [{7}] itself contains the required WSDL file.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00014 0	Unable to obtain WSDL Message details from the GenXDM WSDL Module for the WSDL namespace [{0}] that is referenced in the BW Module [{1}:{2}] due to an exception [{3}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00014 2	Unable to obtain WSDL Definition namespace details from the GenXDM WSDL Module for the WSDL namespace [{0}] that is associated with the BW Module [{1}:{2}] due to an exception [{3}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00014 4	Unable to obtain the WSDL Target namespace from the GenXDM WSDL Module for the WSDL namespace [{0}] that is associated with the BW Module [{1}:{2}] due to an exception [{3}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW-	Unable to obtain WSDL Interface details from the GenXDM WSDL	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
CORE-000146	Module for the PortType [{0}], that is associated with the BW Module [{1}:{2}]. The operation "{3}" returned an exception [{4}].	
TIBCO-BW-CORE-000148	Unable to obtain WSDL Interface details from the GenXDM WSDL Module for the PortType [{0}], that is associated with the BW Module [{1}:{2}]. The operation "{3}" returned null.	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-CORE-000150	Unable to construct PortType details from the GenXDM WSDL Interface for the WSDL namespace [{0}] that is associated with the BW Module [{1}:{2}] due to an exception [{3}].	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-CORE-000152	Invalid BWBxWSDLResolver. The instance of this BWBxWSDLResolver has been already released.	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-CORE-000160	The initial value mode [{0}] specified for the {1} [{2}] in BW Module [{3}:{4}], DeploymentUnit [{5}:{6}] is invalid.	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-CORE-000162	The QName value [{0}] specified for the {1} [{2}] in BW Module [{3}] is invalid or malformed.	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 00020 2	Invalid 'BWComponentHandle'. The BW Component represented by this handle has been already uninstalled or the handle has been already destroyed.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00020 4	Unable to create ServiceEndpointRequestHandler for BW Component due to invalid BW Process ServiceType [{0}], ComponentName={1}, ComponentVersion={2}	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00020 6	Unable to create ServiceEndpointRequestHandler for BW Component due to invalid BW Process ServiceName [{0}], ComponentName={1}, ComponentVersion={2}	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00020 8	Error occurred while creating a ServiceEndpointRequestHandler for service [{0}], BW Component [{1}], Application [{2}]:{3}. Exception[{{4}}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00021 0	Unable to create ServiceEndpointRequestHandler for service [{0}], BW Component [{1}]. The operation "BxSystem.getInterfaceProvider" returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE-	Received an unexpected exception [{0}] from the service binding associated with the component	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
00021 2	service [{1}], Application [{2}] on invocation of method [{3}].	
TIBC O-BW- CORE- 00021 4	Unable to obtain "BundleContext". The operation "{0}" returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00021 6	Unable to obtain "BundleContext" due to an exception [{0}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00022 0	Unable to obtain the GenXDM WSDL Module for the WSDL namespace [{0}] that is associated with the BW Component [{1}], Application[{2};{3}]. The operation "{4}" returned an exception [{5}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00022 2	Unable to obtain the GenXDM WSDL Module for the WSDL namespace [{0}] that is associated with the BW Component [{1}], Application[{2};{3}]. The operation "{4}" returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00022 4	Unable to obtain the WSDL Interface details from the GenXDM WSDL Module for the PortType [{0}], that is associated with the BW Component [{1}], Application[{2};{3}]. The operation "{4}" returned an exception [{5}].	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 00022 6	Unable to obtain WSDL Interface details from the GenXDM WSDL Module for the PortType [{0}], that is associated with the BW Component [{1}], Application[{2}: {3}]. The operation "{4}" returned null.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00022 8	Unable to obtain ServiceReference for the cache service [{0}]. The operation "{1}" returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00023 0	Unable to obtain ServiceReference for the cache service [{0}] due to an exception [{1}]	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00023 1	Unable to obtain cache service [{0}]. The operation "{1}" returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00013 2	Unable to obtain cache service [{0}]. The operation "{1}" returned an exception [{2}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00023	Unable to construct PortType details from the GenXDM WSDL Interface for the WSDL namespace [{0}] that is associated with the BW	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
2	Component [{1}] due to an exception [{2}].	
TIBC O-BW- CORE- 00023 4	Unable to obtain ModuleCache for the BW Component [{0}]. The operation "{1}" returned "null".	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00023 5	Failed obtain value for the component level property [{0}], BW Component [{1}], Application [{2}: {3}]. Encountered an exception [{4}]	The BW framework layer encountered errors when accessing the component level property. Contact TIBCO Support.
TIBC O-BW- CORE- 00030 2	Invalid 'BWApplicationHandle'. The BW Application represented by this handle has been already uninstalled or the handle has been already destroyed.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00030 4	Unable to create 'BWApplicationHandle' due to invalid BWComponentHandle list. The argument of type 'List<BWComponentHandle>,' must contain at least one BWComponentHandle.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00030 6	Unable to create 'BWApplicationHandle' due to inconsistent application names in the BWComponentHandle(s) contained in the argument of type 'List<BWComponentHandle>.'. The handle for the BW Component [{0}]	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
	has application name as [{1}] whereas the first handle in the list has application name as [{2}].	
TIBC O-BW- CORE- 00030 8	Unable to create 'BWApplicationHandle' for the BW Application [{0}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00040 2	Error occurred when accessing the ProcessStarter activity [{0}] in process [{1}], module [{2}] from the BWActivityManager. Error={3}.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00040 4	Error occurred when configuring the ProcessStarter activity [{0}] in process [{1}], module [{2}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00040 6	Unable to configure ProcessStarter activity [{0}] in process [{1}], module [{2}] due to crypto service access error.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00040 8	HotUpdate operation not supported for ProcessStarter activity [{0}] in process [{1}], module [{2}]. The ProcessStarter exists for activitId [{3}].	This error can occur if the BW Process file has been corrupted.
TIBC O-BW-	Failed to obtain activity [{0}] in process [{1}], module [{2}] from the	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
CORE-00060 2	BWActivityManager due to an exception [{3}]. ActivityId [{4}].	
TIBC O-BW- CORE- 00060 4	Error occurred when configuring the activity [{0}] in process [{1}], module [{2}]	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00060 6	Unable to configure activity [{0}] in process [{1}], module [{2}] due to crypto service access error.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00060 8	Unable to execute [{0}] operation for an activity. Failed to lookup activity [{1}] in process [{2}], module [{3}] from the BWActivityManager. ActivityId [{4}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 00061 0	HotUpdate operation not supported for activity [{0}] in process [{1}], module [{2}]. The activity already exists for activitld [{3}].	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 10000 1	{0}	This is a trace message and the resolution is not applicable.
TIBC O-BW-	Activated Application[{0}], Component[{1}] in AppNode[{2}],	This is a trace message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-10000 2	ActivationAlias[{{3}}].	
TIBC O-BW- CORE- 10000 3	Activated Application[{{0}}, Module [{{1}}] in AppNode[{{2}}, ActivationAlias[{{3}}].	This is a trace message and the resolution is not applicable.
TIBC O-BW- CORE- 20000 1	{{0}}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20200 0	{{0}}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20200 2	Initialized BWEngine successfully [{{0}}, {{1}}, {{2}}].	This is a debug message and it indicates the BWEngine was initialized successfully. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20205 2	Stopped(Graceful) BWEngine successfully.	This is a debug message and it indicates the BWEngine was stopped gracefully. The resolution is not applicable for this message.
TIBC O-BW-	Stopped(Forceful) BWEngine successfully.	This is a debug message and it indicates the BWEngine was stopped forcefully before

Error Codes	Error Message	Error Resolution
CORE-202053		completing all application jobs. The resolution is not applicable for this message.
TIBC O-BW-CORE-202054	BWEngine is already in stopped state.	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202055	Enabled BW Debugger in the BWEngine.	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202056	Disabled BW Debugger in the BWEngine.	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202100	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202101	INITIATE: install BW Module [{0}:{1}], DeploymentUnit [{2}:{3}].	This is a debug message and it indicates the BWEngine is starting to create the BW Module. The resolution is not applicable for this message.
TIBC O-BW-	Installed BW Module [{0}:{1}], DeploymentUnit [{2}:{3}].	This is a debug message and it indicates the BWEngine has completed creating the BW

Error Codes	Error Message	Error Resolution
CORE-20210 2		Module. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20210 3	INITIATE: release-resources for BW Module [{0}:{1}], DeploymentUnit [{2}:{3}].	This is a debug message and it indicates the BWEngine is starting to release the BW Module resources. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20210 4	Released-resources for BW Module [{0}:{1}], DeploymentUnit [{2}:{3}].	This is a debug message and it indicates the BWEngine has completed releasing the BW Module resources. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20210 5	INITIATE: undeploy BW Module [{0}:{1}], DeploymentUnit [{2}:{3}].	This is a debug message and it indicates the BWEngine is starting to undeploy the BW Module. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20210 6	Undeployed BW Module [{0}:{1}], DeploymentUnit [{2}:{3}].	This is a debug message and it indicates the BWEngine has completed undeploying the BW Module. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20220 0	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW-	INITIATE: install BW Component [{0}], Application[{1}:{2}].	This is a debug message and it indicates the BWEngine is starting to create the BW

Error Codes	Error Message	Error Resolution
CORE-20220 1		Component. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20220 2	Installed BW Component [{0}], Application[{1}:{2}].	This is a debug message and it indicates the BWEEngine has completed creating the BW Component. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20220 3	INITIATE: initialize BW Component [{0}], Application[{1}:{2}].	This is a debug message and it indicates the BWEEngine is starting to initialize the BW Component. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20220 4	Initialized BW Component [{0}], Application[{1}:{2}].	This is a debug message and it indicates the BWEEngine has completed initializing the BW Component. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20220 5	INITIATE: start BW Component [{0}].	This is a debug message and it indicates the BWEEngine is starting the BW Component. The resolution is not applicable for this message.
TIBC O-BW- CORE- 20220 6	Started BW Component [{0}].	This is a debug message and it indicates the BWEEngine has stated the BW Component. The resolution is not applicable for this message.
TIBC O-BW-	INITIATE: stop(Forceful) BW Component [{0}].	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-202207		
TIBC O-BW-CORE-202208	Stopped(Forceful) BW Component [{0}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202209	INITIATE: destroy BW Component [{0}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202210	Destroyed BW Component [{0}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202211	INITIATE: release-resources for BW Component [{0}], Application[{1}:{2}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202212	Released-resources for BW Component [{0}], Application[{1}:{2}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-	INITIATE: undeploy BW Component [{0}], Application[{1}:{2}].	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-20221 3		
TIBC O-BW- CORE- 20221 4	Undeployed BW Component [{0}], Application[{1};{2}].	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20221 5	INITIATE: start ServiceBinding(s) or ProcessStarter for BW Component [{0}], Application[{1};{2}].	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20221 6	Started ServiceBinding(s) or ProcessStarter for BW Component [{0}], Application[{1};{2}].	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20221 7	INITIATE: stop ServiceBinding(s) or ProcessStarter for BW Component [{0}], Application[{1};{2}].	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20221 8	Stopped ServiceBinding(s) or ProcessStarter for BW Component [{0}], Application[{1};{2}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-	INITIATE: start ServiceBinding [{0}] for BW Component [{1}],	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-202219	Application [{2}]{3}.	
TIBC O-BW-CORE-202220	Started ServiceBinding [{0}] for BW Component [{1}], Application [{2}]{3}.	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202221	INITIATE: stop ServiceBinding [{0}] for BW Component [{1}], Application [{2}]{3}.	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202222	Stopped ServiceBinding [{0}] for BW Component [{1}], Application [{2}]{3}.	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202223	Ready to uninstall BW Component [{0}], Application [{1}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202224	Created ServiceEndpointRequestHandler for the ServiceBinding [{0}], Service [{1}], BW Component [{2}], Application [{3}]{4}.	This is a debug message and the resolution is not applicable.
TIBC O-BW-	{0}	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-202300		
TIBC O-BW-CORE-202301	INITIATE: create BW Application [{0}] handle.	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202302	Created BW Application [{0}] handle.	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202303	INITIATE: start BW Application [{0}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202304	Started BW Application [{0}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202309	INITIATE: stop(Graceful) for BW Application [{0}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-	Stopped(Graceful) BW Application [{0}].	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-202310		
TIBC O-BW-CORE-202311	INITIATE: stop(Forceful) BW Application [{0}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202312	Stopped(Forceful) BW Application [{0}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202313	INITIATE: start all ProcessStarters and ServiceBindings for BW Application [{0};{1}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202314	Started all ProcessStarters and ServiceBindings for BW Application [{0};{1}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202315	INITIATE: stop all ProcessStarters and ServiceBindings for BW Application [{0};{1}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-	Stopped all ProcessStarters and ServiceBindings for BW Application	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-202316	[[0]:{1}].	
TIBC O-BW-CORE-202317	INITIATE: pause BW Application [[0]].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202318	Paused BW Application [[0]].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202319	INITIATE: resume BW Application [[0]].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202320	Resumed BW Application [[0]].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202401	INITIATE: initialize ProcessStarter activity [[0]] in Process[[1]], Module [[2]], DeploymentUnit [[3]:{4}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-	Initialized ProcessStarter activity [[0]] in Process[[1]], Module [[2]],	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-20240-2	DeploymentUnit [{3}]{4}.	
TIBC-O-BW-CORE-20240-3	INITIATE: start ProcessStarter activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}]{4}.	This is a debug message and the resolution is not applicable.
TIBC-O-BW-CORE-20240-4	Started ProcessStarter activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}]{4}.	This is a debug message and the resolution is not applicable.
TIBC-O-BW-CORE-20240-5	INITIATE: stop ProcessStarter activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}]{4}.	This is a debug message and the resolution is not applicable.
TIBC-O-BW-CORE-20240-6	Stopped ProcessStarter activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}]{4}.	This is a debug message and the resolution is not applicable.
TIBC-O-BW-CORE-20240-7	INITIATE: destroy ProcessStarter activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}]{4}.	This is a debug message and the resolution is not applicable.
TIBC-O-BW-	Destroyed ProcessStarter activity [{0}] in Process[{1}], Module [{2}],	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-202408	DeploymentUnit [{3}]{4}].	
TIBC O-BW-CORE-202409	INITIATE: release ProcessStarter activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}]{4}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202410	Released ProcessStarter activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}]{4}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202411	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202509	INITIATE: release ProcessStarter activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}]{4}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-202510	Released ProcessStarter activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}]{4}].	This is a debug message and the resolution is not applicable.
TIBC O-BW-	{0}	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-20251 1		
TIBC O-BW- CORE- 20260 1	INITIATE: initialize Activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}:{4}].	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20260 2	Initialized Activity [{0}] in Process [{1}], Module [{2}], DeploymentUnit [{3}:{4}].	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20260 3	INITIATE: destroy Activity [{0}] in Process[{1}], Module [{2}], DeploymentUnit [{3}:{4}].	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20260 4	Destroyed Activity [{0}] in Process [{1}], Module [{2}], DeploymentUnit [{3}:{4}].	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20260 5	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW-	{0}	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-20611 0		
TIBC O-BW- CORE- 20611 1	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20612 0	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20612 1	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20620 0	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20621 0	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW-	{0}	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-20631 0		
TIBC O-BW- CORE- 20631 1	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20640 0	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20641 0	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20652 0	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW- CORE- 20652 1	{0}	This is a debug message and the resolution is not applicable.
TIBC O-BW-	Activity input data validation details. ActivityName={0},	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
CORE-20661 1	ProcessName={1}, Module={2}:{3}, Schema={4}, Data={5}	
TIBC O-BW-CORE-20661 2	Activity output data validation details. ActivityName={0}, ProcessName={1}, Module={2}:{3}, Schema={4}, Data={5}	This is a debug message and the resolution is not applicable.
TIBC O-BW-CORE-30000 2	The BusinessWorks Event Publisher is disabled.	This message indicates the BWEngine is configured to disable the Event Publisher. Therefore there is no event published by the BWEngine.
TIBC O-BW-CORE-40000 1	{0}	This is a warning message and it highlights situations that may affect the application execution.
TIBC O-BW-CORE-40000 4	Activity resource release operation [com.tibco.bw.runtime.ActivityResource.release()] called at the end of the execution of the BW group or BW Process instance encountered an error. The Activity resource release operation [{0}.release (boolean)] raised an exception: {1}	The activity resource release operation must not raise an exception. This is considered to be an activity resource implementation error.
TIBC O-BW-CORE-40000 6	CatchAll fault details formatting issue. Expected [{0}], but received [{1}]	Received an unexpected data when formatting the CatchAll fault details.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 40001 0	The BW process [{0}] instance canceled, JobId [{1}], ProcessInstanceId [{2}], ParentProcessInstanceId [{3}], Module [{4}:{5}], Application [{6}:{7}].	This message is generated when the BusinessWorks Engine cancels a process instance execution. A process instance can be canceled when one of the following occurs: the invoke activity (in the parent process) that called this process instance timed out, the application is stopped non-gracefully, or the process instance is explicitly canceled through an internal management interface.
TIBC O-BW- CORE- 40010 2	Unable to close the file [{0}] configured for the initial value of the {1} [{2}] in the BW Module [{3}:{4}], DeploymentUnit [{5}:{6}]; encountered an exception [{7}].	The BWEngine was unable to close the file that contains initial values for the Module or Job Shared variables. This error occurred when attempting to close the file, but after reading the file contents.
TIBC O-BW- CORE- 40020 2	The BW Component [{0}:{1}] is already in destroyed state.	The BW framework is attempting to destroy the BW Component that is already in destroyed state. The resolution is not applicable.
TIBC O-BW- CORE- 50000 1	{0}	This error code is used to log BWEngine errors. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50001 0	Failed to initialize BWEngine due to an exception [{0}]	The BWEngine did not successfully initialize, and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-	Failed to initialize BWEngine due to database access error	The BWEngine was not able to establish connection or access the engine database

Error Codes	Error Message	Error Resolution
CORE-50001 1		instance. Ensure that the database driver, connection, username, and password details are correctly specified. Also ensure that the database instance has been started.
TIBC O-BW- CORE- 50001 2	Failed to initialize BWEngine due to engine group connection provider error	The BWEngine failed to establish connection with the engine group connection provider. Ensure that the group connection provider entity (bw.engine.groupProvider.technology) specified in the BWAppNode or BWAppSpace configuration file has been started and accessible to the BWEngine.
TIBC O-BW- CORE- 50001 3	Failed to initialize BWEngine due to database schema configuration error. The BWEngine database does not contain the required tables. Ensure that the BWEngine database has been created with the table schemas required by the engine	The BWEngine was not able to initialize due to the engine database schema configuration error. Create an engine database using the database scripts provided in the TIBCO BusinessWorks product and this can configure the database with the appropriate schemas required by the engine.
TIBC O-BW- CORE- 50001 4	Failed to initialize BWEngine due to missing or incorrect engine database configuration data. The BWEngine persistence mode property [{0}] is set to [datastore] and this option requires valid engine database configuration data	The BWEngine is configured to run in persistence mode "datastore". However, the required database configuration data was not specified. Ensure that the BWEngine is configured with the required database connection details.
TIBC O-BW- CORE- 50001 5	Failed to initialize BWEngine due to missing or incorrect engine database configuration data. The BWEngine persistence mode property [{0}] is set to [group] and this option requires valid engine	The BWEngine is configured to run in persistence mode "group". However, the required database configuration data was not specified. Ensure that the BWEngine is configured with the required database connection details.

Error Codes	Error Message	Error Resolution
	database configuration data	
TIBC O-BW- CORE- 50001 6	Failed to initialize BWEngine due to incompatible engine group name. The group name [{}] configured for the BWEngine does not match the group name value in the BWEngine database. Try using a different engine database or change the engine group name to match the value in the database	This error can occur when the BWEngine is configured to use a group name that does not match the group name in the engine database. To resolve these issues, change the engine group name to match the group name in the engine database, use a different engine database that contains the matching engine group name or create a new engine database. Furthermore, if the group name is not specified, then the BWEngine uses a default group name. Refer to the documentation for more details on the naming convention used for the default engine group name.
TIBC O-BW- CORE- 50001 7	Failed to initialize BWEngine due to incompatible persistence mode between the engine and the engine database. This error can occur if the BWEngine is configured to execute in the persistence mode [group]. However, the BWEngine database is configured for the persistence mode [datastore]. Try using a different database or use a database that is configured for the persistence mode [group].	This error can occur if the engine database was previously used by a BWEngine configured to run in persistence mode 'datastore' (bw.engine.persistenceMode=datastore). When a BWEngine uses the database for the first time, the database is updated with the engine execution persistence mode. Later the persistence mode value stored in the database cannot be altered and the same database cannot be used for different engine persistence mode. To resolve this issue, ensure the engine and the database persistence mode match or create a new database using the database scripts provided by the TIBCO BusinessWorks product.
TIBC O-BW- CORE- 50001	Failed to initialize BWEngine due to incompatible persistence mode between the engine and the engine database. This error can occur if	This error can occur if the engine database was previously used by a BWEngine configured to run in persistence mode 'group'

Error Codes	Error Message	Error Resolution
8	the BWEngine is configured to execute in persistence mode [datastore]. However, the engine database is configured for the persistence mode [group]. Try using a database that is configured for the persistence mode [datastore] or create a new engine database	(bw.engine.persistenceMode=group). When a BWEngine uses the database for the first time, the database is updated with the engine execution persistence mode. Later the persistence mode value stored in the database cannot be altered and the same database cannot be used for different engine persistence mode. To resolve this issue, ensure the engine and the database persistence mode match or create a new database using the database scripts provided by the TIBCO BusinessWorks product.
TIBC O-BW- CORE- 50001 9	Failed to initialize BWEngine due to missing or incorrect group connection provider configuration data. The BWEngine persistence mode property [{0}] is set to [group] and this option requires valid engine group connection provider configuration data.	This error can occur if the BWEngine is configured to run in persistence mode [group] and the engine is not correctly configured with the group connection provider data. Ensure that the BWEngine is configured with the required group connection provider details.
TIBC O-BW- CORE- 50002 0	Failed to initialize BWEngine due to incorrect engine group name. The BWEngine persistence mode property [{0}] is set to [group] and this option requires a valid engine group name specified via the property [{1}].	This error can occur if the BWEngine is configured to run in persistence mode [group] and an empty or invalid engine group name is specified. Ensure that the engine group name is not empty or contains a valid name.
TIBC O-BW- CORE- 50002 1	Failed to initialize BWEngine. The BWEngine thread count value is configured incorrectly. Ensure that the thread count value is set to an integer that is greater than zero	Ensure that the BWEngine thread count is not configured to be empty or null. Furthermore, the thread count value must be an integer that is greater than zero.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50002 2	Failed to initialize BWEEngine. The BWEEngine step count value is configured incorrectly. Ensure that the step count value is set to "-1" or an integer that is greater than zero	Ensure that the BWEEngine step count is not configured to be empty or null. Furthermore, the step count value must be "-1" or an integer that is greater than zero.
TIBC O-BW- CORE- 50002 3	Failed to initialize BWEEngine. The BWEEngine property [{0}] contains an incorrect value [{1}]. Ensure that the value is an integer that is greater than one	Ensure that the specified BWEEngine property is not configured to be empty or null. The value configured for this property must be an integer that is greater than zero.
TIBC O-BW- CORE- 50002 4	Failed to initialize BWEEngine. The BWEEngine property [{0}] contains an incorrect value [{1}]. Ensure that the value is an integer that is greater than one.	Ensure that the specified BWEEngine property is not configured to be empty or null. The value configured for this property must be an integer that is greater than zero.
TIBC O-BW- CORE- 50002 5	Failed to initialize BWEEngine. While creating a SpringApplicationContext, the BWEEngine encountered an exception: {0}.	This is an internal product error. Contact TIBCO Support.
TIBC O-BW- CORE- 50002 6	The ProcessStarter has not been initialized or it is in the destroyed state. The EventSourceContext associated with the ProcessStarter is invalid.	A ProcessStarter is attempting to perform an operation when it has not been initialized or it is in the destroyed state. This is considered to be a ProcessStarter implementation error.
TIBC O-BW- CORE- 50002 7	Failed to initialize BWEEngine due to an exception [{0}]. This error can occur if the BWEEngine persistence mode is set to [{1}] and the same database configuration is used by	This error can be reported when multiple BWEEngines configured for 'datastore' persistence mode is attempting to use the same database configuration. Ensure that a different database configuration is specified for

Error Codes	Error Message	Error Resolution
	multiple BWEngines. When a BWEEngine is configured for the persistence mode <code>[[2]]</code> , then each BWEEngine must have a unique database configuration. This is applicable even if the BWEngines (BW AppNodes) are part of the same BW AppSpace	each BWEEngine when the persistence option is 'datastore'. This is also applicable when multiple BWEngines (BW AppNodes) are part of the same BW AppSpace.
TIBC O-BW- CORE- 50003 0	BWEEngine stop operation encountered an exception <code>[[0]]</code>	An error was encountered when stopping the BWEEngine. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50003 1	BWEEngine graceful stop operation encountered an exception <code>[[0]]</code>	An error was encountered when attempting to stop the BWEEngine gracefully. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50003 2	Exception occurred when accessing the custom XPATH functions associated with the BWEEngine. Exception= <code>{0}</code>	Error was encountered when attempting to access the custom XPath function associated with the BWEEngine. Contact TIBCO Support.
TIBC O-BW- CORE- 50003 3	Failed to enable the BW Debugger entity in the BWEEngine due to an exception <code>[[0]]</code>	Error was encountered when attempting to enable the BW Debugger entity in the BWEEngine. Contact TIBCO Support.
TIBC O-BW- CORE-	BW Debugger connection failed, encountered an exception <code>[[0]]</code>	Ensure that valid BW Debugger connection is provided when enabling the BW Debugger entity in the BWEEngine.

Error Codes	Error Message	Error Resolution
50003 4	Unable to enable Event Publisher in the BWEngine, encountered an exception [{0}]	Error was encountered when attempting to enable the Event Publisher in the BWEngine. Contact TIBCO Support.
TIBC O-BW- CORE- 50003 5	Attempt to disable the Event Publisher in the BWEngine, encountered an exception [{0}]	Error was encountered when attempting to disable the Event Publisher in the BWEngine. Contact TIBCO Support.
TIBC O-BW- CORE- 50003 7	Unable to associate an activity resource with a BW group. The activity [{0}] in process [{1}] is not contained within a group. However, the activity is attempting to associate a resource with a group. {2}	An activity that is not inside a group is attempting to associate a resource with a group. This error can occur due to an activity implementation error.
TIBC O-BW- CORE- 50003 8	Unable to associate an activity resource with a BW loop. The activity [{0}] in process [{1}] is not contained within a loop. However, the activity is attempting to associate a resource with a loop. {2}	An activity that is not inside a loop is attempting to associate a resource with a loop. This error can occur due to an activity implementation error.
TIBC O-BW- CORE- 50003 9	Reference Binding configured for the process reference [{0}], in process [{1}], module [{2}] provided an unsupported message data model [{3}].	The Reference Binding configured for the process provided an invalid message data model. This error can occur due to the Reference Binding implementation error.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50004 0	Invocation of the Process Reference's operation [{0}] failed. The BW Reference Binding [{1}] configured for the process reference [{2}] in process [{3}], module [{4}] returned fault [{5}].	This error indicates the Reference Binding configured for the process reference failed and returned a fault.
TIBC O-BW- CORE- 50004 1	Invalid activity name. The activity name [{0}] is not found in process [{1}], module [{2}]{3}], DeploymentUnit [{4}]{5}].	The error indicates that the specified activity name is not contained within the BW process. Ensure that a valid activity name is specified for this operation.
TIBC O-BW- CORE- 50004 2	The BW Debugger entity is already enabled in the BWEngine and it cannot be enabled again.	The BW Debugger entity in the BWEngine cannot be enabled again when it is already in an enabled state. It is only possible to disable the BW Debugger entity when it is in the enabled state.
TIBC O-BW- CORE- 50005 0	The BW process [{0}] instance faulted, JobId [{1}], ProcessInstanceId [{2}], ParentProcessInstanceId [{3}], Module [{4}]{5}], Application [{6}]{7}]. {8}	This error message indicates that the process instance did not complete successfully. Instead it ended due to an error that occurred during the execution of the process instance. For more details on the process instance failure, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50005 1	Activity [{0}] fault. {1}	This message indicates the potential activity that raised the fault and caused the process instance to fail.
TIBC O-BW-	Invoke activity [{0}] fault. {1}	This message indicates the potential invoke activity that raised the fault and caused the

Error Codes	Error Message	Error Resolution
CORE-50005 2		process instance to fail.
TIBC O-BW- CORE- 50005 3	XSLT transformation error. {0}	This message indicates that the cause of the failure could be due to an XSLT transformation error.
TIBC O-BW- CORE- 50005 4	Activity [{0}] XSLT transformation error. {1}	This message indicates that the cause of the failure could be due to an Activity XSLT transformation error.
TIBC O-BW- CORE- 50005 5	XPATH error. {0}	This message indicates that the cause of the failure could be due to an XPATH error.
TIBC O-BW- CORE- 50005 6	Activity [{0}] XPATH error. {1}	This message indicates that the cause of the failure could be due to an Activity XPATH error.
TIBC O-BW- CORE- 50005 7	XML related error. {0}	This message indicates that the cause of the failure could be due to an XML error.
TIBC O-BW-	Activity [{0}] XML related error. {1}	This message indicates that the cause of the failure could be due to an Activity XML error.

Error Codes	Error Message	Error Resolution
CORE-500058	Reply activity [{0}] error. The reply activity cannot be associated with the ProcessService request message. This error can occur if the process is implemented to send a reply multiple times for the same request, the caller of this process is no longer available or on recovery from a check-point the caller did not recover because it was not part of the check-pointed job. {1}	This error message is reported when a process is implemented to run more than one Reply activity for the same operation. The caller of this process (Service Binding, Parent Process) has ended before the Reply activity can be run or on recovery from a check-point. The Reply activity is run but the caller of this process did not recover because it was not part of the check-pointed job. Ensure that the process is not implemented to reply to the same request multiple times.
TIBC O-BW-CORE-500060	The process instance terminated without replying to the caller of this process. {0}	This message is reported when a process instance ends without replying to the request of a ProcessService operation. This can occur if the process is implemented incorrectly to end the process execution without performing a reply operation or when the process instance is canceled. Ensure that the process is implemented correctly and there is no validation errors.
TIBC O-BW-CORE-500061	Reply activity [{0}] error. The reply activity [{1}] encountered an error on sending the response to the caller of this process. This error can occur if the caller of this process raised a fault when processing the reply message, the caller of this process is no longer available. {2}	This error message can be reported for the following reasons: the caller of this process (Service Binding, Parent Process) raised a fault when processing the reply message, the caller of this process is no longer available.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50006 3	{0}	This message provides information for the process instance failure.
TIBC O-BW- CORE- 50006 4	Activity [{0}] error. {1}	This message indicates the potential activity that raised the fault and caused the process instance to fail.
TIBC O-BW- CORE- 50006 5	Throw activity [{0}] fault. Fault: {1}	This message indicates the name of the Throw activity that raised the fault and caused the process instance to fail.
TIBC O-BW- CORE- 50006 6	Invoke activity faulted due to an error from the invoked subprocess. {0}	This message indicates that the Invoke activity failed due to an unexpected error received for the invoked subprocess. This error can occur if the subprocess ended without replying, the subprocess has faulted, the invoked subprocess does not exist, and so on. Ensure that the invoked subprocess is implemented correctly and confirms to the invoked operation contract.
TIBC O-BW- CORE- 50006 7	Activity [{0}] faulted due to an object serialization error. This error can occur if an object that must be serialized as part of the BusinessWorks process execution is not Serializable or the Java package that contains the class is not exported correctly. {1}	This error can occur when the BWE engine is attempting to serialize a Java object to support the persistence feature and the object cannot be serialized. Ensure that the Java object is Serializable and the Java package that contains the class is exported.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50006 8	Fault occurred due to an object serialization error. This error can occur if the Java class that must be serialized as part of the BusinessWorks process execution is not Serializable or the Java package that contains the class is not exported correctly. {0}	This error can occur when the BWEEngine is attempting to serialize a Java object to support the persistence feature; however the Java object cannot be serialized. Ensure that the Java object is Serializable and the Java package that contains the class is exported.
TIBC O-BW- CORE- 50008 9	Failed to confirm the request message from the receive activity [{0}], in process [{1}], module [{2}]: [{3}], application [{4}]:[{5}]. This error can occur if the process is implemented to confirm multiple times for the same request message, the caller of this process is no longer available, on recovery from a check-point the caller did not recover because it was not part of the check-pointed job or the specified receive activity name is incorrect.	<p>This error message can be reported for the following reasons:</p> <ul style="list-style-type: none"> • The process is implemented to run more than one confirm activity for the same request. • The caller of this process instance (Service Binding, Parent process) has ended before the confirm activity can be run. • On recovery from a check-point, the confirm activity is run. <p>However, the caller of this process did not recover because it was not part of the check-pointed job. Ensure that the process is not implemented to confirm to the same request for multiple times or the activity name configured in the confirm activity is correct.</p>
TIBC O-BW- CORE- 50009 0	The reply operation [com.tibco.bw.runtime.EventContext.reply(..)] is not supported for the activity [{0}], in process [{1}], module [{2}]:[{3}], application [{4}]:[{5}].	The operation [com.tibco.bw.runtime.EventContext.reply(..)] is not allowed for the specified activity and this is an implementation error.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50009 1	Invalid argument value. The BW Application name cannot be null.	The BusinessWorks application specified for this operation cannot be null or empty. Ensure that a valid application name is specified for this operation.
TIBC O-BW- CORE- 50009 2	Unable to get BW Process instances information for the BW Application [{0}] due to an exception [{1}].	Error occurred when obtaining the process instance details for the specified BusinessWorks application.
TIBC O-BW- CORE- 50009 3	Unable to get BW Process instance information for the BW ProcessIntanceld [{0}] due to an exception [{1}].	Error occurred when obtaining the process instance details for the specified BusinessWorks ProcessIntanceld.
TIBC O-BW- CORE- 50009 4	Unable to get BW Process instance summary information for the BW ProcessIntanceld [{0}] due to an exception [{1}].	Error occurred when obtaining the process instance details for the specified BusinessWorks ProcessIntanceld.
TIBC O-BW- CORE- 50009 5	Failed to suspend the BW Process instance for the BW ProcessIntanceld [{0}] due to an exception [{1}].	Error occurred when attempting to suspend the process instance for the specified BusinessWorks ProcessIntanceld.
TIBC O-BW- CORE- 50009 6	Failed to resume the BW Process instance for the BW ProcessIntanceld [{0}] due to an exception [{1}].	Error occurred when attempting to resume the process instance for the specified BusinessWorks ProcessIntanceld.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50009 7	Failed to cancel the BW Process instance for the BW ProcessIntanceld [{0}] due to an exception [{1}].	Error occurred when attempting to cancel the process instance for the specified BusinessWorks ProcessIntanceld.
TIBC O-BW- CORE- 50009 8	BWAppNode name [{0}] exceeds 250 characters and it is possible to create the internal engine alias name.	BWAppNode name exceeds 250 characters this is not possible create unique engine name. Ensure that the AppNode name is fewer than 250 characters.
TIBC O-BW- CORE- 50010 2	Failed to install BW Module [{0}: {1}], DeploymentUnit [{2}:{3}]	The BW Module did not get installed in the BWEngine, and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50010 4	Encountered errors on release-resource operation for the BW Module [{0}:{1}], DeploymentUnit [{2}:{3}]	The BWEngine encountered errors when releasing resources associated with the BW Module and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50010 6	Encountered errors when undeploying the BW Module [{0}: {1}], DeploymentUnit [{2}:{3}]	The BWEngine encountered errors when undeploying the BW Module and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-	Failed to install BW Module [{0}: {1}], DeploymentUnit [{2}:{3}]. The	The BW Module or the process is using a persistence feature, module shared variable

Error Codes	Error Message	Error Resolution
CORE-500110	module or a process is configured to use the BWEngine persistence feature. However, the BWEngine is not configured with a correct engine persistence mode. Ensure that the BWEngine is configured for the engine persistence mode [datastore] or [group] before installing this module.	with persistence option, and so on. However, the BWEngine persistence mode is not set appropriately for this feature. Ensure that the BWEngine persistence mode (<code>bw.engine.persistenceMode</code>) is set to "datastore" or "group" and the required engine database configuration is specified.
TIBC O-BW-CORE-500112	Failed to start BW Module due to an activity start error. CausedBy	This error is reported when the BW Activity in the process fails to initialize and start. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-500117	Unable to obtain SchemaComponentCache (Namespace={0}, Location={1}, BaseURI={2}) for BW Module [{3}: {4}] due to an exception [{5}]	Failed to obtain SchemaComponentCache for the schema required by the BW Module and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-500118	Unable to add schema to SchemaComponentCache (Namespace={0}, Location={1}) due to an exception [{2}]	Failed to add a schema required by the BW Module to SchemaComponentCache and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-500119	Unable to obtain WSDL ModuleCache (Namespace={0}, Location={1}) for BW Module [{2}: {3}]. The WSDLCacheService operation [{4}] returned "null".	Failed to get the WSDL ModuleCache required by the BW Module.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50012 1	Unable to obtain WSDL ModuleCache (Namespace={0}, Location={1}) for BW Module [{2}:{3}]. The WSDLCacheService operation [{4}] returned "null".	Failed to get the WSDL ModuleCache for the WSDL required by the BW Module.
TIBC O-BW- CORE- 50012 2	Unable to obtain WSDL ModuleCache (Namespace={0}, Location={1}) for BW Module [{2}:{3}]. The WSDLCacheService operation [{4}] returned an exception [{5}].	Failed to get the WSDL ModuleCache for the WSDL required by the BW Module and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50012 3	Unable to resolve Schema (Namespace={0}, Location={1}, BaseURI={2}) for BW Module [{3}:{4}]. The SchemaCacheService operation [{5}] returned "null".	Failed to resolve the schema required by the BW Module. Ensure that the schema is valid. The schemas imported/referenced by this schema are valid, and the schemaLocation of the schemas imported by this schema is valid.
TIBC O-BW- CORE- 50013 1	Invalid or empty file name is specified for the initial value of the {0} [{1}] in BW Module [{2}:{3}], DeploymentUnit [{4}:{5}].	The module shared variable or the job shared variable contains an incorrect value or is empty. Ensure that the module or the job shared variable has been initialized or assigned with a correct value.
TIBC O-BW- CORE- 50013 2	The file [{0}] configured for the initial value of the {1} [{2}] is not found in BW Module [{3}:{4}], DeploymentUnit [{5}:{6}].	The module shared variable or the job shared variable has been initialized with a file URL that is not found in the BW Module. Ensure that the specified file name is valid or the file is contained within the BW Module.
TIBC O-BW- CORE- 50013 3	Unable to access the file [{0}] configured for the initial value of the {1} [{2}] in BW Module [{3}:{4}], DeploymentUnit [{5}:{6}]; encountered an exception [{7}].	Failed to access the file specified in the module or job shared variable and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of

Error Codes	Error Message	Error Resolution
		this error message.
TIBC O-BW- CORE- 50013 4	Unable to open the file [{0}] configured for the initial value of the {1} [{2}] in BW Module [{3}:{4}], DeploymentUnit [{5}:{6}]; encountered an exception [{7}].	Failed to open the file specified in the module or job shared variable and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50013 5	Unable to read the file [{0}] configured for the initial value of the {1} [{2}] in BW Module [{3}:{4}], DeploymentUnit [{5}:{6}]; encountered an exception [{7}].	Failed to read the file specified in the module or job shared variable and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50013 6	The contents of the file [{0}] configured for the initial value of the {1} [{2}] in BW Module [{3}:{4}], DeploymentUnit [{5}:{6}] is empty.	Ensure that the file specified for the module or job shared variable is not empty.
TIBC O-BW- CORE- 50014 1	Invalid BW Module property. The module property [{0}] is not defined in the BW Module [{1}:{2}], DeploymentUnit [{3}:{4}]. Therefore the XPath function "getModuleProperty({5})" contained in the XSLT is not able to resolve this module property.	Ensure that the module property correctly defined in the BW Module.
TIBC O-BW- CORE- 50014 2	Unable to resolve the BW Module property [{0}] defined in the BW Module [{1}:{2}], DeploymentUnit [{3}:{4}] via the XPath function "getModuleProperty({5})"	Ensure that the module property correctly defined in the BW Module.

Error Codes	Error Message	Error Resolution
	contained in the XSLT. Encountered an exception [{6}].	
TIBC O-BW- CORE- 50014 3	Failed to create Binding ReferenceEndpoint for the process reference [{0}] in process [{1}], module [{2}:{3}], DeploymentUnit [{4}:{5}]; encountered an exception [{6}]	Encountered errors when creating the binding endpoint for the BW process reference and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50014 4	Failed to obtain module properties for the module [{0}:{1}], DeploymentUnit [{2}:{3}]; encountered an exception [{4}]	BW framework layer encountered errors when accessing module properties for the specified BW Module. Contact TIBCO Support.
TIBC O-BW- CORE- 50014 5	Unable to obtain WSDL Interface details for the PortType [{0}], that is associated with the BW Module [{1}:{2}]. Encountered an exception [{3}]	Error occurred when attempting to obtain WSDL details for the specified PortType, and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50020 2	Failed to install BW Component [{0}], Application [{1}:{2}]	The BW Component did not get installed in the BWEEngine, and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50020 3	Failed to install BW Component [{0}], Application [{1}:{2}]. The application is configured with the Job PageThreshold property [bw.application.job.pageThreshol d.*]. However, the BWEEngine is not	The BusinessWorks application or the component in the application is configured to use the Job PageThreshold property [bw.application.job.pageThreshold.*] and this requires the BWEEngine to be configured for the "datastore" or "group" persistence mode. Stop

Error Codes	Error Message	Error Resolution
	configured with a correct engine persistence mode. Ensure that the BWEngine is configured for the engine persistence mode [datastore] or [group] before installing this application.	the BusinessWorks AppSpace, configure the BWEngine for the engine persistence mode [datastore] or [group] and restart the AppSpace before installing the application.
TIBC O-BW- CORE- 50021 0	Encountered error(s) on release-resource operation for the BW Component [{0}], Application [{1}]: {2}	Error occurred when releasing the resources associated with the BW Component, and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50021 1	Encountered error(s) when undeploying the BW Component [{0}], Application [{1}]:{2}	Error occurred when undeploying the BW Component and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50021 2	Failed to initialize BW Component [{0}], Application [{1}]:{2}	Error occurred when initializing the BW Component and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50021 3	Failed to initialize BW Component [{0}], Application [{1}]:{2} due to activity creation error	Error occurred when creating an instance of an activity that is associated with the BW Component. Therefore the BW Component cannot be initialized. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50021 4	Failed to initialize BW Component [{0}], Application [{1};{2}] due to activity or resource configuration error	There is a configuration error in the activity or resource that is associated with the BW Component; therefore the BW Component cannot be initialized. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50023 0	Failed to initialize BW Component [{0}], Application [{1};{2}] due to activity implementation error	There are implementation errors in the activity that is associated with the BW Component; therefore the BW Component cannot be initialized. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50023 2	Failed to initialize BW Component [{0}], Application [{1};{2}] due to activity initialization error	Error occurred when initializing an activity that is associated with the BW Component; therefore the BW Component cannot be initialized. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50023 8	Encountered error when destroying the BW Component [{0}]	Error occurred when destroying or deleting the BW Component and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50024 0	Encountered errors when destroying the BW Component [{0}]	Error occurred when destroying or deleting the BW Component and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50024 2	Failed to start BW Component [{0}], Application [{1}:{2}]	error message. Error occurred when starting the BW Component and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50024 6	Encountered error(s) when stopping the BW Component [{0}], Application [{1}:{2}]	Error occurred when stopping the BW Component and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50024 8	Encountered error(s) when starting the ProcessStarter associated with the BW Component [{0}], Application [{1}:{2}]	Error occurred when starting the ProcessStarter activity that is associated with the BW Component. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50025 0	Encountered error(s) when stopping the ProcessStarter associated with the BW Component [{0}], Application [{1}: {2}]	Error occurred when stopping the ProcessStarter activity that is associated with the BW Component. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50025 2	Failed to start ServiceBinding [{0}] for the BW Component [{1}], Application [{2}:{3}] due to ServiceBinding lifecycle error	Error occurred when starting the ServiceBinding that is associated with the BW Component. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50025 4	Unable to stop ServiceBinding [{0}] for the BW Component [{1}], Application [{2}]{3} due to ServiceBinding lifecycle error	Error occurred when stopping the ServiceBinding that is associated with the BW Component. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50025 6	The job flow limit property [{0}] for the application or the component is configured incorrectly. Ensure that the job flow limit property value is set to an integer that is greater than zero.	The BW application or component's job flow limit property is configured with an incorrect value. The job flow limit property value must be an integer that is greater than zero.
TIBC O-BW- CORE- 50025 8	The job priority property [{0}] for the application or the component is configured incorrectly. Ensure that the job priority property value is set to "low", "normal" or "high".	The BW application or component's job priority property is configured with an incorrect value. The job priority property can only be configured with the string value "low", "normal" or "high".
TIBC O-BW- CORE- 50026 2	The property to enable activity input validation for the application or the component is configured incorrectly. Ensure properties that are prefixed with [{0}] are set with the value "true" or "false".	The property that is used to determine the enabling of the activity output validation for the application or the component is configured with an incorrect value. This property can only be configured with the string value "true" or "false".
TIBC O-BW- CORE- 50026 4	The property to enable activity output validation for the application or the component is configured incorrectly. Ensure properties that are prefixed with [{0}] are set with the value "true" or "false".	The resolution is not applicable. Contact TIBCO Support.
TIBC	The property that specifies the	The property that specifies the default wait

Error Codes	Error Message	Error Resolution
O-BW-CORE-500265	async activity default wait time is configured incorrectly. Ensure that the property <code>[[0]]</code> or the properties prefixed with <code>[[1]]</code> are configured with a zero or positive numeric value	time (timeout) value for an asynchronous activity is configured incorrectly. The value for this property must be a zero or positive number. This property can be configured the AppSpace/AppNode configuration file 'config.ini'
TIBC O-BW-CORE-500302	Failed to start BW Application <code>[[0]]</code> due to an exception <code>[[1]]</code>	The BW Application did not start and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-500304	Failed to start BW Application <code>[[0]]</code> : <code>[[1]]</code> due to an activity error	Error occurred in an activity that is associated with the BW Application. Therefore the BW Application did not start. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-500306	Encountered error when attempting to stop BW Application <code>[[0]]</code> : <code>[[1]]</code> gracefully	Error occurred when attempting to stop the BW Application gracefully and this could be due to many reasons. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-500307	The BW Application <code>[[0]]</code> : <code>[[1]]</code> is already in stopping state. Unable to perform operation "stopApplicationGraceful"	The BW Application is already in stopped state; therefore it cannot be stopped again.
TIBC O-BW-CORE-	Encountered error when attempting to stop BW Application <code>[[0]]</code> : <code>[[1]]</code>	Error occurred when attempting to stop the BW Application and this could be due to many reasons. For more details, refer to the

Error Codes	Error Message	Error Resolution
50030 8		additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50031 0	Encountered errors when attempting to stop BW Application [{0}:{1}]	The resolution is not applicable. Contact TIBCO Support.
TIBC O-BW- CORE- 50031 2	Unable to start ServiceBinding(s) or ProcessStarter(s) associated with the BW Application [{0}:{1}]	Error occurred when attempting to start the ServiceBinding(s) or ProcessStarter(s) activity that is associated with the BW Application. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50031 4	Unable to stop ServiceBinding(s) or ProcessStarter(s) associated with the BW Application [{0}:{1}]	Error occurred when attempting to stop the ServiceBinding(s) or ProcessStarter(s) activity that is associated with the BW Application. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50031 6	Encountered error when attempting to pause BW Application [{0}:{1}] job(s)	Error occurred when attempting to resume the BW Application. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50031 8	Encountered error when attempting to resume BW Application [{0}:{1}] job(s)	The resolution is not applicable. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50040 2	Failed to create the ProcessStarter activity [{0}] in process [{1}], module [{2}] due to an exception [{3}]	Error occurred when attempting to create an instance of the ProcessStarter activity in a process. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50040 4	Failed to create the ProcessStarter activity [{0}] in process [{1}], module [{2}] due to an unexpected exception [{3}]	Unexpected error occurred when attempting to create an instance of the ProcessStarter activity in a process. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50040 6	Failed to initialize the ProcessStarter activity [{0}] in process [{1}], module [{2}] due to activity lifecycle error	Error occurred when attempting to initialize an instance of the ProcessStarter activity in a process. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50040 8	Failed to initialize the ProcessStarter activity [{0}] in process [{1}], module [{2}] due to an unexpected activity lifecycle error	Unexpected error occurred when attempting to initialize an instance of the ProcessStarter activity in a process. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50041 0	Failed to start the ProcessStarter activity [{0}] in process [{1}], module [{2}] due to activity lifecycle error	Error occurred when attempting to start the ProcessStarter activity in a process. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-	Failed to start the ProcessStarter activity [{0}] in process [{1}],	Unexpected error occurred when attempting to start the ProcessStarter activity in a process.

Error Codes	Error Message	Error Resolution
CORE-50041 2	module [{2}] due to an unexpected activity lifecycle error	For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50041 4	The stop operation for the ProcessStarter activity [{0}] in process [{1}], module [{2}] failed with an unexpected exception [{3}]	Unexpected error occurred when attempting to stop the ProcessStarter activity in a process. The ProcessStarter activity stop operation "com.tibco.bw.runtime.EventSource.stop()" failed and returned an unexpected exception. The ProcessStarter stop operation must not raise a fault and it is considered to be a ProcessStarter activity implementation error.
TIBC O-BW- CORE- 50041 6	The destroy operation for the ProcessStarter activity [{0}] in process [{1}], module [{2}] failed with an unexpected exception [{3}]	Unexpected error occurred when attempting to destroy the ProcessStarter activity in a process. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50041 8	The release operation for the ProcessStarter activity [{0}] in process [{1}], module [{2}] failed with an unexpected exception [{3}]	Unexpected error occurred when attempting to release resources for the ProcessStarter activity in a process. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50042 0	Failed to process the event from the ProcessStarter activity [{0}]	BWEngine failed to process the new events from the ProcessStarter activity. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-	Failed to execute an event from the ProcessStarter activity due to	This error message is reported when the output data generated by the ProcessStarter

Error Codes	Error Message	Error Resolution
CORE-50042 2	activity output data validation error. The output data from ProcessStarter activity [{0}] does not conform to the ProcessStarter activity output schema. Validation error details: {1}.	activity does not comply with the output schema of the ProcessStarter activity. This error can occur if ProcessStarter activity is not implemented correctly to generate the valid output data.
TIBC O-BW- CORE- 50042 4	The BWEngine is unable accept new events from the ProcessStarter activity [{0}], in process [{1}], module [{2}] since the ProcessStarter is in the stopped state. When the ProcessStarter is in the stopped state, the BWEngine cannot accept new events.	The ProcessStarter generated new events when it is in the stopped state. A ProcessStarter must not generate new events during the stopped state and it can be considered as ProcessStarter activity implementation error. The ProcessStarter is in the stopped state once the BWEngine invokes the ProcessStarter operation "com.tibco.bw.runtime.EventSource.stop" or before the invocation of the ProcessStarter operation "com.tibco.bw.runtime.EventSource.start".
TIBC O-BW- CORE- 50060 2	The model or the runtime class for the activity [{0}] in process [{1}], module [{2}] is implemented incorrectly. The activity model class [{3}] does not contain the configuration property [{4}] as defined in the annotation for the member variable [{5}] declared in the activity runtime class [{6}].	This error message is generated if the BW activity is not implemented correctly. Ensure that the BW activity model class contains the required attribute or property.
TIBC O-BW- CORE- 50060 3	The model or the runtime class for the activity [{0}] in process [{1}], module [{2}] is implemented incorrectly. The activity model [{3}] does not contain the attribute [{4}] as defined in the annotation for	The resolution is not applicable. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
	<p>the member variable [{5}] declared in the activity runtime class [{6}]. The attribute must be one of the following that is specified in the activity model [{7}]</p>	
TIBC O-BW- CORE- 50060 4	<p>The model or runtime class for the activity [{0}] in process [{1}], module [{2}] is implemented incorrectly. The activity model class [{3}] associated with the activity runtime class [{4}] has a configuration property, which is of unsupported data type. The activity configuration property data type [{5}] is not supported.</p>	<p>This error message is generated if the BW activity is not implemented correctly. Ensure that the BW activity model class contains the property of a supported data type.</p>
TIBC O-BW- CORE- 50060 5	<p>The model or runtime class for the activity [{0}] in process [{1}], module [{2}] is implemented incorrectly. Unable to set member variable [{3}] declared in the activity runtime class [{4}]. Encountered an exception [{5}].</p>	<p>This error message is generated if the BW activity is not implemented correctly. Ensure that the BW activity runtime class member variable is defined correctly.</p>
TIBC O-BW- CORE- 50060 6	<p>The resource specified for the process property [{0}] in process [{1}], module [{2}] is not available in the runtime environment. This process property is used by the activity [{3}] in process [{4}]. Ensure that the resource is configured and installed correctly.</p>	<p>A resource assigned to the process property is not accessible or resolvable at runtime. Ensure that the process property is configured correctly and the required resource is resolvable at runtime.</p>
TIBC O-BW-	<p>The process property [{0}] in process [{1}], module [{2}] has an</p>	<p>The process property is configured with an incorrect value. Ensure that the process</p>

Error Codes	Error Message	Error Resolution
CORE-500607	incorrect value [{3}]. This process property is used by the activity [{4}] in process [{5}]. For DateTime, ensure that the value has the format [{6}].	property is configured correctly, specially for a DateTime data type.
TIBC O-BW-CORE-500608	The resource obtained from the framework for the process property [{0}] in process [{1}], module [{2}] is not compatible with the data type of the process property. Encountered an exception [{3}].	The value assigned to the process property did resolve to the data type excepted by the process property. Ensure that the process property contains the correct value or the module property assigned to the process property contains the correct value.
TIBC O-BW-CORE-500610	One or more required fields of the activity [{0}] in process [{1}], module [{2}] is not configured correctly. Ensure that the required fields of the activity contain valid data.	The activity is not configured correctly. Ensure that the all required fields for the activity at design time are populated correctly.
TIBC O-BW-CORE-500612	Failed to create the activity [{0}] in process [{1}], module [{2}] due to an exception [{3}]	Unexpected error occurred when attempting to create an instance of an activity. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-500614	Failed to create the activity [{0}] in process [{1}], module [{2}] due to an unexpected exception [{3}]	The resolution is not applicable. Contact TIBCO Support.
TIBC O-BW-CORE-50061	Failed to initialize the activity [{0}] in process [{1}], module [{2}] due to activity lifecycle error	Error occurred when attempting to initialize an instance of an activity. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this

Error Codes	Error Message	Error Resolution
6		error message.
TIBC O-BW- CORE- 50061 8	Failed to initialize the activity [{0}] in process [{1}], module [{2}] due to an unexpected activity lifecycle error	Unexpected error occurred when attempting to initialize an instance of an activity. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50062 0	The execute operation for the activity [{0}] in process [{1}] failed with an unexpected exception [{2}]	The activity execution failed and raised an unexpected exception. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50062 2	The post-execute operation for the asynchronous activity [{0}] in process [{1}] failed with an unexpected exception [{2}]	The post-execute operation for an asynchronous activity failed and raised an unexpected exception. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50062 4	The cancel operation for the activity [{0}] in process [{1}], module [{2}] failed with an unexpected exception [{3}]	The cancel operation for an asynchronous activity failed and raised an unexpected exception. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW- CORE- 50062 6	BWEngine was unable to execute the cancel operation for the activity [{1}] in process [{2}], module [{3}] due to an exception [{4}]	BWEngine encountered an error when attempting to run the cancel operation for the activity. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC	The destroy operation for the	The destroy operation for an activity failed and

Error Codes	Error Message	Error Resolution
O-BW-CORE-500628	activity [{0}] in process [{1}], module [{2}] failed with an unexpected exception [{3}]	raised an unexpected exception. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-500630	The process property [{0}] is not defined in the BW Process [{1}]	Unable to resolve the specified process property. Ensure that this process property is correctly defined in the BW Process.
TIBC O-BW-CORE-500631	The process property [{0}] has not been registered with the activity context or the event source context.	The specified process property has not been correctly registered with the activity context. This error can occur if the BW activity is not implemented correctly to register the process property via the method [com.tibco.bw.runtime.ActivityContext.registerProcessProperty].
TIBC O-BW-CORE-500632	Failed to resolve process property [{0}] from the BW Process [{1}]	Failed to resolve the specified process property. Ensure that the specified process property is defined in the process. For more details, refer to the additional exception message in the cause.
TIBC O-BW-CORE-500633	The module property [{0}] is not defined in the BW Module [{1}]{2}]	Unable to resolve the specified module property. Ensure that this module property is correctly defined in the BW Module.
TIBC O-BW-CORE-500634	The module property [{0}] has not been registered with the activity context or the event source context.	The specified module property has not been correctly registered with the activity context. This error can occur if the BW activity is not implemented correctly to register the module property via the method

Error Codes	Error Message	Error Resolution
TIBC O-BW- CORE- 50063 5	Failed to resolve module property <code>[[{0}]]</code> from the BW Module <code>[[{1}]:{2}]</code>	[com.tibco.bw.runtime.ActivityContext.registerModuleProperty].
TIBC O-BW- CORE- 50063 6	Activity <code>[[{0}]]</code> timed out.	The activity wait or execution time has exceeded the timeout value specified for the activity.
TIBC O-BW- CORE- 50063 8	Activity input data validation error. The input data for activity <code>[[{0}]]</code> in process <code>[[{1}]]</code> , module <code>[[{2}]]</code> does not conform to the activity input schema. <code>{3} {4}</code>	This error message is reported when the data that is provided as an input to the activity does not comply with the input schema of the activity. This error can occur if the previous activity in the process generated incorrect data or the activity input XSLT transformation generated data that does not comply with the input schema of the activity.
TIBC O-BW- CORE- 50064 0	Activity output data validation error. The output data from activity <code>[[{0}]]</code> in process <code>[[{1}]]</code> , module <code>[[{2}]]</code> does not conform to the activity output schema. <code>{3} {4}</code>	This error message is reported when the output data generated by the activity does not comply with the output schema of the activity. Some activities can generate in-compliant output if it receives incorrect data from the external entity it is interacting. In these scenarios, ensure that the external entity provides or returns the correct data expected by the activity.
TIBC	Activity input/output data	This error message is reported when the data

Error Codes	Error Message	Error Resolution
O-BW-CORE-50064 1	validation error. The input/output data for activity [{0}] in process [{1}], module [{2}] does not conform to the activity input/output schema. {3} {4}	that is provided as an input to the activity or the output data generated by the activity does not comply with the output schema of the activity.
TIBC O-BW-CORE-50064 2	Unable to obtain activity input data. The BWEngine has not been initialized or started.	This error message is reported when an entity such as the event subscriber attempts to obtain an activity input data before the BWEngine has been initialized or started. Ensure that the BWEngine has started before performing this operation.
TIBC O-BW-CORE-50064 3	Unable to obtain activity input data. The specified ActivityEvent object is invalid. The ActivityEvent cannot be null.	This error message is reported when an entity such as the event subscriber attempts to obtain an activity input data; however the specified ActivityEvent (com.tibco.bw.runtime.event.ActivityAuditEvent) object is invalid or null. Ensure that the ActivityEvent object is valid.
TIBC O-BW-CORE-50064 4	Unable to obtain activity input data due to an exception [{0}]	Unexpected error occurred when an entity such as the event subscriber is attempting to obtain activity input data. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-50064 5	Unable to obtain activity output data. The BWEngine has not been initialized or started.	This error message is reported when an entity such as the event subscriber attempts to obtain an activity output data before the BWEngine has been initialized or started. Ensure that the BWEngine has started before performing this operation.
TIBC	Unable to obtain activity output	This error message is reported when an entity

Error Codes	Error Message	Error Resolution
O-BW-CORE-500646	data. The specified ActivityEvent object is invalid. The ActivityEvent cannot be null.	such as the event subscriber attempts to obtain an activity output data; however the specified ActivityEvent (com.tibco.bw.runtime.event.ActivityAuditEvent) object is invalid or null. Ensure that the ActivityEvent object is valid.
TIBC O-BW-CORE-500647	Unable to obtain activity output data due to an exception [{0}]	Unexpected error occurred when an entity such as the event subscriber is attempting to obtain activity output data. For more details, refer to the additional exception message or the "CausedBy" statements reported as part of this error message.
TIBC O-BW-CORE-500648	Unable to obtain XPath functions associated with the BusinessWorks Activity, encountered an exception [{0}]	Error was encountered when attempting to obtain the list of XPath functions associated with the BW Activity.
TIBC O-BW-CORE-500705	Unable to find process information for process [{0}] in module ModuleName={1}, ModuleVersion={2}.	BWEngine is not able to obtain process information for the specified BW process. Ensure that the BW Module contains the required process.

Design Time Error Codes

This section describes the error messages that can be reported at design time.

Error Codes	Error Message	Error Resolution
TIBCO-BW-DT-VALIDATION-	Cyclic reference detected in process {0}. Reference {1}	Inspect the reference binding on the process. BWEngine does not support

Error Codes	Error Message	Error Resolution
500023	points to {2}. This might cause the application to reach an impaired state at runtime.	references that point to the same process. This reference needs to be removed. Point to another process/sub process to correct this.
TIBCO-BW-DT-VALIDATION-500024	One or more sources mapped for activity {0} contain invalid references.	Delete existing links and create links again before deploying to runtime.
TIBCO-BW-DT-VALIDATION-500025	Process configuration error. The variable with the name [{0}] is no longer being referenced in the process [{1}].	Remove this variable or quick fix.
TIBCO-BW-DT-VALIDATION-500026	External Shared Module error. The Module [{0}] is out of sync. It is not present on the current Target Definition.	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-DT-VALIDATION-500027	Folder: " {0} " contains special characters.	Replace the special characters with alphanumeric characters, "-", "_", or whitespaces.
BW_VALIDATION_MODULE_VERSION_CONFIG_ERROR-500620	The Bundle-Version of the BusinessWorks module [{0}] must end with .qualifier in the manifest file [META-INF/MANIFEST.MF]	The resolution is not applicable. Contact TIBCO Support.
APPLICATION_MANIFEST_VERSION_ERROR-501005	The Bundle-Version of the Application [{0}] must end with .qualifier in the manifest file [META-INF/MANIFEST.MF].	The resolution is not applicable. Contact TIBCO Support.

Palettes

This section describes the error messages that can be reported by the activities or entities associated with palettes.

File Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the File palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-FILE-000001	{0}	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-FILE-100001	{0}	This is a trace message and the resolution is not applicable.
TIBCO-BW-PALETTE-FILE-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-FILE-300001	{0}	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-FILE-400001	{0}	This is a warning message and it highlights situations that may affect the activity execution.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-FILE-500000	File name [{0}] is not valid.	Ensure that the file name must not be an empty or null string.
TIBCO-BW-PALETTE-FILE-500001	File [{0}] was not found.	Ensure that the file indicated by fileName exists at the given location.
TIBCO-BW-PALETTE-FILE-500002	File [{0}] already exists.	Ensure that the Overwrite checkbox in the general tab is checked or delete the existing file.
TIBCO-BW-PALETTE-FILE-500003	An exception [{0}] occurred when attempting to write to the file [{1}].	Ensure that the file name is valid and the access permissions are set appropriately.
TIBCO-BW-PALETTE-FILE-500004	Unable to create file [{0}] due to file or directory denoted by the pathname [{1}] does not exist.	Ensure that the createNonExistingDirectory option in the general tab is checked.
TIBCO-BW-PALETTE-FILE-500005	Cannot read the binary content from the file [{0}].	Ensure that the file name is valid and the access permissions are set appropriately.
TIBCO-BW-PALETTE-FILE-500006	Cannot read the string content from the file [{0}].	Ensure that the file name is valid and the access permissions are set appropriately.
TIBCO-BW-PALETTE-FILE-500007	The file encoding [{0}] is not valid.	Ensure that the encoding provided is valid.
TIBCO-BW-PALETTE-FILE-500009	Unable to rename the file from [{0}] to file [{1}].	Ensure that the file or directory name is valid and the access permissions are set appropriately.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-FILE-500010	Unable to rename the file from <code>[[{0}]]</code> to file <code>[[{1}]]</code> . The destination file exists and its type is different than the type of the source file.	Ensure that the source file and destination file are both of the same type.
TIBCO-BW-PALETTE-FILE-500011	The file activity <code>[[{0}]]</code> cannot be used to move a directory.	Ensure that the directories cannot be moved unless they have the same parent directory.
TIBCO-BW-PALETTE-FILE-500012	Cannot remove the file <code>[[{0}]]</code> .	Ensure that the file or directory name is valid and the access permissions are set appropriately.
TIBCO-BW-PALETTE-FILE-500013	An exception <code>[[{0}]]</code> occurred when attempting to create the file <code>[[{1}]]</code> .	Ensure that the file or directory name is valid and the access permissions are set appropriately.
TIBCO-BW-PALETTE-FILE-500014	Cannot overwrite the file <code>[[{0}]]</code> to file <code>[[{1}]]</code> , when the overwrite flag is not selected in the activity configuration.	Ensure that the Overwrite checkbox on the general tab is selected or delete the existing file explicitly.
TIBCO-BW-PALETTE-FILE-500015	Cannot copy a directory <code>[[{0}]]</code> to an existing file <code>[[{1}]]</code> .	Ensure that the source should not be a directory when the destination exists and is a file.
TIBCO-BW-PALETTE-FILE-500016	Cannot copy multiple files <code>[[{0}]]</code> to an existing file <code>[[{1}]]</code> .	Ensure that when using a pattern in source it should not match with multiple files to copy into a single destination file.
TIBCO-BW-PALETTE-FILE-500017	Cannot create missing path <code>[[{0}]]</code> .	Ensure that the <code>createNonExistingDirectory</code> in the general tab is checked.
TIBCO-BW-PALETTE-	Cannot copy from file <code>[[{0}]]</code> to file <code>[[{1}]]</code> .	Ensure that the file or directory name is valid and the access

Error Codes	Error Message	Error Resolution
FILE-500018		permissions are set appropriately.
TIBCO-BW-PALETTE-FILE-500019	The file name value provided for the activity input is empty or null.	Ensure that the fileName must not be an empty or null string.
TIBCO-BW-PALETTE-FILE-500020	File [{0}] was not found due to fault [{1}].	Ensure that the file indicated by fileName exists at the given location.
TIBCO-BW-PALETTE-FILE-500502	The ProcessStarter activity [{0}] failed to generate a new event due to an exception [{1}].	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-FILE-500021	The File Poller ProcessStarter activity [{0}] failed to generate a new event due to an exception [{1}] since it is in the stopped state.	This is an internal product error. Contact TIBCO Support.

FTP Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the FTP palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-FTP-500003	Unable to establish FTP connection for the FTP function [{0}]. Encountered error [{1}].	Ensure that FTP connection parameters are set properly.
TIBCO-BW-PALETTE-FTP-500004	File [{0}] already exists.	Ensure that the Overwrite Existing File checkbox is checked or delete the file on the server.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-FTP-500005	Error in PUT or MPUT command.	Error in PUT or MPUT command. See Fault Tab for details.
TIBCO-BW-PALETTE-FTP-500006	Error in GET or MGET command.	Error in GET or MGET command. See Fault Tab for details.
TIBCO-BW-PALETTE-FTP-500008	Client is not initialized [{0}].	Contact TIBCO Support.
TIBCO-BW-PALETTE-FTP-500010	Error in PUT or MPUT command. Local file specified cannot be found [{0}].	Ensure that the local file is specified for the PUT or MPUT command.
TIBCO-BW-PALETTE-FTP-500012	Unexpected reply code. Returned Code [{0}]. Expected Code [{1}].	Contact TIBCO Support.
TIBCO-BW-PALETTE-FTP-500013	Invalid username or password.	Ensure that the username or password is valid.
TIBCO-BW-PALETTE-FTP-500014	Error in executing remote command [{0}].	Contact TIBCO Support.
TIBCO-BW-PALETTE-FTP-500019	FTP Connection Test Failed. Encountered error [{0}].	Ensure that the username or password is valid.
TIBCO-BW-PALETTE-FTP-500020	File [{0}] does not exist.	Ensure that the file exists at a given location.
TIBCO-BW-	Error establishing active data socket.	Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
PALETTE-FTP-500022	Reason [{0}].	
TIBCO-BW-PALETTE-FTP-500024	Error performing MGET. Reason: MGET is not supported for FTP via Proxy	Contact TIBCO Support.
TIBCO-BW-PALETTE-FTP-500025	Error in PUT or MPUT command.Error:[{0}].	Error in PUT or MPUT command. See Fault Tab for details.
TIBCO-BW-PALETTE-FTP-500026	Error in GET or MGET command.Error:[{0}].	Error in GET or MGET command. See Fault Tab for details.

General Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the General Activities palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-GENERALACTIVITIES-VALIDATION-500001	Activity configuration error. The end time must be greater than start time for Timer activity [{0}] in the process [{1}].	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-GENERALACTIVITIES-000001	The Timer ProcessStarter activity [{0}] failed to generate a new event due to exception [{1}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-GENERALACTIVITIES-100001	{0}	This is a trace message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-GENERALACTIVITIES-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-GENERALACTIVITIES-300001	{0}	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-GENERALACTIVITIES-400001	{0}	This is a warning message and it highlights situations that may affect the activity execution.
TIBCO-BW-PALETTE-GENERALACTIVITIES-500000	Error executing external command [{0}]: [{1}].	Ensure that the activity is configured correctly.
TIBCO-BW-PALETTE-GENERALACTIVITIES-500001	Error accessing file or directory [{0}]: [{1}].	Ensure that the file or directory name is valid and the access permissions are set appropriately.
TIBCO-BW-PALETTE-GENERALACTIVITIES-500002	No command specified.	Ensure that the specified field in the activity input is configured with the correct data.
TIBCO-BW-PALETTE-GENERALACTIVITIES-500003	Input data error in field [{0}] expecting a valid [{1}]	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-GENERALACTIVITIES-500004	Sleep interval value [{0}] is not valid.	Ensure that the sleep interval is a positive long value.
TIBCO-BW-PALETTE-	Activity configuration error. The	The resolution is not

Error Codes	Error Message	Error Resolution
GENERAL-ACTIVITIES-500001	{2} Shared Variable must be configured for {3} Shared Variable activity [{0}] in the process [{1}].	applicable. Contact TIBCO Support.

HTTP Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the HTTP palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-HTTP-000001	{0}	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-HTTP-100001	{0}	This is a trace message and the resolution is not applicable.
TIBCO-BW-PALETTE-HTTP-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-HTTP-300001	{0}	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-HTTP-	{0}	This is a warning message and it highlights situations that may affect the activity execution.

Error Codes	Error Message	Error Resolution
400001	The HTTP Server replied with a <code>[[{0}]]</code> status code.	Check the status code to know the reason for the error.
TIBCO-BW-PALETTE-HTTP-500001	The HTTP Server replied with a <code>[[{0}]]</code> status code.	Check the status code to know the reason for the error.
TIBCO-BW-PALETTE-HTTP-500002	The HTTP Server replied with a <code>[[{0}]]</code> status code	Check the status code to know the reason for the error.
TIBCO-BW-PALETTE-HTTP-500003	An exception was thrown while trying to initialize the HTTP client	Correct the configuration of the Send HTTP Request activity.
TIBCO-BW-PALETTE-HTTP-500004	An exception occurred while trying to initialize the HTTP server: <code>[[{0}]]</code>	Check the exception and correct the configuration of the HTTP Connector resource or the HTTP ProcessStarter.
TIBCO-BW-PALETTE-HTTP-500005	A POST Method cannot send parameters if the message body is specified	Correct the input data of the Send HTTP Request activity. Make sure that the message body is not specified when parameters are used.
TIBCO-BW-PALETTE-HTTP-500006	A GET Method does not have a message body	Correct the input data of the Send HTTP Request activity. Make sure that the message body is not specified for a GET request.
TIBCO-BW-PALETTE-	Invalid endpoint URL	Correct either the HTTP client configuration or the input data

Error Codes	Error Message	Error Resolution
HTTP-500007		of the Send HTTP Request activity.
TIBCO-BW-PALETTE-HTTP-500008	Invalid input data. The encoding is not supported	Correct the input data. Make sure that the encoding is supported. See the documentation.
TIBCO-BW-PALETTE-HTTP-500009	The HTTP method [{0}] is not valid	Correct the input data of the Send HTTP Request activity. Make sure that the HTTP method is valid.
TIBCO-BW-PALETTE-HTTP-500010	An exception was thrown while trying to url-encode the data	Correct the input data. See the documentation.
TIBCO-BW-PALETTE-HTTP-500011	Attachment not supported for the HTTP method [{0}]. Only HTTP 'POST' can send attachments	Check the input of the Send HTTP Request activity. Only the POST method can send attachments.
TIBCO-BW-PALETTE-HTTP-500012	Error serializing attachment data, Cause: [{0}]	Check the exception and correct the attachment data.
TIBCO-BW-PALETTE-HTTP-500013	An IOException was thrown while trying to execute the HTTP method	System exception.
TIBCO-BW-PALETTE-HTTP-	An exception was thrown while trying to execute the HTTP method. The Reason-code is [{0}]	System exception.

Error Codes	Error Message	Error Resolution
500014		
TIBCO-BW-PALETTE-HTTP-500015	An IOException was thrown while trying to read the response	System exception.
TIBCO-BW-PALETTE-HTTP-500016	An IOException was thrown while trying to send the response	System exception.
TIBCO-BW-PALETTE-HTTP-500017	An Exception was thrown while trying to send the response	System exception.
TIBCO-BW-PALETTE-HTTP-500019	The header <code>[[{0}]]</code> is defined as a non-repeating Header in Input Headers. This header cannot have multiple occurrences in DynamicHeaders.	Correct the input data.
TIBCO-BW-PALETTE-HTTP-500020	The HTTP ProcessStarter <code>[[{0}]]</code> failed to generate a new event due to exception <code>[[{1}]]</code>	Check the exception and correct the configuration of the HTTP connector or HTTP receiver.
TIBCO-BW-PALETTE-HTTP-500021	Failed to reply to the HTTP ProcessStarter activity. This error can occur if the HTTP Response activity is executed after recovering from a check-pointed BusinessWorks process instance.	Check that point activity should not be placed between the HTTP ProcessStarter and Send HTTP Response activity.
TIBCO-BW-PALETTE-HTTP-	Failed to authenticate request. Username and Password are not set.	Check if the identity resource referenced in the HTTP Client resource contains a username

Error Codes	Error Message	Error Resolution
500022		and password.
TIBCO-BW-PALETTE-HTTP-500022	Failed to authenticate request.	Check if the LDAP resource is configured on the HTTP Connector resource.
TIBCO-BW-PALETTE-HTTP-500023	Value not specified for the DynamicHeader <code>[[{0}]]</code> .	Correct the input data.
TIBCO-BW-PALETTE-HTTP-500024	Reply For field cannot be blank.	Select a value for the Reply For field in the Send HTTP Response activity.
TIBCO-BW-PALETTE-HTTP-500025	The circuit-breaker is open now and can short-circuit all the requests.	Check the circuit-breaker configuration and try again.

Java Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the Java palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JAVA-PROCESSSTARTER-000001	<code>[[{0}]]</code>	The resolution is not applicable. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JAVA-PROCESSSTARTER-100001	[{}]	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JAVA-PROCESSSTARTER-200001	[{}]	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JAVA-PROCESSSTARTER-300001	[{}]	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JAVA-PROCESSSTARTER-400001	[{}]	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JAVA-PROCESSSTARTER-500001	The JAVA ProcessStarter activity [{}] failed to generate a new event due to an exception [{}]	Ensure that the correct object is passed to the 'onEvent' method in the specified Java class. Refer to the declared class implementation for details.
TIBCO-BW-PALETTE-JAVA-PROCESSSTARTER-500002	Illegal onEvent(Object output)/onError(Throwable throwable) method call. OnEvent/OnError method must not be called in the <code>init</code> method or during the initialization phase.	Remove the <code>onEvent(Object output)</code> method call in the <code>init</code> method.
TIBCO-BW-PALETTE-JAVA-PROCESSSTARTER-500003	The JAVA ProcessStarter activity [{}] failed to generate a new event due to an exception [{}] since it is in the stopped state.	Ensure that the ProcessStarter has been stopped properly.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JAVA-000001	[[0]]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-JAVA-100001	[[0]]	This is a trace message and the resolution is not applicable.
TIBCO-BW-PALETTE-JAVA-200001	[[0]]	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JAVA-300001	[[0]]	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-JAVA-400001	[[0]]	This is a warning message and it highlights situations that may affect the activity execution.
TIBCO-BW-PALETTE-JAVA-501005	Internal error occurred. Class=[[0]], Method=[[1]], Cause=[[2]]	Make sure that the Java Global Instance resource has been properly referenced.
TIBCO-BW-PALETTE-JAVA-500504	Input data error in field [[0]] because [[1]].	Ensure that the correct values are provided for the method parameter elements that are in the activity input tab.
TIBCO-BW-PALETTE-JAVA-500604	Output data error in field [[0]] because [[1]].	Ensure that the getter methods are returning the correct values to display the activity output tab.
TIBCO-BW-PALETTE-JAVA-500605	Output data error in the field [[0]] value cannot be null.	Ensure that the getter methods are not returning null to display the activity output tab.
TIBCO-BW-PALETTE-	Output data error in the field [[0]]	Ensure that the getter method

Error Codes	Error Message	Error Resolution
JAVA-500606	value is not serializable.	returns a serializable Java class to display the activity output tab.
TIBCO-BW-PALETTE-JAVA-500001	While executing method [{0}], encountered an exception [{1}] [{2}].	Correct the error stated in the exception message and retry.
TIBCO-BW-PALETTE-JAVA-500013	Activity input data conversion error. Exception [{0}] occurred while trying to render the activity input data. [{1}]	Incorrect object reference was specified for the declared Java class. Ensure that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity.
TIBCO-BW-PALETTE-JAVA-500014	Activity output data conversion error. Exception [{0}] occurred while trying to create the activity output data. [{1}]	Ensure that the unsupported data types are not utilized or referenced in your Java class.
TIBCO-BW-PALETTE-JAVA-500017	The Java class [{0}] is not found in the classpath. Encountered ClassNotFoundException [{1}].	Ensure that the specified class file is contained in the classpath.
TIBCO-BW-PALETTE-JAVA-500019	Activity input error. The activity received an incorrect value for the method parameters. IllegalArgumentException occurred while trying to construct an instance of the Java class [{0}]: [{1}]	Ensure that the correct values are provided for the constructor parameter elements that are in the activity input tab.
TIBCO-BW-PALETTE-JAVA-500020	Unable to construct an instance of the Java class [{0}]. Encountered an exception [{1}] [{2}].	Correct the error stated in the exception message and retry.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JAVA-500021	The constructor for the Java class <code>[[0]]</code> raised an exception <code>[[1]]</code> . <code>[[2]]</code>	The exception was raised by the constructor of the declared Java class. Refer to the Java class implementation for details.
TIBCO-BW-PALETTE-JAVA-500026	Unable to obtain information for the method <code>[[0]]</code> from the class <code>[[1]]</code> . Encountered <code>NoSuchMethodException</code> <code>[[2]]</code> .	Reconfigure this activity or verify that the declared Java class has not changed since the last configuration.
TIBCO-BW-PALETTE-JAVA-500027	Unable to obtain information for the method <code>[[0]]</code> from the class <code>[[1]]</code> . Encountered <code>SecurityException</code> <code>[[2]]</code> .	Correct the error stated in the exception message and retry.
TIBCO-BW-PALETTE-JAVA-500031	Activity input error. The activity received an incorrect value for the method parameters. When attempting to invoke the method <code>[[0]]</code> , encountered <code>IllegalArgumentException</code> <code>[[1]]</code> .	Ensure that the correct values are provided for the method parameter elements that are in the activity input tab.
TIBCO-BW-PALETTE-JAVA-500032	Activity input error. The activity received an incorrect Java object for the declared Java class <code>[[0]]</code> . The activity required an instance of the Java class <code>[[1]]</code> , but received an instance of the Java class <code>[[2]]</code> : <code>[[3]]</code>	Ensure that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. Ensure that the classpath refers to the correct declared class.
TIBCO-BW-PALETTE-JAVA-500033	Activity input error. The activity received an incorrect Java object for the declared Java class <code>[[0]]</code> . The Java object received is not compatible with the Java object required by this activity. The activity required an instance of	Ensure that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. Ensure that the classpath refers to the correct declared class.

Error Codes	Error Message	Error Resolution
	the Java class [{1}]: [{2}]	
TIBCO-BW-PALETTE-JAVA-500034	Activity input error. The activity received 'null' value for the declared Java class. The activity required an instance of the class [{0}], but received a 'null'.	Ensure that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. The preceding activity that provides the input value for this activity should not produce a null for its output.
TIBCO-BW-PALETTE-JAVA-500035	Unable to invoke the method [{0}]. Encountered an exception [{1}] [{2}].	Correct the error stated in the exception message and retry.
TIBCO-BW-PALETTE-JAVA-500036	Unable to invoke the cleanup method [{0}]. Encountered an exception [{1}] [{2}].	Correct the error stated in the exception message and retry.
TIBCO-BW-PALETTE-JAVA-500037	The method [{0}] raised an exception [{1}]. [{2}].	The exception was raised by the method of the specified Java class. Refer to the declared class implementation for details.
TIBCO-BW-PALETTE-JAVA-500038	The cleanup method [{0}] raised an exception [{1}]. [{2}].	The exception was raised by the method of the specified Java class. Refer to the declared class implementation for details.
TIBCO-BW-PALETTE-JAVA-500042	Activity input error. The activity required an instance of class [{0}], but received a 'null' value for the declared Java class.	Ensure that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. The preceding activity that provides the input value for this activity should not produce a null for its output.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JAVA-500043	Activity input error. The activity received an incorrect Java object for the declared Java class. The activity required an instance of a class <code>[[0]]</code> , but received an instance of a class <code>[[1]]</code> .	Ensure that the correct Java object reference is provided for the declared Java class element shown in the input tab of this activity. Ensure that the classpath refers to the correct declared class.
TIBCO-BW-PALETTE-JAVA-500046	Data Conversion error. When attempting to convert Java object to XML data, encountered an exception <code>[[0]]</code> .	Ensure that the unsupported data types are not utilized or referenced in your Java class.
TIBCO-BW-PALETTE-JAVA-500047	Data Conversion error. When attempting to convert XML data to a Java object, encountered an exception <code>[[0]]</code> .	Ensure that the unsupported data types are not utilized or referenced in your Java class.
TIBCO-BW-PALETTE-JAVA-500063	Runtime error. Illegal <code>onEvent</code> (Object output)/ <code>onError</code> (Throwable error) method call. <code>OnEvent/OnError</code> method must not be called in the <code>init</code> method or during the initialization phase.	Remove the <code>onEvent</code> (Object output) method call in the <code>init</code> method.
TIBCO-BW-PALETTE-JAVA-500065	Runtime error. The output type defined by the <code>getOutputObjectType()</code> does not match with the type that is passed in to <code>onEvent(Object object)</code> .	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JAVA-500064	The Java Process Starter <code>onStop</code> method <code>[[0]]</code> raised an exception <code>[[1]]</code> . <code>[[2]]</code> .	The exception was raised by the <code>onStop</code> method of the specified Java class. Refer to the declared class implementation for details.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JAVA-500066	The Java Process Starter onShutdown method [{0}] raised an exception [{1}]. [{2}].	The exception was raised by the 'onShutdown' method of the specified Java class. Refer to the declared class implementation for details.
TIBCO-BW-PALETTE-JAVA-501067	Internal error occurred while loading the Class=[{0}], Cause=[{1}]	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JAVA-501069	Internal error occurred. Method=[{0}] references a Class=[{1}] no longer exists. Cause=[{2}]	Make sure that the Class referenced in the method is valid.
TIBCO-BW-PALETTE-JAVA-500070	Activity input error. The activity does not receive proper input.	Ensure that the input content is not empty.
TIBCO-BW-PALETTE-JAVA-500071	Unable to obtain information for the method [{0}] from the class [{1}].	Reconfigure this activity or verify that the declared Java class has not changed since the last configuration.

JDBC Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the JDBC palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JDBC-000001	The JDBC activity [{0}] is NOT part of a JDBC Transaction Group. However, the activity references the same shared resource as used in the group	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-	The JDBC activity [{0}] is the first activity in the	This is a debug message

Error Codes	Error Message	Error Resolution
PALETTE-JDBC-200001	JDBC Transaction.	and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200002	JDBC activity [{0}] initialized successfully.	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200003	JDBC activity [{0}] task submitted to Threadpool for execution	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200004	Executing SQL Statement [{0}] for activity [{1}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200005	Connection received from Datasource for activity [{0}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200006	Parameters set for activity [{0}] with SQL statement [{1}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200007	Output for activity [{0}] is [{1}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-	Executing an SQL Statement for activity [{0}].	This is a debug message and the resolution is not

Error Codes	Error Message	Error Resolution
JDBC-200008		applicable.
TIBCO-BW-PALETTE-JDBC-200009	Executing Prepared Statement for activity [{0}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200010	Successfully executed SQL statement [{0}] for activity [{1}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200011	Last subset reached for activity [{0}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200012	Process in subset output for activity [{0}] with noofRecords [{1}] is [{2}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200013	All parameters set successfully on Statement for activity [{0}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-200014	Number of updates for JDBC Update activity is [{0}].	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-JDBC-	Number of updates for JDBC Update activity is 0. Executing Insert Statement [{0}] since the activity is in Upsert mode.	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
200015		
TIBCO-BW-PALETTE-JDBC-500001	Batch updates failed on update number [{0}].	Check the activity configuration and if the database is up.
TIBCO-BW-PALETTE-JDBC-500002	Invalid procedure name specified. Procedure name cannot be null.	Check the activity configuration procedure name field.
TIBCO-BW-PALETTE-JDBC-500003	{0} input parameters declared in the SQL statement but no input parameters provided.	Check the activity configuration prepared parameters table.
TIBCO-BW-PALETTE-JDBC-500004	Duplicate field name [{0}] found. Modify the query and create unique aliases for duplicate fields.	Modify the query and create unique aliases for duplicate fields.
TIBCO-BW-PALETTE-JDBC-500005	Improper SQL statement used. {0}	Check the syntax of the SQL Statement specified.
TIBCO-BW-PALETTE-JDBC-500006	Exception occurred when attempting to create a JDBC connection for the JDBC transaction.	Check the Shared Resource configuration that is configured with this activity and also that the database is running.
TIBCO-BW-PALETTE-JDBC-	Missing Input Value for required Column [{0}].	Check the input tab of the activity and set the column value

Error Codes	Error Message	Error Resolution
500007		
TIBCO-BW-PALETTE-JDBC-500009	SQL Exception occurred (SQL STATE = {0}) - detailMessage - {1}	Check the activity configuration and the state of the database that the activity is connected to.
TIBCO-BW-PALETTE-JDBC-500010	{0} is not a valid timezone.	Check the activity configuration input tab and enter a valid timezone
TIBCO-BW-PALETTE-JDBC-500011	Could not create connection to server using Shared Resource [{0}].	Check the JDBC Connection Shared Resource configuration that is configured on the activity.
TIBCO-BW-PALETTE-JDBC-500012	INVALID_JDBC_ACTIVITY_CONFIGURATION = Invalid Activity Configuration. Missing required configuration Field [{0}] in activity [{1}]	Check the activity configuration and enter values for missing fields specified in the message.
TIBCO-BW-PALETTE-JDBC-500013	INVALID_SQL_STATEMENT = Invalid Activity Configuration. Invalid SQL Statement [{0}] in activity [{1}] expected a statement with [{2}]	Check the activity configuration for the SQL statement syntax.
TIBCO-BW-PALETTE-JDBC-500014	PREPARED_PARAMETERS_MORE_THAN_QUESTION_MARKS = Invalid Activity Configuration. Number of Prepared parameters in activity configuration exceed number of '?' in SQL Statement	Check the activity configuration for the Prepared parameters specified.
TIBCO-BW-PALETTE-JDBC-	PREPARED_PARAMETERS_LESS_THAN_QUESTION_MARKS = Invalid Activity Configuration. Number of Prepared parameters	Check the activity configuration for the Prepared parameters

Error Codes	Error Message	Error Resolution
500015	in the activity configuration is less than the number of '?' in SQL Statement	specified.
TIBCO-BW-PALETTE-JDBC-500016	BATCH_UPDATE_WITHOUT_PREPARED_PARAMS = Batch Update mode works only with Prepared statements	Check the SQL statement in the activity configuration to ensure that it is a SQL statement with prepared parameters.
TIBCO-BW-PALETTE-JDBC-500019	JDBC Connection login timed out.	Check the configuration details or increase the login timeout.

JMS Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the JMS palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JMS-000001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JMS-100001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JMS-200001	{0}	The resolution is not applicable. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JMS-300001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JMS-400001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-JMS-500001	Invalid configuration data. JMS connection reference is not specified.	Check activity configuration for JMS Connection Reference.
TIBCO-BW-PALETTE-JMS-500002	Invalid configuration data. Specified connection reference is not found in repository. {0}	Check activity configuration for JMS Connection Reference.
TIBCO-BW-PALETTE-JMS-500003	Invalid configuration data. JMS destination is not specified.	Check activity configuration for the JMS Destination field.
TIBCO-BW-PALETTE-JMS-500004	Error occurred when attempting to create Durable Subscriber	Check activity configuration for the Durable Subscription name box and if JMS server is running.
TIBCO-BW-PALETTE-JMS-500005	Failed to create connection to the JMS server. {0}	Check JMS Connection shared resource configuration and if the JMS server is running.
TIBCO-BW-PALETTE-JMS-500006	Unable to create a session to receive messages [{0}].	Check JMS Connection shared resource configuration and if the JMS server is running.
TIBCO-BW-PALETTE-JMS-500007	Unable to create a reply session/producer [{0}]	Check JMS Connection shared resource configuration and if the JMS server is running.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-JMS-500008	Unable to find destination [{0}] on JMS server	Check JMS Server if it the destination name specified in the error message exists.
TIBCO-BW-PALETTE-JMS-500009	Error occurred when attempting to create MessageConsumer	Check JMS Connection shared resource configuration and if the JMS server is running.
TIBCO-BW-PALETTE-JMS-500010	Error occurred when attempting to resolve destination [{0}]	Check JMS Connection shared resource configuration and if the JMS server is running.
TIBCO-BW-PALETTE-JMS-500011	Invalid configuration data. JMS Reply To Destination Not Specified.	Check the activity configuration and specify a value in the JMS Reply To field.
TIBCO-BW-PALETTE-JMS-500012	Error occurred when attempting to send a JMS message	Check the activity configuration, input data, JMS Connection shared resource configuration and if the JMS server is running.
TIBCO-BW-PALETTE-JMS-500013	Error occurred when attempting to receive a JMS message	Check the activity configuration, JMS Connection shared resource configuration and if the JMS server is running.
TIBCO-BW-PALETTE-JMS-500014	Error occurred when attempting to confirm a JMS message	Check the activity configuration, JMS Connection shared resource configuration and if the JMS server is running.
TIBCO-BW-PALETTE-	Failed to Reply for JMS ProcessStarter[{0}]. This error can occur if the JMSReply activity	The resolution is not applicable. Contact TIBCO

Error Codes	Error Message	Error Resolution
JMS-500015	is executed after recovering from a check-pointed BusinessWorks process instance.	Support.

Mail Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the Mail palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-MAIL-000001	{{0}}	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-MAIL-100001	{{0}}	This is a trace message and the resolution is not applicable.
TIBCO-BW-PALETTE-MAIL-200001	{{0}}	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-MAIL-300001	{{0}}	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-MAIL-	{{0}}	This is a warning message and it highlights situations that may affect the activity execution.

Error Codes	Error Message	Error Resolution
400001	Invalid input data. Reason: Error parsing input data.	Ensure that the destination addresses given are valid.
TIBCO-BW-PALETTE-MAIL-500005	Invalid input data. Reason: Error parsing input data.	Ensure that the destination addresses given are valid.
TIBCO-BW-PALETTE-MAIL-500007	Invalid input data. Reason: Both the comma and semicolon cannot be used at the same time to separate addresses: [{0}]	Ensure that both the comma and semicolon cannot be used at the same time to separate addresses.
TIBCO-BW-PALETTE-MAIL-500020	Error connecting to the mail server. Reason: unknown host - connection parameters: [{0}].	Ensure that the host provided is valid.
TIBCO-BW-PALETTE-MAIL-500033	Error building mail message. Cause: [{0}].	Ensure that the input message details are properly given.
TIBCO-BW-PALETTE-MAIL-500035	From address [{0}] is not valid.	Ensure that the From address must not be empty or null string
TIBCO-BW-PALETTE-MAIL-500036	Error sending mail message.	Ensure that the SMTP shared resource configuration is appropriately specified.
TIBCO-BW-PALETTE-MAIL-500037	The system cannot find the file specified: [{0}].	Ensure that the file exists at a given location.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-MAIL-500038	Invalid recipient address in To, CC or BCC [{0}, {1}, {2}]	Ensure recipient addresses given must be valid.
TIBCO-BW-PALETTE-MAIL-500001	Host cannot be null	Ensure that the host must not be null value.
TIBCO-BW-PALETTE-MAIL-500002	Username cannot be null when using Authentication	Ensure that the username value must not be null when using authentication.
TIBCO-BW-PALETTE-MAIL-500003	Password cannot be null when using Authentication	Ensure that the password value must not be null when using authentication.
TIBCO-BW-PALETTE-MAIL-500004	Error closing mail server connection. Cause: [{0}].	Ensure that the Mail receiver configuration is appropriately given.
TIBCO-BW-PALETTE-MAIL-500008	Mail provider for protocol [{0}] not found. Make sure that the provider jar is in java classpath.	Ensure that the mail provider jar is in java classpath.
TIBCO-BW-PALETTE-MAIL-500009	Configuration error in field [{0}] the value must be a valid Host Name.	Ensure that the host name for mail receiver must be valid.
TIBCO-BW-	Error connecting to the mail server -	Ensure that the mail server is up or

Error Codes	Error Message	Error Resolution
PALETTE-MAIL-500010	connect exception; connection parameters: [Host:{0}, Port:{1}, User:{2}].	check whether the connection parameters are properly configured.
TIBCO-BW-PALETTE-MAIL-500011	Could not connect to mail server - invalid username in field [{0}] and/or invalid password.	Ensure that the username and password provided are valid.
TIBCO-BW-PALETTE-MAIL-500012	The default mail folder was not found on mail server.	Ensure that the Mail receiver configuration is appropriately given.
TIBCO-BW-PALETTE-MAIL-500013	The INBOX mail folder was not found on mail server.	Ensure that the Mail receiver configuration is appropriately given.
TIBCO-BW-PALETTE-MAIL-500014	Error getting folder on mail server.	Ensure that the Mail receiver configuration is appropriately given.
TIBCO-BW-PALETTE-MAIL-500015	Mail is already deleted, Receive Mail activity has 'Delete Mail' turned on.	Ensure that the delete mail option on Receive Mail activity general tab is unchecked or don't use explicit confirm.
TIBCO-BW-PALETTE-MAIL-500021	Error connecting to the mail server using connection parameters: [{0}]	Ensure that the mail server is up or verify connection parameters.
TIBCO-BW-PALETTE-	Error while polling mail server: cannot open INBOX folder.	Ensure that the mail server is up or verify connection parameters.

Error Codes	Error Message	Error Resolution
MAIL-500022		
TIBCO-BW-PALETTE-MAIL-500023	Error parsing received mail.	Ensure that the Mail receiver configuration is appropriately given.
TIBCO-BW-PALETTE-MAIL-500024	Error while polling mail server: cannot close INBOX folder.	Ensure that the mail server is up or verify connection parameters.
TIBCO-BW-PALETTE-MAIL-500025	Unexpected error while polling mail server.	Ensure that the mail server is up or verify connection parameters.
TIBCO-BW-PALETTE-MAIL-500026	The Receive Mail ProcessStarter activity [{0}] failed to generate a new event due to exception [{1}] since it is in the stopped state.	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-MAIL-300001	Marking msg {0} for confirmation.	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.

Parse Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the Parse palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-PARSE-000001	{0}	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-PARSE-100001	{0}	This is a trace message and the resolution is not applicable.
TIBCO-BW-PALETTE-PARSE-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-PARSE-300001	{0}	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-PARSE-400001	{0}	This is a warning message and it highlights situations that may affect the activity execution.
TIBCO-BW-PALETTE-PARSE-500000	Cannot find data format schema resource [{0}]	Check if Data format shared resource is configured.
TIBCO-BW-PALETTE-PARSE-500001	Cannot create schema from data format schema.	Check if the schema is valid.
TIBCO-BW-	Exception in parse eval: [{0}]	An error occurred while processing, refer to

Error Codes	Error Message	Error Resolution
PALETTE-PARSE-500002		the exception thrown and correct the activity configuration or input.
TIBCO-BW-PALETTE-PARSE-500003	Line length must be > 0	Check if line length is greater than zero.
TIBCO-BW-PALETTE-PARSE-500004	Hit EOF on row [{0}] field [{1}] spanning columns [{2}] to [{3}] ... last row contents was: [{4}]	Check the configuration of number of records in input of Parse Data activity. It may be more than the records present in the file.
TIBCO-BW-PALETTE-PARSE-500005	Input type is not specified.	Check configuration of Input type on Parse Data activity. Ensure either File or String is configured.
TIBCO-BW-PALETTE-PARSE-500006	Please specify the Input type field.	Check configuration of Input type on Parse Data activity. Ensure either File or String is configured.
TIBCO-BW-PALETTE-PARSE-500007	Data format resource not specified.	Check if Data format shared resource is configured on the activity.
TIBCO-BW-PALETTE-PARSE-500008	Specify the data format resource.	Check if Data format shared resource is configured on the activity.
TIBCO-BW-PALETTE-	File [{0}] cannot be opened using encoding method [{1}]	Check the encoding configuration on Parse Data activity. Ensure encoding supported by

Error Codes	Error Message	Error Resolution
PARSE-500009		file is selected.
TIBCO-BW-PALETTE-PARSE-500011	Format Type must be selected.	Ensure that the Format type is configured on Data Format shared resource.
TIBCO-BW-PALETTE-PARSE-500012	Line is too long. Specified Line Delimiter may not match file content.	Check field offsets configuration on Data Format shared resource.
TIBCO-BW-PALETTE-PARSE-500013	There are not enough data for the number of required fields in a row.	Check field offsets configuration on Data Format shared resource.
TIBCO-BW-PALETTE-PARSE-500014	Error while parsing headers in the mime message.	Ensure that the input message has MIME headers.
TIBCO-BW-PALETTE-PARSE-500015	An I/O exception occurred while parsing SOAP payload in the root part.	Ensure that the SOAP payload is well formed and valid.
TIBCO-BW-PALETTE-PARSE-500016	An Unexpected exception occurred while parsing Message. Root cause is [{0}]	UNEXPECTED_EXCEPTION.resolution =This is an internal product error. Contact TIBCO Support
TIBCO-BW-PALETTE-PARSE-	The SOAP Message doesn't exist in the Root part.	Ensure that the input message has SOAP payload in it.

Error Codes	Error Message	Error Resolution
500017		
TIBCO-BW-PALETTE-PARSE-500018	Soap Envelope has invalid XML content.	Ensure that the SOAP payload is valid and well formed.
TIBCO-BW-PALETTE-PARSE-500019	One or more mime parts have the same Content-Id value in the Mime Message.	Ensure that in input message does not have the same content id for different mime parts.
TIBCO-BW-PALETTE-PARSE-500020	The <code>xop:Include</code> element must have an 'href' attribute.	Ensure that in the SOAP payload, the <code>xop:Include</code> element has href attribute.
TIBCO-BW-PALETTE-PARSE-500021	Content_Id header is not found in mime part of the Mime Message.	Ensure that each mime part has content-id header and corresponding value.
TIBCO-BW-PALETTE-PARSE-500022	Invalid Content Type Field in the Mime Message.	Ensure that the media type starts with 'multipart'.
TIBCO-BW-PALETTE-PARSE-500023	Boundary attribute not found in the Mime Message.	Ensure that the 'boundary' attribute is not missing in the mime header.
TIBCO-BW-PALETTE-PARSE-500024	The <code>startinfo</code> parameter is missing in the Mime Message.	Ensure that the <code>startinfo</code> attribute is present in the mime header.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-PARSE-500025	The <code>startinfo</code> parameter is not starting with 'application/soap+xml' in the Mime Message.	Ensure that the <code>startinfo</code> attribute has 'application/soap+xml' as value.
TIBCO-BW-PALETTE-PARSE-500026	Content Type header is not found in the Mime Message.	Ensure that the mime message has 'content-type' header.
TIBCO-BW-PALETTE-PARSE-500027	Media type of root part is not 'application/xop+xml' in the Mime Message.	Ensure that the root part's media type is 'application/xop+xml'
TIBCO-BW-PALETTE-PARSE-500028	'type' parameter is not present in root part of the Mime Message.	Ensure that the root part has 'type' parameter.
TIBCO-BW-PALETTE-PARSE-500029	<code>startInfo</code> parameter and <code>type</code> parameter, of root part, does not match in the Mime Message.	Ensure that the value of <code>startInfo</code> parameter and <code>type</code> parameter is the same in the root part of the Mime Message.
TIBCO-BW-PALETTE-PARSE-500030	<p>ERROR_LINE_LESS_THAN_MAX_LENGTH=Line length [{0}] is less than max Field Offset [{1}]</p> <p>ERROR_LINE_LESS_THAN_MAX_LENGTH.errorCode=500030</p> <p>ERROR_LINE_LESS_THAN_MAX_LENGTH</p>	Ensure that the Line length is not less than max Field Offset.

Error Codes	Error Message	Error Resolution
	MAX_ LENGTH.resolution	

Rendezvous Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the ActiveMatrix BusinessWorks Rendezvous palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-RV-000001	{0}	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-RV-100001	{0}	This is a trace message and the resolution is not applicable.
TIBCO-BW-PALETTE-RV-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-RV-300001	{0}	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-RV-300002	Advisory: [{0}] subject, message [{1}]	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-RV-300004	Listening on subject [{}]	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-RV-300005	Received message on subject [{}]	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-RV-300006	Not confirming message because it has already been confirmed seqno: [{}]	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-RV-300009	Sending RV request on subject [{}]	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-RV-300010	RV Listening on reply subject [{}]	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-PALETTE-RV-300011	RV Publishing Message on subject [{}]	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-RV-400001	{0}	This is a warning message and it highlights situations that may affect the activity execution.
TIBCO-BW-PALETTE-RV-400003	RV Message encoding [{0}] not supported.	This is a warning message and it highlights situations that may affect the activity execution.
TIBCO-BW-PALETTE-RV-500001	Error in sending message	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-RV-500002	Error serializing the message	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-RV-500004	Error in processing event: [{0}]	Look at the exception for more information.
TIBCO-BW-PALETTE-RV-500005	Cannot create TibrvQueue: [{0}]	Look at the exception for more information.
TIBCO-BW-PALETTE-RV-500007	Cannot create reply listener for subject: [{0}]	Look at the exception for more information.
TIBCO-BW-PALETTE-RV-500008	Cannot activate TIBRV listener for subject: [{0}]: Exception: [{1}]	Look at the exception for more information.
TIBCO-BW-PALETTE-	Error in sending reply	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
RV-500009		
TIBCO-BW-PALETTE-RV-500015	Error Occurred while receiving an RV Message so the RV EventSource activity [{0}] failed to generate a new event due to exception [{1}]	Look at the exception for more information.
TIBCO-BW-PALETTE-RV-500018	Advisory listening queue caught exception: [{0}]	Look at the exception for more information.
TIBCO-BW-PALETTE-RV-500010	The RV Subscriber ProcessStarter activity [{0}] failed to generate a new event due to exception [{1}] since it is in the stopped state.	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-RV-500012	Failed to Reply for [{0}]. This error can occur if the RV reply to request activity is executed after recovering from a check-pointed BusinessWorks process instance.	Make sure that RV reply to request activity must be used before checkpoint is taken.

TCP Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the TIBCO BusinessWorks Container Edition TCP palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-TCP-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-	Cannot start TCP Receiver	Correct Host and Port and retry.

Error Codes	Error Message	Error Resolution
PALETTE-TCP-500001	on Host [{0}], Port [{1}]. Reason: [{2}].	
TIBCO-BW-PALETTE-TCP-500003	Invalid Port; port must be numeric. Error: [{0}]	The Port must be numeric.
TIBCO-BW-PALETTE-TCP-500004	No value specified for the 'data' input field.	Specify a value in the 'data' input field.
TIBCO-BW-PALETTE-TCP-500006	Error reading TCP data. Reason: [{0}].	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-TCP-500008	Error opening TCP Connection. Reason: [{0}].	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-TCP-500009	Error opening TCP Connection. Reason: Host [{0}] unknown.	Invalid Host, correct the error and retry.
TIBCO-BW-PALETTE-TCP-500013	Exception closing TCP Connection. Reason: [{0}].	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-TCP-500014	Could not read from TCP connection. The input connection is either invalid or closed.	The input connection is either invalid or closed. Correct the error and retry.
TIBCO-BW-PALETTE-TCP-500015	Could not write to TCP connection. The input connection is either invalid or closed.	The input connection is either invalid or closed. Correct the error and retry.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-TCP-500016	Cannot start TCP Receiver on Host=[{0}], Port=[{1}]. Another TCP Receiver is already running with the same configuration.	Check Host and Port and retry.
TIBCO-BW-PALETTE-TCP-500017	Error closing TCP connection. Reason: No connection is available, which matches the input connection key.	Match the input connection key while closing connection.
TIBCO-BW-PALETTE-TCP-500018	Error writing data. Reason: [{0}].	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-TCP-500021	Timeout while reading TCP data	Possible causes for this error are: (1) The data is being read before it is written. (2) If the data that is written is text/binary and it is being read as binary/text. (3) If the data is written with/without separator and is being read without/with separator.
TIBCO-BW-PALETTE-TCP-500022	IOException occurred while retrieving XML Output for activity [{0}].	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-TCP-500023	The TCP Receiver Process Starter activity [{0}] failed to generate a new event due to exception [{1}] since it is in the stopped state.	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-	The Wait For TCP Request activity [{0}] failed to	This is an internal product error. Contact TIBCO Support.

Error Codes	Error Message	Error Resolution
TCP-500024	generate a new event due to exception [{1}] since it is in the stopped state.	
TIBCO-BW-PALETTE-TCP-500025	Invalid SSL Configurations. Reason: [\{0}].	There is error with the SSL Configurations. Correct the SSL Configurations and then retry.
TIBCO-BW-PALETTE-TCP-500026	Cannot start TCP Receiver on Port [\{0}]. Reason: [\{1}].	Correct Port and retry.

XML Palette Error Codes

This section describes the error messages that can be reported by the activities or entities associated with the XML palette.

Error Codes	Error Message	Error Resolution
TIBCO-BW-PALETTE-XML-000001	[\{0}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-PALETTE-XML-100001	[\{0}]	This is a trace message and the resolution is not applicable.
TIBCO-BW-PALETTE-XML-200001	[\{0}]	This is a debug message and the resolution is not applicable.
TIBCO-BW-PALETTE-	[\{0}]	This is an informational message and it highlights the runtime progress of the

Error Codes	Error Message	Error Resolution
XML-300001		activity. The resolution is not applicable.
TIBCO-BW-PALETTE-XML-400001	{{0}}	This is a warning message and it highlights situations that may affect the activity execution.
TIBCO-BW-PALETTE-XML-500000	Internal error occurred Class={{0}}, Method={{1}}, Reason={{2}}.	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-PALETTE-XML-500001	Unable to serialize the XML due to exception {{0}}.	Ensure that the input XML node is properly given.
TIBCO-BW-PALETTE-XML-500002	Unable to parse the XML due to exception {{0}}.	Ensure that the provided input XML is well formed and valid.
TIBCO-BW-PALETTE-XML-500003	Exception {{0}} occurred during XSLT transformation. Exception detail {{1}}.	Ensure that the provided input XML and input XSLT are properly given.
TIBCO-BW-PALETTE-XML-500004	The XSLT transformation Style sheet provided for the activity input is empty or null.	Ensure to provide the XSLT either in the configuration or in the activity input.
TIBCO-BW-PALETTE-XML-500005	The selected encoding {{0}} is not valid.	Ensure that the provided encoding is valid.
TIBCO-BW-PALETTE-XML-500006	Encountered encoding error {{0}}.	Ensure that the provided encoding is correct.
TIBCO-BW-PALETTE-	The encoded bytes content is empty.	Ensure that the input content is not empty.

Error Codes	Error Message	Error Resolution
XML-500007		
TIBCO-BW-PALETTE-XML-500008	Encountered error [{0}] while trying to detect the encoding from the XML.	Ensure that the provided input byte content is correct.
TIBCO-BW-PALETTE-XML-500009	Activity input error. The activity does not receive proper input.	Ensure that the input content is not empty.

Shared Resources

This section describes the error codes that can be reported by various shared resources.

Shared Resource Framework Error Codes

The Shared Resource Framework is responsible for the creating and managing the shared resources required by the product applications. This section describes the error messages that can be reported by the Shared Resource Framework.

Error Codes	Error Message
TIBCO-BW-SR-FRWK-000010	Shared Resource Creation Error. The ResourceDependencyHandler object returned by <code>[[0]#create()]</code> is null.
TIBCO-BW-SR-FRWK-500001	{0}
TIBCO-BW-SR-FRWK-502000	Failed to {0} SharedResource <code>[[1]]</code> for Module <code>[[2]:{3}]</code> , DeploymentUnit <code>[[4]:{5}]{6}</code>
TIBCO-BW-SR-FRWK-503000	Unable to start SharedResource <code>[[0]] {1}</code> . <Reason>: {2}
TIBCO-BW-SR-COMMON-001101	Unable to get IdentitySubject from Trinity for {0}.
TIBCO-BW-SR-COMMON-001102	Object is not of type IdentitySubject for {0}.
TIBCO-BW-SR-COMMON-001103	Unable to get IdentityTrust from Trinity for {0}.

Error Codes	Error Message
TIBCO-BW-SR-COMMON-001104	Object is not of type IdentityTrust for {0}.
TIBCO-BW-SR-COMMON-001105	Unsupported PrivateKey.
TIBCO-BW-SR-COMMON-001105	Key not found.
TIBCO-BW-SR-COMMON-001105	Problem extracting Key.
TIBCO-BW-SR-THREADPOOL-502000	Failed to {0} Thread Pool resource [{1}]
TIBCO-BW-SR-THREADPOOL-500001	Failure during execution of pending task {0} in work queue on ThreadPool shutdown.
TIBCO-BW-SR-THREADPOOL-500002	Could not submit task {0} for execution.
TIBCO-BW-SR-THREADPOOL-500003	No matching time unit found for {0}, possible values are {NANOSECONDS, MICROSECONDS, MILLISECONDS, SECONDS, MINUTES, HOURS, DAYS}.
TIBCO-BW-SR-THREADPOOL-500004	No matching rejection policy found for {0}, possible values are {BLOCKING, CALLER_RUNS, ABORT}.

Error Codes	Error Message
TIBCO-BW-SR-THREADPOOL-500005	Keep Alive Time should be greater than or equal to zero.
TIBCO-BW-SR-THREADPOOL-500006	Maximum Pool Size should be greater than zero and less than or equal Core pool size.
TIBCO-BW-SR-THREADPOOL-500007	Core Pool Size should be greater than or equal to zero.
TIBCO-BW-SR-THREADPOOL-500008	Minimum Pool Size should be greater than or equal to zero.

Data Format Error Codes

This section describes the error messages that can be reported by the Data Format shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-DATAFORMAT-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-SR-DATAFORMAT-500000	Failed to {0} Data Format resource [{1}]	Check the configuration of the Data Format shared resource.

FTP Connection Error Codes

This section describes the error messages that can be reported by the FTP Connection shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-FTP-500004	Failed to {0} FTP Connection resource [{1}]	Correct the error and retry.
TIBCO-BW-SR-FTP-200001	{0}	This is a debug message and the resolution is not applicable.

HTTP Client Error Codes

This section describes the error messages that can be reported by the HTTP Client shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-HTTP-CLIENT-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-SR-HTTP-CLIENT-500000	Failed to {0} HTTP Client resource [{1}]	Check the configuration of the HTTP Client resource.
TIBCO-BW-SR-HTTP-CLIENT-500001	Username or Password is not specified in Identity	Specify a username and password in the Identity shared resource.
TIBCO-BW-SR-HTTP-CLIENT-500002	Username or Password is not set in the identity resource for basic HTTP authentication	Check if the username and password is specified in the Identity shared resource.

HTTP Connector Error Codes

This section describes the error messages that can be reported by the HTTP Connector shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-HTTP-CONNECTOR-100001	{0}	This is a trace message and the resolution is not applicable.
TIBCO-BW-SR-HTTP-CONNECTOR-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-SR-HTTP-CONNECTOR-300003	Error while stopping the HTTP endpoint [{0}]	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.
TIBCO-BW-SR-HTTP-CONNECTOR-300004	Error while stopping HTTP context [{0}]	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.
TIBCO-BW-SR-HTTP-CONNECTOR-500000	Failed to {0} HTTP Connector resource [{1}]	Check the configuration of the HTTP Connector resource.
TIBCO-BW-SR-HTTP-CONNECTOR-500003	Failed to create the HTTP Connector resource [{0}] with the specified configuration. Check the configuration settings.	Check the configuration of the HTTP Connector resource.
TIBCO-BW-SR-HTTP-CONNECTOR-500004	Unable to start the HTTP Server instance for resource [{0}]	Check the configuration of the HTTP Connector resource.
TIBCO-BW-SR-HTTP-	Failed to activate the HTTP endpoint [{0}] because of	Check the exception and correct the configuration of the HTTP Connector

Error Codes	Error Message	Error Resolution
CONNECTOR-500005	exception [{1}]	resource or HTTP Event source.
TIBCO-BW-SR-HTTP-CONNECTOR-500006	The HTTP server instance cannot be started, because it is not configured	Check the configuration of the HTTP Connector resource or HTTP Event source.
TIBCO-BW-SR-HTTP-CONNECTOR-500007	The HTTP server instance [{0}] occurred an error when stopped	System exception.
TIBCO-BW-SR-HTTP-CONNECTOR-500008	Failed to deactivate the HTTP endpoint [{0}]	System exception.
TIBCO-BW-SR-HTTP-CONNECTOR-500009	Failed to get URL for the HTTP endpoint [{0}]	Check the host and port configuration on the HTTP Connector resource.
TIBCO-BW-SR-HTTP-CONNECTOR-500010	Unable to find Application bundle [{0}]	System exception.
TIBCO-BW-SR-HTTP-CONNECTOR-500012	Failed to create the HTTP Connector resource [{0}] configured with port [{1}]	Check the port configured on the HTTP Connector resource is not in use.
TIBCO-BW-SR-HTTP-CONNECTOR-500013	LDAP resource is not configured on the HTTP Connector resource [{0}].	Check if LDAP resource is configured on the HTTP Connector.

Java Global Instance Error Codes

This section describes the error messages that can be reported by the Java Global Instance shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-JAVA-500001	BW6_EXCP_NAME_EXISTS = A connector configuration with the name "[{0}]" already exists with pid [{1}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-SR-JAVA-500002	Unable to find Application bundle [{0}]	This is an internal product error. Contact TIBCO Support.
TIBCO-BW-SR-JAVA-500003	Unable to construct an instance of the Java class [{0}]. Encountered an exception [{1}] [{2}].	Correct the error stated in the exception message and retry.
TIBCO-BW-SR-JAVA-500004	Activity input error. The activity received an incorrect value for the method parameters. IllegalArgumentException occurred while trying to construct an instance of the Java class [{0}]: [{1}]	Ensure that the correct values are provided for the constructor parameter elements that are in the activity input tab.
TIBCO-BW-SR-JAVA-500005	The constructor for the Java class [{0}] raised an exception [{1}]. [{2}]	The exception was raised by the constructor of the declared Java class. Refer to the Java class implementation for details.
TIBCO-BW-SR-JAVA-500006	The Java class [{0}] is not found in the classpath. Encountered ClassNotFoundException [{1}].	Ensure that the specified class file is contained in the classpath.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-JAVA-500007	Unable to obtain information for the method [{0}] from the class [{1}]. Encountered NoSuchMethodException [{2}].	Reconfigure this activity or verify that the declared Java class has not changed since the last configuration.
TIBCO-BW-SR-JAVA-500008	Unable to obtain information for the cleanup method [{0}] from the class [{1}]. NoSuchMethodException occurred. [{2}]	Reconfigure this activity or verify that the declared Java class has not changed since the last configuration.
TIBCO-BW-SR-JAVA-500009	The cleanup method [{0}] raised an exception [{1}]. [{2}]	The exception was raised by the method of the specified Java class. Refer to the declared class implementation for details.
TIBCO-BW-SR-JAVA-500010	Unable to invoke the cleanup method [{0}]. Exception [{1}] occurred. [{2}]	Correct the error stated in the exception message and retry.
TIBCO-BW-SR-JAVA-500012	Unable to invoke the cleanup method [{0}]. Encountered an exception [{1}] [{2}].	The exception was raised by the method of the specified Java class. Refer to the declared class implementation for details.
TIBCO-BW-SR-JAVA-500014	Received an incorrect value for the method [{0}] parameter to get access the BW Module properties. Exception occurred: [{1}]	Ensure that the correct values are provided for the method parameter to get access the BW Module properties.
TIBCO-BW-SR-JAVA-200001	{0}	This is a debug message and the resolution is not applicable.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-JAVA-200002	Failed to {0} Java Global Instance resource [{1}]	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-SR-JAVA-000001	Delete Called on configuration that does not exist with pid [{0}]	The resolution is not applicable. Contact TIBCO Support.

JMS Connection Error Codes

This section describes the error messages that can be reported by the JMS Connection shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-JMS-100001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-SR-JMS-200001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-SR-JMS-300001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-SR-JMS-400001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-SR-JMS-502000	Failed to {0} JMS Connection resource [{1}]	Check JMS Connection Shared resource configuration.

JDBC Connection Error Codes

This section describes the error messages that can be reported by the JDBC Connection shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-JDBC-300001	Received an update request for an existing configuration with PID=[{0}] and Shared resource name [{1}]	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.
TIBCO-BW-SR-JDBC-300002	Updating Password for Shared Resource with PID [{0}] and name[{1}]	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.
TIBCO-BW-SR-JDBC-300003	Updating Username for Shared Resource with PID [{0}] and name[{1}]	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.
TIBCO-BW-SR-JDBC-300004	Updating Database URL[{0}] for Shared Resource with PID [{1}] and name[{2}]	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.
TIBCO-BW-SR-JDBC-300005	Ignoring Hot Update for configuration with PID=[{0}] and name[{1}]. Unsupported parameters updated. Only Username, Password, and URL is supported	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.
TIBCO-BW-SR-JDBC-300006	Adding new configuration for Shared Resource with name [{0}]	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-JDBC-300007	Deleting Configuration for Shared Resource with name <code>{{0}}</code>	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.
TIBCO-BW-SR-JDBC-300008	Following drivers have been loaded in the framework <code>{{0}}</code> . Following Shared Resource Configurations have been deployed before these drivers were loaded <code>{{1}}</code> .	This is an informational message and it highlights the runtime progress of the shared resource. The resolution is not applicable.
TIBCO-BW-SR-JDBC-400001	Exception occurred while closing a bad connection with <code>[Vendor ErrorCode:{{0}}]</code> and <code>SQL STATE[{{1}}]</code>	This is a warning message. A JDBC connection was marked invalid by the driver and was removed from the pool. This connection could not be closed successfully.
TIBCO-BW-SR-JDBC-400002	Maximum permitted connections reached. Cannot create a new connection. Waiting for a connection to be available.	This is a warning message. The JDBC Connection Pool has reached the maximum limit specified by the user. Jobs created wait for a connection to be available before proceeding. Increasing the max connections to a suitable value for the application solves this issue.
TIBCO-BW-SR-JDBC-400003	No suitable DataSourcefactory found for driver <code>{{0}}</code> . The shared resource <code>{{1}}</code> might NOT resolve. The configuration will wait for a driver to be available.	This is a warning message. This message prints out information about a driver not being loaded at the current time. Since the framework has not finished loading, there is a chance of the driver being loaded later. It is safe to ignore this message.
TIBCO-BW-SR-JDBC-502000	Failed to <code>{{0}}</code> JDBC Connection resource <code>{{1}}</code> .	A JDBC connection lifecycle error has occurred. Check the connection configuration and restart the application if necessary.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-JDBC-500001	Exception occurred while trying to retrieve a connection from the JDBC Connection pool	Check the connection configuration and if the database is up and running.
TIBCO-BW-SR-JDBC-500002	Failed to create a new connection to the database server. Database URL [{0}], UserName [{1}], SQLSTATE [{2}]	Check the connection configuration and if the database is up and running.
TIBCO-BW-SR-JDBC-500003	The database driver [{0}] is not found. Ensure that the DataSourceFactory bundle providing this driver is available in the environment.	Run the appropriate script using BWInstall from the bin folder to add the JDBC driver to the runtime environment.
TIBCO-BW-SR-JDBC-200001	Destroying all Unused connections.	This is a debug message and the resolution is not applicable.
TIBCO-BW-SR-JDBC-200002	Published Event to Event Admin on topic {0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-SR-JDBC-000001	Delete Called on configuration that does not exist with pid [{0}]	This is an internal product error. Contact TIBCO Support.

JNDI Configuration Error Codes

This section describes the error messages that can be reported by the JNDI Configuration shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-JNDI-100001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-SR-JNDI-200001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-SR-JNDI-300001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-SR-JNDI-400001	{0}	The resolution is not applicable. Contact TIBCO Support.
TIBCO-BW-SR-JNDI-502000	Failed to {0} JNDI Configuration resource [{1}]	Check JNDI Configuration shared resource configuration.

Proxy Configuration Error Codes

This section describes the error messages that can be reported by the Proxy Configuration shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-HTTP-PROXY-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-SR-HTTP-PROXY-500000	Failed to {0} Proxy Configuration resource [{1}]	Check the configuration of Proxy shared resource.

SMTP Resource Error Codes

This section describes the error messages that can be reported by the SMTP shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-MAIL-200001	{0}	This is a debug message and the resolution is not applicable.
TIBCO-BW-SR-MAIL-300001	Adding new configuration [{0}].	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-SR-MAIL-300002	Deleting configuration [{0}].	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-SR-MAIL-300004	Mail Session created successfully.	This is an informational message and it highlights the runtime progress of the activity. The resolution is not applicable.
TIBCO-BW-SR-MAIL-400001	Called update on an existing configuration [{0}]. Resource will be recreated.	This is a warning message and it highlights situations that may affect the activity execution.
TIBCO-BW-SR-MAIL-500001	Problem extracting mail SSL information from Trinity for JNDI [{0}].	Ensure that the SSL shared resource is appropriately configured.
TIBCO-	Mail Session creation failed.	Ensure that the SMTP shared resource is

Error Codes	Error Message	Error Resolution
BW-SR-MAIL-500002		appropriately configured.
TIBCO-BW-SR-MAIL-500005	Handler for mimeType [{0}] not found.	Ensure that the mimeType is valid.
TIBCO-BW-SR-MAIL-500006	Failed to start SMTP Connection Shared Resource [{0}].	Ensure that the SMTP shared resource is appropriately configured.

TCP Connection

This section describes the error messages that can be reported by the TCP Connection shared resource.

Error Codes	Error Message	Error Resolution
TIBCO-BW-SR-TCP-500004	Failed to {0} TCP Connection resource [{1}]	Correct the error and retry.
TIBCO-BW-SR-TCP-200001	{0}	This is a debug message and the resolution is not applicable.

TIBCO Documentation and Support Services

For information about this product, you can read the documentation, contact TIBCO Support, and join TIBCO Community.

How to Access TIBCO Documentation

Documentation for TIBCO products is available on the [Product Documentation website](#), mainly in HTML and PDF formats.

The [Product Documentation website](#) is updated frequently and is more current than any other documentation included with the product.

Product-Specific Documentation

The following documentation for this product is available on the [TIBCO BusinessWorks™ Container Edition](#) page:

- *TIBCO BusinessWorks™ Container Edition Release Notes*
- *TIBCO BusinessWorks™ Container Edition Installation*
- *TIBCO BusinessWorks™ Container Edition Application Development*
- *TIBCO BusinessWorks™ Container Edition Application Monitoring and Troubleshooting*
- *TIBCO BusinessWorks™ Container Edition Bindings and Palettes Reference*
- *TIBCO BusinessWorks™ Container Edition Concepts*
- *TIBCO BusinessWorks™ Container Edition Error Codes*
- *TIBCO BusinessWorks™ Container Edition Getting Started*
- *TIBCO BusinessWorks™ Container Edition Maven Plug-in*
- *TIBCO BusinessWorks™ Container Edition Migration*
- *TIBCO BusinessWorks™ Container Edition Performance Benchmarking and Tuning*
- *TIBCO BusinessWorks™ Container Edition REST Implementation*
- *TIBCO BusinessWorks™ Container Edition Refactoring Best Practices*

- *TIBCO BusinessWorks™ Container Edition Samples*

How to Contact Support for TIBCO Products

You can contact the Support team in the following ways:

- To access the Support Knowledge Base and getting personalized content about products you are interested in, visit our [product Support website](#).
- To create a Support case, you must have a valid maintenance or support contract with a Cloud Software Group entity. You also need a username and password to log in to the [product Support website](#). If you do not have a username, you can request one by clicking **Register** on the website.

How to Join TIBCO Community

TIBCO Community is the official channel for TIBCO customers, partners, and employee subject matter experts to share and access their collective experience. TIBCO Community offers access to Q&A forums, product wikis, and best practices. It also offers access to extensions, adapters, solution accelerators, and tools that extend and enable customers to gain full value from TIBCO products. In addition, users can submit and vote on feature requests from within the [TIBCO Ideas Portal](#). For a free registration, go to [TIBCO Community](#).

Legal and Third-Party Notices

SOME CLOUD SOFTWARE GROUP, INC. (“CLOUD SG”) SOFTWARE AND CLOUD SERVICES EMBED, BUNDLE, OR OTHERWISE INCLUDE OTHER SOFTWARE, INCLUDING OTHER CLOUD SG SOFTWARE (COLLECTIVELY, “INCLUDED SOFTWARE”). USE OF INCLUDED SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED CLOUD SG SOFTWARE AND/OR CLOUD SERVICES. THE INCLUDED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER CLOUD SG SOFTWARE AND/OR CLOUD SERVICES OR FOR ANY OTHER PURPOSE.

USE OF CLOUD SG SOFTWARE AND CLOUD SERVICES IS SUBJECT TO THE TERMS AND CONDITIONS OF AN AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER AGREEMENT WHICH IS DISPLAYED WHEN ACCESSING, DOWNLOADING, OR INSTALLING THE SOFTWARE OR CLOUD SERVICES (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH LICENSE AGREEMENT OR CLICKWRAP END USER AGREEMENT, THE LICENSE(S) LOCATED IN THE “LICENSE” FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE SAME TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of Cloud Software Group, Inc.

TIBCO, the TIBCO logo, the TIBCO O logo, ActiveMatrix BusinessWorks, ActiveSpaces, Business Studio, TIBCO Business Studio, TIBCO Designer, TIBCO Enterprise Administrator, Enterprise Message Service, Rendezvous, and TIBCO Runtime Agent are either registered trademarks or trademarks of Cloud Software Group, Inc. in the United States and/or other countries.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only. You acknowledge that all rights to these third party marks are the exclusive property of their respective owners. Please refer to Cloud SG’s Third Party Trademark Notices (<https://www.cloud.com/legal>) for more information.

This document includes fonts that are licensed under the SIL Open Font License, Version 1.1, which is available at: <https://scripts.sil.org/OFL>

Copyright (c) Paul D. Hunt, with Reserved Font Name Source Sans Pro and Source Code Pro.

Cloud SG software may be available on multiple operating systems. However, not all operating system platforms for a specific software version are released at the same time. See the “readme” file for the availability of a specific version of Cloud SG software on a specific operating system platform.

THIS DOCUMENT IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. CLOUD SG MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S), THE PROGRAM(S), AND/OR THE SERVICES DESCRIBED IN THIS DOCUMENT AT ANY TIME WITHOUT NOTICE.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "README" FILES.

This and other products of Cloud SG may be covered by registered patents. For details, please refer to the Virtual Patent Marking document located at <https://www.cloud.com/legal>.

Copyright © 2015-2024. Cloud Software Group, Inc. All Rights Reserved.