

TIBCO ActiveMatrix BusinessWorks™ Plug-in for OData Installation

*Software Release 6.0
May 2016*

Important Information

SOME TIBCO SOFTWARE EMBEDS OR BUNDLES OTHER TIBCO SOFTWARE. USE OF SUCH EMBEDDED OR BUNDLED TIBCO SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED TIBCO SOFTWARE. THE EMBEDDED OR BUNDLED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER TIBCO SOFTWARE OR FOR ANY OTHER PURPOSE.

USE OF TIBCO SOFTWARE AND THIS DOCUMENT IS SUBJECT TO THE TERMS AND CONDITIONS OF A LICENSE AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED SOFTWARE LICENSE AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER LICENSE AGREEMENT WHICH IS DISPLAYED DURING DOWNLOAD OR INSTALLATION OF THE SOFTWARE (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH SOFTWARE LICENSE AGREEMENT OR CLICKWRAP END USER LICENSE AGREEMENT, THE LICENSE(S) LOCATED IN THE "LICENSE" FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document contains confidential information that is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of TIBCO Software Inc.

TIBCO, Two-Second Advantage, TIBCO ActiveMatrix BusinessWorks, TIBCO ActiveMatrix BusinessWorks Plug-in for OData, TIBCO Business Studio, and TIBCO Enterprise Administrator are either registered trademarks or trademarks of TIBCO Software Inc. in the United States and/or other countries.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only.

THIS SOFTWARE MAY BE AVAILABLE ON MULTIPLE OPERATING SYSTEMS. HOWEVER, NOT ALL OPERATING SYSTEM PLATFORMS FOR A SPECIFIC SOFTWARE VERSION ARE RELEASED AT THE SAME TIME. SEE THE README FILE FOR THE AVAILABILITY OF THIS SOFTWARE VERSION ON A SPECIFIC OPERATING SYSTEM PLATFORM.

THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. TIBCO SOFTWARE INC. MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THIS DOCUMENT AT ANY TIME.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "READ ME" FILES.

Copyright © 2015-2016 TIBCO Software Inc. All rights reserved.

TIBCO Software Inc. Confidential Information

Contents

TIBCO Documentation and Support Services	4
Installation Overview	5
Installation Requirements	6
Installation Account	6
System Requirements	6
Using TIBCO Universal Installer	8
Installer Overview	8
Installation Modes	8
Installation Environment	8
Installation Components	8
Installation	9
Installing in GUI Mode	9
Installing in Console Mode	10
Installing in Silent Mode	10
Uninstallation	11
Uninstalling in GUI Mode	11
Uninstalling in Console Mode	12
Using Update Site	13
Installing the Plug-in Using a Public Update Site	13
Installing the Plug-in Using a Local Update Site or Directory	13
Uninstalling the Plug-in	14
Installation Logging	16

TIBCO Documentation and Support Services

Documentation for this and other TIBCO products is available on the TIBCO Documentation site. This site is updated more frequently than any documentation that might be included with the product. To ensure that you are accessing the latest available help topics, please visit:

<https://docs.tibco.com>

Product-Specific Documentation

Documentation for TIBCO products is not bundled with the software. Instead, it is available on the TIBCO Documentation site at <https://docs.tibco.com/products/tibco-activematrix-businessworks-plugin-for-odata>. To directly access documentation for this product from the file system, double-click the following file:

`TIBCO_HOME/release_notes/TIB_bwpluginodata_version_docinfo.html`

where `TIBCO_HOME` is the top-level directory in which TIBCO products are installed. On Windows, the default `TIBCO_HOME` is `C:\Program Files\tibco\bw6`. On UNIX systems, the default `TIBCO_HOME` is `/opt/tibco`.

The following documents for this product can be found on the TIBCO Documentation site:

- *TIBCO ActiveMatrix BusinessWorks Plug-in for OData Installation*
- *TIBCO ActiveMatrix BusinessWorks Plug-in for OData User's Guide*
- *TIBCO ActiveMatrix BusinessWorks Plug-in for OData Release Notes*

How to Contact TIBCO Support

For comments or problems with this manual or the software it addresses, contact TIBCO Support:

- For an overview of TIBCO Support, and information about getting started with TIBCO Support, visit this site:

<http://www.tibco.com/services/support>

- If you already have a valid maintenance or support contract, visit this site:

<https://support.tibco.com>

Entry to this site requires a user name and password. If you do not have a user name, you can request one.

How to Join TIBCO Community

TIBCO Community is an online destination for TIBCO customers, partners, and resident experts. It is a place to share and access the collective experience of the TIBCO community. TIBCO Community offers forums, blogs, and access to a variety of resources. To register, go to the following web address:

<https://community.tibco.com>

Installation Overview

You can install TIBCO ActiveMatrix BusinessWorks™ Plug-in for OData either by using TIBCO Universal Installer or an update site.

- TIBCO Universal Installer

You can install the plug-in by using TIBCO Universal Installer, which provides three installation modes.

For more information, see [Using TIBCO Universal Installer](#).

- Update Site

You can install the plug-in from within TIBCO Business Studio™ using the public Update Site maintained by TIBCO or using a local update site managed by your organization.

For more information, see [Using Update Site](#).

A plug-in must be installed into an existing installation environment where TIBCO ActiveMatrix BusinessWorks™ is already installed. The installation environment of TIBCO ActiveMatrix BusinessWorks is referenced as *TIBCO_HOME*. On Microsoft Windows, the default value of *TIBCO_HOME* is `C:\Program Files\tibco\bw6`.



If a previous version of the plug-in is already installed in the TIBCO HOME where the new version is to be installed, you must uninstall the previous version before installing the new version.

Installation Requirements

Before you run the installer, ensure that your system meets all the hardware and software requirements and you have appropriate privileges to run the installer.

Installation Account

To install on Microsoft Windows, Linux, or on Mac OS, you must have appropriate privileges. Privileges differ for various platforms.



Use the same installer account to install all TIBCO ActiveMatrix BusinessWorks products.

Platform	Account Privileges
Microsoft Windows	Only users with administrator privileges can install the plug-in. If you do not have administrator privileges, the installer automatically exits. To install the product on a network drive, ensure that the account used for installation has permission to access the network drive.
Linux	Any type of user, regular (non-root) user and super-user (root), can perform the installation on Linux. A graphic environment such as CDE or X Windows is required to run the installer in GUI mode.
Mac OS	Any type of user, regular (non-root) user and super-user (root), can perform the installation on Mac OS.

System Requirements

Ensure that your system meets the hardware and software requirements before installing the plug-in.

Platform

Before you run the installer, ensure that the appropriate platform is supported. See the `readme` file for information regarding supported operating system platforms, versions, and the required patches.

Disk Space

The installer requires some space in the temporary directory before installation, and additional space in the temporary directory to run the installer. Ensure that sufficient space is available in the directory that you want to use as the installation environment (*TIBCO_HOME*).



While installing the product, avoid running other processes that use disk space in the installation environment directory. If another process uses disk space while the installer is copying files, the installer might fail and display a failure message.

Software

Ensure that you have installed the required software before you run the installer. See the `readme` file for supported products and versions.

The following are useful TIBCO products:

Software	Description
TIBCO ActiveMatrix BusinessWorks	Required. TIBCO ActiveMatrix BusinessWorks supports your integration project throughout the project life cycle. It includes a common graphical user interface for configuration, process design, and deployment.
TIBCO® Enterprise Administrator	Optional. TIBCO Enterprise Administrator consists of a TIBCO Enterprise Administrator server, a web user interface for the server, and a shell interface, with which you can manage the applications that you create in TIBCO Business Studio.

Using TIBCO Universal Installer

TIBCO Universal Installer provides three modes to install TIBCO ActiveMatrix BusinessWorks Plug-in for OData.

Installer Overview

TIBCO Universal Installer provides three installation modes. Using TIBCO Universal Installer, you can select the installation environment and the installation component.

If you are using TIBCO Universal Installer for the first time to install the plug-in, it is good practice to review the following topics before the installation:

- [Installation Modes](#)
- [Installation Environment](#)
- [Installation Components](#)

Installation Modes

You can run TIBCO Universal Installer in GUI, console, or silent mode. Each mode is supported on all platforms.

GUI Mode

In GUI mode, the installer displays panels where you can select a product, product location, and so on. To invoke the installer in GUI mode, double-click the executable file.

Console Mode

In console mode, you can run the installer on a command line. This is useful if your machine does not have a GUI environment.

Silent Mode

In silent mode, the installer installs the product without prompting you for information. The installer uses either default or custom settings that are saved in a response file.

Installation Environment

An installation environment isolates product installations. A product installed into one installation environment cannot access components in other installation environments.

An installation environment is the top level installation directory for TIBCO products. An installation environment consists of the following properties:

- **Directory**
Identifies the directory where the product is installed.
- **Name**
Identifies the name of the folder where the product is installed.

Installation Components

Different installation components are associated with different functions. Using TIBCO Universal Installer, you can select installation components during the installation.

Installation components are grouped into different installation profiles. One installation profile is associated with one or more installation components. When you select a profile, the components grouped to the selected profile are installed. By default, the **Typical** installation profile is selected, therefore, all the installation components are installed.

The following installation components are available for the plug-in:

Component	Description
TIBCO ActiveMatrix BusinessWorks™ Plug-in for OData Design	This component includes the palettes, shared resources, and samples that show how the plug-in interacts with TIBCO ActiveMatrix BusinessWorks. You can configure your own business process in TIBCO Business Studio with an Eclipse user interface.  This component cannot be installed alone without the runtime component.
TIBCO ActiveMatrix BusinessWorks™ Plug-in for OData Runtime	This component passes and converts data to and from vendor applications. The parameters of data exchange are stored in projects that are created using the plug-in palette.

Installation

When using TIBCO Universal Installer, you can install the plug-in in GUI, console, or silent mode.

Ensure that your system meets all the requirements described in the [Installation Requirements](#) section.



The plug-in must be installed into an existing installation environment where TIBCO ActiveMatrix BusinessWorks is installed. Stop all running processes in the installation environment before the installation.

Installing in GUI Mode

In GUI mode, the installer prompts you for information regarding the installation environment, installation profile, and other installation information.

Procedure

1. Open the physical media or download the installation package from the TIBCO eDelivery site (<https://edelivery.tibco.com>).
To download the installation package, a user name and password are required. If you do not have a user name and password, contact TIBCO Technical Support.
2. Extract the content of the installation package to a temporary directory.
3. Use the extracted installation package to start the installation in one of the following ways:
 - On Microsoft Windows, double-click `TIBCOUniversalInstaller-x86-64.exe`.
 - On Linux, run `TIBCOUniversalInstaller-platform_acronym.bin`.
 - On Mac OS, double-click `TIBCOUniversalInstaller-mac.command`.
4. In the Welcome dialog, click **Next**.
5. In the License Agreement dialog, read through the license agreement and click **I accept the terms of the license agreement**. Click **Next**.
6. In the TIBCO Installation Home dialog, click **Use an existing TIBCO_HOME** to select an existing installation environment where TIBCO ActiveMatrix BusinessWorks is installed. Click **Next**.
See [Installation Environment](#) for more details.
7. In the Installation Profile Selection dialog, select an installation profile to specify the installation components to be installed. Or select the **Customize Installation** check box to select the installation components. Click **Next**.
See [Installation Components](#) for more details.

8. In the Pre-Install Summary dialog, review the list of products selected for the installation. Click **Install**.
9. In the Post Install Summary dialog, review the list of the installation information. Click **Finish** to complete the installation process and exit the installer.

Installing in Console Mode

In console mode, you can run the installer on a command line.

Procedure

1. Open the physical media or download the installation package from the TIBCO eDelivery site (<https://edelivery.tibco.com>).
To download the installation package, a user name and password are required. If you do not have a user name and password, contact TIBCO Technical Support.
2. Extract the content of the package to a temporary directory.
3. On a command line, navigate to the temporary directory to which you extracted the installation package.
4. Run the following command to start the installation:
 - On Microsoft Windows: `TIBCOUniversalInstaller.cmd -console`
 - On Linux: `./TIBCOUniversalInstaller-platform_acronym.bin -console`
 - On Mac OS: `./TIBCOUniversalInstaller-mac.command -console`
5. Respond to the messages on the command line.
The installation options are the same as GUI Mode. See [Installing in GUI Mode](#) for more details.
6. When the installation is completed, press Enter to exit the installer.

Installing in Silent Mode

In silent mode, you can run the installer without user input by pointing the installer to an existing response file.

A default response file named `TIBCOUniversalInstaller_bwpluginodata_version.silent` is packaged with TIBCO Universal Installer. Before launching the silent installation, you have to edit the response file with information about your environment. It is good practice to make a copy of the default response file, and then edit that file and use it for the installation.

- If you invoke the installer with the `-silent` argument, the installer reads the input from default response file.
- If you invoke the installer with the `-silent -V responseFile=<filename>` argument, the installer reads the input from the specified response file.

Procedure

1. Open the physical media or download the package from the TIBCO eDelivery site (<https://edelivery.tibco.com>).
To download the installation package, a user name and password are required. If you do not have a user name and password, contact TIBCO Technical Support.
2. Extract the content of the package to a temporary directory and open the `TIBCOUniversalInstaller-product_acronym_version.silent` file.
3. Update the response file directly, or make a copy of the response file first, and then update the copied file.

4. On the command line, navigate to the temporary directory where you extracted the installation package.



If you only want to install the TIBCO ActiveMatrix BusinessWorks™ Plug-in for OData Runtime component, you have to change the parameters `<entry key="selectedProfiles">Typical</entry>` in the response file to `<entry key="selectedProfiles">Runtime</entry>`, and add `<entry key="feature_design_bwpluginodata">false</entry>` in the response file.

5. Enter the following command to start the installation:

- On Microsoft Windows: `TIBCOUniversalInstaller.cmd -silent [-V responseFile="filename"]`
- On Linux: `TIBCOUniversalInstaller-platform_acronym.bin -silent [-V responseFile="filename"]`
- On Mac OS: `TIBCOUniversalInstaller-mac.command -silent [-V responseFile="filename"]`



If you copy the response file to another directory, not the temporary directory containing the installer, you have to provide the absolute path of the response file.

Uninstallation

You can uninstall the plug-in in GUI, or console mode when using TIBCO Universal Installer.



Before uninstalling the plug-in, stop all running processes in the installation environment.

Uninstalling in GUI Mode

You can uninstall all the products or specific products from a selected TIBCO HOME when using TIBCO Universal Installer to uninstall the plug-in in GUI mode.

Procedure

1. Navigate to the `TIBCO_HOME/tools/universal_installer` directory.
2. Use one of the following ways to start the uninstallation:
 - On Microsoft Windows, double-click `TIBCOUniversalInstaller-x86-64.exe`.
 - On Linux, run `TIBCOUniversalInstaller-platform_acronym.bin`.
 - On Mac OS, double-click `TIBCOUniversalInstaller-mac.command`.
3. In the TIBCO Installation Manager dialog, select **Uninstall Products from a TIBCO Home Location**.
4. From the **TIBCO Home Location** list, select the TIBCO HOME where the product is installed. Click **Next**.
5. In the Welcome dialog, click **Next**.
6. In the Uninstallation Type dialog, select an uninstallation option and click **Next**.
 - **Custom Uninstall**
You can select the products to be removed.
 - **Typical Uninstall**
You cannot select the products. All the products in the selected TIBCO HOME are removed.
7. If you select **Custom Uninstall** in [step 6](#), select the check box next to the product to be uninstalled in the Product Uninstall Selection dialog. Click **Next**.

8. In the Pre-Uninstall Summary dialog, review the product to be uninstalled. Click **Uninstall**.
9. In the Post Uninstall Summary dialog, click **Finish** to complete the uninstallation process and exit the installer.
10. If you have uninstalled all the software in the selected TIBCO HOME, delete the folders in the installation environment and user home.

Uninstalling in Console Mode

If you are not working in a GUI environment, you can uninstall the software in console mode.

Procedure

1. On a command line, navigate to the *TIBCO_HOME/tools/universal_installer* directory.
2. Run the following command to start the uninstallation:
 - Microsoft Windows: `TIBCOUniversalInstaller-x86-64.exe -console`
 - Linux: `./TIBCOUniversalInstaller-platform_acronym.bin -console`
 - Mac OS: `./TIBCOUniversalInstaller-mac.command -console`
3. Respond to the messages on the command line.

The uninstallation options are the same as GUI mode. See [Uninstalling in GUI Mode](#) for more details.
4. When the uninstallation is completed, press Enter to exit the installer.

Using Update Site

You can install the plug-in by using a public update site or a local update site.

Installing the Plug-in Using a Public Update Site

You can install TIBCO ActiveMatrix BusinessWorks Plug-in for OData from within TIBCO Business Studio using the public update site maintained by TIBCO.

Prerequisites

The software package must be available on the update site, <http://update.tibco.com/eclipse/bw/version> (where the *version* at the end of the address reflects the version of BusinessWorks you are using). Typically, the package name has the format `<plugin_name>_<version>_p2installer.zip`.

Procedure

1. Start TIBCO Business Studio if it has not already been started.
 - On Microsoft Windows, click **Start > All Programs > TIBCO > TIBCO_HOME > TIBCO Business Studio version_number > Studio for Designers**.
 - On Linux or Mac OS, run the TIBCO Business Studio executable located in the `TIBCO_HOME/studio/version_number/eclipse` directory.
2. From the menu, select **Help > Install New Software** to open Eclipse Update Manager.
3. In the Install dialog, enter the URL of the public update site, <http://update.tibco.com/eclipse/bw/version>, in the **Work with** field.
You can save the URL by adding it to the list of available software sites using the TIBCO Business Studio menu **Window > Preferences > Install/Update > Available Software Sites**.
4. From the list of available plug-ins, select the plug-in you want to install. Click **Next**.



You can select more than one plug-in from the list to install multiple plug-ins at the same time.
5. In the Install Details dialog, review the components you want to install. Click **Next**.
6. In the Review Licenses dialog, review the licenses, and click **I accept the terms of the license agreement**.
7. Click **Finish** to start the installation.

What to do next

After installing the software, restart TIBCO Business Studio. This restart is necessary for the software to install completely.

Installing the Plug-in Using a Local Update Site or Directory

You can install TIBCO ActiveMatrix BusinessWorks Plug-in for OData from within TIBCO Business Studio using a local site or directory maintained by your organization.

Prerequisites

Ensure that the software package is downloaded from the TIBCO download site and stored in an appropriate location, such as a local update site or a directory. Typically, the package name has the format `<plugin_name>_<version>_p2installer.zip`.

Procedure

1. Start TIBCO Business Studio if it has not already been started.
 - On Microsoft Windows, click **Start > All Programs > TIBCO > TIBCO_HOME > TIBCO Business Studio *version_number* > Studio for Designers**.
 - On Linux or Mac OS, run the TIBCO Business Studio executable located in the *TIBCO_HOME/studio/version_number/eclipse* directory.
2. From the menu, select **Help > Install New Software** to open Eclipse Update Manager.
3. In the Install dialog, click **Add** to add a new update site you want to work with.



Only one update site can be added at a time. Repeat the following steps to add multiple repositories that contain the downloaded software packages.

You can manage the list of software sites using the TIBCO Business Studio menu **Window > Preferences > Install/Update > Available Software Sites**.

- a) In the Add Repository dialog, click **Archive** and locate the Eclipse plug-in installation package you want to install, and then click **Open**.
The selected plug-in installation package is added to the **Location** field.
 - b) Provide a name for the repository. For example, specify the name as **TIBCO Plugin Update Site for <plug-in>**. Click **OK**.
The plug-in installation package is added to the list of available software in the Install dialog.
4. In the Install dialog, select the plug-in you want to install. Click **Next**.

If there is more than one plug-in in the dialog, you can select multiple plug-ins to install at the same time.
 5. In the Install Details dialog, review the components you want to install. Click **Next**.
 6. In the Review Licenses dialog, review the licenses, and click **I accept the terms of the license agreement**.
 7. Click **Finish** to start the installation.

What to do next

After installing the software, restart TIBCO Business Studio. This restart is necessary for the software to install completely.

Uninstalling the Plug-in

You can uninstall TIBCO ActiveMatrix BusinessWorks Plug-in for OData from Eclipse Update Manager.

Procedure

1. Open TIBCO Business Studio using one of the following ways:
 - Microsoft Windows: click **Start > All Programs > TIBCO > TIBCO_HOME > TIBCO Business Studio *version_number* > Studio for Designers**.
 - Linux or Mac OS: run the TIBCO Business Studio executable located in the *TIBCO_HOME/studio/version_number/eclipse* directory.
2. From the menu, click **Help > Install New Software** to open Eclipse Update Manager.
3. In the Available Software dialog, click the **already installed** link.
4. In the **Installed Software** tab, select the product to be uninstalled and click **Uninstall**.

5. In the Uninstall Details dialog, review the product to be uninstalled. Click **Finish**.
6. Click **Restart Now** when you are prompted to restart TIBCO Business Studio.

Installation Logging

If you encounter problems with the installation, first ensure that your system meets all requirements. Next, check the installer log for potential problems.

The installer log file, `tibco_universal_installer.username_install.log`, is available in the following locations:

- On Microsoft Windows: `C:\Users\username\.TIBCO\install_timestamp`
- On Linux: `user_home_dir/.TIBCO/install_timestamp`
- On Mac OS: `Users/user_home_dir/.TIBCO/install_timestamp`

The installer log file captures the following information:

- Detailed information regarding the user that invoked the installer, hostname, operating system details, and so on
- List of assemblies installed
- Information related to the Ant scripts executed by the installer

To change the location of the installer log file, specify the option `-V logFile="myLogFile"` when you run the installer.