



TIBCO Enterprise Message Service™ User's Guide

*Software Release 8.5
May 2019*

Important Information

SOME TIBCO SOFTWARE EMBEDS OR BUNDLES OTHER TIBCO SOFTWARE. USE OF SUCH EMBEDDED OR BUNDLED TIBCO SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED TIBCO SOFTWARE. THE EMBEDDED OR BUNDLED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER TIBCO SOFTWARE OR FOR ANY OTHER PURPOSE.

USE OF TIBCO SOFTWARE AND THIS DOCUMENT IS SUBJECT TO THE TERMS AND CONDITIONS OF A LICENSE AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED SOFTWARE LICENSE AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER LICENSE AGREEMENT WHICH IS DISPLAYED DURING DOWNLOAD OR INSTALLATION OF THE SOFTWARE (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH SOFTWARE LICENSE AGREEMENT OR CLICKWRAP END USER LICENSE AGREEMENT, THE LICENSE(S) LOCATED IN THE "LICENSE" FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

ANY SOFTWARE ITEM IDENTIFIED AS THIRD PARTY LIBRARY IS AVAILABLE UNDER SEPARATE SOFTWARE LICENSE TERMS AND IS NOT PART OF A TIBCO PRODUCT. AS SUCH, THESE SOFTWARE ITEMS ARE NOT COVERED BY THE TERMS OF YOUR AGREEMENT WITH TIBCO, INCLUDING ANY TERMS CONCERNING SUPPORT, MAINTENANCE, WARRANTIES, AND INDEMNITIES. DOWNLOAD AND USE OF THESE ITEMS IS SOLELY AT YOUR OWN DISCRETION AND SUBJECT TO THE LICENSE TERMS APPLICABLE TO THEM. BY PROCEEDING TO DOWNLOAD, INSTALL OR USE ANY OF THESE ITEMS, YOU ACKNOWLEDGE THE FOREGOING DISTINCTIONS BETWEEN THESE ITEMS AND TIBCO PRODUCTS.

This document is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of TIBCO Software Inc.

TIBCO, Two-Second Advantage, TIB, Information Bus, and TIBCO Enterprise Message Service are either registered trademarks or trademarks of TIBCO Software Inc. in the United States and/or other countries.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only.

This software may be available on multiple operating systems. However, not all operating system platforms for a specific software version are released at the same time. Please see the readme.txt file for the availability of this software version on a specific operating system platform.

THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. TIBCO SOFTWARE INC. MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THIS DOCUMENT AT ANY TIME.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "READ ME" FILES.

This and other products of TIBCO Software Inc. may be covered by registered patents. Please refer to TIBCO's Virtual Patent Marking document (<https://www.tibco.com/patents>) for details.

Copyright © 1997–2019 TIBCO Software Inc. All rights reserved.

TIBCO Software Inc. Confidential Information

Contents

About this Product	26
TIBCO Documentation and Support Services	27
Overview	29
JMS Overview	29
JMS Compliance	29
JMS Message Models	29
Point-to-Point	30
Publish and Subscribe	30
Durable Subscribers for Topics	31
Shared Subscriptions for Topics	31
EMS Destination Features	32
Client APIs	33
Sample Code	33
TIBCO Rendezvous Java Applications	33
Administration	33
Administering the Server	33
User and Group Management	34
Using TIBCO Hawk	34
Modes, Roles, and States	34
Security	35
Fault Tolerance	35
Routing	35
Integrating with Third-Party Products	36
Transaction Support	36
Messages	37
EMS Extensions to JMS Messages	37
JMS Message Structure	37
JMS Message Header Fields	37
EMS Message Properties	39
Undelivered Message Queue	40
Including the Message Sender	41
JMS Message Bodies	41
Maximum Message Size	42
Message Priority	42
Message Delivery Modes	42
PERSISTENT	42

NON_PERSISTENT	43
RELIABLE_DELIVERY	43
How EMS Manages Persistent Messages	44
Persistent Messages Sent to Queues	44
Persistent Messages Published to Topics	44
Persistent Messages and Synchronous File Storage	45
Store Messages in Multiple Stores	45
Store Types	46
Default Store Files	47
Configuring Multiple Stores	47
File-Based Stores	47
mstores	47
Understanding mstore Intervals	48
mstore Formats	49
tibemsdbconvert Tool	49
Character Encoding in Messages	50
Supported Character Encodings	50
Sending Messages	50
Message Compression	51
About Message Compression	51
Setting Message Compression	51
Message Acknowledgment	51
NO_ACKNOWLEDGE	52
EXPLICIT_CLIENT_ACKNOWLEDGE	52
EXPLICIT_CLIENT_DUPS_OK_ACKNOWLEDGE	53
Message Selectors	53
Identifiers	53
Literals	53
Expressions	53
Operators	54
White Space	55
Performance	55
Data Type Conversion	55
Sending Messages Synchronously and Asynchronously	56
Sending Synchronously	56
Sending Asynchronously	56
Concurrent Message Use	57
Memory Use	57
Fault Tolerant Failovers	57

Receiving Messages Synchronously and Asynchronously	57
Destinations	58
Destination Overview	58
Destination Names	59
Static Destinations	59
Dynamic Destinations	59
Temporary Destinations	60
Destination Bridges	60
Destination Name Syntax	60
Examples of Destination Names	61
Destination Properties	61
exclusive	62
expiration	63
export	63
flowControl	64
global	64
import	64
maxbytes	65
maxmsgs	65
maxRedelivery	66
overflowPolicy	66
default	67
discardOld	67
rejectIncoming	67
Examples	67
prefetch	67
prefetch Values	68
Background	68
acl.conf	69
Automatic Fetch Enabled	69
Automatic Fetch Disabled	70
Inheritance	70
redeliveryDelay	70
secure	71
sender_name	71
sender_name_enforced	71
store	72
trace	72
Temporary Destination Properties	72

Usage Notes	73
Creating and Modifying Destinations	73
Creating Secure Destinations	74
Wildcards	74
Wildcards * and >	74
Overlapping Wildcards and Disjoint Properties	75
Wildcards in Topics	75
Wildcards in Queues	75
Wildcards and Dynamically Created Destinations	75
Inheritance	76
Inheritance of Properties	76
Inheritance of Permissions	77
Destination Bridges	77
Create a Bridge	79
Select the Messages to Bridge	80
Access Control and Bridges	80
Transactions	80
Flow Control	80
Enable Flow Control	80
Enforce Flow Control	81
Flow Control in the Absence of Consumers	81
Routes and Flow Control	81
Destination Bridges and Flow Control	81
Flow Control, Threads and Deadlock	81
Delivery Delay	82
Getting Started	84
About the Sample Clients	84
Compiling the Sample Java Clients	84
Creating Users with the EMS Administration Tool	85
Point-to-Point Messaging Example	86
Creating a Queue	86
Starting the Sender and Receiver Clients	86
Publish and Subscribe Messaging Example	86
Creating a Topic	87
Starting the Subscriber Clients	87
Starting the Publisher Client and Sending Messages	87
Creating a Secure Topic	88
Adding the secure Property to the Topic	88
Granting Topic Access Permissions to Users	89

Starting the Subscriber and Publisher Clients	89
Creating a Durable Subscriber	89
Running the EMS Server	91
Starting and Stopping the EMS Server	91
Starting the EMS Server Using a Sample Configuration	91
Starting the EMS Server Using JSON Configuration	91
Starting Fault Tolerant Server Pairs	92
Starting the EMS Server Using Options	92
tibemspd Options	92
Stopping the EMS Server	93
Running the EMS Server as a Windows Service	93
emsntsrc	93
Error Recovery Policy	95
Security Considerations	96
Secure Environment	96
Destination Security	96
Authorization Parameter	97
Admin Password	97
Connection Security	97
Communication Security	97
Sources of Authentication Data	97
Timestamp	98
Passwords	98
Audit Trace Logs	98
Manage Access to Shared Store Files	98
Performance Tuning	99
Setting Thread Affinity for Increased Throughput	99
Increasing Network Threads without Setting Thread Affinity	99
Determine Core Allocation	99
Transparent Huge Pages	100
Network I/O Connections	100
Other Considerations	100
Using the EMS Administration Tool	101
Starting the EMS Administration Tool	101
Options for tibemspd	101
When You First Start tibemspd	103
Assigning a Password to the Administrator	103
Naming Conventions	103
Name Length Limitations	103

Command Listing	104
add member	104
addprop factory	104
addprop queue	104
addprop route	104
addprop topic	104
autocommit	105
commit	105
compact	105
connect	106
create bridge	106
create durable	106
create factory	106
create group	106
create jndiname	106
create queue	107
create route	107
create rvcmlistener	107
create topic	107
create user	107
delete all	108
delete bridge	108
delete connection	108
delete durable	108
delete factory	108
delete group	108
delete jndiname	108
delete message	109
delete queue	109
delete route	109
delete rvcmlistener	109
delete topic	109
delete user	109
disconnect	109
echo	109
exit	110
grant queue	110
grant topic	110
grant admin	111

help	111
info	111
jaci clear	111
jaci resetstats	111
jaci showstats	111
purge all queues	111
purge all topics	112
purge durable	112
purge queue	112
purge topic	112
remove member	112
removeprop factory	112
removeprop queue	112
removeprop route	112
removeprop topic	113
resume route	113
revoke admin	113
revoke queue	113
revoke topic	113
rotatelog	113
set password	114
set server	114
setprop factory	118
setprop queue	118
setprop route	118
setprop topic	118
show bridge	119
show bridges	119
show config	119
show consumer	120
show consumers	120
show connections	122
show db	124
show durable	124
show durables	125
show factory	126
show factories	126
show jndiname	126
show jndinames	126

show group	127
show groups	127
show members	127
show message	127
show messages	127
show parents	127
show queue	127
show queues	128
show route	129
show routes	129
show rvctransportledger	130
show rvcmlisteners	130
show server	130
show stat	130
show state	131
show store	131
show stores	133
show topic	133
show topics	135
show subscriptions	136
show transaction	137
show transactions	138
show transport	139
show transports	139
show user	139
show users	139
showacl admin	140
showacl group	140
showacl queue	140
showacl topic	140
showacl user	140
shutdown	140
suspend route	141
time	141
timeout	141
transaction commit	141
transaction rollback	141
updatecrl	141
whoami	141

Configuration Files	142
Location of Configuration Files	142
Mechanics of Configuration	142
tibemsd.conf	142
tibemsd.conf Parameters	143
Global System Parameters	151
always_exit_on_disk_error	151
authorization	151
compliant_queue_ack	151
disconnect_non_acking_consumers	151
flow_control	152
flow_control_only_with_active_consumer	152
health_check_listen	152
listen	153
max_msg_field_print_size	153
max_msg_print_size	153
module_path	153
network_thread_count	154
npsend_check_mode	154
password	155
processor_ids	155
routing	155
secondary_health_check_listen	156
selector_logical_operator_limit	156
server	156
startup_abort_list	156
user_auth	157
xa_default_timeout	157
Storage File Parameters	157
store	157
Connection and Memory Parameters	158
destination_backlog_swapout	158
handshake_timeout	158
large_destination_count	158
large_destination_memory	158
max_client_msg_size	158
max_connections	159
max_msg_memory	159
msg_pool_block_size	159

msg_swapping	159
reserve_memory	159
socket_send_buffer_size	160
socket_receive_buffer_size	160
Detecting Network Connection Failure Parameters	161
active_route_connect_time	161
client_heartbeat_server	161
clock_sync_interval	161
server_timeout_client_connection	161
server_heartbeat_server	162
server_timeout_server_connection	162
server_heartbeat_client	162
client_timeout_server_connection	162
Fault Tolerance Parameters	162
ft_active	162
ft_heartbeat	162
ft_activation	163
ft_reconnect_timeout	163
ft_ssl_identity	163
ft_ssl_issuer	163
ft_ssl_private_key	163
ft_ssl_password	163
ft_ssl_trusted	164
ft_ssl_rand_egd	164
ft_ssl_verify_host	164
ft_ssl_verify_hostname	164
ft_ssl_expected_hostname	164
ft_ssl_ciphers	164
Message Tracking Parameters	165
track_message_ids	165
track_correlation_ids	165
TIBCO FTL Transport Parameters	165
ftl_discard_amount	165
ftl_discard_max_events	165
ftl_discard_policy	165
ftl_log_level	166
ftl_password	166
ftl_url	166
ftl_url_secondary	166

ftl_username	166
tibftl_transports	166
Rendezvous Transport Parameters	167
tibrv_transports	167
SmartSockets Transport Parameters	167
tibss_transports	167
tibss_config_dir	167
Tracing and Log File Parameters	167
client_trace	167
console_trace	168
logfile	168
log_trace	168
logfile_max_count	168
logfile_max_size	169
secondary_logfile	169
trace_client_host	169
Statistic Gathering Parameters	169
server_rate_interval	169
statistics	169
rate_interval	170
detailed_statistics	170
statistics_cleanup_interval	170
max_stat_memory	170
SSL Server Parameters	170
ssl_dh_size	170
ssl_server_ciphers	171
ssl_require_client_cert	171
ssl_require_route_cert_only	171
ssl_use_cert_username	171
ssl_cert_user_specname	172
ssl_server_identity	172
ssl_server_key	172
ssl_password	172
ssl_server_issuer	173
ssl_server_trusted	173
ssl_rand_egd	173
ssl_crl_path	173
ssl_crl_update_interval	173
ssl_auth_only	173

fips140-2	174
LDAP Parameters	174
ldap_url	174
ldap_principal	174
ldap_credential	174
ldap_cache_enabled	174
ldap_cache_ttl	174
ldap_conn_type	174
ldap_tls_cacert_file	175
ldap_tls_cacert_dir	175
ldap_tls_cipher_suite	175
ldap_tls_rand_file	175
ldap_tls_cert_file	175
ldap_tls_key_file	175
ldap_user_class	176
ldap_user_attribute	176
ldap_user_base_dn	176
ldap_user_scope	176
ldap_user_filter	176
ldap_all_users_filter	176
ldap_group_base_dn	177
ldap_group_scope	177
ldap_group_filter	177
ldap_all_groups_filter	177
ldap_static_group_class	177
ldap_static_group_attribute	177
ldap_static_group_member_filter	178
ldap_static_member_attribute	178
ldap_dynamic_group_class	178
ldap_dynamic_group_attribute	178
ldap_dynamic_member_url_attribute	178
Extensible Security Parameters	178
jaas_config_file	178
jaas_login_timeout	179
jaci_class	179
jaci_timeout	179
security_classpath	179
JVM Parameters	179
jre_library	180

jre_option	180
Using Other Configuration Files	180
acl.conf	181
bridges.conf	182
durables.conf	182
factories.conf	183
groups.conf	186
jaas.conf	186
queues.conf	186
routes.conf	187
stores.conf	188
tibrvcm.conf	191
topics.conf	192
transports.conf	192
Transport-specific Parameters	194
users.conf	195
Authentication and Permissions	197
Setting up EMS Access Control	197
Administrator Permissions	197
Predefined Administrative User and Group	198
Granting and Revoking Administration Permissions	198
Enforcement of Administrator Permissions	198
Global Administrator Permissions	199
Destination-Level Permissions	201
Protection Permissions	201
Enable Access Control	202
Server Control	202
Destination Control	203
Users and Groups	203
Users	204
Groups	205
Configure an External Directory	205
External User Authentication	205
Group Information	205
Administration Commands and External Users and Groups	205
Using LDAP Directory Servers	206
User Permissions	207
Queue and Topic Permissions	208
Example of Setting User Permissions	208

Inheritance of User Permissions	208
Revoking User Permissions	209
When Permissions Are Checked	209
Example of Permission Checking	210
Extensible Security	211
Overview of Extensible Security	211
How Extensible Security Works	211
Extensible Authentication	212
Enable Extensible Authentication	212
Prebuilt Authentication Modules	212
Writing an Authentication Module	212
LoginModule Requirements	213
Load the LoginModule in the EMS Server	213
Extensible Permissions	213
Cached Permissions	214
What is Cached	214
How Long Permissions are Cached	214
Administer the Cache	214
How Permissions are Granted	214
Durable Subscribers	215
Special Circumstances	216
Implications of Wildcards on Permissions	216
Enable Extensible Permissions	217
Permissions Module	217
Requirements	217
The JVM in the EMS Server	218
Enable the JVM	218
JAAS Authentication Modules	219
Overview of the JAAS Authentication Modules	219
Prebuilt JAAS Modules	219
Custom JAAS Modules	219
Multiple JAAS Modules	219
Authenticate Administrative Connections	220
Enabling Authentication Using JAAS Modules	220
Prebuilt JAAS Modules	221
LDAP Simple Authentication	221
Authentication Process	221
Implementation	221
Parameters	222

LDAP Authentication	223
Authentication Process	223
Implementation	223
Parameters	223
LDAP Group User Authentication	226
Authentication Process	226
Implementation	226
Parameters	227
Host Based Authentication	230
Authentication Process	230
Implementation	230
Parameters	230
Connection Limit Authentication	231
Authentication Process	231
Implementation	232
Parameters	232
Using Multiple JAAS Modules	232
Example: Two Authentication Requirements	232
Example: One Authentication is Sufficient	233
Migrating to the EMS JAAS Modules	233
LDAP Parameter to JAAS Module Parameter Mapping	233
Parameters Requiring Conversion	234
Dynamic Groups	235
Example	235
Troubleshooting Problems in the JAAS Modules	236
Database Stores	238
Database Stores Overview	238
Configuring Database Stores	238
Configuration in tibemsd.conf	239
dbstore_classpath	239
Supported Database Drivers	240
dbstore_driver_name	240
dbstore_driver_dialect	240
Configuration in stores.conf	240
Configuration to Detect Database Unavailability	243
Configuration for the Oracle RAC Database	243
Installing the OCI Driver	243
Using a TAF Configured URL	243
EMS Schema Export Tool	243

How the Schema Export Tool Works	244
Running the Schema Export Tool	244
EMS Schema Export Tool Options	244
Developing an EMS Client Application	247
JMS Specification	247
JMS 2.0 Specification	247
JMS 1.1 Specification	247
JMS 1.0.2b Specification	247
Sample Clients	248
Programmer Checklists	248
Java Programmer's Checklist	248
C Programmer's Checklist	249
C# Programmer's Checklist	252
Assembly Versioning in the Windows .NET Framework Environment	253
Excluded Features and Restrictions	254
Connection Factories	255
Looking up Connection Factories	255
Dynamically Creating Connection Factories	255
Set Connection Attempts, Timeout and Delay Parameters	256
Connect to the EMS Server	256
Start, Stop and Close a Connection	257
Create a Session	257
Set an Exception Listener	258
Dynamically Create Topics and Queues	259
Create a Message Producer	260
Configure a Message Producer	261
Create a Completion Listener for Asynchronous Sending	261
Create a Message Consumer	263
Create a Message Listener for Asynchronous Message Consumption	264
Messages	266
Create Messages	266
Set and Get Message Properties	266
Send Messages	267
Receive Messages	268
The EMS Implementation of JNDI	270
Create and Modify Administered Objects in EMS	270
Create Connection Factories for Secure Connections	270
Create Connection Factories for Fault-Tolerant Connections	271
Look up Administered Objects Stored in EMS	271

Look Up Objects Using Full URL Names	272
Perform Secure Lookups	273
Perform Fault-Tolerant Lookups	274
Interoperation with TIBCO FTL	275
Message Translation	275
Configuration	275
Enabling	275
Transports	276
Destinations	276
Configure EMS Transports for TIBCO FTL	276
Queue Limit Policies	276
Requirements	277
EMS Transport for FTL Definitions	277
Topics	278
Import Only when Subscribers Exist	279
Queues	279
Configuration	279
Import—Start and Stop	279
Message Translation	279
JMS Header Fields	279
JMS Property Fields	280
Import	280
Export	281
Message Body	281
Import	281
Export	281
Message Fields	282
Import	282
Export	283
Interoperation with TIBCO Rendezvous	284
Message Translation	284
Configuration	284
Enabling	284
Transports	284
Destinations	285
RVCM Listeners	285
Configure Transports for Rendezvous	285
How Rendezvous Messages are Imported	285
Queue Limit Policies	285

Transport Definitions	286
Topics	289
import	289
export	289
Example	289
Import Only when Subscribers Exist	290
Wildcards	290
Certified Messages	290
RVCM Ledger	290
Subject Collisions	290
Queues	290
Configuration	290
Import—Start and Stop	291
Wildcards	291
Import Issues	291
Field Identifiers	291
JMSTDestination	291
JMSReplyTo	291
JMSExpiration	291
Guaranteed Delivery	292
Export Issues	292
JMSReplyTo	292
Certified Messages	292
Guaranteed Delivery	292
Message Translation	292
JMS Header Fields	293
Special Cases	293
Import	293
Export	293
JMS Property Fields	294
Import	294
Import RVCM	294
Export	294
Message Body	294
Import	295
Export	295
Data Types	296
Pure Java Rendezvous Programs	297
Interoperation with TIBCO SmartSockets	298

Message Translation	298
Configuration	298
Enabling	298
Transports	298
Destinations	299
Starting the Servers	299
Configure Transports for SmartSockets	299
Transport Definitions	299
Destination Name—Syntax and Semantics	302
Slash & Dot Separators	302
Wildcard Star	302
Trailing Wildcard	302
Topics	302
import	303
export	303
Example	303
Import Only when Subscribers Exist	303
Wildcards	303
Queues	303
Configuration	303
Import—Start and Stop	304
Wildcards	304
Import Issues	304
Import Destination Names Must be Unique	304
JMSReplyTo	304
Guaranteed Delivery	304
Export Issues	305
JMSReplyTo	305
Wildcard Subscriptions	305
Guaranteed Delivery	305
Message Translation	305
JMS Header Fields	305
Two Special Cases	305
Import	306
Export	306
JMS Property Fields	306
Import	306
Export	306
SmartSockets Message Properties	306

Import	306
Export	307
Message Body	307
Import	308
Export	308
Data Types	308
Destination Names	309
Monitor Server Activity	310
Server Health	310
Log Files and Tracing	310
Configure the Log File	310
Trace Messages for the Server	311
Server Tracing Options	311
Message Tracing	314
Enable Message Tracing for a Destination	314
Enable Message Tracing on a Message	315
Monitor Server Events	315
System Monitor Topics	315
Monitor Messages	315
Message monitoring qualifiers	316
View Monitor Topics	317
Performance Implications of Monitor Topics	317
Server Statistics	318
Overall Server Statistics	318
Enable Statistics Gathering	319
Detailed Statistics	319
Display the Statistics	320
SSL Protocol	321
SSL Support in TIBCO Enterprise Message Service	321
Implementations	321
Digital Certificates	322
Digital Certificate File Formats	322
Private Key Formats	322
File Names for Certificates and Keys	323
Configure SSL in the Server	324
SSL Parameters	324
Command Line Options	324
Configure SSL in EMS Clients	324
Client Digital Certificates	324

Configure SSL	325
Configure a Connection Factory	325
ConnectionFactory SSL parameters	327
Specify Cipher Suites	328
Syntax for Cipher Suites	329
Java Client Syntax	329
Syntax for All Other Cipher Suite Specifications	329
Default Cipher List	330
Supported Cipher Suites	330
Supported Cipher Suites for Java Clients	330
Supported Cipher Suites for .NET Clients	335
SSL Authentication Only	335
Motivation	335
Preconditions	335
Enable FIPS Compliance	336
Enable the EMS Server	336
Enable EMS Clients	337
Fault Tolerance	338
Fault Tolerance Overview	338
Shared State	338
Unshared State Failover	338
Shared State Failover Process	339
Detection	339
Response	339
Lock Unavailable	339
Role Reversal	340
Client Transfer	340
Client Notification	340
Message Redelivery	340
Transactions	341
Queues	341
Heartbeat Parameters	341
Configuration Files	341
Unshared State Failover Process	342
Detection	342
Response	342
Message Loss	342
Unsupported Features	342
Dual State Failover	343

Shared State	344
Implement Shared State	344
Support Criteria	344
Hardware Options	344
SCSI and SAN	345
NAS	345
NAS with NFS	345
Software Options	345
Messages Stored in Shared State	345
Storage Files	346
Storage Parameters	346
Configure Fault-Tolerant Servers	346
Shared State	346
Authorization and Fault-Tolerant Servers	346
SSL	347
Reconnect Timeout	347
Unshared State	347
Fault Tolerance in Central Administration	348
Configuring Fault Tolerance	348
Configuration Errors	348
Configure Clients for Shared State Failover Connections	349
Specify More Than Two URLs	349
Set Reconnection Failure Parameters	349
Configure Clients for Unshared State Failover Connections	350
Include the Unshared State Library	350
Create an Unshared State Connection Factory	351
Connection Recovery	351
Specify Server URLs	351
Set Connect Attempt and Reconnect Attempt Behavior	352
Routes	353
Overview	353
Route	353
Basic Operation	353
Global Destinations	353
Unique Routing Path	354
Zone	354
Basic Operation	354
Eliminate Redundant Paths with a One-Hop Zone	355
Overlapping Zones	355

Active and Passive Routes	356
Active-Passive Routes	356
Active-Active Routes	357
Configure Routes and Zones	357
Routes to Fault-Tolerant Servers	358
Routing and SSL	358
SSL Parameters for Routes	358
Routed Topic Messages	360
Registered Interest Propagation	360
Selectors for Routing Topic Messages	362
Example	362
Specifying Selectors	363
Syntax	363
Example Syntax	363
Symmetry	363
Active-Active Configuration	363
Wildcards	364
Routed Queues	364
Owner and Home	364
Example	365
Producers	365
Consumers	365
Configuration	365
Browsing	366
Transactions	366
Routing and Authorization	366
User & Password	366
ACL	366
Monitor Messages	367
Description of Monitor Topics	367
Description of Topic Message Properties	369
Error and Status Messages	378
Error and Status Codes	378

About this Product

TIBCO is proud to announce the latest release of TIBCO Enterprise Message Service™ software.

This release is the latest in a long history of TIBCO products that leverage the power of the Information Bus® technology to enable truly event-driven IT environments. To find out more about how TIBCO Enterprise Message Service software and other TIBCO products are powered by TIB® technology, please visit us at www.tibco.com.

TIBCO Enterprise Message Service software lets application programs send and receive messages according to the Java Message Service (JMS) protocol. It also integrates with TIBCO FTL, TIBCO Rendezvous, and TIBCO SmartSockets messaging products.

TIBCO EMS software is part of TIBCO® Messaging.

Product Editions

TIBCO Messaging is available in a community edition and an enterprise edition.

TIBCO Messaging - Community Edition is ideal for getting started with TIBCO Messaging, for implementing application projects (including proof of concept efforts), for testing, and for deploying applications in a production environment. Although the community license limits the number of production clients, you can easily upgrade to the enterprise edition as your use of TIBCO Messaging expands.

The community edition is available free of charge. It is a full installation of the TIBCO Messaging software, with the following limitations and exclusions:

- Users may run up to 100 application instances or 1000 web/mobile instances in a production environment.
- Users do not have access to TIBCO Support, but you can use TIBCO Community as a resource (<https://community.tibco.com>).
- Available on Red Hat Enterprise Linux Server, Microsoft Windows & Windows Server and Apple macOS.

TIBCO Messaging - Community Edition has the following additional limitations and exclusions:

- Excludes Fault Tolerance of the server.
- Excludes Unshared State Failover.
- Excludes Routing of messages between servers.
- Excludes Central Administration.
- Excludes JSON configuration files.

TIBCO Messaging - Enterprise Edition is ideal for all application development projects, and for deploying and managing applications in an enterprise production environment. It includes all features presented in this documentation set, as well as access to TIBCO Support.

TIBCO Documentation and Support Services

How to Access TIBCO Documentation

Documentation for TIBCO products is available on the TIBCO Product Documentation website, mainly in HTML and PDF formats.

The TIBCO Product Documentation website is updated frequently and is more current than any other documentation included with the product. To access the latest documentation, visit <https://docs.tibco.com>.

TIBCO Enterprise Message Service Documentation

The following documents for this product can be found on the [TIBCO Enterprise Message Service™](#) product documentation page:

- *TIBCO Enterprise Message Service User's Guide* Read this manual to gain an overall understanding of the product, its features, and configuration.
- *TIBCO Enterprise Message Service Central Administration* Read this manual for information on the central administration interface.
- *TIBCO Enterprise Message Service Installation* Read the relevant sections of this manual before installing this product.
- *TIBCO Enterprise Message Service C & COBOL Reference* The C API reference is available in HTML and PDF formats.
- *TIBCO Enterprise Message Service Java API Reference* The Java API reference can be accessed only through the HTML documentation interface.
- *TIBCO Enterprise Message Service .NET API Reference* The .NET API reference can be accessed only through the HTML documentation interface.
- *TIBCO Enterprise Message Service Installation on Red Hat OpenShift Container Platform*: This manual describes how to run TIBCO Enterprise Message Service servers on the Red Hat® OpenShift Container Platform.
- *TIBCO Enterprise Message Service Release Notes* Read the release notes for a list of new and changed features. This document also contains lists of known issues and closed issues for this release. This document is available only in PDF format.

Other TIBCO Product Documentation

You may find it useful to read the documentation for the following TIBCO products:

- TIBCO FTL®
- TIBCO Rendezvous®
- TIBCO SmartSockets®
- TIBCO EMS® Client for z/OS (CICS)
- TIBCO EMS® Client for z/OS (MVS)
- TIBCO EMS® Client for IBM i

Third-Party Documentation

- Java™ Message Service specification, available through <http://www.oracle.com/technetwork/java/jms/index.html>.

- *Java™ Message Service* by Richard Monson-Haefel and David A. Chappell, O'Reilly and Associates, Sebastopol, California, 2001.
- Java™ Authentication and Authorization Service (JAAS) LoginModule Developer's Guide and Reference Guide, available through <http://www.oracle.com/technetwork/java/javase/jaas/index.html>.

How to Contact TIBCO Support

You can contact TIBCO Support in the following ways:

- For an overview of TIBCO Support, visit <http://www.tibco.com/services/support>.
- For accessing the Support Knowledge Base and getting personalized content about products you are interested in, visit the TIBCO Support portal at <https://support.tibco.com>.
- For creating a Support case, you must have a valid maintenance or support contract with TIBCO. You also need a user name and password to log in to <https://support.tibco.com>. If you do not have a user name, you can request one by clicking Register on the website.

How to Join TIBCO Community

TIBCO Community is the official channel for TIBCO customers, partners, and employee subject matter experts to share and access their collective experience. TIBCO Community offers access to Q&A forums, product wikis, and best practices. It also offers access to extensions, adapters, solution accelerators, and tools that extend and enable customers to gain full value from TIBCO products. In addition, users can submit and vote on feature requests from within the [TIBCO Ideas Portal](#). For a free registration, go to <https://community.tibco.com>.

Overview

The following sections contain a general overview of Java Message Service (JMS) and TIBCO Enterprise Message Service concepts.

JMS Overview

Java Message Service (JMS) is a Java framework specification for messaging between applications. This specification was developed to supply a uniform messaging interface among enterprise applications.

Using a message service allows you to integrate the applications within an enterprise. For example, you may have several applications: one for customer relations, one for product inventory, and another for raw materials tracking. Each application is crucial to the operation of the enterprise, but even more crucial is communication between the applications to ensure the smooth flow of business processes. Message-oriented-middleware (MOM) creates a common communication protocol between these applications and allows you to easily integrate new and existing applications in your enterprise computing environment.

The JMS framework (an interface specification, not an implementation) is designed to supply a basis for MOM development. TIBCO Enterprise Message Service implements JMS and integrates support for connecting other message services, such as TIBCO FTL, TIBCO Rendezvous, and TIBCO SmartSockets. This chapter describes the concepts of JMS and its implementation in TIBCO Enterprise Message Service. For more information on JMS requirements and features, see the following sources:

- Java Message Service specification, available through <http://www.oracle.com/technetwork/java/jms/index.html>.
- *Java Message Service* by Richard Monson-Haefel and David A. Chappell, O'Reilly and Associates, Sebastopol, California, 2001.

JMS Compliance

TIBCO Enterprise Message Service 8.5 has passed the Oracle Technology Compatibility Kit (TCK) tests for Java Message Service 2.0 (JMS 2.0). Therefore, Enterprise Message Service 8.5 is compliant with the Java Message Service 2.0 specification, assuming the following requirements are met:

- Both the Java client and EMS server must be software release 8.0 or higher.
- All EMS software must be run on a supported operating system. Supported systems are listed in the readme file.
- The EMS software must be properly installed to include correct versions of software the EMS is dependent on.
- The EMS server configuration parameter `jms_2_0_compliance` must be set to `true`.




All Oracle Technology Compatibility Kit (TCK) tests were run using Oracle Java SE v.8, as the current version of the TCK does not support later Java versions.

JMS Message Models

JMS is based on creation and delivery of messages. Messages are structured data that one application sends to another.

The creator of the message is known as the *producer* and the receiver of the message is known as the *consumer*. The TIBCO EMS server acts as an intermediary for the message and manages its delivery to the correct destination. The server also provides enterprise-class functionality such as fault-tolerance, message routing, and communication with other messaging systems, such as TIBCO FTL, TIBCO Rendezvous, and TIBCO SmartSockets.

The following image illustrates an application producing a message, sending it by way of the server, and a different application receiving the message.



JMS supports these messaging models:


- [Point-to-Point](#) (queues)
- [Publish and Subscribe](#) (topics)

Point-to-Point

Point-to-point messaging has one producer and one consumer per message. This style of messaging uses a *queue* to store messages until they are received. The message producer sends the message to the queue; the message consumer retrieves messages from the queue and sends acknowledgment that the message was received.

More than one producer can send messages to the same queue, and more than one consumer can retrieve messages from the same queue. The queue can be configured to be exclusive, if desired. If the queue is exclusive, then all queue messages can only be retrieved by the first consumer specified for the queue. Exclusive queues are useful when you want only one application to receive messages for a specific queue. If the queue is not exclusive, any number of receivers can retrieve messages from the queue. Non-exclusive queues are useful for balancing the load of incoming messages across multiple receivers. Regardless of whether the queue is exclusive or not, only one consumer can ever consume each message that is placed on the queue.

The following image illustrates point-to-point messaging using a non-exclusive queue. Each message consumer receives a message from the queue and acknowledges receipt of the message. The message is taken off the queue so that no other consumer can receive it.




Publish and Subscribe

In a publish and subscribe message system, producers address messages to a *topic*. In this model, the producer is known as a *publisher* and the consumer is known as a *subscriber*.

Many publishers can publish to the same topic, and a message from a single publisher can be received by many subscribers. Subscribers subscribe to topics, and all messages published to the topic are received by all subscribers to the topic. This type of message protocol is also known as *broadcast* messaging because messages are sent over the network and received by all interested subscribers, similar to how radio or television signals are broadcast and received.

The following image illustrates publish and subscribe messaging. Each message consumer subscribes to a topic. When a message is published to that topic, all subscribed consumers receive the message.



Durable Subscribers for Topics

By default, subscribers only receive messages when they are active. If messages arrive on the topic when the subscriber is not available, the subscriber does not receive those messages.

The EMS APIs allow you to create durable subscribers to ensure that messages are received, even if the message consumer is not currently running. Messages for durable subscriptions are stored on the server as long as durable subscribers exist for the topic, or until the message expiration time for the message has been reached, or until the storage limit has been reached for the topic. Durable subscribers can receive messages from a durable subscription even if the subscriber was not available when the message was originally delivered.

When an application restarts and recreates a durable subscriber with the same ID, all messages stored on the server for that topic are delivered to the durable subscriber.

See [Create a Message Consumer](#) for details on how to create durable subscribers.

Shared Subscriptions for Topics

Shared subscriptions allow an application to share the work of receiving messages on a topic among multiple message consumers.

When multiple consumers share a subscription, only one consumer in the group receives each new message. This is similar in function to a queue; however, there are no restrictions placed on the type of consumers to the topic, meaning that a topic can have a mix of shared and not shared, durable and non-durable consumers. When a message is published to the topic, the same message goes to all the matching subscriptions.

Shared subscriptions are created with a specific name, and optionally a client ID. Consumers sharing the subscription specify this name when subscribing to the topic. If the shared subscription type is durable, it persists and continues to accumulate messages until deleted. If the shared subscription type is non-durable, it persists only so long as subscribers exist.

For example, the topic `foo` might have the following subscriptions:

- not shared, non-durable subscription
- not shared, durable subscription
- shared, non-durable subscription called `mySharedSub` with three shared consumers
- shared, durable subscription called `myDurableSharedSub` with two shared consumers

If a message is received on `foo`, each of the above four subscriptions receive that same message. For the shared subscriptions `mySharedSub` and `myDurableSharedSub`, the message is delivered to only one of its respective shared consumers.

If the shared consumers of the shared durable subscription `myDurableSharedSub` are closed, then the shared durable subscription continues to exist and accumulate messages until it is deleted, or until the application creates a new durable shared consumer named `myDurableSharedSub` to resume this subscription. If the shared consumers of `mySharedSub` are all closed, the subscription is removed from topic `foo`.

See [Create a Message Consumer](#) for details on how to create shared subscriptions.

EMS Destination Features

TIBCO Enterprise Message Service allows you to configure destinations to enhance the functionality of each messaging model.

The EMS destination features allow you to:

- Set a [secure](#) mode for access control at the queue or topic level, so that some destinations may require permission and others may not. See [Destination Control](#).
- Set threshold limits for the amount of memory used by the EMS server to store messages for a topic or a queue and fine-tune the server's response to when the threshold is exceeded. See [flowControl](#) and [overflowPolicy](#).
- Route messages sent to destinations to other servers. See [Routes](#).
- Create bridges between destinations of the same or different types to create a hybrid messaging model for your application. This can be useful if your application requires that you send the same message to both a topic and a queue. For more information on creating bridges between destinations and situations where this may be useful, see [Destination Bridges](#).
- Control the flow of messages to a destination. This is useful when message producers send messages much faster than message consumers can receive them. For more information on flow control, see [Flow Control](#).
- Exchange messages with other message services, such as TIBCO FTL, TIBCO Rendezvous, and TIBCO SmartSockets. Queues can receive messages from any of these services. Topics can either receive or send messages. See [Interoperation with TIBCO FTL](#), [Interoperation With TIBCO Rendezvous](#), and [Interoperation with TIBCO SmartSockets](#).
- Set queues to be exclusive or non-exclusive. Only one receiver can receive messages from an exclusive queue. More than one receiver can receive messages from non-exclusive queues. See [exclusive](#).
- Specify a redelivery policy for queues. When messages must be redelivered, you can specify a property on the queue that determines the maximum number of times a message should be redelivered. See [maxRedelivery](#).
- Trace and log all messages passing through a destination. See [trace](#).
- Include the user name of the message producer in the message. See [sender_name](#) and [sender_name_enforced](#).
- Administrator operations can use wildcards in destination names. The wildcard destination name is the parent, and any names that match the wildcard destination name inherit the properties of the parent. See [Wildcards](#).
- Use the `store` property to cause messages sent to a destination to be written to a store file. Set the destination store to `store=$sys.fail-safe` to direct the server to write messages to the file synchronously and guarantee that messages are not lost under any circumstances. See [store](#) for more information.
- Specify that a consumer is to receive batches of messages in the background to improve performance. Alternatively, you can specify that queue receivers are to only receive one message at a time. See [prefetch](#) for more information.

Client APIs

Java applications use the `javax.jms` package to send or receive JMS messages. This is a standard set of interfaces, specified by the JMS specification, for creating the connection to the EMS server, specifying the type of message to send, and creating the destination (topic or queue) on which to send or receive messages. You can find a description of the `javax.jms` package in *TIBCO Enterprise Message Service Java API Reference* included in the online documentation.

Because EMS implements the JMS standard, you can also view the documentation on these interfaces along with the JMS specification at <http://www.oracle.com/technetwork/java/jms/index.html>.

TIBCO Enterprise Message Service includes parallel APIs for other development environments. See the following for more information:

- *TIBCO Enterprise Message Service C & COBOL API Reference*
- *TIBCO Enterprise Message Service .NET API Reference* (online documentation)

Sample Code

EMS includes several example programs that illustrate the various features of EMS.

You may wish to view these example programs when reading about the corresponding features in this manual. The examples are included in the samples subdirectory of the EMS installation directory.

For more information about running the examples, see [Getting Started](#).

TIBCO Rendezvous Java Applications

EMS includes a Java class that allows pure Java TIBCO Rendezvous applications to connect directly with the EMS server.

For more information see [Pure Java Rendezvous Programs](#).

Administration

EMS provides mechanisms for administering server operations and creating objects that are managed by the server, such as ConnectionFactories and Destinations.

Administration functions can be issued either using the command-line administration tool or by creating an application that uses the administration API (either Java or .NET). The command-line administration tool is described in [EMS Administration Tool](#). The administration APIs are described in the online documentation.

The administration interfaces allow you to create and manage administered objects such as ConnectionFactories, Topics, and Queues. EMS clients can retrieve references to these administered objects by using Java Naming and Directory Interface (JNDI). Creating static administered objects allows clients to use these objects without having to implement the objects within the client.

Administering the Server

EMS has several administration features that allow you to monitor and manage the server. The following table provides a summary of administration features and details where in the documentation you can find more information.

Feature	More Information
Configuration files allow you to specify server characteristics.	Configuration Files

Feature	More Information
Administration tool provides a command line interface for managing the server.	EMS Administration Tool
Authentication and permissions can restrict access to the server and to destinations. You can also specify who can perform administrative activities with administrator permissions.	Authentication and Permissions
Configure log files to provide information about various server activity.	Monitor Server Activity
The server can publish messages when various system events occur. This allows you to create robust monitoring applications that subscribe to these system monitor topics.	Monitor Server Activity
The server can provide various statistics at the desired level of detail.	Monitor Server Activity

User and Group Management

EMS provides facilities for creating and managing users and groups locally for the server. The EMS server can also use an external system, such as an LDAP server for authenticating users and storing group information.

See [Authentication and Permissions](#) for more information about configuring EMS to work with external systems for user and group management.

Using TIBCO Hawk

You can use TIBCO Hawk® for monitoring and managing the EMS server. See TIBCO Hawk documentation for more information.

Modes, Roles, and States

The *mode* of an EMS server is determined by its configuration, and dictates how it operates in its environment. If a fault tolerant mode is selected, two EMS servers are required and each operates in a defined *role*. How an EMS server is operating at any given moment can be determined by viewing its fault tolerant *state*.

For example, an EMS server operating in fault tolerant mode can play either a primary or secondary role. Once both EMS servers in the fault tolerant pair have been started, one of the two servers will be in the active state while its peer will be in the standby state. In the event of a failover, the server that was standby becomes active.

Modes

By default, the EMS server operates in standalone mode. However, it can also be configured to run in a fault tolerant mode:

- Standalone — the default EMS server mode.
- Classic Fault Tolerant — configured through the [ft_active](#) parameter.

Roles

Each server operating in a fault tolerant mode has a distinct role: primary or secondary.

These roles are implicit for EMS servers started using `tibemsd.conf` files. They are explicit for EMS servers started using a JSON configuration file. For JSON-configured servers, the primary server is the EMS server started without the `-secondary` command line parameter, while the secondary server is started with it. In the `.conf` files, each server in the fault tolerant pair has a distinct `tibemsd.conf` file.

States

The state of the EMS server tells you about its current operations.

Use the [info](#) or [show state](#) command in the administration tool to determine the state of the EMS server.

State	Description
active	The server is fully operational and ready to service clients.
standby	The server is in classic fault tolerant mode and is ready to take over should its peer fail.

Security

For communication security between servers and clients, and between servers and other servers, you must explicitly configure SSL within EMS.

Secure Sockets Layer (SSL) is a protocol for transmitting encrypted data over the Internet or an internal network. SSL works by using public and private keys to encrypt data that is transferred over the SSL connection. Most web browsers support SSL, and many Web sites and Java applications use the protocol to obtain confidential user information, such as credit card numbers.

EMS supports SSL between the following components:

- between an EMS client and the EMS server
- between the administration tool and the EMS server
- between the administration APIs and the EMS server
- between routed servers
- between fault-tolerant servers

See [SSL Protocol](#) for more information about SSL support in EMS.

Fault Tolerance

You can configure EMS servers as primary and secondary servers to provide fault tolerance for your environment. The primary and secondary servers act as a pair, one of them starting out in the active state and the other in the standby state. The active server accepts client connections and performs the work of handling messages, while the standby server acts as a backup in case of failure. If the active server fails, the standby server assumes operation and becomes the active server.

See [Fault Tolerance](#) for more information about the fault-tolerance features of EMS.

Routing

EMS provides the ability for servers to route messages between each other. Topic messages can be routed across multiple hops, provided there are no cycles (that is, the message can not be routed to any server it has already visited). Queue messages can travel at most one hop to any other server from the server that owns the queue.

EMS stores and forwards messages in most situations to provide operation when a route is not connected.

See [Routes](#) for more information about the routing features of EMS.

Integrating with Third-Party Products

EMS allows you to work with third-party naming/directory service products or with third-party application servers.

Transaction Support

TIBCO Enterprise Message Service can integrate with Java Transaction API (JTA) compliant transaction managers. EMS implements all interfaces necessary to be JTA compliant.

The EMS C API is compliant with the X/Open XA specification. The EMS .NET API supports Microsoft Distributed Transaction Coordinator (MS DTC) with .NET Framework. Transactions created using MSDTC in a .NET Framework client are seen as XA transactions in C and Java clients.

Messages

The following sections provide an overview of EMS messages.

EMS Extensions to JMS Messages

The JMS specification details a standard format for the header and body of a message. Properties are provider-specific and can include information on specific implementations or enhancements to JMS functionality. See [EMS Message Properties](#) for the list of message properties that are specific to EMS.

In addition to the EMS message properties, EMS provides a select number of extensions to JMS. These are:

- The JMS standard specifies two delivery modes for messages, `PERSISTENT` and `NON_PERSISTENT`. EMS also includes a `RELIABLE_DELIVERY` mode that eliminates some of the overhead associated with the other delivery modes. See [RELIABLE_DELIVERY](#).
- For consumer sessions, you can specify a `NO_ACKNOWLEDGE` mode so that consumers do not need to acknowledge receipt of messages, if desired. EMS also provides an `EXPLICIT_CLIENT_ACKNOWLEDGE` and `EXPLICIT_CLIENT_DUPS_OK_ACKNOWLEDGE` mode that restricts the acknowledgment to single messages. See [Message Acknowledgement](#).
- EMS extends the [MapMessage](#) and [StreamMessage](#) body types. These extensions allow EMS to exchange messages with TIBCO Rendezvous, which contains certain features not available within the JMS `MapMessage` and `StreamMessage`.

TIBCO Enterprise Message Service adds these two extensions to the `MapMessage` and `StreamMessage` body types:

- You can insert another `MapMessage` or `StreamMessage` instance as a submessage into a `MapMessage` or `StreamMessage`, generating a series of nested messages, instead of a flat message.
- You can use arrays as well as primitive types for the values.

These extensions add considerable flexibility to the `MapMessage` and `StreamMessage` body types. However, they are extensions and therefore not compliant with JMS specifications. Extended messages are tagged as extensions with the vendor property tag `JMS_TIBCO_MSG_EXT`.

For more information on compatibility with Rendezvous messages, see [Message Body](#).

JMS Message Structure

JMS messages have a standard structure.

The JMS message structure includes the following sections:

- Header (required)
- Properties (optional)
- Body (optional)

JMS Message Header Fields

The header contains predefined fields that contain values used to route and deliver messages.

Header Field	Set by	Comments
<code>JMSDestination</code>	send or publish method	Destination to which message is sent

Header Field	Set by	Comments
JMSDeliveryMode	send or publish method	<p>Persistent or non-persistent message. The default is persistent.</p> <p>EMS extends the delivery mode to include a RELIABLE_DELIVERY mode.</p>
JMSExpiration	send or publish method	<p>Length of time that message will live before expiration. If set to 0, message does not expire. The time-to-live is specified in milliseconds.</p> <p>If the server expiration property is set for a destination, it will override the JMSExpiration value set by the message producer.</p>
JMSDeliveryTime	send or publish method	<p>Read-only field. If the message producer has a delivery delay set, then the time returned here after calling the send method represents the earliest time when the EMS server will deliver the message to consumers. Once the message has been received, it carries that same value. This value is calculated by adding the delivery delay value held by the message producer to the time the message was sent. For transactions, the delivery time is calculated using the time the client sends the message, not the time the transaction is committed.</p> <p>For more information, see Delivery Delay.</p>
JMSPriority	send or publish method	<p>Uses a numerical ranking, between 0 and 9, to define message priority as normal or expedited. Larger numbers represent higher priority.</p> <p>See Message Priority for more information.</p>
JMSMessageID	send or publish method	Value uniquely identifies each message sent by a provider.
JMSTimestamp	send or publish method	Timestamp of time when message was handed off to a provider to be sent. Message may actually be sent later than this timestamp.
JMSCorrelationID	message client	This ID can be used to link messages, such as linking a response message to a request message. Entering a value in this field is optional. The JMS Correlation ID has a recommended maximum of 4 KB. Higher values may result in the message being rejected.
JMSReplyTo	message client	A destination to which a message reply should be sent. Entering a value for this field is optional.
JMSType	message client	Message type identifier.
JMSRedelivered	JMS provider	If this field is set, it is possible that the message was delivered to the client earlier, but not acknowledged at that time.

EMS Message Properties

In the properties area, applications, vendors, and administrators on JMS systems can add optional properties. The properties area is optional, and can be left empty. The JMS specification describes the JMS message properties. This section describes the message properties that are specific to EMS.

TIBCO-specific property names begin with `JMS_TIBCO`. Client programs may use the TIBCO-specific properties to access EMS features, but not for communicating application-specific information among client programs.

The EMS properties are summarized in the following table and described in more detail in subsequent sections.

Property	Description	More Info
<code>JMS_TIBCO_CM_PUBLISHER</code>	Correspondent name of an RVCN sender for messages imported from TIBCO Rendezvous.	Import RVCN
<code>JMS_TIBCO_CM_SEQUENCE</code>	Sequence number of an RVCN message imported from TIBCO Rendezvous.	Import RVCN
<code>JMS_TIBCO_COMPRESS</code>	Allows messages to be compressed for more efficient storage.	Message Compression
<code>JMS_TIBCO_DISABLE_SENDER</code>	Specifies that the user name of the message sender should not be included in the message, if possible.	Including the Message Sender
<code>JMS_TIBCO_IMPORTED</code>	Set by the server when the message has been imported from TIBCO FTL, Rendezvous, or SmartSockets.	Import (for Rendezvous) Import (for SmartSockets)
<code>JMS_TIBCO_MSG_EXT</code>	Extends the functionality of the MapMessage and StreamMessage body types to include submessages or arrays.	EMS Extensions to JMS Messages Import (for Rendezvous) Import (for SmartSockets)
<code>JMS_TIBCO_MSG_TRACE</code>	Specifies the message should be traced from producer to consumer.	Message Tracing

Property	Description	More Info
JMS_TIBCO_PRESERVE_UNDELIVERED	Specifies the message is to be placed on the undelivered message queue if the message must be removed.	Undelivered Message Queue
JMS_TIBCO_SENDER	Contains the user name of the message sender.	Including the Message Sender
JMS_TIBCO_SS_SENDER	When the EMS server imports a message from TIBCO SmartSockets, it sets this property to the SmartSockets sender header field (in SmartSockets syntax).	Import

Undelivered Message Queue

If a message could not be delivered for one of the reasons below, the server checks the message's [JMS_TIBCO_PRESERVE_UNDELIVERED](#) property. If that property is set to true, the server moves the message to the undelivered message queue, `$sys.undelivered`. Otherwise, the message is deleted by the server.

The server will examine the `JMS_TIBCO_PRESERVE_UNDELIVERED` property of the message if any of the following conditions are met:

- the message has expired
- the message has exceeded the value specified by the [maxRedelivery](#) property on a queue
- the message had a delivery delay that has expired and was sent to a destination that has reached its [maxmsgs](#) limit and also has [overflowPolicy=rejectIncoming](#)

`$sys.undelivered` is a system queue that is always present and cannot be deleted. To make use of it, the application that sends or publishes the message must set the boolean `JMS_TIBCO_PRESERVE_UNDELIVERED` property to true before sending or publishing the message.

You can only set the undelivered property on individual messages, there is no way to set the undelivered message queue as an option at the per-topic or per-queue level.

You should create a queue receiver to receive and handle messages as they arrive on the undelivered message queue. If you wish to remove messages from the undelivered message queue without receiving them, you can purge the `$sys.undelivered` queue with the administration tool, using the `purge queue` command described under [Command Listing](#). You can also remove messages using the administrative API included with TIBCO Enterprise Message Service.

Note that `$sys.undelivered` ignores the [global](#) destination property setting. Messages in the undelivered message queue are not routed to other servers.

Filtering Messages in the Undelivered Message Queue

You can filter messages in the undelivered message queue by destination using a selector. Note that this is an exception to the JMS Specification that is made only for messages in the undelivered message queue. In the undelivered message queue, the `JMSDestination` header field can be used in a selector the same way that a supported header field or any other message property with a string value is used.

The expected value of the `JMSDestination` field depends on the original message destination type and name:

```
JMSDestination operator 'Topic|Queue[destination_name]'
```

For example:

```
JMSDestination='Queue[A]'  
JMSDestination='Topic[B7]'  
JMSDestination NOT LIKE 'Queue[A]'  
JMSDestination LIKE 'Queue[A]'  
JMSDestination LIKE 'Q%'  
JMSDestination IS NOT NULL  
JMSDestination IN ('Queue[H]','Queue[J]')  
JMSDestination NOT IN ('Topic[H]','Topic[J]')  
JMSDestination='Queue[A]' OR JMSDestination='Queue[B]'
```

Including the Message Sender

Within a message, EMS can supply the user name given by the message producer when a connection is created. The `sender_name` and `sender_name_enforced` server properties on the destination determine whether the message producer's user name is included in the sent message.

When a user name is included in a message, a message consumer can retrieve that user name by getting the string message property named [JMS_TIBCO_SENDER](#).

When the `sender_name` property is enabled and the `sender_name_enforced` property is not enabled on a destination, message producers can specify that the user name is to be left out of the message. Message producers can specify the [JMS_TIBCO_DISABLE_SENDER](#) boolean property for a particular message, and the message producer's user name will not be included in the message. However, if the `sender_name_enforced` property is enabled, the `JMS_TIBCO_DISABLE_SENDER` property is ignored and the user name is always included in the message.

JMS Message Bodies

A JMS message has one of several types of message bodies, or no message body at all.

The types of messages are described in the following table.

Message Type	Contents of Message Body
Message	This message type has no body. This is useful for simple event notification.
TextMessage	A <code>java.lang.String</code> .
MapMessage	<p>A set of name/value pairs. The names are <code>java.lang.String</code> objects, and the values are Java primitive value types or their wrappers. The entries can be accessed sequentially by enumeration or directly by name. The order of entries is undefined.</p> <p>When EMS is exchanging messages with Rendezvous, you can generate a series of nested MapMessages, as described in EMS Extensions to JMS Messages.</p>
BytesMessage	A stream of uninterrupted bytes. The bytes are not typed; that is, they are not assigned to a primitive data type.
StreamMessage	<p>A stream of primitive values in the Java programming language. Each set of values belongs to a primitive data type, and must be read sequentially.</p> <p>When EMS is exchanging messages with Rendezvous, you can generate a series of nested StreamMessages, as described in EMS Extensions to JMS Messages.</p>

Message Type	Contents of Message Body
ObjectMessage	A serializable object constructed in the Java programming language.

Maximum Message Size

EMS supports messages up to a maximum size of 512MB. However, we recommend that application programs use smaller messages, since messages approaching this maximum size will strain the performance limits of most current hardware and operating system platforms.

Message Priority

The JMS specification includes a [JMSPriority](#) message header field in which senders can set the priority of a message, as a value in the range [0,9]. EMS *does* support message priority (though it is optional, and other vendors might not implement it).

When the EMS server has several messages ready to deliver to a consumer client, and must select among them, then it delivers messages with higher priority before those with lower priority.

However, priority ordering applies only when the server has a *backlog* of deliverable messages for a consumer. In contrast, when the server has only one message at a time to deliver to a consumer, then the priority ordering feature will not be apparent.

You can set default message priority for the Message Producer, as described in [Configure a Message Producer](#). The default priority can be overridden by the client when sending a message, as described in [Send Messages](#).

Also refer to JMS Specification, chapter 3.4.10.


Message Delivery Modes

The [JMSDeliveryMode](#) message header field defines the delivery mode for the message. JMS supports PERSISTENT and NON_PERSISTENT delivery modes for both topic and queue. EMS extends these delivery modes to include a [RELIABLE_DELIVERY](#) mode.

You can set the default delivery mode for the Message Producer, as described in [Configure a Message Producer](#). This default delivery mode can be overridden by the client when sending a message, as described in [Send Messages](#).

PERSISTENT

When a producer sends a PERSISTENT message, the producer must wait for the server to reply with a confirmation. The message is persisted on disk by the server. This delivery mode ensures delivery of messages to the destination on the server in almost all circumstances. However, the cost is that this delivery mode incurs two-way network traffic for each message or committed transaction of a group of messages.




NON_PERSISTENT

Sending a `NON_PERSISTENT` message omits the overhead of persisting the message on disk to improve performance.

If [authorization](#) is disabled on the server, the server does not send a confirmation to the message producer.

If [authorization](#) is enabled on the server, the default condition is for the producer to wait for the server to reply with a confirmation in the same manner as when using `PERSISTENT` mode.


Regardless of whether [authorization](#) is enabled or disabled, you can use the `npsend_check_mode` parameter in the `tibemsd.conf` file to specify the conditions under which the server is to send confirmation of `NON_PERSISTENT` messages to the producer. See the description for [npsend_check_mode](#) for details.



RELIABLE_DELIVERY

EMS extends the JMS delivery modes to include reliable delivery. Sending a `RELIABLE_DELIVERY` message omits the server confirmation to improve performance regardless of the [authorization](#) setting.

Also see [authorization](#).



When using `RELIABLE_DELIVERY` mode, the server never sends the producer a receipt confirmation or access denial and the producer does not wait for it. Reliable mode decreases the volume of message traffic, allowing higher message rates, which is useful for messages containing time-dependent data, such as stock price quotations.

When you use the reliable delivery mode, the client application does not receive any response from the server. Therefore, all publish calls will always succeed (not throw an exception) unless the connection to the server has been terminated.

In some cases a message published in reliable mode may be disqualified and not handled by the server because the destination is not valid or access has been denied. In this case, the message is not sent to any message consumer. However, unless the connection to the server has been terminated, the publishing application will not receive any exceptions, despite the fact that no consumer received the message.

How EMS Manages Persistent Messages

JMS defines two message delivery modes, `PERSISTENT` and `NON_PERSISTENT`, and EMS defines a `RELIABLE_DELIVERY` mode.


For more information see [Message Delivery Modes](#).

`NON_PERSISTENT` and `RELIABLE_DELIVERY` messages are never written to persistent storage.

`PERSISTENT` messages are written to persistent storage when they are received by the EMS server.

Persistent Messages Sent to Queues


Persistent messages sent to a queue are always written to disk. Should the server fail before sending persistent messages to subscribers, the server can be restarted and the persistent messages will be sent to the subscribers when they reconnect to the server.



Persistent Messages Published to Topics

Persistent messages published to a topic are written to disk *only* if that topic has at least one durable subscriber or one subscriber with a fault-tolerant connection to the EMS server.

In the absence of a durable subscriber or subscriber with a fault-tolerant connection, there are no subscribers that need messages resent in the event of a server failure. In this case, the server does not needlessly save persistent messages. This improves performance by eliminating the unnecessary disk I/O to persist the messages.



This behavior is consistent with the JMS specification because durable subscribers to a topic cause published messages to be saved. Additionally, subscribers to a topic that have a fault-tolerant connection need to receive messages from the new active server after a failover. However, non-durable subscribers without a fault-tolerant connection that re-connect after a server failure are considered newly created subscribers and are not entitled to receive any messages created prior to the time they are created (that is, messages published before the subscriber re-connects are not resent).

Persistent Messages and Synchronous File Storage

When using file storage, persistent messages received by the EMS server are by default written asynchronously to disk. This means that, when a producer sends a persistent message, the server does not wait for the write-to-disk operation to complete before returning control to the producer.

Should the server fail before completing the write-to-disk operation, the producer has no way of detecting the failure to persist the message and taking corrective action.

You can set the mode parameter to sync for a given file storage in the [stores.conf](#) file to specify that persistent messages for the topic or queue be synchronously written to disk. When mode = sync, the persistent producer remains blocked until the server has completed the write-to-disk operation.

Each EMS server writes persistent messages to a store file. To prevent two servers from using the same store file, each server restricts access to its store file for the duration of the server process. For details on how EMS manages shared store files, see [Managing Access to Shared Store Files](#).

Store Messages in Multiple Stores

The EMS server writes PERSISTENT messages to disk while waiting for confirmation of receipt from the subscriber. Messages are persisted to a *store*. The EMS server can write messages to different types of *stores*: file-based stores, mstores, and database stores.

By default, the EMS server writes persistent messages to file-based stores. There are three default store files, as described in [Default Store Files](#). You can configure the system to change the default store files and locations, and also to store persistent messages to one or more store files, filtering them by destination. Stores are defined in the [stores.conf](#) configuration file, and associated with a destination using the [store](#) destination property.

Stores have properties that allow you to control how the server manages the store files. For example:

- When using file-based stores:
 - Preallocate disk space for the store file.
 - Truncate the file periodically to relinquish disk space.
 - Specify whether messages are written synchronously or asynchronously.
- Store messages in a database.

With the multiple stores feature, you can configure your messaging application to store messages in different locations for each application, or to create separate files for related destinations. For example, you can create one store for messages supporting Marketing, and one for messages supporting Sales. Because stores are configured in the server, they are transparent to clients.

The EMS Administration Tool allows administrators to review the system's configured stores and their settings by using the [show stores](#) and [show store](#) commands.

Store Types

TIBCO Enterprise Message Service allows you to configure several different types of stores, described here.

File-Based Stores

The EMS server stores persistent messages in file-based stores. You can use the default store files, or create your own file-based stores. You direct the EMS server to write messages to these store files by associating a destination with a store.

File-based stores are enabled by default, and the server automatically defines three default stores, described below. You do not need to do anything in order to use the default stores.

The section [Configuring Multiple Stores](#) describes how to change store settings or create custom stores.

mstores

The mstore is designed to recover quickly after a failover. When mstores are in use, the EMS server starts quickly, but may run more slowly until the mstore cache is fully loaded. This is because the EMS server continually monitors the store in the background. The server reads through the mstore incrementally and discards stale data, such as purged and expired messages.

As a result, expired and purged messages are not immediately removed from the mstore, and may remain in the store longer than they would in a file-based or database store—although they are not delivered to the consumer. These messages are discarded during the periodic scans of the store. The scanning behavior is determined by parameter settings in the store configuration, and is further described in [Understanding mstore Intervals](#).

Because of this behavior, querying the server for a total pending message count may return an inaccurate value. However, querying specific destinations returns an accurate count.

The section [Configuring Multiple Stores](#) describes the mstore configuration process. Note that an mstore cannot be configured dynamically.

Database Stores

The EMS server can store messages in one or more database instances. Database stores must be configured to use a supported database. See [Database Stores](#) for a full description of this feature.

Default Store Files

The EMS server defines these default store files, and writes persistent messages and meta data to them:

- `$sys.nonfailsafe`—Persistent messages without a store property designation are written to `$sys.nonfailsafe` by default. The server writes messages to this store using asynchronous I/O calls.
- `$sys.failsafe`—Associate a destination with this store to write messages synchronously. The server writes messages to this store using synchronous I/O calls.
- `$sys.meta`—The server writes state information about durable subscribers, fault-tolerant connections, and other metadata in this store.

The EMS server creates these file-based stores automatically, and no steps are required to enable or deploy them. However, you can change the system configuration to customize the default store file settings, or even override the default store settings to either point to different file location, or write to an mstore or database.



The `$sys.meta` store may not be reconfigured to use the mstore type.

Configuring Multiple Stores

This section describes the basic steps required to configure file-based stores and mstores.

For more information on database store configuration, see [Database Stores](#). Settings for creating and configuring multiple stores are managed in the EMS server, and are transparent to clients. To configure the multiple stores feature, follow these steps:

Procedure

1. Setup and configure stores in the `stores.conf` file.

Stores are created and configured in the `stores.conf` file. Each store must have a unique name. The stores are configured through parameters.

- File-based stores have two required parameters, `type` and `file`, which determine that the store is a file-based store, and set its location and filename. Optional parameters allow you to determine other settings, including how messages are written to the file, the minimum size of the file, and whether the EMS server attempts to truncate the file.
- mstores also have two required parameters, `type` and `file`. Optional parameters configure the scan interval, during which expired and purged messages are removed. See [Understanding mstore Intervals](#) below for information about interval settings.

2. Associate destinations with the configured stores.

Messages are sent to different stores according to their destinations. Destinations are associated with specific stores with the `store` parameter in the `topics.conf` and `queues.conf` files.

File-Based Stores

When using file-based stores, you can also change store associations dynamically using the `setprop topic` or `setprop queue` command in the EMS Administration Tool.

mstores

When using mstores, you cannot dynamically change the mstore associations after they have been set. In order to change a destination's `store` property from a store of the type mstore:

1. Stop the EMS server.

2. Empty the associated mstore of messages from the destination.
3. Change the store association by manually editing the destination's store property in the `topics.conf` or `queues.conf` file.
4. Restart the EMS server.



Once mstores are enabled for a destination, you cannot dynamically change the store property value using `setprop` or `addprop`. To change the store property, you must stop the server, empty the mstore, manually make the change, and restart.



The mstore stores data in multiple files. As a result, mstores cannot operate in out of space conditions. In order to prevent an out of space situation from arising, we recommend ensuring that there is at least twice as much disk space available for the mstore as needed to hold the maximum amount of data that might be stored in it.

Multiple destinations can be mapped to the same store, either explicitly or using wildcards. Even if no stores are configured, the server sends persistent messages that are not associated with a store to default stores. See [Default Store Files](#) for more information.

For details about the store parameter, see [store](#).

Understanding mstore Intervals

The mstore is designed to ensure a quick EMS server start-up time. To enable this functionality, the EMS server must continually monitor the store in the background. The server reads through the mstore incrementally and discards stale data, such as purged and expired messages.

In order to keep the background activity from degrading server performance, the examination is performed in increments. The length of these increments and the amount of data processed each increment are controlled by two parameter settings. These `stores.conf` parameters can be configured for each mstore.

The default parameter settings are optimized for best performance in most production environments (see [mstore Parameters](#) for information about the default values). However, if the amount of data in the mstore grows significantly, the read rates associated with the background activity may begin to affect message transmission rates in the EMS server. If the EMS server performance is negatively affected by the size of the mstore, you can tune the mstore parameter values to spread mstore background activity over a longer period of time, thereby decreasing the associated read rates.

- [scan_target_interval](#) — the maximum amount of time allowed before each message in the store is examined.

For example, if the `scan_target_interval` is 24 hours, each section of the mstore will be examined at least once every day. Because purged and expired messages are not removed from the mstore until they are examined by this background process, this means that it can take up to 24 hours before a message is removed from the queue following a purge command (making underlying storage space available for re-use).

- [scan_iter_interval](#) — the length of time between each increment of background activity.

For example, if the `scan_iter_interval` is 10 seconds, the EMS server begins examining a new section of the mstore every 10 seconds. The amount of data read in each increment is dependent on the total size of the store and the length of the `scan_target_interval`. The server must examine enough data in each interval to fully traverse the store within the target interval.

Example

For example, assume that `scan_iter_interval` is 10 seconds, `scan_target_interval` is 1 day (86,400 seconds), and the mstore contains 9 GBs of data. Every 10 seconds, the EMS server will examine about 1 MB of data. This produces an average read rate of about 100 KB/sec, which is unlikely to produce performance degradation with most modern storage mediums.

If EMS server performance does slow, you may need to increase the `scan_target_interval` value in order to spread the background activity over longer period of time. You can monitor the settings for problems using the `show store` command and checking the ratio of "Discard scan bytes" to "Discard scan interval". For best results, this ratio should be kept below 20% of the disk processing capacity for each mstore. Consider this ratio in relation to your storage medium's overall data transfer capacity, so as to make sure that the background activity does not occupy an excessive amount of the system's resources.

Implications for Statistics

The background monitoring and cleanup that occurs in the mstore also affect some key server statistics. Before the first scan has been completed, some message statistics may be underreported due to purged and expired messages that the server has not yet removed. Until the first background scan is complete for some or all mstores, the server may not have an accurate messages count.

For example, when the EMS server first starts, the "Pending Messages" and "Pending Message Size" counts reported by the `info` command in the administration tool can be understated, because the command only reports on messages it has scanned before the command is issued. Similarly, the "Message Count" and "Message Size" reported by the `show store` command may report a smaller number than actually exist in the store.

Once the first scan is complete, these counts can be considered accurate. To check the scan status on an mstore, use the `show store` command. The statistics returned now include a "First scan finished" field, which reports the scan status since the last EMS server start time. When the value of this field is `true`, the server statistics can be considered accurate.

If it is important to acquire the correct values for these statistics sooner, you will need to decrease the `scan_target_interval`.

mstore Formats

mstore files come in different formats:

- 8.1 format — The legacy mstore format. This is the only format that an EMS 8.1 or earlier server accepts.
- 8.2 format — This is the default format created by all EMS servers from version 8.2 and later. This format provides faster performances than the 8.1 format and supports no-limit `compact`. When an 8.1 or earlier mstore is opened for the first time by an EMS 8.2 or later server, it is automatically converted to this format.
- 8.3 format — This format is compatible with the time-bound `compact` and the `mstore_truncate` property. Note that an EMS 8.3 or later server does *not* automatically create or convert mstores to the 8.3 format. You must convert an older mstore to 8.3 using the `tibemsdbconvert` tool.

tibemsdbconvert Tool

The `tibemsdbconvert` tool, which is available in the `EMS_HOME/bin` directory, converts mstore files from one format to another. It has the following syntax:

```
tibemsdbconvert -file mstore-file -version format
```

where *mstore-file* is the location and file name of your existing mstore file, and *format* is one of the following:

- 8.3 to convert the file to the 8.3 format.
- 8.2 to revert to the 8.2 format.
- 8.1 to revert to the 8.1 mstore format, which is compatible with older versions of the EMS server.

Character Encoding in Messages

Character encodings are named sets of numeric values for representing characters. For example, ISO 8859-1, also known as Latin-1, is the character encoding containing the letters and symbols used by most Western European languages.

If your applications are sending and receiving messages that use only English language characters (that is, the ASCII character set), you do not need to alter your programs to handle different character encodings. The EMS server and application APIs automatically handle ASCII characters in messages.

Character sets become important when your application is handling messages that use non-ASCII characters (such as the Japanese language). Also, clients encode messages by default as UTF-8. Some character encodings use only one byte to represent each character, but UTF-8 can potentially use two bytes to represent the same character. For example, the Latin-1 is a single-byte character encoding. If all strings in your messages contain only characters that appear in the Latin-1 encoding, you can potentially improve performance by specifying Latin-1 as the encoding for strings in the message.

EMS clients can specify a variety of common character encodings for strings in messages. The character encoding for a message applies to strings that appear in any of the following places within a message:

- property names and property values
- `MapMessage` field names and values
- data within the message body

The EMS client APIs (Java, .NET and C) include mechanisms for handling strings and specifying the character encoding used for all strings within a message. The following sections describe the implications of string character encoding for EMS clients.



Nearly all character sets include unprintable characters. EMS software does not prevent programs from using unprintable characters. However, messages containing unprintable characters (whether in headers or data) can cause unpredictable results if you instruct EMS to print them. For example, if you enable the message tracing feature, EMS prints messages to a trace log file.

Supported Character Encodings

Each message contains the name of the character encoding used to encode strings within the message. This character encoding name is one of the canonical names for character encodings contained in the Java specification.

You can obtain a list of canonical character encoding names from the java.sun.com website.

Java and .NET clients use these canonical character encoding names when setting or retrieving the character encoding names.

Sending Messages

When a client sends a message, the message stores the character encoding name used for strings in that message. Java clients represent strings using Unicode. A message created by a Java client that does not specify an encoding will use UTF-8 as the named encoding within the message.

UTF-8 uses up to four bytes to represent each character, so a Java client can improve performance by explicitly using a single-byte character encoding, if possible.

Java clients can globally set the encoding to use with the `setEncoding` method or the client can set the encoding for each message with the `setMessageEncoding` method. For more information about these methods, see the *TIBCO Enterprise Message Service Java API Reference*.

Typically, C clients manipulate strings using the character encoding of the machine on which they are running. The EMS C client library itself does not do any encoding or decoding of characters. When sending a message, an EMS C client application can use `tibemsMsg_SetEncoding` to put information into the message describing the encoding used. When receiving a message in an EMS C client

application, the encoding can be retrieved using `tibemsMsg_GetEncoding`. Use a third party library to do the actual decoding based on the retrieved encoding information.

Message Compression

The TIBCO Enterprise Message Service client can compress the body of a message before sending the message to the server. EMS supports message compression/decompression across client types (Java, C and C#). For example, a Java producer may compress a message and a C consumer may decompress it.

About Message Compression

Message compression is especially useful when messages will be stored on the server (persistent queue messages, or topics with durable subscribers). Setting compression ensures that messages will take less memory space in storage. When messages are compressed and then stored, they are handled by the server in the compressed form. Compression assures that the messages will usually consume less space on disk and will be handled faster by the EMS server.

The compression option only compresses the body of a message. Headers and properties are never compressed. It is best to use compression when the message bodies will be large and the messages will be stored on a server.

When messages will not be stored, compression is not as useful. Compression normally takes time, and therefore the time to send or publish and receive compressed messages is generally longer than the time to send the same messages uncompressed. There is little purpose to message compression for small messages that are not be stored by the server.

Setting Message Compression

Message compression is specified for individual messages. That is, message compression, if desired, is set at the message level. TIBCO Enterprise Message Service does not define a way to set message compression at the per-topic or per-queue level.


To set message compression, the application that sends or publishes the message must access the message properties and set the boolean property `JMS_TIBCO_COMPRESS` to true before sending or publishing the message.

Compressed messages are handled transparently. The client code only sets the `JMS_TIBCO_COMPRESS` property. The client does not need to take any other action. The client automatically decompresses any compressed messages it receives.

Message Acknowledgment

The interface specification for JMS requires that message delivery be guaranteed under many, but not all, circumstances.

The following figure illustrates the basic structure of message delivery and acknowledgment.



The following describes the steps in message delivery and acknowledgment:

1. A message is sent from the message producer to the machine on which the EMS server resides.

2. For persistent messages, the EMS server sends a confirmation to the producer that the message was received.
3. The server sends the message to the consumer.
4. The consumer sends an acknowledgment to the server that the message was received. A session can be configured with a specific session mode that specifies how the consumer-to-server acknowledgment is handled. These session modes are described below.
5. In many cases, the server then sends a confirmation of the acknowledgment to the consumer.

The JMS specification defines three levels of acknowledgment for non-transacted sessions:

- `CLIENT_ACKNOWLEDGE` specifies that the consumer is to acknowledge all messages that have been delivered so far by the session. When using this mode, it is possible for a consumer to fall behind in its message processing and build up a large number of unacknowledged messages.
- `AUTO_ACKNOWLEDGE` specifies that the session is to automatically acknowledge consumer receipt of messages when message processing has finished.
- `DUPS_OK_ACKNOWLEDGE` specifies that the session is to "lazily" acknowledge the delivery of messages to the consumer. "Lazy" means that the consumer can delay acknowledgment of messages to the server until a convenient time; meanwhile the server might redeliver messages. This mode reduces session overhead. Should JMS fail, the consumer may receive duplicate messages.

EMS extends the JMS session modes to include:

- `NO_ACKNOWLEDGE`
- `EXPLICIT_CLIENT_ACKNOWLEDGE`
- `EXPLICIT_CLIENT_DUPS_OK_ACKNOWLEDGE`



The Simplified JMS API introduced in JMS 2.0 supports the session modes defined in the JMS specification: `CLIENT_ACKNOWLEDGE`, `AUTO_ACKNOWLEDGE`, `DUPS_OK_ACKNOWLEDGE`, and `SESSION_TRANSACTED`. However, it does not support the EMS extended session modes.

The session mode is set when creating a Session, as described in [Create a Session](#).

NO_ACKNOWLEDGE

`NO_ACKNOWLEDGE` mode suppresses the acknowledgment of received messages.

After the server sends a message to the client, all information regarding that message for that consumer is eliminated from the server. Therefore, there is no need for the client application to send an acknowledgment to the server about the received message. Not sending acknowledgments decreases the message traffic and saves time for the receiver, therefore allowing better utilization of system resources.



Sessions created in no-acknowledge receipt mode cannot be used to create durable subscribers.

Also, queue receivers on a queue that is routed from another server are not permitted to specify `NO_ACKNOWLEDGE` mode.

EXPLICIT_CLIENT_ACKNOWLEDGE

`EXPLICIT_CLIENT_ACKNOWLEDGE` is like `CLIENT_ACKNOWLEDGE` except it acknowledges only the individual message, rather than all messages received so far on the session.

One example of when `EXPLICIT_CLIENT_ACKNOWLEDGE` would be used is when receiving messages and putting the information in a database. If the database insert operation is slow, you may want to use multiple application threads all doing simultaneous inserts. As each thread finishes its insert, it can use `EXPLICIT_CLIENT_ACKNOWLEDGE` to acknowledge only the message that it is currently working on.

EXPLICIT_CLIENT_DUPS_OK_ACKNOWLEDGE

EXPLICIT_CLIENT_DUPS_OK_ACKNOWLEDGE is like DUPS_OK_ACKNOWLEDGE except it 'lazily' acknowledges only the individual message, rather than all messages received so far on the session.

Message Selectors

A message selector is a string that lets a client program specify a set of messages, based on the values of message headers and properties. A selector *matches* a message if, after substituting header and property values from the message into the selector string, the string evaluates to true. Consumers can request that the server deliver only those messages that match a selector.

The syntax of selectors is based on a subset of the SQL92 conditional expression syntax.

Identifiers

Identifiers can refer to the values of message headers and properties, but not to the message body. Identifiers are case-sensitive.

Basic Syntax

An identifier is a sequence of letters and digits, of any length, that begins with a letter. As in Java, the set of letters includes _ (underscore) and \$ (dollar).

Illegal

Certain names are exceptions, which cannot be used as identifiers. In particular, NULL, TRUE, FALSE, NOT, AND, OR, BETWEEN, LIKE, IN, IS, and ESCAPE are defined to have special meaning in message selector syntax.

Value

Identifiers refer either to message header names or property names. The type of an identifier in a message selector corresponds to the type of the header or property value. If an identifier refers to a header or property that does not exist in a message, its value is NULL.

Literals

String Literal

A string literal is enclosed in single quotes. To represent a single quote within a literal, use two single quotes; for example, 'literal' 's'. String literals use the Unicode character encoding. String literals are case sensitive. The server has a limit of 32,767 string literals in a selector string.

Exact Numeric Literal

An exact numeric literal is a numeric value without a decimal point, such as 57, -957, and +62; numbers of long are supported.

Approximate Numeric Literal

An approximate numeric literal is a numeric value with a decimal point (such as 7., -95.7, and +6.2), or a numeric value in scientific notation (such as 7E.3 and -57.9E2); numbers in the range of double are supported. Approximate literals use floating-point literal syntax of the Java programming language.

Boolean Literal

The boolean literals are TRUE and FALSE (case insensitive).

Internal computations of expression values use a 3-value boolean logic similar to SQL. However, the final value of an expression is always either TRUE or FALSE, but never UNKNOWN.

Expressions

Selectors as Expressions

Every selector is a conditional expression. A selector that evaluates to `true` matches the message; a selector that evaluates to `false` or `unknown` does not match.

Arithmetic Expression

Arithmetic expressions are composed of numeric literals, identifiers (that evaluate to numeric literals), arithmetic operations, and smaller arithmetic expressions.

Conditional Expression

Conditional expressions are composed of comparison operations, logical operations, and smaller conditional expressions.

Order of Evaluation

Order of evaluation is left-to-right, within precedence levels. Parentheses override this order.

Operators

Case Insensitivity

Operator names are case-insensitive.

Logical Operators

Logical operators in precedence order: NOT, AND, OR.

Comparison Operators

Comparison operators: `=`, `>`, `>=`, `<`, `<=`, `<>` (not equal).

These operators can compare only values of comparable types. (Exact numeric values and approximate numerical values are comparable types.) Attempting to compare incomparable types yields `false`. If either value in a comparison evaluates to `NULL`, then the result is `unknown` (in SQL 3-valued logic).

Comparison of string values is restricted to `=` and `<>`. Two strings are equal if and only if they contain the same sequence of characters.

Comparison of boolean values is restricted to `=` and `<>`.

Arithmetic Operators

Arithmetic operators in precedence order:

- `+`, `-` (unary)
- `*`, `/` (multiplication and division)
- `+`, `-` (addition and subtraction)

Arithmetic operations obey numeric promotion rules of the Java programming language.

Between Operator

arithmetic-expr1 [NOT] BETWEEN *arithmetic-expr2* AND *arithmetic-expr3*

The BETWEEN comparison operator includes its endpoints. For example:

- `age BETWEEN 5 AND 9` is equivalent to `age >= 5 AND age <= 9`
- `age NOT BETWEEN 5 AND 9` is equivalent to `age < 5 OR age > 9`

String Set Membership

identifier [NOT] IN (*string-literal1*, *string-literal2*, ...)

The *identifier* must evaluate to either a string or `NULL`. If it is `NULL`, then the value of this expression is `unknown`. You can use a maximum of 32,767 string-literals in the string set.

Pattern Matching

identifier [NOT] LIKE *pattern-value* [ESCAPE *escape-character*]

The *identifier* must evaluate to a string.

The *pattern-value* is a string literal, in which some characters bear special meaning:

- `_` (underscore) can match any single character.
- `%` (percent) can match any sequence of zero or more characters.
- *escape-character* preceding either of the special characters changes them into ordinary characters (which match only themselves).

Null Header or Property

identifier IS NULL

This comparison operator tests whether a message header is null, or a message property is absent.

identifier IS NOT NULL

This comparison operator tests whether a message header or message property is non-null.

White Space

White space is any of the characters space, horizontal tab, form feed, or line terminator—or any contiguous run of characters in this set.

Performance

In order to efficiently handle queue consumers with a selector when there is a large backlog of messages in the queue, message headers and properties are cached in the memory of the server for the queue. The caching begins for a given queue the first time a queue consumer with a selector is created.

This may result in an increase of the memory footprint of the server when such queue consumers are created. Both new incoming messages and messages already existing in the backlog are optimized through the server cache. If the server is restarted and a fault tolerant consumer on the queue is restored, then all recovered messages in that queue are optimized.

Data Type Conversion

The following table summarizes legal data type conversions. The symbol X in the following table indicates that a value written into a message as the row type can be extracted as the column type. This table applies to all message values—including map pairs, headers and properties except as noted below.

	bool	byte	short	char	int	long	float	double	string	byte[]
bool	X								X	
byte		X	X		X	X			X	
short			X		X	X			X	
char				X					X	
int					X	X			X	
long						X			X	
float							X	X	X	
double								X	X	

	bool	byte	short	char	int	long	float	double	string	byte[]
string	X	X	X		X	X	X	X	X	
byte[]										X



- Message properties cannot have byte array values.
- Values written as strings can be extracted as a numeric or boolean type only when it is possible to parse the string as a number of that type.

Sending Messages Synchronously and Asynchronously

TIBCO Enterprise Message Service supports two modes of sending messages:

- **Synchronous** sending blocks the application thread until the entire send is complete.
- **Asynchronous** sending offloads the notification of the success or failure to another thread, thereby increasing performance in certain situations.

Each sending mode has certain benefits. The following sections describe the benefits of the different modes.

Sending Synchronously

Because synchronous sending does not have the overhead involved in asynchronous sending, it yields better performance in most cases. Synchronous sending is also the best choice when sending the following types of messages:

- **Non-Persistent Messages**

When high performance is a concern, use synchronous sending for non-persistent or reliable messages. Although asynchronous sending of non-persistent messages is supported, it is generally not recommended.

- **Transactions**

Typically, it makes sense for applications to use synchronous sending when using transactions. Sending messages within a transaction does not require a response from the server, so higher throughput can be obtained sending synchronously within a transaction.

Synchronous sending simplifies a transaction; coordination of asynchronous send notifications and committing or rolling back a transaction introduces complexity to the application.

See [Send Messages](#) for details.

Sending Asynchronously

The message producer can send messages asynchronously by registering a *completion listener* to monitor message send success or failure.

Operating in a thread separate from that of the message producer, the completion listener manages the response to a successful or failed send, leaving the message producer free to perform other operations. See [Create a Completion Listener for Asynchronous Sending](#) for details.

Asynchronous sending can increase performance in certain circumstances. One of the best uses for asynchronous sending is when sending persistent messages. High level outgoing message throughput can be obtained when sending non-transacted persistent messages.

There are other considerations for the application programmer when sending messages asynchronously. These considerations are described below.

Concurrent Message Use

For simplicity, it is suggested that application programmers create a new message for every asynchronous send call. If concurrent message use is acceptable in an application, messages may be reused when sending asynchronously, but generally it is not recommended due to the complexity it may add.



During asynchronous sends, the application programmer should be very aware of concurrent message usage between the application and the thread handling completion listeners. The message passed to the completion listener is the same message passed to the MessageProducer send method, which means modification of that particular message is reflected in both the application thread and the thread invoking the completion listener.

For example, if a TextMessage is asynchronously sent with the text of `foo`, and then the same message object's text is subsequently set to `bar`, it is conceivable that when the completion listener is invoked the message will contain `bar` even though it contained `foo` at the time it was sent.

Memory Use

Application programmers should be aware that some additional memory is used by the EMS server when asynchronously sending. Memory use increases if the performance of completion listeners is slower than overall application send rates.

Fault Tolerant Failovers

Because send notifications are handled in a separate thread when messages are sent asynchronously, it is possible to receive messages out of order after a fault tolerant switch.

For example, consider an application that sends messages A, B, and C. Message A succeeds, Message B fails, but message C succeeds immediately after reconnect to the fault tolerant server. The application may not know message B failed before message C was sent. Message consumers could conceivably receive messages in the order of A, C, B; it is up to the application to appropriately handle this situation.

Receiving Messages Synchronously and Asynchronously

The EMS APIs allow for both synchronous or asynchronous message consumption. For synchronous consumption, the message consumer explicitly invokes a receive call on the topic or queue.

When synchronously receiving messages, the consumer remains blocked until a message arrives. See [Receive Messages](#) for details.

The consumer can receive messages asynchronously by registering a *message listener* to receive the messages. When a message arrives at the destination, the message listener delivers the message to the message consumer. The message consumer is free to do other operations between messages. See [Create a Message Listener for Asynchronous Message Consumption](#) for details.

Destinations

Destinations for messages can be either Topics or Queues. A destination can be created statically in the server configuration files, or dynamically by a client application.

Servers connected by routes exchange messages sent to temporary topics. As a result, temporary topics are ideal destinations for reply messages in request/reply interactions.

Destination Overview

The following table summarizes the differences between static, dynamic, and temporary destinations. The sections that follow provide more detail.

Aspect	Static	Dynamic	Temporary
Purpose	Static destinations let administrators configure EMS behavior at the enterprise level. Administrators define these administered objects, and client programs use them—relieving program developers and end users of the responsibility for correct configuration.	Dynamic destinations give client programs the flexibility to define destinations as needed for short-term use.	Temporary destinations are ideal for limited-scope uses, such as reply subjects.
Scope of Delivery	Static destinations support concurrent use. That is, several client processes (and in several threads within a process) can create local objects denoting the destination, and consume messages from it.	Dynamic destinations support concurrent use. That is, several client processes (and in several threads within a process) can create local objects denoting the destination, and consume messages from it.	Temporary destinations support only local use. That is, only the client connection that created a temporary destination can consume messages from it. However, servers connected by routes do exchange messages sent to temporary topics.
Creation	Administrators create static destinations using EMS server administration tools or API.	Client programs create dynamic destinations, if permitted by the server configuration.	Client programs create temporary destinations.
Lookup	Client programs lookup static destinations by name. Successful lookup returns a local object representation of the destination.	Not applicable.	Not applicable.

Aspect	Static	Dynamic	Temporary
Duration	A static destination remains in the server until an administrator explicitly deletes it.	<p>A dynamic destination remains in the server as long as at least one client actively uses it. The server automatically deletes it (at a convenient time) when all applicable conditions are true:</p> <ul style="list-style-type: none"> • Topic or Queue All client programs that access the destination have disconnected. • Topic No offline durable subscribers exist for the topic. • Queue Queue, no messages are stored in the queue. 	A temporary destination remains in the server either until the client that created it explicitly deletes it, or until the client disconnects from the server.

Destination Names

A destination name is a string divided into elements, each element separated by the dot character (.). The dot character allows you to create multi-part destination names that categorize destinations.

For example, you could have an accounting application that publishes messages on several destinations. The application could prefix all messages with ACCT, and each element of the name could specify a specific component of the application. ACCT.GEN_LEDGER.CASH, ACCT.GEN_LEDGER.RECEIVABLE, and ACCT.GEN_LEDGER.MISC could be subjects for the general ledger portion of the application.

Separating the subject name into elements allows applications to use wildcards for specifying more than one subject. See [Wildcards](#) for more information. The use of wildcards in destination names can also be used to define "parent" and "child" destination relationships, where the child destinations inherit the properties from its parents. See [Inheritance of Properties](#).

Static Destinations

Configuration information for static destinations is stored in configuration files for the EMS server. Changes to the configuration information can be made in a variety of ways. To manage static destinations, you can edit the configuration files using a text editor, you can use the administration tool, or you can use the administration APIs.

Clients can obtain references to static destinations through a naming service such as JNDI or LDAP. See [Creating and Modifying Destinations](#) for more information about how clients use static destinations.

Dynamic Destinations

Dynamic destinations are created on-the-fly by the EMS server, as required by client applications. Dynamic destinations do not appear in the configuration files and exist as long as there are messages or consumers on the destination. A client cannot use JNDI to lookup dynamic queues and topics.

When you use the [show queues](#) or [show topics](#) command in the administration tool, you see dynamic topics and queues have an asterisk (*) in front of their name in the list of topics or queues. If a

property of a queue or topic has an asterisk (*) character in front of its name, it means that the property was inherited from the parent queue or topic and cannot be changed.

See [Dynamically Create Topics and Queues](#) for details on topics and queues can be dynamically created by the EMS server.

Temporary Destinations

TIBCO Enterprise Message Service supports temporary destinations as defined in JMS specification and its API.

Servers connected by routes exchange messages sent to temporary topics. As a result, temporary topics are ideal destinations for reply messages in request/reply interactions.

For more information on temporary queues and topics, refer to the JMS documentation described in [Third Party Documentation](#).

Destination Bridges

You can create server-based bridges between destinations of the same or different types to create a hybrid messaging model for your application. This allows all messages delivered to one destination to also be delivered to the bridged destination. You can bridge between different destination types, between the same destination type, or to more than one destination. For example, you can create a bridge between a topic and a queue or from a topic to another topic.

See [Destination Bridges](#) for more information about destination bridging.

Destination Name Syntax

TIBCO Enterprise Message Service places few restrictions on the syntax and interpretation of destination names. System designers and developers have the freedom to establish their own conventions when creating destination names. The best destination names reflect the structure of the data in the application itself.

Structure

A destination name is a string divided into elements, each element separated by the dot character (.). The dot character allows you to create multi-part destination names that categorize destinations.

Empty strings ("") are not permitted in destination names. Likewise, elements cannot incorporate the dot character by using an escape sequence.

Although they are not prohibited, we recommend that you do not use tabs, spaces, or any unprintable character in a destination name. You may, however, use wildcards. See [Wildcards](#) for more information.

Length

Destinations are limited to a total length of 249 characters. However, some of that length is reserved for internal use. The amount of space reserved for internal use varies according to the number of elements in the destination; destinations that include the maximum number of elements are limited to 196 characters.

A destination can have up to 64 elements. Each element cannot exceed 127 characters. Dot separators are not included in element length.

Destination Name Performance Considerations

When designing destination naming conventions, remember these performance considerations:

- Shorter destination names perform better than long destination names.
- Destinations with several short elements perform better than one long element.

- A set of destinations that differ early in their element lists perform better than subjects that differ only in the last element.

Special Characters in Destination Names

These characters have special meanings when used in destination names:

Char	Char Name	Special Meaning
.	Dot	Separates elements within a destination name.
>	Greater-than	Wildcard character, matches one or more trailing elements.
*	Asterisk	Wildcard character, matches one element.

For more information on wildcard matching, see [Wildcards * and >](#).

Examples of Destination Names

These examples illustrate the syntax for destination names.

Examples of Destination Names
Valid Examples
<code>NEWS.LOCAL.POLITICS.CITY_COUNCIL</code>
<code>NEWS.NATIONAL.ARTS.MOVIES.REVIEWS</code>
<code>CHAT.MRKTG.NEW_PRODUCTS</code>
<code>CHAT.DEVELOPMENT.BIG_PROJECT.DESIGN</code>
<code>News.Sports.Baseball</code>
<code>finance</code>
<code>This.long.subject_name.is.valid.even.though.quite.uninformative</code>
Invalid Examples
<code>News..Natural_Disasters.Flood</code> (null element)
<code>WRONG.</code> (null element)
<code>.TRIPLE.WRONG..</code> (three null elements)
<code>News.Tennis.Stats.Roger\Federer</code> (backslash in the element Roger will be included in the element name, and will not escape the dot)

Destination Properties

The following section contain a description of properties for topics and queues.

You can set the destination properties directly in the [topics.conf](#) or [queues.conf](#) file or by means of the [setprop topic](#) or [setprop queue](#) command in the EMS Administration Tool.

The following table lists the properties that can be assigned to topics and queues. The sections that follow describe each property.

Property	Topic	Queue
<code>exclusive</code>	No	Yes
<code>expiration</code>	Yes	Yes
<code>export</code>	Yes	No
<code>flowControl</code>	Yes	Yes
<code>global</code>	Yes	Yes
<code>import</code>	Yes	Yes
<code>maxbytes</code>	Yes	Yes
<code>maxmsgs</code>	Yes	Yes
<code>maxRedelivery</code>	No	Yes
<code>overflowPolicy</code>	Yes	Yes
<code>prefetch</code>	Yes	Yes
<code>redeliveryDelay</code>	No	Yes
<code>secure</code>	Yes	Yes
<code>sender_name</code>	Yes	Yes
<code>sender_name_enforced</code>	Yes	Yes
<code>store</code>	Yes	Yes
<code>trace</code>	Yes	Yes

exclusive

The `exclusive` property is available for queues only (not for topics), and cannot be used with global queues.

When `exclusive` is set for a queue, the server sends all messages on that queue to one consumer. No other consumers can receive messages from the queue. Instead, these additional consumers act in a *standby* role; if the primary consumer fails, the server selects one of the standby consumers as the new primary, and begins delivering messages to it.

You can set `exclusive` using the form:

```
exclusive
```

Non-Exclusive Queues & Round-Robin Delivery

By default, `exclusive` is not set for queues and the server distributes messages in a round-robin—one to each receiver that is ready. If any receivers are still ready to accept additional messages, the server distributes another round of messages—one to each receiver that is still ready. When none of the

receivers are ready to receive more messages, the server waits until a queue receiver reports that it can accept a message.

This arrangement prevents a large buildup of messages at one receiver and balances the load of incoming messages across a set of queue receivers.

expiration

If an expiration property is set for a destination, the server honors the overridden expiration period and retains the message for the length of time specified by the expiration property.

However, the server overrides the [JMSExpiration](#) value set by the producer in the message header with the value 0 and therefore the consuming client does not expire the message.

You can set the expiration property for any queue and any topic using the form:

```
expiration=time[msec|sec|min|hour|day]
```

where *time* is the number of seconds. Zero is a special value that indicates messages to the destination never expire.

You can optionally include time units, such as msec, sec, min, hour or day to describe the *time* value as being in milliseconds, seconds, minutes, hours, or days, respectively. For example:

```
expiration=10min
```

means 10 minutes.

When a message expires it is either destroyed or, if the [JMS_TIBCO_PRESERVE_UNDELIVERED](#) property on the message is set to true, the message is placed on the undelivered queue so it can be handled by a special consumer. See [Undelivered Message Queue](#) for details.

All machines running EMS servers must be synchronized using NTP. Machines running EMS clients do not need to be synchronized. For information about how non-synchronized client machines are handled, refer to the [clock_sync_interval](#) parameter.

export

The export property allows messages published by a client to a topic to be exported to the external systems with configured transports.

You can set export using the form:

```
export="list"
```

where *list* is one or more transport names, as specified by the *[transport_name]* ids in the [transports.conf](#) file. Multiple transport names in the list are separated by commas.

For example:

```
export="RV1,RV2"
```

You can configure transports for TIBCO FTL, SmartSockets, or Rendezvous reliable and certified messaging protocols. You can specify the name of one or more transports of the same type in the export property.

You must purchase, install, and configure the external system (for example, Rendezvous) before configuring topics with the export property. Also, you must configure the communication parameters to the external system by creating a named transport in the [transports.conf](#) file.

For complete details about external message services, see:

- [Interoperation with TIBCO FTL](#)
- [Interoperation with TIBCO Rendezvous](#)
- [Interoperation with TIBCO SmartSockets](#)

flowControl

The `flowControl` property specifies the target maximum size the server can use to store pending messages for the destination. Should the number of messages exceed the maximum, the server will slow down the producers to the rate required by the message consumers.

This is useful when message producers send messages much more quickly than message consumers can consume them. Unlike the behavior established by the `overflowPolicy` property, `flowControl` never discards messages or generates errors back to producer.

You can set `flowControl` using the form:

```
flowControl=size[KB|MB|GB]
```

where *size* is the maximum number of bytes of storage for pending messages of the destination. If you specify the `flowControl` property without a value, the target maximum is set to 256KB.

You can optionally include a KB, MB or GB after the number to specify kilobytes, megabytes, or gigabytes, respectively. For example:

```
flowControl=1000KB
```

Means 1000 kilobytes.

The `flow_control` parameter in `tibemsd.conf` file must be set to enabled before the value in this property is enforced by the server. See [Flow Control](#) for more information about flow control.

global

Messages destined for a topic or queue with the `global` property set are routed to the other servers that are participating in routing with this server.

You can set `global` using the form:

```
global
```

For further information on routing between servers, see [Routes](#).

import

The `import` property allows messages published by an external system to be received by a EMS destination (a topic or a queue), as long as the transport to the external system is configured.

You can set `import` using the form:

```
import="list"
```

where *list* is one or more transport names, as specified by the `[NAME]` ids in the `transports.conf` file. Multiple transport names in the list are separated by commas. For example:

```
import="RV1,RV2"
```

You can configure transports for TIBCO FTL, TIBCO SmartSockets, or TIBCO Rendezvous reliable and certified messaging protocols. You can specify the name of one or more transports of the same type in the `import` property.

You must purchase, install, and configure the external system (for example, Rendezvous) before configuring topics with the `import` property. Also, you must configure the communication parameters to the external system by creating a named transport in the `transports.conf` file.

For complete details about external message services, see:

- [Interoperation with TIBCO FTL](#)
- [Interoperation with TIBCO Rendezvous](#)
- [Interoperation with TIBCO SmartSockets](#)

maxbytes

Topics and queues can specify the `maxbytes` property in the form:

```
maxbytes=value[KB|MB|GB]
```

where *value* is the number of bytes. For example:

```
maxbytes=1000
```

Means 1000 bytes.

You can optionally include a KB, MB or GB after the number to specify kilobytes, megabytes, or gigabytes, respectively. For example:

```
maxbytes=1000KB
```

Means 1000 kilobytes.

For queues, `maxbytes` defines the maximum size (in bytes) that the queue can store, summed over all messages in the queue. Should this limit be exceeded, messages will be rejected by the server and the message producer send calls will return an error (see also [overflowPolicy](#)). For example, if a receiver is off-line for a long time, then the queue size could reach this limit, which would prevent further memory allocation for additional messages.

If `maxbytes` is zero, or is not set, the server does not limit the memory allocation for the queue.

You can set both `maxmsgs` and `maxbytes` properties on the same queue. Exceeding either limit causes the server to reject new messages until consumers reduce the queue size to below these limits.



If the `maxbytes` limit is not set on a destination, the server still checks to see if that destination's memory footprint is growing beyond a threshold. If so, a warning is logged. For more details, see [large_destination_memory](#) and [large_destination_count](#).

For topics, `maxbytes` limits the maximum size (in bytes) that the topic can store for delivery to each durable or non-durable online subscriber on that topic. That is, the limit applies separately to each subscriber on the topic. For example, if a durable subscriber is off-line for a long time, pending messages accumulate until they exceed `maxbytes`; when the subscriber consumes messages (freeing storage) the topic can accept additional messages for the subscriber. For a non-durable subscriber, `maxbytes` limits the number of pending messages that can accumulate while the subscriber is online.



Under certain conditions, because of the pipelined nature of message processing or the requirements of transactional messaging, the `maxbytes` limit can be slightly exceeded. You may see message totals that are marginally larger than the set limit.

When a destination inherits different values of this property from several parent destinations, it inherits the smallest value.



You can further protect against consumers that receive messages without acknowledging them using the parameter [disconnect_non_acking_consumers](#).

maxmsgs

Topics and queues can specify the `maxmsgs` property in the form:

```
maxmsgs=value
```

where *value* defines the maximum number of messages that can be waiting in a queue. When adding a message would exceed this limit, the server does not accept the message into storage, and the message producer's send call returns an error (but see also [overflowPolicy](#)).

If `maxmsgs` is zero, or is not set, the server does not limit the number of messages in the queue.



If the `maxmsgs` limit is not set on a destination, the server still checks to see if that destination's memory footprint is growing beyond a threshold. If so, a warning is logged. For more details, see [large_destination_memory](#) and [large_destination_count](#).

You can set both `maxmsgs` and `maxbytes` properties on the same queue. Exceeding either limit causes the server to reject new messages until consumers reduce the queue size to below these limits.



Under certain conditions, because of the pipelined nature of message processing or the requirements of transactional messaging, the `maxmsgs` limit can be slightly exceeded. You may see message totals that are marginally larger than the set limit.



You can further protect against consumers that receive messages without acknowledging them using the parameter `disconnect_non_acking_consumers`.

maxRedelivery

The `maxRedelivery` property specifies the number of attempts the server should make to deliver a message sent to a queue.

Set `maxRedelivery` using the form:

```
maxRedelivery=count
```

where `count` is an integer between 2 and 255 that specifies the maximum number of times a message can be delivered to receivers. A value of zero disables `maxRedelivery`, so there is no maximum.

Once the server has attempted to deliver the message the specified number of times, the message is either destroyed or, if the `JMS_TIBCO_PRESERVE_UNDELIVERED` property on the message is set to true, the message is placed on the undelivered queue so it can be handled by a special consumer. See [Undelivered Message Queue](#) for details.

For messages that have been redelivered, the `JMSRedelivered` header property is set to true and the `JMSXDeliveryCount` property is set to the number of times the message has been delivered to the queue. If the server restarts, the current number of delivery attempts in the `JMSXDeliveryCount` property is not retained.



In the event of an abrupt exit by the client, the `maxRedelivery` count can be mistakenly incremented. An abrupt exit prevents the client from communicating with the server; for example, when the client exits without closing the connection or when the client application crashes. If a client application exits abruptly, the EMS server counts all messages sent to the client as delivered, even if they were not presented to the application.

overflowPolicy

Topics and queues can specify the `overflowPolicy` property to change the effect of exceeding the message capacity established by either `maxbytes` or `maxmsgs`.

Set the `overflowPolicy` using the form:

```
overflowPolicy=default|discardOld|rejectIncoming
```

If `overflowPolicy` is not set, then the policy is default.

The effect of `overflowPolicy` on the `maxbytes` and `maxmsgs` behaviors differs depending on whether you set it on a topic or a queue, so the impact of each `overflowPolicy` value is described separately for topics and queues.

If wildcards are used in the `.conf` file the inheritance of the `overflowPolicy` policy from multiple parents works as follows:

- If a child destination has a non-default `overflowPolicy` policy set, then that policy is used and it does not inherit any conflicting policy from a parent.
- If a parent has `OVERFLOW_REJECT_INCOMING` set, then it is inherited by the child destination over any other policy.
- If no parent has `OVERFLOW_REJECT_INCOMING` set and a parent has `OVERFLOW_DISCARD_OLD` policy set, then that policy is inherited by the child destination.
- If no parent has the `OVERFLOW_REJECT_INCOMING` or `OVERFLOW_DISCARD_OLD` set, then the default policy is used by the child destination.

default

For topics, `default` specifies that messages are sent to each subscriber in turn. If the `maxbytes` or `maxmsgs` setting has been reached for a subscriber, that subscriber does not receive the message. No error is returned to the message producer.

For queues, `default` specifies that new messages are rejected by the server and an error is returned to the producer if the established `maxbytes` or `maxmsgs` value has been exceeded.



When delivery delay is enabled for a topic, the behavior of `overflowPolicy=default` mimics that of a queue. That is, when `maxbytes` or `maxmsgs` has been reached, new messages are rejected by the server and an error is returned to the producer.

discardOld

For topics, `discardOld` specifies that, if any of the subscribers have an outstanding number of undelivered messages on the server that are over the message limit, the oldest messages are discarded before they are delivered to the subscriber.

The `discardOld` setting impacts subscribers individually. For example, you might have three subscribers to a topic, but only one subscriber exceeds the message limit. In this case, only the oldest messages for the one subscriber are discarded, while the other two subscribers continue to receive all of their messages.

When messages for a topic or queue exceed the `maxbytes` or `maxmsgs` value, the oldest messages are silently discarded. No error is returned to the producer.

rejectIncoming

For topics, `rejectIncoming` specifies that, if *any* of the subscribers have an outstanding number of undelivered messages on the server that are over the message limit, all new messages are rejected and an error is returned to the producer.

For queues, `rejectIncoming` specifies that, if messages on the queue have exceeded the `maxbytes` or `maxmsgs` value, all new messages are rejected and an error is returned to the producer. (This is the same as the `default` behavior.)

Examples

To discard messages on `myQueue` when the number of queued messages exceeds 1000, enter:

```
setprop queue myQueue maxmsgs=1000,overflowPolicy=discardOld
```

To reject all new messages published to `myTopic` when the memory used by undelivered messages for any of the topic subscribers exceeds 100KB, enter:

```
setprop topic myTopic maxbytes=100KB,overflowPolicy=rejectIncoming
```

prefetch

The message consumer portion of a client and the server cooperate to regulate fetching according to the `prefetch` property. The `prefetch` property applies to both topics and queues.

You can set `prefetch` using the form:

```
prefetch=value
```

where *value* is one of the values in [prefetch Values](#).

prefetch Values

The following table lists values used with the `prefetch` property.

Value	Description
2 or more	The message consumer automatically fetches messages from the server. The message consumer never fetches more than the number of messages specified by <i>value</i> . See Automatic Fetch Enabled for details.
1	The message consumer automatically fetches messages from the server—initiating fetch only when it does not currently hold a message.
none	Disables automatic fetch. That is, the message consumer initiates fetch only when the client calls <code>receive</code> —either an explicit synchronous call, or an implicit call (in an asynchronous consumer). This value cannot be used with topics or global queues. See Automatic Fetch Disabled for details.
0	The destination inherits the <code>prefetch</code> value from a parent destination with a matching name. If it has no parent, or no destination in the parent chain sets a value for <code>prefetch</code> , then the default value is 5 queues and 64 for topics. When a destination does not set any value for <code>prefetch</code> , then the default value is 0 (zero; that is, inherit the <code>prefetch</code> value). See Inheritance for details.



If both `prefetch` and [maxRedelivery](#) are set to a non-zero value, then there is a potential to lose prefetched messages if one of the messages exceeds the `maxRedelivery` limit. For example, `prefetch=5` and `maxRedelivery=4`. The first message is redelivered 4 times, hits the `maxRedelivery` limit and is sent to the undelivered queue (as expected). However, the other 4 pre-fetched messages are also sent to the undelivered queue and are not processed by the receiving application. The work around is to set `prefetch=none`, but this can have performance implications on large volume interfaces.

Background

Delivering messages from the server destination to a message consumer involves two independent phases—fetch and accept.

- The *fetch* phase is a two-step interaction between a message consumer and the server.
 - The message consumer initiates the fetch phase by signaling to the server that it is ready for more messages.
 - The server responds by transferring one or more messages to the client, which stores them in the message consumer.
- In the *accept* phase, client code takes a message from the message consumer.

The `receive` call embraces both of these phases. It initiates fetch when needed and it accepts a message from the message consumer.

To reduce waiting time for client programs, the message consumer can *prefetch* messages—that is, fetch a batch of messages from the server, and hold them for client code to accept, one by one.

acl.conf

This file defines all permissions on topics and queues for all users and groups.

The format of the file is:

```
TOPIC=topic USER=user PERM=permissions
TOPIC=topic GROUP=group PERM=permissions
QUEUE=queue USER=user PERM=permissions
QUEUE=queue GROUP=group PERM=permissions
ADMIN USER=user PERM=permissions
ADMIN GROUP=group PERM=permissions
```

Parameter Name	Description
TOPIC	Name of the topic to which you wish to add permissions.
QUEUE	Name of the queue to which you wish to add permissions.
ADMIN	Specifies that you wish to add administrator permissions.
USER	Name of the user to whom you wish to add permissions.
GROUP	Name of the group to which you wish to add permissions. The designation <code>all</code> specifies a predefined group that contains all users.
PERM	<p>Permissions to add.</p> <p>The permissions which can be assigned to queues are <code>send</code>, <code>receive</code> and <code>browse</code>. The permissions which can be assigned to topics are <code>publish</code>, <code>subscribe</code> and <code>durable</code> and <code>use_durable</code>. The designation <code>all</code> specifies all possible permissions. For information about these permissions, refer to When Permissions Are Checked and Inheritance of Permissions.</p> <p>Administration permissions are granted to users to perform administration activities. See Administrator Permissions for more information about administration permissions.</p>

Example

```
ADMIN USER=sys-admins PERM=all
TOPIC=foo USER=user2 PERM=publish,subscribe
TOPIC=foo GROUP=group1 PERM=subscribe
```

Automatic Fetch Enabled

To enable automatic fetch, set `prefetch` to a positive integer. Automatic fetch ensures that if a message is available, then it is waiting when client code is ready to accept one. It can improve performance by decreasing or eliminating client idle time while the server transfers a message.

However, when a queue consumer prefetches a group of messages, the server does not deliver them to other queue consumers (unless the first queue consumer's connection to the server is broken).



A positive `prefetch` must be configured in order to use `receiveNoWait` function calls.

Automatic Fetch Disabled

To disable automatic fetch, set `prefetch=none`.

Even when `prefetch=none`, a queue consumer can still hold a message. For example, a `receive` call initiates fetch, but its timeout elapses before the server finishes transferring the message. This situation leaves a fetched message waiting in the message consumer. A second `receive` call does not fetch another message; instead, it accepts the message that is already waiting. A third `receive` call initiates another fetch.

Notice that a waiting message still belongs to the queue consumer, and the server does not deliver it to another queue consumer (unless the first queue consumer's connection to the server is broken). To prevent messages from waiting in this state for long periods of time, code programs either to call `receive` with no timeout, or to call it (with timeout) repeatedly and shorten the interval between calls.



Automatic fetch cannot be disabled for global queues or for topics.

Inheritance

When a destination inherits the `prefetch` property from parent destination with matching names, these behaviors are possible:

- When all parent destinations set the value `none`, then the child destination inherits the value `none`.
- When any parent destination sets a non-zero numeric value, then the child destination inherits the *largest* value from among the entire parent chain.
- When none of the parent destinations sets any non-zero numeric value, then the child destination uses the default value (which is 5).

redeliveryDelay

When `redeliveryDelay` is set, the EMS server waits the specified interval before returning an unacknowledged message to the queue.

When a previously delivered message did not receive a successful acknowledgment, the EMS server waits the specified redelivery delay before making the message available again in the queue. This is most likely to occur in the event of a transaction rollback, session or message recovery, session or connection close, or the abrupt exit of a client application. However, note that the delay time is not exact, and in most situations will exceed the specified `redeliveryDelay`.



The redelivery delay is not available for routed queues.

The value can be specified in seconds, minutes, or hours. The value may be in the range of 15 seconds and 8 hours.

You can set `redeliveryDelay` using the form:

```
redeliveryDelay=time[sec|min|hour]
```

where *time* is the number of seconds. Zero is a special value that indicates no redelivery delay.

You can optionally include time units, such as `sec`, `min`, or `hour` describe the *time* value as being in seconds, minutes, or hours, respectively. For example:

```
redeliveryDelay=30min
```

specifies a redelivery delay of 30 minutes.

During the delay interval, messages are placed in the `$sys.redelivery.delay` queue. This queue can be browsed, but it cannot be consumed from or purged. However, purging the queue from which the delayed message came, or removing the message using its message ID, immediately removes that message from `$sys.redelivery.delay`.



While a message is on the `$sys.redelivery.delay` queue, it is not on the queue from which it came and so it is not included in statistical message counts. This includes `maxmsgs`, `maxbytes`, `flowControl`, and so on.

secure

When the `secure` property is enabled for a destination, it instructs the server to check user permissions whenever a user attempts to perform an operation on that destination.

You can set `secure` using the form:

```
secure
```

If the `secure` property is not set for a destination, the server does not check permissions for that destination and any authenticated user can perform any operation on that topic or queue.



The `secure` property is independent of SSL—it controls basic authentication and permission verification within the server. To configure secure communication between clients and server, see [SSL Protocol](#).

The server `authorization` property acts as a master switch for checking permissions. That is, the server checks user permissions on secure destinations only when the `authorization` property is enabled. To enforce permissions, you must *both* enable the authorization configuration parameter, and set the `secure` property on each affected destination.

See [Authentication and Permissions](#) for more information on permissions and the `secure` property.

sender_name

The `sender_name` property specifies that the server may include the sender's user name for messages sent to this destination.

You can set `sender_name` using the form:

```
sender_name
```

When the `sender_name` property is enabled, the server takes the user name supplied by the message producer when the connection is established and places that user name into the `JMS_TIBCO_SENDER` property in the message.

The message producer can override this behavior by specifying a property on a message. If a message producer sets the `JMS_TIBCO_DISABLE_SENDER` property to true for a message, the server overrides the `sender_name` property and does not add the sender name to the message.

If authentication for the server is turned off, the server places whatever user name the message producer supplied when the message producer created a connection to the server. If authentication for the server is enabled, the server authenticates the user name supplied by the connection and the user name placed in the message property will be an authenticated user. If SSL is used, the SSL connection protocol guarantees the client is authenticated using the client's digital certificate.

sender_name_enforced

The `sender_name_enforced` property specifies that messages sent to this destination *must* include the sender's user name. The server retrieves the user name of the message producer using the same procedure described in the `sender_name` property above.

However, unlike, the `sender_name` property, there is no way for message producers to override this property.

You can set `sender_name_enforced` using the form:

```
sender_name_enforced
```

If the `sender_name` property is also set on the destination, this property overrides the `sender_name` property.



In some business situations, clients may not be willing to disclose the user name of their message producers. If this is the case, these clients may wish to avoid sending messages to destinations that have the `sender_name` or `sender_name_enforced` properties enabled.

In these situations, the operator of the EMS server should develop a policy for disclosing a list of destinations that have these properties enabled. This will allow clients to avoid sending messages to destinations that would cause their message producer usernames to be exposed.

store

The `store` property determines where messages sent to this destination are stored. Messages may be stored in a file, or in a database.

See [Store Messages in Multiple Stores](#) for more information on using and configuring multiple stores.



When using the `setprop` or `addprop` commands to change the store settings for a topic or queue, note that existing messages are not migrated to the new store. As a result, stopping the EMS server and deleting the original store may result in data loss, if a destination still had messages in the original store.

Set the store property using this form:

```
store=name
```

where *name* is the name of a store, as defined in the `stores.conf` file.

For example, this will send all messages sent to the destination `giants.games` to the store named `baseball`; messages sent to all other destinations will be stored in `everythingelse`:

```
> store=everythingelse
giants.games store=baseball
```

Only one store is allowed for each destination. If there is a conflict, for example if overlapping wildcards cause a topic to inherit multiple store properties, the topic creation will fail.



This parameter cannot be used without first enabling this feature in the `tibemsd.conf` file. The `stores.conf` file must also exist, but can be left empty if the only store names that are associated with destinations are the default store files.

See [Store Messages in Multiple Stores](#) for more information.

trace

The `trace` property specifies that tracing should be enabled for this destination.

You can set `trace` using the form:

```
trace = [body]
```

Specifying `trace` (without `=body`), generates trace messages that include the message sequence, message ID, and message size. Specifying `trace=body` generates trace messages that include the message body. See [Message Tracing](#) for more information about message tracing.

Temporary Destination Properties

Temporary destinations, both topics and queues, support the following properties:

- `maxbytes`
- `maxmsgs`
- `overflowPolicy`

Temporary destinations tend to be short-lived objects by nature. Applications have no control over destination names for temporary topics and queues. For these reasons, you cannot directly set the above supported properties on temporary destinations.

However, EMS defines a special temporary destination wildcard that can be used to assign properties and values to temporary topics and queues by way of inheritance.

The temporary destination wildcard is defined as `TMP.>`, and can be used for both topics and queues. All properties set on topics using the wildcard are inherited by all temporary topics. Similarly, all properties set on queues using the wildcard are inherited by all temporary queues.

Although the same wildcard is used for both destination types, property values assigned using the wildcard are not shared between topics and queues. That is, you can assign one `overflowPolicy` to all temporary topics, and a different `overflowPolicy` to all temporary queues.

Properties can also be set on the `TMP.>` temporary destination wildcard through a variety of ways:

- Using the following `tibemsadmin` commands:
 - `create topic TMP.> [properties]`
 - `create queue TMP.> [properties]`
 - `addprop topic TMP.> [properties]`
 - `addprop queue TMP.> [properties]`
 - `setprop topic TMP.> [properties]`
 - `setprop queue TMP.> [properties]`
- Using the Central Administration interface.
- In the `topics.conf` and `queues.conf` configuration files.
- In the JSON configuration file.

Topics

Properties set on the `TMP.>` topic are immediately and directly inherited by all existing temporary topics and all temporary topics created in the future.

Queues

Properties set on the `TMP.>` queue are immediately and directly inherited by all existing temporary queues and all temporary queues created in the future.

Usage Notes

The temporary destination wildcard `TMP.>` can *only* be used to set properties on temporary topics or queues through inheritance.

- `TMP.>` cannot be used to send or receive messages.
- `TMP.>` cannot be used as the source or target of a destination bridge.
- You cannot create a durable subscription on the temporary topic wildcard `TMP.>`.
- You cannot use `TMP.>` to import or export messages from TIBCO FTL, Rendezvous, or SmartSockets transports.
- `TMP.>` never inherits any properties from other destination wildcards. For example, `TMP.>` does not inherit from the wildcard `>`.

Creating and Modifying Destinations

Destinations are typically "static" administered objects that can be stored in a JNDI or LDAP server. Administered objects can also be stored in the EMS server and looked up using the EMS implementation of JNDI.

This section describes how to use the EMS Administration Tool to create and modify destination objects in EMS. For more information, see [EMS Administration Tool](#).

You create a queue using the `create queue` command and a topic using the `create topic` command. For example, to create a new queue named `myQueue`, enter:

```
create queue myQueue
```

To create a topic named `myTopic`, enter:

```
create topic myTopic
```

The queue and topic data stored on the EMS server is located in the `queues.conf` and `topics.conf` files, respectively. You can use the `show queues` and `show topics` commands to list all of the queues and topics on your EMS server and the `show queue` and `show topic` commands to show the configuration details of specific queues and topics.

A queue or topic may include optional properties that define the specific characteristics of the destination. These properties are described in [Destination Properties](#) and they can be specified when creating the queue or topic or modified for an existing queue or topic using the `addprop queue`, `addprop topic`, `setprop queue`, `setprop topic`, `removeprop queue`, and `removeprop topic` commands.

For example, to discard messages on `myQueue` when the number of queued messages exceeds 1000, you can set an `overflowPolicy` by entering:

```
addprop queue myQueue maxmsgs=1000,overflowPolicy=discardOld
```

To change the `overflowPolicy` from `discardOld` to `rejectIncoming`, enter:

```
addprop queue myQueue overflowPolicy=rejectIncoming
```

The `setprop queue` and `setprop topic` commands remove properties that are not explicitly set by the command. For example, to change `maxmsgs` to 100 and to *remove* the `overflowPolicy` parameter, enter:

```
setprop queue myQueue maxmsgs=100
```

Creating Secure Destinations

By default, all authenticated EMS users have permissions to perform any action on any topic or queue.

You can set the `secure` property on a topic or queue and then use the `grant topic` or `grant queue` command to specify which users and/or groups are allowed to perform which actions on the destination.

The `secure` property requires that you enable the `authorization` property on the EMS server.

For example, to create a secure queue, named `myQueue`, to which only users "joe" and "eric" can send messages and "sally" can receive messages, in the EMS Administration Tool, enter:

```
set server authorization=enabled
create queue myQueue secure
grant queue myQueue joe send
grant queue myQueue eric send
grant queue myQueue sally receive
```

See [Authentication and Permissions](#) for more information.

Wildcards

You can use wildcards when specifying statically created destinations in `queues.conf` and `topics.conf`.

The use of wildcards in destination names can be used to define "parent" and "child" destination relationships, where the child destinations inherit the properties and permissions from its parents. You must first understand wildcards to understand the inheritance rules described in [Inheritance](#).

Wildcards * and >

To understand the rules for inheritance of properties, it is important to understand the use of the two wildcards, `*` and `>`.

- The wildcard `>` by itself matches any destination name.
- When `>` is mixed with text, it matches one or more trailing elements. For example:

```
foo.>
```

Matches `foo.bar`, `foo.boo`, `foo.boo.bar`, and `foo.bar.boo`.

- The wildcard `*` means that any token can be in the place of `*`. For example:

```
foo.*
```

Matches `foo.bar` and `foo.boob`, but not `foo.bar.boob`.

```
foo.*.bar
```

Matches `foo.boob.bar`, but not `foo.bar`.

Overlapping Wildcards and Disjoint Properties

Some destination properties are disjoint, and the server allows that property to be set only once for each destination. If an existing destination includes a value for a disjoint property and you attempt to assign a different value, the action will fail.

Overlapping wildcard destinations can cause conflicts with disjoint properties. For example, consider the following configuration of the store property:

```
topic.sample.>          store=$sys.fail-safe
topic.sample.quotes.*  store=$sys.nonfail-safe
```

The topic `topic.sample.quotes.tibx` would be assigned both stores, `$sys.fail-safe` and `$sys.nonfail-safe`. Therefore, the wildcard topics `topic.sample.>` and `topic.sample.quotes.*` cannot coexist. Their creation would fail.

EMS currently has only one disjoint property: [store](#).

Wildcards in Topics

TIBCO Enterprise Message Service enables you to use wildcards in topic names in some situations.

- You can subscribe to wildcard topics.

If you subscribe to a topic containing a wildcard, you will receive any message published to a matching topic. For example, if you subscribe to `foo.*` you will receive messages published to a topic named `foo.bar`.

You can subscribe to a wildcard topic (for example `foo.*`), whether or not there is a matching topic in the configuration file (for example, `foo.*`, `foo.>`, or `foo.bar`). However, if there is no matching topic name in the configuration file, no messages will be published on that topic.

- You cannot publish to wildcard topics.
- If `foo.bar` is not in the configuration file, then you can publish to `foo.bar` if `foo.*` or `foo.>` exists in the configuration file.
- On routed topic messages, subscribers must specify a topic that is a direct subset (or equal) of the configured global topic. For more information, see [Wildcards](#).

Wildcards in Queues

TIBCO Enterprise Message Service enables you to use wildcards in queue names in some situations. You can neither send to nor receive from wildcard queue names. However, you can use wildcard queue names in the configuration files.

For example, if the queue configuration file includes a line:

```
foo.*
```

then users can dynamically create queues `foo.bar`, `foo.bob`, and so forth, but not `foo.bar.bob`.

Wildcards and Dynamically Created Destinations

The EMS server may dynamically create destinations on behalf of its clients. The use of wildcards in the `.conf` files can be used to control the allowable names of dynamically created destinations.

The same basic wildcard rules apply to dynamically created destinations as described above for static destinations.

Examples

- If the `queues.conf` file contains:

```
>
```

The EMS server can dynamically create a queue with any name.

- If the `topics.conf` file contains only:

```
foo.>
```

The EMS server can dynamically create topics with names like `foo.bar`, `foo.boo`, `foo.boo.bar`, and `foo.bar.boo`.

- If the `queues.conf` file contains only:

```
foo.*
```

The EMS server can dynamically create queues with names like `foo.bar` and `foo.boo`, but not `foo.bar.boo`.

- If the `topics.conf` file contains only:

```
foo.*.bar
```

The EMS server can dynamically create topics with names like `foo.boo.bar`, but not `foo.bar`.

Inheritance

The following sections describe the inheritance of properties and permissions.

The [Wildcards](#), [Destination Properties](#), and [Authentication and Permissions](#) sections provide useful information in this context

Inheritance of Properties

All destination properties are inheritable for both topics and queues. This means that a property set for a "wildcarded" destination is inherited by all destinations with matching names.

For example, if you have the following in your `topics.conf` file:

```
foo.* secure
```

```
foo.bar
```

```
foo.bob
```

Topics `foo.bar` and `foo.bob` are [secure](#) topics because they inherit secure from their parent, `foo.*`. If your EMS server were to dynamically create a `foo.new` topic, it too would have the secure property.

The properties inherited from a parent are *in addition* to the properties defined for the child destination.

For example, if you have the following in your `topics.conf` file:

```
foo.* secure
foo.bar sender_name
```

Then `foo.bar` has both the [secure](#) and [sender_name](#) properties.

In the above example, there is no way to make topic `foo.*` secure without making `foo.bar` secure. In other words, EMS does not offer the ability to remove inherited properties. However, for properties that are assigned values, you can override the value established in a parent.

For example, if you have the following in your `queues.conf` file:

```
foo.* maxbytes=200
foo.bar maxbytes=2000
```

The `foo.bar` queue has a [maxbytes](#) value of 2000.

When there are multiple ancestors for a destination, the destination inherits the properties from all of the parents. For example:

```
> sender_name
foo.* secure
foo.bar trace
```

The `foo.bar` topic has the `sender_name`, `secure` and `trace` properties.

When there are multiple parents for a destination that contain conflicting property values, the destination inherits the smallest value. For example:

```
> maxbytes=2000
foo.* maxbytes=200
foo.bar
```

The `foo.bar` topic has a `maxbytes` value of 200.

Property inheritance is powerful, but can be complex to understand and administer. You must plan before assigning properties to topics and queues. Using wildcards to assign properties must be used carefully. For example, if you enter the following line in the `topics.conf` file:

```
> store=mystore
```

you make every topic store messages, regardless of additional entries. This might require a great deal of memory for storage and greatly decrease the system performance.

Inheritance of Permissions

Inheritance of permissions is similar to inheritance of properties. If the parent has a permission, then the child inherits that permission.

For example, if Bob belongs to GroupA, and GroupA has publish permission on a topic, then Bob has publish permission on that topic.

Permissions for a single user are the union of the permissions set for that user, and of all permissions set for every group in which the user is a member. These permission sets are additive. Permissions have positive boolean inheritance. Once a permission right has been granted through inheritance, it can not be removed.

All rules for wildcards apply to inheritance of permissions. For example, if a user has permission to publish on topic `foo.*`, the user also has permission to publish on `foo.bar` and `foo.new`.

For more information on wildcards, refer to [Wildcards](#). For more information on permissions, refer to [User Permissions](#).

Destination Bridges

Some applications require the same message to be sent to more than one destination, possibly of different types.

For example, an application may send messages to a queue for distributed load balancing. That same application, however, may also need the messages to be published to several monitoring applications. Another example is an application that publishes messages to several topics. All messages however, must also be sent to a database for backup and for data mining. A queue is used to collect all messages and send them to the database.

An application can process messages so that they are sent multiple times to the required destinations. However, such processing requires significant coding effort in the application. EMS provides a server-based solution to this problem. You can create bridges between destinations so that messages sent to one destination are also delivered to all bridged destinations.

Bridges are created between one destination and one or more other destinations of the same or of different types. That is, you can create a bridge from a topic to a queue or from a queue to a topic. You can also create a bridge between one destination and multiple destinations. For example, you can create a bridge from topic `a.b` to queue `q.b` and topic `a.c`.

When specifying a bridge, you can specify a particular destination name, or you can use wildcards. For example, if you specify a bridge on topic `foo.*` to queue `foo.queue`, messages delivered to any topic matching `foo.*` are sent to `foo.queue`.




Because global topics are routed between servers and global queues are limited to their neighbors, in most cases the best practice is to send messages to a topic and then bridge the topic to a queue.


When multiple bridges exist, using wildcards to specify a destination name may result in a message being delivered twice. For example, if the queues `Q.1` and `Q.>` are both bridged to `QX.1`, the server will deliver two copies of sent messages to `QX.1`.

The following figures illustrate example bridging scenarios.


Bridging a topic to a queue:



Bridging a topic to multiple destinations:



Bridging a queue to multiple destinations:



When a bridge exists between two queues, the message is delivered to both queues. The queues operate independently; if the message is retrieved from one queue, that has no effect on the status of the message in the second queue.

Bridges are not transitive. That is, messages sent to a destination with a bridge are only delivered to the specified bridged destinations and are not delivered across multiple bridges. For example, topic A.B has a bridge to queue Q.B. Queue Q.B has a bridge to topic B.C. Messages delivered to A.B are also delivered to Q.B, but not to B.C.

The bridge copies the source message to the target destination, which assigns the copied message a new message identifier. Note that additional storage may be required, depending on the target destination store parameters.

Create a Bridge

Bridges are configured using the `bridges.conf` configuration file.

You specify a bridge using the following syntax:

```
[destinationType:destinationName]
  destinationType=destinationToBridgeTo selector="messageSelector"
```

where *destinationType* is the type of the destination (either `topic` or `queue`), *destinationName* is the name of the destination from which you wish to create a bridge, *destinationToBridgeTo* is the name of the destination you wish to create a bridge to, and `selector="messageSelector"` is an optional message selector to specify the subset of messages the destination should receive.

Each *destinationName* can specify wildcards, and therefore any destination matching the pattern will have the specified bridge. Each *destinationName* can specify more than one *destinationToBridgeTo*.

For example, the bridges illustrated in the images [Bridging a topic to a queue](#) and [Bridging a topic to multiple destinations](#) would be specified as the following in `bridges.conf`:

```
[topic:A.B]
  queue=queue.B
  topic=C.B
```

Specifying a message selector on a bridged destination is described in the following section.



Deleting the source destination or a target destination of a bridge is prohibited. The server prevents you from deleting the source destination, however it does not prevent you from deleting a target destination. Regardless, prior to deleting a destination that is the source or target of a bridge, you must first remove the bridge.

Select the Messages to Bridge

By default, all messages sent to a destination with a bridge are sent to all bridged destinations. This can cause unnecessary network traffic if each bridged destination is only interested in a subset of the messages sent to the original destination. You can optionally specify a message selector for each bridge to determine which messages are sent over that bridge.

Message selectors for bridged destinations are specified as the selector property on the bridge. The following is an example of specifying a selector on the bridges defined in the previous section:

```
[topic:A.B]
  queue=queue.B
  topic=C.B selector="urgency in('medium', 'high')"
```

For detailed information about message selector syntax, see the documentation for the Message class in the relevant EMS API reference document.

Access Control and Bridges

Message producers must have access to a destination to send messages to that destination. However, a bridge automatically has permission to send to its target destination. Special configuration is not required.

Transactions

When a message producer sends a message within a transaction, all messages sent across a bridge are part of the transaction. Therefore, if the transaction succeeds, all messages are delivered to all bridged destinations. If the transaction fails, no consumers for bridged destinations receive the messages.

If a message cannot be delivered to a bridged destination because the message producer does not have the correct permissions for the bridged destination, the transaction cannot complete, and therefore fails and is rolled back.

Flow Control

In some situations, message producers may send messages more rapidly than message consumers can receive them. The pending messages for a destination are stored by the server until they can be delivered, and the server can potentially exhaust its storage capacity if the message consumers do not receive messages quickly enough.

To avoid this, EMS allows you to control the flow of messages to a destination. Each destination can specify a target maximum size for storing pending messages. When the target is reached, EMS blocks message producers when new messages are sent. This effectively slows down message producers until the message consumers can receive the pending messages.

Enable Flow Control

The `flow_control` parameter in `tibemsd.conf` enables and disables flow control globally for the EMS server.

When `flow_control` is disabled (the default setting), the server does not enforce any flow control on destinations. When `flow_control` is enabled, the server enforces any flow control settings specified for each destination. See [Configuration Files](#) for more information about working with configuration parameters.

When you wish to control the flow of messages on a destination, set the `flowControl` property on that destination. The `flowControl` property specifies the target maximum size of stored pending messages for the destination. The size specified is in bytes, unless you specify the units for the size. You can specify KB, MB, or GB for the units. For example, `flowControl = 60MB` specifies the target maximum storage for pending messages for a destination is 60 Megabytes.

Enforce Flow Control

The value specified for the `flowControl` property on a destination is a target maximum for pending message storage. When flow control is enabled, the server may use slightly more or less storage before enforcing flow control, depending upon message size, number of message producers, and other factors.

Setting the `flowControl` property on a destination but specifying no value causes the server to use a default value of 256KB.

When the storage for pending messages is near the specified limit, the server blocks all new calls to send a message from message producers. The calls do not return until the storage has decreased below the specified limit, or the `flowControl` limit is increased. Once message consumers have received messages and the pending message storage goes below the specified limit, the server allows the send message calls to return to the caller and the message producers can continue processing.

Flow Control in the Absence of Consumers

The server enforces flow control on destinations regardless of the presence of consumers.



Prior to release 8.4, if there was no message consumer for a destination, the server would not enforce flow control for the destination. That is, if a queue had no started receiver, the server did not enforce flow control for that queue. Also, if a topic had inactive durable subscriptions or no current subscriber, the server did not enforce flow control for that topic. For topics, if flow control was set on a specific topic (for example, `foo.bar`), then flow control was enforced as long as there were subscribers to that topic or any parent topic (for example, if there were subscribers to `foo.*`).

This behavior can be restored by setting the `flow_control_only_with_active_consumer` property but note that this property and the corresponding behavior are deprecated and will be removed in a future release.

Routes and Flow Control

For global topics where messages are routed between servers, flow control can be specified for a topic on either the server where messages are produced or the server where messages are received. Flow control is not relevant for queue messages that are routed to another server.

If the `flowControl` property is set on the topic on the server receiving the messages, when the pending message size limit is reached, messages are not forwarded by way of the route until the topic subscriber receives enough messages to lower the pending message size below the specified limit.

If the `flowControl` property is set on the topic on the server sending the messages, the server may block any topic publishers when sending new messages if messages cannot be sent quickly enough by way of the route. This could be due to network latency between the routed servers or it could be because flow control on the other server is preventing new messages from being sent.

Destination Bridges and Flow Control

Flow control can be specified on bridged destinations.

If you wish the flow of messages sent over the bridge to slow down when receivers on the bridged-to destination cannot process the messages quickly enough, you must set the `flowControl` property on both destinations on either side of the bridge.

Flow Control, Threads and Deadlock


When using flow control, you must be careful to avoid potential deadlock. When flow control is in effect for a destination, producers to that destination can block waiting for flow control signals from the destination's consumers. If any of those consumers are within the same thread of program control, a potential for deadlock exists.

Namely, the producer will not unblock until the destination contains fewer messages, and the consumer in the blocked thread cannot reduce the number of messages.

The simplest case to detect is when producer and consumer are in the same session (sessions are limited to a single thread). But more complex cases can arise. Deadlock can even occur across several threads, or even programs on different hosts, if dependencies link them. For example, consider the situation in the following image that illustrates a flow control deadlock across two threads:

- Producer P1 in thread T1 has a consumer C2 in thread T2.
- Producer P2 in T2 has a consumer C1 in T1.
- Because of the circular dependency, deadlock can occur if either producer blocks its thread waiting for flow control signals.

The dependency analysis is analogous to mutex deadlock. You must analyze your programs and distributed systems in a similar way to avoid potential deadlock.



Delivery Delay

The delivery delay feature allows the message producer to specify the earliest time at which a message should be delivered to consumers. This is done by using the `setDeliveryDelay()` method to set the minimum length of time that must elapse after a message is sent before the EMS server may deliver the message to a consumer.

Whenever a message is sent to destination *dest* with a non-zero delivery delay for the first time, the server dynamically creates a queue named `$sys.delayed.q.dest` when *dest* is a queue, or `$sys.delayed.t.dest` when *dest* is a topic.

`$sys.delayed` queues support browsing and purging but do not support other permissions such as receive or send. They inherit destination limits, security, and storage selection properties from *dest*. However, note that a `$sys.delayed.t` queue created for a topic that has the [secure](#) property cannot be browsed.

Note that the `$sys.delayed` queue corresponding to a destination takes any `maxmsgs` property setting from the destination. That is, if *dest* has property `maxmsgs` set to *X*, its `$sys.delayed` queue also has `maxmsgs` set to *X*. This doubles the number of messages that can potentially be held for *dest* in the server.

If the `maxmsgs` limit has been reached and the destination has the property `overflowPolicy=rejectIncoming`, when the delivery delay expires for a message one of two things can happen. If the message has the `JMS_TIBCO_PRESERVE_UNDELIVERED` set to `true`, it is put on the `$sys.undelivered` queue. Otherwise, the message is discarded.

Note that, when delivery delay is enabled for a topic, the behavior of `overflowPolicy=default` mimics that of a queue. That is, when `maxbytes` or `maxmsgs` has been reached, new messages are rejected by the server and an error is returned to the producer.

Getting Started

The following topics provide a quick introduction to setting up a simple EMS configuration and running some sample client applications to publish and subscribe users to a topic.

About the Sample Clients

The EMS sample clients were designed to allow you to run TIBCO Enterprise Message Service with minimum start-up time and coding.

The *EMS_HOME/samples* directory contains several subdirectories. The *emsc* subdirectory contains samples related to the Central Administration interface. The *c*, *cs*, and *java* subdirectories contain the C, .NET, and Java sample clients.

In this chapter, you will compile and run the Java sample clients. For information on how to run the C, .NET, and Central Administration sample clients, see the readme files in their respective directories.

The *EMS_HOME/samples/java* directory contains the following sets of files:

- Sample clients for TIBCO Enterprise Message Service implementation.
- The *JNDI* subdirectory contains sample clients that use the JNDI lookup technique.
- The *tibrv* subdirectory contains sample clients that demonstrate the interoperation of TIBCO Enterprise Message Service with TIBCO Rendezvous applications.
- The *admin* subdirectory contains samples that illustrate the use of the Admin API.

The *EMS_HOME/samples/c* directory contains sample clients.

On Windows platforms only, the *EMS_HOME\samples\cs* directory contains two sets of files:

- Sample clients for TIBCO Enterprise Message Service implementation.
- The *admin* subdirectory contains samples that illustrate the use of the Admin API.

In this chapter, you will use some of the sample clients in the *EMS_HOME/samples/java* directory. For information on compiling and running the other sample clients, see the Readme files in their respective folders.

Compiling the Sample Java Clients

To compile and run the sample Java clients you need to execute "setup" script, which is located in the *EMS_HOME/samples/java* directory.

On Windows systems, the setup file is *setup.bat*.

On Unix systems, the setup file is *setup.sh*.

Procedure

1. Make sure you have JDK 1.8 or greater installed and that you've added the bin directory to your PATH variable.
2. Open a command line or console window, and navigate to the *EMS_HOME/samples/java* directory.
3. Open the correct setup script file and verify that the *TIBEMS_ROOT* environment variable identifies the correct pathname to your *EMS_HOME* directory. For example, on a Windows system this might look like:

```
set TIBEMS_ROOT=C:\tibco\ems\8.5
```

4. Enter setup to set the environment and classpath:

```
> setup
```

5. Compile the samples:

```
> javac -d . *.java
```

This compiles all the samples in the directory, except for those samples in the `JNDI` and `tibrv` subdirectories.

If the files compile successfully, the class files will appear in the `EMS_HOME/samples/java` directory. If they do not compile correctly, an error message appears.

Creating Users with the EMS Administration Tool

In this example, you will create topics and users using the [EMS Administration Tool](#). You must first start the EMS server before starting the EMS administration tool.

Follow these steps to start the EMS server and to use the administration tool to create two new users.



All of the parameters you set using the administration tool in this chapter can also be set by editing the configuration files described in [Configuration Files](#). You can also programmatically set parameters using the C, .NET, or Java APIs. Parameters set programmatically by a client are only set for the length of the session.

Procedure

1. **Start the EMS server**

Start the EMS server as described in [Starting and Stopping the EMS Server](#).

2. **Start the Administration Tool and Connect to the EMS Server**

- a) Start the EMS administration tool as described in [Starting the EMS Administration Tool](#).
- b) After starting the administration tool, connect it to the EMS server.

To connect the EMS administration tool to the EMS server, execute one of the following commands:

- If you are using TIBCO Enterprise Message Service on a single computer, type **connect** in the command line of the Administration tool:

```
> connect
```

You will be prompted for a login name. If this is the first time you've used the EMS administration tool, follow the procedure described in [When You First Start tibemsadmin](#).

Once you have logged in, the screen will display:

```
connected to tcp://localhost:7222
tcp://localhost:7222>
```

- If you are using TIBCO Enterprise Message Service in a network, use the connect server command as follows:

```
> connect [server URL] [user-name] [password]
```

For more information on this command, see [connect](#).

For further information on the administration tool, see [Starting the EMS Administration Tool](#) and [Command Listing](#).

3. **Create Users**

Once you have connected the administration tool to the server, use the **create user** command to create two users.

In the administration tool, enter:

```
tcp://localhost:7222> create user user1
```

```
tcp://localhost:7222> create user user2
```

The tool will display messages confirming that `user1` and `user2` have been created.

You have now created two users. You can confirm this with the `show users` command:

```
tcp://localhost:7222> show users
```

User Name	Description
user1	
user2	

For more information on the `create user` command, refer to [create user](#).

Point-to-Point Messaging Example

This section demonstrates how to use point-to-point messaging, as described in [Point-to-Point](#).

Creating a Queue

In the point-to-point messaging model, client send messages to and receive messages from a queue.

To create a new queue in the administration tool, use the `create queue` command to create a new queue named `myQueue`:

```
tcp://localhost:7222> create queue myQueue
```

For more information on the `create queue` command, refer to [create queue](#). For more information on the `commit` command, see [commit](#) and [autocommit](#).

Starting the Sender and Receiver Clients

Procedure

1. Open two command line windows and in each window navigate to the `EMS_HOME/samples/java` folder.
2. In each command line window, enter `setup` to set the environment and classpath:

```
> setup
```
3. In the first command line window, execute the `tibjmsMsgProducer` application to direct `user1` to place some messages to the `myQueue` queue:

```
> java tibjmsMsgProducer -queue myQueue -user user1 Hello User2
```
4. In the second command line window, execute the `tibjmsMsgConsumer` client to direct `user2` to read the messages from the message queue:

```
> java tibjmsMsgConsumer -queue myQueue -user user2
```

The messages placed on the queue are displayed in the receiver's window.



Messages placed on a queue by the sender are persistent until acknowledged by the receiver, so you can start the sender and receiver clients in any order.

Publish and Subscribe Messaging Example

In this section, you will execute a message producer client and two message consumer clients that demonstrate the publish/subscribe messaging model described in [Publish and Subscribe](#). This example is not intended to be comprehensive or representative of a robust application.

To execute the client samples, you must give them commands from within the sample directory that contains the compiled samples. For this exercise, open three separate command line windows and navigate to the *EMS_HOME/samples/java* directory in each window.

For more information on the samples, refer to the *readme* file within the sample directory. For more information on compiling the samples, refer to [Compiling the Sample Java Clients](#).

Creating a Topic

In the publish/subscribe model, you publish and subscribe to topics.

To create a new topic in the administration tool, use the `create topic` command to create a new topic named `myTopic`:

```
tcp://localhost:7222> create topic myTopic
```

For more information on the `create topic` command, refer to [create topic](#). For more information on the `commit` command, see [commit](#) and [autocommit](#).

Starting the Subscriber Clients

You start the subscribers first because they enable you to observe the messages being received when you start the publisher.

Procedure

To start `user1` as a subscriber:

1. In the first command line window, navigate to *EMS_HOME/samples/java*.
2. Enter `setup` to set the environment and classpath:

```
> setup
```
3. Execute the `tibjmsMsgConsumer` client to assign `user1` as a subscriber to the `myTopic` topic:

```
> java tibjmsMsgConsumer -topic myTopic -user user1
```

The screen will display a message showing that `user1` is subscribed to `myTopic`.

To start `user2` as a subscriber:

4. In the second command line window, navigate to the *EMS_HOME/samples/java* folder.
5. Enter `setup` to set the environment and classpath:

```
> setup
```
6. Execute the `tibjmsMsgConsumer` application to assign `user2` as a subscriber to the `myTopic` topic:

```
> java tibjmsMsgConsumer -topic myTopic -user user2
```

The screen will display a message showing that `user2` is subscribed to `myTopic`.



The command windows do not return to the prompt when the subscribers are running.

Starting the Publisher Client and Sending Messages

Setting up the publisher is very similar to setting up the subscriber. However, while the subscriber requires the name of the topic and the user, the publisher also requires messages.

To start the publisher:

Procedure

1. In the third command line window, navigate to the *EMS_HOME/samples/java* folder.
2. Enter `setup` to set the environment and classpath:

```
> setup
```

3. Execute the `tibjmsMsgProducer` client to direct `user1` to publish some messages to the `myTopic` topic:

```
> java tibjmsMsgProducer -topic myTopic -user user1 hello user2
```

where 'hello' and 'user2' are separate messages.



In this example, `user1` is both a publisher and subscriber.

Result

The command line window will display a message stating that both messages have been published:

```
Publishing on topic 'myTopic'
Published message: hello
Published message: user2
```

After the messages are published, the command window for the publisher returns to the prompt for further message publishing.

Note that if you attempt to use the form:

```
java tibjmsMsgProducer -topic myTopic -user user1
```

without adding the messages, you will see an error message, reminding you that you must have at least one message text.

The first and second command line windows containing the subscribers will show that each subscriber received the two messages:

```
Subscribing to destination: myTopic

Received message: TextMessage={ Header={ JMSMessageID={ID:EMS-SERVER.
16C5B5C81B3CB4:1} JMSDestination={Topic[myTopic]} JMSReplyTo={null}
JMSDeliveryMode={PERSISTENT} JMSRedelivered={false} JMSCorrelationID={null}
JMSType={null} JMSTimestamp={Thu Mar 07 18:18:01 CST 2019} JMSDeliveryTime={Thu Mar
07 18:18:01 CST 2019} JMSExpiration={0} JMSPriority={4} }
Properties={ JMSXDeliveryCount={Integer:1} } Text={hello} }
Received message: TextMessage={ Header={ JMSMessageID={ID:EMS-SERVER.
16C5B5C81B3CB4:2} JMSDestination={Topic[myTopic]} JMSReplyTo={null}
JMSDeliveryMode={PERSISTENT} JMSRedelivered={false} JMSCorrelationID={null}
JMSType={null} JMSTimestamp={Thu Mar 07 18:18:01 CST 2019} JMSDeliveryTime={Thu Mar
07 18:18:01 CST 2019} JMSExpiration={0} JMSPriority={4} }
Properties={ JMSXDeliveryCount={Integer:1} } Text={user2} }
```

Creating a Secure Topic

In this example, you make `myTopic` into a secure topic and grant `user1` permission to publish to the `myTopic` and `user2` permission to subscribe to `myTopic`.

Adding the secure Property to the Topic

When the secure property is added to a topic, only users who have been assigned a certain permission can perform the actions allowed by that permission. For example, only users with publish permission on the topic can publish, while other users cannot publish.

If the secure property is not added to a topic, all authenticated users have all permissions (publish, subscribe, create durable subscribers) on that topic.

For more information on the secure property, see the section about [secure](#). For more information on topic permissions, see [Authentication and Permissions](#).

To enable server authorization and add the secure property to a topic, do the following steps:

Procedure

1. In each subscriber window, enter Control-C to stop each subscriber.

2. In the administration tool, use the `set server` command to enable the [authorization](#) property:

```
tcp://localhost:7222> set server authorization=enabled
```

The `authorization` property enables checking of permissions set on destinations.

3. Enter the following command to add the secure property to a topic named `myTopic`:

```
tcp://localhost:7222> addprop topic myTopic secure
```

For more information on the `set server` command, refer to [set server](#). For more information on the `addprop topic` command, refer to [addprop topic](#).

Granting Topic Access Permissions to Users

To see how permissions affect the ability to publish and receive messages, grant publish permission to `user1` and subscribe permission to the `user2`.

Use the `grant topic` command to grant permissions to users on the topic `myTopic`.

In the administration tool, enter:

```
tcp://localhost:7222> grant topic myTopic user1 publish
tcp://localhost:7222> grant topic myTopic user2 subscribe
```

For more information on the `grant topic` command, refer to [grant topic](#).

Starting the Subscriber and Publisher Clients

Start the subscribers, as described in [Starting the Subscriber Clients](#). Note that you cannot start `user1` as a subscriber because `user1` has permission to publish, but not to subscribe. As a result, you receive an exception message including the statement:

```
Operation not permitted.
```

`User2` should start as a subscriber in the same manner as before.

You can now start `user1` as the publisher and send messages to `user2`, as described in [Starting the Publisher Client and Sending Messages](#).

Creating a Durable Subscriber

As described in [Publish and Subscribe](#), subscribers, by default, only receive messages when they are active. If messages are published when the subscriber is not available, the subscriber does not receive those messages. You can create durable subscriptions, where subscriptions are stored on the server and subscribers can receive messages even if it was inactive when the message was originally delivered.

In this example, you create a durable subscriber that stores messages published to topic `myTopic` on the EMS server.

To start `user2` as a durable subscriber:

Procedure

1. In the a command line window, navigate to the `EMS_HOME/samples/java` folder.
2. Enter `setup` to set the environment and classpath:

```
> setup
```

3. Execute the `tibjmsDurable` application to assign `user2` as a durable subscriber to the `myTopic` topic:

```
> java tibjmsDurable -topic myTopic -user user2
```

4. In the administration tool, use the [show durables](#) command to confirm that user2 is a durable subscriber to myTopic:

```
tcp://localhost:7222> show durables
```

Topic Name	Durable	User	Msgs	Size
* myTopic	subscriber	user2	0	0.0 Kb

5. In the subscriber window, enter Ctrl+C to stop the subscriber.
6. In another command line window, execute the `tibjmsMsgProducer` client, as described in [Starting the Publisher Client and Sending Messages](#):

```
> java tibjmsMsgProducer -topic myTopic -user user1 hello user2
```

7. Restart the subscriber:

```
> java tibjmsDurable -topic myTopic -user user2
```

The stored messages are displayed in the subscriber window.

8. Enter Ctrl+C to stop the subscriber and then unsubscribe the durable subscription:

```
> java tibjmsDurable -unsubscribe
```

The subscriber is no longer durable and any additional messages published to the `myTopic` topic are lost.

Running the EMS Server

To use TIBCO Enterprise Message Service with your applications, the TIBCO Enterprise Message Service Server must be running.

Starting and Stopping the EMS Server

The server and the clients work together to implement TIBCO Enterprise Message Service. The server implements all types of message persistence and no messages are stored on the client side. The following topics describe how to start and stop the EMS Server.

Starting the EMS Server Using a Sample Configuration

To start the EMS server from the command line using sample configuration files, navigate to `EMS_HOME/samples/config` and perform the following steps:

Procedure

1. Create a local directory called `datastore` (for example, `/opt/tibco/ems/samples/config/datastore`)
2. Execute the command:
`tibemsd -config tibemsd.conf`

Starting the EMS Server Using JSON Configuration



Users using the Central Administration feature must start the EMS server in JSON mode. This is done from the command line, using the `-config` option to specify the JSON configuration file. For more information, see 'JSON Configuration Files' in the *TIBCO Enterprise Message Service Central Administration* guide.

Your JSON-configured `tibemsd` must be running before it can be added to the Central Administration server list. To start the TIBCO Enterprise Message Service server using the JSON configuration file:

Procedure

1. From the command line, navigate to `EMS_HOME/bin`.
2. Enter the following command and option:

```
tibemsd -config json-file-path
```

where `json-file-path` is the path to your JSON configuration file. For example:

```
tibemsd -config /tibemsconfig/tibemsd.json
```

When started using the JSON configuration, the `tibemsd` silently ignores any unknown parameters. For example, no configuration errors are thrown if the `tibemsd.json` file contains an obsolete parameter.



For information on converting `.conf` configuration files to JSON configuration files, see 'Conversion of Server Configuration Files to JSON' in the *TIBCO Enterprise Message Service Central Administration* guide.

Starting Fault Tolerant Server Pairs

In Central Administration, fault tolerant pairs share a single JSON configuration file. Primary and secondary server roles are determined when the servers are started.

Start the primary EMS server as usual. Start the secondary server using the `-secondary` flag. For example, where the JSON configuration file is `tibemsd.json`:

- To start the primary server:
`tibemsd -config tibemsd.json`
- To start the secondary server:
`tibemsd -config tibemsd.json -secondary`

For more information, see [Fault Tolerance in Central Administration](#).

Starting the EMS Server Using Options

To start the EMS server from the command line using options:

Procedure

1. Navigate to the `samples` subdirectory.

Sample EMS server configuration files are located in `EMS_HOME/samples/config`. For more information, see 'Installing TIBCO Enterprise Message Service' in *TIBCO Enterprise Message Service Installation*.

The EMS server dynamically loads the SSL and compression shared libraries, rather than statically linking them. If the `tibemsd` executable is executed from the `samples` directory, it automatically locates these libraries. If the server is moved elsewhere, the shared library directory must be moved as well.

2. Start the `tibemsd`

Type `tibemsd [options]`

where *options* are described in [tibemsd Options](#). The command options to `tibemsd` are similar to the parameters you specify in `tibemsd.conf`, and the command options override any value specified in the parameters. See [tibemsd.conf](#) for more information about configuration parameters.

tibemsd Options

The `tibemsd` options override any value specified in the parameters.

Option	Description
<code>-config config file name</code>	<p><i>config file name</i> is the name of the main configuration file for <code>tibemsd</code> server. Default is <code>tibemsd.conf</code>.</p> <p>For example, to start an EMS server using the default JSON configuration file, use:</p> <pre>tibemsd -config tibemsd.json</pre>
<code>-trace items</code>	<p>Specifies the trace items. These items are not stored in the configuration file. The value has the same format as the value of <code>log_trace</code> parameter specified with <code>set server</code> command of the administration tool; see Trace Messages for the Server.</p>

Option	Description
<code>-secondary</code>	Specifies the secondary server in a fault tolerant pair. This option is only valid for EMS servers started using JSON config.
<code>-ssl_password <i>string</i></code>	Private key password.
<code>-ssl_trace</code>	Print the certificates loaded by the server and do more detailed tracing of SSL-related situation.
<code>-ssl_debug_trace</code>	Turns on tracing of SSL connections.
<code>-ft_active <i>active_url</i></code>	URL of the active server. If this server can connect to the active server, it will act as a standby server. If this server cannot connect to the active server, it will become the active server.
<code>-ft_heartbeat <i>seconds</i></code>	Heartbeat signal for the active server, in seconds. Default is 3.
<code>-ft_activation <i>seconds</i></code>	Activation interval (maximum length of time between heartbeat signals) which indicates that active server has failed. Set in seconds: default is 10. This interval should be set to at least twice the heartbeat interval.
<code>-forceStart</code>	Causes the sever to delete corrupted messages in the store files, allowing the server to start even if it encounters errors. Note that using this option causes data loss, and it is important to backup store files before using <code>-forceStart</code> . See Error Recovery Policy for more information.

Stopping the EMS Server

You can stop the EMS server by using the shutdown command from the EMS Administration Tool. For more information, see [shutdown](#).

Running the EMS Server as a Windows Service

Some situations require the EMS server to start automatically. You can satisfy this requirement by registering it with the Windows service manager. The `emsntsrg` utility facilitates registry.

emsntsrg

The `emsntsrg` utility registers or unregisters the EMS server as a Windows service.

Syntax

```
emsntsrg /i [/a][[/d] service_name emsntsct_directory service_directory [arguments] [suffix]
```

```
emsntsrg /r [service_name] [suffix]
```

Remarks

Some situations require the EMS server processes to start automatically. You can satisfy this requirement by registering these with the Windows service manager. This utility facilitates registry.

Restrictions

You must have administrator privileges to change the Windows registry.

Location

Locate this utility program as an executable file in the EMS bin directory.

Parameter	Description
<code>/i</code>	Insert a new service in the registry (that is, register a new service).
<code>/a</code>	Automatically start the new service. Optional with <code>/i</code> . You can use either <code>/a</code> or <code>/d</code> but not both.
<code>/d</code>	Automatically start the new service with a delay. Optional with <code>/i</code> . You can use either <code>/a</code> or <code>/d</code> but not both.
<code>/?</code>	Display usage.
<i>service_name</i>	Insert or remove a service with this base name. When inserting a service, this parameter is required, and must be <code>tibemsd</code> . When removing a service, this parameter is optional. However, if it is present, it must be <code>tibemsd</code> .
<i>emsntsct_directory</i>	Use this directory pathname to specify the location of the <code>emsntsct.exe</code> executable. The <code>emsntsrg</code> utility registers the <code>emsntsct.exe</code> program as a windows service. The <code>emsntsct.exe</code> program then invokes the associated <code>tibemsd</code> . By default, <code>emsntsct.exe</code> is located in <code>EMS_HOME\bin</code> . This parameter is only required when installing a service.
<i>service_directory</i>	Use this directory pathname to locate the service executable, <code>tibemsd</code> . Required.
<i>arguments</i>	Supply command line arguments. Optional with <code>/i</code> . Enclose the entire arguments string in double quote characters.
<i>suffix</i>	When registering more than one instance of a service, you can use this suffix to distinguish between them in the Windows services applet. Optional.
<code>/r</code>	Remove a service from the registry.

Register

To register `tibemsd` as a Windows service, run the utility with this command line:

```
emsntsrg /i [/a][[/d] tibemsd emsntsct_directory tibemsd_directory [arguments]
[suffix]
```

- Example 1

This simple example registers one `tibemsd` service:

```
emsntsrgr /i tibemsd C:\tibco\ems\8.5\bin C:\tibco\ems\8.5\bin
```

- Example 2

This example registers a service with command line arguments:

```
emsntsrgr /i tibemsd C:\tibco\ems\8.5\bin C:\tibco\ems\8.5\bin "-trace DEFAULT"
```

- Example 3

This pair of example commands registers two `tibemsd` services with different configuration files. In this example, the numerical suffix and the configuration directory both reflect the port number that the service uses.

```
emsntsrgr /i tibemsd C:\tibco\ems\8.5\bin C:\tibco\ems\8.5\bin "-config C:\tibco\ems\8.5\7222\tibemsd.conf" 7222
emsntsrgr /i tibemsd C:\tibco\ems\8.5\bin C:\tibco\ems\8.5\bin "-config C:\tibco\ems\8.5\7223\tibemsd.conf" 7223
```

Notice these aspects of this example:

- When installing `tibemsd`, if you supply a `-config` argument, the service process finds the directory containing the main configuration file (`tibemsd.conf`), and creates all secondary configuration files in that directory. In this example, each service uses a different configuration directory.
- When you register several EMS services, you must avoid configuration conflicts. For example, two instances of `tibemsd` cannot listen on the same port.

Remove

To unregister a service, run the utility with this command line:

```
emsntsrgr /r [service_name] [suffix]
```

Both parameters are optional. If the `service_name` is present, it must be `tibemsd`. To supply the `suffix` parameter, you must also supply the `service_name`. When both parameters are absent, the utility removes the services named `tibemsd`.

Command Summary

To view a command line summary, run the utility with this command line:

```
emsntsrgr
```

Windows Services Applet

The Windows services applet displays the name of each registered service. For EMS services, it also displays this additional information:

- The suffix (if you supply one)
- The process ID (PID)—when the service is running

Error Recovery Policy

During startup the EMS server can encounter a number of errors while it recovers information from the store files.

Potential errors include:

- Low-level file errors. For example, corrupted disk records.
- Low-level object-specific errors. For example, a record that is missing an expected field.
- Inter-object errors. For example, a session record with no corresponding connection record.

When the EMS server encounters one of these errors during startup, the recovery policy is:

- By default, the server exits startup completely when a corrupt disk record error is detected. Because the state can not be safely restored, the server can not proceed with the rest of the recovery. You can then examine your configuration settings for errors. If necessary, you can then copy the store and configuration files for examination by TIBCO Support.
- You can direct the server to delete bad records by including the `-forceStart` command line option. This prevents corruption of the server runtime state.
- The server exits if it runs out of memory during startup.

It is important to backup the store files before restarting the server with the `-forceStart` option, because data will be lost when the problematic records are deleted.

Keep in mind that different type of records are stored in the store files. The most obvious are the persistent JMS Messages that your applications have sent. However, other internal records are also stored. If a consumer record used to persist durable subscriber state information were to be corrupted and later deleted with the `-forceStart` option, all JMS messages that were persisted (and valid in the sense that they were not corrupted) would also be lost because the durable subscription itself would not be recovered.

When running in this mode, the server still reports any errors found during the recovery, but problematic records are deleted and the recovery proceeds. This mode may report more issues than are reported without the `-forceStart` option, because without that flag the server stops with the very first error.



We strongly recommended that you make a backup of all store files before restarting the server with the `-forceStart` option. The backup is useful when doing a postmortem analysis to find out what records were deleted with the `-forceStart` option.

Security Considerations



This section highlights information relevant to secure deployment. We recommend that all administrators read this section.

Secure Environment

To ensure secure deployment, EMS administration must meet certain criteria.

These criteria include:

- **Correct Installation:** EMS is correctly installed and configured.
- **Physical Controls:** The computers where EMS is installed are located in areas where physical entry is controlled to prevent unauthorized access. Only authorized administrators have access, and they cooperate in a benign environment.
- **Domain Control:** The operating system, file system and network protocols ensure domain separation for EMS, to prevent unauthorized access to the server, its configuration files, LDAP servers, etc.
- **Benign Environment:** Only authorized administrators have physical access or domain access, and those administrators cooperate in a benign environment.

Destination Security

Three interacting factors affect the security of destinations (that is, topics and queues). In a secure deployment, you must properly configure all three of these items.

- The server's authorization parameter (see [Authorization Parameter](#), below)
- The secure property of individual destinations (see [secure](#))
- The ACL permissions that apply to individual destinations (see [Authentication and Permissions](#))

Authorization Parameter

The [authorization](#) parameter of the server acts as a master switch for checking permissions for connection requests and operations on secure destinations.

The default value of this parameter is `disabled`—the server does not check any permissions, and allows all operations. For secure deployment, you must enable this parameter.

Admin Password

For ease in installation and initial testing, the default setting for the admin password is no password at all. Until you set an actual password, the user `admin` can connect without a password. Once the administrator password has been set, the server always requires it.

To configure a secure deployment, the administrator must change the admin password immediately after installation; see [Assigning a Password to the Administrator](#).

Connection Security

When [authorization](#) is enabled, the server requires a name and password before users can connect. Only authenticated users can connect to the server. The form of authentication can be either an X.509 certificate or a username and password (or both).

When [authorization](#) is disabled, the server does not check user authentication; all user connections are allowed. However, even when [authorization](#) is disabled, the user `admin` must still supply the correct password to connect to the server.

Even when [authorization](#) is enabled, the administrator (`admin`) may explicitly allow anonymous user connections, which do not require password authorization. To allow these connections, create a user with the name `anonymous` and no password.



Creating the user `anonymous` does not mean that `anonymous` has all permissions. Individual topics and queues can still be secure, and the ability to use these destinations (either sending or receiving) is controlled by the access control list of permissions for those destinations. The user `anonymous` can access only non-secure destinations.

Nonetheless, this feature (anonymous user connections) is outside the tested configuration of EMS security certification.

For more information on destination security, refer to the destination property [secure](#), and [Create Users](#).

Communication Security

For communication security between servers and clients, and between servers and other servers, you must explicitly configure SSL within EMS.

SSL communication requires software to implement SSL on both server and client. The EMS server includes the OpenSSL implementation. Java client programs use JSSE (part of the Java environment). JSSE is not a part of the EMS product. C client programs can use the OpenSSL library shipped with EMS.

For more information, see [SSL Protocol](#)

Sources of Authentication Data

The server uses only one source of X.509 certificate authentication data, namely, the server parameter `ssl_server_trusted` (its value is set in EMS an configuration file). The server can use three sources of secure password authentication data:

- Local data from the EMS configuration files.
- External data from an LDAP.

- A user-supplied JAAS LoginModule.

You must safeguard the security of EMS configuration files and LDAP servers.

For more information, see [ssl_server_trusted](#).

Timestamp

The administration tool can either include or omit a timestamp associated with the output of each command.

To ensure a secure deployment, you must explicitly enable the timestamp feature. Use the following administration tool command:

```
time on
```

Passwords



Passwords are a significant point of vulnerability for any enterprise. We recommend enforcing strong standards for passwords.

For security equivalent to single DES (an industry minimum), security experts recommend passwords that contain 8–14 characters, with at least one upper case character, at least one numeric character, and at least one punctuation character.

EMS software does not automatically enforce such standards for passwords. You must enforce such policies within your organization.

Audit Trace Logs

Audit information is output to log files (and `stderr`), and is configured by the server parameters `log_trace` and `console_trace`.

For more information on these parameters, see [Tracing and Log File Parameters](#).

The DEFAULT setting includes +ADMIN, so all administrative operations produce audit output. For further details, see [Server Tracing Options](#).

Audit information in log files always includes a time stamp.

Administrators can read and print the log files for audit review using tools (such as text editors) commonly available within all IT environments. EMS software does not include a special tool for audit review.

Manage Access to Shared Store Files

To prevent two EMS servers from using the same store file, each server restricts access to its store file for the duration of the server process. This section describes how EMS manages locked store files.

Windows

On Windows platforms, servers use the standard Windows `CreateFile` function, supplying `FILE_SHARE_READ` as the `dwShareMode` (third parameter position) to restrict access to other servers.

UNIX

On UNIX platforms, servers use the standard `fcntl` operating system call to implement cooperative file locking:

```
struct flock fl;
int err;

fl.l_type = F_WRLCK;
fl.l_whence = 0;
fl.l_start = 0;
fl.l_len = 0;
```

```
err = fcntl(file, F_SETLK, &fl);
```

To ensure correct locking, we recommend checking the operating system documentation for this call, since UNIX variants differ in their implementations.

Performance Tuning

By default, the TIBCO Enterprise Message Service server has the following general thread architecture:

- A single thread to process network traffic.
- One thread for each store.
- Additional threads for various background tasks such as expiring messages, connecting routes, and so on.

Setting Thread Affinity for Increased Throughput

If the default behavior of the EMS server cannot provide the required throughput and the EMS server machine has multiple cores, you can assign specific cores to the EMS threads that handle network traffic and stores.

For instance, with a 4-core machine, you can use the `processor_ids` parameter to assign core 0 and core 1 to handle network traffic. You can also use the store configuration `processor_id` parameter to assign core 2 to handle the `$sys.failsafe` store. This configuration causes the EMS server to create two threads that handle network traffic, and sets the affinity of them to core 0 and core 1 respectively. It also sets the affinity of the thread handling the store `$sys.failsafe` to core 2. No affinity is set for other threads.

Increasing Network Threads without Setting Thread Affinity

If you want to increase the number of network threads without assigning them to specific cores, use the `network_thread_count` parameter.

The `network_thread_count` lets the EMS server control the number of network threads and also lets the administrator control the thread affinity externally (for example, by using the Linux `taskset` command).

If you set the thread affinity externally, we recommend that you avoid setting any thread affinity in the EMS server for either network traffic or stores.

The EMS server ignores the `network_thread_count` if the `processor_ids` parameter is also specified.

Determine Core Allocation

The phrase "less is more" summarizes the best practices for EMS performance tuning.

- When the EMS server does not set thread affinity, the operating system can better schedule EMS server threads to react to changing workloads on the machine. Also examine if the application is making efficient use of the API before changing the default behavior. For example, when performing persistent messaging operations, consider using multiple threads in the applications (each with its own session) or consider using local transactions to batch sends and acknowledgments.
- Use the minimum number of threads to handle network traffic. Specifying a single thread may yield sufficient performance improvements over the default behavior, so start testing affinity there. Using excessive numbers of threads leads to greater thread contention for global data structures, which can reduce throughput and waste machine resources. Excessive numbers can also lead to more unbalanced connection assignments. TIBCO tests have shown that three (or four under some workloads) is the maximum useful number for network traffic.
- Specifying thread affinity to specific cores can provide the highest performance but can also lead to a configuration that does not react well to changing workloads. If you specify thread affinity for

network traffic for persistent messaging, also set thread affinity for stores in order to prevent contention between threads handling those tasks.

Transparent Huge Pages

The Transparent Huge Pages (THP) feature of Linux does not have a significant impact on the performance of EMS.

Network I/O Connections

When a client connects to the EMS server, the EMS server assigns it to one of the threads handling network traffic based on which of those threads have the fewest existing connections. This balances the total number of connections evenly across those threads.

Note that if all the connections to one thread are closed, the EMS server does not move existing connections from other threads in order to rebalance them.

Also note that the EMS server does not account for the traffic generated by those connections. For instance, the EMS server could assign ten connections to one thread and ten connections to another thread but still have an unbalanced state if the first ten connections account for 90% of all network traffic to the EMS server.

Other Considerations

- When assigning cores for EMS use, ensure that the Operating System does not schedule those cores for other processes.
- Assign cores on the same die if possible. This reduces cache sharing between dies. High levels of cache sharing between dies reduces memory performance.
- Hyper-threads are not real cores. Disable hyper-threading if possible. Do not assign cores to the EMS server such that it sets affinity for two "cores" that are actually sharing the same physical core by hyper-threading.

Using the EMS Administration Tool

The following sections give an overview of the commands in use in the administration tool for TIBCO Enterprise Message Service.

Starting the EMS Administration Tool

The EMS Administration Tool is located in your `EMS_HOME/bin` directory and is a stand-alone executable named `tibemsadmin` on UNIX and `tibemsadmin.exe` on Windows platforms.

The EMS server must be started as described in [Running the EMS Server](#) before you start the EMS Administration Tool.

When a system uses shared configuration files in the `.conf` format, actions performed using the `tibemsadmin` tool take effect only when connected to the active server.



When a system uses a shared configuration file in the `.json` format, most commands in the `tibemsadmin` tool are unavailable when connected to a server that is not in the active state. In such a situation, the only commands available are [show connections](#), [show state](#), [shutdown](#), and [rotatelog](#).

Additionally, if the `tibemsadmin` tool is connected to the standby server, it will be disconnected when a failover occurs.

Options for tibemsadmin

Type `tibemsadmin -help` to display information about `tibemsadmin` startup parameters. All `tibemsadmin` parameters are optional.

Option	Description
<code>-help</code> or <code>-h</code>	Print the help screen.
<code>-script script-file</code>	Execute the specified text file containing <code>tibemsadmin</code> commands then quit. Any valid <code>tibemsadmin</code> command described in this chapter can be executed. Line breaks within the file delimit each command. That is, every command must be contained on a single line (no line breaks within the command), and each command is separated by a line break.
<code>-server server-url</code>	Connect to specified server.
<code>-user user-name</code>	Use this user name to connect to server.
<code>-password password</code>	Use this password to connect to server.
<code>-pwdfile password-file</code>	Use the clear-text password in the specified file to connect to the server. If both <code>-pwdfile</code> and <code>-password</code> options are given, the password specified through the <code>-password</code> option takes precedence.
<code>-ignore</code>	Ignore errors when executing script file. This parameter only ignores errors in command execution but not syntax errors in the script.

Option	Description
<code>-mangle [password]</code>	Mangle the password and quit. Mangled string in the output can be set as a value of one of these passwords from the configuration files: <ul style="list-style-type: none"> • server password • server SSL password • LDAP admin password • database password If the password is not entered it is prompted for.
<code>-module_path</code>	Specifies a directory or directories that contain the SSL and Zlib shared library files, upon which the Administration Tool is dependent.
<code>-ssl_trusted filename</code>	File containing trusted certificate(s). This parameter may be entered more than once if required.
<code>-ssl_identity filename</code>	File containing client certificate and (optionally) extra issuer certificate(s), and the private key.
<code>-ssl_issuer filename</code>	File containing extra issuer certificate(s) for client-side identity.
<code>-ssl_key filename</code>	File containing the private key.
<code>-ssl_password password</code>	Private key or PKCS#12 password. If the password is required, but has not been specified, it will be prompted for.
<code>-ssl_pwdfilename password-file</code>	Use the private key or PKCS12 password in the specified file to connect to the server. If both <code>-ssl_pwdfilename</code> and <code>-ssl_password</code> options are given, the password specified through the <code>-ssl_password</code> option takes precedence.
<code>-ssl_noverifyhostname</code>	Do not verify hostname against the name on the certificate.
<code>-ssl_hostname name</code>	Name expected in the certificate sent by the host.
<code>-ssl_trace</code>	Show loaded certificates and certificates sent by the host.
<code>-ssl_debug_trace</code>	Show additional tracing, which is useful for debugging.

When a command specifies `-user` and `-password`, that information is not stored for later use. It is only used to connect to the server specified in the same command line. The user name and password entered on one command line are not reused with subsequent connect commands entered in the script file or interactively.

Examples

```
tibemsadmin -server "tcp://host:7222"
tibemsadmin -server "tcp://host:7222" -user admin -password secret
```

Some options are needed when you choose to make a SSL connection. For more information on SSL connections, refer to [SSL Protocol](#).

When You First Start tibemsadmin

The administration tool has a default user with the name `admin`. This is the default user for logging in to the administration tool.

To protect access to the server configuration, you must assign a password to the user `admin`.

Assigning a Password to the Administrator

Procedure

1. Log in and connect to the administration tool, as described directly above.
2. Use the `set password` command to change the password:

```
set password admin password
```

Result

When you restart the administration tool and type `connect`, the administration tool now requires your password before connecting to the server.

For further information about setting and resetting passwords, refer to [set password](#).

Naming Conventions

These rules apply when naming users, groups, topics or queues:

- `$` is illegal at the beginning of the queue or topic names—but legal at the beginning of user and group names.
- A user name cannot contain colon (":") character.
- Space characters are permitted in a description field—if the entire description field is enclosed in double quotes (for example, "description field").
- Both `*` and `>` are wildcards, and cannot be used in names except as wildcards.
For more information about wildcards, see [Wildcards](#).
- Dot separates elements within a destination name (**foo.bar.***) and can be used only for that purpose.

Name Length Limitations

The following length limitations apply for these parameter names:

- Destination name — cannot exceed 249 characters. For more information on topic and queue naming conventions, see [Destination Name Syntax](#).
- Username — cannot exceed 255 characters. The `username` parameter is described in [users.conf](#).
- Group name — cannot exceed 255 characters. The `group-name` parameter is described in [groups.conf](#).
- Client ID — cannot exceed 255 characters.
- Connection URL — cannot exceed 1000 characters.



For more information on Client ID and Connection URL, see [factories.conf](#).

- Passwords — cannot exceed 4096 characters. This length limitation applies to passwords used by the `tibemsd` to authenticate connecting clients or servers.

Command Listing

The command line interface of the administration tool allows you to perform a variety of functions. Note that when a system uses shared configuration files, the actions performed using the administration tool take effect only when connected to the active server.



Many of the commands listed below accept arguments that specify the names of users, groups, topics or queues. For information about the syntax and that apply to these names, see [Naming Conventions](#).

SSL aspects are addressed in [SSL Protocol](#).

The following is an alphabetical listing of the commands including command syntax and a description of each command.

add member

```
add member group_name user_name [ ,user2,user3,... ]
```

Add one or more users to the group. User names that are not already defined are added to the group as external users; see [Administration Commands and External Users and Groups](#).

addprop factory

```
addprop factory factory-name properties ...
```

Adds properties to the factory. Property names are separated by spaces.

See [factories.conf](#) for the list of factory properties.

Example

```
addprop factory MyTopicFactory ssl_trusted=cert1.pem ssl_trusted=cert2.pem  
ssl_verify_host=disabled
```

addprop queue

```
addprop queue queue-name properties,...
```

Adds properties to the queue. Property names are separated by commas.

For information on properties that can be assigned to queues, see [Destination Properties](#).

addprop route

```
addprop route route-name prop=value[ prop-value... ]
```

Adds properties to the route.

Destination (topic and queue) properties must be separated by commas but properties of routes and factories are separated with spaces.

You can set the `zone_name` and `zone_type` parameters when creating a route, but you cannot subsequently change them.

For route properties, see [Configure Routes and Zones](#).

For the configuration file `routes.conf`, see [routes.conf](#).

addprop topic

```
addprop topic topic_name properties,...
```

Adds properties to the topic. Property names are separated by commas.

For information on properties that can be assigned to topics, see [Destination Properties](#).

autocommit

```
autocommit [on|off]
```

When autocommit is set to **on**, the changes made to the configuration files are automatically saved to disk after each command. When autocommit is set to **off**, you must manually use the `commit` command to save configuration changes to the disk.

By default, autocommit is set to **on** when interactively issuing commands.

Entering **autocommit** without parameters displays the current setting of autocommit (on or off).



Regardless of the autocommit setting, the EMS server acts on each admin command immediately making it part of the configuration. The autocommit feature only determines when the configuration is written to the files.

commit

```
commit
```

Commits all configuration changes into files on disk.

compact

```
compact store-name max-time
```

Compacts the store files for the specified store. Compaction is available for stores of type `file` and `mstore`, but is not available for stores of type `dbstore`.

Since compaction can be a lengthy operation and it blocks other operations, *max-time* specifies a time limit (in seconds) for the operation. Note that *max-time* must be a number greater than zero. For `mstore` files, you can optionally specify `nolimit` for the *max-time*. See below for more information.

For stores of type `file`:

- If truncation is not enabled for the store file, the `compact` command does not reduce the file size. Enable truncation using the `file_truncate` parameter in the `stores.conf` file. See [stores.conf](#) for more information.
- We recommend compacting the store files only when the Used Space usage is 30% or less (see [show store](#)).

For stores of type `mstore`:

- The following types of compaction are available:
 - **Time-bound compact**
Use *max-time* to specify a time limit (in seconds) for the compact operation. Time-bound compaction may increase the fragmentation of the store files. This feature is not available by default. Before using it, you need to run the `tibemsdbconvert` tool with option `-version 8.3` on the required `mstore` files. See [tibemsdbconvert Tool](#) for more information.
 - **No-limit compact**
Enter `nolimit` for *max-time*. This triggers a full re-write of the store **with no time limit**. Once started, it is not possible to interrupt the re-write. All other operations (creating new connections, sending and receiving messages, and so forth) are suspended until the store is fully re-written. This can take a very long time for large stores. Using `nolimit` effectively defragments a store file.
- Compaction for `mstores` is not affected by the value of the `mstore_truncate` parameter.

connect

```
connect [server-url {admin|user_name} password]
```

Connects the administration tool to the server. Any administrator can connect. An administrator is either the admin user, any user in the \$admin group, or any user that has administrator permissions enabled. See [Administrator Permissions](#) for more information about administrator permissions.

server-url is usually in the form:

```
protocol://host-name:port-number
```

for example:

```
tcp://myhost:7222
```

The protocol can be `tcp` or `ssl`.

If a user name or password are not provided, the user is prompted to enter a user name and password, or only the password, if the user name was already specified in the command.

You can enter `connect` with no other options and the administrative tool tries to connect to the local server on the default port, which is 7222.

create bridge

```
create bridge source=type:dest_name target=type:dest_name [selector=selector]
```

Creates a bridge between destinations.

type is either `topic` or `queue`.

For further information, see [bridges.conf](#).

create durable

```
create durable topic-name durable-name [property, ... ,property]
```

Creates a static durable subscriber.

For descriptions of parameters and properties, and information about conflict situations, see [durables.conf](#).

create factory

```
create factory factory_name factory_parameters
```

Creates a new connection factory.

For descriptions of factory parameters, see [factories.conf](#).

create group

```
create group group_name "description"
```

Creates a new group of users.

Initially, the group is empty. You can use the `add member` command to add users to the group.

create jndiname

```
create jndiname new_jndiname topic|queue|jndiname name
```

Creates a JNDI name for a topic or queue, or creates an alternate JNDI name for a topic that already has a JNDI name.

The following example will create new JNDI name FOO referring the same object referred by JNDI name BAR

```
create jndiname FOO jndiname BAR
```

create queue

```
create queue queue_name [properties]
```

Creates a queue with the specified name and properties. The possible queue properties are described in [Destination Properties](#). Properties are listed in a comma-separated list, as described in [queues.conf](#).

create route

```
create route name url=URL [properties ...]
```

Creates a route.

The *name* must be the name of the other server to which the route connects.

The local server connects to the destination server at the specified URL. If you have configured fault-tolerant servers, you may specify the URL as a comma-separated list of URLs.

The route properties are listed in [routes.conf](#) and are specified as a space-separated list of parameter name and value pairs.

You can set the *zone_name* and *zone_type* parameters when creating a route, but you cannot subsequently change them.

If a passive route with the specified *name* already exists, this command promotes it to an *active-active* route; see [Active and Passive Routes](#).

For additional information on route parameters, see [Configure Routes and Zones](#).

create rvcmlistener

```
create rvcmlistener transport_name cm_name subject
```

Registers an RVCML listener with the server so that any messages exported to a *tibrvcml* transport (including the first message sent) are guaranteed for the specified listener. This causes the server to perform the TIBCO Rendezvous call *tibrvcmlTransport_AddListener*.

The parameters are:

- *transport_name* — the name of the transport to which this RVCML listener applies.
- *cm_name* — the name of the RVCML listener to which topic messages are to be exported.
- *subject* — the RVCML subject name that messages are published to. This should be the same name as the topic names that specify the export property.

For more information, see [tibrvcml.conf](#) and [Rendezvous Certified Messaging \(RVCML\) Parameters](#).

create topic

```
create topic topic_name [properties]
```

Creates a topic with specified name and properties. See [Destination Properties](#) for the list of properties. Properties are listed in a comma-separated list, as described in [topics.conf](#).

create user

```
create user user_name ["user_description"] [password=password]
```

Creates a new user. Following the user name, you can add an optional description of the user in quotes. The password is optional and can be added later using the `set password` command.



User names cannot contain colon (:) characters.

delete all

```
delete all users|groups|topics|queues|durables [topic-name-pattern|queue-name-pattern]
```

If used as `delete all users|groups|topics|queues|durables` without the optional parameters, the command deletes all users, groups, topics, or queues (as chosen).

If used with a topic or queue, and the optional parameters, such as those seen below, the command deletes all topics and queues that match the topic or queue name pattern.

```
delete all topics|queues topic-name-pattern|queue-name-pattern
```

delete bridge

```
delete bridge source=type:dest_name target=type:dest_name
```

Delete the bridge between the specified source and target destinations.

type is either topic or queue.

See [Destination Bridges](#) for more information on bridges.

delete connection

```
delete connection connection-id
```

Delete the named connection for the client. The connection ID is shown in the first column of the connection description printed by `show connection`.

delete durable

```
delete durable durable-name clientID
```

Delete the named durable subscriber.

When both the durable name and the client ID are specified, the EMS Server looks for a durable named *clientID:durable-name* in the list of durables. If a matching durable subscriber is not found, the administration tool prints an error message including the fully qualified durable name.

See also, [Conflicting Specifications](#).

delete factory

```
delete factory factory-name
```

Delete the named connection factory.

delete group

```
delete group group-name
```

Delete the named group.

delete jndiname

```
delete jndiname jndiname
```

Delete the named JNDI name. Notice that deleting the last JNDI name of a connection factory object will remove the connection factory object as well.

See [The EMS Implementation of JNDI](#) for more information.

delete message

```
delete message messageID
```

Delete the message with the specified message ID.

delete queue

```
delete queue queue-name
```

Delete the named queue.

delete route

```
delete route route-name
```

Delete the named route.

delete rvcmlistener

```
delete rvcmlistener transport_name cm_name subject
```

Unregister an RVCML listener with the server so that any messages being held for the specified listener in the RVCML ledger are released. This causes the server to perform the TIBCO Rendezvous call `tibrvcmlTransport_RemoveListener`.

The parameters are:

- *transport_name* — the name of the transport to which this RVCML listener applies.
- *cm_name* — the name of the RVCML listener to which topic messages are exported.
- *subject* — the RVCML subject name that messages are published to. This should be the same name as the topic names that specify the export property.

For more information, see [tibrvcml.conf](#) and [Rendezvous Certified Messaging \(RVCML\) Parameters](#).

delete topic

```
delete topic topic-name
```

Delete the named topic.

delete user

```
delete user user-name
```

Delete the named user.

disconnect

```
disconnect
```

Disconnect the administrative tool from the server.

echo

```
echo [on|off]
```

Echo controls the reports that are printed into the standard output. When echo is off the administrative tool only prints errors and the output of queries. When echo is on, the administrative tool report also contains a record of successful command execution.

Choosing the parameter on or off in this command controls echo. If echo is entered in the command line without a parameter, it displays the current echo setting (on or off). This command is used primarily for scripts.

The default setting for echo is on.

exit

```
exit (aliases: quit, q, bye, end)
```

Exit the administration tool.

The administrator may choose the `exit` command when there are changes in the configuration have which have not been committed to disk. In this case, the system will prompt the administrator to use the `commit` command before exiting.

grant queue

```
grant queue queue-name user=name | group=name permissions
```

Grants specified permissions to specified user or group on specified queue. The name following the queue name is first checked to be a group name, then a user name.

Specified permissions are added to any existing permissions. Multiple permissions are separated by commas. Enter **all** in the *permissions* string if you choose to grant all possible user permissions.

User permissions are:

- receive
- send
- browse

For more information on queue permissions, see [User Permissions](#).

Destination-level administrator permissions can also be granted with this command. The following are administrator permissions for queues.

- view
- create
- delete
- modify
- purge

For more information on destination permissions, see [Destination-Level Permissions](#).

grant topic

```
grant topic topic-name user=name | group=name permissions
```

Grants specified permissions to specified user or group on specified topic. The name following the topic name is first checked to be a group name, then a user name.

Specified permissions are added to any existing permissions. Multiple permissions are separated by commas. Enter **all** in the *permissions* string if you choose to grant all possible permissions.

Topic permissions are:

- subscribe
- publish
- durable
- use_durable

For more information on topic permissions, see [User Permissions](#).

Destination-level administrator permissions can also be granted with this command. The following are administrator permissions for topics.

- view
- create
- delete
- modify
- purge

For more information on destination permissions, see [Destination-Level Permissions](#).

grant admin

```
grant admin user=name | group=name admin_permissions
```

Grant the named global administrator permissions to the named user or group. For a complete listing of global administrator permissions, see [Global Administrator Permissions](#).

help

```
help (aliases: h, ?)
```

Display help information.

Enter help commands for a summary of all available commands.

Enter help *command* for help on a specific command.

info

```
info (alias: i)
```

Shows server name and information about the connected server.

jaci clear

```
jaci clear
```

Empties the JACI permission cache of all entries.

jaci resetstats

```
jaci resetstats
```

Resets all statistics counters for the JACI cache to zero.

jaci showstats

```
jaci showstats
```

Prints statistics about JACI cache performance.

purge all queues

```
purge all queues [pattern]
```

Purge all or selected queues.

When used without the optional pattern parameter, this command erases all messages in all queues for all receivers.

When used with the *pattern* parameter, this command erases all messages in all queues that fit the pattern (for example: *foo.**).

purge all topics

```
purge all topics [pattern]
```

Purge all or selected topics.

When used without the optional pattern parameter, this command erases all messages in all topics for all subscribers.

When used with the *pattern* parameter, this command erases all messages in all topics that fit the pattern (for example: *foo.**).

purge durable

```
purge durable durable-name
```

Purge all messages in the topic for the named durable subscriber

purge queue

```
purge queue queue-name
```

Purge all messages in the named queue.

purge topic

```
purge topic topic-name
```

Purge all messages for all subscribers on the named topic.

remove member

```
remove member group-name user-name [, user2, user3, ...]
```

Remove one or more named users from the named group.

removeprop factory

```
removeprop factory factory-name properties
```

Remove the named properties from the named factory. See [Connection Factory Parameters](#) for a list of properties.

removeprop queue

```
removeprop queue queue-name properties
```

Remove the named properties from the named queue.

removeprop route

```
removeprop route route-name properties
```

Remove the named properties from the named route.

You cannot remove the URL.

You can set the *zone_name* and *zone_type* parameters when creating a route, but you cannot subsequently change them.

For route parameters, see [Configure Routes and Zones](#).

For the configuration file *routes.conf*, see [routes.conf](#).

removeprop topic

```
removeprop topic topic-name properties
```

Remove the named properties from the named topic.

resume route

```
resume route route-name
```

Resumes sending messages to named route, if messages were previously suspended using the [suspend route](#) command.

revoke admin

```
revoke admin user=name | group=name permissions
```

Revoke the specified global administrator permissions from the named user or group. See [Authentication and Permissions](#), for more information about administrator permissions.

revoke queue

```
revoke queue queue-name user=name | group=name permissions  
revoke queue queue-name * [user | admin | both]
```

Revoke the specified permissions from a user or group for the named queue.

User and group permissions for queues are receive, send, browse, and all. Administrator permissions for queues are view, create, delete, modify, and purge.

If you specify an asterisk (*), all user-level permissions on this queue are removed. You can use the optional admin parameter to revoke all administrative permissions, or the both parameter to revoke all user-level and administrative permissions on the queue.

For more information, see [Authentication and Permissions](#).

revoke topic

```
revoke topic topic-name user=name | group=name permissions  
revoke topic topic-name * [user | admin | both]
```

Revoke the specified permissions from a user or group for the named topic.

User and group permissions for topics are subscribe, publish, durable, use_durable, and all. Administrator permissions for topics are view, create, delete, modify, and purge.

If you specify an asterisk (*), all user-level permissions on this topic are removed. You can use the optional admin parameter to revoke all administrative permissions, or the both parameter to revoke all user-level and administrative permissions on the topic.

For more information, see [Authentication and Permissions](#).

rotatelog

```
rotatelog
```

Force the current log file to be backed up and truncated. The server starts writing entries to the newly empty log file.

The backup file name is the same as the current log file name with a sequence number appended to the filename. The server queries the current log file directory and determines what the highest sequence number is, then chooses the next highest sequence number for the new backup name. For example, if the log file name is tibems.log and there is already a tibems.log.1 and tibems.log.2, the server names the next backup tibems.log.3.

set password

```
set password user-name [password]
```

Set the password for the named user.

If you do not supply a password in the command, the server prompts you to type one.

- To reset a password, type:

```
set password user-name
```

Type a new password at the prompt.

- To remove a password, use this command without supplying a password, and press the **Enter** key at the prompt (without typing a password).

Passwords are a significant point of vulnerability for any enterprise. We recommend enforcing strong standards for passwords.



For security equivalent to single DES (an industry minimum), security experts recommend passwords that contain 8–14 characters, with at least one upper case character, at least one numeric character, and at least one punctuation character.

set server

```
set server parameter=value [parameter=value ...]
```

The **set server** command can control many parameters. Multiple parameters are separated by spaces. The following table describes the parameters you can set with this command.

Parameter	Description
password [= string]	<p>Sets server password used by the server to connect to other routed servers. If the value is omitted it is prompted for by the administration tool. Entered value will be stored in the main server configuration file in mangled form (but not encrypted).</p> <p>To reset this password, enter the empty string twice at the prompt.</p>
authorization=enabled disabled	<p>Sets the authorization mode in the tibemsd.conf file.</p> <p>After a transition from disabled to enabled, the server checks ACL permissions for all subsequent requests. While the server requires valid authentication for existing producers and consumers, it does not retroactively reauthenticate them; it denies access to users without valid prior authentication.</p>

Parameter	Description
<code>log_trace=trace-items</code>	<p>Sets the trace preference on the file defined by the <code>logfile</code> parameter. If <code>logfile</code> is not set, the values are stored but have no effect.</p> <p>The value of this parameter is a comma-separated list of trace options. For a list of trace options and their meanings, see Server Tracing Options.</p> <p>You may specify trace options in three forms:</p> <ul style="list-style-type: none"> • <code>plain</code> A trace option without a prefix character replaces any existing trace options. • <code>+</code> A trace option preceded by <code>+</code> adds the option to the current set of trace options. • <code>-</code> A trace option preceded by <code>-</code> removes the option from the current set of trace options. <p>Examples</p> <p>The following example sets the trace log to only show messages about access control violations.</p> <pre>log_trace=ACL</pre> <p>The next example sets the trace log to show all default trace messages, in addition to SSL messages, but ADMIN messages are not shown.</p> <pre>log_trace=DEFAULT, -ADMIN, +SSL</pre>
<code>console_trace=console-trace-items</code>	<p>Sets trace options for output to <code>stderr</code>. The values are the same as for <code>log_trace</code>. However, console tracing is independent of log file tracing.</p> <p>If <code>logfile</code> is defined, you can stop console output by specifying:</p> <pre>console_trace=-DEFAULT</pre> <p>Note that important error messages (and some other messages) are always output, overriding the trace settings.</p> <p>Examples</p> <p>This example sends a trace message to the console when a TIBCO Rendezvous advisory message arrives.</p> <pre>console_trace=RVADV</pre>

Parameter	Description
<code>client_trace={enabled disabled}</code> <code>[target=location] [filter=value]</code>	<p>Administrators can trace a connection or group of connections. When this property is enabled, the client generates trace output for opening or closing a connection, message activity, and transaction activity. This type of tracing does not require restarting the client program.</p> <p>The client sends trace output to <i>location</i>, which may be either <code>stderr</code> (the default) or <code>stdout</code>.</p> <p>You can specify a filter to selectively trace specific connections. The <i>filter</i> can be <code>user</code>, <code>connid</code> or <code>clientid</code>. The <i>value</i> can be a user name or ID (as appropriate to the filter).</p> <p>When the filter and value clause is absent, the default behavior is to trace all connections.</p> <p>Setting this parameter using the administration tool does not change its value in the configuration file tibemsd.conf.</p>
<code>max_msg_memory=value</code>	<p>Maximum memory the server can use for messages.</p> <p>For a complete description, see <code>max_msg_memory</code> in tibemsd.conf.</p> <p>Specify units as KB, MB or GB. The minimum value is 8MB. Zero is a special value, indicating no limit.</p> <p>Lowering this value will not immediately free memory occupied by messages.</p>
<code>msg_swapping=enabled disabled</code>	Enables or disables the ability to swap messages to disk.
<code>track_message_ids=enabled disabled</code>	Enables or disables tracking messages by MessageID.
<code>track_correlation_ids=enabled disabled</code>	Enables or disables tracking messages by CorrelationID.
<code>ssl_password[=string]</code>	<p>This sets a password for SSL use only.</p> <p>Sets private key or PKCS#12 file password used by the server to decrypt the content of the server identity file. The password is stored in mangled form.</p>

Parameter	Description
<code>ft_ssl_password[=<i>string</i>]</code>	<p>This sets a password for SSL use with Fault Tolerance.</p> <p>Sets private key or PKCS#12 file password used by the server to decrypt the content of the FT identity file. The password is stored in mangled form.</p>
<code>server_rate_interval=<i>num</i></code>	<p>Sets the interval (in seconds) over which overall server statistics are averaged. This parameter can be set to any positive integer greater than zero.</p> <p>Overall server statistics are always gathered, so this parameter cannot be set to zero. By default, this parameter is set to 1.</p> <p>Setting this parameter allows you to average message rates and message size over the specified interval.</p>
<code>statistics=enabled disabled</code>	<p>Enables or disables statistic gathering for producers, consumers, destinations, and routes. By default this parameter is set to disabled.</p> <p>Disabling statistic gathering resets the total statistics for each object to zero.</p>
<code>rate_interval=<i>num</i></code>	<p>Sets the interval (in seconds) over which statistics for routes, destinations, producers, and consumers are averaged. By default, this parameter is set to 3 seconds. Setting this parameter to zero disables the average calculation.</p>
<code>detailed_statistics= NONE PRODUCERS, CONSUMERS, ROUTES</code>	<p>Specifies which objects should have detailed statistic tracking. Detailed statistic tracking is only appropriate for routes, producers that specify no destination, or consumers that specify wildcard destinations. When detailed tracking is enabled, statistics for each destination are kept for the object.</p> <p>Setting this parameter to NONE disables detailed statistic tracking. You can specify any combination of PRODUCERS, CONSUMERS, or ROUTES to enable tracking for each object. If you specify more than one type of detailed tracking, separate each item with a comma.</p>

Parameter	Description
<code>statistics_cleanup_interval=num</code>	Specifies how long (in seconds) the server should keep detailed statistics if the destination has no activity. This is useful for controlling the amount of memory used by detailed statistic tracking. When the specified interval is reached, statistics for destinations with no activity are deleted.
<code>max_stat_memory=num</code>	<p>Specifies the maximum amount of memory to use for detailed statistic gathering. If no units are specified, the amount is in bytes, otherwise you can specify the amount using KB, MB, or GB as the units.</p> <p>Once the maximum memory limit is reached, the server stops collecting detailed statistics. If statistics are deleted and memory becomes available, the server resumes detailed statistic gathering.</p>

setprop factory

```
setprop factory factory-name properties ...
```

Set the properties for a connection factory, overriding any existing properties. Multiple properties are separated by spaces. See [Connection Factory Parameters](#) for the list of the properties that can be set for a connection factory.

setprop queue

```
setprop queue queue-name properties, ...
```

Set the properties for a queue, overriding any existing properties. Any properties on a queue that are not explicitly specified by this command are removed.

Multiple properties are separated by commas. See [Destination Properties](#) for the list of the properties that can be set for a queue.

setprop route

```
setprop route route-name properties ...
```

Set the properties for a route, overriding any existing properties. Any properties on a route that are not explicitly specified by this command are removed.

You can set the `zone_name` and `zone_type` parameters when creating a route, but you cannot subsequently change them.

Multiple properties are separated by spaces. For route parameters, see [routes.conf](#) and [Configure Routes and Zones](#).

setprop topic

```
setprop topic topic-name properties
```

Set topic properties, overriding any existing properties. Any properties on a topic that are not explicitly specified by this command are removed.

Multiple properties are separated by commas. See [Destination Properties](#) for the list of the properties that can be set for a topic.

show bridge

```
show bridge topic|queue bridge_source
```

Display information about the configured bridges for the named topic or queue. The *bridge_source* is the name of the topic or queue established as the source of the bridge.

The following is example output for this command:

Target Name	Type	Selector
queue.dest	Q	
topic.dest.1	T	"urgency in ('high', 'medium')"
topic.dest.2	T	

The names of the destinations to which the specified destination has configured bridges are listed in the Target Name column. The type and the message selector (if one is defined) for the bridge are listed in the Type and Selector column.

show bridges

```
show bridges [type=topic|queue] [pattern]
```

Shows a summary of the destination bridges that are currently configured. The type option specifies the type of destination established as the bridge source. For example, `show bridges topic` shows a summary of configured bridges for all topics that are established as a bridge source. The *pattern* specifies a pattern to match for source destination names. For example `show bridges foo.*` returns a summary of configured bridges for all source destinations that match the name `foo.*`. The type and *pattern* are optional.

The following is example output for this command:

Source Name	Queue Targets	Topic Targets
Q queue.source	1	1
T topic.source	1	2

Destinations that match the specified pattern and/or type are listed in the Source Name column. The number of bridges to queues for each destination is listed in the Queue Targets column. The number of bridges to topics for each destination is listed in the Topic Targets column.

show config

```
show config
```

Shows the configuration parameters for the connected server. The output includes:

- configuration files
- server database
- server JVM
- server JDBC database
- listen ports
- configuration settings
- message tracking
- server tracing parameters
- statistics settings
- fault-tolerant setup

- external transport setup
- server SSL setup

show consumer

```
show consumer consumerID
```

Shows details about a specific consumer. The *consumerID* can be obtained from the [show consumers](#) output.

show consumers

```
show consumers [topic=name | queue=name] [durable] [user=name] [connection=id]  
[sort=conn|user|dest|msgs] [full]
```

Shows information about all consumers or only consumers matching specified filters. Output of the command can be controlled by specifying the `sort` or `full` parameter. If the `topic` or `queue` parameter is specified, then only consumers on destinations matching specified queue or topic are shown. The `user` and/or `connection` parameters show consumers only for the specified user or connection. Note that while the queue browser is open, it appears as a consumer in the EMS server.

The `durable` parameter shows only durable topic subscribers and queue receivers, but it does not prevent queue consumers to be shown. To see only durable topic consumers, use:

```
show consumers topic=> durable
```

The `sort` parameter sorts the consumers by either connection ID, user name, destination name, or number of pending messages. The `full` parameter shows all columns listed below and can be as wide as 120-140 characters or wider. Both topic and queue consumers are shown in separate tables, first the topic consumers and then the queue consumers.



When connected to an EMS 8.0 or higher server, this command no longer displays offline durable subscribers. In order to see offline durables, use the command [show durables](#) or [show subscriptions](#).

show consumers (description of output fields)

Heading	Description
Id	Consumer ID.
Conn	Consumer's connection ID. If performed on an EMS 7.x or earlier server, this field displays '-' to indicate a disconnected durable topic subscriber.
Sess	Consumer's session ID. If performed on an EMS 7.x or earlier server, this field displays '-' to indicate a disconnected durable topic subscriber.

Heading	Description
T	<p>Consumer type character which can be one of:</p> <p>For topic consumer:</p> <ul style="list-style-type: none"> • T - non-durable topic subscriber. • D - durable topic subscriber. • R - system-created durable for a routed topic. • P - proxy subscriber on route's temporary topic. <p>For queue consumer:</p> <ul style="list-style-type: none"> • Q - regular queue receiver. • q - inactive queue receiver. • P - system-created receiver on global queue for user receiver created in one of routes.
Topic/Queue	Name of the subscription topic or queue.
Name	(Topics Only.) Durable or shared subscription name. This column is shown for topic consumers if at least one consumer is a durable or shared consumer.
SAS[NMBS]	<p>Description of columns:</p> <ul style="list-style-type: none"> • S - '+' if consumer's connection started, '-' otherwise. • A - mode of consumer's session, values are: <ul style="list-style-type: none"> – N - no acknowledge – A - auto acknowledge – D - dups_ok acknowledge – C - client acknowledge – T - session is transactional – X - XA or MS DTC session – Z - connection consumer • S - '+' if consumer has a selector, '-' otherwise. • N - (TOPICS ONLY) '+' if subscriber is "NoLocal." • B - (QUEUES ONLY) '+' if consumer is a queue browser. • S - (TOPICS ONLY) '+' if this is a shared consumer.
Pre	Prefetch value of the consumer's destination.
Pre Dlv	Number of prefetch window messages delivered to consumer
Msgs Sent	Current number of messages sent to consumer which are not yet acknowledged by consumer's session.

Heading	Description
Size Sent	Combined size of unacknowledged messages currently sent to consumer. Value is rounded and shown in bytes, (K)ilobytes, (M)egabytes or (G)igabytes.
Pend Msgs	(Topics Only.) Total number of messages pending for the topic consumer.
Pend Size	(Topics Only.) Combined size of messages pending for the topic consumer. Value is rounded and shown in bytes, (K)ilobytes, (M)egabytes or (G)igabytes.
Uptime	Uptime of the consumer.
Last Sent	Approximate time elapsed since last message was sent by the server to the consumer. Value is approximate with precision of 1 second.
Last Ackd	Approximate time elapsed since last time a message sent to the consumer was acknowledged by consumer's session. Value is approximate with precision of 1 second.
Total Sent	Total number of messages sent to consumer since it was created. This includes resends due to session recover or rollback.
Total Acked	Total number of messages sent to the consumer and acknowledged by consumer's session since consumer created.

show connections

```
show connections [type=q|t|s] [host=hostname] [user=username] [version] [address]
[counts] [full]
```

Show connections between clients and server. The table [show connections \(description of output fields\)](#) describes the output.

The `type` parameter selects the subset of connections to display as shown in the following table. The `host` and `user` parameters can further narrow the output to only those connections involving a specific host or user. When the `version` flag is present, the display includes the client's version number.

If the `address` parameter is specified, then the IP address is printed in the output table. If the `counts` parameter is specified, then number of producers, consumers and temporary destinations are printed. Specifying the `full` parameter prints all of the available information.

Type	Description
type=q	Show queue connections only.
type=t	Show topic connections only.
type=s	Show system connections only.
absent	Show queue and topic connections, but not system connections.

show connections (description of output fields)

Heading	Description
L	<p>The type of client. Can be one of the following:</p> <ul style="list-style-type: none"> • J — Java client • C — C client • # — C# client • - — unknown system connection
Version	The EMS version of the client.
ID	Unique connection ID. Each connection is assigned a unique, numeric ID that can be used to delete the connection.
FSXT	<p>Connection type information.</p> <p>The F column displays whether the connection is fault-tolerant.</p> <ul style="list-style-type: none"> • - — not a fault-tolerant connection, that is, this connection has no alternative URLs • + — fault-tolerant connection, that is, this connection has alternative URLs <p>The S column displays whether the connection uses SSL.</p> <ul style="list-style-type: none"> • - — connection is not SSL • + — connection is SSL <p>The X column displays whether the connection is an XA or MS DTC transaction.</p> <ul style="list-style-type: none"> • - — connection is not XA or MS DTC • + — connection is either an XA or MS DTC connection <p>The T column displays the connection type.</p> <ul style="list-style-type: none"> • C — generic user connection • T — user TopicConnection • Q — user QueueConnection • A — administrative connection • R — system connection to another route server • F — system connection to the fault-tolerant server
S	Connection started status, + if started, - if stopped.
IP Address	<p>Shows client IP address.</p> <p>The address or full parameter must be specified to display this field.</p>
Port	<p>The ephemeral port used by the client on the client machine.</p> <p>The address or full parameter must be specified to display this field.</p>

Heading	Description
Host	Connection's host name. (If the name is not available, this column displays the host's IP address.)
Address	Connection's IP address. If you supply the keyword <code>address</code> , then the table includes this column.
User	Connection user name. If a user name was not provided when the connection was created, it is assigned the default user name <code>anonymous</code> .
ClientID	Client ID of the connection.
Sess	Number of sessions on this connection.
Prod	Number of producers on this connection. The <code>counts</code> or <code>full</code> parameter must be specified to display this field.
Cons	Number of consumers on this connection. The <code>counts</code> or <code>full</code> parameter must be specified to display this field.
TmpT	Number of temporary topics created by this connection. The <code>counts</code> or <code>full</code> parameter must be specified to display this field.
TmpQ	Number of temporary queues created by this connection. The <code>counts</code> or <code>full</code> parameter must be specified to display this field.
Uncomm	Number of messages in uncommitted transactions on the connection. The <code>counts</code> or <code>full</code> parameter must be specified to display this field.
UncommSize	The combined size, in bytes, of messages in uncommitted transactions on the connection. The <code>counts</code> or <code>full</code> parameter must be specified to display this field.
Uptime	Time that the connection has been in effect.

show db

```
show db
```

Print a summary of the server's databases. Databases are also printed by [show stores](#), the preferred command.

See [show store](#) for details about a specific database.

show durable

```
show durable durable-name
```

Show information about a durable subscriber.

show durable (description of output field)

Heading	Description
Durable Subscriber	Fully qualified name of the durable subscriber. This name concatenates the client ID (if any) and the subscription name (separated by a colon).
Subscription name	Full name of the durable subscriber.
Shared	yes if this is a shared durable subscription, no otherwise.
Client ID	Client ID of the subscriber's connection.
Topic	The topic from which the durable subscription receives messages.
Type	dynamic—created by a client static—configured by an administrator
Status	online offline
Username	Username of the durable subscriber (that is, of the client's connection). If the durable subscriber is currently offline, the value in this column is offline.
Consumer ID	This internal ID number is not otherwise available outside the server.
No Local	enabled—the subscriber does not receive messages sent from its local connection (that is, the same connection as the subscriber). disabled—the subscriber receives messages from all connections.
Selector	The subscriber receives only those messages that match this selector.
Pending Msgs	Number of all messages in the topic. (This count includes the number of delivered messages.)
Delivered Msgs	Number of messages in the topic that have been delivered to the durable subscriber, but not yet acknowledged.
Pending Msgs Size	Total size of all pending messages

show durables

```
show durables [pattern]
```

If a pattern is not entered, this command shows a list of all durable subscribers on all topics.

If a pattern is entered (for example `foo.*`) this command shows a list of durable subscribers on topics that match that pattern.

show durable (description of output fields)

Heading	Description
Topic Name	Name of the topic. An asterisk preceding this name indicates a dynamic durable subscriber. Otherwise the subscriber is static (configured by an administrator).
Durable	Full name of the durable subscriber.
Shared	Y to indicate that this is a shared durable subscription, N otherwise.
User	Name of the user of this durable subscriber. If the durable subscriber is currently <code>offline</code> , the value in this column is <code>offline</code> . If this is a shared durable subscription, the value of this column is <code>shared</code> . For users defined externally, there is an asterisk in front of the user name.
Msgs	Number of pending messages
Size	Total size of pending messages

For more information, see [Destination Properties](#).

show factory

```
show factory factory-name
```

Shows properties of specified factory.

show factories

```
show factories [generic|topic|queue]
```

Shows all factories. You can refine the listed output by specifying only generic, topic, or queue factories be listed.

show jndiname

```
show jndiname jndi-name
```

Shows the object that the specified name is bound to by the JNDI server.

show jndinames

```
show jndinames [type]
```

The optional parameter *type* can be:

- destination
- topic
- queue
- factory
- topicConnectionFactory
- queueConnectionFactory

When type is specified only JNDI names bound to objects of the specified type are shown. When type is not specified, all JNDI names are shown.

show group

```
show group group-name
```

Shows group name, description, and number of members in the group.

For groups defined externally, there is an asterisk in front of the group name. Only external groups with at least one currently connected user are shown.

show groups

```
show groups
```

Shows all user groups.

For groups defined externally, there is an asterisk in front of the group name.

show members

```
show members group-name
```

Shows all user members of specified user group.

show message

```
show message messageID
```

Shows the message for the specified message id.

This command requires that tracking by message ID be turned on using the `track_message_ids` configuration parameter.

show messages

```
show messages correlationID
```

Shows the message IDs of all messages with the specified correlation ID set as `JMSCorrelationID` message header field. You can display the message for each ID returned by this command by using the [show message *messageID*](#) command.

This command requires that tracking by correlation ID be turned on using the `track_correlation_ids` configuration parameter.

show parents

```
show parents user-name
```

Shows the user's parent groups. This command can help you to understand the user's permissions.

show queue

```
show queue queue-name
```

Shows the details for the specified queue.



If the queue is a routed queue, specify only the name of the queue (do not specify the server using the `queue-name@server` form).

show queue (description of output fields)

Heading	Description
Queue	Full name of the queue.

Heading	Description
Type	dynamic—created by a client static—configured by an administrator
Properties	A list of property names that are set on the queue, and their values. For an index list of property names, see Destination Properties .
JNDI Names	A list of explicitly assigned JNDI names that refer to this queue.
Bridges	A list of bridges from this queue to other destinations.
Receivers	Number of consumers on this queue.
Pending Msgs	Number of all messages in the queue, followed by the number of persistent messages in parenthesis. These counts include the number of delivered messages.
Delivered Msgs	Number of messages in the queue that have been delivered to a consumer, but not yet acknowledged.
Pending Msgs Size	Total size of all pending messages, followed by the size of all persistent messages in parenthesis.

show queues

```
show queues [pattern-name [notemp|static|dynamic] [first=n|next=n|last=n]]
```

If a *pattern-name* is not entered, this command shows a list of all queues.

If a *pattern-name* is entered (for example `foo.*` or `foo.>`) this command shows a list of queues that match that pattern. See [Wildcards * and >](#) for more information about using wildcards.

You can further refine the list of queues that match the pattern by using one of the following parameters:

- `notemp` — do not show temporary queues
- `static` — show only static queues
- `dynamic` — show only dynamic queues

When a *pattern-name* is entered, you can also cursor through the list of queues using one of the following commands, where *n* is whole number:

- `first=n` — show the first *n* queues
- `next=n` — show the next *n* queues
- `last=n` — show the next *n* queues and terminate the cursor

The cursor examines *n* queues and displays queues that match the *pattern-name*. Because it does not traverse the full list of queues, the cursor may return zero or fewer than *n* queues. To find all matching queues, continue to use next until you receive a `Cursor complete` message.

A `*` appearing before the queue name indicates a dynamic queue.

show queues (description of output fields)

Heading	Description
Queue Name	Name of the queue. If the name is prefixed with an asterisk (*), then the queue is temporary or was created dynamically. Properties of dynamic and temporary queues cannot be changed.
SNFGXIBCT	Prints information on the topic properties in the order (S)ecure (N)sender_name or sender_name_enforced (F)ailsafe (G)lobal e(X)clusive (I)mport (B)ridge (C)flowControl (T)race The characters in the value section show: - Property not present + Property is present, and was set on the topic itself * Property is present, and was inherited from another queue Note that inherited properties cannot be removed.
Pre	Prefetch value. If the value is followed by an asterisk (*), then it is inherited from another queue or is the default value.
Rcvrs	Number of currently active receivers
All Msgs	
Msgs	Number of pending messages
Size	Total size of pending messages
Persistent Msgs	
Msgs	Number of pending persistent messages
Size	Total size of pending persistent messages

For more information, see [Destination Properties](#).

show route

```
show route route-name
```

Shows the properties (URL and SSL properties) of a route.

show routes

```
show routes
```

Shows the properties (URL and SSL properties) of all created routes.

These commands print the information described in the following table.

Heading	Description
Route	Name of the route.

Heading	Description
T	Type of route: <ul style="list-style-type: none"> • A indicates an active route. • P indicates a passive route.
ConnID	Unique ID number of the connection from this server to the server at the other end of the route. A hyphen (-) in this column indicates that the other server is not connected.
URL	URL of the server at the other end of the route.
ZoneName	Name of the zone for the route.
ZoneType	Type of the zone: <ul style="list-style-type: none"> • m indicates a multi-hop zone. • 1 indicates a one-hop zone.

show rvctransportledger

```
show rvctransportledger transport_name [subject-or-wildcard]
```

Displays the TIBCO Rendezvous certified messaging (RVCN) ledger file entries for the specified transport and the specified subject. You can specify a subject name, use wildcards to retrieve all matching subjects, or omit the subject name to retrieve all ledger file entries.

For more information about ledger files and the format of ledger file entries, see TIBCO Rendezvous documentation.

show rvcmlisteners

```
show rvcmlisteners
```

Shows all RVCN listeners that have been created using the `create rvcmlistener` command or by editing the `tibrvcn.conf` file.

show server

```
show server (aliases: info, i)
```

Shows server name and information about the connected server.

show stat

```
show stat consumers [topic=name|queue=name] [user=name]
                    [connection=id] [total]
show stat producers [topic=name|queue=name] [user=name]
                    [connection=id] [total]
show stat route name [topic=name|queue=name] [total] [wide]
show stat topic name [total] [wide]
show stat queue name [total] [wide]
```

Displays statistics for the specified item. You can display statistics for consumers, producers, routes, or destinations. Statistic gathering must be enabled for statistics to be displayed. Also, detailed statistics for each item can be displayed if detailed statistic tracking is enabled. Averages for inbound/outbound

messages and message size are available if an interval is specified in the `rate_interval` configuration parameter.

The `total` keyword specifies that only total number of messages and total message size for the item should be displayed. The `wide` keyword displays inbound and outbound message statistics on the same line.

See [Server Statistics](#) for a complete description of statistics and how to enable/disable statistic gathering options.



When connected to an EMS 8.0 or higher server, this command does not return statistics for offline durable subscribers.

show state

```
show state
```

Shows the state and a minimal subset of the information about the connected EMS server.

show store

```
show store store-name
```

Show the details of a specific store. This command can be used to get details about either a file-based store or a database store.

The *store-name* must be the exact name of a specific store.

This command prints a table of information described in the following table.

Heading	Description
Store	Name of the store.
Type	Type of store: <ul style="list-style-type: none"> • <code>file</code> indicates a file-based store. • <code>dbstore</code> indicates a database store. • <code>mstore</code> indicates an mstore.
Message Count	The number of messages that are stored in the file.
Swapped Count	The number of messages that have been swapped from process memory to store file.
Average Write Time	Average time in seconds a write call takes. (Not available for asynchronous file stores.)
Write Usage	The ratio between time spent within write calls and the time specified by the server_rate_interval . (Not available for asynchronous file stores.)
Headings specific to file-based stores	
File	File name associated with this store file, as it is set by the file parameter in the stores.conf file.

Heading	Description
Access Mode	<p>asynchronous — the server stores messages in the file using asynchronous I/O calls.</p> <p>synchronous — the server stores messages in the file using synchronous I/O calls.</p>
Pre-allocation Minimum	The amount of disk space, if any, that is preallocated to this file.
CRC	<p>enabled — the server uses CRC to validate checksum data when reading the store file.</p> <p>disabled — the server does not validate checksum data when reading the store file.</p>
Periodic Truncation	<p>enabled — the EMS server occasionally truncates the store file, relinquishing unused disk space.</p> <p>disabled — the EMS server does not truncate the store file to relinquish unused disk space.</p>
Destination Defrag Batch Size	The size of the batch used by the destination defrag feature.
File Size	The size of the store file, including unused allocated file space.
Free Space	The amount of unused allocated file space.
Fragmentation	The level of fragmentation in the file.
Used Space	The amount of used space in the file.
Message Size	Total size of all messages in the file.
Swapped Size	The total size of swapped messages in the file.
Storage Write Rate	The number of bytes written per second.
Headings specific to mstores	
Note that output for mstores includes many of the same fields available to file-based stores.	
Access Mode	<p>asynchronous — the server writes messages in the mstore files using asynchronous I/O calls.</p> <p>synchronous — the server writes messages in the mstore files using synchronous I/O calls.</p>
Time-bound compact	<p>available — this mstore can be compacted in a time-bound manner or through the <code>mstore_truncate</code> property.</p> <p>unavailable — this mstore <i>cannot</i> be compacted in a time-bound manner or through the <code>mstore_truncate</code> property.</p>

Heading	Description
Periodic Truncation	<p>enabled — the server occasionally truncates the mstore files, relinquishing unused disk space.</p> <p>disabled — the server does not truncate the mstore files to relinquish unused disk space.</p>
Discard Scan Interval	The maximum length of time that the EMS server takes to examine all messages in the mstore. This interval is controlled with the <code>scan_iter_interval</code> parameter in the <code>stores.conf</code> file.
Discard Scan Interval Bytes	The bytes read and processed every Discard Scan Interval. This number is proportional to the mstore file size, and must be kept within the limits of your storage medium. See Understanding mstore Intervals for more information.
First Scan Finished	<p>true — all the data in the store has been examined at least once since the EMS server startup.</p> <p>false — not all data has been examined since the EMS server last started. When false, certain server statistics (such as the Message Count field) may be underreported as a result of expired or purged messages still in the store. See Implications for Statistics for more information.</p>
Storage Write Rate	The number of bytes written per second.
Headings specific to database stores	
JDBC Driver Name	The name of the JDBC database server.
JDBC URL	The location of the JDBC database server.
Username	The username that the EMS server uses to access the database.
Dialect	The SQL dialect used to construct SQL commands.

show stores

```
show stores
```

Print a list of the server's stores.

show topic

```
show topic topic-name
```

show topic (description of output fields)

Heading	Description
Topic	Full name of the topic.

Heading	Description
Type	dynamic—created by a client static—configured by an administrator
Properties	A list of property names that are set on the topic, and their values. For an index list of property names, see Destination Properties .
JNDI Names	A list of explicitly assigned JNDI names that refer to this topic.
Bridges	A list of bridges from this topic to other destinations.
Subscriptions	Number of subscriptions on this topic. (This count also includes durable subscriptions.)
Durable Subscriptions	The number of durable subscriptions on the topic.
Consumers	Number of active consumers on this topic. Note: When a durable consumer is offline, it is not included in the count reported here. However, if this command is performed on an EMS 7.x or earlier server, the count also includes offline durable consumers.
Durable Consumers	Number of active durable consumers on this topic. Note: When a durable consumer is offline, it is not included in the count reported here. However, if this command is performed on an EMS 7.x or earlier server, the count also includes offline durable consumers.
Pending Msgs	The total number of messages sent but not yet acknowledged by the consumer, followed by the number of persistent messages in parenthesis. These counts include copies sent to multiple subscribers.
Pending Msgs Size	Total size of all pending messages, followed by the size of all persistent messages in parenthesis.
The server accumulates the following statistics only when the administrator has enabled statistics. Otherwise these items are zero.	
Total Inbound Msgs	Cumulative count of all messages delivered to the topic.
Total Inbound Bytes	Cumulative total of message size over all messages delivered to the topic.
Total Outbound Msgs	Cumulative count of messages consumed from the topic by consumers. Each consumer of a message increments this count independently of other consumers, so one inbound message results in n outbound messages (one per consumer).
Total Outbound Bytes	Cumulative total of message size over all messages consumed from the topic by consumers. Each consumer of a message contributes this total independently of other consumers.

show topics

```
show topics [pattern-name [notemp|static|dynamic] [first=n|next=n|last=n]]
```

If a *pattern-name* is not entered, this command shows a list of all topics.

If a *pattern-name* is entered (for example `foo.*` or `foo.>`) this command shows a list of topics that match that pattern. See [Wildcards](#) * and > for more information about using wildcards.

You can further refine the list of topics that match the pattern by using one of the following parameters:

- `notemp` — do not show temporary topics
- `static` — show only static topics
- `dynamic` — show only dynamic topics

When a *pattern-name* is entered, you can also cursor through the list of topics using one of the following commands, where *n* is whole number:

- `first=n` — show the first *n* topics
- `next=n` — show the next *n* topics
- `last=n` — show the next *n* topics and terminate the cursor

The cursor examines *n* topics and displays topics that match the *pattern-name*. Because it does not traverse the full list of topics, the cursor may return zero or fewer than *n* topics. To find all matching topics, continue to use `next` until you receive a `Cursor complete` message.

show topics (description of output fields)

Heading	Description
Topic Name	Name of the topic. If the name is prefixed with an asterisk (*), then the topic is temporary or was created dynamically. Properties of dynamic and temporary topics cannot be changed.
SNFGEIBCTM	Prints information on the topic properties in the order: (S)ecure (N)sender_name or sender_name_enforced (F)ailsafe (G)lobal (E)xport (I)mport (B)ridge (C)flowControl (T)race (M)ulticast The characters in the value section show: - Property not present + Property is present, and was set on the topic itself * Property is present, and was inherited from another topic Note that inherited properties cannot be removed.
Subs	Number of current subscriptions on the topic, including durable subscriptions. If this command is performed on an EMS 7.x or earlier server, the count reflects the number of <i>subscribers</i> , not the number of subscriptions.

Heading	Description
Durs	Number of durable subscriptions on the topic. If this command is performed on an EMS 7.x or earlier server, the count reflects the number of durable <i>subscribers</i> , not the number of subscriptions.
All Msgs Msgs	The total number of messages sent but not yet acknowledged by the consumer. This count includes copies sent to multiple subscribers. To see the count of actual messages (not multiplied by the number of topic subscribers) sent to all destinations, use the show server command.
Size	Total size of pending messages
Persistent Msgs Msgs	The total number of persistent messages sent but not yet acknowledged by the consumer.
Size	Total size of pending persistent messages

For more information, see [Destination Properties](#).

show subscriptions

```
show subscriptions [topic=name] [name=sub-name] [shared=only|none] [durable=only|none] [sort=msgs|topic|name|cons|id]
```

This command prints information about all topic subscriptions, or only subscriptions matching specified filters. Command output is controlled using the sort parameter.

If `topic=name` is specified, then only subscriptions on destinations matching specified topic are shown.

If `name=sub-name` is specified, then only subscriptions of that name are shown.

If `durable=only` is specified, then only durable subscriptions are shown.

If `durable=none` is specified, then only non-durable subscriptions are shown.

If `shared=only` is specified, then only shared subscriptions are shown.

If `shared=none` is specified, then only unshared subscriptions are shown.

The parameter `sort` allows you to specify how the command output is sorted in the output table. You can use to sort by number of pending messages, topic name, subscription name, number of consumers on that subscription, or the subscription's identifier.

show subscriptions (description of output fields)

Heading	Description
Id	The ID of the subscription.
T	The subscription type: <ul style="list-style-type: none"> T — non-durable subscription D — durable subscription

Heading	Description
Topic	Name of the topic associated with the subscription.
Name	Name of the subscription (durable or shared name). If this is an unshared non-durable subscription, this value is empty.
SS	Description of columns: <ul style="list-style-type: none"> • S - '+' if the subscription has a selector, '-' otherwise. • S - '+' if the subscription is shared, '-' otherwise.
Cons Count	The number of active consumers on this subscription. For an unshared non-durable subscription, the value is always 1. For a durable subscription, the value can be 0, meaning that there is no active consumer and the subscription is offline.
Pend Msgs	Total number of messages pending for the subscription.
Pend Size	Combined size of messages pending for the subscription. Value is rounded and shown in bytes, (K)ilobytes, (M)egabytes or (G)igabytes.
Uptime	The length of time, in hours, minutes, and seconds, since the subscription was created.

show transaction

```
show transaction XID
```

Shows a list of messages that were sent or received within the specified transaction. This command returns information on transactions in prepared, ended, and roll back states only. Transactions in a suspended or active state are not included.

show transaction (description of output fields)

Heading	Description
State	Transaction state: <ul style="list-style-type: none"> • A active • E ended • R rollback only • P prepared • S suspended Suspended transactions can be rolled back, but cannot be rolled forward (committed).

Heading	Description
Remaining time before timeout	The seconds remaining before the TX timeout is reached. For example, 3 sec. This field is only applicable for transactions in State ENDSUCCESS or ROLLBACKONLY.
Messages to be consumed	
Message ID	The message ID of the message. null indicates the message ID could not be obtained or was disabled. If <code>track_message_ids</code> is not enabled, this field displays Disabled.
Type	The destination type to which the message was sent: <ul style="list-style-type: none"> • Q queue • T topic
Destination	The destination name to which the message was sent. null indicates that destination could not be found.
Consumer ID	The consumer ID of the Consumer that is consuming the message. Zero indicates that the consumer is offline.
Messages to be produced	
Message ID	The message ID of the message. null indicates the message ID could not be obtained or was disabled. If <code>track_message_ids</code> is not enabled, this field displays Disabled.
Type	The destination type to which the message was sent: <ul style="list-style-type: none"> • Q queue • T topic
Destination	The destination name to which the message was sent. null indicates that destination could not be found.
JMSTimestamp	The timestamp indicating the time at which the message was created.

show transactions

```
show transactions
```

Shows the XID for all client transactions that were created using the XA or MS DTC interfaces. Each row presents information about one transaction. The XID is the concatenation of the Format ID, GTrid Len, Bqual Len, and Data fields for a transaction. For example, if show transactions returns the row:

State	Format ID	GTrid Len	Bqual Len	Data
E	0	6	2	branchid

then the XID is 0 6 2 branchid.

Note that the spaces are required.

show transactions (description of output fields)

Heading	Description
State	<p>Transaction state:</p> <ul style="list-style-type: none"> • A active • E ended • R rollback only • P prepared • S suspended <p>Suspended transactions can be rolled back, but cannot be rolled forward (committed).</p>
Format ID	<p>The XA transaction format identifier.</p> <p>0 = OSI CCR naming is used</p> <p>>0 = some other format is used</p> <p>-1 = NULL</p>
GTrid Len	The number of bytes that constitute the global transaction ID.
Bqual Len	The number of bytes that constitute the branch qualifier.
Data	The global transaction identifier (gtrid) and the branch qualifier (bqual).

show transport

```
show transport transport
```

Displays the configuration for the specified transport defined in [transports.conf](#).

See [Configure EMS Transports for TIBCO FTL](#), [Configure Transports for Rendezvous](#), and [Configure Transports for SmartSockets](#) for details.

show transports

```
show transports
```

Lists all configured transport names in [transports.conf](#).

show user

```
show user user-name
```

Shows user name and description. If no user name is specified, this command displays the currently logged in user.

For users defined externally, there is an asterisk in front of the user name.

show users

```
show users
```

Shows all users.

For users defined externally, there is an asterisk in front of the user name. Only currently connected external users are shown.

showacl admin

```
showacl admin
```

Shows all administrative permissions for all users and groups, but does not include administrative permissions on destinations.

showacl group

```
showacl group group-name [admin]
```

Shows all permissions set for a given group. Shows the group and the set of permissions. You can optionally specify `admin` to show only the administrative permissions for destinations or principals. Specifying `showacl admin` shows all administrative permissions for all users and groups (not including administrative permissions on destinations).

showacl queue

```
showacl queue queue-name [admin]
```

Shows all permissions set for a queue. Lists all entries from the `acl` file. Each entry shows the “grantee” (user or group) and the set of permissions. You can optionally specify `admin` to show only the administrative permissions for destinations or principals. Specifying `showacl admin` shows all administrative permissions for all users and groups (not including administrative permissions on destinations).

showacl topic

```
showacl topic topic-name [admin]
```

Shows all permissions set for a topic. Lists all entries from the `acl` file. Each entry shows the “grantee” (user or group) and the set of permissions. You can optionally specify `admin` to show only the administrative permissions for destinations or principals. Specifying `showacl admin` shows all administrative permissions for all users and groups (not including administrative permissions on destinations).

showacl user

```
showacl user user-name [admin | all | admin-all]
```

Shows the user and the set of permissions granted to the user for destinations and principals.

`showacl user username` — displays permissions granted directly to the user. (An administrator can use this form of the command to view own permissions, even without permissions to view any other user permissions.)

`showacl user username admin` — displays administrative permissions granted directly to the user.

`showacl user username all` — displays direct and inherited (from groups to which the user belongs) permissions.

`showacl user username admin-all` — displays all administrative permissions for a given user (direct and inherited)



The output from this command displays inherited permissions prefixed with a '*'. Inherited permissions cannot be changed. An attempt to revoke an inherited permission for the principal user will not change the permission.

shutdown

```
shutdown
```

Shuts down currently connected server.

suspend route

```
suspend route route-name
```

Suspends outgoing messages to the named route.

Message flow can be recovered later using the command `resume route`.

time

```
time [on | off]
```

Specifying on places a timestamp before each command's output. By default, the timestamp is off.

timeout

```
timeout [seconds]
```

Show or change the current command timeout value. The timeout value is the number of seconds the Administration Tool will wait for a response from the server after sending a command.

By default, the timeout is 30 seconds. When `timeout` is entered with the optional *seconds* parameter, the timeout value is reset to the specified number of seconds. When entered without parameter, the current timeout value is returned.

transaction commit

```
transaction commit XID
```

Commits the transaction identified by the transaction ID. The transaction must be in the ended or prepared state. To obtain a transaction ID, issue the `show transactions` command, and cut and paste the XID into this command.

transaction rollback

```
transaction rollback XID
```

Rolls back the transaction identified by the transaction ID. The transaction must be in the ended, rollback only, or the prepared state. To obtain a transaction ID, issue the `show transactions` command, and cut and paste the XID into this command.



Messages sent to a queue with `prefetch=none` and `maxRedelivery=number` properties are not received *number* times by an EMS application that receives in a loop and does an XA rollback after the XA prepare phase.

updatecrl

```
updatecrl
```

Immediately update the server's certificate revocation list (CRL).

whoami

```
whoami
```

Alias for the `show user` command to display the currently logged in user.

Configuration Files

This chapter describes configuring TIBCO Enterprise Message Service.

Location of Configuration Files

The installation process places a complete set of configuration files in `EMS_HOME/samples/config`. For deployment, we recommend copying files from this directory to a production configuration directory, and modifying those copies.

When selecting a production configuration directory, we recommend using a file system with regular backup commensurate with your need for reliability and disaster recovery. It is essential that the EMS server have both read and write privileges in the configuration directory.

Mechanics of Configuration

Configuration Files

The EMS server reads configuration files only once, when the server starts. It ignores subsequent changes to the configuration files. If you change a configuration file, use the [shutdown](#) command from the EMS Administration Tool to shutdown the server and then restart the server as described in [Running the EMS Server](#).

Administrative Requests

You can also change the server configuration with administrative requests, using either `tibemsadmin` (a command line tool), the Java or .NET administrative APIs, or TIBCO Administrator™ (a separate TIBCO product).

When the server validates and accepts an administrative request, it writes the change to the appropriate configuration file as well (overwriting any manual changes to that file). This policy keeps configuration files current in case the server restarts (for example, in a fault-tolerant situation, or after a hardware failure).

Re-installing or updating EMS overwrites the files in the `bin/` and `samples/config/` directories. Do not use these directories to configure your deployment.

tibemsd.conf

The main configuration file controls the characteristics of the EMS server. This file is usually named `tibemsd.conf`, but you can specify another file name when starting the server.

You can find more information about starting the server in [Running the EMS Server](#).

An example of the `tibemsd.conf` file is included in the `config-file-directory/cfmgmt/ems/data/` directory, where `config-file-directory` is specified during TIBCO Enterprise Message Service installation. You can edit this configuration file with a text editor. There are a few configuration items in this file that can be altered using the administration tool, but most configuration parameters must be set by editing the file (that is, the server does not accept changes to those parameters). See [EMS Administration Tool](#) for more information about using the administration tool.

Several parameters accept boolean values. In the description of the parameter, one specific set of values is given (for example, `enable` and `disable`), but all parameters that accept booleans can have the following values:

- `enable`, `enabled`, `true`, `yes`, `on`
- `disable`, `disabled`, `false`, `no`, `off`

Parameters that take multiple elements cannot contain spaces between the elements, unless the elements are enclosed in starting and ending double quotes. Parameters are limited to line lengths no greater than 256,000 characters in length.

`tibemsd.conf` **Parameters**

The following table summarizes the parameters in `tibemsd.conf` according to category. The sections that follow provide more detail on each parameter.

Parameter	Description
Global System Parameters	
<code>always_exit_on_disk_error</code>	Enable or disable the server behavior to exit on any disk error.
<code>authorization</code>	Enable or disable server authorization.
<code>compliant_queue_ack</code>	Guarantees that a message will not be redelivered after a client has successfully acknowledged its receipt from a routed queue.
<code>disconnect_non_acking_consumers</code>	Causes the server to review unacknowledged pending messages size and counts in consumers.
<code>flow_control</code>	Enable or disable flow control for destinations.
<code>flow_control_only_with_active_consumer</code>	Restore the flow control behavior that was enforced before release 8.4.
<code>health_check_listen</code>	Specifies the port on which the server is to listen for health check requests.
<code>listen</code>	Specifies the port on which the server is to listen for connections from clients.
<code>max_msg_field_print_size</code>	Limits the size of string fields in trace messages.
<code>max_msg_print_size</code>	Limits the size of the printed message of traced messages.
<code>module_path</code>	Specifies a directory or directories that contain shared library files upon which the server is dependent.
<code>network_thread_count</code>	Specifies the number of network threads used by the EMS server.
<code>npsend_check_mode</code>	Specifies when the server is to provide confirmation upon receiving a <code>NON_PERSISTENT</code> message from a producer.
<code>password</code>	Password used to authenticate with other servers that have <code>authorization</code> enabled.
<code>processor_ids</code>	Specifies the processors to be used for network I/O traffic.
<code>routing</code>	Enable or disable routing functionality for this server.

Parameter	Description
<code>secondary_health_check_listen</code>	Specifies the port on which the server designated as secondary in a fault tolerant pair is to listen for health check requests.
<code>selector_logical_operator_limit</code>	Limits the number of operators that the server reviews during selector evaluation.
<code>server</code>	Name of server.
<code>startup_abort_list</code>	Specifies conditions under which the server is to exit during its initialization sequence.
<code>user_auth</code>	Specifies the source of authentication information used to authenticate users attempting to access the EMS server.
<code>xa_default_timeout</code>	Specifies the TX timeout for XA transactions.
Storage File Parameter	
<code>store</code>	Specifies the directory in which the server stores data.
Connection and Memory Parameters	
<code>destination_backlog_swapout</code>	Specifies the maximum number of messages per destination that are stored in the server before message swapping is enabled.
<code>handshake_timeout</code>	Specifies the amount of time that the EMS server waits for a connection to complete.
<code>large_destination_count</code>	Specifies the number of messages that an unbounded destination can gather before the server starts logging warnings about that destination's message count.
<code>large_destination_memory</code>	Specifies the size in memory that an unbounded destination can grow to before the server starts logging warnings about that destination's size.
<code>max_client_msg_size</code>	Sets a maximum size for incoming messages.
<code>max_connections</code>	Specifies the maximum number of simultaneous client connections to the server.
<code>max_msg_memory</code>	Specifies the maximum memory the server can use for messages.
<code>msg_pool_block_size</code>	Specifies the size of the pool to be pre-allocated by the server to store messages.
<code>msg_swapping</code>	Enable or disable message swapping.

Parameter	Description
<code>reserve_memory</code>	Specifies the amount of memory to reserve for use in emergency situations.
<code>socket_send_buffer_size</code>	Sets the size of the send buffer used by clients when connecting to the EMS server.
<code>socket_receive_buffer_size</code>	Sets the size of the receive buffer used by clients when connecting to the EMS server.
Detecting Network Connection Failure Parameters	
<code>active_route_connect_time</code>	Specifies the interval at which an EMS server will attempt to connect or reconnect a route to another server.
<code>client_heartbeat_server</code>	Specifies the interval clients are to send heartbeats to the server.
<code>clock_sync_interval</code>	Periodically sends the EMS server's UTC time to clients.
<code>server_timeout_client_connection</code>	Specifies the period of time server will wait for a client heartbeat before terminating the client connection.
<code>server_heartbeat_server</code>	Specifies the interval this server is to send heartbeats to another server.
<code>server_timeout_server_connection</code>	Specifies the period of time this server will wait for a heartbeat from another server before terminating the connection to that server.
<code>server_heartbeat_client</code>	Specifies the interval this server is to send heartbeats to all of its clients.
<code>client_timeout_server_connection</code>	Specifies the period of time a client will wait for a heartbeat from the server before terminating the connection.
Fault Tolerance Parameters	
<code>ft_active</code>	Specifies the URL of the active server.
<code>ft_heartbeat</code>	Specifies the interval the active server is to send a heartbeat signal to the standby server to indicate that it is still operating.
<code>ft_activation</code>	Specifies the maximum length of time between heartbeat signals the standby server is to wait before assuming the active server has failed.
<code>ft_reconnect_timeout</code>	Specifies the maximum length of time the standby server is to wait for clients to reconnect after becoming the active server in a failover situation.
<code>ft_ssl_identity</code>	Specifies the server's digital certificate.

Parameter	Description
<code>ft_ssl_issuer</code>	Specifies the certificate chain member for the server.
<code>ft_ssl_private_key</code>	Specifies the server's private key.
<code>ft_ssl_password</code>	Specifies the password for private keys.
<code>ft_ssl_trusted</code>	Specifies the list of trusted certificates.
<code>ft_ssl_rand_egd</code>	Specifies the path for the installed entropy gathering daemon (EGD).
<code>ft_ssl_verify_host</code>	Specifies whether the fault-tolerant server should verify the other server's certificate.
<code>ft_ssl_verify_hostname</code>	Specifies whether the fault-tolerant server should verify the name in the CN field of the other server's certificate.
<code>ft_ssl_expected_hostname</code>	Specifies the name the server is expected to have in the CN field of the fault-tolerant server's certificate.
<code>ft_ssl_ciphers</code>	Specifies the cipher suites used by the server.
Message Tracking Parameters	
<code>track_message_ids</code>	Enable or disable message tracking by message ID.
<code>track_correlation_ids</code>	Enable or disable message tracking by correlation ID.
TIBCO FTL Transport Parameters	
<code>ftl_discard_amount</code>	Specifies the number of messages (events) that should be discarded from the TIBCO FTL event queue when its maximum capacity is reached.
<code>ftl_discard_max_events</code>	Specifies the maximum number of messages (events) that a TIBCO FTL queue can hold.
<code>ftl_discard_policy</code>	Determines the behavior of the TIBCO FTL queue when the maximum number of messages (events) that the queue can hold is reached.
<code>ftl_log_level</code>	Determines the trace level of FTL messages logged in the server when the EMS Server FTL trace item is enabled.
<code>ftl_password</code>	Specifies the password that the EMS server should use to authenticate itself when connecting to the TIBCO FTL realm service.
<code>ftl_url</code>	Required. Specifies the URL at which the EMS server can connect to the TIBCO FTL realm service.

Parameter	Description
<code>ftl_url_secondary</code>	Specifies the URL for a backup realm service used for fault tolerance. (FTL 5.x only)
<code>ftl_username</code>	The username that the EMS server should use to authenticate itself when connecting to the TIBCO FTL realm service.
<code>tibftl_transports</code>	Enable or disable the TIBCO FTL transports defined in <code>transports.conf</code> file.
TIBCO Rendezvous Transport Parameters	
<code>tibrv_transports</code>	Enable or disable the TIBCO Rendezvous transports defined in <code>transports.conf</code> file.
TIBCO SmartSockets Transport Parameters	
<code>tibss_transports</code>	Enable or disable the TIBCO SmartSockets transports defined in <code>transports.conf</code> file.
<code>tibss_config_dir</code>	Specifies the directory for SmartSockets configuration and message files.
Tracing and Log File Parameters	
<code>client_trace</code>	Enable or disable client generation of trace output for opening or closing a connection, message activity, and transaction activity.
<code>console_trace</code>	Specifies the trace options for output to <code>stderr</code> .
<code>logfile</code>	Name and location of the server log file.
<code>log_trace</code>	Specifies the trace options on the file defined by the <code>logfile</code> parameter.
<code>logfile_max_count</code>	Specifies the maximum number of log files to be kept.
<code>logfile_max_size</code>	Specifies the maximum log file size before the log file is copied to a backup and then emptied.
<code>secondary_logfile</code>	Name and location of the server log file used by the server designated as secondary in a fault tolerant pair.
<code>trace_client_host</code>	Specifies whether the trace statements related to connections identify the host by its hostname, its IP address, or both.
Statistic Gathering Parameters	
<code>server_rate_interval</code>	Specifies the interval at which overall server statistics are averaged.

Parameter	Description
<code>statistics</code>	Enables or disables statistic gathering for producers, consumers, destinations, and routes.
<code>rate_interval</code>	Specifies the interval at which statistics for routes, destinations, producers, and consumers are averaged.
<code>detailed_statistics</code>	Specifies which objects should have detailed statistic tracking.
<code>statistics_cleanup_interval</code>	Specifies how long the server should keep detailed statistics if the destination has no activity.
<code>max_stat_memory</code>	Specifies the maximum amount of memory to use for detailed statistic gathering.
SSL Server Parameters	
<code>ssl_dh_size</code>	Specifies the size of the Diffie-Hellman key.
<code>ssl_server_ciphers</code>	Specifies the cipher suites used by the server.
<code>ssl_require_client_cert</code>	Specifies if the server is to only accept SSL connections from clients that have digital certificates.
<code>ssl_require_route_cert_only</code>	Overrides <code>ssl_require_client_cert</code> to restrict requiring digital certificates to SSL connections only from routes.
<code>ssl_use_cert_username</code>	Specifies if a client's user name is to always be extracted from the CN field of the client's digital certificate.
<code>ssl_cert_user_specname</code>	Specifies a special username to identify which clients are to have their usernames taken from their digital certificates.
<code>ssl_server_identity</code>	Specifies the server's digital certificate.
<code>ssl_server_key</code>	Specifies the server's private key.
<code>ssl_password</code>	Specifies the password for private keys.
<code>ssl_server_issuer</code>	Specifies the certificate chain member for the server.
<code>ssl_server_trusted</code>	Specifies the list of CA root certificates the server trusts as issuers of client certificates.
<code>ssl_rand_egd</code>	Specifies the path for the installed entropy gathering daemon (EGD).
<code>ssl_crl_path</code>	Specifies the pathname to the certificate revocation list (CRL) files.
<code>ssl_crl_update_interval</code>	Specifies the interval at which the server is to update its CRLs.

Parameter	Description
<code>ssl_auth_only</code>	Specifies whether the server allows clients to request the use of SSL only for authentication.
<code>fips140-2</code>	Enables the server for FIPS compliance.
LDAP Parameters	
<code>ldap_url</code>	Specifies the URL of the external directory server.
<code>ldap_principal</code>	Specifies the distinguished name (DN) of the LDAP administrator.
<code>ldap_credential</code>	Specifies the password associated with the user defined in the <code>ldap_principal</code> property.
<code>ldap_cache_enabled</code>	Enables or disables caching of LDAP data.
<code>ldap_cache_ttl</code>	Specifies the maximum time that cached LDAP data is retained before it is refreshed.
<code>ldap_conn_type</code>	Specifies the type of connection that the server uses to get LDAP information.
<code>ldap_tls_cacert_file</code>	Specifies the file that contains the CA certificate the EMS server trusts to sign the LDAP server's certificate.
<code>ldap_tls_cacert_dir</code>	When there are two or more CA certificates in the verify chain, use this parameter to specify the directory containing the CA certificates.
<code>ldap_tls_cipher_suite</code>	Specifies the cipher suite to use for encryption on secure LDAP connections.
<code>ldap_tls_rand_file</code>	Specifies the file containing random data for encryption.
<code>ldap_tls_cert_file</code>	Specifies the file containing the certificate that identifies the EMS server to the LDAP server.
<code>ldap_tls_key_file</code>	Specifies the file containing the private key required by the LDAP server to authenticate the client.
<code>ldap_user_class</code>	Specifies the name of the LDAP object class that stores users.
<code>ldap_user_attribute</code>	Specifies the name of the attribute on the user object class that holds the name of the user.
<code>ldap_user_base_dn</code>	Specifies the base distinguished name (DN) of the LDAP tree that contains the users.
<code>ldap_user_scope</code>	Specifies how deeply under the base DN to search for users.

Parameter	Description
<code>ldap_user_filter</code>	Specifies the LDAP search filter for finding a given user name.
<code>ldap_all_users_filter</code>	Specifies the LDAP search filter for finding all users beneath the user base DN.
<code>ldap_group_base_dn</code>	Specifies the base distinguished name (DN) of the LDAP tree that contains groups.
<code>ldap_group_scope</code>	Specifies how deeply under the base DN to search for groups.
<code>ldap_group_filter</code>	Specifies the LDAP search filter for finding a group with a given group name.
<code>ldap_all_groups_filter</code>	Specifies the LDAP search filter for finding all groups beneath the group base DN.
<code>ldap_static_group_class</code>	Specifies the name of the LDAP object class that stores static groups.
<code>ldap_static_group_attribute</code>	Specifies the name of the attribute on the static group object class that holds the name of the group.
<code>ldap_static_group_member_filter</code>	Specifies the LDAP search filter for finding all static members of a group
<code>ldap_static_member_attribute</code>	Specifies the attribute of an LDAP static group object that specifies the distinguished names (DNs) of the members of the group.
<code>ldap_dynamic_group_class</code>	Specifies the name of the LDAP object class that stores dynamic groups.
<code>ldap_dynamic_group_attribute</code>	Specifies the name of the attribute on the dynamic group object class that holds the name of the group.
<code>ldap_dynamic_member_url_attribute</code>	Specifies the attribute of the dynamic LDAP group object that specifies the URLs of the members of the dynamic group.
Extensible Security Parameters	
<code>jaas_config_file</code>	Specifies the location of the JAAS configuration file used to run a custom authentication LoginModule.
<code>jaas_login_timeout</code>	Specifies the length of time, in milliseconds, that the server waits for the JAAS authentication module to execute and respond.
<code>jaci_class</code>	Specifies the name of the class that implements the extensible permissions interface.

Parameter	Description
<code>jaci_timeout</code>	Specifies the length of time, in milliseconds, that the server waits for the JACI permissions module to execute and respond.
<code>security_classpath</code>	Includes the JAR files and dependent classes used by the JAAS LoginModules and JACI modules.
JVM Parameters	
<code>jre_library</code>	Enables the JVM in the EMS server.
<code>jre_option</code>	Passes command line options to the JVM at start-up.

Global System Parameters

`always_exit_on_disk_error`

Enable or disable the server behavior to exit on any disk error.

```
always_exit_on_disk_error = enable | disable
```

Defaults to disable.

`authorization`

Enable or disable server authorization.

```
authorization = enabled | disabled
```

Authorization is disabled by default. If you require that the server verify user credentials and permissions on secure destinations, you must enable this parameter.

See [Enable Access Control](#) for more information.

For example:

```
authorization = enabled
```

See [Authentication and Permissions](#) for more information about these parameters.

`compliant_queue_ack`

Guarantees that, once a client successfully acknowledges a message received from a routed queue, the message will not be redelivered. This is accomplished by the EMS server waiting until the message has been successfully acknowledged by the queue's home EMS server before sending the response to the client.

```
compliant_queue_ack = enable | disable
```

The `compliant_queue_ack` parameter is enabled by default. Because of the extra overhead incurred with compliant queue acknowledgments, you can disable this feature when performance is an issue. If compliant queue acknowledgment is disabled and a message is redelivered, the message's `JMSRedelivered` indicator will be set.

`disconnect_non_acking_consumers`

This parameter works in conjunction with the `maxbytes` and `maxmsgs` destination properties. In situations where consumers consume messages but do not acknowledge them, the messages are held in the server until they are confirmed. This can push the server above the set limits.

```
disconnect_non_acking_consumers = enabled | disabled
```

When enabled, `disconnect_non_acking_consumers` causes the server to check the number and size of pending messages sent to a consumer. If the `maxbytes` or `maxmsgs` limit is reached and the consumer has not acknowledged its messages, the server discards the messages sent to the consumer and disconnects the consumer's connection. This protects the server against applications that consume messages without ever acknowledging them.

Before enabling this property, ensure that the `maxbytes` and `maxmsgs` limits are set with reference to the `prefetch` setting, the size of the transaction (if transacted receive), or number of messages acknowledged when using client or explicit client acknowledgment mode. Otherwise the server may disconnect the consumer before it has a chance to acknowledge the messages.

When routes are deployed, all routed servers should use the same `disconnect_non_acking_consumers` setting. Additionally, if `maxbytes` or `maxmsgs` is set for a global destination, the same setting should be applied on all servers. The server does not discard or disconnect a routed consumer, since disconnecting the route may impact other well-behaved applications. Servers discard and disconnect their local consumers, which other servers involved are made aware of and discard messages for those remote consumers accordingly.

This parameter is disabled by default.

flow_control

Specifies whether flow control for destinations is enabled or disabled.

```
flow_control = enable | disable
```

By default, flow control is disabled. When flow control is enabled, the `flowControl` property on each destination specifies the target maximum storage for pending messages on the destination.

See [Flow Control](#) for more information about flow control.

flow_control_only_with_active_consumer

Restores the flow control behavior that was enforced before release 8.4. This property and the corresponding behavior are deprecated and will be removed in a future release.

```
flow_control_only_with_active_consumer = enable | disable
```

By default, this parameter is disabled. For more information, see [Flow Control in the Absence of Consumers](#).

health_check_listen

Specifies the port on which the server is to listen for health check requests.

```
health_check_listen = http://servername:port
```

For example:

```
health_check_listen = http://machine1:7220
```

When using `localhost` as the `servername`, the listen will only be accessible from the local machine. If you omit the `servername`, the listen will behave similarly to setting `localhost` in the server `listen` parameter.

For example:

```
health_check_listen = http://:7220
```

You can use an IP address instead of hostname.

For example:

```
health_check_listen = http://192.168.10.107:7220
```

When specifying an IPv6 address, use square brackets around the address specification.

For example:

```
health_check_listen = http://[2001:cafe::107]:7220
```


You can use only one `health_check_listen` entry at a time. For more information, see [Server Health](#).

listen

Specifies the port on which the server is to listen for connections from clients.

```
listen=protocol://servername:port
```

For example:

```
listen=tcp://localhost:7222
```

If you are enabling SSL, for example:

```
listen=ssl://localhost:7222
```

You can use multiple listen entries if you have computers with multiple interfaces. For example:

```
listen=tcp://localhost:7222
listen=tcp://localhost:7224
```

If `localhost` is specified, or if the *servername* is not present, then the server uses every available interface. For example:

```
listen=tcp://7222
listen=ssl://7243
```

You can use an IP address instead of a host name. For example:

```
listen=tcp://192.168.10.107:7222
```

When specifying an IPv6 address, use square brackets around the address specification. For example:

```
listen=tcp://[2001:cafe::107]:7222
```

max_msg_field_print_size

Limits the size of string fields in trace messages. If a string field is larger than *size*, the field is truncated in the trace message.

```
max_msg_field_print_size = size [KB|MB|GB]
```

Specify signed 32-bit integer values as KB, MB or GB. The minimum permitted size is 1 KB. By default, the field limit is 1 KB.

max_msg_print_size

Limits the size of the printed message of traced messages. If the message is larger than *size*, the message is truncated.

```
max_msg_print_size = size [KB|MB|GB]
```

Specify signed 32-bit integer values as KB, MB or GB. The minimum permitted size is 8 KB. By default, the field limit is 8 KB.

module_path

```
module_path = shared-library-directory
```

where *shared-library-directory* is the absolute path to the directory containing any library the server is dependent on. This may include TIBCO FTL, Rendezvous, or SmartSockets libraries, as well as OpenSSL or the JVM.

You can specify multiple directories (for example, to load both TIBCO FTL and Rendezvous libraries). Separate paths using a colon (:) on UNIX platforms, or semicolon (;) on Windows platforms.

For example:

```
module_path = c:\tibco\ss\bin\i86_w32\amd64
```



When deploying EMS 8.3, 8.4, and 8.5 transports for older versions of TIBCO FTL or Rendezvous, you must configure the `module_path` parameter to include the path to the EMS libraries before the FTL and Rendezvous libraries. This is the case when working with transports for:

- TIBCO FTL 4.3.0 and FTL 4.2.0
- TIBCO Rendezvous 8.4.4 and earlier

This is not necessary when configuring transports for TIBCO FTL 5.0.0 or later.



The `module_path` parameter is also used on AIX platform installations to load the IBM JVM. Specify the directories containing the `libjvm.so` and its dependent libraries.

network_thread_count

Specifies the number of network threads used by the EMS server.

```
network_thread_count = threads
```

The *threads* count can be any positive integer. The default value is 1.

When set, this parameter allows the EMS server to control the number of threads while still allowing the system administrator to control the thread affinity externally (for example, by using the Linux `taskset` command).

If you intend to set the thread affinity externally, we recommend that you avoid setting any thread affinity in the EMS server for either network traffic or stores.

The EMS server ignores this parameter if the `processor_ids` parameter is also specified.

npsend_check_mode

Specifies when the server is to provide confirmation upon receiving a `NON_PERSISTENT` message from a producer.

```
npsend_check_mode = [always | never | temp_dest | auth | temp_auth]
```

The `npsend_check_mode` parameter applies only to producers sending messages using `NON_PERSISTENT` delivery mode and non-transactional sessions.

Message confirmation has a great deal of impact on performance and should only be enabled when necessary. The circumstances in which a producer might want the server to send confirmation a `NON_PERSISTENT` message are:

- When `authorization` is enabled, so the producer can take action if permission to send the message is denied by the server.
- When sending to a temporary destination, so the producer can take action if the message is sent to a temporary destination that has been destroyed.
- The message exceeded queue/topic limit (requires `rejectIncoming` policy for topics).
- Bridging of the message has failed.
- The server is out of memory or has encountered some other severe error.

The possible `npsend_check_mode` parameter modes are:

- `default` (no mode specified) - this means the server only provides confirmation of a `NON_PERSISTENT` message if `authorization` is enabled.
- `always` - the server always provides confirmation of a `NON_PERSISTENT` message.
- `never` - the server never provides confirmation of `NON_PERSISTENT` messages.
- `temp_dest` - the server provides confirmation of a `NON_PERSISTENT` message only when sending to a temporary destination.

- `auth` - the server provides confirmation of a `NON_PERSISTENT` message only if authorization was enabled when the connection was created.
- `temp_auth` - the server provides confirmation of a `NON_PERSISTENT` message if sending to a temporary destination or if authorization was enabled when the connection was created.

password

The password used when connecting to another EMS server that has authorization enabled.

```
password = password
```

For information on authorization between routed servers, see [Routing and Authorization](#).

For information on authorization between fault tolerant server pairs, see [Authorization and Fault-Tolerant Servers](#).

processor_ids

Setting this parameter causes the EMS Server to start as many network I/O threads as there are processor IDs specified in the list. Each network I/O thread is bound to the given processor ID, which means that the thread can execute only on that processor.

```
processor_ids = processor-id1,processor-id2,...
```



Do not use this parameter if the default behavior provides sufficient throughput.

Specify the *processor-id* as an integer. Ask your system administrator for the valid processor IDs on the EMS Server host. Note that the IDs can be listed in any order. List IDs in a comma-separated list, with no spaces separating list items. For example:

```
processor_ids = 0,1,3,6
```

On startup, the parameter is parsed and the server refuses to start (regardless of the presence of the `startup_abort_list` parameter) if:

- The list is malformed. That is, if it contains invalid values such as non-numeric elements.
- The server is unable to bind a network I/O thread to a given processor ID. This can happen when the processor ID has been disabled, or the `tibemsd` process has been restricted by the system administrator to a set of processors that does not contain this processor ID. Additionally, the server cannot correctly bind the network I/O thread to the process ID if spaces are included in the parameter definition.

Do not use hyper threading.



For instance, consider a machine with 24 processors, with 2 dies and processor IDs ranging from 0 to 5 and 12 to 17 on the first die, and 6 to 11 and 18 to 23 on the second die. In this example, you should specify processor IDs in either the 0 to 5 range, or the 6 to 11 range.

Specifying processor IDs 0 and 12 in the list would cause thrashing because two network I/O threads would be bound to the same processor (or core). Also, for optimal performance, processor IDs should be from the same die.

This parameter can be used in conjunction with the `stores.conf` parameter `processor_id`. For more information, see [Performance Tuning](#).

routing

Enables or disables routing functionality for this server.

```
routing = enabled | disabled
```

For example:

```
routing = enabled
```

See [Routes](#) for more information about routing.

secondary_health_check_listen

Specifies the port on which the server designated as secondary in a fault tolerant pair is to listen for health check requests.

```
secondary_health_check_listen = http://machine1:7220
```

If the `secondary_health_check_listen` is not set, the secondary server assumes the value of `health_check_listen`.

For more information, see [health_check_listen](#).



This parameter is available only for JSON-configured EMS servers.

selector_logical_operator_limit

Limits the number of operators that the server reviews during selector evaluation.

```
selector_logical_operator_limit = number
```

The server evaluates operators until reaching the specified *number* of false conditions. The server then stops evaluating further to protect itself from too many recursive evaluations. A very long selector clause, such as one including many OR conditions, can cause recursive selector evaluation and lead to a stack overflow in the EMS server.

number may be any positive integer. The default value is 5000. Zero is a special value, indicating no limit.

For example, if `selector_logical_operator_limit = 10` and the selector is:

```
a=1 or b=2 or c=3 or d=4 or e=5 or f=6 or g=7 or h=8 or i=9 or j=10 or k=11 or l=12
or m=13 or n=14 or o=15 or p=16 or q=17 or r=18 or s=19 or t=20 or u=21 or v=22 or
w=23 or x=24 or y=25 or z=26
```

if the first 10 conditions are false, the server stops further evaluation.

server

Name of server.

```
server = serverName
```

Server names are limited to at most 64 characters, and may not include the dot character (.).

startup_abort_list

Specifies conditions that cause the server to exit during its initialization sequence.

```
startup_abort_list=[SSL,TRANSPORTS,CONFIG_FILES,CONFIG_ERRORS,
DB_FILES]
```

You may specify any subset of the conditions in a comma-separated list. The list cannot contain spaces between the elements, unless the elements are enclosed in starting and ending double quotes. If a space is included but not enclosed in quotation marks, the server ignores any conditions following the space.

Conditions that do not appear in the list are ignored by the server. The default is an empty list.

The conditions are:

- **SSL**—If SSL initialization fails, then it exits.
- **TRANSPORTS**—If any of the transports cannot be created as specified in the configuration files, then it exits.
- **CONFIG_FILES**—If any configuration file listed in `tibemsd.conf` does not exist, then it exits.
- **CONFIG_ERRORS**—If the server detects any errors while reading the config files, then it exits.

Note that the `tibemsd` silently ignores any unknown parameters when it is started using the JSON configuration. For example, no configuration errors are thrown if the `tibemsd.json` file contains an obsolete parameter.

- **DB_FILES**—If the server cannot find one or more of its stores, then it exits. Stores include the default store files as well as any file or database stores configured in the `stores.conf` configuration file.

Note that if `DB_FILES` is *not* included in the `startup_abort_list` and the server cannot find a store, the server will create the missing file or database. For best results, do not include `DB_FILES` the first time a server is started, allowing it to create the files. After initial startup or a major store configuration change (such as the addition of a new store), include `DB_FILES` in the list so that on restart the server will only start if all the configured files are present.

user_auth

Specifies the source of user authentication information.

```
user_auth = [local, ldap, jaas]
```

This parameter can have one or more of the following values (separated by comma characters):

- `local`—obtain user authentication information from the local EMS server user configuration.
- `ldap`—obtain user authentication information from an LDAP directory server (see the LDAP-specific configuration parameters).
- `jaas`—obtain user authentication information from a custom authentication module (see [Extensible Authentication](#) and [JAAS Authentication Modules](#)).

Each time a user attempts to authenticate, the server seeks corresponding authentication information from each of the specified locations in the order that this parameter specifies. The EMS server accepts successful authentication using any of the specified sources.



The `user_auth` setting does not affect authentication of the default administrator. The server always authenticates the admin user from the local configuration file. See [Assigning a Password to the Administrator](#) for more information.

xa_default_timeout

Specifies the default TX timeout, in seconds, for XA transactions. The default is 0, which specifies no timeout.

```
xa_default_timeout = seconds
```

The default timeout setting cannot be changed dynamically. However, you can specify a different transaction timeout for each individual XA resource using the API.

Storage File Parameters

The parameter described here configures file-based and mstores. For information about database stores, see [Database Stores](#).

store

```
store = directory
```

Directory in which the server stores data files. For example:

```
store = /usr/tmp
```

Connection and Memory Parameters

The parameters described in the following topics affect the memory and connection management of the EMS server.

destination_backlog_swapout

Specifies the number of messages that may be stored in the server's memory before message swapping is enabled. The limit given is for each destination. For example, if the limit is 10,000 and you have three queues, the server can store up to 30,000 unswapped messages in memory.

```
destination_backlog_swapout = number
```

The specified *number* may be any positive value. When `destination_backlog_swapout` is 0, the server attempts to immediately swap out the message.

By default, the limit for each destination is 1024 messages.

handshake_timeout

```
handshake_timeout = seconds
```

The amount of time that the EMS server waits for a connection to complete depends on the `server_timeout_server_connection` and `server_timeout_client_connection` properties.

If either is specified, the connection handshake times out only after the duration mentioned in one of these properties. If both are specified, the largest of the two values is used. If neither is specified, you can set the period (in seconds) using `handshake_timeout`. The period specified must be a positive integer. If absent, the timeout defaults to 3 seconds. When the timeout is reached, the EMS server closes the connection and continues handling other clients.

large_destination_count

Specifies the number of messages that an unbounded destination (a destination without either of its `maxbytes` or `maxmsgs` properties set) can gather before the server starts logging warnings about that destination's message count.

```
large_destination_count = number
```

By default, `large_destination_count` is not set and the server establishes its own message count threshold. It can be set dynamically. Zero is a special value that disables the logging of the corresponding warning.

large_destination_memory

Specifies the size in memory that an unbounded destination (a destination without either of its `maxbytes` or `maxmsgs` properties set) can grow to before the server starts logging warnings about that destination's size.

```
large_destination_memory = size [KB|MB|GB]
```

By default, `large_destination_memory` is not set and the server establishes its own size threshold. It can be set dynamically. Zero is a special value that disables the logging of the corresponding warning.

max_client_msg_size

Maximum size allowed for an incoming message. This parameter setting instructs the server to reject incoming messages that are larger than the specified size limit.

```
max_client_msg_size = size [KB|MB|GB]
```

Specify whole numbers as KB, MB or GB. The maximum value is 2 GB.

When omitted or zero, the EMS server accepts and attempts to process messages of any size.

max_connections

Maximum number of simultaneous client connections.

```
max_connections = number
```

Set to 0 to allow unlimited simultaneous connections.

max_msg_memory

Maximum memory the server can use for messages. This parameter lets you limit the memory that the server uses for messages, so server memory usage cannot grow beyond the system's memory capacity.

```
max_msg_memory = size [KB|MB|GB]
```

When `msg_swapping` is enabled, and messages overflow this limit, the server begins to swap messages from process memory to disk. Swapping allows the server to free process memory for incoming messages, and to process message volume in excess of this limit.

When the server swaps a message to disk, a small record of the swapped message remains in memory. If all messages are swapped out to disk, and their remains still exceed this memory limit, then the server has no room for new incoming messages. The server stops accepting new messages, and send calls in message producers result in an error. (This situation probably indicates either a very low value for this parameter, or a very high message volume.)

Specify units as KB, MB or GB. The minimum value is 8 MB. The default value of 0 (zero) indicates no limit.

For example:

```
max_msg_memory = 512MB
```

msg_pool_block_size

To lessen the overhead costs associated with `malloc` and `free`, the server pre-allocates pools of storage for messages. This parameter determines the behavior of these pools. Performance varies depending on operating system platform and usage patterns.

```
msg_pool_block_size size
```



Consult with your TIBCO support representative before using this parameter.

The *size* argument determines the approximate number of internal message structs that a block or pool can accommodate (not the number of bytes).

`msg_pool_block_size` instructs the server to allocate an *expandable* pool. Each time the server exhausts the pool, the server increases the pool by this size, as long as additional storage is available. The value may be in the range 32 to 65536.

When this parameter is not present, the default is `msg_pool_block_size 128`.

msg_swapping

This parameter enables and disables the message swapping feature (described above for [max_msg_memory](#)).

```
msg_swapping = enable | disable
```

The default value is enabled, unless you explicitly set it to disabled.

reserve_memory

When `reserve_memory` is non-zero, the EMS server allocates a block of memory for use in emergency situations to prevent the EMS server from being unstable in low memory situations.

```
reserve_memory = size
```

When the server process exhausts memory resources, it disables clients and routes from producing new messages, and frees this block of memory to allow consumers to continue operation (which tends to free memory).

The EMS server attempts to reallocate its reserve memory once the number of pending messages in the server has dropped to 10% of the number of pending messages that were in the server when it experienced the allocation error. If the server successfully reallocates memory, it begins accepting new messages.

The `reserve_memory` parameter only triggers when the EMS server has run out of memory and therefore is a reactive mechanism. The appropriate administrative action when an EMS server has triggered release of reserve memory is to drain the majority of the messages by consuming them and then to stop and restart the EMS server. This allows the operating system to reclaim all the virtual memory resources that have been consumed by the EMS server. A trace option, `MEMORY`, is also available to help show what the server is doing during the period when it is not accepting messages.

Specify *size* in units of MB. When non-zero, the minimum block is 16MB. When absent, the default is zero.



There are a variety of limits that the user can set to prevent the EMS server from storing excessive messages, which can lead to situations where the EMS server runs out of memory. These include global parameters, such as `max_msg_memory`, as well as destination properties such as `maxbytes`. These limits should be used to prevent the `reserve_memory` mechanism from triggering.

socket_send_buffer_size

Sets the size (in bytes) of the send buffer used by clients when connecting to the EMS server.

```
socket_send_buffer_size = size [KB|MB|GB]
```

The specified *size* may be:

- any number greater than 512
- 0 to use the default buffer size
- -1 to skip the call for the specified buffer
- Optionally, specify units of KB, MB, or GB for units. If no units are specified, the file size is assumed to be in bytes.

When omitted, the server skips the call for the specified buffer. In this case, the operating system's auto-tuning controls buffering.

socket_receive_buffer_size

Sets the size (in bytes) of the receive buffer used by clients when connecting to the EMS server.

```
socket_receive_buffer_size = size [KB|MB|GB]
```

The specified *size* may be:

- any number greater than 512
- 0 to use the default buffer size
- -1 to skip the call for the specified buffer
- Optionally, specify units of KB, MB, or GB for units. If no units are specified, the file size is assumed to be in bytes.

When omitted, the server skips the call for the specified buffer. In this case, the operating system's auto-tuning controls buffering.

Detecting Network Connection Failure Parameters

This feature lets servers and clients detect network connection failures quickly. When these parameters are absent, or this feature is disabled, `tibemsd` closes a connection only upon the operating system notification.

active_route_connect_time

Specifies the interval (in seconds) at which an EMS server attempts to connect or reconnect a route to the another server. The default is 2 seconds.

```
active_route_connect_time = interval
```

client_heartbeat_server

In a server-to-client connection, clients send heartbeats to the server at this interval (in seconds).

```
client_heartbeat_server = interval
```

The `client_heartbeat_server` parameter must be specified when a `server_timeout_client_connection` is set. The `client_heartbeat_server` interval should be no greater than one third of the `server_timeout_client_connection` limit.

This setting also ensures that garbage collection occurs on the connection. Collection is triggered by incoming messages and heartbeats. If the size of messages can vary widely or there is not a steady stream of message traffic, can use this parameter to ensure that collection occurs.

When omitted or zero, `client_heartbeat_server` is disabled.

clock_sync_interval

Periodically send the EMS server's Coordinated Universal Time (UTC) time to clients. This allows EMS clients to update their offset.

```
clock_sync_interval = seconds
```

The time specified, in seconds, determines the interval at which clock sync commands are sent from the server to its clients.

When omitted or zero, the EMS server sends the offset time only when the EMS client connects to the server. If `clock_sync_interval` is -1, the offset is never sent, not even on connect. Clients do not adjust their time values to match the server time.

server_timeout_client_connection

In a server-to-client connection, if the server does not receive a heartbeat for a period exceeding this limit (in seconds), it closes the connection.

```
server_timeout_client_connection = limit
```

We recommend setting this value to approximately 3 times the heartbeat interval, as it is specified in `client_heartbeat_server`.



If you do not set the `client_heartbeat_server` parameter when a `server_timeout_client_connection` is specified, a configuration error is generated during startup. If `CONFIG_ERRORS` is part of the `startup_abort_list`, the server will not start. If not, the error is printed but the server starts, and clients will be disconnected after `server_timeout_client_connection` seconds.

Zero is a special value, which disables heartbeat detection in the server (although clients still send heartbeats).

server_heartbeat_server

In a server-to-server connection, this server sends heartbeats at this interval (in seconds). The two servers can be connected either by a route, or as a fault-tolerant pair.

```
server_heartbeat_server = interval
```

server_timeout_server_connection

In a server-to-server connection, if this server does not receive a heartbeat for a period exceeding this limit (in seconds), it closes the connection. This parameter applies to connections from other routes and to the standby server connection.

```
server_timeout_server_connection = limit
```

We recommend setting this value to approximately 3.5 times the heartbeat interval of the other server. When the other server or the network are heavily loaded, or when client programs send very large messages, we recommend a larger multiple.



In a fault-tolerant configuration, the `server_timeout_server_connection` parameter has no effect on the standby server following a failover. The standby server activates only after the timeout set by the `ft_activation` parameter.

server_heartbeat_client

In a server-to-client connection, the server sends heartbeats to all clients at this interval (in seconds).

```
server_heartbeat_client = interval
```

When omitted or zero, the default is 5 seconds.

client_timeout_server_connection

In a server-to-client connection, if a client does not receive a heartbeat for a period exceeding this limit (in seconds), it closes the connection.

```
client_timeout_server_connection = limit
```

We recommend setting this value to approximately 3.5 times the heartbeat interval.

Zero is a special value, which disables heartbeat detection in the client (although the server still sends heartbeats).

Fault Tolerance Parameters

See [Fault Tolerance](#) for more information about these parameters.

The fault tolerance parameters that begin with the prefix `ft_ssl` are used to secure communications between pairs of fault tolerant servers. See [SSL](#) for additional information about this process.

ft_active

Specifies the URL of the active server. If this server can connect to the active server, it will act as a standby server. If this server cannot connect to the active server, it will become the active server.

```
ft_active = URL
```

ft_heartbeat

Specifies the interval (in seconds) the server is to send a heartbeat signal to its peer to indicate that it is still operating.

```
ft_heartbeat = seconds
```

Default is 3 seconds.

ft_activation

Activation interval (maximum length of time between heartbeat signals) which indicates that server has failed.

```
ft_activation = seconds
```

Set in seconds: default is 10. This interval should be set to at least twice the heartbeat interval.

For example:

```
ft_activation = 60
```

See the [server_timeout_server_connection](#) parameter for more information on heartbeats.

ft_reconnect_timeout

The amount of time (in seconds) that a standby server waits for clients to reconnect (after it becomes the active server in a failover situation).

```
ft_reconnect_timeout = seconds
```

If a client does not reconnect within this time period, the server removes its state from the shared state files. The [ft_reconnect_timeout](#) time starts once the server has fully recovered the shared state, so this value does not account for the time it takes to recover the store files.

The default value of this parameter is 60.

ft_ssl_identity

The path to a file that contains the certificate in one of the supported formats. The supported formats are PEM, DER, or PKCS#12.

```
ft_ssl_identity = pathname
```

See [File Names for Certificates and Keys](#) for more information on file types for digital certificates.

ft_ssl_issuer

Certificate chain member for the server. Supply the entire chain, including the CA root certificate. The server reads the certificates in the chain in the order they are presented in this parameter.

```
ft_ssl_issuer = chain_member
```

The certificates must be in PEM, DER, PKCS#7, or PKCS#12 format. See [File Names for Certificates and Keys](#) for more information on file types for digital certificates.

ft_ssl_private_key

The server's private key. If it is included in the digital certificate in [ft_ssl_identity](#), then this parameter is not needed.

```
ft_ssl_private_key = key
```

This parameter supports private keys in the following formats: PEM, DER, PKCS#12.

You can specify the actual key in this parameter, or you can specify a path to a file that contains the key. See [File Names for Certificates and Keys](#) for more information on file types for digital certificates.

ft_ssl_password

Private key or password for private keys.

```
ft_ssl_password = password
```

You can set passwords by way of the [tibemsadmin](#) tool. When passwords are set with this tool, the password is obfuscated in the configuration file. See [EMS Administration Tool](#) for more information about using [tibemsadmin](#) to set passwords.

ft_ssl_trusted

List of trusted certificates. This sets which Certificate Authority certificates should be trusted as issuers of the client certificates.

```
ft_ssl_trusted = trusted_certificates
```

The certificates must be in PEM, DER, or PKCS#7 format. You can either provide the actual certificates, or you can specify a path to a file containing the certificate chain.

See [File Names for Certificates and Keys](#) for more information on file types for digital certificates.

ft_ssl_rand_egd

The path for the installed entropy gathering daemon (EGD), if one is installed. This daemon is used to generate random numbers for the EMS server.

```
ft_ssl_rand_egd = pathname
```

ft_ssl_verify_host

Specifies whether the fault-tolerant server should verify the other server's certificate.

```
ft_ssl_verify_host = enabled | disabled
```

The values for this parameter are enabled or disabled.

By default, this parameter is enabled, signifying the server should verify the other server's certificate.

When this parameter is set to disabled, the server establishes secure communication with the other fault-tolerant server, but does not verify the server's identity.

ft_ssl_verify_hostname

Specifies whether the fault-tolerant server should verify the name in the CN field of the other server's certificate.

```
ft_ssl_verify_hostname = enabled | disabled
```

The values for this parameter are enabled and disabled. By default, this parameter is enabled, signifying the fault-tolerant server should verify the name of the connected host or the name specified in the `ft_ssl_expected_hostname` parameter against the value in the server's certificate. If the names do not match, the connection is rejected.

When this parameter is set to disabled, the fault-tolerant server establishes secure communication with the other server, but does not verify the server's name.

ft_ssl_expected_hostname

Specifies the name the server is expected to have in the CN field of the fault-tolerant server's certificate.

```
ft_ssl_expected_hostname = serverName
```

If this parameter is not set, the expected name is the hostname of the server.

This parameter is used when the `ft_ssl_verify_hostname` parameter is set to enabled.

ft_ssl_ciphers

Specifies the cipher suites used by the server; each suite in the list is separated by a colon (:). This parameter can use the OpenSSL name for cipher suites or the longer, more descriptive names.

```
ft_ssl_ciphers = cipherSuite
```

See [Specify Cipher Suites](#) for more information about the cipher suites available in EMS and the OpenSSL names and longer names for the cipher suites.

Message Tracking Parameters

The parameters described in the following topics configure the message tracking behavior of the EMS server.

track_message_ids

Tracks messages by message ID. Default is disabled.

```
track_message_ids = enabled | disabled
```

Enabling this parameter allows you to display messages using the `show message messageID` command in the administration tool.

track_correlation_ids

Tracks messages by correlation ID. Disabled by default.

```
track_correlation_ids = enabled | disabled
```

Enabling this parameter allows you to display messages using the `show messages correlationID` command in the administration tool.

TIBCO FTL Transport Parameters

The parameters listed here enable the EMS server to connect to a TIBCO FTL realm service using transports configured in the [transports.conf](#) file.



The EMS server creates a single FTL event queue that is used for all EMS transports for FTL configured in the `transports.conf` file.

The discard parameters set here are global, and refer to the EMS server and its single FTL event queue. These settings cannot be set for individual transports.

For more information, see [Interoperation with TIBCO FTL](#).

ftl_discard_amount

Optional. Specifies the number of messages (events) that should be discarded from the TIBCO FTL event queue when the limit specified by `ftl_discard_max_events` is reached.

```
ftl_discard_amount = integer
```

When absent, `ftl_discard_amount` defaults to 5000.

Sets the `com.tibco.ftl.client.discard.amount` property. For more details, see the TIBCO FTL documentation on event queues.

ftl_discard_max_events

Optional. Specifies the maximum number of messages (events) that a TIBCO FTL queue can hold.

```
ftl_discard_max_events = integer
```

When absent, `ftl_discard_max_events` defaults to 100000.

Sets the `com.tibco.ftl.client.discard.max_events` property. For more details, see the TIBCO FTL documentation on event queues.

ftl_discard_policy

Optional. Determines the behavior of the TIBCO FTL queue when the maximum number of messages (events) that the queue can hold is reached.

```
ftl_discard_policy = none | old | new
```

When absent, `ftl_discard_policy` is `old`.

Sets the `com.tibco.ftl.client.discard.policy` property. For more details, see the TIBCO FTL documentation on event queues.

ftl_log_level

Optional. Determines the trace level of FTL messages logged in the server when the EMS Server FTL trace item is enabled.

```
ftl_log_level = level
```

When absent, the `ftl_log_level` defaults to `warn`.

For more details, see the TIBCO FTL documentation on logging.

ftl_password

Optional. The password that the EMS server should use to authenticate itself when connecting to the TIBCO FTL realm service. Note that the password can be stored in a mangled form.

```
ftl_password = password
```

Sets the `com.tibco.ftl.client.userpassword` property. For more details, see the TIBCO FTL documentation on realms.

ftl_url

Required. Specifies the URL at which the EMS server can connect to the TIBCO FTL realm service.

```
ftl_url = URL
```

For example, `ftl_url=http://localhost:5633`.

For more details, see the TIBCO FTL documentation on realms.

ftl_url_secondary

Optional. Specifies the URL for a backup realm server.

If the EMS server cannot connect to the realm server at the URL specified by `ftl_url`, it attempts to connect using the URL specified here. This is only applicable to FTL 5.x.

With FTL 6.x, supply the `ftl_url` with a pipe-separated list of URLs of FTL servers that provide realm services.

```
ftl_url_secondary = URL
```

Sets the `com.tibco.ftl.client.secondary` property. For more details, see the TIBCO FTL documentation on realms.

ftl_username

Optional. The username that the EMS server should use to authenticate itself when connecting to the TIBCO FTL realm service.

```
ftl_username = user
```

Sets the `com.tibco.ftl.client.username` property. For more details, see the TIBCO FTL documentation on realms.

tibftl_transports

Specifies whether the TIBCO FTL transports defined in `transports.conf` are enabled or disabled.

```
tibftl_transports = enabled | disabled
```

Unless you explicitly set this parameter to enabled, the default value is `disabled`—that is, all transports are disabled and will neither send messages to external systems nor receive messages from them.

Rendezvous Transport Parameters

For more information, see [Interoperation With TIBCO Rendezvous](#).

`tibrv_transports`

Specifies whether TIBCO Rendezvous transports defined in `transports.conf` are enabled or disabled.

```
tibrv_transports = enabled | disabled
```

Unless you explicitly set this parameter to enabled, the default value is `disabled`—that is, all transports are disabled and will neither send messages to external systems nor receive message from them.

SmartSockets Transport Parameters

For more information, see [Interoperation with TIBCO SmartSockets](#).

`tibss_transports`

Specifies whether TIBCO SmartSockets transports defined in `transports.conf` are enabled or disabled.

```
tibss_transports = enabled | disabled
```

Unless you explicitly set this parameter to enabled, the default value is `disabled`—that is, all transports are disabled and will neither send messages to external systems nor receive message from them.

`tibss_config_dir`

Specifies the directory for SmartSockets configuration files and message files.

```
tibss_config_dir = pathname
```

- `tal_ss.cat` is a required file of messages. If it is missing, `tibemsd` outputs a warning message.
- `tibems_ss.cm` is an optional file of SmartSockets RTclient configuration options.

When this parameter is absent, `tibemsd` searches for these files in its current working directory.

For more information about these files, see *TIBCO SmartSockets User's Guide*.

Tracing and Log File Parameters

See [Monitor Server Activity](#), for more information about these parameters.

`client_trace`

Administrators can trace a connection or group of connections. When this property is enabled, the server instructs each client to generate trace output for opening or closing a connection, message activity, and transaction activity. This type of tracing does not require restarting the client program.

```
client_trace = {enabled|disabled} [target=location]
               [user|connid|clientid=value]
```

Each client sends trace output to *location*, which may be either `stderr` (the default) or `stdout`.



You can also direct client tracing output to a file, using the `tibems_SetTraceFile`, `Tibjms.setTraceFile` and `Tibems.SetTraceFile` in the C, Java and .NET libraries, respectively.

The default behavior is to trace all connections. You can specify either `user`, `connid` or `clientid` to selectively trace specific connections. The *value* can be a user name or ID (as appropriate).

Setting this parameter using the administration tool does not change its value in the configuration file `tibemsd.conf`; that is, the value does not persist across server restarts unless you set it in the configuration file.

console_trace

Sets trace options for output to `stderr`. The possible values are the same as for `log_trace`. However, console tracing is independent of log file tracing.

```
console_trace = traceOptions
```

If `logfile` is defined, you can stop console output by specifying:

```
console_trace=-DEFAULT
```



Important error messages (and some other messages) are always output, overriding the trace settings.

This example sends a trace message to the console when a TIBCO Rendezvous advisory message arrives.

```
console_trace=RVADV
```

logfile

Name and location of the server log file.

```
logfile = pathname
```

If the *pathname* contains spaces, it must be enclosed in double quotes.

By default, the logfile specified here is used by both servers in fault tolerant pair. Optionally, a JSON-configured server pair can set the [secondary_logfile](#) parameter to direct the server designated as secondary to write to a different file.

log_trace

Sets the trace preference on the file defined by the `logfile` parameter. If `logfile` is not set, the values have no effect.

```
log_trace = traceOptions
```

The value of this parameter is a comma-separated list of trace options. For a list of trace options and their meanings, see [Server Tracing Options](#).

You may specify trace options in three forms:

- plain A trace option without a prefix character replaces any existing trace options.
- + A trace option preceded by + adds the option to the current set of trace options.
- - A trace option preceded by - removes the option from the current set of trace options.

The following example sets the trace log to only show messages about access control violations.

```
log_trace=ACL
```

The next example sets the trace log to show all default trace messages, in addition to SSL messages, but ADMIN messages are not shown.

```
log_trace=DEFAULT, -ADMIN, +SSL
```

logfile_max_count

Specifies the maximum number of log files to be kept.

```
logfile_max_count = integer
```

Specify any number greater than 2.

When 0 or not specified, there is no limit to the number of log files kept.

logfile_max_size

Specifies the recommended maximum log file size before the log file is rotated. Set to 0 to specify no limit. Use KB, MB, or GB for units (if no units are specified, the file size is assumed to be in bytes).

```
logfile_max_size = size [KB|MB|GB]
```

The server periodically checks the size of the current log file. If it is greater than the specified size, the file is copied to a backup and then emptied. The server then begins writing to the empty log file until it reaches the specified size again.

Backup log files are named sequentially and stored in the same directory as the current log.

secondary_logfile

Name and location of the server log file used by the secondary EMS server in a fault tolerant pair. The EMS server designated as primary in the pair writes to the file specified by the `logfile` parameter.

```
secondary_logfile = pathname
```

If the `secondary_logfile` parameter is not set, the secondary server assumes the value of `logfile`.

If the *pathname* contains spaces, it must be enclosed in double quotes.

For more information, see [logfile](#).



This parameter is available only for JSON-configured EMS servers.

trace_client_host

Trace statements related to connections can identify the host by its hostname, its IP address, or both. When absent, the default is `hostname`. The `both_with_port` option displays the ephemeral port used on the host as well as the IP address and hostname.

```
trace_client_host = [hostname|address|both|both_with_port]
```

Statistic Gathering Parameters

See [Monitor Server Activity](#), for more information about these parameters.

server_rate_interval

Sets the interval (in seconds) over which overall server statistics are averaged.

```
server_rate_interval = seconds
```

This parameter can be set to any positive integer greater than zero.

Overall server statistics are always gathered, so this parameter cannot be set to zero. By default, this parameter is set to 1.

Setting this parameter allows you to average message rates and message size over the specified interval.

statistics

Enables or disables statistic gathering for producers, consumers, destinations, and routes. By default this parameter is set to disabled.

```
statistics = enabled | disabled
```

Disabling statistic gathering resets the total statistics for each object to zero.

rate_interval

Sets the interval (in seconds) over which statistics for routes, destinations, producers, and consumers are averaged.

```
rate_interval = seconds
```

By default, this parameter is set to 3 seconds. Setting this parameter to zero disables the average calculation.

detailed_statistics

Specifies which objects should have detailed statistic tracking.

```
detailed_statistics = NONE | [PRODUCERS, CONSUMERS, ROUTES]
```

Detailed statistic tracking is only appropriate for routes, producers that specify no destination, or consumers that specify wildcard destinations. When detailed tracking is enabled, statistics for each destination are kept for the object.

Setting this parameter to NONE disabled detailed statistic tracking. You can specify any combination of PRODUCERS, CONSUMERS, or ROUTES to enable tracking for each object. If you specify more than one type of detailed tracking, separate each item with a comma.

For example:

```
detailed_statistics = NONE
```

Turns off detailed statistic tracking.

```
detailed_statistics = PRODUCERS, ROUTES
```

Specifies detailed statistics should be gathered for producers and routes.

statistics_cleanup_interval

Specifies how long (in seconds) the server should keep detailed statistics if the destination has no activity.

```
statistics_cleanup_interval = seconds
```

This is useful for controlling the amount of memory used by detailed statistic tracking. When the specified interval is reached, statistics for destinations with no activity are deleted.

max_stat_memory

Specifies the maximum amount of memory to use for detailed statistic gathering.

```
max_stat_memory = size [KB|MB|GB]
```

If no units are specified, the amount is in bytes, otherwise you can specify the amount using KB, MB, or GB as the units.

Once the maximum memory limit is reached, the server stops collecting detailed statistics. If statistics are deleted and memory becomes available, the server resumes detailed statistic gathering.

SSL Server Parameters

See [SSL Protocol](#) for more information about these parameters.

ssl_dh_size

Size of the Diffie-Hellman key.

```
ssl_dh_size = [512 | 768 | 1024 | 2048]
```

Can be 512, 768, 1024, or 2048 bits. The default value is 1024.

This key is not used for cipher suites available for export.

ssl_server_ciphers

Specifies the cipher suites used by the server; each suite in the list is separated by a colon (:). This parameter must follow the OpenSSL cipher string syntax.

```
ssl_server_ciphers = cipherSuites
```

For example, you can enable two cipher suites with the following setting:

```
ssl_server_ciphers = DES-CBC3-SHA:AES128-SHA
```

See [Specify Cipher Suites](#) for more information about the cipher suites available in EMS and the syntax for specifying them in this parameter.

ssl_require_client_cert

If this parameter is set to `enable`, the server only accepts SSL connections from clients that have digital certificates. Connections from clients without certificates are denied.

```
ssl_require_client_cert = enable | disable
```

If this parameter is set to `disable`, then connections are accepted from clients that do not have a digital certificate.

Whether this parameter is set to `enable` or `disable`, clients that do have digital certificates are always authenticated against the certificates supplied to the [ssl_server_trusted](#) parameter.

The default value is `disable`.

ssl_require_route_cert_only

This parameter overrides the `ssl_require_client_cert` parameter.

```
ssl_require_route_cert_only = enable | disable
```

If `ssl_require_route_cert_only` is set to `enable`, the server requires a digital certificate only for SSL connections coming from routes, regardless of the value of [ssl_require_client_cert](#). In this case, the server does not require a digital certificate for SSL connections coming from clients and from its fault-tolerant peer.

If `ssl_require_route_cert_only` is set to `disable`, whether the server requires a digital certificate for SSL connections coming from all sources (routes, clients, and fault-tolerant peer) still depends on the value of `ssl_require_client_cert`.

The default value is `disable`.

ssl_use_cert_username

If this parameter is set to `enable`, a client's user name is always extracted from the CN field of the client's digital certificate, if the digital certificate is specified.

```
ssl_use_cert_username = enable | disable
```

If a different username is provided through the connection factory or API calls, then that username is discarded. Only the username from the CN is used.

The CN field is either a username, an email address, or a web address.



When `ssl_use_cert_username` is enabled, the username given by the CN becomes the only valid username. Any permissions associated with a different username, for example one assigned with an API call, are ignored.

ssl_cert_user_specname

This parameter is useful if clients are required to supply a username, but you wish to designate a special username to use when the client's username should be taken from the client's digital certificate.

```
ssl_cert_user_specname = username
```

For example, you may wish all clients to specify their username when logging in. This means the `ssl_use_cert_username` parameter would be set to `disable`. The username is supplied by the user, and not taken from the digital certificate. However, you may wish one username to signify that the client logging in with that name should have the name taken from the certificate. A good example of this username would be `anonymous`. All clients logging in as `anonymous` will have their user names taken from their digital certificates.

The value specified by this parameter is the username that clients will use to log in when the username should be taken from their digital certificate. A good example of the value of this parameter would be `anonymous`.

Also, the value of this parameter is ignored if `ssl_use_cert_username` is set to `enable`, in which case all client usernames are taken from their certificates. This parameter has no effect for users that have no certificate.

ssl_server_identity

The server's digital certificate in PEM, DER, or PKCS#12 format. You can specify the path to a file that contains the certificate in one of the supported formats.

```
ssl_server_identity = certificate
```

This parameter must be specified if any SSL ports are listed in the `listen` parameter.

PEM and PKCS#12 formats allow the digital certificate to include the private key. If these formats are used and the private key is part of the digital certificate, then setting `ssl_server_key` is optional.

For example:

```
ssl_server_identity = certs/server.cert.pem
```

ssl_server_key

The server's private key. If it is included in the digital certificate in `ssl_server_identity`, then this parameter is not needed.

```
ssl_server_key = private_key
```

This parameter supports private keys in the following formats: PEM, DER, PKCS#12.

You must specify a path to a file that contains the key.

ssl_password

Private key or password for private keys. This password can optionally be specified on the command line when `tibemsd` is started.

```
ssl_password = password
```

If SSL is enabled, and the password is not specified with this parameter or on the command line, `tibemsd` will ask for the password upon startup.

You can set passwords by way of the `tibemsadmin` tool. When passwords are set with this tool, the password is obfuscated in the configuration file. See [EMS Administration Tool](#) for more information about using `tibemsadmin` to set passwords.



Because connection factories do not contain the `ssl_password` (for security reasons), the EMS server uses the password that is provided in the "create connection" call for user authentication. If the create connection password is different from the `ssl_password`, the connection creation will fail.

ssl_server_issuer

Certificate chain member for the server. The server reads the certificates in the chain in the order they are presented in this parameter.

```
ssl_server_issuer = chain_member
```

The same certificate can appear in multiple places in the certificate chain.

The certificates must be in PEM, DER, PKCS#7, or PKCS#12 format.

See [File Names for Certificates and Keys](#) for more information on file types for digital certificates.

ssl_server_trusted

List of CA root certificates the server trusts as issuers of client certificates.

```
ssl_server_trusted = certificates
```

Specify only CA root certificates. Do not include intermediate CA certificates.

The certificates must be in PEM, DER, or PKCS#7 format. You can either provide the actual certificates, or you can specify a path to a file containing the certificate chain.

For example:

```
ssl_server_trusted = certs\CA1_root.pem  
ssl_server_trusted = certs\CA2_root.pem
```

See [File Names for Certificates and Keys](#) for more information on file types for digital certificates.

ssl_rand_egd

The path for the installed entropy gathering daemon (EGD), if one is installed. This daemon is used to generate random numbers for C clients and the EMS server. Java clients do not use this parameter.

```
ssl_rand_egd = pathname
```

ssl_crl_path

A non-null value for this parameter activates the server's certificate revocation list (CRL) feature.

```
ssl_crl_path = pathname
```

The server reads CRL files from this directory. The directory should contain only CRL files. If other files are located in the *pathname* directory, SSL initialization will fail.

ssl_crl_update_interval

The server automatically updates its CRLs at this interval (in hours).

```
ssl_crl_update_interval = hours
```

When this parameter is absent, the default is 24 hours.

ssl_auth_only

When enabled, the server allows clients to request the use of SSL only for authentication (to protect user passwords).

```
ssl_auth_only = enable | disable
```

For an overview of this feature, see [SSL Authentication Only](#).

When disabled, the server ignores client requests for this feature. When absent, the default value is disabled.

fips140-2

When `true`, the EMS server is enabled to run in FIPS 140-2 compliant mode. When `false` or excluded, the server is not FIPS compliant.

```
fips140-2 = true | false
```

For more information, see [Enable FIPS Compliance](#).

LDAP Parameters

See [Authentication and Permissions](#) for more information about these parameters.

ldap_url

URL of the external directory server.

This can take the following forms:

```
LDAP://host:tcp_port
```

or

```
LDAPS://host:ssl_port
```

For example:

```
LDAP://myLdapServer:1855
```

ldap_principal

The distinguished name (DN) of the LDAP user that the EMS sever uses to bind to the LDAP server. This user must have privileges that allow it to bind and browse group users, but does not necessarily need to have administrative privileges.

```
ldap_principal = DN
```

For example:

```
ldap_principal = "cn=Manager"
```

ldap_credential

The password associated with the user defined in the `ldap_principal` property.

```
ldap_credential = password
```

This value must be specified and cannot be an empty string.

ldap_cache_enabled

Enables caching of LDAP data.

```
ldap_cache_enabled = enable | disable
```

ldap_cache_ttl

Specifies the maximum time (in seconds) that cached LDAP data is retained before it is refreshed.

```
ldap_cache_ttl = seconds
```

ldap_conn_type

Specifies the type of connection that the server uses to get LDAP information.

```
ldap_conn_type = [ldaps | startTLS]
```

- When this parameter is absent, LDAP connections use TCP (non-secure). For backward compatibility, this is the default setting.

- `ldaps`—Use SSL on the LDAP connection (secure).
- `startTLS`—Use the startTLS extension to the LDAP version 3 protocol (secure).

ldap_tls_cacert_file

This file contains the CA certificate that the EMS server trusts to sign the LDAP server's certificate.

```
ldap_tls_cacert_file = pathname
```

You must provide `ldap_tls_cacert_file` in order to create secure connections. Optionally, `ldap_tls_cacert_dir` can be used *in addition to* `ldap_tls_cacert_file` in order to specify a directory with additional individual CA certificates.

ldap_tls_cacert_dir

When there are two or more CA certificates in the verify chain, the server scans this directory for CA certificates.

```
ldap_tls_cacert_dir = pathname
```

You must also provide `ldap_tls_cacert_file` in order to create secure connections. `ldap_tls_cacert_dir` is an optional parameter that can be used *in addition to* `ldap_tls_cacert_file` in order to specify a directory with additional individual CA certificates.

ldap_tls_cipher_suite

Optional. You can specify the cipher suite to use for encryption on secure LDAP connections.

```
ldap_tls_cipher_suite = cipher_suite
```

This parameter must follow the OpenSSL cipher string syntax; see [Specify Cipher Suites](#). You must use OpenSSL names when specifying the suite. For example, use AES128-SHA rather than TLS_RSA_WITH_AES_128_CBC_SHA. Using Java names results in an authorization error when connecting to a client.

In addition to the actual cipher names, you may specify cipher quality; for example:

- HIGH
- HIGH:MEDIUM

ldap_tls_rand_file

When the operating system does not include a random data feature, this file is the source of random data for encryption.

```
ldap_tls_rand_file = pathname
```

ldap_tls_cert_file

When the LDAP server requires client authentication, use the certificate in this file to identify the EMS server.

```
ldap_tls_cert_file = pathname
```

ldap_tls_key_file

When the LDAP server requires client authentication, use the private key in this file.

```
ldap_tls_key_file = pathname
```

When you plan to start the server remotely, we recommend that you do not password-encrypt the key file.

See [Authentication and Permissions](#), for more information about these parameters.

ldap_user_class

Name of the LDAP object class that stores users.

```
ldap_user_class = class_name
```

For example:

```
ldap_user_class = person
```

ldap_user_attribute

Name of the attribute on the user object class that holds the name of the user.

```
ldap_user_attribute = attribute
```

For example:

```
ldap_user_attribute = uid
```

ldap_user_base_dn

Base distinguished name (DN) of the LDAP tree that contains the users.

```
ldap_user_base_dn = DN
```

For example:

```
ldap_user_base_dn = "ou=People,dc=Corp"
```

ldap_user_scope

Specifies how deeply under the base DN to search for users.

```
ldap_user_scope = onelevel | subtree
```

You can specify `onelevel` and `subtree` for this parameter. `onelevel` specifies to search only one level below the DN, `subtree` specifies to search all sub-trees.

For example:

```
ldap_user_scope = subtree
```

ldap_user_filter

Optional LDAP search filter for finding a given user name.

```
ldap_user_filter = filter
```

Use `%s` as the placeholder for the user name in the filter. For example:

```
uid=%s
```

The full LDAP search grammar is specified in RFC 2254 and RFC 2251.

If unspecified, then a default search filter is generated based on the user object class and user name attribute.

ldap_all_users_filter

An optional LDAP search filter for finding all users beneath the user base DN.

```
ldap_all_users_filter = filter
```

If not specified, then a default search filter is generated based on the user object class and user name attribute.

See [Authentication and Permissions](#) for more information about these parameters.

ldap_group_base_dn

Base distinguished name (DN) of the LDAP tree that contains groups.

```
ldap_group_base_dn = DN
```

For example:

```
ldap_group_base_dn = "ou=Groups,dc=Corp"
```

ldap_group_scope

Specifies how deeply under the base DN to search for groups.

```
ldap_group_scope = onelevel | subtree
```

You can specify `onelevel` and `subtree` for this parameter. `onelevel` specifies to search only one level below the DN, `subtree` specifies to search all sub-trees.

For example:

```
ldap_group_scope = subtree
```

ldap_group_filter

Optional LDAP search filter for finding a group with a given group name. Use `%s` as the placeholder for the group name in the filter.

```
ldap_group_filter = filter
```

The full LDAP search grammar is specified in RFC 2254 and RFC 2251.

If unspecified, then a default search filter is generated based on the group object class and group attribute.

For example:

```
ldap_group_filter = "(|(&(cn=%s)(objectClass=groupofUniqueNames))(&(cn=%s)(objectClass=groupOfURLs)))"
```

ldap_all_groups_filter

Optional LDAP search filter for finding all groups beneath the group base DN.

```
ldap_all_groups_filter = filter
```

If unspecified, then a default search filter is generated based on the group object class and group attribute.

ldap_static_group_class

Name of the LDAP object class that stores static groups.

```
ldap_static_group_class = name
```

For example:

```
ldap_static_group_class = groupofuniquenames
```

ldap_static_group_attribute

Name of the attribute on the static group object class that holds the name of the group.

```
ldap_static_group_attribute = class
```

For example:

```
ldap_static_group_attribute = cn
```

ldap_static_group_member_filter

Optional LDAP search filter for finding all static members of a group. Use %s as the placeholder for the group name in the filter.

```
ldap_static_group_member_filter = filter
```

The full LDAP search grammar is specified in RFC 2254 and RFC 2251.

If unspecified, then the following default search filter is generated based on the group object class and group attribute:

```
ldap_static_group_member_filter = "(&(<ldap_static_member_attribute>=<user DN>)  
(objectClass=<ldap_static_group_class>))"
```

ldap_static_member_attribute

Attribute of an LDAP static group object that specifies the distinguished names (DNs) of the members of the group.

```
ldap_static_member_attribute = attribute
```

For example:

```
ldap_static_member_attribute = uniquemember
```

ldap_dynamic_group_class

Name of the LDAP object class that stores dynamic groups.

```
ldap_dynamic_group_class = class
```

For example:

```
ldap_dynamic_group_class = groupofURLs
```

ldap_dynamic_group_attribute

Name of the attribute on the dynamic group object class that holds the name of the group.

```
ldap_dynamic_group_attribute = attribute
```

For example:

```
ldap_dynamic_group_attribute = cn
```

ldap_dynamic_member_url_attribute

Attribute of the dynamic LDAP group object that specifies the URLs of the members of the dynamic group.

```
ldap_dynamic_member_url_attribute = attribute
```

For example:

```
ldap_dynamic_member_url_attribute = memberURL
```

Extensible Security Parameters

The extensible security feature allows you to write your own authentication and permissions modules for the server.

For more information on this feature, see [Extensible Security](#).

jaas_config_file

Specifies the location of the JAAS configuration file used by the EMS server to run a custom authentication LoginModule.

```
jaas_config_file = file-name
```

For more information, see [Loading the LoginModule in the EMS Server](#).

This parameter is required to enable the extensible security feature for authentication.

For example:

```
jaas_config_file = jaas.conf
```

jaas_login_timeout

Specifies the length of time, in milliseconds, that the EMS server will wait for the JAAS authentication module to execute and respond.

```
jaas_login_timeout = milliseconds
```

This timeout is used each time the server passes a username and password to the LoginModule. If the module does not return a response, the server denies authentication.

This parameter is optional. If it is not included, the default timeout is 10000 milliseconds.

For example:

```
jaas_login_timeout = 250
```

jaci_class

Specifies the name of the class that implements the extensible permissions interface.

```
jaci_class = class-name
```

The class must be written using the Java Access Control Interface (JACI). For more information about writing a custom application using JACI to grant permissions, see [Permissions Module](#).

For example:

```
jaci_class = com.userco.auth.CustomAuthorizer
```

jaci_timeout

Specifies the length of time, in milliseconds, that the EMS server will wait for the JACI permissions module to execute and respond.

```
jaci_timeout = milliseconds
```

This timeout is used each time the server passes a destination, username, and action to the permissions module. If the module does not return a response, the server denies authorization.

This parameter is optional. If it is not included, the default timeout is 500 milliseconds.

For example:

```
jaci_timeout = 250
```

security_classpath

Includes the JAR files and dependent classes used by the JAAS LoginModules and JACI modules.

```
security_classpath = classpath
```

This parameter is required to enable the extensible security feature for authentication and the extensible security feature for granting permissions.

For example:

```
security_classpath = ../usr/local/custom/user_jaci_plugin.jar
```

JVM Parameters

These parameters enable and configure the Java virtual machine (JVM) in the EMS server.

For more information on how the JVM works in EMS, see [Enable the JVM](#).

jre_library

Enables the JVM in the EMS server, where *path* is the absolute path to the JRE shared library file that is installed with the JRE.

```
jre_library = path
```

Depending on your platform, this could be `jvm.dll`, `libjvm.so`, `libjvm.dylib`, and so forth.

If this parameter is not included, the JVM is disabled by default.

If the *path* contains any spaces, the path must be enclosed in quotation marks.

For example:

```
jre_library = "C:\Program Files\Java\jdk1.8.0_121\jre\bin\server\jvm.dll"
```

jre_option

Passes command line options to the JVM at start-up.

```
jre_option = JVMoption
```

The `jre_option` parameter can be used to define Java system properties, which are used by applications running in the JVM, such as extensible security modules.

You can use multiple `jre_option` entries in order to pass more than one options to the JVM. Permitted values for *JVMoption* include most JVM options that are defined by Sun Microsystems.

For example, this restricts the maximum heap size of the JVM to 256 megabytes:

```
jre_option = -Xmx256m
```

Using Other Configuration Files

In addition to the main configuration file, there are several other configuration files used for various purposes.

These configuration files can be edited by hand, but you can also use the administration tool or the administration APIs to modify some of these files. See [EMS Administration Tool](#) for more information about using the administration tool.

Configuration File	Description
acl.conf	Defines EMS access control lists.
bridges.conf	Defines bridges between destinations.
durables.conf	Defines static durable subscribers.
factories.conf	Defines the connection factories stored as JNDI names on the EMS server.
groups.conf	Defines EMS groups.
jaas.conf	Locates and loads the LoginModule.
queues.conf	Defines EMS Queues.
routes.conf	Defines routes between this and other EMS servers
stores.conf	Defines the locations, either store files or a database, where the EMS server will store messages.

Configuration File	Description
<code>tibrvcn.conf</code>	Defines the TIBCO Rendezvous certified messaging (RVCM) listeners for use by topics that export messages to a tibrvcn transport.
<code>topics.conf</code>	Defines EMS Topics.
<code>transports.conf</code>	Defines transports used by EMS to import messages from or export messages to external message service, such as TIBCO FTL, Rendezvous, and SmartSockets.
<code>users.conf</code>	Defines EMS users.

acl.conf

This file defines all permissions on topics and queues for all users and groups.

The format of the file is:

```

TOPIC=topic USER=user PERM=permissions
TOPIC=topic GROUP=group PERM=permissions
QUEUE=queue USER=user PERM=permissions
QUEUE=queue GROUP=group PERM=permissions
ADMIN USER=user PERM=permissions
ADMIN GROUP=group PERM=permissions

```

Parameter Name	Description
TOPIC	Name of the topic to which you wish to add permissions.
QUEUE	Name of the queue to which you wish to add permissions.
ADMIN	Specifies that you wish to add administrator permissions.
USER	Name of the user to whom you wish to add permissions.
GROUP	Name of the group to which you wish to add permissions. The designation <code>all</code> specifies a predefined group that contains all users.
PERM	<p>Permissions to add.</p> <p>The permissions which can be assigned to queues are <code>send</code>, <code>receive</code> and <code>browse</code>. The permissions which can be assigned to topics are <code>publish</code>, <code>subscribe</code> and <code>durable</code> and <code>use_durable</code>. The designation <code>all</code> specifies all possible permissions. For information about these permissions, refer to When Permissions Are Checked and Inheritance of Permissions.</p> <p>Administration permissions are granted to users to perform administration activities. See Administrator Permissions for more information about administration permissions.</p>

Example

```

ADMIN USER=sys-admins PERM=all
TOPIC=foo USER=user2 PERM=publish,subscribe
TOPIC=foo GROUP=group1 PERM=subscribe

```

bridges.conf

This file defines bridges between destinations.

See [Destination Bridges](#) for more information about destination bridges.

The format of the file is:

```
[destinationType:destinationName] # mandatory -- include brackets
destinationType=destinationToBridgeTo1 [selector="msg-selector"]
destinationType=destinationToBridgeTo2 [selector="msg-selector"]
...
```

The *destination-name* can be any specific destination or a wildcard pattern to match multiple destinations.

Parameter Name	Description
<i>destinationType</i>	The type of the destination. That is, <code>topic</code> or <code>queue</code> .
<i>destinationName</i>	The name of the destination.
<i>destinationToBridgeTo</i>	One or more names of destinations to which to create a bridge.
<i>selector</i>	<p>This optional property specifies a message selector to limit the messages received by the bridged destination.</p> <p>For detailed information about message selector syntax, see the 'Message Selectors' section in description for the Message class in <i>TIBCO Enterprise Message Service Java API Reference</i>.</p>

Example

```
[topic:myTopic1]
  topic=myTopic2
  queue=myQueue1
```

durables.conf

This file defines static durable subscribers.

The file consists of lines with either of these formats:

```
topic-name durable-name
[route]
[clientid=id]
[nolocal]
[selector="msg-selector"]
```

Parameter Name	Description
<i>topic-name</i>	The topic of the durable subscription.
<i>durable-name</i>	The name of the durable subscriber.
<i>route</i>	<p>When present, the subscriber is another server, and the <i>durable-name</i> is the name of that server.</p> <p>When this property is present, no other properties are permitted.</p>
<i>clientid=id</i>	The client ID of the subscriber's connection.

Parameter Name	Description
<code>nolocal</code>	When present, the subscriber does not receive messages published from its own connection.
<code>selector="string"</code>	<p>When present, this selector narrows the set of messages that the durable subscriber receives.</p> <p>For detailed information about message selector syntax, see the 'Message Selectors' section in description for the Message class in <i>TIBCO Enterprise Message Service Java API Reference</i>.</p>

Example

```
topic1 dName1
topic2 dName2 clientid=myId,nolocal
topic3 dName3 selector="urgency in ('high','medium')"
topic4 Paris route
```

Conflicting Specifications

When the server detects an conflict between durable subscribers, it maintains the earliest specification, and outputs a warning. Consider these examples:

- A static specification in this file takes precedence over a new durable dynamically created by a client.
- An existing durable dynamically created by a client takes precedence over a new static durable defined by an administrator.
- A static durable subscription takes precedence over a client attempting to dynamically unsubscribe (from the same topic and durable name).

Conflict can also arise because of wildcards. For example, if a client dynamically creates a durable subscriber for topic `foo.*`, and an administrator later attempts to define a static durable for topic `foo.1`, then the server detects this conflict and warns the administrator.

Configuration

To configure durable subscriptions in this file, we recommend using the `create durable` command in the `tibemsadmin` tool; see [create durable](#).

If the `create durable` command detects an existing dynamic durable subscription with the same topic and name, it promotes it to a static subscription, and writes a specification to the file [durables.conf](#).

factories.conf

This file defines the connection factories for the internal JNDI names.

The file consists of factory definitions with this format:

```
[factory-name] # mandatory -- square brackets included
type = generic|xageneric|topic|queue|xatopic|xaqueue|
url = url-string
metric = connections | byte_rate
clientID = client-id
[connect_attempt_count|connect_attempt_delay|
connect_attempt_timeout|reconnect_attempt_count|
reconnect_attempt_delay|reconnect_attempt_timeout = value]
[ssl-prop = value]*
```

Parameter Name	Description
Mandatory Parameters These parameters are required. Values given to these parameters cannot be overridden using API calls.	
<code>[factory-name]</code>	<p><code>[factory-name]</code> is the name of the connection factory.</p> <p>Note that the square brackets [] DO NOT indicate that the <i>factory-name</i> is optional; they must be included around the name.</p>
<code>type</code>	<p>Type of the connection factory. The value can be:</p> <ul style="list-style-type: none"> <code>generic</code>: Generic connection <code>xageneric</code>: Generic XA connection <code>topic</code>: Topic connection <code>queue</code>: Queue connection <code>xatopic</code>: XA topic connection <code>xaqueue</code>: XA queue connection
<code>url</code>	<p>This string specifies the servers to which this factory creates connections:</p> <ul style="list-style-type: none"> A single URL specifies a unique server. For example: <code>tcp://host1:8222</code> A pair of URLs separated by a comma specifies a pair of fault-tolerant servers. For example: <code>tcp://host1:8222,tcp://backup1:8222</code> A set of URLs separated by vertical bars specifies a load balancing among those servers. For example: <code>tcp://a:8222 tcp://b:8222 tcp://c:8222</code> You can combine load balancing with fault tolerance. For example: <code>tcp://a1:8222,tcp://a2:8222 tcp://b1:8222,tcp://b2:8222</code> <p>This example defines two servers (a and b), each of which has a fault-tolerant backup. The client program checks the load on the active a server and the active b server, and connects to the one that has the smaller load. If it cannot connect to one of the active servers, the client attempts to connect to the standby server. For example, if it cannot connect to b1, it connects to b2.</p> <p>The connection URL cannot exceed 1000 characters.</p> <p>For cautionary information, see Load Balancing.</p>
Optional Parameters These parameters are optional. The values of these parameters can be overridden using API calls.	

Parameter Name	Description
<code>metric</code>	<p>The factory uses this metric to balance the load among a group of servers:</p> <ul style="list-style-type: none"> <code>connections</code>—Connect to the server with the fewest client connections. <code>byte_rate</code>—Connect to the server with the lowest byte rate. Byte rate is a statistic that includes both inbound and outbound data. <p>When this parameter is absent, the default metric is <code>connections</code>. For cautionary information, see Load Balancing.</p>
<code>clientID</code>	The factory associates this client ID string with the connections that it creates. The client ID cannot exceed 255 characters in length.
<code>connect_attempt_count</code>	A client program attempts to connect to its server (or in fault-tolerant configurations, it iterates through its URL list) until it establishes its first connection to an EMS server. This property determines the maximum number of iterations. When absent, the default is 2.
<code>connect_attempt_delay</code>	When attempting a first connection, the client sleeps for this interval (in milliseconds) between attempts to connect to its server (or in fault-tolerant configurations, iterations through its URL list). When absent, the default is 500 milliseconds.
<code>connect_attempt_timeout</code>	When attempting to connect to the EMS server, you can set this connection timeout period to abort the connection attempt after a specified period of time (in milliseconds).
<code>reconnect_attempt_count</code>	After losing its server connection, a client program configured with more than one server URL attempts to reconnect, iterating through its URL list until it re-establishes a connection with an EMS server. This property determines the maximum number of iterations. When absent, the default is 4.
<code>reconnect_attempt_delay</code>	When attempting to reconnect, the client sleeps for this interval (in milliseconds) between iterations through its URL list. When absent, the default is 500 milliseconds.
<code>reconnect_attempt_timeout</code>	When attempting to reconnect to the EMS server, you can set this connection timeout period to abort the connection attempt after a specified period of time (in milliseconds).
<code>ssl-prop</code>	<p>SSL properties for connections that this factory creates.</p> <p>For further information on SSL, refer to SSL Protocol.</p>

Example

```
[north_america]
  type = topic
  url = tcp://localhost:7222,tcp://server2:7222
```

```
clientID = "Sample Client ID"
ssl_verify_host = disabled
```

Configuration

To configure connection factories in this file, we recommend using the `tibemsadmin` tool; see [create factory](#).

Load Balancing

Do not specify load balancing in situations with durable subscribers.

If a client program that creates durable subscriber connects to server A using a load-balanced connection factory, then server A creates and supports the durable subscription. If the client program exits and restarts, and this time connects to server B, then server B creates and supports a new durable subscription—however, pending messages on server A remain there until the client reconnects to server A.

Do not specify load balancing when your application requires strict message ordering.

Load balancing chooses from among multiple servers, which inherently violates strict ordering.

groups.conf

This file defines all groups. The format of the file is:

```
group-name1:"description"
    user-name1
    user-name2
group-name2:"description"
    user-name1
    user-name2
```

Group Parameters

Parameter Name	Description
<i>group-name</i>	The name of the group. The group name cannot exceed 255 characters in length.
<i>description</i>	A string describing the group.
<i>user-name</i>	One or more users that belong to the group.

Example

```
administrators: "TIBCO Enterprise Message Service administrators"
    admin
    Bob
```

jaas.conf

This file directs the TIBCO Enterprise Message Service server to the JAAS LoginModule.

See [Loading the LoginModule in the EMS Server](#) for more information about the `jaas.conf` file.

queues.conf

This file defines all queues.

The format of the file is:

```
[jndi-name1, jndi-name2, ...]queue-name property1, property2, ...
```



Note that, while including JNDI names is optional, the square brackets [] must be included around JNDI names if they are included. For more information about setting JNDI names, see [create jndiname](#).

For example, you might enter:

```
test store=mystore,secure,prefetch=2
```

Only queues listed in this file or queues with names that match the queues listed in this file can be created by the applications (unless otherwise permitted by an entry in [acl.conf](#)). For example, if queue `foo.*` is listed in this file, queues `foo.bar` and `foo.baz` can be created by the application.

Properties of the queue are inherited by all static and dynamic queues with matching names. For example, if `test.*` has the property [secure](#), then `test.1` and `test.foo` are also secure. For information on properties that can be assigned to queues, see [Destination Properties](#).

For further information on the inheritance of queue properties, refer to [Wildcards * and >](#) and [Inheritance of Properties](#).



In the sample file, a `>` wildcard at the beginning of the file allows the applications to create valid queues with any name. A `>` at the beginning of the queue configuration file means that name-matching is not required for creation of queues.

Restrictions and rules on queue names are described in [Destination Name Syntax](#).

routes.conf

This file defines routes between this TIBCO Enterprise Message Service server and other TIBCO Enterprise Message Service servers.



Routes may only be configured administratively, using the administration tool (see [Using the EMS Administration Tool](#)), or the administration APIs (see `com.tibco.tibjms.admin.RouteInfo` in the online documentation). Directly editing the `routes.conf` file causes errors.

The format of the file is:

```
[route-name] # mandatory -- square brackets included.
url=url-string
zone_name=zone_name
zone_type=zone_type
topic_prefetch=value
[selector]*
[ssl-prop = value]*
```

Parameter Name	Description
<code>[route-name]</code>	<code>[route-name]</code> is the name of the passive server (at the other end of the route); it also becomes the name of the route. Note that the square brackets [] DO NOT indicate that the <code>route-name</code> is an option; they must be included around the name.
<code>url</code>	The URL of the server to and from which messages are routed.
<code>zone_name</code>	<p>The route belongs to the routing zone with this name. When absent, the default value is <code>default_mhop_zone</code>.</p> <p>You can set this parameter when creating a route, but you cannot subsequently change it.</p> <p>For further information, see these sections:</p> <ul style="list-style-type: none"> Zone Configure Routes and Zones

Parameter Name	Description
<code>zone_type</code>	<p>The zone type is either <code>1hop</code> or <code>mhop</code>. When omitted, the default value is <code>mhop</code>.</p> <p>You can set this parameter when creating a route, but you cannot subsequently change it.</p> <p>The EMS server will refuse to start up if the zone type in the <code>routes.conf</code> file does not match the zone type already created in the <code>\$sys.meta</code> file that holds the shared state for the primary and secondary server.</p>
<code>topic_prefetch</code>	<p>A prefetch value for the route. Setting a prefetch at the route level allows you to assign larger values for WAN routing functions.</p> <p>If <code>topic_prefetch</code> is not set, the route uses the <code>prefetch</code> value specified for the destination. If a <code>topic_prefetch</code> is set for the route and a different <code>prefetch</code> is set for the destination, the <code>topic_prefetch</code> value overrides the destination prefetch.</p> <p>See the prefetch destination property for valid settings.</p>
<code>selector</code>	<p>Topic selectors (for <code>incoming_topic</code> and <code>outgoing_topic</code> parameters) control the flow of topics along the route.</p> <p>For syntax and semantics, see Selectors for Routing Topic Messages.</p>
<code>ssl-prop</code>	<p>SSL properties for this route.</p> <p>For further information on SSL, refer to SSL Protocol.</p>

Example

```
[test_route_2]
url = tcp://server2:7222
ssl_verify_host = disabled
```

stores.conf

This file defines the locations, either store files, mstore, or a database, where the EMS server will store messages or metadata (if the default `$sys.meta` definition is overridden). You can configure one or many stores in the `stores.conf` file.

Each store configured is either a file-based store, mstore, or a database store. File-based store and mstore parameters are described here. Database store parameters are described in [Database Stores](#).

The format of the file is:

```
[store_name] # mandatory -- square brackets included
  type=file
  file=name
  file_destination_defrag=size
  [file_crc=true|false]
  [file_minimum=value]
  [file_truncate=value]
  [mode=async|sync]
  [processor_id=processor id]
[store_name]
  type=mstore
  file=name
  [mode=async|sync]
  [mstore_truncate=value]
  [processor_id=processor-id]
```

```
[scan_iter_interval=time msec|sec|min|hour|day]
[scan_target_interval=time msec|sec|min|hour|day]
```

Parameter Name	Description
[<i>store_name</i>]	<p>[<i>store_name</i>] is the name that identifies this store file configuration.</p> <p>Note that the square brackets [] DO NOT indicate that the <i>store_name</i> is an option; they must be included around the name.</p>
type	<p>Identifies the store type. This parameter is required for all store types. The type can be:</p> <ul style="list-style-type: none"> file — for file-based stores. mstore — for mstores. dbstore — for database stores. <p>For information about the parameters used to configure database stores, see Configuration in stores.conf.</p>
file	<p>The filename that will be used when creating this store file. This parameter is required for both file and mstore types. For example, <i>mystore.db</i>.</p> <p>The location for this file can be specified using absolute or relative path names. If no path separators are present, the file will be saved in the location specified by the store parameter in the tibemsd.conf file, if any is specified there.</p>
mode	<p>The mode determines whether messages will be written to the store synchronously or asynchronously. Mode is either:</p> <ul style="list-style-type: none"> async — the server stores messages in this file using asynchronous I/O calls. sync — the server stores messages in this file using synchronous I/O calls. <p>When absent, the default for file-based stores is <i>async</i>. The default mode for mstores is <i>sync</i>.</p>
processor_id	<p>When specified, the EMS Server binds the storage thread of this store to the specified processor.</p> <p>Do not use this parameter if the default behavior provides sufficient throughput. If no processor ID is specified for a store, the store is not bound to a specific processor.</p> <p>Specify the <i>processor-id</i> as an integer.</p> <p>This parameter has similar requirements, limitations, and benefits as the processor_ids parameter in tibemsd.conf.</p> <p>For use guidelines, see Performance Tuning.</p>
File-Based Store Parameters	

Parameter Name	Description
<code>file_destination_defrag</code>	<p>This parameter specifies a maximum batch size used by the destination defrag feature.</p> <p>Destination defrag improves store file performance by maintaining contiguous space for new messages, while improving server read performance. When persistent pending messages begin to accumulate in a queue, messages are grouped into a batch that is re-written to disk. Messages are written close together, allowing the server to read them more efficiently when later delivering the messages to consumers.</p> <p>Specify <i>size</i> in bytes, KB, MB or GB.</p> <p>The <i>size</i> should be set to a size that is known to be acceptable for the disk where the store points to. For instance, if it is set to 2MB, your disk must be able to write a 2MB batch efficiently.</p> <p>If <code>file_destination_defrag</code> is zero or absent, the destination defrag feature is disabled.</p>
<code>file_crc</code>	<p>This parameter specifies whether the EMS server uses CRC to validate data integrity when reading the store files.</p> <p>When this parameter is absent, the default is <code>true</code>.</p>
<code>file_minimum</code>	<p>This parameter preallocates disk space for the store file. Preallocation occurs when the server first creates the store file.</p> <p>You can specify units of MB or GB. Zero is a special value, which specifies no minimum preallocation. Otherwise, the value specified must be greater than 4MB.</p> <p>For example:</p> <pre>file_minimum = 32MB</pre> <p>If <code>file_truncate</code> is set to <code>true</code>, the <code>file_minimum</code> parameter prevents the EMS server from truncating the file below the set size.</p> <p>When this parameter is absent, there is no default minimum preallocation.</p>
<code>file_truncate</code>	<p>Determines whether the EMS server will occasionally attempt to truncate the store file, relinquishing unused disk space.</p> <p>When <code>file_truncate</code> is <code>true</code>, the store file can be truncated, but not below the size set in <code>file_minimum</code>.</p> <p>When this parameter is absent, the default is <code>true</code>, and the server will periodically attempt to truncate the store file.</p>
mstore Parameters	

Parameter Name	Description
<code>scan_iter_interval</code>	<p>Determines the length of time between each interval of the store scan. The EMS server begins scanning a new section of the mstore at the time interval specified here.</p> <p>Specify <i>time</i> in units of <code>msec</code>, <code>sec</code>, <code>min</code>, <code>hour</code> or <code>day</code> to describe the time value as being in milliseconds, seconds, minutes, hours, or days, respectively. For example:</p> <pre>scan_iter_interval=100msec</pre> <p>By default, the mstore examines stores every 10 seconds.</p> <p>For more information, see Understanding mstore Intervals.</p>
<code>scan_target_interval</code>	<p>Controls the approximate length of time taken to complete a full scan of the mstore.</p> <p>Specify <i>time</i> in units of <code>msec</code>, <code>sec</code>, <code>min</code>, <code>hour</code> or <code>day</code> to describe the time value as being in milliseconds, seconds, minutes, hours, or days, respectively. For example:</p> <pre>scan_target_interval=12hour</pre> <p>By default, the scan interval is 24 hours.</p> <p>For more information, see Understanding mstore Intervals.</p>
<code>mstore_truncate</code>	<p>When <code>mstore_truncate</code> is true, the EMS server occasionally attempts to truncate the mstore files, relinquishing unused disk space. Enabling <code>mstore_truncate</code> may increase the fragmentation of the store files.</p> <p>When this parameter is absent, the default is <code>false</code>.</p> <p>This feature is not available by default. Before using it, you must run the <code>tibemsdbconvert</code> tool with option <code>-version 8.3</code> on the required mstore files.</p>

Example

```
[my_sync]
type = file
file = /var/local/tibems/my_sync.db
file_destination_defrag=2MB
file_crc = true
file_minimum = 10MB
file_truncate = true
mode = sync
```

Example

```
[mstore1]
type = mstore
file = /var/local/tibems/mstore1.db
mode = async
mstore_truncate = true
scan_iter_interval=100msec
scan_target_interval=12hour
```

tibrvcn.conf

This file defines the TIBCO Rendezvous certified messaging (RVCN) listeners for use by topics that export messages to a `tibrvcn` transport. The server preregisters these listeners when the server starts up so that all messages (including the first message published) sent by way of the `tibrvcn` transport

are guaranteed. If the server does not preregister the RVCN listeners before exporting messages, the listeners are created when the first message is published, but the first message is not guaranteed.

The format of this file is

```
transport listenerName subjectName
```

Parameter Name	Description
<i>transport</i>	The name of the transport for this RVCN listener.
<i>listenerName</i>	The name of the RVCN listener to which topic messages are to be exported.
<i>subjectName</i>	The RVCN subject name that messages are published to. This should be the same name as the topic names that specify the export property.

Example

```
RVCN01 listener1 foo.bar
RVCN01 listener2 foo.bar.bar
```

topics.conf

This file defines all topics.

The format of the file is:

```
[jndi-name1, jndi-name2, ...]topic-name property1, property2, ...
```



Note that, while including JNDI names is optional, the square brackets [] must be included around JNDI names if they are included. For more information about setting JNDI names, see [create jndiname](#).

For example, you might enter:

```
business.inventory global, import="RV01,RV02", export="RV03", maxbytes=1MB
```

Only topics listed in this file or topics with names that match the topics listed in this file can be created by the applications (unless otherwise permitted by an entry in [acl.conf](#)). For example, if topic `foo.*` is listed in this file, topics `foo.bar` and `foo.baz` can be created by the application.

Properties of the topic are inherited by all static and dynamic topics with matching names. For example, if `test.*` has the property [secure](#), then `test.1` and `test.foo` are also secure. For information on properties that can be assigned to topics, see [Destination Properties](#).

For further information on the inheritance of topic properties, refer to [Wildcards * and >](#) and [Inheritance of Properties](#).

Restrictions and rules on topic names are described in [Destination Name Syntax](#).

transports.conf

This file defines transports for importing messages from or exporting messages to external message services, such as TIBCO FTL, TIBCO Rendezvous, and TIBCO SmartSockets.

The format of the file is:

```
[transport_name] # mandatory -- square brackets included
type = tibftl | tibrv | tibrvcn | tibss # mandatory
[topic_import_dm = TIBEMS_PERSISTENT |
                    TIBEMS_NON_PERSISTENT |
                    TIBEMS_RELIABLE]
[queue_import_dm = TIBEMS_PERSISTENT |
                   TIBEMS_NON_PERSISTENT |
                   TIBEMS_RELIABLE]
```



```
[export_headers = true | false]
[export_properties = true | false]
transport-specific-parameters
```

Parameter Name	Description
[<i>transport_name</i>]	The name of the transport. Note that the square brackets [] DO NOT indicate that the <i>transport_name</i> is an option; they must be included around the name.
type	<p>Transport type.</p> <ul style="list-style-type: none"> • <code>tibftl</code> identifies TIBCO FTL transport • <code>tibrv</code> identifies TIBCO Rendezvous transport • <code>tibrvc</code> identifies TIBCO Rendezvous Certified Messaging transport • <code>tibss</code> identifies TIBCO SmartSockets transport <p>Each transport includes additional <i>transport-specific-parameters</i>.</p>
topic_import_dm queue_import_dm	<p>EMS sending clients can set the JMSDeliveryMode header field for each message. However, Rendezvous clients cannot set this header. Instead, these two parameters determine the delivery modes for all topic messages and queue messages that <code>tibemsd</code> imports on this transport.</p> <p>TIBEMS_PERSISTENT TIBEMS_NON_PERSISTENT TIBEMS_RELIABLE</p> <p>When absent, the default is TIBEMS_NON_PERSISTENT.</p>
export_headers	<p>When <code>true</code>, <code>tibemsd</code> includes JMS header fields in exported messages.</p> <p>When <code>false</code>, <code>tibemsd</code> suppresses JMS header fields in exported messages.</p> <p>When absent, the default value is <code>true</code>.</p>
export_properties	<p>When <code>true</code>, <code>tibemsd</code> includes JMS properties in exported messages.</p> <p>When <code>false</code>, <code>tibemsd</code> suppresses JMS properties in exported messages.</p> <p>When absent, the default value is <code>true</code>.</p>
transport-specific-parameters	See Transport-specific Parameters .



If you have multiple TIBCO Rendezvous transports configured in your `transports.conf` file, and if the EMS server fails to create a transport based on the last entry, the server will continue to traverse through the entries and attempt to create further transports.

Transport-specific Parameters

tibftl transports

If type = tibftl, the extended syntax is:

```
[endpoint = endpoint-name]
[import_subscriber_name = subscriber-name]
[import_match_string = {"fieldname1":value1, ..., "fieldnameN":valueN}]
[export_format = format-name]
[export_constant = constant1, value1]
...
[export_constant = constantN, valueN]
```

See [TIBCO FTL Parameters](#) for descriptions.

tibrv transports

If type = tibrv, the extended syntax is:

```
[service = service]
[network = network]
[daemon = daemon]
[temp_destination_timeout = seconds]
[rv_queue_policy = [TIBRVQUEUE_DISCARD_NONE |
                   TIBRVQUEUE_DISCARD_FIRST |
                   TIBRVQUEUE_DISCARD_LAST]:max_msgs:qty_discard]
```

See [Rendezvous Parameters](#) for descriptions.

tibrvcn transports

If type = tibrvcn, the extended syntax is:

```
rv_tport = name # mandatory
[cm_name = name]
[ledger_file = file-name]
[sync_ledger = true | false]
[request_old = true | false]
[explicit_config_only = true | false]
[default_ttl = seconds]
[rv_queue_policy = [TIBRVQUEUE_DISCARD_NONE |
                   TIBRVQUEUE_DISCARD_FIRST |
                   TIBRVQUEUE_DISCARD_LAST]:max_msgs:qty_discard]
```

See [Rendezvous Certified Messaging \(RVCN\) Parameters](#) for descriptions.

tibss transports

If type = tibss, the extended syntax is:

```
[username = name]
[password = password]
[server_names = single_or_list_of_servers]
[project = name]
[delivery_mode = best_effort | gmd_all | gmd_some | ordered]
[lb_mode = none | round_robin | weighted | sorted]
[override_lb_mode = enable | disable]
[gmd_file_delete = enable | disable]
[import_ss_headers = none | type_num | all]
[preserve_gmd = always | receivers | never]
```

See [SmartSockets Parameters](#) for descriptions.

Example

```
[FTL01]
  type = tibftl
  endpoint = EP1
```

```

import_subscriber_name = sub1
import_match_string = {"f1":"foo","f2":true}
export_format = format-1
export_constant = constant1,value1
export_constant = constant2,value2
export_constant = constant3,value3

[RV01]
type = tibrv
topic_import_dm = TIBEMS_RELIABLE
queue_import_dm = TIBEMS_PERSISTENT
service = 7780
network = lan0
daemon = tcp:host5:7885

[RVC01]
type = tibrvcm
export_headers = true
export_properties = true
rv_tport = RV02
cm_name = RVCMTTrans1
ledger_file = ledgerFile.store
sync_ledger = true
request_old = true
default_ttl = 600

[SS01]
type = tibss
server_names = tcp:rtHost2A:5555, ssl:rtHost2B:5571
username = emsServer6
password = myPasswd
project = mfg_process_control
override_lb_mode = enable
delivery_mode = gmd_some

[RV02]
type = tibrv
topic_import_dm = TIBEMS_PERSISTENT
queue_import_dm = TIBEMS_PERSISTENT
service = 7780
network = lan0
daemon = tcp:host5:7885
rv_queue_policy = TIBRVQUEUE_DISCARD_LAST:10000:100

```

users.conf

This file defines all users.

The format of the file is:

```
username:password:"description"
```

Parameter Name	Description
<i>username</i>	The name of the user. The username cannot exceed 255 characters in length.
<i>password</i>	<p>Leave this item blank when creating a new user. For example:</p> <pre>bob::"Bob Smith"</pre> <p>There is one predefined user, the administrator.</p> <p>User passwords are not entered in this configuration file, and remain empty (and therefore <i>not</i> secure) until you set them using the administration tool; see Assigning a Password to the Administrator. You can also create users and assign passwords using API calls; see the API reference for the language you are working with.</p>

Parameter Name	Description
<i>description</i>	A string describing the user.

Example

```
admin: "Administrator"  
Bob: "Bob Smith"  
Bill: "Bill Jones"
```

After the server has started and passwords have been assigned, the file will look like this:

```
admin: $1$urmKVgq78: "Administrator"  
Bob: $2$sldfkj;lsafd: "Bob Smith"  
Bill: $3$tyavmwq92: "Bill Jones"
```

Authentication and Permissions

You can create users and assign passwords to the users to control access to the EMS server. EMS can also be configured to use an external directory (such as an LDAP server) to control access to the server.

You can also assign permissions to users and groups to control actions that can be performed on destinations.

Setting up EMS Access Control

EMS supports two basic access levels: administrative and user.

Administrator permissions control the ability of a user to login as an administrator to create, delete, or view the status of users, destinations, connections, factories, and so on. Administrators with the correct permissions can control user access to the EMS server by creating users, assigning passwords, and setting permissions.

The following procedure describes the general process for administrators to configure users, groups, and permissions and where to find more information on performing each step.

Procedure

1. Enable access control for the system. See [Enable Access Control](#).
2. Determine which destinations require access control, and enable access control for those destinations. See [Destination Control](#).
3. Determine which users need administration permissions, and decide whether administrators can perform actions globally or be restricted to a subset of actions. See [Administrator Permissions](#) for more information.
4. Determine the names of the authorized users of the system and create usernames and passwords for these users. See [Users and Groups](#).
5. Optionally, set up groups and assign users to groups. See [Users and Groups](#).
6. Optionally enable an external directory for storing users and group information. See [Configure an External Directory](#).
7. Create the access control list by granting specific permissions to users (or groups) for destinations that need to be secure. See [User Permissions](#).

Administrator Permissions

Administrators are a special class of users that can manage the EMS server. Administrators create, modify, and delete users, destinations, routes, factories, and other items. In general, administrators must be granted permission to perform administration activities when using the administration tool or API. Administrators can be granted global permissions (for example, permission to create users or to view all queues), and administrators can be granted permissions to perform operations on specific destinations (for example, purging a queue, or viewing properties for a particular topic).

Administrator permissions control what administrators can view and change in the server only when using the administration tool or API. Administrator commands create entries in each of the configuration files (for example, [tibemsd.conf](#), [acl.conf](#), [routes.conf](#), and so on).



You should control access to the configuration files so that only certain system administrators can view or modify the configuration files. If a user can view or modify the configuration files, setting permissions to control which destination that user can manage would not be enforced when the user manually edits the files.

Use the facilities provided by your Operating System to control access to the server's configuration files.

Administrators must be created using the administration tool, the administration APIs, or in the configuration files.

Predefined Administrative User and Group

There is a special, predefined user named `admin` that can perform any administrative action. You cannot grant or revoke any permissions to `admin`. You must assign a password for `admin` immediately after installation.

For more information about changing the `admin` password, see [When You First Start tibemsadmin](#).

There is also a special group named `$admin` for system administrator users. When a user becomes a member of this group, that user receives the same permissions as the `admin` user. You cannot grant or revoke administrator permissions from any user that is a member of the `$admin` group. You should only assign the overall system administrator(s) to the `$admin` group.

Granting and Revoking Administration Permissions

You grant and revoke administrator permissions to users using the `grant` and `revoke` commands in `tibemsadmin`, or by means of the Java or .NET `admin` API. You can either grant global administrator permissions or permissions on specific destinations.

See [Global Administrator Permissions](#) for a complete list of global administrator permissions. See [Destination-Level Permissions](#) for a description of administrator permissions for destinations.

Global and destination-level permissions are granted and revoked separately using different administrator commands. See [Command Listing](#) for the syntax of the `grant` and `revoke` commands.

If a user has both global and destination-level administrator permissions, the actions that user can perform are determined by combining all global and destination-level administrator permissions granted to the user. For example, if an administrator is granted the `view-destination` permission, that administrator can view information about all destinations, even if the `view` permission is not granted to the administrator for specific destinations.

The `admin` user or all users in the `$admin` group can grant or revoke any administrator permission to any user. All other users must be granted the `change-admin-acl` permission and the `view-user` and/or the `view-group` permissions before they can grant or revoke administrator permissions to other users.

If a user has the `change-admin-acl` permission, that user can only grant or revoke permissions that have been granted to the user. For example, if user `BOB` is not part of the `$admin` group and he has only been granted the `change-admin-acl` and `view-user` permissions, `BOB` cannot grant any administrator permissions except the `view-user` or `change-admin-acl` permissions to other users.

Users have all administrator permissions that are granted to any group to which they belong. You can create administrator groups, grant administrator permissions to those groups, and then add users to each administrator group. The users will be able to perform any administrative action that is allowed by the permissions granted to the group to which the user belongs.

Any destination-level permission granted to a user or group for a wildcard destination is inherited for all child destinations that match the parent destination.

If protection permissions are set up, administrators can only grant or revoke permissions to other users that have the same protection permission as the administrator. See [Protection Permissions](#) for more information about protection permissions.

Enforcement of Administrator Permissions

An administrator can only perform actions for which the administrator has been granted permission. Any action that an administrator performs may be limited by the set of permissions granted to that administrator.

For example, an administrator has been granted the `view` permission on the `foo.*` destination. This administrator has not been granted the global `view-destination` permission. The administrator is only able to view destinations that match the `foo.*` parent destination. If this administrator is granted the

global `view-acl` permission, the administrator is only able to view the access control list for destinations that match the `foo.*` parent. Any access control lists for other destinations are not displayed when the administrator performs the `showacl topic` or `showacl queue` commands.

If the administrative user attempts to execute a command without permission, the user may either receive an error or simply see no output. For example, if the administrator issues the `showacl queue bar.foo` command, the administrator receives a “Not authorized to execute command” error because the administrator is not authorized to view any destination except those that match `foo.*`.

An administrator can always change his/her own password, even if the administrator is not granted the `change-user` permission.



An administrator can always view his/her own permissions by issuing the:

```
showacl username
```

command, even if the administrator is not granted the `view-acl` permission.

Global Administrator Permissions

Certain permissions allow administrators to perform global actions, such as creating users or viewing all queues.

The following table describes the global administrator permissions.

Permission	Allows Administrator To...
<code>all</code>	Perform all administrative commands.
<code>view-all</code>	View any item that can be administered (for example, users, groups, topics, and so on).
<code>change-acl</code>	Grant and revoke user-level permissions.
<code>change-admin-acl</code>	Grant and revoke administrative permissions.
<code>change-bridge</code>	Create and delete destination bridges.
<code>change-connection</code>	Delete connections.
<code>create-destination</code>	Create any destination.
<code>modify-destination</code>	Modify any destination.
<code>delete-destination</code>	Delete any destination.
<code>change-durable</code>	Delete durable subscribers.
<code>change-factory</code>	Create, delete, and modify factories.
<code>change-group</code>	Create, delete, and modify groups.
<code>change-message</code>	Delete messages stored in the server.
<code>change-route</code>	Create, delete, and modify routes
<code>change-server</code>	Modify server parameters.

Permission	Allows Administrator To...
change-user	Create, delete, and modify users.
purge-destination	Purge destinations.
purge-durable	Purge durable subscribers.
shutdown	Shutdown the server.
view-acl	View user-level permissions.
view-admin-acl	View administrative permissions.
view-connection	View connections, producers and consumers.
view-bridge	View destination bridges.
view-destination	View destination properties and information.
view-durable	View durable subscribers. To view a durable subscriber, you must also have view-destination permission (because information about a durable subscriber includes information about the destination to which it subscribes.)
view-factory	View factories.
view-group	View all groups. Granting this permission implicitly grants view-user as well.
view-message	View messages stored in the server.
view-route	View routes.
view-server	View server configuration and information.
view-user	View any user.



Any type of modification to an item requires that the user can view that item. Therefore, granting any create, modify, delete, change, or purge permission implicitly grants the permission to view the associated item.

Granting the view permissions is useful when you want specific users to only be able to view items. It is not necessary to grant the view permission if a user already has a permission that allows the user to modify the item.

Global permissions are stored in the `acl.conf` file, along with all other permissions. Global permissions in this file have the following syntax:

```
ADMIN USER=<username> PERM=<permission>
```

or

```
ADMIN GROUP=<groupname> PERM=<permission>
```


For example, if a user named BOB is granted the `view-user` global administration permission and the group `sys-admins` is granted the `change-acl` permission, the following entries are added to the `acl.conf` file:

```
ADMIN USER=BOB PERM=view-user
ADMIN GROUP=sys-admins PERM=change-acl
```

Destination-Level Permissions

Administrators can be granted permissions on each destination. Destination-level permissions control the administration functions a user can perform on a specific destination. Global permissions granted to a user override any destination-level permissions.

The typical use of destination-level administration permissions is to specify permissions on wildcard destinations for different groups of users. This allows you to specify particular destinations over which a group of users has administrative control. For example, you may allow one group to control all `ACCOUNTING.*` topics, and another group to control all `PAYROLL.*` queues.

The following table describes the destination-level administration permissions.

Permission	Allows Administrator To...
<code>view</code>	View information for this destination.
<code>create</code>	Create the specified destination. This permission is useful when used with wildcard destination names. This allows the user to create any destination that matches the specified parent.
<code>delete</code>	Delete this destination.
<code>modify</code>	Change the properties for this destination.
<code>purge</code>	Either purge this queue, if the destination is a queue, or purge the durable subscribers, if the destination is a topic with durable subscriptions.

Any type of modification to an item requires that the user can view that item. Therefore, granting `create`, `modify`, `delete`, `change`, or `purge` implicitly grants the permission to view the associated item.

Granting the `view` permissions is useful when you want specific users to only be able to view items. It is not necessary to grant the `view` permission if a user already has a permission that allows the user to modify the item.

Administration permissions for a destination are stored alongside all other permissions for the destination in the `acl.conf` file. For example, if user BOB has `publish` and `subscribe` permissions on topic `foo`, and then BOB is granted `view` permission, the `acl` listing would look like the following:

```
TOPIC=foo USER=BOB PERM=publish,subscribe,view
```

Both user and administrator permissions for a destination are stored in the same entry in the `acl.conf` file. This is for convenience rather than for clarity. User permissions specify the actions a client application can perform on a destination (`publish`, `subscribe`, `send`, `receive`, and so on). Administrator permissions specify what administrative commands the user can perform on the destination when using the administration tool or API.

Protection Permissions

Protection permissions allow you to group users into administrative domains so that administrators can only perform actions within their domain. An administrator can only perform administrative operations on a user that has the same protection permission as the user.

There are four protection permissions (`protect1`, `protect2`, `protect3`, and `protect4`) that allow you to create four groups of administrators. Protection permissions do not apply to the `admin` user or users

in the `$admin` group — these users can perform any action on any user regardless of protection permissions.

To use protection permissions, grant one of the protection permissions to a set of users (either individually, or to a defined group(s)). Then, grant the same protection permission to the administrator that can perform actions on those users.

For example, there are four departments in a company: sales, finance, manufacturing, and system administrators. Each of these departments has a defined group and a set of users assigned to the group. Within the system administrators, there is one manager and three other administrators, each responsible for administering the resources of the other departments. The manager of the system administrators can perform any administrator action. Each of the other system administrators can only perform actions on members of the groups for which they are responsible.

The user name of the manager is `mgr`, the user names of the other system administrators are `admin1`, `admin2`, and `admin3`. The following commands illustrate the grants necessary for creating the example administration structure.

```
add member $admin mgr
grant admin sales protect1
grant admin admin1 protect1,all
grant admin manufacturing protect2
grant admin admin2 protect2,all
grant admin finance protect3
grant admin admin3 protect3,all
```



You can grant a protection permission, in addition to the `all` permission. This signifies that the user has all administrator privileges for anyone who also has the same protection permission. However, if you revoke the `all` permission from a user, all permissions, including any protection permissions are removed from the access control list for the user.

An administrator is able to view users that have a different protection permission set, but the administrator can only perform actions on users with the same protection permission.

For example, `admin1` can perform any action on any user in the `sales` group, and can view any users in the `manufacturing` or `finance` groups. However, `admin1` is not able to grant permissions, change passwords, delete users from, or perform any other administrative action on users of the `manufacturing` or `finance` groups. The `mgr` user is able to perform any action on any user, regardless of their protection permission because `mgr` is a member of the `$admin` group.

Enable Access Control

Administrators can enable or disable access control for the server. Administrators can also enable and disable permission checking for specific destinations.

Server Control

The property in the main configuration file enables or disables the checking of permissions for all destinations managed by the server.

The [authorization](#) property also enables or disables verification of user names and passwords.



The default setting is `disabled`. For secure deployments, the administrator must explicitly set `authorization` to `enabled`.

When `authorization` is disabled, the server grants any connection request, and does not check permissions when a client accesses a destination (for example, publishing a message to a topic).

When `authorization` is enabled, the server grants connections only from valid authenticated users. The server checks permissions for client operations involving secure destinations.

To enable `authorization`, either edit `tibemsd.conf` (set the `authorization` property to `enabled`, and restart the server). Or you can use the `tibemsaadmin` tool to dynamically enable `authorization` with the following [set server](#) command:

```
set server authorization=enabled
```

Authorization does affect connections between fault-tolerant server pairs; see [Authorization and Fault-Tolerant Servers](#).

Administrators must always log in with the correct administration username and password to perform any administrative function—even when authorization is disabled.

Destination Control

When server [authorization](#) is enabled, the server checks user names and password of all connections without exceptions. However, operations on destinations, such as sending a message or receiving a message, are not verified unless the destination has enabled the [secure](#) property on the destination. All operations by applications on the destination with secure enabled are verified by the server according to the permissions listed in `acl.conf`. Destinations with secure disabled continue to operate without any restrictions.



The secure property is independent of SSL-level security. The secure property controls only basic authentication and permission verification. It does not affect the security of communication between clients and server.

When a destination does not have the secure property set, any authenticated user can perform any actions on that topic or queue.


See [Destination Properties](#) for more information about destination properties.

Users and Groups

User permissions apply to the activities a user can perform on each destination (topic and queue). Using permissions you can control which users have permission to send, receive, or browse messages for queues. You can also control who can publish or subscribe to topics, or who can create durable subscriptions to topics. Permissions are stored in the access control list for the server.

Groups allow you to create classes of users and control permissions on a more global level. Rather than granting and revoking permissions on destinations to individual users, you can control destination access at the group level. Users inherit any permissions from each of the groups they belong to, in addition to any permissions that are granted to them directly.

The following figure illustrates the relationships between users, groups and permissions.



Externally-configured users and groups are defined and managed using the external directory. Locally-configured users and groups, as well as the access control list, are configured using any of the administration interfaces (editing configuration files, using the administration tool, or the administration APIs).



Access control and Secure Sockets Layer (SSL) have some similar characteristics. SSL allows for servers to require user authentication by way of the user's digital certificate. SSL does not, however, specify any access control at the destination level. SSL and the access control features described in this chapter can be used together or separately to ensure secure access to your system. See , [SSL Protocol](#), for more information about SSL.

The following sections describe users and groups in EMS.

Users

Users are specific, named IDs that allow you to identify yourself to the server. When a client logs in, the connect request should be accompanied by a username and the password associated with the username.



In special cases, you may wish to allow anonymous access to the server. In this case, a connect request does not have to supply a username or password. To configure the server to allow anonymous logins, you must create a user named `anonymous` and specify no password. Anonymous logins are not permitted unless the `anonymous` user exists.

Clients logging in anonymously are only able to perform the actions that the `anonymous` user has permission to perform.

There is one predefined user, `admin`, that performs administrative tasks, such as creating other users.

You can create and remove users and change passwords by specifying the users in the `users.conf` configuration file, using the `tibemsadmin` tool, or by using the administration APIs. For more information about specifying users in the configuration file, see [users.conf](#). For more information about

specifying users using the `tibemsadmin` tool, see [EMS Administration Tool](#). For more information on the administration APIs, see the online documentation.

Groups

Groups allow you to create classes of users. Groups make access control administration significantly simpler because you can grant and revoke permissions to large numbers of users with a single operation on the group.

Each user can belong to as many groups as necessary. A user's permissions are the union of the permissions of the groups the user belongs to, in addition to any permissions granted to the user directly.

You can create, remove, or add users to groups by specifying the groups in `groups.conf`, using the `tibemsadmin` tool, or by using the administration APIs. For more information about specifying groups in the configuration file, see [groups.conf](#). For more information about specifying groups using the `tibemsadmin` tool, see [EMS Administration Tool](#). For more information on the administration APIs, see the online documentation.

Configure an External Directory

You can define user authentication and group information either in EMS server configuration files, or in an external directory (such as an LDAP server).

External User Authentication

EMS can be configured to authenticate users stored in an external directory server, such as an LDAP server.

The parameter `user_auth` in `tibemsd.conf` guides the EMS server when authenticating users. When a user attempts to authenticate to the EMS server, this parameter specifies the source of authentication information. This parameter can have one or more of the following values (separated by comma characters):

- `local`—obtain user authentication information from the local EMS server user configuration.
- `ldap`—obtain user authentication information from an LDAP directory server (see the LDAP-specific configuration parameters).
- `jaas`—obtain user authentication information from a custom authentication module (see [Extensible Authentication](#)).

Each time a user attempts to authenticate, the server seeks corresponding authentication information from each of the specified locations in the order that this parameter specifies. The EMS server accepts successful authentication using any of the specified sources.

Group Information

Group information stored in an external directory can also be retrieved by the EMS server. Static and dynamic groups are supported and you can configure the EMS server to retrieve either or both.

Administration Commands and External Users and Groups

You can perform administrative commands on users and groups defined either locally (in the EMS server's local configuration files) or in an external LDAP. Furthermore, you can combine users and groups that are defined in different locations (for example, you can grant and revoke permissions for users and groups defined in an LDAP, or add LDAP-defined users to locally-defined groups).



Combining authentication sources requires that the configuration parameter `user_auth` includes both `ldap` and `local`.

When you attempt to view users and groups using the `show user/s` or `show group/s` commands, any users and groups that exist in external directories have an asterisk next to their names. Users and

groups from external directories will only appear in the output of these commands in the following situations:

- an externally-defined user successfully authenticates
- a user belonging to an externally-defined group successfully authenticates
- an externally-defined user has been added to a locally-defined group
- permissions on a topic or queue have been granted to an externally-defined user or group

Therefore, not all users and groups defined in the external directory may appear when the `show user/s` or `show group/s` commands are executed. Only the users and groups that meet the above criteria at the time the command is issued will appear.

You can create users and groups with the same names as externally-defined users and groups. If a user or group exists in the server's configuration and is also defined externally, the local definition of the user takes precedence. Locally-defined users and groups will not have an asterisk by their names in the `show user/s` or `show group/s` commands.

You can also issue the `delete user` or `delete group` command to delete users and groups from the local server's configuration. The permissions assigned to the user or group are also deleted when the user or group is deleted. If you delete a user or group that is defined externally, this deletes the user or group from the server's memory and deletes any permissions assigned in the access control list, but it has no effect on the external directory. The externally-defined user can once again log in, and the user is created in the server's memory and any groups to which the user belongs are also created. However, any permissions for the user or group have been deleted and therefore must be re-granted.

Using LDAP Directory Servers

You should be able to use EMS with external directory servers that are compliant with LDAP v2 or higher.

The description for [tibemsd.conf](#) provides the complete list of configuration parameters for configuring an external directory server. The following table describes parameter settings for default configurations of popular LDAP servers.

External Directory Server	Parameter Configuration
Active Directory	<pre> ldap_principal = CN=Administrator, CN=Users, DC=<your_domain> ldap_user_class = user ldap_user_attribute = cn ldap_user_filter = (&(cn=%s)(objectclass=user)) ldap_group_filter = (&(cn=%s)(objectclass=group)) ldap_static_group_class = group ldap_static_group_attribute = cn ldap_static_member_attribute = member ldap_static_group_member_filter = (&(member=%s) (objectclass=group)) </pre>

External Directory Server	Parameter Configuration
OpenLDAP	<pre> ldap_user_class = person ldap_user_attribute = cn ldap_user_base_dn = ou=people, dc=<your_domain_component>, dc=<your_domain_component> ldap_user_filter = (&(cn=%s)(objectclass=user)) ldap_group_base_dn = ou=groups, dc=<your_domain_component>, dc=<your_domain_component> ldap_group_filter = (&(cn=%s)(objectclass=groupofnames)) ldap_static_group_class = groupofnames ldap_static_group_attribute = cn ldap_static_member_attribute = member ldap_static_group_member_filter = (&(member=%s) (objectclass=groupofnames)) </pre>
Novell	<pre> ldap_user_class = person ldap_user_attribute = cn ldap_user_base_dn = ou=people, o=<your_organization> ldap_user_filter = (&(cn=%s)(objectclass=person)) ldap_group_base_dn = ou=groups, o=<your_organization> ldap_group_filter = (&(cn=%s)(objectclass=groupofnames)) ldap_static_group_class = grouponames ldap_static_group_attribute = cn ldap_static_member_attribute = uniquemember ldap_static_group_member_filter = (&(uniquemember=%s) (objectclass=groupofnames)) </pre>

User Permissions

User permissions are stored in the access control list and determine the actions a user can perform on a destination. A user's permissions are the union of the permissions granted explicitly to that user along with any permissions the user receives by belonging to a group.

When granting user permissions, you specify the user or group to whom you wish to grant the permission, the name of the destination, and the permission(s) to grant. Granting permissions is an action that is independent from both the [authorization](#) server parameter, and the [secure](#) property of the relevant destinations. The currently granted permissions are stored in the access control file, however, the server enforces them only if the authorization is enabled, and only for secure destinations.



When setting permissions for users and groups defined externally, user and group names are case-sensitive. Make sure you use the correct case for the name when setting the permissions.

User permissions can only be granted by an administrator with the appropriate permissions described in [Administrator Permissions](#).

You assign permissions either by specifying them in the [acl.conf](#) file, using the `tibemsadmin` tool, or by using the administration APIs. When setting user permissions, you can specify either explicit destination names or wildcard destination names. See [Inheritance of User Permissions](#) for more information on wildcard destination names and permissions.

Queue and Topic Permissions

The permissions that can be granted to users to access queues and topics are listed in the following tables.

Queue Permission

Name	Description
receive	permission to create queue receivers
send	permission to create queue senders
browse	permission to create queue browsers

Topic Permission

Name	Description
subscribe	permission to create non-durable subscribers on the topic
publish	permission to publish on the topic
durable	permission to create, delete, or modify durable subscribers on the topic
use_durable	permission to use an existing durable subscriber on the topic, but <i>not</i> to create, delete, or modify the durable subscriber

Example of Setting User Permissions

The user bob has the following permission recorded in the `acl.conf` file:

```
USER=bob TOPIC=foo PERM=subscribe,publish
```

This set of permissions means that bob can subscribe to topic `foo` and publish messages to it, but bob cannot create durable subscribers to `foo`.

If bob is a member of group `engineering` and the group has the following entry in the `acl` file:

```
GROUP=engineering TOPIC=bar PERM=subscribe,publish
```

then bob can publish and subscribe to topics `foo` and `bar`.

If both the user `bob` and the group `engineering` have entries in the [acl.conf](#) file, then bob has permissions that are a union of all permissions set for bob directly and the permissions of the group `engineering`.

Inheritance of User Permissions

When you grant permissions to users for topics or queues with wildcard specifications, all created topics and queues that match the specification will have the same granted permissions as the permissions on the parent topic.

If there are multiple parent topics, the user receives the union of all parent topic permissions for any child topic. You can add permissions to a user for topics or queues that match a wildcard specification, but you cannot remove permissions.

For example, you can grant user Bob the browse permission on queue `foo.*`. The user Bob receives the browse permission on the `foo.bar` queue, and you can also grant Bob the send permission on the `foo.bar` queue. However, you cannot take away the inherited browse permission from Bob on the `foo.bar` queue.

See [Wildcards](#) for more information about wildcards in destination names.

Revoking User Permissions

Administrators can revoke permissions for users to create consumers on a destination. Without permission, the user cannot create new consumers for a destination—however, existing consumers of the destination continue to receive messages.

You can only revoke a permission that is granted directly. That is, you cannot revoke a permission from a user that the user receives from a group. Also, you cannot revoke a permission that is inherited from a parent topic. The `revoke` command in `tibemsadmin` can only remove items from specific entries in the `acl.conf` file. The `revoke` command cannot remove items that are inherited from other entries.

You can revoke permissions in several ways:

- Remove or edit entries in the `acl.conf` file.
- Use the `revoke` commands in `tibemsadmin`.
- Use the administration APIs.

When Permissions Are Checked

If permissions are enforced (that is, the `authorization` configuration property is set, and the `secure` property is set for the destination), the server checks them when a user attempts to perform an operation on a destination. For example, create a subscription to a topic, send a message to a queue, and so on. Since permissions can be granted or revoked dynamically, the server checks them each time an operation is performed on a destination (and each time a consumer or producer is created).

For specific (non-wildcard) destination names, permissions are checked when a user performs one of the following actions:

- creates a subscription to a topic
- attempts to become a consumer for a queue
- publishes or sends a message to a topic or queue
- attempts to create queue browser

A user cannot create or send a message to a destination for which he or she has not explicitly been granted the appropriate permission. So, before creating or sending messages to the destination, a user must be granted permissions on the destination.

However, for wildcard topic names (queue consumers cannot specify wildcards), permissions are not checked when users create non-durable subscriptions. Therefore, a user can create a subscription to topic `foo.*` without having explicit permission to create subscriptions to `foo.*` or any child topics. This allows administrators to grant users the desired permissions after the user's application creates the subscriptions. You may wish to allow users to subscribe to unspecific wildcard topics, then grant permission to specific topics at a later time. Users are not able to receive messages based on their wildcard subscriptions until permissions for the wildcard topic or one or more child topics are granted.

Attempts to perform an operation by a user who does not have the permission to perform it are traced in the server log file.



When creating a durable subscriber, users must have the `durable` permission explicitly set for the topic they are subscribing to. For example, to create a durable subscriber to topic `foo.*`, the user must have been granted the durable permission to create durable subscriptions for topic `foo.*`. To subscribe an existing durable subscriber to a topic, you must have either `durable` or `use_durable` permission set on that topic.

Example of Permission Checking

This example walks through a scenario for granting and revoking permissions to a user, and describes what happens as various operations are performed.

1. User bob is working with a EMS application that subscribes to topics and displays any messages sent to those topics.
2. User bob creates a subscription to `user.*`. This topic is the parent topic of each user. Messages are periodically sent to each user (for example, messages are sent to the topic `user.bob`). Because the same application is used by many users, the application creates a subscription to the parent topic.
3. User bob creates a subscription to topic `corp.news`. This operation fails because bob has not been granted access to that topic yet.
4. A message is sent to the topic `user.bob`, but the application does not receive the message because bob has not been granted access to the topic yet.
5. The administrator, as part of the daily maintenance for the application, grants access to topics for new users. The administrator grants the `subscribe` permission to topic `user.bob` and `corp.*` to user bob. These grants occur dynamically, and user bob is now able to receive messages sent to topic `user.bob` and can subscribe to topic `corp.news`.
6. The administrator sends a message on the topic `user.bob` to notify bob that access has been granted to all `corp.*` topics.
7. The application receives the new message on topic `user.bob` and displays the message.
8. User bob attempts to create a subscription for topic `corp.news` and succeeds.
9. A message is sent to topic `corp.news`. User bob's application receives this message and displays it.
10. The administrator notices that bob is a contractor and not an employee, so the administrator revokes the `subscribe` permission on topic `corp.*` to user bob.

The subscription to `corp.news` still exists for user bob's application, but bob cannot create any new subscriptions to children of the `corp.*` topic.

Extensible Security

The following sections outline how to develop and implement custom authentication and permissions modules.

Overview of Extensible Security

The extensible security feature allows you to use your own authentication and permissions systems, in addition to the prebuilt JAAS modules and default LDAP server included in EMS, to authenticate users and authorize them to perform actions such as publish and subscribe operations. Developing custom applications to grant authentication and permissions gives you more flexibility in architecting your system.


How Extensible Security Works

Extensible security works by allowing you to write your own authentication and permissions modules, which run in a Java virtual machine (JVM) in the EMS server. The modules connect to the server using the Java Authentication and Authorization Service (JAAS) for authentication modules, and the Java Access Control Interface (JACI) for permissions modules.

If the extensible security features are enabled when the EMS server starts, the server checks each user as it connects for authentication, and checks user permissions when they attempt to perform actions that require authorization.

Permission results are cached in the server for specified timeouts, and the permissions module is re-invoked when a cached permission expires. The server then replaces the old permission data with new data.

Extensible authentication and extensible permissions are enabled in the `tibemsd.conf` configuration file. Extensible security modules can connect to external security services, such as single sign on (SSO) servers or LDAP directories, which operate outside of the TIBCO Enterprise Message Service framework. Extensible security modules can work in tandem with other authorization and permissions methods, such as LDAP or the EMS `ac1.conf` configuration file. The following figure shows the different security methods available in the server.



Extensible Authentication

The extensible authentication feature uses the Java virtual machine (JVM) and the Java Authentication and Authorization Service (JAAS) to allow you to run your own Java-based authentication module in the EMS server.

Your authentication module, or LoginModule, runs in the JVM within the EMS server, and is accessed by `tibemsd` using the JAAS interface. This is a flexible way to extend the security of your EMS application. The LoginModule can be used to augment existing authentication processes, or can be the sole method of authentication used by the EMS server. The `user_auth` parameter in the main configuration file determines when the LoginModule is used.

Each time an EMS client attempts to create a connection to the server, the server will authenticate the client before accepting the connection. When extensible authentication is enabled, `tibemsd` passes user information to the LoginModule, which returns an allow or deny response.

If more than one authentication mechanism is enabled, it's important to note the order that the authentication processes are employed, as determined by their order in the `user_auth` parameter. The server will search each authentication source in order, and if the user does not exist there, `tibemsd` passes the username and password to the next source.

For example, if local authentication appears before JAAS authentication, the server will search for the provided username and password first in the `users.conf` file. If the user does not exist there, `tibemsd` passes the username and password to the LoginModule, which allows or denies the connection attempt.

Consider a connection request from a client with the username `avogus`. If `avogus` exists in the `users.conf`, the EMS server will either authenticate or deny access to `avogus` based on the username and password located there. Only if `avogus` does not exist in the `users.conf` does the server pass the username and password to the LoginModule.

Enable Extensible Authentication

Extensible authentication is enabled in the EMS server, through parameters in the `tibemsd.conf` configuration file. The required parameters are:

- `authorization`—directs the server to verify user credentials and permissions on secure destinations.
- `user_auth`—directs the EMS server to use the LoginModule for authentication.
- `security_classpath`—specifies the JAR files and dependent classes used by the LoginModule.
- `jaas_config_file`—specifies the configuration file, usually `jaas.conf`, that loads the LoginModule. For more information, see the [Example jaas.conf Configuration File](#).

Because the LoginModule runs in the Java virtual machine, you must also enable the JVM in the EMS server. See [Enable the JVM](#) for more information.

Prebuilt Authentication Modules

TIBCO Enterprise Message Service includes several supported JAAS authentication modules that offer flexible authentication for the EMS server. The source files of the prebuilt modules are provided in `EMS_HOME/src/java/jaas`, and provide an excellent template for developing custom modules. Multiple instances of any prebuilt JAAS module can be used in any stacked combination to suit the authentication requirements of your environment.

These modules are described in [JAAS Authentication Modules](#).

Writing an Authentication Module

The LoginModule is a custom module that runs inside the EMS server within a JVM. The LoginModule is written using JAAS, a set of APIs provided by Sun Microsystems, and used to create plugable Java

applications. JAAS provides the interface between your code and the EMS server. JAAS is a standard part of JRE, and is installed with EMS.

LoginModule Requirements

In order to implement extensible authentication, you must write a LoginModule implementing the JAAS interface.

There are some requirements for a LoginModule that will run in the EMS server:

- The LoginModule must accept the username and password from the EMS server by way of the `NameCallback` and `PasswordCallback` callbacks. The EMS server passes the username and password to the LoginModule using these callbacks, ignoring the prompt argument.
- If the username and password combination is invalid, the LoginModule must throw a `FailedLoginException`. The EMS server then rejects the corresponding connection attempt.
- The LoginModule must be thread-safe. That is, the LoginModule must be able to function both in a multi-threaded environment and in a single-threaded environment.
- The LoginModule should perform authentication only, by determining whether a username and password combination is valid. For information about custom permissions, see [Extensible Permissions](#).
- The LoginModule, like the Permissions Module, should not perform long operations, and should return values quickly. As these modules become part of the EMS server's message handling process, slow operations can have a severe effect on performance.
- The LoginModule must be named `EMSUserAuthentication`.

More information about JAAS, including documentation of JAAS classes and interfaces, is available through <http://java.sun.com/products/jaas/>.

Load the LoginModule in the EMS Server

The EMS server locates and loads the LoginModule based on the contents of the configuration file specified by the `jaas_config_file` parameter in the `tibemsd.conf` file. Usually, the JAAS configuration file is named `jaas.conf`. This file contains the configuration information used to invoke the LoginModule.

The contents of the `jaas.conf` file should follow the JAAS configuration syntax, as documented at: <http://docs.oracle.com/javase/8/docs/api/javax/security/auth/login/Configuration.html>



The LoginModule in the JAAS configuration file must have the name `EMSUserAuthentication`.

Example jaas.conf Configuration File

```
EMSUserAuthentication {
com.tibco.tibems.tibemsd.security.example.FlatFileUserAuthLoginModule required
debug=true filename=jaas_users.txt;
};
```

Extensible Permissions

The extensible permissions feature uses the Java virtual machine (JVM) and the Java Access Control Interface (JACI) to allow you to run your own Java-based permissions module in the EMS server.

Your Permissions Module runs in the JVM within the EMS server, and connects to `tibemsd` using the JACI interface. Like the LoginModule, the Permissions Module provides an extra layer of security to your EMS application. It does not supersede standard EMS procedures for granting permissions. Instead, the module augments the existing process.

When a user attempts to perform an action, such as subscribing to a topic or publishing a message, the EMS server checks the `acl.conf` file, the Permissions Module, and cached results from previous

Permissions Module queries, for authorization. This process is described in detail in [Granting Permissions](#).

Cached Permissions

In order to speed the authorization process, the EMS server caches responses received from the Permissions Module in two pools, the *allow cache* and the *deny cache*. Before invoking the Permissions Module, the server first checks these caches for a cache entry matching the user's request.

What is Cached

Each cache entry consists of a username and action, and the authorization result response from the Permissions Module.

Properties of cache entries:

- The username is specific; the cached permission applies only to this user.
- The action is also specific. Only one action is included in each cache entry. Actions that require authorization are the same as those listed in the [acl.conf](#) file.
- The destination can include wildcards. That is, a single cache entry can determine the user's authorization to perform the action on multiple destinations.

If the response from the Permissions Module authorized the action, the permission is cached in the allow cache. If the action was denied, it is cached in the deny cache.

How Long Permissions are Cached

Permissions Module results also include timeouts, which determine how long the cache entry is kept in the cache before it expires.

When a timeout has expired, the entry is removed from the cache. Because these timeouts are assigned by the Permissions Module, you can control how often the Permissions Module is called, and therefore how much load it puts on the EMS server.



Long timeouts on permissions cache entries can increase performance, but they also lower the system's responsiveness to changes in permissions. Consider timeout lengths carefully when writing your Permissions Module.

Administer the Cache

You can view and reset cache statistics, as well as clear all cache entries.

These commands are available in the administration tool:

- `jaci showstats`
- `jaci resetstats`
- `jaci clear`

How Permissions are Granted

When an EMS client attempts to perform an action that requires permissions, the EMS server looks in several locations for authorization.

1. First, the server checks the `acl.conf` for authorization. This is the standard EMS mechanism for granting permissions, as is documented in [Authentication and Permissions](#).
2. Next, the server checks the Permissions Module allow cache for authorization. If an entry matching the username, action, and destination exists in the cache, the request is allowed.

Because destinations with wildcards can exist in the cache, an entry can have a wildcard destination that contains the requested destination. If that entry specifies the same username and action, the

request is allowed. For more information on this topic, see [Implications of Wildcards on Permissions](#) below.


3. The server then checks the deny cache for a matching entry. If an entry exists in the deny cache, the request is denied.

As in the allow cache, wildcards used in destinations can result in a cache entry with a destination that contains the requested destination. If that entry matches the username and action, the request is denied. For more information on this topic, see [Implications of Wildcards on Permissions](#) below.

4. Finally, if there are no matching entries in either cache, the server passes the username, action type, and destination to the Permissions Module, which returns an allow or deny authorization response. The response is also saved to the cache for the timeout specified in the response.

If the Permissions Module does not respond to the request within the timeout specified by the `jaci_timeout` parameter in the `tibemsd.conf` file, the server denies authorization by default.

Actions that require permissions are the same as those listed in the `acl.conf` file, and include operations such as subscribe to a topic and publishing to a queue. Permissions are described in `acl.conf`. The following figure shows the decision tree the server follows when granting or denying permissions.



In general, permissions are checked when a client initiates an operation. In the case of a browsing request, it's useful to note that the server reviews permissions only at certain points during the browsing operation.



The server checks for browsing permission when a client starts to browse a queue and whenever the client needs to refresh its list of browse-able messages. The client receives the list of messages from the server when it first begins browsing. The server refreshes the list and rechecks permissions whenever the client browses to the end of the current list.

Durable Subscribers

When a durable subscriber is disconnected from the EMS server, the server continues to accumulate messages for the client. However, while the client is disconnected, there is no user associated with the

durable subscriber. Because of this, the server cannot immediately check permissions for a message that is received when the client is not connected.

When a user later reconnects to the server and resubscribes to the durable subscription, the server checks permissions for the subscribe operation itself, but all messages in the backlog are delivered to the consumer without additional permission checks.

Special Circumstances

There are some special circumstances under which the request, although it is not exactly matched in the `acl.conf` file, will be denied without reference to either the permissions cache or the Permissions Module. Any request will be denied if, in the `acl.conf`

- The username exists but is not associated with any destinations.
- The username exists and is associated with destinations, but not with the specific destination in the request.
- The username is part of a group, but the group is not associated with any destinations.
- The username is part of a group and the group is associated with destinations, but not with the specific destination in the request.

In general entries in the `acl.conf` file supersede entries in the Permissions Module, allowing you to optimize permission checks in well-defined static cases. When the `acl.conf` does not mention the user, the Permissions Module is fully responsible for permissions.

Implications of Wildcards on Permissions

A permission result from the Permissions Module can allow or deny the user authorization to perform the action on a range of destinations by including wildcards in the destination name.

For example, even though the application attempts to have user `mwalt on` publish on topic `foo.bar.1`, the Permissions Module can grant permission to user `mwalt on` to publish messages to the topic `foo.bar.*`. For as long as this authorization is cached, `mwalt on` can also publish to the topics `foo.bar.baz` and `foo.bar.boom`, because `foo.bar.*` contains both those topics.

As long as a permission to perform an action on a destination is cached in the allow cache, the user will be authorized to perform that action, even if the permission is revoked in the external system used by the Permissions Module. This permission also extends to any destination contained by the authorized destination through the use of wildcards. The EMS server checks the allow cache for permissions before checking the deny cache and before sending an uncached permission request to the Permissions Module. In other words, the authorization status cannot be changed until the timeout on the cache entry expires and it is removed from the cache.

Similarly, an entry in the deny cache remains there until the timeout has expired and the entry is removed. Only then does the EMS server send the request to the Permissions Module, so that a change in status can take effect.

Overlapping wildcards can make this situation even more complex. For example, consider these three destinations:

```
foo.*.baz
foo.bar.*
foo.>
```

It might seem that, if `foo.*.baz` were in a cache, then `foo.bar.*` would match it and permissions for that destination would come from the cache. In fact, however, permissions could not be determined by the cache entry, because `foo.bar.*` intersects but is not a subset of `foo.*.baz`. That is, not every destination that matches `foo.bar.*` will also match `foo.*.baz`. The destination `foo.bar.boom`, for example, would be granted permissions by `foo.bar.*`, but not by `foo.*.baz`.

Since not all destinations that `foo.bar.*` matches will also match `foo.*.baz`, we say that `foo.*.baz` intersects `foo.bar.*`. The cache entry can determine a permission if the requested destination is a subset of the cache entry, but not if it is merely an intersection. In this case, permissions cannot be determined by the cache.

The destination `foo.>`, on the other hand, contains as subsets both `foo.bar.*` and `foo.*.baz`, because any destination name that matches either `foo.bar.*` or `foo.*.baz` will also match `foo.>`. If `foo.>` is in the cache, permissions will be determined by the cache.

Enable Extensible Permissions

Extensible permissions are enabled in the EMS server, through parameters in the `tibemsd.conf` configuration file.

The required parameters are:

- `authorization`—enables authorization.
- `jaci_class`—specifies the class that implements the Permissions Module.
- `security_classpath`—specifies the JAR files and dependent classes used by the Permissions Module.

The Permissions Module will be used to grant permissions only to those destinations that are defined as secure in the `topics.conf` and `queues.conf` configuration files. If there are no topics or queues that include the `secure` property, then the Permissions Module will never be called because the server does not check permissions at all.

Because the Permissions Module runs in the Java virtual machine, you must also enable the JVM in the EMS server. See [Enable the JVM](#) for more information.

Permissions Module

The Permissions Module is a custom module that runs inside the EMS server within a JVM. The Permissions Module is written using JACI, a set of APIs developed by TIBCO Software Inc. that you can use to create a Java module that will authorize EMS client requests.

JACI provides the interface between your code and the EMS server. JACI is a standard component of EMS, and JACI classes and interfaces are documented in `com.tibco.tibems.tibemsd.security`.

Requirements

In order to implement extensible permissions, you must write a Permissions Module implementing the JACI interface.

There are some requirements for a Permissions Module that will run in the EMS server:

- The Permissions Module must implement the JACI Authorizer interface, which accepts information about the operation to be authorized.
- The Permissions Module must return a permission result, by way of the `AuthorizationResult` class. Permission results contain:
 - An `allowed` parameter, where `true` means that the request is allowed and `false` means the request is denied.
 - A `timeout`, which determines how long the permission result will be cached. Results can be cached for a time of up to 24 hours, or not at all.
 - The destination on which the user is authorized to perform the action. The destination returned can be more inclusive than the request. For example, if the user requested to subscribe to the topic `foo.bar`, the permission result can allow the user to subscribe to `foo.*`. If a destination is not included in the permission result, then the allow or deny response is limited to the originally requested destination.
 - The action type that the permission result replies to. For example, authorization to publish to the destination, or authorization to receive messages from a queue. Permissions can be granted to multiple action types, for example permission to publish and subscribe on `foo.>`. Note that the EMS server creates one cache entry for each action specified in the result.

- The Permissions Module must be thread-safe. That is, the Permissions Module must be able to function both in a multi-threaded environment and in a single-threaded environment.
- The Permissions Module, like the LoginModule, should not employ long operations, and should return values quickly. As these modules become part of the EMS server's message handling process, slow operations can have a severe effect on performance.

Documentation of JACI classes and interfaces is available through [com.tibco.tibems.tibemspd.security](#).

The JVM in the EMS Server

The Java virtual machine (JVM) is a virtual machine on the Java platform, capable of running inside the EMS server.

Select independent Java modules can operate in the JVM and plug into the EMS server. The JVM is required to use the following TIBCO Enterprise Message Service features:

- Extensible Security—see [Extensible Security](#).
- JAAS Authentication Modules —see [JAAS Authentication Modules](#).
- Database Stores—see [Database Stores](#).

Enable the JVM

The Java virtual machine is enabled in the EMS server, through parameters in the `tibemspd.conf` configuration file.

The parameters that enable and configure the JVM are:

- `jre_library`—enables the JVM.
- `jre_option`—allows you to pass standard JVM options, defined by Sun Microsystems, to the JVM at start-up.

For more information about these parameters, see [JVM Parameters](#) and `tibemspd.conf`.

JAAS Authentication Modules

TIBCO provides several compiled and fully functional JAAS modules that can be used to enable LDAP and host-based authentication in the EMS server.

Overview of the JAAS Authentication Modules

The JAAS Authentication modules are LoginModules that use the JVM in the EMS server to authenticate connections to the EMS server.

Refer to [Extensible Authentication](#) for further information the use of JAAS in TIBCO Enterprise Message Service.

Prebuilt JAAS Modules

TIBCO Enterprise Message Service provides a number of JAAS modules that can be used with the EMS server. These default modules are very flexible, and offer a variety of configuration options to suit most needs.

An EMS server file, `tibemsd-jaas.conf`, that is preconfigured to use the prebuilt JAAS modules, is located with the other sample configuration files in the `EMS_HOME/samples/config` directory.

The module classes are found in `EMS_HOME/bin/tibemsd_jaas.jar`, and example module configuration files can be found in `EMS_HOME/samples/config/jaas` directory.

The default modules are:

- [LDAP Simple Authentication](#) — a simple user authentication scheme using LDAP. This module requires the fewest parameters and is easiest to configure.
- [LDAP Authentication](#) — a full featured user authentication scheme using LDAP. This module provides greater functionality and better performance than the LDAP Simple Authentication module.
- [LDAP Group User Authentication](#) — a full featured user authentication scheme using LDAP. An extension of LDAP Authentication, this module also retrieves LDAP group membership information and passes it back into the EMS server, where it may be used for authorization. This modules provides the most functionality but generates more requests to the LDAP server.
- [Host Based Authentication](#) — authentication based on the hostname or IP of a user connection. The module is most often used in conjunction with other modules, or in situations where only specific network nodes may authenticate to the EMS server.

Custom JAAS Modules

The default JAAS modules included with your TIBCO Enterprise Message Service installation will accommodate most environments. However, sometimes specialized support for authentication is required.

To support this, well-documented source-code is provided for all of the EMS JAAS modules in the directory:

```
EMS_HOME/src/java/jaas
```

The `readme.txt` file in that directory contains instructions on compiling the source files.

Multiple JAAS Modules

The prebuilt JAAS modules support stacking, which provides great flexibility. Using multiple modules, you can direct the EMS server to check authentication using any arrangement of the modules.

A common example would stack the LDAP Authentication module with the Host Based Authentication module to authenticate a user by credentials and IP address. Another example would include stacking multiple LDAP Authentication modules to search different branches of an LDAP tree.

There are no restrictions on which or how many modules can be stacked.

For examples of stacking, see [Using Multiple JAAS Modules](#).

Authenticate Administrative Connections

Administrative connections, such as those created by the EMS Administration Tool and the EMS administrative API, are authorized differently than client connections.

When establishing an administrative connection, local authentication is always attempted before JAAS authentication. If the local authentication attempt fails, JAAS authentication proceeds.

It is recommended that users making administrative connections to the EMS server are *not* defined in both the EMS server's user configuration file and externally through JAAS. Administrative users should only be defined in one place.

An exception is the default administrative user, `admin`, which is always defined locally by the EMS server. If the default administrative user is to be defined elsewhere and authenticated through JAAS, one can set an undisclosed password for the default administrative user in the EMS server's user configuration file (`users.conf`) so that local authentication of the `admin` user never succeeds, thus allowing JAAS to handle authentication.

Enabling Authentication Using JAAS Modules

The JAAS modules are designed to be simple to use.

A default EMS server configuration file, `tibemsd-jaas.conf`, is located with the other sample configuration files in the `EMS_HOME/samples/config` directory.

This file provides a default JAAS configuration that includes the security-related parameters required to use any of the TIBCO EMS JAAS modules. However, some additional steps are required to complete the configuration.

Procedure

1. Configure the JAAS Module

Create a JAAS module configuration file with parameter values appropriate to your environment.

If you are using one of the provided default modules, locate the configuration file for the desired module in the `EMS_HOME/samples/config/jaas` directory, and configure the module parameters for your environment. It is a good practice to copy this file along side your other EMS configuration files.

The prebuilt JAAS modules and their parameters are described in [Prebuilt JAAS Modules](#).

2. Configure the EMS Server Parameters

The default `EMS_HOME/samples/config/tibemsd-jaas.conf` file is configured for JAAS. This file can be copied as `tibemsd.conf`, or the server can be started with the `-config` parameter to specify this file. See [Starting the EMS Server Using Options](#) for details.

If you prefer to manually configure JAAS, then take the following steps to modify the main EMS server configuration file, `tibemsd.conf`:

- a) Set the `jre_library` parameter to enable the JVM. For more information, see [The JVM in the EMS Server](#).
- b) Set the `security_classpath` parameter to include the following JAR files:

```
EMS_HOME/bin/tibemsd_jaas.jar
EMS_HOME/lib/tibjmsadmin.jar
EMS_HOME/lib/tibjms.jar
EMS_HOME/lib/jms-2.0.jar
```

For example:

```
security_classpath = c:\tibco\ems\8.5\bin\tibemsd_jaas.jar;c:\tibco\ems\8.5\lib\tibjmsadmin.jar;c:\tibco\ems\8.5\lib\tibjms.jar;c:\tibco\ems\8.5\lib\jms-2.0.jar
```

- c) Set the `jaas_config_file` to reference the JAAS module configuration file created in [Step 1](#).

For example:

```
jaas_config_file = jaas_configuration.txt
```

- d) Set the `user_auth` parameter to enable JAAS for LDAP authentication. The parameter should specify `jaas`, and should not include `ldap`.

For example:

```
user_auth=jaas
```

Prebuilt JAAS Modules

This section provides detailed descriptions of the prebuilt JAAS modules.

Configuration files for these modules are provided in the `EMS_HOME/samples/config/jaas` directory.

For the LDAP modules, properties added in the JAAS configuration file that do not begin with `tibems` are passed into every LDAP context creation, allowing LDAP-specific parameters to be set in the JAAS configuration file.

Properties that must be set in the environment, such as SSL related properties, are configured through the `jre_option` parameter in the EMS server configuration. However, an SSL key store location can be set using the `tibems.ldap.truststore` parameter for convenience. See the parameter descriptions for each module type for details.

LDAP Simple Authentication

The LDAP Simple Authentication module implements a very basic form of LDAP authentication. The module validates all connections (users, routes, and so on) by authenticating to the LDAP server. The authentication process uses the name and password that the application used when connecting to the EMS server.

The user name must be in the form of a distinguished name, unless a user name pattern is supplied through the `tibems.ldap.user_pattern` parameter. When a user pattern is supplied, the DN used for the lookup is that pattern string, with `%u` replaced with the name of the user.

Authentication Process

The simple authentication login module creates a local LDAP context, binding to the LDAP server as a particular user with credentials from the incoming connection. The result of the bind dictates authentication success or failure.

Implementation

The LDAP Simple Authentication module name is:

```
com.tibco.tibems.tibemsd.security.jaas.LDAPSimpleAuthentication
```

The JAAS configuration file entry for this login module should have a section similar to the following:

```
EMSSUserAuthentication {
    com.tibco.tibems.tibemsd.security.jaas.LDAPSimpleAuthentication required
    tibems.ldap.url="ldap://ldapserver:389"
    tibems.ldap.user_pattern="CN=%u" ;
};
```

Parameters

The LDAP Simple Authentication Module parameters are listed in the following table.

Parameter	Description
<code>debug</code>	<p>When set to <code>true</code>, enables debug output for the module. Enabling this parameter may aid in diagnosing configuration problems.</p> <p>Warning: Enabling the debug flag may create security vulnerabilities by revealing information in the log file.</p> <p>The default setting is <code>false</code>.</p>
<code>tibems.ldap.operation_timeout</code>	<p>The timeout, in milliseconds, set for LDAP connect and LDAP read operations.</p> <p>If not set, these two LDAP operations will follow their default behavior.</p>
<code>tibems.ldap.truststore</code>	<p>The key store that is used for SSL connections.</p> <p>On Windows, the trust store must use forward slashes or escape backslashes when specifying a path.</p>
<code>tibems.ldap.url</code>	<p>The location of the LDAP server. Specify a single URL or comma-separated list of URLs. Each URL must use the format described by RFC 2255.</p> <p>The server configuration can be defined as a single URL, or as a series of LDAP URLs representing the primary and backups servers. To configure a backup, provide a comma-separated list of URLs. For example:</p> <pre>ldap://localhost:389,ldap://localhost:489</pre> <p>The servers are attempted in the order listed. Should the first server in the list be unavailable or fail, the next URL is tried. Any number of backup servers may be specified.</p> <p>The default is <code>ldap://localhost:389</code>.</p>
<code>tibems.ldap.user_pattern</code>	<p>The user pattern to use with simple LDAP authentication.</p> <p>When a user pattern is supplied, the DN used for the lookup will be this pattern string entered here, with <code>'%u'</code> replaced with the name of the user. For example, <code>uid=%u;ou=People</code>.</p> <p>The default pattern is <code>CN=%u</code>.</p>

LDAP Authentication

The LDAP Authentication login module is a more fully featured LDAP authentication module. This module validates all connections (users, routes, and so on) by authenticating to the LDAP server using the supplied credentials.

This EMS JAAS module keeps one lookup context open using a manager context, and then uses copies of that context to search for users. This allows the LDAP implementation to reuse the connection for subsequent searches, improving performance.

Authentication Process

This implementation queries LDAP, and optionally a user cache, to authenticate a user. A context with LDAP manager credentials is first used to look up a user and retrieve the complete distinguished name of the user's entry. If the user exists, a separate LDAP context is then created to authenticate the user. For performance reasons, the manager context, once created, exists for the lifetime of the module.

Should connectivity with the LDAP server break, multiple reconnection attempts may be made based on the parameters.

To increase performance, you can enable user caching. When enabled, a user is added to the user cache after being authenticated through LDAP. This allows for faster authentication on subsequent logins. If the user cache entry is found to be expired, the user is authenticated with LDAP again and the cache is updated.

Implementation

The LDAP Authentication module name is:

```
com.tibco.tibems.tibemsd.security.jaas.LDAPAuthentication.
```

The JAAS configuration file entry for this login module should have a section similar to the following:

```
EMSSUserAuthentication {
    com.tibco.tibems.tibemsd.security.jaas.LDAPAuthentication required
    tibems.ldap.url="ldaps://ldapserver:391"
    tibems.ldap.truststore="/certificates/cacerts"
    tibems.ldap.user_base_dn="ou=Marketing,dc=company,dc=com"
    tibems.ldap.user_attribute="uid"
    tibems.ldap.scope="subtree"
    tibems.cache.enabled=true
    tibems.cache.user_ttl=600
    tibems.ldap.manager="CN=Manager"
    tibems.ldap.manager_password="password" ;
};
```

Parameters

The LDAP Authentication Module parameters are listed in the following table.

Parameter	Description
debug	<p>When set to true, enables debug output for the module. Enabling this parameter may aid in diagnosing configuration problems.</p> <p>Warning: Enabling the debug flag may create security vulnerabilities by revealing information in the log file.</p> <p>The default setting is false.</p>

Parameter	Description
<code>tibems.ldap.operation_timeout</code>	<p>The timeout set for LDAP connect and LDAP read operations. The property is specified in milliseconds.</p> <p>If not set, these two LDAP operations will follow their default behavior.</p>
<code>tibems.ldap.truststore</code>	<p>The key store that is used for SSL connections.</p> <p>On Windows, the trust store must use forward slashes or escape backslashes when specifying a path.</p>
<code>tibems.ldap.url</code>	<p>The location of the LDAP server. Specify a single URL or comma-separated list of URLs. Each URL must use the format described by RFC 2255.</p> <p>The server configuration can be defined as a single URL, or as a series of LDAP URLs representing the primary and backups servers. To configure a backup, provide a comma-separated list of URLs. For example:</p> <p><code>ldap://localhost:389,ldap://localhost:489</code></p> <p>The servers are attempted in the order listed. Should the first server in the list be unavailable or fail, the next URL is tried. Any number of backup servers may be specified.</p> <p>The default is <code>ldap://localhost:389</code>.</p>
<code>tibems.ldap.user_base_dn</code>	<p>The base DN used for the LDAP search. For example:</p> <p><code>ou=People,dc=TIBCO,dc=com</code></p>
<code>tibems.cache.enabled</code>	<p>When true, enables caching of user information for better performance.</p> <p>The default is false.</p>
<code>tibems.cache.instance</code>	<p>A string that represents an instance of the user cache. When stacked login modules specify the same instance, they share the same user cache as a form of optimization.</p> <p>The default is a unique cache based on the values of the <code>tibems.ldap.url</code>, <code>tibems.ldap.user_base_dn</code>, and <code>tibems.ldap.user_attribute</code> parameters.</p>

Parameter	Description
<code>tibems.cache.user_ttl</code>	<p>Specifies the maximum time (in seconds) that cached LDAP data is retained before it is refreshed.</p> <p>The default is 60.</p>
<code>tibems.ldap.user_filter</code>	<p>The filter used when searching for a user.</p> <p>If a more complex filter is needed, use this property to override the default. Any occurrence of {0} in the search string will be the user attribute, and {1} will be replaced with the user name.</p> <p>The default is {0}={1}.</p>
<code>tibems.ldap.manager</code>	<p>The distinguished name of the user that this module uses when binding to the LDAP server to perform a search.</p> <p>The specified user must have permissions to search LDAP for users under the entry specified by <code>tibems.ldap.user_base_dn</code>.</p> <p>The default is CN=Manager.</p>
<code>tibems.ldap.manager_password</code>	<p>The password used when binding to the LDAP server as the manager. This password may be mangled using the EMS Administration Tool.</p>
<code>tibems.ldap.retries</code>	<p>The number of times that the module should reattempt a connection if there is a communication failure with the LDAP server.</p> <p>If one or more backup servers are specified in <code>tibems.ldap.url</code>, this parameter determines the number of times the EMS server iterates through the list of backup LDAP servers.</p> <p>The default value is 0, meaning no retries are attempted.</p>
<code>tibems.ldap.retry_delay</code>	<p>The module waits this number of milliseconds before retrying the connection to the LDAP server.</p> <p>The default is 1000.</p>
<code>tibems.ldap.scope</code>	<p>The scope of the search. Valid values include:</p> <ul style="list-style-type: none"> • <code>onelevel</code> • <code>subtree</code> • <code>object</code> <p>The default is to use a one level search.</p>

Parameter	Description
<code>tibems.ldap.user_attribute</code>	The attribute that is compared to the user name for the search. The default is <code>uid</code> .

LDAP Group User Authentication

The LDAP Group User Authentication module extends the full featured LDAP Authentication module and provides additional group information to the EMS server. This module validates all connections (users, routes, and so on) by authenticating to the LDAP server using the supplied credentials, and then updates the EMS server with any related group information found.

If caching is enabled, changes to group membership in the LDAP server are not reflected in EMS until the user's entry in the cache has expired.

Authentication Process

The Group User LDAP module authenticates a user just as the LDAP Authentication module does, but will make additional requests to garner group membership information from LDAP and update the EMS server for authorization purposes.

For example, consider a user "Joe", who belongs to the "Engineering" group in the LDAP server. When an application connects to the EMS server using Joe's credentials, the information that Joe belongs to the Engineering group is passed back up to the server after a successful authentication. If access controls are set up in EMS for the group Engineering, then Joe inherits those permissions.

Implementation

The LDAP Group User Authentication module name is:

```
com.tibco.tibems.tibemspd.security.jaas.LDAPGroupUserAuthentication
```

The JAAS configuration file entry for this module should have an entry similar to:

```
EMSLdapAuthentication {
    com.tibco.tibems.tibemspd.security.jaas.LDAPGroupUserAuthentication required
    tibems.ldap.url="ldap://ldapserver:389"
    tibems.ldap.user_base_dn="ou=Marketing,dc=company,dc=com"
    tibems.ldap.user_attribute="uid"
    tibems.ldap.scope="subtree"
    tibems.ldap.group_base_dn="ou=Groups,dc=company"
    tibems.ldap.group_member_attribute="uniqueMember"
    tibems.ldap.dynamic_group_base_dn="ou=Groups,dc=company"
    tibems.ldap.dynamic_group_class="groupOfURLs"
    tibems.ldap.dynamic_group_member_attribute="uid"
    tibems.ldap.dynamic_group_filter="(objectClass=GroupOfURLs)"
    tibems.cache.enabled=true
    tibems.cache.user_ttl=600
    tibems.ldap.manager="CN=Manager"
    tibems.ldap.manager_password="password" ;
};
```

Parameters

In addition to all parameters available for the LDAP Authentication module, which are described in the following table, the following parameters are supported:

Parameter	Description
<code>tibems.ldap.group_attribute</code>	The attribute of a static LDAP group that contains the group name. Default is <code>cn</code> .
<code>tibems.ldap.group_base_dn</code>	The base path for the LDAP static group search. If null or not set, static groups are not searched.
<code>tibems.ldap.group_filter</code>	The filter used in the static group search. By default, a filter is created using the <code>ems.ldap.group_member_attribute</code> parameter. If a more complex filter is needed, use this property to override the default. Any occurrence of <code>{0}</code> in the search string is replaced with the group member attribute. Any occurrence of <code>{1}</code> is replaced with the user DN. <code>{2}</code> contains solely the user name for cases where the DN does not match group membership. Default is <code>{0}={1}</code> .
<code>tibems.ldap.group_member_attribute</code>	The attribute ID of a dynamic LDAP group object that specifies the name of members of the group. Default is <code>uniqueMember</code> .
<code>tibems.ldap.group_scope</code>	The scope of the static group search. Valid values include <code>onelevel</code> , <code>subtree</code> , and <code>object</code> . Default is to use a subtree search.
<code>tibems.ldap.dynamic_group_base_dn</code>	Base path for the LDAP dynamic group search. If null or not set, dynamic groups are not searched.
<code>tibems.ldap.dynamic_group_class</code>	The class name of a dynamic group. Default is <code>groupOfURLs</code> .
<code>tibems.ldap.dynamic_group_attribute</code>	The attribute of an LDAP dynamic group that contains the group name. Default is <code>cn</code> .

Parameter	Description
<code>tibems.ldap.dynamic_group_filter</code>	<p>The filter used in the dynamic group search. By default, a filter is created using the <code>ems.ldap.dynamic_group_member_attribute</code> property. If a more complex filter is needed, use this property to override the default. Any occurrence of {0} is replaced with the group member property. Any occurrence of {1} is replaced with the DN of the user for cases where that may be required. A {2} in the search string is replaced with the user name.</p> <p>When using <code>tibems.ldap.dynamic_group_search_direct</code>, a simple filter should be used which matches all dynamic groups that may contain the user. For example, <code>(objectClass=GroupOfURLs)</code>.</p> <p>Default is {0}={1}.</p>
<code>tibems.ldap.dynamic_group_member_attribute</code>	<p>The attribute ID of a dynamic LDAP group object that specifies the name of members of the group.</p> <p>Default is <code>uniqueMember</code>.</p>
<code>tibems.ldap.dynamic_group_member_url</code>	<p>The attribute of a dynamic LDAP group object that specifies the URL generating the membership list.</p> <p>Default is <code>memberURL</code>.</p>
<code>tibems.ldap.dynamic_group_scope</code>	<p>The scope of the dynamic group search. Valid values include <code>onelevel</code>, <code>subtree</code>, and <code>object</code>.</p> <p>Default is to use a subtree search.</p>

Parameter	Description
<code>tibems.ldap.dynamic_group_search_direct</code>	<p>Changes the search algorithm used for determining membership of dynamic groups.</p> <p>Normally, LDAP servers automatically populate dynamic groups based on a configured search URL. However, some LDAP servers have issues where the generated attributes representing members of the groups are not properly returned by a search. When enabled, this parameter changes the group search algorithm to parse out a DN, scope, and filter from the search URL specified by the dynamic group and use those to search for a user. Use of this parameter is only recommended when it has been determined that dynamic group searches are not working.</p> <p>Default is <code>false</code>.</p>
<code>tibems.ldap.backlink_group_base_dn</code>	<p>The base path for the back-linked LDAP group search.</p> <p>By default, back-linked group searches are not enabled. If enabled, back-linked groups, including nested groups, are searched using back link parameters. To disable nested searches for back links, set <code>tibems.ldap.nested_groups_enabled</code> to <code>false</code>.</p> <p>Back link parameter defaults are set for use with Active Directory, the most commonly used LDAP server supporting back links.</p>
<code>tibems.ldap.backlink_group_attribute</code>	<p>The attribute that contains the groups an LDAP object (member or group) belongs to.</p> <p>Default is <code>memberOf</code>.</p>
<code>tibems.ldap.backlink_group_rdn</code>	<p>A back-link RDN that specifies the name portion of the DN representing the group. If the entire contents of the back link value is to be used as the group name, do not set this value.</p> <p>Default is <code>CN</code>.</p>
<code>tibems.ldap.backlink_group_filter</code>	<p>A back-link filter used by a group search to find groups the member belongs to. If nested groups are not used, then it is highly advisable to disable nested groups.</p> <p>Default is <code>(distinguishedName={1})</code>.</p>

Parameter	Description
<code>tibems.ldap.backlink_group_scope</code>	<p>The scope of the back link group search. Valid values include <code>onelevel</code>, <code>subtree</code>, and <code>object</code>.</p> <p>Default is to use a subtree search.</p>

Host Based Authentication

The Host Based Authentication module authenticates a user based on the IP address or host name that is associated with their client connection during authentication.

When enabled, the IP address of the incoming connection is evaluated against a whitelist of IP addresses and/or IP masks. If any of the IP addresses or masks result in a match, IP authentication for the user is considered successful.

If an IP match is not found, then the host name of the incoming connection is compared with the configured whitelist of patterns, which may be specific host names or regular expressions. If the connection's host name evaluates to true with any of the patterns in the list, authentication is considered successful.

Either the host name *or* IP mask must match for authentication success.

Authentication Process

When a client connects to the EMS server, this module compares the IP address with the specified IP net/prefix list, if configured. If that is not successful, then the hostname is compared with the list of hostnames or domain names. Should none of the above succeed, authentication fails.



If hostname verification is configured, the module may do a DNS lookup. This could impact performance.

Implementation

The Host Based Authentication module name is:

```
com.tibco.tibems.tibemsd.security.jaas.HostBasedAuthentication
```

The JAAS configuration file entry for this login module should have a section similar to the following:

```
EMSUserAuthentication {
    com.tibco.tibems.tibemsd.security.jaas.HostBasedAuthentication required
    tibems.hostbased.accepted_hostnames="'production.*','tibco.com'"
    tibems.hostbased.accepted_addresses"10.1.2.23, 10.100.0.0/16, 0:0:0:0:0:0:0:1"
};
```

Parameters

The Host Based Authentication Module parameters are listed in the following table.

Parameter	Description
<code>debug</code>	<p>When set to <code>true</code>, enables debug output for the module. Enabling this parameter may aid in diagnosing configuration problems.</p> <p>Warning: Enabling the debug flag may create security vulnerabilities by revealing information in the log file.</p> <p>The default setting is <code>false</code>.</p>

Parameter	Description
<code>tibems.hostbased. accepted_hostnames</code>	<p>A comma delimited list of host names or patterns to compare with the incoming connection's host name, as known by the EMS server. A match results in successful authentication.</p> <p>Host names or domains can be explicitly specified, or any regular expression working with the Java Pattern class may be used. A domain may be used by beginning the string with a dot (.). Each host-name or pattern must be encapsulated by a single quote and separated by a comma. These entries are compared with the hostname associated with the IP of the connecting EMS client.</p> <p>WARNING: This could have a performance impact as a NIS or DNS lookup may be performed. If this property is not set, host names are not checked during authentication.</p> <p>For example:</p> <pre>'host1', '.tibco.com', '^.*_SERVER\ \tibco\\.com'</pre>
<code>tibems.hostbased. accepted_addresses</code>	<p>A comma delimited list of IP addresses or net/prefix (CIDR notation) masks to compare with the incoming connection's IP address.</p> <p>Both IPV4 and IPV6 are supported. Any match results in successful authentication. If this property is not set, IP address checking is disabled.</p> <p>For example:</p> <pre>10.1.2.23, 10.100.0.0/16, 0:0:0:0:0:0:1</pre>

Connection Limit Authentication

The Connection Limit Authentication module limits the number of active connections a user can have at any one time.

Authentication Process

When a client connects, the user name is identified and then authenticated based on the number of connections open for that user. If the number of connections is less than the configured limit, the user is authenticated successfully, and the internal connection count is incremented. When a user disconnects, the internal connection count is decremented.

A client's user name can be specified as one of the following types: hostname, IP address, LDAP ID, or LDAP ID and hostname.



If you plan on stacking this module with other JAAS modules, it is important to use this as the final JAAS module and to list all of the JAAS modules as 'requisite'. This ensures that the internal connection count of the Connection Limit Authentication module remains accurate.

Implementation

The Connection Limit Authentication module name is:

```
com.tibco.tibems.tibemsd.security.jaas.ConnectionLimitAuthentication
```

The JAAS configuration file entry for this login module should have a section similar to the following:

```
EMSSUserAuthentication {
    com.tibco.tibems.tibemsd.security.jaas.ConnectionLimitAuthentication required
    tibems.connectionlimit.max_connections="5"
    tibems.connectionlimit.type="HOSTNAME" ;
};
```

Parameters

The Host Based Authentication Module parameters are listed in the following table.

Parameter	Description
debug	<p>When set to true, enables debug output for the module. Enabling this parameter may aid in diagnosing configuration problems.</p> <p>Warning: Enabling the debug flag may create security vulnerabilities by revealing information in the log file.</p> <p>The default setting is false.</p>
tibems.connectionlimit.max_connections	An integer to indicate the number of connections allowed per user.
tibems.connectionlimit.type	Identifies the type of user for an incoming connection. For example: "HOSTNAME", "IP", "LDAPID", or "LDAPID@HOSTNAME".

Using Multiple JAAS Modules

You can stack the provided JAAS modules to suit your environment and authentication needs. There are no restrictions on which or how many modules can be stacked.

To stack multiple JAAS modules, include the desired module configurations and JAAS flags in the same configuration file that is reference by the JAAS configuration parameter, `jaas_config`.

The behavior and authentication requirements of the included modules are controlled by the module *Flag* value assigned to each module in the stack. For more information, see the Oracle `javax.security.auth.login.Configuration` Class documentation for information on using multiple JAAS modules.

Example: Two Authentication Requirements

In this example, a user is authenticated based on network location. If that succeeds, the user is then authenticated using LDAP credentials. Both must succeed for the user to be authenticated.

This behavior is controlled by the requisite *Flag*.

```
EMSSUserAuthentication {
    com.tibco.tibems.tibemsd.security.jaas.HostBasedAuthentication requisite
    tibems.hostbased.accepted_addresses="10.98.48.45, ::1"
    tibems.hostbased.accepted_hostnames="'jsmith.*', '.tibco.com';
    com.tibco.tibems.tibemsd.security.jaas.LDAPSimpleAuthentication requisite
    tibems.ldap.user_pattern="uid=%u,ou=People,dc=tibco.com"
    tibems.ldap.url="ldap://localhost:389" ;
};
```


Example: One Authentication is Sufficient

In this example, a user is authenticated against multiple LDAP branches. If authentication fails in the first branch, the second is tried. Only one module instance needs to succeed for the user to be authenticated.

This behavior is controlled by the sufficient *Flag*.

```
EMSUserAuthentication {
    com.tibco.tibems.tibemsd.security.jaas.LDAPSimpleAuthentication sufficient
    tibems.ldap.user_pattern="uid=%u,ou=People,dc=Local"
    tibems.ldap.url="ldap://localhost:389" ;
    com.tibco.tibems.tibemsd.security.jaas.LDAPSimpleAuthentication sufficient
    tibems.ldap.user_pattern="uid=%u,ou=People,dc=Remote"
    tibems.ldap.url="ldap://localhost:389" ;
};
```

Migrating to the EMS JAAS Modules

Migrating from LDAP authentication within the EMS server to authentication using the JAAS modules is relatively straightforward. Many of the parameters directly map to each other. Nevertheless, there are some differences and so care must still be taken.

The LDAP Group User Authentication module provides similar functionality to that of the EMS server. However, if group membership is not required for authentication, then the LDAP Authentication module is a better choice.

LDAP Parameter to JAAS Module Parameter Mapping

When parameters have an exact equivalent, as indicated in the notes column, the same values from the EMS Server LDAP parameters can be used in the JAAS modules, except that the JAAS modules expect parameter values to be enclosed in quotes.

EMS Server LDAP Parameter	EMS JAAS Equivalent	Notes
ldap_url	<code>tibems.ldap.url</code>	Exact
ldap_principal	<code>tibems.ldap.manager</code>	Exact
ldap_credential	<code>tibems.ldap.manager_password</code>	Exact
ldap_cache_enabled	<code>tibems.cache.enabled</code>	Exact
ldap_cache_ttl	<code>tibems.cache.user_ttl</code>	Exact
ldap_conn_type	<code>tibems.ldap.url</code>	See ldap_conn_type below.
ldap_tls_cacert_file	<code>tibems.ldap.truststore</code>	See ldap_tls Parameters .
ldap_tls_cacert_dir	<code>tibems.ldap.truststore</code>	See ldap_tls Parameters .
ldap_tls_cipher_suite	N/A	See ldap_tls Parameters .
ldap_tls_rand_file	N/A	See ldap_tls Parameters .
ldap_tls_cert_file	<code>tibems.ldap.truststore</code>	See ldap_tls Parameters .
ldap_tls_key_file	<code>tibems.ldap.truststore</code>	See ldap_tls Parameters .

EMS Server LDAP Parameter	EMS JAAS Equivalent	Notes
<code>ldap_user_class</code>	<code>tibems.ldap.user_filter</code>	See <code>ldap_user_class</code> and <code>ldap_static_group_class</code> .
<code>ldap_user_attribute</code>	<code>tibems.ldap.user_attribute</code>	Exact
<code>ldap_user_base_dn</code>	<code>tibems.ldap.user_base_dn</code>	Exact
<code>ldap_user_scope</code>	<code>tibems.ldap.scope</code>	Exact
<code>ldap_user_filter</code>	<code>tibems.ldap.user_filter</code>	See Filters .
<code>ldap_group_base_dn</code>	<code>tibems.ldap.group_base_dn</code>	Exact
<code>ldap_group_scope</code>	<code>tibems.ldap.group_scope</code>	Exact
<code>ldap_group_filter</code>	<code>tibems.ldap.group_filter</code>	See Filters .
<code>ldap_all_groups_filter</code>	N/A	See Filters .
<code>ldap_static_group_class</code>	<code>tibems.ldap.group_filter</code>	See <code>ldap_user_class</code> and <code>ldap_static_group_class</code> .
<code>ldap_static_group_attribute</code>	<code>tibems.ldap.group_attribute</code>	Exact
<code>ldap_static_group_member_filter</code>	<code>tibems.ldap.group_filter</code>	See Filters .
<code>ldap_static_member_attribute</code>	<code>tibems.ldap.group_member_attribute</code>	Exact
<code>ldap_dynamic_group_class</code>	<code>tibems.ldap.dynamic_group_class</code>	Exact
<code>ldap_dynamic_group_attribute</code>	<code>tibems.ldap.dynamic_group_attribute</code>	Exact
<code>ldap_dynamic_member_url_attribute</code>	<code>tibems.ldap.dynamic_group_member_url</code>	Exact

Parameters Requiring Conversion

`ldap_conn_type`

The connection type is indirectly supported by the JAAS modules through the protocol portion of the LDAP URL.

- `ldap://` creates a TCP connection.
- `ldaps://` creates an SSL connection.

If the `startTLS` LDAP extension is required, additional JNDI parameters may be specified through the JAAS configuration. Alternately, you can customize the JAAS module. See [Custom JAAS Modules](#) for more information.

Idap_tls Parameters

The JAAS modules have the ability to pass any parameters to JNDI. It is up to the user to determine what java SSL parameters to pass to JNDI through the JAAS configuration.

In most cases, only a certificate key store is required. For convenience, the `tibems.ldap.truststore` parameter can be used to specify the store. Refer to Java documentation for additional information regarding the use of SSL.

Filters

Filters perform the same function in the JAAS modules as they do when LDAP authentication is configured within the EMS server, but the specification of the filter parameters is slightly different.

Be sure to substitute the EMS server's %s filters for the appropriate {n} JAAS module filter.

Idap_user_class and Idap_static_group_class

The `ldap_user_class` and `ldap_static_group_class` parameters are not necessary in the JAAS modules.

LDAP class names are specified in the filters, as in the following examples:

```
tibems.ldap_user_filter="(&({0}={1})(objectClass=uniqueMember))"
```

and

```
tibems.ldap_group_filter="(&({0}={1})(objectClass=groupofUniqueNames))"
```

Refer to the filter documentation to map various identifiers. For example, in converting the user filter, the EMS server LDAP parameter, %s maps to {1} in the JAAS filter. Many group searches should work with a filter similar to:

```
(&({0}={1})(objectClass=<group class>)
```

However, dynamic groups do allow you to specify the class in order to mirror the search algorithm used by the EMS server native LDAP functionality.

Dynamic Groups

Dynamic groups in LDAP should normally behave similarly to static groups in LDAP. However, some LDAP implementations require a modified search algorithm.

In order to perform this type of search with the JAAS modules, set the parameter:

```
tibems.ldap.dynamic_group_search_direct="true"
```

It is recommended this parameter be enabled after you have determined that there is a problem, or when using an OpenLDAP server. In some cases, this is required in order to mirror the EMS Server native LDAP functionality.

Example

This section provides a walk through converting an existing set of LDAP parameters in the EMS server using the LDAP Group User Authentication login module.

1. Set the `jre_library` parameter to enable the JVM.

For more information, see [The JVM in the EMS Server](#).

2. Set the `security_classpath`.

For example:

```
security_classpath = c:\tibco\ems\8.5\bin\tibemsd_jaas.jar;c:\tibco\ems\8.5\lib\tibjmsadmin.jar;c:\tibco\ems\8.5\lib\tibjms.jar;c:\tibco\ems\8.5\lib\jms-2.0.jar
```

3. Enable JAAS for LDAP authentication by modifying the `user_auth` parameter. Remove `ldap` from the list of authentication sources, and verify that `jaas` is present.

For example:

```
user_auth=jaas
```

4. Edit the provided `com.tibco.tibems.tibemsd.security.jaas.LDAPGroupUserAuthentication` module for your LDAP server configuration:
 - a. Locate the sample configuration file `ems_ldap_with_groups.txt` in `EMS_HOME\samples\config\jaas`.
 - b. Copy the file to a secure location, ideally alongside the other EMS server configuration files.
5. Set the `jaas_config_file` to reference the JAAS module configuration file created in [Step 4](#) above.

For example:

```
jaas_config_file = ems_ldap_with_groups.txt
```

LDAP Parameters in the `tibemsd.conf`

Consider the following LDAP server configuration parameters in the EMS server configuration file, `tibemsd.conf`:

```
ldap_url           = ldap://ldaphost:389
ldap_principal     = cn=Manager
ldap_credential    = $man$fPSdYgyVTQloUv36Km36AEOrARW
ldap_user_class    = person
ldap_user_attribute = uid
ldap_user_base_dn  = "ou=People,dc=TIBCO"
ldap_user_scope    = subtree
ldap_user_filter   = "(&(uid=%s)(objectclass=person))"
ldap_group_base_dn = "ou=Groups,dc=TIBCO"
ldap_group_scope   = subtree
ldap_group_filter  = "(&(cn=%s)(objectclass=groupOfUniqueNames))"
ldap_static_group_class = groupOfUniqueNames
ldap_static_group_attribute = cn
ldap_static_member_attribute = uniqueMember
ldap_cache_enabled = FALSE
```

Mapped to LDAP Group User Authentication Module

The LDAP configuration parameters shown above map to the following JAAS configuration file:

```
EMSUserAuthentication {
    com.tibco.tibems.tibemsd.security.jaas.LDAPGroupUserAuthentication required
    tibems.ldap.url="ldap://ldaphost:389"
    tibems.ldap.manager="cn=Manager"
    tibems.ldap.manager_password="$man$fPSdYgyVTQloUv36Km36AEOrARW"
    tibems.ldap.user_attribute="uid"
    tibems.ldap.user_base_dn="ou=People,dc=TIBCO"
    tibems.ldap.scope="subtree"
    tibems.ldap.user_filter="(&(uid={1})(objectclass=person))"
    tibems.ldap.group_base_dn="ou=Groups,dc=TIBCO"
    tibems.ldap.group_scope="subtree"
    tibems.ldap.group_filter="(&({0}={1})(objectclass=groupOfUniqueNames))"
    tibems.ldap.group_attribute="cn"
    tibems.ldap.group_member_attribute="uniqueMember"
    tibems.ldap.cache.enabled = "false" ;
};
```

Troubleshooting Problems in the JAAS Modules

In order to troubleshoot JAAS modules,

Procedure

1. Add JAAS to the EMS server trace options in the main server configuration file:

```
console_trace = DEFAULT, +JAAS, +JVM, +JVMERR
```

2. Enable debugging in the JAAS module itself, by setting the debug parameter to true:

```
EMSSUserAuthentication {  
    com.tibco.tibems.tibemspd.security.jaas.LDAPSimpleAuthentication required  
    debug="true"  
    tibems.ldap.url="ldap://ldapserver:389"  
    tibems.ldap.user_pattern="CN=%u"  
};
```



Note that enabling the debug flag may create security vulnerabilities by revealing information in the log file. This parameter should be enabled only for troubleshooting purposes.

Result

This will provide a list of parameters passed into LDAP, which is useful in identifying any mistyped parameters or default values that need to be changed. Verbose output is provided to help identify the problem.

When developing a custom JAAS module, it is possible for a runtime exception inside a JAAS method to cause the JAAS module to fail. In those cases, catching and printing exceptions to the default output stream provides valuable information.

Database Stores

You can configure the TIBCO Enterprise Message Service server to store messages in a database.

The following topics describe database stores. For more information about file-based stores, see [Store Messages in Multiple Stores](#).

Database Stores Overview

The EMS server can connect to a database, and store messages in one or more database instances. The server connects to the database using Hibernate Core for Java to interface between the database and the EMS server.



On certain platforms, the optional database store feature requires the installation and use of Hibernate Core for Java and associated jar files.

Requirements

To create database stores, you must have:

- Hibernate Core for Java and related JAR files.
- A database server that is supported by Hibernate, the corresponding dialect, and the appropriate JDBC driver.

The database server must be running, and the databases that the EMS server will connect to must have already been created by the database administrator.

- A username with read-write permissions and a password to the database server.

Configuring Database Stores

This section describes the steps required to configure and deploy database stores.

For general conceptual information about the multiple store feature, see [Store Messages in Multiple Stores](#).

Settings for creating and configuring database stores are managed in the EMS server, and are transparent to clients. To configure the database stores feature, follow these steps:

Procedure

1. Enable the database store feature in the `tibemsd.conf` by setting the parameters:

- `dbstore_classpath`
- `dbstore_driver_name`
- `dbstore_driver_dialect`
- [jre_library](#)

For detailed information about the `dbstore` parameters, see [Configuration in tibemsd.conf](#). The `jre_library` parameter, which enables the JVM in the EMS server, is described in [JVM Parameters](#).

2. Setup and configure stores in the `stores.conf` file.

You can create multiple database stores, or a combination of database and file-based stores. Each store must have a unique name. Parameters determine whether the store is a database store, provide the location of the database server, and specify the username and password that the EMS server uses to access the database.

For a list of database store parameters, see [Configuration in stores.conf](#) below.

3. Associate destinations with the configured stores.

Messages are sent to different stores according to their destinations. You associate a destination with a specific store using the `store` parameter in the `topics.conf` and `queues.conf` files. You can also change store associations using the `setprop topic` or `setprop queue` command in the EMS Administration Tool.

Multiple destinations can be mapped to the same store, either explicitly or using wildcards. Even if no stores are configured, the server sends persistent messages that are not associated with a store to default stores. See [Default Store Files](#) for more information.

For details about the `store` parameter, see [store](#).

4. Export database tables.

When the EMS server is configured to store messages in a database, the database schema must be exported before the server is started. Use the EMS Schema Export Tool to create, drop, and update the database tables.

For details, see [EMS Schema Export Tool](#).

Configuration in `tibemsd.conf`

These parameters are set in the `tibemsd.conf` configuration file.

`dbstore_classpath`

Includes all the JAR files required by the EMS server when employing the database store feature. This parameter must be set when a store of type `dbstore` has been created in the `stores.conf` file.

```
dbstore_classpath = pathname
```

Required JAR files are determined by the installed Hibernate release, and are documented in the `_README.txt` file that is located in the `lib/` directory of the Hibernate distribution. Many of these JAR files are version-specific, and the required versions may change with new Hibernate releases. You should verify the required version and modify the `dbstore_classpath` variable accordingly.

If you are using Hibernate release 3.2.5, for example, the `dbstore_classpath` should include paths to the following JAR files:

- `hibernate3.jar`
- `dom4j-1.6.1.jar`
- `commons-collections-2.1.1.jar`
- `commons-logging-1.0.4.jar`
- `ehcache-1.2.3.jar`
- `jta.jar`
- `cglib-2.1.3.jar`
- `antlr-2.7.6.jar`
- `c3p0-0.9.1.jar`
- `asm.jar`
- `asm-attrs.jar`
- Database-specific driver JAR file. Supported jar files are listed in the table below. Supported databases are described in the section on *Supported Databases* in *TIBCO Enterprise Message Service Installation*.

For an example, see `EMS_HOME/samples/config/tibemsd-db.conf`.

For information on parameters used by the database store feature, see [stores.conf](#).

Supported Database Drivers

Database	Driver
MySQL	mysql-connector-java-5.0.7-bin.jar
Microsoft SQL Server	mssql-jdbc-7.0.0.jre8.jar
Oracle	ojdbc7.jar
Oracle Real Application Clusters (RAC)	Oracle JDBC OCI Instant Client, including ojdbc7.jar
IBM DB2	db2jcc.jar and db2jcc_license_cu.jar

dbstore_driver_name

Specifies the name of the JDBC driver used by Hibernate.

```
dbstore_driver_name = name
```

For example:

- If you are using the MySQL InnoDB database server:
dbstore_driver_name=com.mysql.jdbc.Driver
- If you are using the Microsoft SQL Server:
dbstore_driver_name= com.microsoft.sqlserver.jdbc.SQLServerDriver
- If you are using Oracle 12c:
dbstore_driver_name=oracle.jdbc.driver.OracleDriver
- If you are using IBM DB2 Server:
dbstore_driver_name=com.ibm.db2.jcc.DB2Driver

dbstore_driver_dialect

Specifies the Hibernate SQL dialect used to construct SQL commands.

```
dbstore_driver_dialect = dialect
```

For example, if you are using the MySQL with InnoDB database server:

```
dbstore_driver_dialect = org.hibernate.dialect.MySQL5InnoDBDialect
```

The SQL dialect is defined by Hibernate. For a list of databases and the associated dialects, see the `readme.txt` file located in the Hibernate install directory archive.

Configuration in stores.conf

This section describes parameters configured for each database store in the `stores.conf` file. The `stores.conf` includes definitions for both database and file-based stores.

For information about configuring file-based stores, see [stores.conf](#).

The format of the file is:

```
[store_name] # mandatory -- square brackets included.
type = dbstore
dbstore_driver_url = JDBCURL
dbstore_driver_username = username
dbstore_driver_password = password
[processor_id = processor-id]
```


Parameter Name	Description
<code>[store_name]</code>	<p><code>[store_name]</code> is the name that identifies this store configuration.</p> <p>Note that the square brackets <code>[]</code> DO NOT indicate that the <code>store_name</code> is an option; they must be included around the name.</p>
<code>type=dbstore</code>	<p>Identifies the store type. This parameter is required for all store types. The type can be:</p> <ul style="list-style-type: none"> • <code>file</code> — for file-based stores. • <code>mstore</code> — for mstores. • <code>dbstore</code> — for database stores. <p>For information about the parameters used to configure file-based stores, see stores.conf.</p>
<code>dbstore_driver_url</code>	<p>Provides the location of the database server. The URL entered uses the syntax specified by the JDBC driver for your database.</p> <p>See documentation specific to your JDBC driver for more information. If you are using an Oracle RAC database, also see Using a TAF Configured URL.</p>
<code>dbstore_driver_username</code>	<p>The username that the EMS server uses to access the database.</p> <p>Note that this user must have read and write permissions to the database.</p>
<code>dbstore_driver_password</code>	<p>The password that the server uses, in conjunction with the username provided in <code>dbstore_driver_username</code>, to access the database.</p> <p>You can mangle this and other passwords by way of the <code>tibemsadmin</code> tool. See tibemsadmin Options for more information about using <code>tibemsadmin</code> to mangle passwords.</p>
<code>processor_id</code>	<p>When specified, the EMS Server binds the storage thread of this store to the specified processor.</p> <p>Do not use this parameter if the default behavior provides sufficient throughput. If no processor ID is specified for a store, the store is not bound to a specific processor.</p> <p>Specify the <i>processor-id</i> as an integer.</p> <p>This parameter has similar requirements, limitations, and benefits as the processor_ids parameter in <code>tibemsd.conf</code>. For use guidelines, see Performance Tuning.</p>

Example Using MySQL Server

```
[$sys.fail-safe]
type=dbstore
dbstore_driver_url=jdbc:mysql://mysqlsrv_1:3306/sysfs
```

```

dbstore_driver_username=admin
dbstore_driver_password=admin123

[$sys.meta]
type=dbstore
dbstore_driver_url=jdbc:mysql://mysqlsrv_1:3306/sysmeta
dbstore_driver_username=admin
dbstore_driver_password=admin123

```

Example Using Microsoft SQL Server

```

[$sys.meta]
type=dbstore
dbstore_driver_url=jdbc:sqlserver://sqlsrv_1:3415;databaseName=sysmeta
dbstore_driver_username=admin
dbstore_driver_password=admin123

[$sys.fail-safe]
type=dbstore
dbstore_driver_url=jdbc:sqlserver://sqlsrv_1:3415;databaseName=sysfs
dbstore_driver_username=admin
dbstore_driver_password=admin123

```

Example Using Oracle 12c

```

[$sys.meta]
type=dbstore
dbstore_driver_url=jdbc:oracle:thin:adminmeta/admin123@osrv_1:1521:orclperf
dbstore_driver_username=adminmeta
dbstore_driver_password=admin123

[$sys.fail-safe]
type=dbstore
dbstore_driver_url=jdbc:oracle:thin:adminfs/admin123@osrv_1:1521:orclperf
dbstore_driver_username=adminfs
dbstore_driver_password=admin123

```

Example Using Oracle RAC 12c

```

[$sys.fail-safe]
type=dbstore
dbstore_driver_url=jdbc:oracle:oci:<user>/
<passwd>@((DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=<host1>)(PORT=1521))
(ADDRESS=(PROTOCOL=TCP)(HOST=<host2>)(PORT=1521))(CONNECT_DATA=(SERVICE_NAME=orcl)
(FAILOVER_MODE=(TYPE=SELECT)(METHOD=BASIC)(RETRIES=180)(DELAY=5))))
dbstore_driver_username=admin
dbstore_driver_password=admin123

```

For more information, see [Configuration for the Oracle RAC Database](#) below.

Example Using IBM DB2 Server

```

[$sys.meta]
type=dbstore
dbstore_driver_url=jdbc:db2://db2srv_1:50000/SYSMETA
dbstore_driver_username=admin
dbstore_driver_password=admin123

[$sys.fail-safe]
type=dbstore
dbstore_driver_url=jdbc:db2://db2srv_1:50000/SYSFS
dbstore_driver_username=admin
dbstore_driver_password=admin123

```

Configuration to Detect Database Unavailability

If the database becomes unresponsive or unreachable, the JDBC driver does not automatically notify the EMS server of that situation until the operating system's TCP keep-alive mechanism kicks in, which usually defaults to a delay of 2 hours.

To expedite the notification of such a situation, you can adjust the TCP keep-alive parameters to a shorter delay.

You may also expedite the notification by the JDBC driver to the EMS server of the database becoming unresponsive or unreachable by adjusting the appropriate JDBC driver property. The way to do this varies with the driver vendor.

For example, for the Oracle thin client, add this type of entry to the `jre_option` property in `tibemsd.conf`:

```
jre_option=-Doracle.jdbc.ReadTimeout=30000
```

This results in EMS server database operations timing out after 30 seconds, leading to a server shutdown when the database is unavailable.

Configuration for the Oracle RAC Database

The TIBCO Enterprise Message Service server must connect to the Oracle RAC 12c database using the Oracle JDBC OCI driver and TAF configuration.

Installing the OCI Driver

We recommend using the Oracle Instant Client, which is an optimized light-weight OCI driver package available from Oracle:

www.oracle.com/technetwork/database/features/instant-client/index.html

Follow the instructions provided to install the Oracle Instant Client.

Using a TAF Configured URL

To ensure that the EMS server does not lose its connection to the database during a database failover, the server should connect to the database using a Transparent Application Failover (TAF) configured URL. For example:

```
jdbc:oracle:oci:@(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST=host1)(PORT=1521))
(ADDRESS=(PROTOCOL=TCP)(HOST=host2)(PORT=1521))(CONNECT_DATA=(SERVICE_NAME=orcl)
(FAILOVER_MODE=(TYPE=SELECT)(METHOD=BASIC)(RETRIES=180)(DELAY=5))))
```



True Transparent Application Failover is not supported. If a database failover occurs while the EMS server is performing a transactional activity, the EMS server does not replay or restart the failed transaction. However, a TAF connection allows the EMS server to recover fully as long as no transaction was taking place at the time of the failover.

EMS Schema Export Tool

Each database store that is configured for an EMS server includes a configuration parameter pointing to a database. The EMS Schema Export Tool creates and exports database tables for the database stores. Database administrators can use the Schema Export Tool to selectively export and tune schemas to suit your database and messaging system.



The EMS Schema Export Tool must be used to export database tables when one or more database stores are configured. That is, if any stores of type `dbstore` are configured, you must export the database schema before starting the EMS server.

The Schema Export Tool is a JAR file, `tibemsd_util.jar`, located in the same directory as `tibemsd`. Command line options, described in [EMS Schema Export Tool Options](#), determine whether database

tables are created or dropped, and whether they are printed to the console, saved to a file, or exported to the database.

Before invoking the Schema Export Tool, you must:

- Configure the global database store parameters for the EMS server. The parameters that configure the global database store settings begin with `dbstore_`. See [Configuration in tibemsd.conf](#) for details about these parameters.
- Configure at least one store of type `dbstore`. See [Configuration in stores.conf](#) for more information about configuring database stores.

How the Schema Export Tool Works

When it is invoked, the Schema Export Tool accepts the `tibemsd.conf` or `tibemsd.json` file and reviews the database store parameters, then parses the stores configured, either in the `stores.conf` file or in the JSON configuration file. Depending on the options specified when it was invoked, the Schema Export Tool will create, drop, or update the database tables for the stores of type `dbstore` that are configured.

The tool can perform the selected actions on all database stores, or only on specific stores. The Schema Export Tool can also print the database tables it creates to the console, or export them either to the database or to a specified file.

Running the Schema Export Tool

The Schema Export Tool is invoked from the command line. The tool can be invoked from its directory, or by giving the absolute path to the `tibems_util.jar` file.

For example:

- **On Windows**

```
> java -jar EMS_HOME\bin\tibemsd_util.jar options
```

Or

```
> java -jar c:\tibco\ems\8.5\bin\tibemsd_util.jar options
```

- **On Unix**

```
$ java -jar EMS_HOME/bin/tibemsd_util.jar options
```

Or

```
$ java -jar /opt/tibco/ems/8.5/bin/tibemsd_util.jar options
```

EMS Schema Export Tool Options

The following table shows the options that are used with the Schema Export Tool.

Option	Description
<code>-tibemsdconf <i>pathname</i></code>	<p>The absolute path to the <code>tibemsd.conf</code> or <code>tibemsd.json</code> file. For example, on a UNIX system:</p> <pre>/opt/tibco/ems/8.5/samples/config/tibemsd.conf</pre> <p>This tool supports JSON configuration files only when run on those platforms for which Central Administration is supported. For a list of supported platforms, see the supported platforms list for <i>Central Administration</i> in the <i>TIBCO Enterprise Message Service Installation</i> guide.</p> <p>Text-based <code>tibemsd.conf</code> files are supported on all platforms.</p>

Option	Description
<code>-exporttofile</code>	<p>Export the schema to a file named <i>store-name</i>.ddl.log, where <i>store-name</i> is the name of the database store. If multiple database stores are configured, then one file is created for each database store.</p> <p>If neither <code>exporttofile</code> nor <code>export</code> option is included, the schema export tool prints the schema to the console.</p> <p>If both <code>-exporttofile</code> and <code>-export</code> are included, the Schema Export Tool exports the database schema to both locations.</p>
<code>-export</code>	<p>Export the schema to the database configured for the store.</p> <p>If neither <code>export</code> nor <code>exporttofile</code> option is included, the schema export tool prints the schema to the console.</p> <p>If both <code>-export</code> and <code>-exporttofile</code> are included, the Schema Export Tool exports the database schema to both locations.</p>
<code>-store storename=create update drop</code>	<p>Create, update, or drop the schema for one or more specific stores that are named in the stores configuration file.</p> <p>If you choose the <code>create</code> option for a schema that already exists, the Schema Export Tool recreates the schema.</p> <p>Note that <code>create</code> prints the schema to screen but does not deploy it. You must use <code>export</code> or <code>exporttofile</code> in order to implement the schema.</p>
<code>-createall</code>	Create all the stores found in the stores configuration file. Note that this option drops any existing configurations when creating the new stores.
<code>-dropall</code>	Drop all the stores found in the stores configuration file.
<code>-updateall</code>	Update the schema for all stores configured in the found in stores configuration file.
<code>-help</code>	Print information about the schema export tool and its options, and exit the tool.

Examples

The following examples show how the Schema Export Tool can be used to create database schemas in various configurations.

- Example 1

This example shows how the Schema Export Tool can be invoked from any directory by giving the absolute path to the `tibemsd_util.jar`:

```
$ java -jar /opt/tibco/ems/8.5/bin/tibemsd_util.jar -help
```

- Example 2

In this example, the Schema Export Tool creates and exports database schemas for all the stores found in the `stores.conf` that is set in the specified `tibemsd-mssqlserver.conf` file:

```
$ java -jar /opt/tibco/ems/8.5/bin/tibemsd_util.jar -tibemsdconf /opt/tibco/ems/8.5/samples/config/tibemsd.conf -createall -export
```

- Example 3

In this example, the Schema Export Tool exports the database schema for the `$sys.failsafe` store to the database:

```
$ java -jar /opt/tibco/ems/8.5/bin/tibemsd_util.jar -tibemsdconf /opt/tibco/ems/8.5/samples/config/tibemsd.conf -export -store \$sys.failsafe=create
```

- Example 4

In this example, the Schema Export Tool writes the database schema for the `$sys.failsafe` store to the file `$sys.failsafe.ddl.log`:

```
$ java -jar /opt/tibco/ems/8.5/bin/tibemsd_util.jar -tibemsdconf /opt/tibco/ems/8.5/samples/config/tibemsd.conf -exporttofile -store \$sys.failsafe=create
```

- Example 5

In this example the Schema Export Tool creates and exports the database schema for the store `mystore1`, but drops the schema associated with `mystore2` and exports the change:

```
$ java -jar /opt/tibco/ems/8.5/bin/tibemsd_util.jar -tibemsdconf /opt/tibco/ems/8.5/samples/config/tibemsd.conf -store mystore1=create -store mystore2=drop -export
```

Developing an EMS Client Application

The following topics outline the development of EMS client applications in Java, C, and C#.

JMS Specification

EMS implements the JMS 2.0 specification, which is backward compatible with earlier versions of the specification.

While the old JMS 1.0.2b interfaces are still supported, newly developed applications should use the JMS 2.0 or 1.1 interfaces instead. It is recommended to avoid using 1.0.2b interfaces, in particular due to their lack of flexibility. With these, an application initially written to work with topics has to be reworked if it needs to use queues, whereas an application based on the 1.1 or 2.0 APIs relies on a generic destination infrastructure that would not need to be altered significantly.

To get a better understanding and illustration of how the various JMS objects relate to each other, refer to the [JMS Specification](#) and to the samples client applications provided with EMS.

The code examples in this chapter illustrate the use of the JMS 2.0 interface.

JMS 2.0 Specification

The JMS 2.0 specification introduces several new features, including delivery delay, shared subscriptions, asynchronous sending and the Simplified API.

The Simplified API is offered in addition to the API originally provided with JMS 1.1, which is now called the Classic API. The Simplified API is less verbose than the Classic API, and introduces several important new objects:

- **JMSContext**

Used to create messages, as well as JMS consumers and JMS producers. Each JMS context uses one session and one connection, but does not expose those. Additionally, multiple JMS context objects can share the same connection.

- **JMSConsumer**

A message consumer that has the ability to receive a message body without the need to use a Message object.

- **JMSProducer**

Similar to an anonymous message producer, and provides a convenient API for configuring delivery options, message properties, and message headers.

Methods in the Simplified API throw unchecked exceptions rather than checked exceptions. For a sample showing the Simplified API in use, see the new Java sample file called `tibjmsJMSContextSendRecv.java`. This sample file demonstrates the Simplified API in the simplest possible way; for greater detail, refer to the Java API Reference Pages.

JMS 1.1 Specification

In the JMS 1.1 specification, applications using the point to point (queues) or publish and subscribe (topics) models use the same interfaces to create objects.

The JMS specification refers to these interfaces as *common facilities* because these interfaces create objects that can be used for either topics or queues.

JMS 1.0.2b Specification

The JMS 1.0.2b specification defined specific interfaces for topics and for queues.

The JMS 1.0.2b interfaces have the same structure as the JMS 1.1 common facilities, but the interfaces are specific to topics or queues.

Sample Clients

TIBCO Enterprise Message Service includes several sample client applications that illustrate various features of EMS. You may wish to view these sample clients when reading about the corresponding features in this manual.

The samples are included in the *EMS_HOME/samples/java*, *EMS_HOME/samples/c*, and *EMS_HOME/samples/cs* subdirectories of the EMS installation directory. Each subdirectory includes a README file that describes how to compile and run the sample clients.

[Getting Started](#) walks through the procedures for setting up your EMS environment and running some of the sample clients.

Programmer Checklists

This section provides a checklist that outlines the steps for creating an EMS application in each language:

- [Java Programmer's Checklist](#)
- [C Programmer's Checklist](#)
- [C# Programmer's Checklist](#)

Java Programmer's Checklist

Install

- Install the EMS software release, which automatically includes the EMS jar files in the *EMS_HOME/lib* subdirectory.
- Add the full pathnames for the following jar files to your CLASSPATH:


```
jms-2.0.jar
tibjms.jar
```
- Programs that use the unshared state failover API must add the following file to the CLASSPATH:


```
tibjmsufo.jar
```



All jar files listed in this section are located in the *lib* subdirectory of the TIBCO Enterprise Message Service installation directory.

Code

Import the following packages into your EMS application:

```
import javax.jms.*;
import javax.naming.*;
```

Compile

Compile your EMS application with the `javac` compiler to generate a `.class` file.

For example:

```
javac MyApp.java
```

generates a `MyApp.class` file.

Run

Use the `java` command to execute your EMS `.class` file.

For example:

```
java MyApp
```


C Programmer's Checklist

Developers of EMS C programs can use this checklist during the five phases of the development cycle.

Install

Install the EMS software release, which automatically includes the EMS client libraries, binaries, and header files in the *EMS_HOME/lib* subdirectory.

Code

Application programs must:

- Add *EMS_HOME/include* to the include path. (OpenVMS environments do not require an include path; skip this item.)
- Include the *tibems.h* header file:

```
#include <tibems/tibems.h>
```
- Programs that use the C administration API must also include the *emsadmin.h* header file:

```
#include <tibems/emsadmin.h>
```
- Programs that use the unshared state failover API must also include the *tibufo.h* header file:

```
#include <tibems/tibufo.h>
```
- Call *tibems_Open()* to initialize the EMS C API and *tibems_Close()* to deallocate the memory used by EMS when complete.

Compile and Link

- Compile programs with an ANSI-compliant C compiler.
- Link with the appropriate EMS C library files; see [Link These Library Files](#).

See the *samples/c/readme.txt* file for details.

Run

- **UNIX**
 If you use dynamic EMS libraries on a UNIX platform, the environment variable *\$LD_LIBRARY_PATH* must include the *EMS_HOME/lib* directory (which contains the shared library files). (On some UNIX platforms, this variable is called *\$SHLIB_PATH* or *\$SYLIB_LIBRARY_PATH*).
- **Windows**
 The *PATH* must include the *ems\8.5\bin* directory.
- **OpenVMS**
 The installation procedure automatically installs the shareable images required for using EMS dynamic libraries.
- **All Platforms**
 The application must be able to connect to a EMS server process (*tibemsd*).

Link These Library Files

EMS C programs must link the appropriate library files. The following sections describe which files to link for your operating system platform:

- [UNIX](#)

- [Microsoft Windows](#)
- [OpenVMS](#)

UNIX

In UNIX environments, both shared and static libraries are available. We recommend shared libraries to ease forward migration.

Include `TIBCO_HOME/ems/8.5/lib/64` in your library path.

Linker Flag	Description
<code>-ltibems64</code>	All programs must link using this library flag.
<code>-lssl</code> <code>-lcrypto</code>	Programs that use SSL must link using these library flags.
<code>-lz</code>	Programs that use compression must link using this library flag.
<code>-ltibemslookup64</code> <code>-lldap</code> <code>-lxml2</code> <code>-llber</code>	Programs that use EMS LDAP lookup must link using these library flags.
<code>-ltibemsadmin64</code>	Programs that use the C administration library must link using this library flag.
<code>-ltibemsufo64</code>	Programs that use the unshared state failover library must link using this library flag.

Microsoft Windows

For a list of Windows platforms that Release 8.5 supports, see the file `readme.txt` in the installation directory. Both DLLs and static libraries are available. We recommend DLLs to ease forward migration.

Library File	Description
With dynamic libraries (DLLs), use the <code>/MT</code> compiler option.	
<code>tibems.lib</code> <code>libeay32.dll</code> <code>ssleay32.dll</code>	All programs must link these libraries.
<code>tibemslookup.lib</code> <code>libxml2.lib</code>	Programs that use EMS LDAP lookup must link these libraries.
<code>libldap32.lib</code> <code>liblber32.lib</code>	In addition, programs that use EMS lookup must link these libraries.
<code>tibemsadmin.lib</code>	Programs that use the C administration library must link using this library.
<code>tibemsufo.lib</code>	Programs that use the C unshared state failover library must link using this library.



The version of the `libeay32.dll` shared library that is included with EMS is built to optionally support FIPS. This has a side-effect of preventing its relocation in a process address space during run time.

If your Windows application fails to start due to a relocation error, try these workarounds:

Relink your application with the `/FIXED` flag.

Relink your application with static libraries.

Library File	Description
With static libraries (DLLs), use the <code>/MD</code> compiler option.	
<code>libtibems.lib</code> <code>ssleay32mt.lib</code> <code>libeay32mt.lib</code> <code>zlib.lib</code>	All programs must link these libraries.
<code>libtibemsadmin.lib</code>	Programs that use the C administration library must link using this library.
<code>libtibemsufo.lib</code>	Programs that use the C unshared state failover library must link using this library.



Programs that perform JNDI lookups, whether they use LDAP or not, cannot be statically linked on Windows. Use dynamic linking instead.

OpenVMS

In OpenVMS environments, both shared and static libraries are available. We recommend shared libraries to ease forward migration.

Shareable Image Library Files for OpenVMS

Library File	Description
<code>LIBTIBEMSSHR.EXE</code>	All programs must link this library.
<code>LIBCRYPTOSHR.EXE</code> <code>LIBSSLSSH.EXE</code>	Programs that use SSL must link these libraries.
<code>LIBZSHR.EXE</code>	Programs that use data compression must link this library.
<code>LIBTIBEMSADMINSHR.EXE</code>	Programs that use the C administration library must link this library.
<code>LIBTIBEMSUFOSHR.EXE</code>	Programs that use the C unshared state failover library must link using this library.

Static Library Files for OpenVMS

Library File	Description
LIBTIBEMS.OLB	All programs must link this library.
LIBCRYPTO.OLB LIBSSL.OLB	Programs that use SSL must link these libraries.
LIBZ.OLB	Programs that use data compression must link this library.
LIBTIBEMSADMIN.OLB	Programs that use the C administration library must link this library.
LIBTIBEMSUFO.OLB	Programs that use the C unshared state failover library must link using this library.

C# Programmer's Checklist

Developers of EMS C# programs can use this checklist during the four phases of the development cycle.

The EMS .NET client libraries are built to the .NET Standard 2.0 specification. They can be used to build both .NET Framework applications, which can only run on Windows, and .NET Core applications, which can run on both Windows and Linux.

Install

Install the EMS software release, which automatically includes the EMS assembly DLLs in the *EMS_HOME\bin* subdirectory.

Code

Import the correct EMS assembly (see the following table).

Version	DLL
.NET API	TIBCO.EMS.dll
.NET Administration API	TIBCO.EMS.ADMIN.dll
.NET Unshared State API	TIBCO.EMS.UFO.dll

Compile

Both .NET Framework and .NET Core applications can be built using the Microsoft `dotnet build` tool, C# project files (*.csproj) and, optionally, solution files (*.sln).

For example, to build a .NET Framework EMS application:

```
> dotnet build my-EMS-net-program.csproj -f net472
```

This will create a .NET Framework executable application: `my-EMS-net-program.exe`.

And to build a .NET Core EMS application:

```
> dotnet build my-EMS-net-core-program.csproj -f netcoreapp2.1
```

This will create a .NET Core DLL application: `my-EMS-net-core-program.dll`.

The `EMS_HOME/samples/cs` and `EMS_HOME/samples/cs/admin` directories contain sample C# project files (*.csproj) and solution files (*.sln) that are used to build the .NET Framework and .NET Core sample applications.

Run

The .NET Framework application built in the above example can be executed directly in the .NET Framework environment:

```
> my-EMS-net-program.exe
```

The .NET Core application built in the above example can be executed in the .NET Core runtime environment:

```
> dotnet my-EMS-net-core-program.dll
```

- In the .NET Framework environment, the EMS assembly must be in the global assembly cache (this location is preferred), or in the system path, or in the same directory as your program executable.
- In the .NET Framework environment, to automatically upgrade to the latest .NET assemblies, include the appropriate policy file in the global cache. See [Automatic Upgrades Between Versions](#) for more information.
- In the .NET Core environment, the EMS assembly must be in the same directory as your application executable.
- In both the .NET Framework and .NET Core environments, the application must be able to connect to a EMS server process (tibemsd).

Assembly Versioning in the Windows .NET Framework Environment

TIBCO Enterprise Message Service assembly DLLs are versioned using the format `1.0.release.version`, where *release* is the EMS release number and *version* is an arbitrary value. For example, the assembly version number for software release 8.2.0 is similar to 1.0.820.8.

Automatic Upgrades Between Versions

In order to allow for seamless upgrades between releases, the TIBCO Enterprise Message Service installation includes policy and configuration files that redirect existing applications from an older assembly to the newest assembly. There is a policy and configuration file for each EMS library:

- A `policy.1.0.assembly` file. For example, `policy.1.0.TIBCO.EMS.dll`. The policy file must be included in the global cache to enable automatic upgrades.
- An `assembly.config` file. For example, `TIBCO.EMS.dll.config`. The configuration file must be present when the related policy file is added to the global cache.

The following table shows the policy and configuration files for each EMS assembly.

Version	Files
.NET API	policy.1.0.TIBCO.EMS.dll TIBCO.EMS.dll.config
.NET Administration API	policy.1.0.TIBCO.EMS.ADMIN.dll TIBCO.EMS.ADMIN.dll.config
.NET Unshared State API	policy.1.0.TIBCO.EMS.UFO.dll TIBCO.EMS.UFO.dll.config

Enabling Updates

To enable automatic updates for a library, add the appropriate policy file to the global cache. Note that the related configuration file must be located in the directory with the policy file in order to add the policy file to the global cache.

Disabling Automatic Upgrades

If you do not want your older applications to automatically move to the newer version, do not include the policy DLL in the global cache. When the `policy.1.0.assembly` file is absent, the client application is not upgraded.

Running Multiple Clients from Different EMS Releases

To deploy two or more applications that are built with different TIBCO Enterprise Message Service releases:

- Build clients using the different .NET client assemblies.
- Include all desired versions of the .NET client assemblies in the global cache.
- Do not include the `policy` DLL in the global cache.

Excluded Features and Restrictions

This section summarizes features that are not available in the .NET library.

Feature	Framework	Core
Distributed transactions	Yes	No
XA protocols for external transactions managers	No	No
ConnectionConsumer, ServerSession, ServerSessionPool	No	No
LDAP JNDI Lookups	Yes	Windows only

Character Encoding

.NET programs represent strings within messages as byte arrays. Before sending an outbound message, EMS programs translate strings to their byte representation using an encoding, which the program specifies. Conversely, when EMS programs receive inbound messages, they reconstruct strings from byte arrays using the same encoding.

When a program specifies an encoding, it applies to all strings in message bodies (names and values), and properties (names and values). It does not apply to header names nor values. The method `BytesMessage.WriteUTF` always uses UTF-8 as its encoding.

Outbound Messages

Programs can determine the encoding of strings in outbound messages in three ways:

- Use the default global encoding, UTF-8.
- Set a non-default global encoding (for all outbound messages) using `Tibems.SetEncoding`.
- Set the encoding for an individual message using `Tibems.SetMessageEncoding`.

Inbound Messages

An inbound message from another EMS client explicitly announces its encoding. A receiving client decodes the message using the proper encoding.

For more information about character encoding, see [Character Encoding in Messages](#).

Connection Factories

A client must connect to a running instance of the EMS server to perform any JMS operations. A connection factory is an object that encapsulates the data used to define a client connection to an EMS server. The minimum factory parameters are the type of connection and the URL for the client connection to the EMS server.

A connection factory is either dynamically created by the application or obtained from a data store by means of a naming service, such as a Java Naming and Directory Interface (JNDI) server or a Lightweight Directory Access Protocol (LDAP) server.

Looking up Connection Factories

EMS provides a JNDI implementation that can be used to store connection factories. Java, C, and C# clients can use the EMS JNDI implementation to lookup connection factories.

You can also store connection factories in any JNDI-compliant naming service or in an LDAP server. Java clients can lookup connection factories in any JNDI-compliant naming service. C and C# clients use LDAP servers.

[Look up Administered Objects Stored in EMS](#) describes how to lookup a connection factory from an EMS server. How to create connection factories in a EMS server is described in [Create and Modify Administered Objects in EMS](#).

Dynamically Creating Connection Factories

Normally client applications use JNDI to look up a Connection Factory object. However, some situations require clients to connect to the server directly. To connect to the EMS server directly, the application must dynamically create a connection factory.

The following examples show how to create a connection factory in each supported language for JMS connections. Each API also supports connection factories for JMS XA connections.

In each example, the `serverUrl` parameter in these expressions is a string defining the protocol and the address of the running instance of the EMS Server. The `serverUrl` parameter has the form:

```
serverUrl = protocol://host:port
```

The supported *protocols* are `tcp` and `ssl`. For example:

```
serverUrl = tcp://server0:7222
```

For a fault-tolerant connection, you can specify two or more URLs. For example:

```
serverUrl = tcp://server0:7222,tcp://server1:7344
```

See [Configure Clients for Shared State Failover Connections](#) for more information. For details on using SSL for creating secure connections to the server, see [Configure SSL in EMS Clients](#) and [Create Connection Factories for Secure Connections](#).

- Java

To dynamically create a `TibjmsConnectionFactory` object in a Java client:

```
ConnectionFactory factory = new
    com.tibco.tibjms.TibjmsConnectionFactory(serverUrl);
```

See the `tibjmsMsgProducer.java` sample client for a working example.

- C

To dynamically create a `tibemsConnectionFactory` type in a C client:

```
factory = tibemsConnectionFactory_Create();
status = tibemsConnectionFactory_SetServerURL(
    factory, serverUrl);
```

See the `tibemsMsgProducer.c` sample client for a working example.

- C#

To dynamically create a `ConnectionFactory` object in a C# client:

```
ConnectionFactory factory = new
    TIBCO.EMS.ConnectionFactory(serverUrl);
```

See the `csMsgProducer.cs` sample client for a working example.

Set Connection Attempts, Timeout and Delay Parameters

By default, a client will attempt to connect to the server two times with a 500 ms delay between each attempt.

A client can modify this behavior by setting new connection attempt count and delay values. There are also a number of factors that may cause a client to hang while attempting to create a connection to the EMS server, so you can set a connection timeout value to abort a connection attempt after a specified period of time. For best results, timeouts should be at least 500 milliseconds. EMS also allows you to establish separate count, delay and timeout settings for reconnections after a fault-tolerant failover, as described in [Set Reconnection Failure Parameters](#).

The following examples establish a connection count of 10, a delay of 1000 ms and a timeout of 1000 ms.

- Java

Use the `TibjmsConnectionFactory` object's `setConnAttemptCount()`, `setConnAttemptDelay()`, and `setConnAttemptTimeout()` methods to establish new connection failure parameters:

```
factory.setConnAttemptCount(10);
factory.setConnAttemptDelay(1000);
factory.setConnAttemptTimeout(1000);
```

- C

Use the `tibemsConnectionFactory_SetConnectAttemptCount` and `tibemsConnectionFactory_SetConnectAttemptDelay` functions to establish new connection failure parameters:

```
status = tibemsConnectionFactory_SetConnectAttemptCount(
    factory, 10);
status = tibemsConnectionFactory_SetConnectAttemptDelay(
    factory, 1000);
status = tibemsConnectionFactory_SetConnectAttemptTimeout(
    factory, 1000);
```

- C#

Use the `ConnectionFactory.SetConnAttemptCount`, `ConnectionFactory.SetConnAttemptDelay`, and `ConnectionFactory.SetConnAttemptTimeout` and methods to establish new connection failure parameters:

```
factory.setConnAttemptCount(10);
factory.setConnAttemptDelay(1000);
factory.setConnAttemptTimeout(1000);
```

Connect to the EMS Server

A connection with the EMS server is defined by the `Connection` object obtained from a `ConnectionFactory`.

For more information, see [Connection Factories](#).

A connection is a fairly heavyweight object, so most clients will create a connection once and keep it open until the client exits. Your application can create multiple connections, if necessary.

The following examples show how to create a `Connection` object.

- Java

Use the [TibjmsConnectionFactory](#) object's [createConnection\(\)](#) method to create a [Connection](#) object:

```
Connection connection =
    factory.createConnection(userName,password);
```

See the `tibjmsMsgProducer.java` sample client for a working example.

- C

Use the `tibemsConnectionFactory_CreateConnection` function to create a connection of type `tibemsConnection`:

```
tibemsConnection connection = NULL;
status = tibemsConnectionFactory_CreateConnection(factory,
    &connection, userName, password);
```

If there is no connection factory, a C client can use the `tibemsConnection_Create` function to dynamically create a `tibemsConnection` type:

```
status = tibemsConnection_Create(&connection,
    serverUrl,NULL,userName,password);
```

The `tibemsConnection_Create` function exists for backward compatibility, but the recommended procedure is that you create `tibemsConnection` objects from factories.

See the `tibemsMsgProducer.c` sample client for a working example.

- C#

Use the [ConnectionFactory.CreateConnection](#) method to create a [Connection](#) object:

```
Connection connection =
    factory.CreateConnection(userName, password);
```

See the `csMsgProducer.cs` sample client for a working example.

Start, Stop and Close a Connection

Before consuming messages, the Message Consumer client must "start" the connection. If you wish to temporarily suspend message delivery, you can "stop" the connection. When a client application exits, all open connections must be "closed."

See [Create a Message Consumer](#) for more details about Message Consumers.

Unused open connections are eventually closed, but they do consume resources that could be used for other applications. Closing a connection also closes any sessions created by the connection.

See the "start," "stop" and "close" methods for the Java [Connection](#) object, the C `tibemsConnection` type, and the C# [Connection](#) object.

Create a Session

A Session is a single-threaded context for producing or consuming messages. You create Message Producers or Message Consumers using Session objects.

A Session can be transactional to enable a group of messages to be sent and received in a single transaction. A non-transactional Session can define the acknowledge mode of message objects received by the session. See [Message Acknowledgement](#) for details.

- Java

Use the [Connection](#) object's [createSession\(\)](#) method to create a [Session](#) object.

For example, to create a Session that uses the default `AUTO_ACKNOWLEDGE` session mode:

```
Session session = connection.createSession();
```

The EMS extended session modes, such as [NO_ACKNOWLEDGE](#), require that you include the `com.tibco.tibjms.Tibjms` constant when you specify the EMS session mode. For example, to create a Session that uses the `NO_ACKNOWLEDGE` session mode:

```
Session session = connection.createSession(
    com.tibco.tibjms.Tibjms.NO_ACKNOWLEDGE);
```

See the `tibjmsMsgProducer.java` sample client for a working example.

- C

Use the `tibemsConnection_CreateSession` function to create a session of type `tibemsSession`:

```
tibemsSession session = NULL;
status = tibemsConnection_CreateSession(connection,
    &session, TIBEMS_FALSE, TIBEMS_AUTO_ACKNOWLEDGE);
```

See the `tibemsMsgProducer.c` sample client for a working example.

- C#

Use the `Connection.CreateSession` method to create a Session object:

```
Session session = connection.CreateSession(false,
    Session.AUTO_ACKNOWLEDGE);
```

See the `csMsgProducer.cs` sample client for a working example.

Set an Exception Listener

All the APIs support the ability to set an exception listener on the connection that gets invoked when a connection breaks or experiences a fault-tolerant failover.

When the event is a disconnect, the exception handler can call various EMS methods without any problem. However, when the event is a fault-tolerant failover, the exception handler is not allowed to call any EMS method. To do so risks a deadlock. You can call the `setExceptionOnFTSwitch` method to receive an exception that contains the new server URL after a fault-tolerant failover has occurred.

The following examples demonstrate how to establish an exception listener for a connection.

- Java

Implement an `ExceptionListener.onException` method, use the `Connection` object's `setExceptionListener` method to register the exception listener, and call `Tibjms.setExceptionOnFTSwitch` to call the exception handler after a fault-tolerant failover:

```
public class tibjmsMsgConsumer
    implements ExceptionListener
{
    .....
    public void onException(JMSEException e)
    {
        /* Handle exception */
    }
    .....
    connection.setExceptionListener(this);
    com.tibco.tibjms.Tibjms.setExceptionOnFTSwitch(true);
    .....
}
```

See the `tibjmsMsgConsumer.java` sample client for a working example (without the `setExceptionOnFTSwitch` call).

- C

Define an `onException` function to handle exceptions, use the `tibemsConnection_SetExceptionListener` function to call `onException` when an error is encountered, and call `tibems_setExceptionOnFTSwitch` to call the exception handler after a fault-tolerant failover:

```
void onException(
    tibemsConnection conn,
```

```

        tibems_status      reason,
        void*              closure)
    {
        /* Handle exception */
    }
    .....
    status = tibemsConnection_SetExceptionListener(
                                                connection,
                                                onException,
                                                NULL);
    tibems_setExceptionOnFTSwitch(TIBEMS_TRUE);

```

See the `tibemsMsgConsumer.c` sample client for a working example (without the `setExceptionOnFTSwitch` call).

- C#

Implement an `IExceptionListener.OnException` method, set the `Connection` object's `ExceptionListener` property to register the exception listener, and call `Tibems.SetExceptionOnFTSwitch` to call the exception handler after a fault-tolerant failover:

```

public class csMsgConsumer : IExceptionListener
{
    .....
    public void OnException(EMSEException e)
    {
        /* Handle exception */
    }
    .....
    connection.ExceptionListener = this;
    TIBCO.EMS.Tibems.SetExceptionOnFTSwitch(true);
    .....
}

```

See the `csMsgConsumer.cs` sample client for a working example (without the `setExceptionOnFTSwitch` call).

Dynamically Create Topics and Queues

EMS provides a JNDI implementation that can be used to store topics and queues. Java, C, and C# clients can use the EMS JNDI implementation to lookup topics and queues.

You can also store topics and queues in any JNDI-compliant naming service or in an LDAP server. Java clients can lookup topics and queues in any JNDI-compliant naming service. C and C# clients use LDAP servers.

[Look up Administered Objects Stored in EMS](#) describes how to lookup topics and queues from an EMS server.

Clients can also create destinations as needed. If a client requests the creation of a destination that already exists, the existing destination is used. If the destination does not exist, and the specification of the `topics.conf`, `queues.conf`, or `acl.conf` files allow the destination, the server dynamically creates the new destination. The new destination inherits properties and permissions from its ancestors as described in [Wildcards and Dynamically Created Destinations](#). The destination is managed by the server as long as clients that use the destination are running.



Because dynamic destinations do not appear in the configuration files, a client cannot use JNDI to lookup dynamically created queues and topics.

The following examples show how to create destinations dynamically:

- Java

Use the `Session` object's `createTopic()` method to create a topic as a `Destination` object:

```
Destination topic = session.createTopic(topicName);
```

Use the `Session` object's `createQueue()` method to create a queue as a `Destination` object:

```
Destination queue = session.createQueue(queueName);
```

See the `tibjmsMsgProducer.java` sample client for a working example.

- C

Use the `tibemsTopic_Create` function to create a topic of type `tibemsDestination`:

```
tibemsDestination topic = NULL;
status = tibemsTopic_Create(&topic, topicName);
```

Use the `tibemsQueue_Create` function to create a queue of type `tibemsDestination`:

```
tibemsDestination queue = NULL;
status = tibemsQueue_Create(&queue, queueName);
```

See the `tibemsMsgProducer.c` sample client for a working example.

- C#

Use the `Session.CreateTopic` method to create a `Topic` object:

```
Destination topic = session.CreateTopic(topicName);
```

Use the `Session.CreateQueue` method to create a `Queue` object:

```
Destination queue = session.CreateQueue(queueName);
```

See the `csMsgProducer.cs` sample client for a working example.

Create a Message Producer

A *Message Producer* is an EMS client that either publishes messages to a topic or sends messages to a queue. When working with topics, a Message Producer is commonly referred to as a *Publisher*.

Optionally, when creating a Message Producer, you can set the destination to NULL and specify the destination when you send or publish a message, as described in [Send Messages](#).

You must have [send](#) permission on a queue to create a message producer that sends messages to that queue. You must have [durable](#) permission on the topic to create a new durable subscriber for that topic, and have at least [use_durable](#) permission on the topic to attach to an existing durable subscriber for the topic. See [User Permissions](#) for details.

The following examples create a message producer that sends messages to the queue that was dynamically created in [Dynamically Create Topics and Queues](#).

- Java

Use the `Session` object's `createProducer()` method to create a `MessageProducer` object:

```
MessageProducer QueueSender = session.createProducer(queue);
```

See the `tibjmsMsgProducer.java` sample client for a working example.

- C

Use the `tibemsSession_CreateProducer` function to create a message producer of type `tibemsMsgProducer`:

```
tibemsMsgProducer QueueSender = NULL;
status = tibemsSession_CreateProducer(session,
&QueueSender, queue);
```

See the `tibemsMsgProducer.c` sample client for a working example.

- C#

Use the `Session.CreateProducer` method to create a `MessageProducer` object:

```
MessageProducer QueueSender = session.CreateProducer(queue);
```

See the `csMsgProducer.cs` sample client for a working example.

Configure a Message Producer

A message producer can be configured to generate messages with default headers and properties that define how those messages are to be routed and delivered.

Specifically, you can:

- Set the producer's default delivery mode.
- Set whether message IDs are disabled.
- Set whether message timestamps are disabled.
- Set the producer's default priority.
- Set the default length of time that a produced message should be retained by the message system.

For example, as described in the [Message Delivery Modes](#), you can set the message deliver mode to either PERSISTENT, NON_PERSISTENT, or RELIABLE_DELIVERY.

- Java

Use the `MessageProducer` object's `setDeliveryMode()` method to configure your Message Producer with a default delivery mode of RELIABLE_DELIVERY:

```
QueueSender.setDeliveryMode(
    com.tibco.tibjms.Tibjms.RELIABLE_DELIVERY);
```

To configure the Message Producer with a default delivery mode of NON_PERSISTENT:

```
QueueSender.setDeliveryMode(
    javax.jms.DeliveryMode.NON_PERSISTENT);
```

See the `tibjmsMsgProducerPerf.java` sample client for a working example.



Delivery mode cannot be set by using the `Message.setJMSDeliveryMode()` method. According to the JMS specification, the publisher ignores the value of the `JMSDeliveryMode` header field when a message is being published.

- C

Use the `tibemsMsgProducer_SetDeliveryMode` function to configure your Message Producer to set a default delivery mode for each message it produces to RELIABLE_DELIVERY:

```
tibems_int deliveryMode = TIBEMS_RELIABLE;
status tibemsMsgProducer_SetDeliveryMode(QueueSender,
    deliveryMode);
```

- C#

Set the `DeliveryMode` on the `MessageProducer` object to RELIABLE_DELIVERY:

```
QueueSender.DeliveryMode = DeliveryMode.RELIABLE_DELIVERY;
```

See the `csMsgProducerPerf.cs` sample client for a working example.

Create a Completion Listener for Asynchronous Sending

TIBCO Enterprise Message Service provides APIs for a Message Producer to send messages either synchronously or asynchronously. For asynchronous sending, you need to implement a `CompletionListener` that serves as an asynchronous event handler for message send result notification.

A completion listener implementation has two methods: `onCompletion()` is invoked after a message has successfully been sent, and `onException()` is invoked if the send failed. These methods are invoked in a different thread from that in which the message was sent. You implement the methods to perform the desired actions when the application is notified of send success or failure. Your implementation should handle all exceptions, and it should not throw any exceptions.

Once you create a completion listener, you pass it as an argument into the `MessageProducer` `send` method, or into the `JMSProducer` `setAsync()` method. If passed into the `JMSProducer` `setAsync` method, the `JMSProducer` will always send asynchronously.

- Java

Create an implementation of the `CompletionListener` interface, create a `CompletionListener` and pass that into the appropriate `send` method:

```
/* create connection, session, producer, message */
TibjmsCompletionListener completionListener = new
    TibjmsCompletionListener();
msgProducer.send(destination, msg, completionListener);
```

Create a `CompletionListener` class and implement the `onCompletion()` and `onException()` method to perform the desired actions when a message arrives:

```
class TibjmsCompletionListener implements CompletionListener
{
    public void onCompletion(Message msg)
    {
        /* Handle the send success case for the message */
    }
    public void onException(Message msg, Exception ex)
    {
        /* Handle the send failure case for the message */
    }
}
```

See the `tibjmsMsgProducer.java` sample client for a working example.

- C

In C, implement an `onCompletion()` function to perform the desired actions when a message is sent:

```
static void
onCompletion(tibemsMsg msg, tibems_status status, void* closure)
{
    if (status == TIBEMS_OK)
    {
        /* Handle the send success case for the message */
    }
    else
    {
        /* Handle the send failure case for the message */
    }
}
/* Create a connection, session, and producer. When sending, pass
 * the onCompletion() function as the tibemsMsgCompletionCallback
 */
status = tibemsMsgProducer_AsyncSend(producer, msg, onCompletion, NULL);
```

See the `tibemsMsgProducer.c` sample client for a working example.

- C#

Create an implementation of the `ICompletionListener` interface, create a `CompletionListener` and pass that into the appropriate `send` method.

```
EMSCpletionListener completionListener = new EMSCpletionListener();
producer.Send(destination, msg, completionListener);
```

Create an implementation of the `IMessageListener` interface to perform actions when a message is sent:

```
class EMSCpletionListener : ICompletionListener
{
    public void OnCompletion(Message msg)
    {
        /* Handle the send success case for the message */
    }
    public void OnException(Message msg, Exception ex)
    {
    }
}
```

```

    /* Handle the send failure case for the message */
  }
}

```

See the `csMsgProducer.cs` sample client for a working example.

Create a Message Consumer

Message consumers are clients that receive messages published to a topic or sent to a queue. When working with topics, a Message Consumer is commonly referred to as a *Subscriber*.

A Message Consumer can be created with a "message selector" that restricts the consumption of message to those with specific properties. When creating a Message Consumer for topics, you can set a `noLocal` attribute that prohibits the consumption of messages that are published over the same connection from which they are consumed.

Carefully consider the message selectors that are used with queue consumers. Because messages that do not match a queue consumer's message selectors remains in the queue until it is retrieved by another consumer, a non-matching message can experience many failed selectors. This is especially so when queue consumers connect, consume a message, and immediately disconnect.

As described in [Durable Subscribers for Topics](#), messages published to topics are only consumed by active subscribers to the topic; otherwise the messages are not consumed and cannot be retrieved later. You can create a durable subscriber that ensures messages published to a topic are received by the subscriber, even if it is not currently running. For queues, messages remain on the queue until they are either consumed by a Message Consumer, the message expiration time has been reached, or the maximum size of the queue is reached.

The following examples create a Message Consumer that consumes messages from the queue and a durable subscriber that consumes messages from a topic. The queue and topic are those that were dynamically created in [Dynamically Create Topics and Queues](#).



The `createDurableSubscriber` method either creates a new durable subscriber for a topic or attaches the client to a previously created durable subscriber. A user must have [durable](#) permission on the topic to create a new durable subscriber for that topic. A user must have at least [use_durable](#) permission on the topic to attach to an existing durable subscriber for the topic. See [User Permissions](#) for details.

- Java

Use the `Session` object's `createConsumer()` method to create a `MessageConsumer` object:

```
MessageConsumer QueueReceiver = session.createConsumer(queue);
```

See the `tibjmsMsgConsumer.java` sample client for a working example.

The following `Session.createDurableSubscriber()` method creates a durable subscriber, named "MyDurable":

```
TopicSubscriber subscriber =
    session.createDurableSubscriber(topic, "myDurable");
```

See the `tibjmsDurable.java` sample client for a working example.

Shared Subscriptions

Use the `Session` object's `createSharedConsumer()` method to create or add to a shared subscription:

```
MessageConsumer cons1 = session.createSharedConsumer(topic, "mySharedSub");
MessageConsumer cons2 = session.createSharedConsumer(topic, "mySharedSub");
```

`cons1` and `cons2` are two shared consumers on the same subscription called `mySharedSub`. If a message is published to the topic, then one of those two consumers will receive it. Note that shared consumers on a given subscription do not have to use the same session/connection.

Use the Session object's `createSharedDurableConsumer()` method to create or add to a shared durable subscription:

```
MessageConsumer cons1 = session.createSharedDurableConsumer(topic,
    "myDurableSharedSub");
MessageConsumer cons2 = session.createSharedDurableConsumer(topic,
    "myDurableSharedSub");
```

`cons1` and `cons2` are two shared durable consumers on the same durable subscription called `myDurableSharedSub`. If a message is published to the topic, then one of those two consumers will receive it. Note that shared durable consumers on a given subscription do not have to use the same session/connection.

- C

Use the `tibemsSession_CreateConsumer` function to create a message consumer of type `tibemsMsgConsumer`:

```
tibemsMsgConsumer QueueReceiver = NULL;
status = tibemsSession_CreateConsumer(session,
    &QueueReceiver, queue, NULL, TIBEMS_FALSE);
```

See the `tibemsMsgConsumer.c` sample client for a working example.

The following `tibemsSession_CreateDurableSubscriber` function creates a durable subscriber, named "myDurable," of type `tibemsMsgConsumer`:

```
tibemsMsgConsumer msgConsumer = NULL;
status = tibemsSession_CreateDurableSubscriber(session,
    &msgConsumer, topic, "myDurable",
    NULL, TIBEMS_FALSE);
```

See the `tibemsDurable.c` sample client for a working example.

- C#

Use the `Session.CreateConsumer` method to create a `MessageConsumer` object:

```
MessageConsumer QueueReceiver = session.createConsumer(queue);
```

See the `csMsgConsumer.cs` sample client for a working example.

The following `Session.CreateDurableSubscriber` method creates a durable subscriber, named "MyDurable":

```
TopicSubscriber subscriber =
    session.CreateDurableSubscriber(topic, "myDurable");
```

See the `csDurable.cs` sample client for a working example.

Create a Message Listener for Asynchronous Message Consumption

EMS allows a Message Consumer to consume messages either synchronously or asynchronously. For synchronous consumption, the Message Consumer explicitly calls a receive method on the topic or queue. For asynchronous consumption, you can implement a *Message Listener* that serves as an asynchronous event handler for messages.

A Message Listener implementation has one method, `onMessage`, that is called by the EMS server when a message arrives on a destination. You implement the `onMessage` method to perform the desired actions when a message arrives. Your implementation should handle all exceptions, and it should not throw any exceptions.

Once you create a Message Listener, you must register it with a specific Message Consumer before calling the connection's `start` method to begin receiving messages.

A Message Listener is not specific to the type of the destination. The same listener can obtain messages from a queue or a topic, depending upon the destination set for the Message Consumer with which the listener is registered.



The J2EE 1.3 platform introduced message-driven beans (MDBs) that are a special kind of Message Listener. See the J2EE documentation for more information about MDBs.

- Java

Create an implementation of the [MessageListener](#) interface, create a [MessageConsumer](#), and use the [MessageConsumer](#) object's [setMessageListener\(\)](#) method to register the Message Listener with the Message Consumer:

```
public class tibjmsAsyncMsgConsumer implements MessageListener
{
    /* Create a connection, session and consumer */
    ...
    MessageConsumer QueueReceiver =
        session.createConsumer(queue);
    QueueReceiver.setMessageListener(this);
    connection.start();
}
```



Do not use the [Session.setMessageListener\(\)](#) method, which is used by application servers, rather than by applications.

Implement the [onMessage\(\)](#) method to perform the desired actions when a message arrives:

```
public void onMessage(Message message)
{
    /* Process message and handle exceptions */
}
```

See the `tibjmsAsyncMsgConsumer.java` sample client for a working example.

- C

Implement an [onMessage\(\)](#) function to perform the desired actions when a message arrives:

```
void onMessage(tibemsMsgConsumer QueueReceiver,
               tibemsMsg message, void* closure)
{
    /* Process message and handle exceptions */
}
```

In another function, that creates a `tibemsMsgConsumer` and uses the `tibemsMsgConsumer_SetMsgListener` function to create a message listener for the Message Consumer, specifying `onMessage()` as the callback function:

```
void run()
{
    tibemsMsgConsumer QueueReceiver = NULL;
    /* Create a connection, session and consumer */
    ...
    status = tibemsSession_CreateConsumer(session,
        &QueueReceiver, queue, NULL, TIBEMS_FALSE);
    status = tibemsMsgConsumer_SetMsgListener(QueueReceiver,
        onMessage, NULL);
    status = tibemsConnection_Start(connection);
}
```

See the `tibemsAsyncMsgConsumer.c` sample client for a working example.

- C#

Create an implementation of the [IMessageListener](#) interface, use [Session.CreateConsumer](#) to create a [MessageConsumer](#), and set the `MessageListener` property on the `MessageConsumer` object to register the Message Listener with the Message Consumer:

```
public class csAsyncMsgConsumer : IMessageListener
{
    /* Create a connection, session and consumer */
    ...
    MessageConsumer QueueReceiver =
        session.CreateConsumer(queue);
    QueueReceiver.MessageListener = this;
    connection.Start();
}
```

Implement the [IMessageListener.OnMessage](#) method to perform the desired actions when a message arrives:

```
public void OnMessage(Message message) {
    try
    {
        /* Process message and handle exceptions */
    }
}
```

See the `csAsyncMsgConsumer.cs` and `csAsyncMsgConsumerUsingDelegate.cs` sample clients for working examples.

Messages

Messages are a self-contained units of information used by JMS applications to exchange data or request operations.

Create Messages

As described in [JMS Message Bodies](#), EMS works with the following types of messages:

- Messages with no body
- Text Messages
- Map Messages
- Bytes Messages
- Stream Messages
- Object Messages

There is a separate create method for each type of message.

The following examples show how to create a simple text message containing the string "Hello."

- Java

Use the [Session](#) object's `createTextMessage()` method to create a [TextMessage](#):

```
TextMessage message = session.createTextMessage("Hello");
```

See the `tibjmsMsgProducer.java` sample client for a working example.

- C

Use the `tibemsTextMsg_Create` function to create a text message of type `tibemsTextMsg`:

```
tibemsTextMsg message = "Hello";
status = tibemsTextMsg_Create(&message);
```

See the `tibemsMsgProducer.c` sample client for a working example.

- C#

Use the [Session.CreateTextMessage](#) method to create text message of type [TextMessage](#):

```
TextMessage message = session.CreateTextMessage("Hello");
```

See the `csMsgProducer.cs` sample client for a working example.

Set and Get Message Properties

Before a client sends a message, it can use a "set property" method to set the message properties. The client can check the message properties with a "get property" method.

For more information on message properties, see [EMS Message Properties](#).

- Java

Use the `Message` object's `setBooleanProperty()` method to set the `JMS_TIBCO_PRESERVE_UNDELIVERED` property to true:

```
message.setBooleanProperty("JMS_TIBCO_PRESERVE_UNDELIVERED",
                           true);
```

Use the `getStringProperty()` method to get the user ID of the `JMS_TIBCO_SENDER`:

```
userID = message.getStringProperty("JMS_TIBCO_SENDER");
```

- C

Use the `tibemsMsg_SetBooleanProperty` function to set the `JMS_TIBCO_PRESERVE_UNDELIVERED` property to true:

```
status = tibemsMsg_SetBooleanProperty(message,
                                       "JMS_TIBCO_PRESERVE_UNDELIVERED", true);
```

Use the `tibemsMsg_GetStringProperty` function to get the user ID of the `JMS_TIBCO_SENDER`:

```
char* userID = NULL;
status = tibemsMsg_GetStringProperty(message,
                                       "JMS_TIBCO_SENDER", &userID);
```

- C#

Use the `Message.SetBooleanProperty` method to set the `JMS_TIBCO_PRESERVE_UNDELIVERED` property to true:

```
message.SetBooleanProperty("JMS_TIBCO_PRESERVE_UNDELIVERED",
                           true);
```

Use the `Message.GetStringProperty` method to get the user ID of the `JMS_TIBCO_SENDER`:

```
string userID = message.GetStringProperty("JMS_TIBCO_SENDER");
```

Send Messages

Use a Message Producer client to send messages to a destination. You can either send a message to the destination specified by the Message Producer or, if the Message Producer specifies NULL as the destination, you can send a message to a specific destination.

In either case, you can optionally set the `JMSDeliveryMode`, `JMSExpiration`, and `JMSPriority` message header fields described in [JMS Message Header Fields](#) when sending each message.

The following examples show different ways to send a text message in each language:

- Send the message to the Message Producer, `QueueSender`, created in [Create a Message Producer](#).
- Use a Message Producer with a NULL destination that sends the message to the topic created in [Dynamically Create Topics and Queues](#).
- Use a Completion Listener, created in [Create a Message Listener for Asynchronous Message Consumption](#), to send the message asynchronously.

See [EMS Extensions to JMS Messages](#) for more information about creating messages.

- Java

Use the `MessageProducer` object's `send()` method to send a message to the destination specified by the `MessageProducer` object:

```
QueueSender.send(message);
```

Use the following form of the `send()` method to send a message to a specific destination:

```
MessageProducer NULLsender = session.createProducer(null);
...
NULLsender.send(topic, message);
```

Use the form of the `send()` method with a completion listener argument to send a message asynchronously:

```
QueueSender.send(message, completionListener);
```

See the `tibjmsMsgProducer.java` sample client for a working example.

- C

Use the `tibemsMsgProducer_Send` function to send a message to the destination specified by the `tibemsMsgProducer`:

```
status = tibemsMsgProducer_Send(QueueSender, message);
```

Use the `tibemsMsgProducer_SendToDestination` function to send the message to a specific destination:

```
status = tibemsMsgProducer_SendToDestination(NULLsender,
                                              topic, message);
```

See the `tibemsMsgProducer.c` sample client for a working example.



Unlike the Java and C# APIs, in the C API, you can use the `tibemsMsgProducer_SendToDestination` function to specify the destination regardless of whether a destination is in the `tibemsMsgProducer`.

- C#

Use the `MessageProducer.Send` method to send a message to the destination specified by the `MessageProducer`:

```
QueueSender.Send(message);
```

Use the following form of the `MessageProducer.Send` method to send a message to a specific destination:

```
MessageProducer NULLsender = session.CreateProducer(NULL);
NULLsender.Send(topic, message);
```

See the `csMsgProducer.cs` sample client for a working example.

Receive Messages

A Message Consumer receives messages from a destination and acknowledges the receipt of messages using the mode established for the session, as described in [Create a Session](#).

Before receiving messages, the Message Consumer must start the connection to the EMS server. Before exiting, the Message Consumer must close the connection.

The following examples start the connection created in [Connect to the EMS Server](#); synchronously receive messages from the queue created in [Dynamically Create Topics and Queues](#), and then close the connection.



You can also implement a Message Listener for your Message Consumer to asynchronously receive messages, as described in [Create a Message Listener for Asynchronous Message Consumption](#).

- Java

Use the [Connection](#) object's `start()` method to start the connection:

```
connection.start();
```

Use the [MessageConsumer](#) object's `receive()` method to receive a message. This is typically used in a loop for the duration the client wishes to receive messages:

```
Message message = QueueReceiver.receive();
```

When the client has finished receiving messages, it uses the `Close()` method to close the connection:

```
connection.close();
```

See the `tibjmsMsgConsumer.java` sample client for a working example.

- C

Use the `tibemsConnection_Start` function to start the connection:

```
status = tibemsConnection_Start(connection);
```

Use the `tibemsMsgConsumer_Receive` function to receive a message. This is typically used in a loop for the duration the client wishes to receive messages:

```
tibemsMsg message = NULL;
status = tibemsMsgConsumer_Receive(QueueReceiver,&message);
```

When the client has finished receiving messages, use the `tibemsConnection_Close` function to close the connection:

```
status = tibemsConnection_Close(connection);
```

See the `tibemsMsgConsumer.c` sample client for a working example.

- C#

Use the `Connection.Start` function to start the connection:

```
connection.Start();
```

Use the `MessageConsumer.Receive` function to receive a message. This is typically used in a loop for the duration the client wishes to receive messages:

```
Message message = QueueReceiver.receive();
```

When the client has finished receiving messages, use the `Connection.Close` function to close the connection:

```
connection.Close();
```

See the `csMsgConsumer.cs` sample client for a working example.

The EMS Implementation of JNDI

The EMS server provides a implementation of JNDI that enables you to lookup connection factories, topics and queues, which are collectively referred to as administered objects. Java clients can look up administered objects stored in EMS using standard JNDI calls. The C and C# APIs provide similar calls to look up object data in the EMS server.

How to create topics and queues is described in [Creating and Modifying Destinations](#).

Create and Modify Administered Objects in EMS

You can create administered objects for storage in EMS using either the administration tool or the administration APIs, or directly in the configuration files. This section describes how to create administered objects using the administration tool.

To create a connection factory, use the `create factory` command in the EMS Administration Tool. For example, to create a generic connection factory, named *myFactory*, that establishes a TCP connection to port 7344 on *server1*, start the EMS Administration Tool and enter:

```
create factory myFactory generic URL=tcp://server1:7344
```

The connection factory data stored on the EMS server is located in the `factories.conf` file. You can use the `show factories` command to list all of the connection factories on your EMS server and the `show factory` command to show the configuration details of a specific connection factory.

A connection factory may include optional properties for balancing server load and establishing thresholds for attempted connections, as described in [Connection Factory Parameters](#). These properties can be specified when creating the factory or modified for an existing factory using the `addprop factory`, `setprop factory`, and `removeprop factory` commands.

For example, to set the maximum number of connection attempts for the connection factory, *myFactory*, from the default value of 2 to 5, start the EMS Administration Tool and enter:

```
addprop factory myFactory connect_attempt_count=5
```

And to reset the value back to 2, enter:

```
setprop factory myFactory connect_attempt_count=2
```

Create Connection Factories for Secure Connections

This topic describes how to create a static connection factory for establishing an SSL connection.

Similar SSL parameters must be used when looking up the connection factory, as described in [Perform Secure Lookups](#).

Connections that are to be secured using SSL identify the transport protocol as 'ssl' and may include any number of the SSL configuration parameters listed in [SSL Server Parameters](#).

For example, to create a generic connection factory, named *mySecureFactory*, that establishes a SSL connection to port 7243 on *server1*, start the EMS Administration Tool and enter:

```
create factory mySecureFactory generic URL=ssl://server1:7243
```

To create a factory to set up a generic connection and check the server's certificate to confirm the name of the server is *myServer*, enter (all one line):

```
create factory MySSLFactory generic url=ssl://7243 ssl_verify_host=enabled
ssl_expected_hostname=myServer ssl_trusted=certs/server_root.cert.pem
```

To create a factory to set up a topic connection, check the server's certificate (but not the name inside the certificate), and to set the `ssl_auth_only` parameter so that SSL is only used by the client when creating the connection, enter (all one line):

```
create factory AnotherSSLFactory topic url=ssl://7243 ssl_verify_host=enabled
ssl_verify_hostname=disabled ssl_trusted=certs/server_root.cert.pem
ssl_auth_only=enabled
```



These samples assume that the certificate `server_root.cert.pem` is located in "certs" subdirectory of the directory where the server is running.

See [SSL Protocol](#) for details.

Create Connection Factories for Fault-Tolerant Connections

When connecting a fault-tolerant client to EMS, you must specify two or more EMS servers in your connection factory. When creating a connection factory for a fault-tolerant client, specify multiple server URLs in the `url` argument of the create factory command.

For example, to create a generic connection factory, named *myFtFactory*, that establishes TCP connections to port 7545 on the primary server, *server0*, and port 7344 on the secondary server, *server1*, start the EMS Administration Tool and enter (on one line):

```
create factory myFtFactory generic url=tcp://server0:7545,tcp://server1:7344
```

Should *server0* become unavailable, the client will connect to *server1*. See [Fault Tolerance](#) for details.

Look up Administered Objects Stored in EMS

You can lookup objects from an EMS server by name. All clients can lookup objects in the EMS naming service. Alternatively, Java applications can lookup objects in a third-party JNDI server, and C and C# clients can lookup objects in a third-party LDAP server.

To lookup administered objects stored in EMS, you need to create the initial context that identifies the URL of the naming service provider and any other properties, such as the username and password to authenticate the client to the service. The naming service provider URL has form:

```
tibjmsnaming://host:port
```

The following examples demonstrate how to access JMS administered objects when using TIBCO Enterprise Message Service. Each of these examples assume that a connection factory, named *ConFac*, exists in the `factories.conf` file, a `topic.sample` topic exists in `topics.conf`, and a `queue.sample` queue exists in `queues.conf`.

- Java

Create an `InitialContext` object for the initial context, which consists of the provider context factory and JNDI provider URL, as well as the username and password to authenticate the client to the EMS server:

```
Hashtable env = new Hashtable();
env.put(Context.INITIAL_CONTEXT_FACTORY,
        "com.tibco.tibjms.naming.TibjmsInitialContextFactory");
env.put(Context.PROVIDER_URL, "tibjmsnaming://localhost:7222");
env.put(Context.SECURITY_PRINCIPAL, "userName");
env.put(Context.SECURITY_CREDENTIALS, "password");
InitialContext jndiContext = new InitialContext(env);
```

Look up a connection factory, named *ConFac*, and destinations, named *topic.sample* and *queue.sample*, from the initial context:

```
ConnectionFactory factory =
    (javax.jms.ConnectionFactory)
    jndiContext.lookup("ConFac");
javax.jms.Topic sampleTopic =
    (javax.jms.Topic)jndiContext.lookup("topic.sample");
javax.jms.Queue sampleQueue =
    (javax.jms.Queue)jndiContext.lookup("queue.sample");
```

See the `tibjmsJNDI.java` sample client located in the `EMS_HOME/samples/java/JNDI` directory.

- C

Create a `tibemsLookupContext` object for the initial context, which consists of the JNDI provider URL and the username and password to authenticate the client to the EMS server:

```
tibemsLookupContext* contextstatus = NULL;
status = tibemsLookupContext_Create(
```

```
&context,
"tibjmsnaming://localhost:7222",
"userName",
"password");
```

Use the `tibemsLookupContext_LookupConnectionFactory` function to look up a connection factory, named `ConFac`, and use the `tibemsLookupContext_LookupDestination` function to look up the destinations, named `topic.sample` and `queue.sample`, from the initial context:

```
topic.sample
tibemsConnectionFactory factory = NULL;
tibemsDestination sampleTopic = NULL;
tibemsDestination sampleQueue = NULL;

status = tibemsLookupContext_Lookup(context,
                                     "ConFac",
                                     (void*)&factory);
status = tibemsLookupContext_Lookup(context,
                                     "sample.queue",
                                     (void*)&sampleQueue);
status = tibemsLookupContext_Lookup(context,
                                     "topic.sample",
                                     (void*)&sampleTopic);
```

- C#

Create a `ILookupContext` object for the initial context, which consists of the JNDI provider URL and the username and password to authenticate the client to the EMS server.

```
Hashtable env = new Hashtable();
env.Add(LookupContext.PROVIDER_URL,
        "tibjmsnaming://localhost:7222");
env.Add(LookupContext.SECURITY_PRINCIPAL, "myUserName");
env.Add(LookupContext.SECURITY_CREDENTIALS, "myPassword");

LookupContextFactory factory = new LookupContextFactory();
ILookupContext searcher = factory.CreateContext(
    LookupContextFactory.TIBJMS_NAMING_CONT
    EXT,
    env);
```

Use the `ILookupContext.Lookup` method to look up a connection factory, named `ConFac`, and destinations, named `topic.sample` and `queue.sample`, from the initial context:

```
ConnectionFactory factory =
    (ConnectionFactory) searcher.Lookup("ConFac");
Topic sampleTopic =
    (Topic)searcher.Lookup("topic.sample");
TIBCO.EMS.Queue sampleQueue =
    (TIBCO.EMS.Queue)searcher.Lookup("queue.sample");
```

Look Up Objects Using Full URL Names

Java clients can look up administered objects using full URL names. In this case, the `Context.URL_PKG_PREFIXES` property is used in place of the `Context.PROVIDER_URL` property.

For example:

```
Hashtable env = new Hashtable();
env.put(Context.URL_PKG_PREFIXES, "com.tibco.tibjms.naming");
env.put(Context.PROVIDER_URL, "tibjmsnaming://localhost:7222");
env.put(Context.SECURITY_PRINCIPAL, "userName");
env.put(Context.SECURITY_CREDENTIALS, "password");
jndiContext = new InitialContext(env);
```

When using full URL names, you can look up objects like the following example:

```
Topic sampleTopic = (javax.jms.Topic)jndiContext.lookup(
    "tibjmsnaming://jmshost:7222/topic.sample");
Queue sampleQueue = (javax.jms.Queue)jndiContext.lookup(
    "tibjmsnaming://jmshost:7222/queue.sample");
```

For further information on how to use full URL names, refer to the `tibjmsJNDIRead.java` example located in the `EMS_HOME/samples/java/JNDI` directory.

Perform Secure Lookups

TIBCO Enterprise Message Service client programs can perform secure JNDI lookups using the Secure Sockets Layer (SSL) protocol. To accomplish this, the client program must set SSL properties in the environment when the `InitialContext` is created. The SSL properties are similar to the SSL properties for the TIBCO Enterprise Message Service server.

See [SSL Protocol](#) for more information about using SSL in the TIBCO Enterprise Message Service server.

The following examples illustrate how to create an `InitialContext` that can be used to perform JNDI lookups using the SSL protocol.

- Java

In this example, the port number specified for the `Context.PROVIDER_URL` is set to the SSL listen port that was specified in the server configuration file `tibjsmd.conf`. The value for `TibjmsContext.SECURITY_PROTOCOL` is set to `ssl`. Finally, the value of `TibjmsContext.SSL_ENABLE_VERIFY_HOST` is set to `"false"` to turn off server authentication. Because of this, no trusted certificates need to be provided and the client will then not verify the server it is using for the JNDI lookup against the server's certificate.

```
Hashtable env = new Hashtable();
env.put(Context.INITIAL_CONTEXT_FACTORY,
        "com.tibco.tibjms.naming.TibjmsInitialContextFactory");
env.put(Context.PROVIDER_URL, tibjmsnaming://jms host:7223);
env.put(Context.URL_PKG_PREFIXES, "com.tibco.tibjms.naming");
env.put(TibjmsContext.SECURITY_PROTOCOL, "ssl");
env.put(TibjmsContext.SSL_ENABLE_VERIFY_HOST,
        new Boolean("false"));
Context context = new InitialContext(env);
```

- C

Create a `tibemsSSLParams` object and use the `tibemsSSLParams_SetIdentityFile` function to establish the client identity by means of a pkcs12 file. Use the `tibemsLookupContext_CreateSSL` function to create a `tibemsLookupContext` object that uses an SSL connection for the initial context.

```
tibemsLookupContext* context = NULL;
tibemsConnection_Factory factory = NULL;
tibemsSSLParams sslParams = NULL;
tibems_status status = TIBEMS_OK;

sslParams = tibemsSSLParams_Create();
status = tibemsSSLParams_SetIdentityFile(
        ssl_params,
        "client_identity.p12",
        TIBEMS_SSL_ENCODING_AUTO);

status = tibemsLookupContext_CreateSSL(
        &context,
        "tibjmsnaming://localhost:7222",
        "userName",
        "password",
        sslParams,
        "pk_password");
```

- C#

Create a `ILookupContext` object for the initial context over an SSL connection. The SSL Store Info consists of a pkcs12 file that identifies the client and the client's password, which are stored in an `EMSSSLFileStoreInfo` object.

```
string ssl_identity = client_identity.p12;
string ssl_target_hostname = "server";
string ssl_password = "password";

EMSSSLFileStoreInfo StoreInfo = new EMSSSLFileStoreInfo();
info.SetSSLClientIdentity(ssl_identity);
info.SetSSLPassword(ssl_password.ToCharArray());
```

```

Hashtable env = new Hashtable();
env.Add(LookupContext.PROVIDER_URL, "adc1.na.tibco.com:10636");
env.Add(LookupContext.SECURITY_PRINCIPAL, "myUserName");
env.Add(LookupContext.SECURITY_CREDENTIALS, "myPassword");
env.Add(LookupContext.SECURITY_PROTOCOL, "ssl");
env.Add(LookupContext.SSL_TARGET_HOST_NAME,
        ssl_target_hostname);
env.Add(LookupContext.SSL_STORE_TYPE,
        EMSSLStoreType.EMSSL_STORE_TYPE_FILE);
env.Add(LookupContext.SSL_STORE_INFO, StoreInfo);

```

Perform Fault-Tolerant Lookups

TIBCO Enterprise Message Service can perform fault-tolerant JNDI lookups. If the active server fails and the standby server becomes active, the JNDI provider automatically uses the new active server for JNDI lookups. You accomplish this by providing multiple URLs in the `Context.PROVIDER_URL` property when creating the `InitialContext`. Specify more than one URL separated by commas (,) in the property.

Example

The following illustrates setting up the `Context.PROVIDER_URL` property with the URLs of a primary EMS server on the machine named `emshost` and a secondary EMS server on the machine named `backuphost`.

```

env.put(Context.PROVIDER_URL, "tibjmsnaming://jmshost:7222,tibjmsnaming://
backuphost:7222");

```

Assuming `emshost` starts out as active, if at any time it fails the JNDI provider automatically switches to the EMS server on the host `backuphost` for JNDI lookups. If `emshost` is repaired and restarted, it then becomes the standby EMS server.

Limitations of Fault-Tolerant JNDI Lookups

Fault-tolerant JNDI lookups do not occur in scenarios:

- When using full URL names in argument to the lookup method.
- When looking up an object that has been bound into a foreign naming/directory service such as LDAP.

Interoperation with TIBCO FTL


TIBCO Enterprise Message Service can exchange messages with supported versions of TIBCO FTL.



This feature is supported on those platforms where TIBCO FTL is supported. Refer to the respective readme files of TIBCO Enterprise Message Service and TIBCO FTL.

Scope

- EMS can import and export messages to TIBCO FTL through an EMS *topic*.
- EMS can import messages from TIBCO FTL to an EMS *queue* (but queues cannot export).



Do not configure EMS and FTL round-tripping. That is, do not send messages from EMS to FTL and then back to EMS, or the other way around.

Message Translation

EMS and TIBCO FTL use different formats for messages and their data.

When `tibemspd` imports or exports a messages, it translates the message and its data to the appropriate format; for details, see [Message Translation](#).

Configuration

In classic EMS configuration, the `tibemspd` uses definitions and parameters in three configuration files to guide the exchange of messages with TIBCO FTL. In JSON-configured servers, all configuration options are in the same file.

Enabling

An EMS server is part of exactly one FTL realm, so all EMS transports for TIBCO FTL use the same TIBCO FTL realm. Thus, some parameters are shared for every EMS transport instance. These parameters are found in `tibemspd.conf`.

To enable EMS transports for TIBCO FTL, you must set these parameters in the configuration file `tibemspd.conf`:

- `tibftl_transports` globally enables or disables message exchange with TIBCO FTL. The default value is `disabled`. To use EMS transports for TIBCO FTL, you must explicitly set this parameter to `enabled`.
- `ftl_url` specifies the URL at which the EMS server should connect to the realm service.

- `module_path` specifies the location of the TIBCO FTL shared library files.
- Additional optional parameters can be used to further configure how the EMS server and FTL realm service interact. See [TIBCO FTL Transport Parameters](#).

Transports

Transport definitions (in the configuration file `transports.conf`) specify the communication protocol between EMS and TIBCO FTL.

For more information, see [Configure EMS Transports for TIBCO FTL](#).

Destinations

Destination definitions (in the configuration files `topics.conf` and `queues.conf`) can set the `import` and `export` properties to specify one or more EMS transport for TIBCO FTL.

- `import` instructs `tibemsd` to import messages that arrive on those transports from TIBCO FTL, and deliver them to the EMS destination. When a destination is configured to import a given `tibftl` transport, the EMS server creates a single FTL subscriber for the transport.
- `export` instructs `tibemsd` to take messages that arrive on the EMS destination, and export them to TIBCO FTL using those EMS transports for TIBCO FTL. When a destination is configured to export a given `tibftl` transport, the EMS server creates a single FTL publisher for the transport.

For details, see [Topics](#), and [Queues](#).

Configure EMS Transports for TIBCO FTL

EMS transports mediate the flow of messages between TIBCO Enterprise Message Service and TIBCO FTL.



In TIBCO FTL, *transport* refers to the underlying mechanism that moves message data between FTL publishers and subscribers.

In TIBCO Enterprise Message Service, a transport is a more narrowly defined concept, referring specifically to the connections between an EMS server and an external system.

The EMS server joins a TIBCO FTL realm as any other TIBCO FTL client would. EMS transport definitions (in the file `transports.conf`) configure the behavior of these connections.

All messages received from the transports for TIBCO FTL that are configured in the `transports.conf` file are processed in a single TIBCO FTL event queue.

After being dispatched from the TIBCO FTL event queue, all TIBCO FTL messages that are imported through an EMS transport are processed by the EMS server. The EMS server creates JMS message copies of the incoming TIBCO FTL messages and begins processing them as EMS messages. EMS transports for TIBCO FTL determine how the messages are converted to EMS messages.

If the EMS server cannot keep up with the rate of incoming TIBCO FTL messages, by default, the FTL library begins discarding incoming messages.

Queue Limit Policies

In order to limit the number of pending messages in TIBCO FTL queues, EMS server properties allow you to set a queue limit policy, as you would for TIBCO FTL client applications.

When the queue limit for the EMS transport is reached, the FTL library discards a set number of messages if the event queue discard policy dictates so. Review the FTL discard policy and related parameters for more information.

Requirements

In order to successfully deploy the EMS transport for TIBCO FTL, your TIBCO FTL deployment must meet the following requirements:

- In TIBCO FTL, configure transports to be non-blocking when EMS exports messages.
- In TIBCO FTL, specify a discard policy of new when the EMS server's subscriber name is specified.

EMS Transport for FTL Definitions

`transports.conf` contains zero or more transport definitions. Each definition begins with the name of a transport, surrounded by square brackets. Subsequent lines set the parameters of the transport.

Parameter	Description
<code>type</code>	Required. For all EMS transports for TIBCO FTL, the value must be <code>tibftl</code> .
TIBCO FTL Parameters The syntax and semantics of these parameters are identical to the corresponding parameters in TIBCO FTL clients. For full details, see the TIBCO FTL documentation set.	
<code>endpoint</code>	Optional. Specify a TIBCO FTL endpoint name. To define multiple transports that use the same TIBCO FTL endpoint, include the same endpoint name in each transport definition. If absent, the endpoint name defaults to the name of the EMS transport.
<code>import_subscriber_name</code>	Optional. The name of the subscriber this EMS transport for FTL creates when it receives messages.
<code>import_match_string</code>	Optional. Creates a content matcher object to filter messages. Specify content matchers using the syntax: <pre>{ "fieldname1": value1, ..., "fieldnameN": valueN }</pre> The following rules must be observed: <ul style="list-style-type: none"> • Field name and value declarations must conform to the match string syntax described in the TIBCO FTL documentation. • The <code>import_match_string</code> must be specified on a single line. No manual line breaks may be inserted. Spaces are not allowed. For example: <pre>import_match_string = { "Item": "Book", "Title": "Outliers", "Stocked": true }</pre>
<code>export_format</code>	Optional. Specifies a format name to be used when a message is created. If not provided, the EMS server passes NULL to the TIBCO FTL message create call, resulting in a dynamically formatted message.

Parameter	Description
<code>export_constant</code>	Optional. Defines fields that are always set to a constant value. Each line adds additional constants. For example: <pre>export_constant = constant1,value1 export_constant = constant2,value2 export_constant = constant3,value3</pre>

Example

These examples from `transports.conf` illustrate the syntax of EMS transport for FTL definitions.

```
[FTL1]
type = tibftl
endpoint = EP1
import_subscriber_name = sub1
import_match_string = {"f1":"foo","f2":true}
export_format = format-1
export_constant = constant1,value1
export_constant = constant2,value2
export_constant = constant3,value3

[FTL2]
type = tibftl
```

Topics

Topics can both export and import messages. Accordingly, you can configure topic definitions (in the configuration file `topics.conf`) with `import` and `export` properties that specify one or more external transports:

import

`import` instructs `tibemsd` to import messages that arrive on those EMS transports from TIBCO FTL, and deliver them to the EMS destination. Each named `tibftl` transport can be named on only one EMS destination. That is, if the transport `FTL01` is included on `import` property for destination `myTopics.Fiction`, it cannot also be added to the destination `myTopics.Nonfiction`.



An EMS transport for TIBCO FTL may be specified as an import transport by only one destination. If the `topics.conf` configuration has a transport for TIBCO FTL included as an import transport by more than one destination, the server handles this as a configuration error.

export

`export` instructs `tibemsd` to take messages that arrive on the EMS destination, and export them to TIBCO FTL using the specified EMS transport for TIBCO FTL.



The EMS server never re-exports an imported message on the same topic.

(For general information about `topics.conf` syntax and semantics, see [topics.conf](#). You can also configure topics using the administration tool command `addprop topic`.)

Example

For example, the following `tibemsadmin` commands configure the topic `myTopics.news` to import messages on the transports `FTL01` and `FTL02`, and to export messages on the transport `FTL02`.

```
addprop topic myTopics.news import="FTL01,FTL02"
addprop topic myTopics.news export="FTL02"
```

TIBCO FTL messages with subject `myTopics.news` arrive at `tibemsd` over the transports `FTL01` and `FTL02`. EMS clients can receive those messages by subscribing to `myTopics.news`.

EMS messages sent to `myTopics.news` are exported to TIBCO FTL over transport `FTL02`. TIBCO FTL clients of the corresponding daemons can receive those messages by subscribing to the endpoint associated with `myTopics.news` in the `FTL02` transport definition.

Import Only when Subscribers Exist

When a topic specifies `import` on a connected transport, `tibemsd` imports messages only when the topic has at least one subscriber.

For more information, see [import](#).

Queues

Queues can import messages, but cannot export them.

Configuration

You can configure queue definitions (in the configuration file `queues.conf`) with the `import` property to specify one or more external transports.

`import` instructs `tibemsd` to import messages that arrive on those EMS transports from TIBCO FTL, and deliver them to the EMS destination.

(For general information about `queues.conf` syntax and semantics, see [queues.conf](#). You can also configure queues using the administration tool command `addprop queue`.)

Example

For example, the following `tibemsadmin` command configures the queue `myQueue.in` to import messages on the EMS transports `FTL01` and `FTL02`.

```
addprop queue myQueue.in import="FTL01,FTL02"
```

TIBCO FTL messages with subject `myQueue.in` arrive at `tibemsd` over the transports `FTL01` and `FTL02`. EMS clients can receive those messages by subscribing to `myQueue.in`.

Import—Start and Stop

When a queue specifies `import` on a connected transport, `tibemsd` immediately begins importing messages to the queue, even when no receivers exist for the queue.

For static queues (configured by an administrator) `tibemsd` continues importing until you explicitly delete the queue. When the queue is deleted, the transport no longer imports messages.

Message Translation

The following topics describe how a message is translated by the EMS server when either imported from or exported to FTL.

JMS Header Fields

EMS supports the predefined JMS header fields.

For more information, see [JMS Message Header Fields](#).

The `JMSTimestamp` JMS header field is a special case.



The JMS header `JMSTimestamp` corresponds to the time when the message was created. If this header field is not present when the `tibemsd` receives the message, it sets the `JMSTimestamp` to the current time.

TIBCO FTL messages do not have destinations or subjects, or a mandatory set of predefined header fields. Instead, message fields and their values are set for individual messages.

If the `export_headers` is defined as `true` in the common EMS transport properties, the EMS server converts the JMS header fields and their values to TIBCO FTL fields and values and adds them to the outgoing message. This allows TIBCO FTL to use content matchers on the fields.

If the `export_headers` property is `false`, then the JMS header fields and their values are *not* included in the exported TIBCO FTL message. This includes the destination name. That is, if `export_headers = false` for the transport, then the message exported to TIBCO FTL will not contain the destination name.

When converting the JMS header fields to TIBCO FTL message fields, header fields are given the prefix `_emsHdr:`. For example, the `JMSDeliveryMode` header field is assigned the field name `_emsHdr:JMSDeliveryMode` when inserted into the TIBCO FTL message.

The following table presents the mapping of JMS header fields to TIBCO FTL message field name and types (that is, the name and type of the corresponding field in the exported message).

JMS Header Name	TIBCO FTL Field Name	FTL Field Type
JMSDestination	<code>_emsHdr:JMSDestination</code>	<code>char*</code>
JMSDeliveryMode	<code>_emsHdr:JMSDeliveryMode</code>	<code>tibint64_t</code>
JMSPriority	<code>_emsHdr:JMSPriority</code>	<code>tibint64_t</code>
JMSMessageID	<code>_emsHdr:JMSMessageID</code>	<code>char*</code>
JMSTimestamp	<code>_emsHdr:JMSTimestamp</code>	<code>tibint64_t</code>
JMSCorrelationID	<code>_emsHdr:JMSCorrelationID</code>	<code>char*</code>
JMSType	<code>_emsHdr:JMSType</code>	<code>char*</code>
JMSDeliveryTime	<code>_emsHdr:JMSDeliveryTime</code>	<code>tibint64_t</code>
JMSExpiration	<code>_emsHdr:JMSExpiration</code>	<code>tibint64_t</code>
JMSRedelivered	<code>_emsHdr:JMSRedelivered</code>	<code>tibint64_t</code>
JMSReplyTo	<code>_emsHdr:JMSReplyTo</code>	<code>char*</code>

JMS Property Fields

EMS supports the JMS property fields described in [EMS Message Properties](#).

Import

When importing a TIBCO FTL message to an EMS message, `tibemsd` sets these JMS properties:

- `JMS_TIBCO_IMPORTED` gets the value `true`, to indicate that the message did not originate from an EMS client.
- `JMS_TIBCO_MSG_EXT` gets the value `true`, to indicate that the message *might* contain submessage fields or array fields.

Export

TIBCO FTL messages do not have destinations or subjects, or a mandatory set of predefined header fields. Instead, message fields and their values are set for individual messages.

If `export_properties` is defined as `true` in the common EMS transport properties, the EMS server converts the JMS properties and their values to TIBCO FTL fields and values and adds them to the outgoing message. This allows TIBCO FTL to use content matchers on the fields.

When converting the JMS properties to TIBCO FTL message fields, the property fields are given the prefix `_emsprop:.` For example the `JMS_TIBCO_SENDER` property would become the `_emsprop:JMS_TIBCO_SENDER` field.

The `tibemsd` server ignores any JMS property fields that are not set, or are set to null—it omits them from the exported message.

You can instruct `tibemsd` to exclude the properties fields from the exported message by setting the transport property `export_properties = false`.

Message Body

`tibemsd` can export messages with most JMS message body types to TIBCO FTL. However, Object messages and Stream messages cannot be exported. They are discarded with a warning.

`tibemsd` can import messages with any message format from TIBCO FTL.

For information about JMS body types, see [JMS Message Bodies](#). For information about the structure of messages, see [JMS Message Structure](#).

Import

When importing a TIBCO FTL message, `tibemsd` translates it to an EMS message body type based on the TIBCO FTL message format.

TIBCO FTL Message Format	EMS Message Type
FTL Message	Map Message
Built-in Opaque Format	Map Message with a bytes field, <code>_data</code> .
Keyed Opaque Format	Map Message with two fields: <ul style="list-style-type: none"> <code>_key</code> (char*) <code>_data</code> (bytes)

Export

When exporting an EMS message, `tibemsd` translates it to a TIBCO FTL message with the following structure:

- When `export_headers` is enabled on the EMS transport, JMS header fields are converted to TIBCO FTL message fields. See [JMS Header Fields](#). When the transport parameter `export_headers` is `false`, these fields are omitted.
- When `export_properties` is enabled on the EMS transport, JMS property fields are converted to TIBCO FTL message fields. See [JMS Property Fields](#). When the transport parameter `export_properties` is `false`, these fields are omitted.
- When translating the data fields of an EMS message, the results depend on the JMS body type. specifies the mapping.

JMS Body Type	Export Translation
MapMessage	An FTL message of the format specified. If no format was specified, it is a dynamically formatted FTL message.
BytesMessage	An FTL message with one opaque field with the key of <code>_data</code> .
TextMessage	FTL message with a <code>_text</code> field.
Message	Empty FTL message.
ObjectMessage	Not converted. Messages with this JMS body type cannot be exported to TIBCO FTL.
StreamMessage	Not converted. Messages with this JMS body type cannot be exported to TIBCO FTL.

Message Fields

When `tibemsd` converts messages, it converts fields individually, based on field type. Some field types are equivalent between EMS and TIBCO FTL, while converting others may result in some information loss of data type, or require additional formatting.

The mapping of equivalent fields is bidirectional. These field types are equivalent in EMS and TIBCO FTL, and no additional formatting is required during conversion:

EMS Field Type	TIBCO FTL Field Type
<code>tibems_long</code>	<code>tibint64_t</code>
<code>tibems_long array</code>	<code>tibint64_t array</code>
<code>tibems_double</code>	<code>tibdouble_t</code>
<code>tibems_double array</code>	<code>tibdouble_t array</code>
<code>char*</code>	<code>char*</code>
<code>MapMsg</code>	<code>Message</code>
<code>bytes</code>	<code>Opaque</code>

Import

Not all TIBCO FTL field types are supported by EMS. When `tibemsd` imports a TIBCO FTL message, these fields are converted into EMS sub-messages as shown below.

TIBCO FTL Field Type	EMS Field Type	Map Message Field Name
<code>Message Array</code>	Sub-message with message fields named 0, 1, and so on.	<code>_ftlMsgArray:fieldname</code>

TIBCO FTL Field Type	EMS Field Type	Map Message Field Name
char* array	Sub-message with message fields named 0, 1, and so on.	_ftlStringArray:fieldname
tibDateTime	Sub-message with two fields: <ul style="list-style-type: none"> s – long, representing seconds. n – long, representing nanoseconds. 	_ftlDateTime:fieldname
tibDateTime array	Sub-message containing tibDateTime equivalent sub-messages. Each submessage contains two fields: <ul style="list-style-type: none"> s – long, representing seconds. n – long, representing nanoseconds. 	_ftlDateTimeArray:fieldname
tibInbox	Discarded during conversion	N/A

Export

When exporting an EMS message, `tibemsd` translates it to a TIBCO FTL message. Not all field types that are supported by EMS map to TIBCO FTL. When `tibemsd` converts these fields, some information about data size is lost. The EMS fields are converted to TIBCO FTL fields as shown here:


EMS Field Type	TIBCO FTL Field Type
tibems_wchar	tibint64_t
tibems_byte	tibint64_t
tibems_short	tibint64_t
tibems_short_array	tibint64_t array
tibems_int	tibint64_t
tibems_int_array	tibint64_t array
tibems_float	tibdouble_t
tibems_float_array	tibdouble_t array

Interoperation with TIBCO Rendezvous

TIBCO Enterprise Message Service can exchange messages with supported versions of TIBCO Rendezvous.

Scope

- EMS can import and export messages to an external system through an EMS *topic*.
- EMS can import messages from an external system to an EMS *queue* (but queues cannot export).



Message Translation

EMS and Rendezvous use different formats for messages and their data. When `tibemsd` imports or exports a messages, it translates the message and its data to the appropriate format.

For more information, see [Message Translation](#).

Configuration

`tibemsd` uses definitions and parameters in four configuration files to guide the exchange of messages with Rendezvous.

Enabling

The parameter `tibrv_transports` (in the configuration file `tibemsd.conf`) globally enables or disables message exchange with Rendezvous. The default value is `disabled`. To use these transports, you must explicitly set this parameter to `enabled`.

The parameter `module_path` (in the configuration file `tibemsd.conf`) specifies the location of the Rendezvous shared library files.

Transports

Transport definitions (in the configuration file `transports.conf`) specify the communication protocol between EMS and the external system.

For more information, see [Configure Transports for Rendezvous](#).

Destinations

Destination definitions (in the configuration files `topics.conf` and `queues.conf`) can set the `import` and `export` properties to specify one or more transports:

- `import` instructs `tibemsd` to import messages that arrive on those transports from Rendezvous, and deliver them to the EMS destination.
- `export` instructs `tibemsd` to take messages that arrive on the EMS destination, and export them to Rendezvous via those transports.

For details, see [Topics](#), and [Queues](#).

RVCM Listeners

When exporting messages on a transport configured for certified message delivery, you can pre-register RVCM listeners in the file `tibrvcn.conf`.

For details, see [tibrvcn.conf](#), and [Certified Messages](#)

Configure Transports for Rendezvous

Transports mediate the flow of messages between EMS and TIBCO Rendezvous.

`tibemsd` connects to Rendezvous daemons in the same way as any other Rendezvous client would. Transport definitions (in the file [transports.conf](#)) configure the behavior of these connections. You must properly configure these transports.

Additionally, you must configure the parameter `module_path` (in the configuration file [tibemsd.conf](#)) to specify the location of the Rendezvous shared library files.

How Rendezvous Messages are Imported

The EMS server connects to the Rendezvous daemon as any other Rendezvous client would. Messages received from the Rendezvous daemon are stored in Rendezvous queues, then are dispatched to callbacks. The EMS server creates JMS message copies of the Rendezvous messages, and begins processing them as EMS messages. Transports determine how messages are imported.

Rendezvous messages that are imported through a transport are held in queues specific to that transport. Each transport is associated with a different Rendezvous queue, which holds as many Rendezvous messages as necessary. The number of pending messages in the queue will grow if the rate of incoming Rendezvous messages is greater than the rate at which the EMS server is able to process the corresponding EMS messages.

Depending on the import delivery mode defined for the transport, the EMS messages will be persisted on disk, which increases the likelihood of backlog in the Rendezvous queues, and which in turn results in a EMS process memory growth. This memory growth is not accounted for in any of the EMS server statistics.

Queue Limit Policies

In order to limit the number of pending messages in Rendezvous queues, a transport property allows you to set a queue limit policy, as you would for TIBCO Rendezvous client applications.

When the queue limit for the transport is reached, the Rendezvous library discards a set number of messages. The default policy is `TIBRVQUEUE_DISCARD_NONE`, which means that no message is ever discarded. Setting `TIBRVQUEUE_DISCARD_FIRST` or `TIBRVQUEUE_DISCARD_LAST` allows you to specify the maximum number of Rendezvous messages that can be pending in the queue before the discard policy that you have selected is applied. When the limit is reached, the number of messages discarded is based on the discard amount value.

When the limit is reached, Rendezvous messages are discarded, and so are not imported as EMS messages, regardless of the EMS import delivery mode. As stated above, a Rendezvous message

becomes a EMS message only after it has been dispatched from the Rendezvous queue. If a queue limit is exceeded, reliable Rendezvous messages are lost.

Rendezvous certified messages are not lost, but the message flow is interrupted. The redelivery of the missed messages is handled automatically by the Rendezvous libraries, and can not be controlled by the EMS server.

Reaching a queue limit also generates a Rendezvous advisory that is logged (see RVADV log and console trace in the TIBCO Rendezvous documentation), indicating which transport reached its queue limit. This advisory goes into an independent, non limited, Rendezvous queue. If lots of advisories are generated, this internal queue may also grow, signaling that the limit policy is not appropriate for your environment.

Take care when setting a queue limit policy. In a controlled environment where the risk of Rendezvous producers overwhelming the EMS server is low, there is no need to set a queue limit policy.

Transport Definitions

`transports.conf` contains zero or more transport definitions. Each definition begins with the name of a transport, surrounded by square brackets. Subsequent lines set the parameters of the transport.

Parameter	Description
<code>type</code>	Required. For Rendezvous transports, the value must be either <code>tibrv</code> or <code>tibrvcn</code> .
Rendezvous Parameters Use these properties for either <code>tibrv</code> or <code>tibrvcn</code> transports. The syntax and semantics of these parameters are identical to the corresponding parameters in Rendezvous clients. For full details, see the Rendezvous documentation set.	
<code>service</code>	When absent, the default value is 7500.
<code>network</code>	When absent, the default value is the host computer's primary network.
<code>daemon</code>	When absent, the default value is an <code>rvd</code> process on the local host computer. When transporting messages between EMS and Rendezvous, the <code>rvd</code> process must be configured to run on the same host as the EMS daemon (<code>tibemsd</code>). To connect to a non-default daemon, supply <code>protocol:hostname:port</code> . You may omit any of the three parts. The default protocol is <code>tcp</code> . The default <code>hostname</code> is the local host computer. The default <code>port</code> is 7500.
Rendezvous Certified Messaging (RVCM) Parameters Use these properties only for <code>tibrvcn</code> transports. The syntax and semantics of these parameters are identical to the corresponding parameters in Rendezvous CM clients. For full details, see the Rendezvous documentation set.	
<code>cm_name</code>	The name of the correspondent RVCM listener transport.

Parameter	Description
<code>rv_tport</code>	Required. Each RVCN transport depends in turn upon an ordinary Rendezvous transport. Set this parameter to the name of a Rendezvous transport (type <code>tibrv</code>) defined in the EMS configuration file <code>transports.conf</code> .
<code>ledger_file</code>	Name for file-based ledger.
<code>sync_ledger</code>	true or false. If true, operations that update the ledger do not return until changes are written to the storage medium.
<code>request_old</code>	true or false. If true, this transport server requests unacknowledged messages sent from other RVCN senders while this transport was unavailable.
<code>default_ttl</code>	This parameter sets default CM time limit (in seconds) for all CM messages exported on this transport.
<code>explicit_config_only</code>	<p>true or false. If true, <code>tibemsd</code> allows RVCN listeners to register for certified delivery only if they are configured in advance with the EMS server (either in <code>tibrvcn.conf</code> or using the <code>create rvcnlistener</code> command). That is, <code>tibemsd</code> ignores registration requests from non-configured listeners.</p> <p>If false (the default), <code>tibemsd</code> allows any RVCN listener to register.</p>
EMS Parameters Use these properties for either <code>tibrv</code> or <code>tibrvcn</code> transports.	
<code>topic_import_dm</code> <code>queue_import_dm</code>	<p>EMS sending clients can set the <code>JMSDeliveryMode</code> header field for each message. However, Rendezvous clients cannot set this header. Instead, these two parameters determine the delivery modes for all topic messages and queue messages that <code>tibemsd</code> imports on this transport.</p> <p>TIBEMS_PERSISTENT TIBEMS_NON_PERSISTENT TIBEMS_RELIABLE</p> <p>When absent, the default is <code>TIBEMS_NON_PERSISTENT</code>.</p>
<code>export_headers</code>	<p>When true, <code>tibemsd</code> includes JMS header fields in exported messages.</p> <p>When false, <code>tibemsd</code> suppresses JMS header fields in exported messages.</p> <p>When absent, the default value is true.</p>
<code>export_properties</code>	<p>When true, <code>tibemsd</code> includes JMS properties in exported messages.</p> <p>When false, <code>tibemsd</code> suppresses JMS properties in exported messages.</p> <p>When absent, the default value is true.</p>

Parameter	Description
<code>rv_queue_policy</code>	<p>Set the queue limit policy for the Rendezvous queue used by the transport to hold incoming Rendezvous messages. This parameter has three parts:</p> <p><i>policy:max_msgs:qty_discard</i></p> <p>where <i>policy</i> is one of the queue limit policies described below, <i>max_msgs</i> is the maximum number of messages permitted in the queue before discard, and <i>qty_discard</i> is the number of messages that the EMS server discards when <i>max_msgs</i> is reached.</p> <p>The queue limit policies are:</p> <ul style="list-style-type: none"> • <code>TIBRVQUEUE_DISCARD_NONE</code> — do not discard messages. Use this policy when the queue has no limit on the number of messages it can contain. • <code>TIBRVQUEUE_DISCARD_FIRST</code> — discard the first message in the queue. The first message in the queue is the oldest message, which if not discarded would be the next message dispatched from the queue. • <code>TIBRVQUEUE_DISCARD_LAST</code> — discard the last message in the queue. The last message is the most recent message received into the queue. <p>For example, the following would cause the Rendezvous library to discard the 100 oldest messages in the queue when the total number of messages in the queue reached 10,000:</p> <p><i>rv_queue_policy=TIBRVQUEUE_DISCARD_FIRST:10000:100</i></p> <p>If the <code>rv_queue_policy</code> is not present, the default queue limit policy is <code>TIBRVQUEUE_DISCARD_NONE</code>.</p>
<code>temp_destination_timeout</code>	<p>Specifies the amount of time the server is to keep the temporary destination (created for the RV inbox) after its last use of the destination. This is useful for a multi-server configuration. For example, in a configuration in which <code>rv-requester -> serverA -> serverB -> rv-responder</code>, setting <code>temp_destination_timeout=60</code> on <code>serverB</code> specifies that <code>serverB</code> is to hold the temporary destination for 60 seconds.</p>

Example

These examples from [transports.conf](#) illustrate the syntax of transport definitions.

```
[RV01]
type = tibrv
topic_import_dm = TIBEMS_RELIABLE
queue_import_dm = TIBEMS_PERSISTENT
service = 7780
network = lan0
daemon = tcp:host5:7885

[RV02]
type = tibrv
service = 7890
network = lan0
daemon = tcp:host5:7995
temp_destination_timeout = 60
```



```
[RVC01]
type = tibrvcm
export_headers = true
export_properties = true
rv_tport = RV02
cm_name = RVCMTTrans1
ledger_file = ledgerFile.store
sync_ledger = true
request_old = true
default_ttl = 600
```

In the following two examples, RVC03 is an RVC transport which does not define a queue limit policy, but references the RV transport RV03, which *does* have a queue limit policy. If Rendezvous messages are published to a subject that in EMS has the destination property `import=RVC03`, no Rendezvous message will ever be discarded because each transport uses its own queue. Only messages that are imported directly through the RV03 transport will potentially be discarded, should the queue limit of 10000 messages be reached.

```
[RV03]
type = tibrv
service = 7890
network = lan0
daemon = tcp:host5:7995
rv_queue_policy = TIBRVQUEUE_DISCARD_LAST:10000:100

[RVC03]
type = tibrvcm
rv_tport = RV03
cm_name = RVCMTTrans2
ledger_file = ledgerFile2.store
sync_ledger = true
request_old = true
default_ttl = 600
```

Topics

Topics can both export and import messages. Accordingly, you can configure topic definitions (in the configuration file `topics.conf`) with `import` and `export` properties that specify one or more external transports:

import

import instructs `tibemsd` to import messages that arrive on those transports from Rendezvous, and deliver them to the EMS destination.

export

export instructs `tibemsd` to take messages that arrive on the EMS destination, and export them to Rendezvous via those transports.



The EMS server never re-exports an imported message on the same topic.

(For general information about `topics.conf` syntax and semantics, see [topics.conf](#). You can also configure topics using the administration tool command `addprop topic`.)

Example

For example, the following `tibemsd` commands configure the topic `myTopics.news` to import messages on the transports RV01 and RV02, and to export messages on the transport RV02.

```
addprop topic myTopics.news import="RV01,RV02"
addprop topic myTopics.news export="RV02"
```

Rendezvous messages with subject `myTopics.news` arrive at `tibemsd` over the transports RV01 and RV02. EMS clients can receive those messages by subscribing to `myTopics.news`.

EMS messages sent to `myTopics.news` are exported to Rendezvous over transport RV02. Rendezvous clients of the corresponding daemons can receive those messages by subscribing to `myTopics.news`.

Import Only when Subscribers Exist

When a topic specifies [import](#) on a connected transport, `tibemsd` imports messages only when the topic has registered subscribers.

Wildcards

Wildcards in the [import](#) and [export](#) properties obey EMS syntax and semantics (which is identical to Rendezvous syntax and semantics); see [Destination Name—Syntax and Semantics](#).

Certified Messages

You can [import](#) and [export](#) TIBCO Rendezvous certified messages (`tibrvcml` transport) to EMS topics. Rendezvous certified transports guarantee message delivery.

RVCM Ledger

`tibrvcml` transports can store information about subjects in a ledger file. You can review the ledger file using an administration tool command; see [show rvcmltransportledger](#).

For more information about ledger files, see TIBCO Rendezvous documentation.

Subject Collisions

Subscribers to destinations that import from RVCM transports are subject to the same restrictions that direct RVCM listeners. These restrictions are described in the TIBCO Rendezvous documentation, and include subject collisions.

When importing messages from RV, the EMS server creates RVCM listeners using a single name for each transport. This can result in subject collisions if the corresponding EMS subscribers have overlapping topics.

Queues

Queues can import messages, but cannot export them.

See [import](#) and [export](#) for more information.

Configuration

You can configure queue definitions (in the configuration file `queues.conf`) with the `import` property that specify one or more external transports.

[import](#) instructs `tibemsd` to import messages that arrive on those transports from Rendezvous, and deliver them to the EMS destination.

(For general information about `queues.conf` syntax and semantics, see [queues.conf](#). You can also configure queues using the administration tool command `addprop queue`.)

Example

The following `tibemsadmin` command configures the queue `myQueue.in` to import messages on the transports `RV01` and `RV02`.

```
addprop queue myQueue.in import="RV01,RV02"
```

Rendezvous messages with subject `myQueue.in` arrive at `tibemsd` over the transports `RV01` and `RV02`. EMS clients can receive those messages by subscribing to `myQueue.in`.

Import—Start and Stop

When a queue specifies `import` on a connected transport, `tibemsd` immediately begins importing messages to the queue, even when no receivers exist for the queue.

For static queues (configured by an administrator) `tibemsd` continues importing until you explicitly delete the queue.

Wildcards

Wildcards in the `import` property obey EMS syntax and semantics (not Rendezvous syntax and semantics).

For more information, see [Destination Name—Syntax and Semantics](#).

EMS clients cannot subscribe to wildcard queues—however, you can define wildcard queues in the EMS server for the purpose of property inheritance. That is, you can configure a static queue named `foo.*` and set properties on it, so that child queues named `foo.bar` and `foo.baz` will both inherit those properties.

If you define a queue that imports `foo.*`, `tibemsd` begins importing all matching messages from Rendezvous. As messages arrive, `tibemsd` creates dynamic child queues (for example, `foo.bar` and `foo.baz`) and delivers the messages to them. Notices that `tibemsd` delivers messages to these dynamic child queues even when no consumers exist to drain them.

Import Issues

This section presents issues associated with importing messages to EMS from Rendezvous—whether on a topic or a queue.

Field Identifiers

When importing and translating Rendezvous messages, `tibemsd` is only able to process standard message field types that are identified by name in the Rendezvous program application. Custom fields and fields identified using a field identifier cannot be imported to EMS.

JMSDestination

When `tibemsd` imports and translates a Rendezvous message, it sets the `JMSDestination` field of the EMS message to the value of the Rendezvous subject.

Therefore, imported destination names must be unique. When a topic and a queue share the same name, at most one of them may set the `import` property. For example, if a topic `foo.bar` and a queue `foo.bar` are both defined, only one may specify the `import` property.

See [JMSDestination](#) for more information.

JMSReplyTo

When `tibemsd` imports and translates a Rendezvous message, it sets the `JMSReplyTo` field of the EMS message to the value of the Rendezvous reply subject, so that EMS clients can reply to the message.

Usually this value represents a Rendezvous subject. You must explicitly configure `tibemsd` to create a topic with a corresponding name, which exports messages to Rendezvous.

See [JMSReplyTo](#) for more information.

JMSExpiration

When `tibemsd` imports and translates a Rendezvous certified message, it sets the `JMSExpiration` field of the EMS message to the time limit of the certified message.

See [JMSExpiration](#) for more information.

If the message time limit is exceeded, the sender program no longer certifies delivery.

Note that if the [expiration](#) property is set for a destination, it will override the `JMSExpiration` value set by the message producer.

Guaranteed Delivery



For full end-to-end certified delivery from Rendezvous to EMS, all three of these conditions must be true:

- Rendezvous senders must send labeled messages on RVCN transports. See the *TIBCO Rendezvous Concepts* manual for more information.
- The transport definition must set `topic_import_dm` or `queue_import_dm` (as appropriate) to `TIBEMS_PERSISTENT`.
- Either a durable queue or a subscriber for the EMS topic must exist.

Export Issues

This section presents issues associated with exporting messages from EMS to Rendezvous.

JMSReplyTo

Topics

Consider an EMS message in which the field `JMSReplyTo` contains a topic. When exporting such a message to Rendezvous, you must explicitly configure `tibemsd` to import replies from Rendezvous to that reply topic.

Temporary Topics

Consider an EMS message in which the field `JMSReplyTo` contains a temporary topic. When `tibemsd` exports such a message to Rendezvous, it automatically arranges to import replies to that temporary topic from Rendezvous; you do not need to configure it explicitly.

Certified Messages

RVCN Registration

When an RVCN listener receives its first labeled message, it registers to receive subsequent messages as certified messages. Until the registration is complete, it receives labeled messages as reliable messages. When exporting messages on a `tibrvcn` transport, we recommend either of two actions to ensure certified delivery for all exported messages:

- Create the RVCN listener before sending any messages from EMS clients.
- Pre-register an RVCN listener, either with the administration tool (see [create rvcnlistener](#)), or in the configuration file `tibrvcn.conf` (see [tibrvcn.conf](#)).

Guaranteed Delivery

For full end-to-end certified delivery to Rendezvous from EMS, the following condition must be true:

- EMS senders must send persistent messages.

Message Translation

The following topics describe how a message is translated by the EMS server when either imported from or exported to Rendezvous.

JMS Header Fields

EMS supports the predefined JMS header fields described in [JMS Message Header Fields](#).

Special Cases

The following header fields are special cases:

- JMS header [JMSDestination](#) corresponds to Rendezvous subject.
- JMS header [JMSReplyTo](#) corresponds to Rendezvous reply subject.
- JMS header [JMSExpiration](#) corresponds to the time limit of the Rendezvous certified message.
- JMS header [JMSTimestamp](#) corresponds to the time when the message was created. If this header field is not present, when the `tibemsd` receives the message it sets the `JMSTimestamp` to the current time.

Import

When importing a Rendezvous message to an EMS message, `tibemsd` does not set any JMS header fields, except for the special cases noted above.

Export

When exporting an EMS message to a Rendezvous message, `tibemsd` groups all the JMS header fields (except for the special cases noted above) into a single submessage within the Rendezvous message. The field `JMSHeaders` contains that submessage. Fields of the submessage map the names of JMS header fields to their values.

`tibemsd` ignores any JMS header fields that are null or absent—it omits them from the exported message.

You can instruct `tibemsd` to suppress the entire header submessage in all exported messages by setting the transport property `export_headers = false`.

The following table shows the mapping of JMS header fields to Rendezvous data types (that is, the type of the corresponding field in the exported message).

JMS Header Name	Rendezvous Type
<code>JMSDeliveryMode</code>	<code>TIBRVMSG_U8</code>
<code>JMSDeliveryTime</code>	<code>TIBRVMSG_U64</code>
<code>JMSPriority</code>	<code>TIBRVMSG_U8</code>
<code>JMSTimestamp</code>	<code>TIBRVMSG_U64</code>
<code>JMSExpiration</code>	<code>TIBRVMSG_U64</code>
<code>JMSType</code>	<code>TIBRVMSG_STRING</code>
<code>JMSMessageID</code>	<code>TIBRVMSG_STRING</code>
<code>JMSCorrelationID</code>	<code>TIBRVMSG_STRING</code>
<code>JMSRedelivered</code>	<code>TIBRVMSG_BOOL</code>

JMS Header Name	Rendezvous Type
JMSDestination	send subject in TIBCO Rendezvous
JMSReplyTo	reply subject in TIBCO Rendezvous

JMS Property Fields

Import

When importing a Rendezvous message to an EMS message, `tibemsd` sets these JMS properties:

- `JMS_TIBCO_IMPORTED` gets the value `true`, to indicate that the message did not originate from an EMS client.
- `JMS_TIBCO_MSG_EXT` gets the value `true`, to indicate that the message *might* contain submessage fields or array fields.

Import RVCM

In addition to the two fields described above, when `tibemsd` imports a certified message on a `tibrvc` transport, it can also set these properties (if the corresponding information is set in the Rendezvous message).

Property	Description
JMS_TIBCO_CM_PUBLISHER	A string value indicating the correspondent name of the TIBCO Rendezvous CM transport that sent the message (that is, the sender name).
JMS_TIBCO_CM_SEQUENCE	A long value indicating the CM sequence number of an RVCM message imported from TIBCO Rendezvous.

Export

When exporting an EMS message to a Rendezvous message, `tibemsd` groups all the JMS property fields into a single submessage within the Rendezvous message. The field `JMSProperties` contains that submessage. Fields of the submessage map the names of JMS property fields to their values.

The `tibemsd` server ignores any JMS property fields that are not set, or are set to null—it omits them from the exported message.

You can instruct `tibemsd` to suppress the entire properties submessage in the exported message by setting the transport property `export_properties = false`.

Message Body

`tibemsd` can export messages with any JMS message body type to TIBCO Rendezvous. Conversely, `tibemsd` can import messages with any message type from TIBCO Rendezvous.

For information about JMS body types, see [JMS Message Bodies](#).

For information about the structure of messages, see [JMS Message Structure](#).

Import

When importing a Rendezvous message, `tibemsd` translates it to an EMS message body type based on the presence of the field as seen in the following table.

Rendezvous Field	EMS Body Type
JMSBytes	JMSBytesMessage
JMSObject	JMSObjectMessage
JMSStream	JMSStreamMessage
JMSText	JMSTextMessage
None of these fields are present.	JMSMapMessage



The field names `DATA` and `_data_` are reserved. We strongly discourage you from using these field names in either EMS and Rendezvous applications, and especially when these two message transport mechanisms interoperate.



Only standard Rendezvous fields identified by name can be imported into EMS. Custom fields and fields identified in the Rendezvous application by field identifiers cannot be imported.

Export

When exporting an EMS message, `tibemsd` translates it to a Rendezvous message with the following structure.

- The field `JMSHeaders` contains a submessage; see [JMS Header Fields](#). When the transport parameter `export_headers` is `false`, this field is omitted.
- The field `JMSProperties` contains a submessage; see [JMS Property Fields](#). When the transport parameter `export_properties` is `false`, this field is omitted.
- When translating the data fields of an EMS message, the results depend on the JMS body type. The following table specifies the mapping.

JMS Body Type	Export Translation
BytesMessage	The message data translates to a byte array that contains the bytes of the original EMS message. The field <code>JMSBytes</code> receives this data. It has type <code>TIBRVMSG_OPAQUE</code> .
ObjectMessage	The message data translates to a byte array containing the serialized Java object. The field <code>JMSObject</code> receives this data. It has type <code>TIBRVMSG_OPAQUE</code> .
StreamMessage	The message data translates to a byte array that encodes the objects in the original EMS message. The field <code>JMSStream</code> receives this data. It has type <code>TIBRVMSG_OPAQUE</code> .

JMS Body Type	Export Translation
TextMessage	The message data translates to a UTF-8 string corresponding to the text of the original EMS message. The field <code>JMSText</code> receives this data. It has type <code>TIBRVMSG_STRING</code> .
MapMessage	The message data fields map directly to top-level fields in the Rendezvous message. The fields retain the same names as in the original EMS message. See also, EMS Extensions to JMS Messages .

Data Types

The mapping between EMS datatypes and Rendezvous datatypes is bidirectional, except for the Rendezvous types that have no corresponding EMS type (for these types the mapping is marked as unidirectional in the middle column).

EMS	Map	Rendezvous
Boolean		<code>TIBRVMSG_BOOL</code>
Byte		<code>TIBRVMSG_I8</code>
Short	<—	<code>TIBRVMSG_U8</code>
Short		<code>TIBRVMSG_I16</code>
Integer	<—	<code>TIBRVMSG_U16</code>
Integer		<code>TIBRVMSG_I32</code>
Long	<—	<code>TIBRVMSG_U32</code>
Long		<code>TIBRVMSG_I64</code>
Long	<—	<code>TIBRVMSG_U64</code>
Float		<code>TIBRVMSG_F32</code>
Double		<code>TIBRVMSG_F64</code>
Short	<—	<code>TIBRVMSG_IPPORT16</code>
Integer	<—	<code>TIBRVMSG_IPADDR32</code>
MapMessage		<code>TIBRVMSG_MSG</code>
Long	<—	<code>TIBRVMSG_DATETIME</code>
<code>byte[]</code>		<code>TIBRVMSG_OPAQUE</code>
<code>java.lang.String</code>		<code>TIBRVMSG_STRING</code>

EMS	Map	Rendezvous
byte[]	<—	TIBRVMSG_XML
byte[]	<—	TIBRVMSG_I8ARRAY
short[]	<—	TIBRVMSG_U8ARRAY
short[]		TIBRVMSG_I16ARRAY
int[]	<—	TIBRVMSG_U16ARRAY
int[]		TIBRVMSG_I32ARRAY
long[]	<—	TIBRVMSG_U32ARRAY
long[]		TIBRVMSG_I64ARRAY
long[]	<—	TIBRVMSG_U64ARRAY
float[]		TIBRVMSG_F32ARRAY
double[]		TIBRVMSG_F64ARRAY

Pure Java Rendezvous Programs

TIBCO Enterprise Message Service is shipped with the `tibrvjms.jar` file that you can include in your TIBCO Rendezvous applications. This JAR file includes the implementation of the `com.tibco.tibrv.TibrvJMSTransport` class. This class extends the `com.tibco.tibrv.TibrvNetTransport` class and allows your pure Java Rendezvous programs to communicate directly with the EMS server instead of through `rva`.

the application must include `tibrvjms.jar` and EITHER `tibrvjweb.jar` OR `tibrvj.jar`, but CANNOT include `tibrvnative.jar`

To use the `TibrvJMSTransport` class, your application must include `tibrvjms.jar` (included with EMS) and either `tibrvjweb.jar` or `tibrvj.jar` (included with TIBCO Rendezvous). Your application *cannot* include `tibrvnative.jar`.



You can use `TibrvJMSTransport` only in Rendezvous applications. This class is not intended for use in your EMS Java clients.

Both TIBCO Rendezvous and EMS must be purchased, installed, and configured before creating pure Java Rendezvous applications that use the `TibrvJMSTransport` class.

The `TibrvJMSTransport` class provides Rendezvous reliable communication only. Other types of communication, such as certified messaging, are not supported by this transport.

Applications using this transport can send messages to a topic on an EMS server that has the same topic name as the subject of the message. EMS topics receiving Rendezvous messages sent by way of the `TibrvJMSTransport` do not need to specify the `import` property. This transport cannot be used to send messages to JMS queues.

For more information about `TibrvNetTransport` and how to create use transports in TIBCO Rendezvous Java programs, see TIBCO Rendezvous documentation. For more information about the additional methods of `TibrvJMSTransport`, see the *TIBCO Enterprise Message Service Java API Reference*.

Interoperation with TIBCO SmartSockets


TIBCO Enterprise Message Service can exchange messages with TIBCO SmartSockets.



This feature is supported on those platforms where TIBCO SmartSockets is supported. Refer to the respective readme files of TIBCO Enterprise Message Service and TIBCO SmartSockets.

Scope

- EMS can import and export messages to an external system through an EMS *topic*.
- EMS can import messages from an external system to an EMS *queue* (but queues cannot export).



Message Translation

EMS and SmartSockets use different formats for messages and their data. When `tibemsd` imports or exports a messages, it translates the message and its data to the appropriate format.

For more information, see [Message Translation](#).

Configuration

`tibemsd` uses definitions and parameters in three configuration files to guide the exchange of messages with SmartSockets.

Enabling

The parameter `tibss_transports` (in the configuration file `tibemsd.conf`) globally enables or disables message exchange with SmartSockets. The default value is `disabled`. To use these transports, you must explicitly set this parameter to `enabled`.

The parameter `tibss_config_dir` (in the configuration file `tibemsd.conf`) specifies the location of SmartSockets files needed by the SmartSockets client within `tibemsd`.

The parameter `module_path` (in the configuration file `tibemsd.conf`) specifies the location of the SmartSockets shared library files.

Transports

Transport definitions (in the configuration file `transports.conf`) specify the communication protocol between EMS and the external system.

For details, see [Configure Transports for SmartSockets](#).

Destinations

Destination definitions (in the configuration files [topics.conf](#) and [queues.conf](#)) can set the import and export properties to specify one or more transports:

- `import` instructs `tibemsd` to import messages that arrive on those transports from SmartSockets, and deliver them to the EMS destination.
- `export` instructs `tibemsd` to take messages that arrive on the EMS destination, and export them to SmartSockets via those transports.

For details, see [Topics](#), and [Queues](#).

Starting the Servers

We recommend starting the SmartSockets RTserver before starting `tibemsd`.

Configure Transports for SmartSockets

Transports mediate the flow of messages between TIBCO Enterprise Message Service and TIBCO SmartSockets.

`tibemsd` connects to SmartSockets RTservers in the same way as any other SmartSockets client. Transport definitions (in the file [transports.conf](#)) configure the behavior of these connections. You must properly configure these transports.

Transport Definitions

`transports.conf` contains zero or more transport definitions. Each definition begins with the name of a transport, surrounded by square brackets. Subsequent lines set the parameters of the transport.

Parameter	Description
<code>type</code>	Required. For SmartSockets transports, the value must be <code>tibss</code> .
SmartSockets Parameters The syntax and semantics of these parameters are identical to the corresponding parameters in SmartSockets clients. For full details, see the SmartSockets documentation set.	
<code>server_names</code>	<p>The value is a comma-separated list specifying connections to one or more SmartSockets RTservers.</p> <p>Each item in the list has the form <i>protocol:hostname:port</i>. You may omit any of the three parts. The default <i>hostname</i> is the local host computer. The default protocols and ports vary with hardware and operating system platforms; on Windows platforms, the default protocol is <code>tcp</code> and the default port is <code>5101</code>.</p> <p>A list of several servers specifies fault tolerance—<code>tibemsd</code> attempts to connect to them in the order listed.</p> <p>When this parameter is absent, the default instructs the EMS server to attempt to connect to an RTserver on the local host computer (the same computer as the EMS server), using default protocols and ports.</p>
<code>username</code> <code>password</code>	<code>tibemsd</code> uses these two parameters to authenticate itself to the SmartSockets servers.

Parameter	Description
<code>project</code>	SmartSockets uses projects to maintain orthogonal subject name-spaces. When absent, the default project is <code>rtworks</code> .
<code>delivery_mode</code>	This parameter determines the quality of service with which delivers messages to the SmartSockets server over this transport: <code>best_effort</code> <code>gmd_all</code> <code>gmd_some</code> <code>ordered</code> When absent, the default is <code>best_effort</code> .
<code>lb_mode</code>	SmartSockets servers balance the message load by distributing messages among several clients. This parameter determines the load balancing regimen for messages that this transport exports to the SmartSockets server. <code>none</code> <code>round_robin</code> <code>weighted</code> <code>sorted</code> When absent, the default is <code>none</code> .
<code>override_lb_mode</code>	<code>enable</code> instructs the RTserver to deliver all messages on this client connection—even if other clients participate in load balancing. For example, even though many order-processing clients might share the load of order messages, a message logging facility would require all order messages, rather than a subset. <code>disable</code> informs the RTserver that this client (that is, the EMS server) participates in load balancing (for example, sharing the load with other EMS servers). When absent, the default is <code>enable</code> .
<code>gmd_file_delete</code>	SmartSockets clients keep data for guaranteed message delivery (GMD) in a store file. <code>disable</code> instructs <code>tibemsd</code> to open the existing GMD store file. <code>enable</code> instructs <code>tibemsd</code> to delete the GMD store file and create a new one when creating this transport. When absent, the default is <code>disable</code> .
<code>import_ss_headers</code>	This parameter governs the import of SmartSockets message headers to EMS properties. The value can be <code>none</code> , <code>type_num</code> , or <code>all</code> . For complete details, see SmartSockets Message Properties . When absent, the default value is <code>none</code> .

Parameter	Description
<code>preserve_gmd</code>	<p>This parameter determines the behavior of the EMS server when it has exported a GMD message to SmartSockets, and SmartSockets cannot deliver that message. When SmartSockets returns the undelivered message, EMS can either preserve it in the EMS undelivered message queue, or discard it.</p> <ul style="list-style-type: none"> • <code>always</code> instructs EMS to preserve all undelivered GMD messages in the EMS undelivered message queue. • <code>receivers</code> instructs EMS to preserve only those undelivered GMD messages that SmartSockets could not deliver despite the existence of one or more GMD receivers. That is, if SmartSockets cannot deliver a message because no GMD receivers exist, then EMS does not preserve the undelivered message. • <code>never</code> instructs EMS to discard all undelivered SmartSockets GMD messages. <p>When absent, the default value is <code>never</code>.</p> <p>This parameter applies only when the transport's <code>delivery_mode</code> parameter is either <code>gmd_all</code> or <code>gmd_some</code>.</p> <p>When the EMS server preserves a GMD message, it follows these rules to convert the returned SmartSockets message to an EMS message:</p> <ul style="list-style-type: none"> • Follow all general rules for importing messages; see Message Translation. • Disregard the value of the <code>import_ss_headers</code> parameter, and instead import all SmartSockets headers (as if the value of <code>import_ss_headers</code> were <code>all</code>). For a list of headers, see SmartSockets Message Properties. • Set the value of <code>JMS_TIBCO_SS_EXPIRATION</code> to the current time—that is, the time at which the SmartSockets server returned the undelivered message to EMS. (Notice that the this header would otherwise remain unused, since GMD messages do not expire.)
EMS Parameters	
<code>topic_import_dm</code> <code>queue_import_dm</code>	<p>EMS sending clients can set the <code>JMSDeliveryMode</code> header field for each message. However, SmartSockets clients cannot set this header. Instead, these two parameters determine the delivery modes for all topic messages and queue messages that <code>tibemsd</code> imports on this transport.</p> <p><code>TIBEMS_PERSISTENT</code> <code>TIBEMS_NON_PERSISTENT</code> <code>TIBEMS_RELIABLE</code></p> <p>When absent, the default is <code>TIBEMS_NON_PERSISTENT</code>.</p>
<code>export_headers</code>	<p>When <code>true</code>, <code>tibemsd</code> includes JMS header fields in exported messages.</p> <p>When <code>false</code>, <code>tibemsd</code> suppresses JMS header fields in exported messages.</p> <p>When absent, the default value is <code>true</code>.</p>
<code>export_properties</code>	<p>When <code>true</code>, <code>tibemsd</code> includes JMS properties in exported messages.</p> <p>When <code>false</code>, <code>tibemsd</code> suppresses JMS properties in exported messages.</p> <p>When absent, the default value is <code>true</code>.</p>

Example

These examples from `transports.conf` illustrate the syntax of transport definitions.

```
[SS01]
  type = tibss
  server_names = rtHost1
  username = emsServer6
  password = myPasswd
  project = sales_order_entry

[SS02]
  type = tibss
  server_names = tcp:rtHost2A:5555, ssl:rtHost2B:5571
  username = emsServer6
  password = myPasswd
  project = mfg_process_control
  override_lb_mode = enable
  delivery_mode = gmd_some
```

Destination Name—Syntax and Semantics

This section examines the similarities and differences in the syntax and semantics of the EMS destination names and SmartSocket subjects.

Slash & Dot Separators

This aspect of the mapping between EMS destination names and SmartSockets subjects is straightforward, one-to-one, and bidirectional.

EMS destination names consist of tokens separated by the dot (.) character. SmartSockets subjects consists of tokens preceded by the slash (/) character (like UNIX directory pathnames).

For example, the EMS name `foo.bar.baz` corresponds to the SmartSockets name `/foo/bar/baz`. (Remember that SmartSockets names must begin with a leading slash, but EMS names need not begin with a leading dot. A leading dot indicates an empty element preceding it.)

The slash and dot characters have complementary roles in EMS and SmartSockets. In EMS slash is an ordinary character, while dot is a separator. In SmartSockets slash is a separator, while dot is an ordinary character. To translate names between EMS and SmartSockets, substitute these characters one for another. For example, the EMS name `foo/bar.baz` corresponds to the SmartSockets name `/foo.bar/baz`. However, to avoid confusion, we discourage using either slash or dot as ordinary characters.

Wildcard Star

Although both EMS and SmartSockets both interpret the star (*) character as a wildcard, they differ in its semantics. In this aspect, the mapping is not one-to-one.

In EMS, star can match any whole token of a name, but not part of a token. In SmartSockets, star can match part of a token—for example, `/foo/b*/baz` matches `/foo/bar/baz` and `/foo/box/baz`.

If you are familiar with SmartSockets wildcards but not EMS wildcards, see [Wildcards](#).

Trailing Wildcard

In EMS the greater-than (>) character is a wildcard that matches any number of trailing tokens. In SmartSockets a string of three dots (...) signifies identical semantics.

Topics

Topics can both export and import messages. Accordingly, you can configure topic definitions (in the configuration file `topics.conf`) with import and export properties that specify one or more external transports:

import

`import` instructs `tibemspd` to import messages that arrive on those transports from SmartSockets, and deliver them to the EMS destination.

export

`export` instructs `tibemspd` to take messages that arrive on the EMS destination, and export them to SmartSockets via those transports.



The EMS server never re-exports an imported message on the same topic.

(For general information about `topics.conf` syntax and semantics, see [topics.conf](#). You can also configure topics using the administration tool command `addprop topic`.)

Example

For example, the following `tibemspd` commands configure the topic `myTopics.news` to import and export messages on three transports.

```
addprop topic myTopics.news import="SS01,SS02"
addprop topic myTopics.news export="SS01,SS02,SS03"
```

SmartSockets messages with subject `/myTopics/news` arrive at `tibemspd` over the transports `SS01` and `SS02`. EMS clients can receive those messages by subscribing to `myTopics.news`.

EMS messages sent to `myTopics.news` are exported to SmartSockets over all three transports—`SS01`, `SS02` and `SS03`. SmartSockets clients of the corresponding RTservers can receive those messages by subscribing to `/myTopics/news`.

Import Only when Subscribers Exist

When a topic specifies `import` on a connected transport, `tibemspd` imports messages only when the topic has registered subscribers.

Wildcards

Wildcards in the `import` and `export` properties obey EMS syntax and semantics (not SmartSockets syntax and semantics).

For more information, see [Destination Name—Syntax and Semantics](#).

Queues

Queues can import messages, but cannot export them.

Configuration

You can configure queue definitions (in the configuration file `queues.conf`) with the `import` property that specify one or more external transports.

`import` instructs `tibemspd` to import messages that arrive on those transports from SmartSockets, and deliver them to the EMS destination.

(For general information about `queues.conf` syntax and semantics, see [queues.conf](#). You can also configure queues using the administration tool command `addprop queue`.)

Example

For example, the following `tibemspd` command configures the queue `myTopics.news` to import messages on the transports `SS01` and `SS02`.

```
addprop queue myQueue.in import="SS01,SS02"
```

SmartSockets messages with subject `/myQueue/in` arrive at `tibemsd` over the transports `SS01` and `SS02`. EMS clients can receive those messages by subscribing to `myQueue.in`.

Import—Start and Stop

When a queue specifies import on a connected transport, `tibemsd` immediately begins importing messages to the queue, even when no receivers exist for the queue.

For static queues (configured by an administrator) `tibemsd` continues importing until you explicitly delete the queue.

Wildcards

Wildcards in the `import` property obey EMS syntax and semantics (not SmartSockets syntax and semantics).

For more information, see [Destination Name—Syntax and Semantics](#).

EMS clients cannot subscribe to wildcard queues—however, you can define wildcard queues in the EMS server for the purpose of property inheritance. That is, you can configure a static queue named `foo.*` and set properties on it, so that child queues named `foo.bar` and `foo.baz` will both inherit those properties.

If you define a queue that imports `foo.*`, `tibemsd` begins importing all matching messages from SmartSockets. As messages arrive, `tibemsd` creates dynamic child queues (for example, `foo.bar` and `foo.baz`) and delivers the messages to them. Notices that `tibemsd` delivers messages to these dynamic child queues even when no subscribers exist to drain them.

Import Issues

This section presents issues associated with importing messages to EMS from SmartSockets—whether on a topic or a queue.

Import Destination Names Must be Unique



When a topic and a queue share the same name, *at most one* of them may set the `import` property. For example, if a topic `foo.bar` and a queue `foo.bar` are both defined, only one may specify the `import` property.

JMSReplyTo

When `tibemsd` imports and translates a SmartSockets message, it sets the `JMSReplyTo` field of the EMS message to the value of the SmartSockets `reply_to` header, so that EMS clients can reply to the message.

Usually this value represents a SmartSockets subject. You must explicitly configure `tibemsd` to create a topic with a corresponding name, which exports messages to SmartSockets.

Guaranteed Delivery

For full end-to-end guaranteed delivery from SmartSockets to EMS, all the following conditions must be true:

- SmartSockets senders must send messages with guaranteed message delivery (GMD).
- The transport definition must set `topic_import_dm` or `queue_import_dm` (as appropriate) to `TIBEMS_PERSISTENT`.
- A durable subscription for the EMS topic or queue must exist.

For export guarantees, see [Guaranteed Delivery](#).

Export Issues

This section presents issues associated with exporting messages from EMS to SmartSockets.

JMSReplyTo

Topics

Consider an EMS message in which the field `JMSReplyTo` contains a topic. When exporting such a message to SmartSockets, you must explicitly configure `tibemsd` to import replies from SmartSockets to that reply topic.

Temporary Topics

Consider an EMS message in which the field `JMSReplyTo` contains a temporary topic. When `tibemsd` exports such a message to SmartSockets, it automatically arranges to import replies to that temporary topic from SmartSockets; you do not need to configure it explicitly.

Wildcard Subscriptions

Star Wildcard

Both EMS and SmartSockets interpret the star character (*) as a wildcard—but with different semantics. EMS accepts star only as a whole element, which matches a whole element. In contrast, SmartSockets accepts star as part of an element, matching a substring within the element.

When a SmartSockets client subscribes to `foo.bar*`, then configure `tibemsd` to export the superset `foo.*`; RTserver narrows the set by delivering only messages that match subscribers. For a full discussion of the differences between EMS and SmartSockets wildcards, see [Destination Name—Syntax and Semantics](#).

Guaranteed Delivery

For full end-to-end guaranteed delivery to SmartSockets from EMS, all the following conditions must be true:

- EMS senders must send persistent messages.
- The transport definition must set `delivery_mode` to `gmd_some` or `gmd_all` (as appropriate).

To preserve undelivered GMD messages in the EMS undelivered queue, see [preserve_gmd](#). For import guarantees, see [Guaranteed Delivery](#).

Message Translation

The following topics describe how a message is translated by the EMS server when either imported from or exported to SmartSockets.

JMS Header Fields

EMS supports the predefined JMS header fields described in [JMS Message Header Fields](#).

Two Special Cases

These two header fields are special cases:

- JMS header `JMSDestination` corresponds to SmartSockets `dest`.
- JMS header `JMSReplyTo` corresponds to SmartSockets `reply_to`.

Import

When importing a SmartSockets message to an EMS message, `tibemsd` does not set any JMS header fields, except for the special cases noted above.

Export

When exporting an EMS message to a SmartSockets message, `tibemsd` groups all the JMS header fields (except for the special cases noted above) into a single submessage within the SmartSockets message. The field `JMSHeaders` contains that submessage. Fields of the submessage map the names of JMS header fields to their values.

`tibemsd` ignores any JMS header fields that are null or absent—it omits them from the exported message.

You can instruct `tibemsd` to suppress the entire header submessage in all exported messages by setting the transport property `export_headers = false`.

JMS Property Fields

Import

When importing a SmartSockets message to an EMS message, `tibemsd` sets these JMS properties:

- `JMS_TIBCO_IMPORTED` gets the value `true`, indicating that the message did not originate from an EMS client.
- `JMS_TIBCO_MSG_EXT` gets the value `true`, indicating that the message *might* contain submessage fields or array fields.
- `JMS_TIBCO_SS_SENDER` gets the value of the SmartSockets `sender` header field (in SmartSockets syntax).

In addition, `tibemsd` maps SmartSockets message properties to EMS properties; for details see [SmartSockets Message Properties](#).

Export

When exporting an EMS message to a SmartSockets message, `tibemsd` groups all the JMS property fields into a single submessage within the SmartSockets message. The field `JMSProperties` contains that submessage. Fields of the submessage map the names of JMS property fields to their values.

`tibemsd` ignores any JMS property fields that are not set, or are set to null—it omits them from the exported message.

You can instruct `tibemsd` to suppress the entire properties submessage in the exported message by setting the transport property `export_properties = false`.

SmartSockets Message Properties

`tibemsd` maps SmartSockets message headers to EMS message properties on import.

[SmartSockets Mapping Message Properties \(Import & Export\)](#) summarizes the mapping. The first column indicates the EMS property, and the second column indicates the SmartSockets method that gets the corresponding header.

Import

The transport parameter `import_ss_headers` governs the import behavior.

The third column of the table included in [SmartSockets Mapping Message Properties \(Import & Export\)](#) lists the values of that parameter for which `tibemsd` imports the message property in that row. See [import_ss_headers](#).

Export

EMS client programs may modify the values of these properties within imported messages for re-export to SmartSockets. (However, exporting a native EMS message does not carry these properties to SmartSockets.)

Export of these properties depends on the value of the transport parameter [export_properties](#).

When exporting an EMS message to SmartSockets, `tibemsd` maps these properties in reverse. In most cases, the mapping is symmetric—export maps them back to the same SmartSockets header.

However, three exceptions ([JMS_TIBCO_SS_SENDER](#), [JMS_TIBCO_SS_MESSAGE_ID](#) and [JMS_TIBCO_SS_SEQ_NUM](#)) are asymmetric—export maps them to subfields of the field `JMSProperties` within the SmartSockets message. The fourth column indicates this asymmetry.

SmartSockets Mapping Message Properties (Import & Export)

EMS Property	SmartSockets Method	Import	Export Asymmetr.
JMS_TIBCO_SS_SENDER	TipcMsgGetSender	none type_num all	Asymmetr.
JMS_TIBCO_SS_TYPE_NUM	TipcMsgGetType	type_num all	
JMS_TIBCO_SS_DELIVERY_MODE	TipcMsgGetDeliveryMode	all	
JMS_TIBCO_SS_LB_MODE	TipcMsgGetLbMode	all	
JMS_TIBCO_SS_EXPIRATION	TipcMsgGetExpiration	all	
JMS_TIBCO_SS_PRIORITY	TipcMsgGetPriority	all	
JMS_TIBCO_SS_SENDER_TIMESTAMP	TipcMsgGetSenderTimestamp	all	
JMS_TIBCO_SS_CORRELATION_ID	TipcMsgGetCorrelationId	all	
JMS_TIBCO_SS_USER_PROP	TipcMsgGetUserProp	all	
JMS_TIBCO_SS_MESSAGE_ID	TipcMsgGetMessageId	all	Asymmetr.
JMS_TIBCO_SS_SEQ_NUM	TipcMsgGetSeqNum	all	Asymmetr.

Message Body

`tibemsd` can export messages with any JMS message body type to TIBCO SmartSockets. Conversely, `tibemsd` can import messages with any message type from TIBCO SmartSockets.

For information about JMS body types, see [JMS Message Bodies](#).

For information about the structure of messages, see [JMS Message Structure](#).

Import

When importing a SmartSockets message, `tibemsd` translates it to one of these EMS message body types:

- If the SmartSockets message contains only *unnamed* fields, then it translates into a `JMSStreamMessage`. The stream contains the values of the unnamed fields in the same order as they appear in the SmartSockets message.
- If the SmartSockets message contains one or more named fields, then it translates into a `JMSMapMessage`. The map message contains the named fields; the order of the fields is indeterminate.

Export

When exporting an EMS message, `tibemsd` translates it to one of six SmartSockets message types .

The message has the following structure:

- The named field `JMSHeaders` is the first field (omitted when the transport parameter `export_headers` is `false`). It contains a submessage; see [JMS Header Fields](#).
- The named field `JMSProperties` is the next field (omitted when the transport parameter `export_properties` is `false`). It contains a submessage; see [JMS Property Fields](#).
- The data fields follow the JMS headers and properties (when present). For details about field names and types, see the third column of the following table.

JMS Message Type	SmartSockets Message Type	Data Fields
<code>JMSBytesMessage</code>	<code>T_MT_JMS_BYTES</code>	One unnamed field of type <code>T_MSG_FT_BINARY</code>
<code>JMSMapMessage</code>	<code>T_MT_JMS_MAP</code>	Named fields; indeterminate order
<code>JMSObjectMessage</code>	<code>T_MT_JMS_OBJECT</code>	One unnamed field of type <code>T_MSG_FT_BINARY</code>
<code>JMSStreamMessage</code>	<code>T_MT_JMS_STREAM</code>	Unnamed fields in order
<code>JMSTextMessage</code>	<code>T_MT_JMS_TEXT</code>	One unnamed field of type <code>T_MSG_FT_STR</code>
All other JMS message types	<code>T_MT_INFO</code>	No data fields

Data Types

The following table presents the mapping between EMS and SmartSockets datatypes. The mapping is bidirectional, except for a few SmartSockets types that have no corresponding EMS type. For these SmartSockets datatypes that have no corresponding type, the mapping is marked as unidirectional.

EMS	Map	SmartSockets
Boolean		<code>T_MSG_FT_BOOL</code>

EMS	Map	SmartSockets
Byte		T_MSG_FT_BYTE
Character	—>	T_MSG_FT_INT2
Character	<—	T_MSG_FT_CHAR
Short		T_MSG_FT_INT2
Integer		T_MSG_FT_INT4
Long		T_MSG_FT_INT8
Float		T_MSG_FT_REAL4
Double		T_MSG_FT_REAL8
Double	<—	T_MSG_FT_TIMESTAMP
String		T_MSG_FT_STR
String	<—	T_MSG_FT_XML
String	<—	T_MSG_FT_UTF8
Byte Array		T_MSG_FT_BINARY
Short Array	<—	T_MSG_FT_BOOL_ARRAY
Short Array		T_MSG_FT_INT2_ARRAY
Integer Array		T_MSG_FT_INT4_ARRAY
Long Array		T_MSG_FT_INT8_ARRAY
Float Array		T_MSG_FT_REAL4_ARRAY
Double Array		T_MSG_FT_REAL8_ARRAY
Double Array	<—	T_MSG_FT_TIMESTAMP_ARRAY
Stream Message		T_MSG_FT_MSG
Map Message		(See Import.)

Destination Names

tibemsd automatically translates destination names when importing or exporting a message.

When importing, it translates names in the SmartSockets subject and reply_to fields. When exporting, it translates names in the EMS JMSDestination and JMSReplyTo fields.

For more information, see [Slash & Dot Separators](#).

Monitor Server Activity

System administrators must monitor and manage the TIBCO Enterprise Message Service server. The logging, monitoring, and statistics facilities provided by the server allow system administrators to effectively view system activity and track system performance.

Server Health

You can configure the TIBCO Enterprise Message Service server to service HTTP GET requests for the current health of the server on a dedicated port.

This feature can be used to support the health check probes in an OpenShift cluster. For more information refer to the [OpenShift](#) documentation.



The EMS server supports this feature only on the Linux, macOS, and Windows platforms.

Configure the Health Check Listen

The `health_check_listen` configuration property in `tibemsd.conf` controls the interface and port the server will service HTTP health check requests on. If this property is not set, the server will not attempt to service these type of requests. This property cannot be set dynamically.

You can use only one `health_check_listen` and this listen should not conflict with other server listens.

These same restrictions apply to `secondary_health_check_listen` which is used by a server designated as secondary in a fault tolerant pair.

Health Check Response

A requestor can check whether the server is live or ready. An OK response to a liveness request means the server is up and running. An OK response on a readiness request means the server is in the active state while a BAD response means the server is not.

Liveness requests to the server should be HTTP GET requests for the path `/isLive`. Readiness requests to the server should be HTTP GET requests for the path `/isReady`.

For example: `http://machine:7220/isLive` and `http://machine:7220/isReady`.

Log Files and Tracing

You can configure the TIBCO Enterprise Message Service server to write a variety of information to the log. Several parameters and commands control where the log is located as well as what information is written to the log. The log can be written to a file, to the system console, or to both.

Configure the Log File

The `logfile` configuration parameter in `tibemsd.conf` controls the location and the name of the log file.

You can specify that the log file should be backed up and emptied after it reaches a maximum size. This allows you to rotate the log file and ensure that the log file does not grow boundlessly. The `logfile_max_size` configuration parameter allows you to specify the maximum size of the current log file. Set the parameter to 0 to specify no limit. Use KB, MB, or GB units.

Once the log file reaches its maximum size, it is copied to a file with the same name as the current log file except a sequence number is appended to the name of the backup file. On startup—and only on startup—the server queries the directory and determines the first available sequence number. It then uses the next sequence number when it needs to back up the current log file. By doing so, you can keep a continuous sequencing, as long as you retain the most recent log file (highest sequence number)

between server restarts. Conversely, if you move or remove all log files before a server restart, then the sequencing will restart at 1.

For example, if the current log file is named `tibems.log`, the first copy is named `tibems.log.1`, the second is named `tibems.log.2`, and so on. Similarly, if the highest sequence number in use when the server starts is 19, or `tibemsd.log.19`, then the next backup file created will be named `tibemsd.log.20`. This is true even if you removed `tibemsd.log.19` and all other log files after the server started.

If `logfile_max_count` is specified, the server keeps at most the number of log files specified by that parameter, including the current log file. When the maximum number of log files has been reached and the server needs to back up the current log file, it deletes the oldest log file (the ones with smallest number). If you change the parameter setting, after the server is restarted, the next time it needs to rotate the log file it deletes however many of the lowest sequence numbered files required to reach the `logfile_max_count` maximum.

You can also dynamically force the log file to be backed up and truncated using the `rotatelog` command in `tibemsadmin`. See [Command Listing](#) for more information about the `rotatelog` command.

For other configuration parameters that affect the log file, see [Tracing and Log File Parameters](#).

Trace Messages for the Server

The TIBCO Enterprise Message Service server can be configured to produce trace messages. These messages can describe actions performed for various areas of functionality (for example, Access Control, Administration, or Routing). These messages can also provide information about activities performed on or by the server, or the messages can provide warnings in the event of failures or illegal actions.

Trace messages can be sent to a log file, the console, or both. You configure tracing in the following ways:

- By configuring the `log_trace` and/or `console_trace` parameters in the `tibemsd.conf` file; see [set server](#).
- By specifying the `-trace` option when starting the server
- By using the `set server` command when the server is running.

`log_trace` and `console_trace` can be used to configure what types of messages are to go to the log file and to the console.



When you want trace messages to be sent to a log file, you must also configure the `logfile` configuration parameter. If you specify `log_trace`, and the `logfile` configuration parameter is not set to a valid file, the tracing options are stored, but they are not used until the server is started with a valid log file.

Server Tracing Options

When configuring log or console tracing, you have a variety of options for the types of trace messages that can be generated.

Specify tracing with a comma-separated list of trace options. You may specify trace options in three forms:

- `plain`: A trace option without a prefix character replaces any existing trace options.
- `+`: A trace option preceded by `+` adds the option to the current set of trace options.
- `-`: A trace option preceded by `-` removes the option from the current set of trace options.

Trace Option	Description
DEFAULT	<p>Sets the trace options to the default set. This includes:</p> <ul style="list-style-type: none"> • INFO • WARNING • ACL • LIMITS • ROUTE • ADMIN • RVADV • CONNECT_ERROR • CONFIG • MSG
ACL	Prints a message when a user attempts to perform an unauthorized action. For example, if the user attempts to publish a message to a secure topic for which the user has not been granted the publish permission.
ADMIN	Prints a message whenever an administration function is performed.
AUTH	Prints a message when the server authenticates a user using an external LDAP system.
CONFIG	Prints information about configuration files and their contents as the EMS server is starting up.
CONNECT	Prints a message when a user attempts to connect to the server.
CONNECT_ERROR	Prints a message when an error occurs on a connection.
DBSTORE	Prints a message when a database store is created, along with general database store information and errors.
DEST	Prints a message when a dynamic destination is created.
FLOW	Prints a message when the server enforces flow control or stops enforcing flow control on a destination.
FTL	Prints trace messages related to TIBCO FTL transports.
INFO	Prints messages as the server performs various internal housekeeping functions, such as creating a configuration file, opening the persistent database files, and purging messages. Also prints a message when tracking by message ID is enabled or disabled.

Trace Option	Description
JAAS	Prints messages related to any extensible security modules. Messages are printed when a username and password are passed to the LoginModule for authentication, and when a user and action are passed to the Permissions Modules for authorization.
JNDI	Prints a trace message for each JNDI lookup performed by a client, including the name and type of the object looked up and its return value.
JVM	Prints startup information about the JVM configuration, as well as any output from custom modules running in the JVM that uses <code>System.out</code> .
JVMERR	Prints output from custom modules running in the JVM that uses <code>System.err</code> .
LDAP_DEBUG	Prints messages when LDAP is used for authentication or to obtain group information.
LIMITS	Prints a message when a limit is exceeded, such as the maximum size for a destination.
LOAD	Prints the paths of any dynamically loaded libraries. For example, the tibemsd can load Zlib, SmartSockets, and SSL libraries.
MEMORY	Prints a server trace information when reserve memory is triggered because of low server memory conditions.
MSG	Specifies that message trace messages should be printed. Message tracing is enabled/disabled on a destination or on an individual message. If message tracing is not enabled for any messages or destinations, no trace messages are printed when this option is specified for log or console tracing. See Message Tracing for more information about message tracing.
PRODCONS	Prints a message when a client creates or closes a producer or consumer.
ROUTE	Prints a message when routes are created or when a route connection is established.
ROUTE_DEBUG	Prints status and error messages related to the route.
RVADV	Prints TIBCO Rendezvous advisory messages whenever they are received.
SS	Prints trace messages related to SmartSockets transports.
SSL	Prints detailed messages of the SSL process, including certificate content.
SSL_DEBUG	Prints messages that trace the establishment of SSL connections.
TX	Prints a message when a client performs a transaction.

Trace Option	Description
WARNING	Prints a message when a failure of some sort occurs, usually because the user attempts to do something illegal. For example, a message is printed when a user attempts to publish to a wildcard destination name.

Examples

The following example sets the trace log to only show messages about access control violations.

```
log_trace=ACL
```

The next example sets the trace log to show all default trace messages, in addition to SSL messages, but ADMIN messages are not shown.

```
log_trace=DEFAULT, -ADMIN, +SSL
```

The next example sends a trace message to the console when a TIBCO Rendezvous advisory message arrives.

```
console_trace=RVADV
```

Message Tracing

In addition to other server activity, you can trace messages as they are processed.

Trace entries for messages are only generated for destinations or messages that specify tracing should be performed. For destinations, you specify the `trace` property to enable the generation of trace messages. For individual messages, the `JMS_TIBCO_MSG_TRACE` property specifies that tracing should be performed for this message, regardless of the destination settings. The sections below describe the tracing properties for destinations and messages.

Message trace entries can be output to either the console or the log. The `MSG` trace option specifies that message trace entries should be displayed, and the `DEFAULT` trace option includes the `MSG` option. See [Trace Messages for the Server](#) for more information about specifying trace options.

You must set the tracing property on either destinations or messages and also set the `MSG` or `DEFAULT` trace option on the console or the log before you can view trace entries for messages.



EMS tracing features do not filter unprintable characters from trace output. If your application uses unprintable characters within messages (whether in data or headers), the results of message tracing are unpredictable.

Enable Message Tracing for a Destination

The `trace` property on a destination specifies that trace entries are generated for that destination.

The `trace` property can optionally be specified as `trace=body`. Setting `trace=body` includes the message body in trace messages. The EMS server prints up to one kilobyte of a message string field, and up to a total message size of 8 KB. The trace message indicates if the full message is not printed.

Setting `trace` without the `body` option specifies that only the message sequence and message ID are included in the trace message.

When message tracing is enabled for a destination, a trace entry is output for each of the following events that occur in message processing:

- messages are received into a destination
- messages are sent to consumers
- messages are imported or exported to/from an external system
- messages are acknowledged
- messages are sent across a destination bridge

- messages are routed

Replies to request messages are traced only when the reply destination has the `trace` property. Similarly, replies to exported messages are only traced when the `trace` property is set.

Enable Message Tracing on a Message

You can enable tracing on individual messages by setting the `JMS_TIBCO_MSG_TRACE` property on the message.

The value of the property can be either null (Java/.NET null or NULL in C) or the string "body". Setting the property to null specifies only the message ID and message sequence will be included in the trace entries for the message. Setting the property to "body" specifies the message body will be included in the trace entries for the message.

When the `JMS_TIBCO_MSG_TRACE` property is set for a message, trace entries are generated for the message as it is processed, regardless of whether the `trace` property is set for any destinations the message passes through. Trace messages are generated for the message when it is sent by the producer and when it is received by the consumer.

Monitor Server Events

The TIBCO Enterprise Message Service server can publish topic messages for internal system events. For example, the server can publish a message when users connect or disconnect.

System event messages contain detail about the event stored in properties of the message. This section gives an overview of the monitoring facilities provided by the server. For a list of monitor topics and a description of the message properties for each topic, see [Monitor Messages](#).

System Monitor Topics

The TIBCO Enterprise Message Service server can publish messages to various topics when certain events occur. There are several types of event classes, each class groups a set of related events. For example, some event classes are connection, admin, and route. Each event class is further subdivided into the events for each class. For example, the connection class has two events: connect and disconnect. These event classes are used to group the system events into meaningful categories.

All system event topic names begin with `$sys.monitor`. The remainder of the name is the event class followed by the event. For example, the server publishes a message to the topic `$sys.monitor.connection.disconnect` whenever a client disconnects from the server. The naming scheme for system event topics allows you to create wildcard subscriptions for all events of a certain class. For example, to receive messages whenever clients connect or disconnect, you would create a topic subscriber for the topic `$sys.monitor.connection.*`.

Monitor topics are created and maintained by the server. Monitor topics are not listed in the `topics.conf` file. Users can subscribe to monitor topics but cannot create them.

Monitor Messages

You can monitor messages processed by a destination as they are sent, received, or acknowledged.

You can also monitor messages that have prematurely exited due to expiration, being discarded, or a [maxRedelivery](#) failure.

The `$sys.monitor` topic for monitor messages has the following format:

```
$sys.monitor.D.E.destinationName
```

where *D* is the type of destination, *E* is the event you wish to monitor, and *destinationName* is the name of the destination whose messages you wish to monitor.

Message monitoring qualifiers

Possible values of *D* and *E* in message monitoring topics.

Qualifier	Value	Description
<i>D</i>	T	Destination to monitor is a topic. Include the message body in the monitor message as a byte array. Use the <code>createFromBytes()</code> method when viewing the monitor message to recreate the message body, if desired.
	t	Destination to monitor is a topic. Do not include the message body in the monitor message.
	Q	Destination to monitor is a queue. Include the message body in the monitor message as a byte array. Use the <code>createFromBytes()</code> method when viewing the monitor message to recreate the message body, if desired.
	q	Destination to monitor is a queue. Do not include the message body in the monitor message.
<i>E</i>	s	Monitor message is generated when a message is sent by the server to: <ul style="list-style-type: none"> • a consumer • a route • an external system by way of a transport
	r	Monitor message is generated when a message is received by the specified destination. This occurs when the message is: <ul style="list-style-type: none"> • Sent by a producer • Sent by a route • Forwarded from another destination by way of a bridge • Imported from transport to an external system
	a	Monitor message is generated when a message is acknowledged.
	p	Monitor message is generated when a message prematurely exits due to expiration, being discarded, or a maxRedelivery failure.
	*	Monitor message is generated when a message is sent, received, or acknowledged for the specified destination.

For example, `$sys.monitor.T.r.corp.News` is the topic for monitoring any received messages to the topic named `corp.News`. The message body of any received message is included in monitor messages on this topic. The topic `$sys.monitor.q.*.corp.*` monitors all message events (send, receive, acknowledge) for all queues matching the name `corp.*`. The message body is not included in this topic's messages.

The messages sent to this type of monitor topic include a description of the event, information about where the message came from (a producer, route, external system, and so on), and optionally the

message body, depending upon the value of *D*. See [Monitor Messages](#), for a complete description of the properties available in monitor messages.

You must explicitly subscribe to a message monitoring topic. That is, subscribing to `$sys.monitor.>` will subscribe to all topics beginning with `$sys.monitor`, but it does not subscribe you to any specific message monitoring topic such as `$sys.monitor.T.*.foo.bar`. However, if another subscriber generates interest in the message monitor topics, this subscriber will also receive those messages.

You can specify wildcards in the *destinationName* portion of the message monitoring topic to subscribe to the message monitoring topic for all matching destinations. For example, you can subscribe to `$sys.monitor.T.r.>` to monitor all messages received by all topics. For performance reasons, you may want to avoid subscribing to too many message monitoring topics. See [Performance Implications of Monitor Topics](#) for more information.

View Monitor Topics

Monitor topics are similar to other topics. To view these topics, create a client application that subscribes to the desired topics.

Because monitor topics contain potentially sensitive system information, authentication and permissions are always checked when clients access a monitor topic. That is, even if authentication for the server is disabled, clients are not able to access monitor topics unless they have logged in with a valid username and password and the user has permission to view the desired topic.

The admin user and members of the `$admin` group have permission to perform any server action, including subscribing to monitor topics. All other users must be explicitly granted permission to view monitor topics before the user can successfully create subscribers for monitor topics. For example, if user BOB is not a member of the `$admin` group, and you wish to allow user BOB to monitor all connection events, you can grant BOB the required permission with the following command using the administration tool:

```
grant topic $sys.monitor.connection.* BOB subscribe
```

Bob's application can then create a topic subscriber for `$sys.monitor.connect.*` and view any connect or disconnect events.



Topics starting with `$sys.monitor` do not participate in any permission inheritance from parent topics other than those starting with `$sys.monitor` (that is, `.*` or `>` is not a parent of `$sys.monitor`).

Therefore, granting permission to a user to subscribe to `>` does not allow that user to subscribe to `$sys.monitor` topics. You must explicitly grant users permission to `$sys.monitor` topics (or parent topics, such as `$sys.monitor.admin.*`) for a user to be able to subscribe to that topic.

Monitor topics publish messages of type [MapMessage](#). Information about the event is stored within properties in the message. Each system event has different properties. [Monitor Messages](#), describes each of the monitor topics and the message properties for the messages published on that topic. Your application can receive and display all or part of a monitor message, just as it would handle any message sent to a topic. However, there are some ways in which monitor messages are handled differently from standard messages:

- Monitor messages cannot be routed to other servers.
- Monitor messages are not stored persistently on disk.
- Monitor messages are not swapped from process memory to disk.

You can have any number of applications that subscribe to monitor messages. You can create different applications that subscribe to different monitor topics, or you can create one application that subscribes to all desired monitor topics. Your topic subscribers can also use message selectors to filter the monitor messages so your application receives only the messages it is interested in.

Performance Implications of Monitor Topics

The TIBCO Enterprise Message Service server only generates messages for monitor topics that currently have subscribers. So, if no applications subscribe to monitor topics, no monitor messages are

generated. Generating a monitor message does consume system resources, and therefore you should consider what kinds of monitoring your environment requires. System performance is affected by the number of subscribers for monitor topics as well as the frequency of messages for those topics.

For development and testing systems, monitoring all system events is probably desirable. Usually, development and testing systems do not have large message volumes, and monitoring can give you information about system problems.

For production systems, monitoring all events may have an adverse effect on system performance. Therefore, you should not create topic subscribers for `$sys.monitor.>` in your production system. Also, monitor events are likely to be added in future releases, so the number of monitor topics may grow. Subscriptions to monitor topics in production systems should always be limited to specific monitor topics or wildcard subscriptions to specific classes of monitor topics that are required.

Also, consider the frequency of messages to each monitor topic. System administration events, such as creating topics, routes, and changing permissions, do not occur frequently, so creating subscriptions for these types of events will most likely not have a significant effect on performance.

Also, using message selectors to limit monitor messages can improve performance slightly. The server does not send any messages that do not match a subscriber's message selector. Even though the message is not sent, the message is still generated. Therefore there is still system overhead for subscribers to a monitor topic, even if all messages for that topic do not match any subscriber's message selector filter.

Server Statistics

The TIBCO Enterprise Message Service server allows you to track incoming and outgoing message volume, message size, and message statistics for the server overall as well as for each producer, consumer, or route. You can configure the type of statistics collected, the interval for computing averages, and amount of detail for each type.

Statistic tracking can be set in the server's configuration file, or you can change the configuration dynamically using commands in the administration tool or by creating your own application with the administration APIs.

Statistics can be viewed using the administration tool, or you can create your own application that performs more advanced analysis of statistics using the administration APIs.

This section details how to configure and view statistics using the configuration files and administration tool commands. For more information about the administration APIs, see the description of `com.tibco.tibjms.admin` in the online documentation.

The TIBCO Enterprise Message Service server tracks the number of incoming or outgoing messages, but only messages sent or received by a producer, consumer, or route are tracked. The server also sends system messages, but these are not included in the number of messages.

However, the server can add a small amount of data to a message for internal use by the server. This overhead is counted in the total message size, and you may notice that some messages have a greater message size than expected.



Overall Server Statistics

The server always collects certain overall server statistics. This includes the rate of inbound and outbound messages (expressed as number of messages per second), message memory usage, disk storage usage, and the number of destinations, connections, and durable subscriptions. Gathering this information consumes virtually no system resources, therefore these statistics are always available. You can view overall server statistics by executing the `show server` command.

The default interval for collecting overall server statistics is 1 second. You may wish to view average system usage statistics over a larger interval. The `server_rate_interval` configuration parameter controls the collection interval for server statistics. The parameter can be set in the configuration file or

dynamically using the `set server` command. This parameter can only be set to positive integers greater than zero.

Enable Statistics Gathering

Each producer, consumer, destination, and route can gather overall statistics and statistics for each of its destinations. To enable statistic gathering, you must set the `statistics` parameter to `enabled`. This parameter can be specified in the configuration file, and it can be changed dynamically using the `set server` command.

The `statistics` parameter allows you to globally enable and disable statistic gathering. Statistics are kept in server memory for the life of each object. If you wish to reset the total statistics for all objects to zero, disable statistic gathering, then re-enable it. Server statistics are also reset when the server shuts down and restarts, or in the event of a fault-tolerant failover.

For each producer, consumer, destination, and route the total number of sent/received messages and total size of messages is maintained. Also, producers and consumers keep these statistics for each destination that they use to send or receive messages.

The rate of incoming/outgoing messages and message size is calculated over an interval. By default, the average is calculated every three seconds. You can increase or decrease this value by altering the `rate_interval` parameter. This parameter can be set in the configuration file or dynamically using the `set server` command. Setting this parameter to 0 disables the tracking of statistics over an interval—only the total statistics for the destination, route, producer, or consumer are kept.

Gathering total statistics for producers, consumers, destinations, and routes consumes few system resources. Under most circumstances, enabling statistic gathering and average calculations should not affect system performance.

Detailed Statistics

In some situations, the default statistic gathering may not be sufficient. For example, if a topic subscriber subscribes to wildcard topics, the total statistics for all topics that match the wildcard are kept. You may wish to get further detail in this case and track the statistics for each actual topic the subscriber receives.

The following situations may require detailed statistic gathering:

- Topic subscribers that subscribe to wildcard topics
- Message producers that do not specify a destination when they are created. These message producers can produce messages for any destination, and the destination name is specified when a message is sent.
- Routes can have incoming and outgoing messages on many different topics.

To enable detailed statistics, set the `detailed_statistics` parameter to the type of statistics you wish to receive. The parameter can have the following values:

- `NONE` — disables detailed statistic gathering.
- `CONSUMERS` — enables detailed statistics for topic subscribers with wildcard topic names.
- `PRODUCERS` — enables detailed statistics for producers that do not specify a destination when they are created.
- `ROUTES` — enables detailed statistics for routes.

You can set the `detailed_statistics` parameter to `NONE` or any combination of `CONSUMERS`, `PRODUCERS`, or `ROUTES`. To specify more than one type of detailed statistic gathering, provide a comma-separated list of values. You can set the `detailed_statistics` parameter in the configuration file or dynamically by using the `set server` command. For example, the following `set server` command enables detailed statistic tracking for producers and routes.

```
set server detailed_statistics = PRODUCERS,ROUTES
```


Collecting detailed statistics does consume memory, and can adversely affect performance when gathering a high volume of statistics. There are two parameters that allow you to control resource consumption when collecting detailed statistics. First, you can control the amount of time statistics are kept, and second you can set a maximum amount of memory for detailed statistic gathering. When application programs create many dynamic destinations, we recommend against gathering detailed statistics.

The `statistics_cleanup_interval` parameter controls how long detailed statistics are kept. This parameter can be set either in the configuration file or dynamically with the `set server` command. By default, statistics are kept for 15 seconds. For example, if there is a topic subscriber for the topic `foo.*`, and the subscriber receives a message on topic `foo.bar`, if no new messages arrive for topic `foo.bar` within 15 seconds, statistics for topic `foo.bar` are deleted for that consumer. You can set this parameter to 0 to signify that all detailed statistics are to be kept indefinitely. Of course, statistics for an object only exist as long as the object itself exists. That is, if a message consumer terminates, all detailed statistics for that consumer are deleted from memory.

The `max_stat_memory` parameter controls the amount of memory used by detailed statistics. This parameter can be set either in the configuration file or dynamically with the `set server` command. By default, this parameter is set to 0 which signifies that detailed statistics have no memory limit. If no units are specified, the value of this parameter is in bytes. Optionally, you can specify units as KB, MB, or GB. When the specified limit is reached, the server stops collecting new statistics. The server will only resume collecting statistics if the amount of memory used decreases (for example, if the `statistics_cleanup_interval` is set and old statistics are removed).

Display the Statistics

When statistic collecting is enabled, you can view statistics for producers, consumers, routes, and destinations using the `show stat` command in the administration tool.

The `show stat` command allows you to filter the statistics based on destination name, user name, connection ID, or any combination of criteria. You can optionally specify the `total` keyword to retrieve only the total statistics (this suppresses the detailed output). You can also optionally specify the "wide" keyword when displaying statistics for destinations or routes. This specifies that inbound and outbound message statistics should be displayed on the same line (the line can be 100 characters or more).

The following illustrates displaying statistics for a route where detailed statistic tracking is enabled.

```
tcp://server1:7322> show stat route B
Inbound statistics for route 'B':
```

Destination	Total Count		Rate/Second	
	Msgs	Size	Msgs	Size
<total>	189	37.9 Kb	10	2.0 Kb
Topic: dynamic.0	38	7.6 Kb	2	0.4 Kb
Topic: dynamic.1	38	7.6 Kb	2	0.4 Kb
Topic: dynamic.2	38	7.6 Kb	2	0.4 Kb
Topic: dynamic.3	38	7.6 Kb	2	0.4 Kb
Topic: dynamic.4	37	7.4 Kb	2	0.4 Kb

```
Outbound statistics for route 'B':
```

Destination	Total Count		Rate/Second	
	Msgs	Size	Msgs	Size
<total>	9538	1.9 MB	10	2.1 Kb
Topic: dynamic.0	1909	394.9 Kb	2	0.4 Kb
Topic: dynamic.1	1908	394.7 Kb	2	0.4 Kb
Topic: dynamic.2	1907	394.5 Kb	2	0.4 Kb
Topic: dynamic.3	1907	394.5 Kb	2	0.4 Kb
Topic: dynamic.4	1907	394.5 Kb	2	0.5 Kb

See `show stat` for more information and detailed syntax of the `show stat` command.

SSL Protocol

Secure Sockets Layer (SSL) is a protocol that provides secure authentication and transmits encrypted data over the Internet or an internal network. Most web browsers support SSL, and many Web sites and Java applications use it to obtain confidential user information, such as credit card numbers.

The SSL protocol is complex, and this chapter is not a complete description of SSL. Instead, this chapter describes how to configure SSL in the TIBCO Enterprise Message Service server and in client applications that communicate with the server. For a more complete description of SSL, see the TLS specification at <https://tools.ietf.org/html/rfc5246> and the article at https://en.wikipedia.org/wiki/Transport_Layer_Security.

SSL Support in TIBCO Enterprise Message Service

TIBCO Enterprise Message Service supports the Secure Sockets Layer (SSL) protocol.

SSL uses public and private keys to encrypt data over a network connection to secure communication between pairs of components:

- between an EMS client and the `tibemspd` server
- between the `tibemsadmin` tool and the `tibemspd` server
- between two routed servers
- between two fault-tolerant servers
- between the Central Administration server and `tibemspd` servers
- between the Central Administration server and Web browsers

SSL provides secure communication that works with other mechanisms for authentication available in the EMS server. When [authorization](#) is enabled in the server, the connection undergoes a two-phase authentication process. First, an SSL hand-shake between client and server initializes a secure connection. Second, the EMS server checks the credentials of the client using the supplied username and password. If the connecting client does not supply a valid username and password combination, the connection fails, even if the SSL handshake succeeded.



When authorization is enabled, usernames and passwords are always checked, even on SSL secured connections.

Implementations

The TIBCO Enterprise Message Service server and the C client libraries use OpenSSL for SSL support.

For more information, see www.openssl.org.

EMS Java clients use JSSE (from Sun JavaSoft). JSSE is included in Java distributions.

EMS .NET Framework clients use the Microsoft implementation of SSL. The Microsoft implementation of SSL is compatible with OpenSSL. Certificates required by the client can either be stored in files or the Microsoft certificate store. However, Microsoft requires that the root certificate be installed in the Microsoft Certificate Store, even when certificate files are in use.

EMS distributions usually build and include the latest versions of OpenSSL and OpenLDAP publicly available at the time of release. For exact version numbers see the Third Party Software License Agreements documented in the TIBCO Software Inc. End User License Agreement for TIBCO Enterprise Message Service.

Digital Certificates

Digital certificates are data structures that represent identities. EMS uses certificates to verify the identities of servers and clients. Though it is not necessary to validate either the server or the client for them to exchange data over SSL, certificates provide an additional level of security.

A digital certificate is issued either by a trusted third-party certificate authority, or by a security officer within your enterprise. Usually, each user and server on the network requires a unique digital certificate, to ensure that data is sent from and received by the correct party.

In order to support SSL, the EMS server must have a digital certificate. Optionally, EMS clients may also be issued certificates. If the server is configured to verify client certificates, a client must have a certificate and have it verified by the server. Similarly, an EMS client can be configured to verify the server's certificate. Once the identity of the server and/or client has been verified, encrypted data can be transferred over SSL between the clients and server.

A digital certificate has two parts—a public part, which identifies its owner (a user or server); and a private key, which the owner keeps confidential.

The public part of a digital certificate includes a variety of information, such as the following:

- The name of the owner, and other information required to confirm the unique identity of the subject. This information can include the URL of the web server using the digital certificate, or an email address.
- The subject's public key.
- The name of the certificate authority (CA) that issued the digital certificate.
- A serial number.
- The length of time the certificate will remain valid—defined by a start date and an end date.

The most widely-used standard for digital certificates is ITU-T X.509. TIBCO Enterprise Message Service supports digital certificates that comply with X.509 version 3 (X.509v3); most certificate authorities, such as Verisign and Entrust, comply with this standard.

Digital Certificate File Formats

TIBCO Enterprise Message Service supports the following file formats for digital certificates:

- PEM (Privacy Enhanced Mail)
- DER (Distinguished Encoding Rules)
- PKCS#7
- PKCS#12
- Java KeyStore (for client digital certificates)

Private Key Formats

TIBCO Enterprise Message Service supports the following file formats for private keys:

- PEM (Privacy Enhanced Mail)
- DER (Distinguished Encoding Rules)
- PKCS#8
- PKCS#12

The EMS server uses OpenSSL to read private keys. It does *not* read Java KeyStore files.

File Names for Certificates and Keys

For all parameters that specify the identity (digital certificate), private key, issuer (certificate chain), or trusted list of certificate authorities, valid files must be specified. Not all types of files are supported for clients and servers. The description of each parameter details which formats it supports.

The following table lists the valid types of files.

Extension	Description
.pem	PEM encoded certificates and keys (allows the certificate and private key to be stored together in the same file)
.der	DER encoded certificates
.p8	PKCS#8 file
.p7b	PKCS#7 file
.p12	PKCS12 file (allows the certificate and private key to be stored together in the same file)
.jks	Java KeyStore file

Certificates are located in the *EMS_HOME/samples/certs* directory. EMS is installed with some sample certificates and private keys that are used by the sample configuration files.

The sample certificates include:

- A root, self-signed certificate and corresponding private keys in encrypted PEM and PKCS8 formats:

```
server_root.cert.pem
server_root.key.pem
server_root.key.p8
```

- A server certificate and corresponding private keys in encrypted PEM and PKCS8 formats. This certificate is issued by `server_root.cert.pem` and is used by the server:

```
server.cert.pem
server.key.pem
server.key.p8
```

- A root, self-signed certificate and corresponding private key in encrypted PEM and PKCS8 formats.

```
client_root.cert.pem
client_root.key.pem
client_root.key.p8
```

- A client certificate and corresponding private key in encrypted PEM and PKCS8 formats. This certificate is issued by `client_root.cert.pem` and is used by the clients:

```
client.cert.pem
client.key.pem
client.key.p8
```

- A PKCS12 file that includes the `client.cert.pem` client certificate, the `client.key.pem` client private key, and the `client_root.cert.pem` issuer certificate:

```
client_identity.p12
```

- An identity file to be used with the `--https-identity` command line option for Central Administration, along with the corresponding self-signed root certificate to be used by web browsers connecting to Central Administration through HTTPS:

```
emsc_a_https_identity.p12
emsc_a_https_root.cert.pem
```

Configure SSL in the Server

To use SSL, each instance of `tibemsd` must have a digital certificate and a private key. The server can optionally require a certificate chain or trusted certificates.

Set the server to listen for SSL connections from clients by using the `listen` parameter in `tibemsd.conf`. To specify that a port accept SSL connections, specify the SSL protocol in the `listen` parameter as follows:

```
listen = ssl://localhost:7243
```

SSL Parameters

Several SSL parameters can be set in `tibemsd.conf`. The minimum configuration is only one required parameter—`ssl_server_identity`. However, if the server's certificate file does not contain its private key, then you must specify it in `ssl_server_key`.

[SSL Server Parameters](#) provides a complete description of the SSL parameters that can be set in `tibemsd.conf`.

Command Line Options

The server accepts a few command-line options for SSL.

When starting `tibemsd`, you can specify the following options:

- `-ssl_trace`—enables tracing of loaded certificates. This prints a message to the console during startup of the server that describes each loaded certificate.
- `-ssl_debug_trace`—enables more detailed SSL tracing for debugging only; it is not for use in production systems.
- `-ssl_password`—specifies the private key password. Alternatively, you can specify this password in the `ssl_server_password` parameter in `tibemsd.conf`. If you do not supply a password using either of these methods, `tibemsd` will prompt for the password when it starts. For more information, see the description of the `ssl_password` configuration parameter.

Configure SSL in EMS Clients

In basic SSL connections to the EMS server, with standard ciphers, EMS Java clients require no additional libraries or JAR files. The use of ciphers that use stronger encryption may require the installation of the Java Cryptography Extension (JCE) Unlimited Strength Jurisdiction Policy Files into the JRE.

Client Digital Certificates

When client authentication with a digital certificate is required by the EMS server (see the description of the `ssl_require_client_cert` parameter in `tibemsd.conf`), the client may combine its client certificate and private key in a single file in one of the following formats:

- PKCS#12
- Java KeyStore

You can also store the private key file separately from the client certificate file. If this is the case, the certificate and private key must be stored in one of the following formats:

- PEM
- PKCS#8

The format of the client digital certificate and private key file depends on the SSL vendor used by the client. For more information about formats, see your SSL vendor's documentation.

Configure SSL

A client connecting to an EMS server can configure SSL characteristics in the following ways:

- Create a connection factory that specifies the appropriate SSL parameters and use JNDI to lookup the connection factory. The server URL in the connection factory must specify the SSL protocol, and the factory must specify appropriate SSL parameters.

A preconfigured connection factory is the preferred mechanism in many situations. See [Create Connection Factories for Secure Connections](#) and [Perform Secure Lookups](#) for details on how to create a connection factory with SSL parameters in EMS.

- Dynamically create a connection factory, as described in [Dynamically Creating Connection Factories](#) and set the global SSL parameters locally using the `TibjmsSSL` class (Java), `tibemsSSLParams` type (C), or `EMSSSL` class (C#).

Specifying any SSL parameters within a connection factory causes all global SSL parameters set with the `TibjmsSSL` class, `tibemsSSLParams` type or `EMSSSL` class to be ignored.

Configure a Connection Factory

You can configure a connection factory using the administration tool or the EMS Administration APIs.

See [EMS Administration Tool](#).

When configuring a connection factory, you can specify several SSL parameters, similar to the server parameters that you can configure in `tibemsd.conf`.



When configuring a connection factory, EMS does not verify any file names specified in the SSL parameters. At the time the factory is retrieved using JNDI, the EMS server attempts to resolve any file references. If the files do not match the supported types or the files are not found, the JNDI lookup fails with a `ConfigurationException`.



Because connection factories do not contain the `ssl_password` (for security reasons), the EMS server uses the password that is provided in the "create connection" call for user authentication. If the create connection password is different from the `ssl_password`, the connection creation will fail.

The following table describes the SSL parameters that can be set in a connection factory.

For more information about each parameter, see the description of the equivalent parameter in `tibemsd.conf`.

Parameter	Description
<code>ssl_vendor</code>	The vendor name of the SSL implementation that the client uses. Since software release 8.4.0, only one vendor (JSSE) is supported for the Java client, so use of this parameter is optional in that context.
<code>ssl_identity</code>	The client's digital certificate. For more information on file types for digital certificates, see File Names for Certificates and Keys .

Parameter	Description
ssl_issuer	<p>Issuer's certificate chain for the client's certificate. Supply the entire chain, including the CA root certificate. The client reads the certificates in the chain in the order they are presented in this parameter.</p> <p>Example</p> <pre>ssl_issuer = certs\CA_root.pem ssl_issuer = certs\CA_child1.pem ssl_issuer = certs\CA_child2.pem</pre> <p>For more information on file types for digital certificates, see File Names for Certificates and Keys.</p>
ssl_private_key	<p>The client's private key. If the key is included in the digital certificate in <code>ssl_identity</code>, then you may omit this parameter.</p> <p>For more information on file types for digital certificates, see File Names for Certificates and Keys.</p>
ssl_trusted	<p>List of CA certificates to trust as issuers of server certificates. Supply only CA root certificates.</p> <p>For more information on file types for digital certificates, see File Names for Certificates and Keys.</p>
ssl_verify_host	<p>Specifies whether the client should verify the server's certificate. The values for this parameter are <code>enabled</code> or <code>disabled</code>. By default, this parameter is <code>enabled</code>, signifying the client should verify the server's certificate.</p> <p>When <code>disabled</code>, the client establishes secure communication with the server, but does not verify the server's identity.</p>
ssl_verify_hostname	<p>Specifies whether the client should verify the name in the CN field of the server's certificate. The values for this parameter are <code>enabled</code> and <code>disabled</code>. By default, this parameter is <code>enabled</code>, signifying the client should verify the name of the connected host or the name specified in the <code>ssl_expected_hostname</code> parameter against the value in the server's certificate. If the names do not match, the client rejects the connection.</p> <p>When <code>disabled</code>, the client establishes secure communication with the server, but does not verify the server's name.</p>
ssl_expected_hostname	<p>The name the client expects in the CN field of the server's certificate. If this parameter is not set, the expected name is the hostname of the server.</p> <p>The value of this parameter is used when the <code>ssl_verify_hostname</code> parameter is <code>enabled</code>.</p>
ssl_ciphers	<p>Specifies the cipher suites that the client can use.</p> <p>Supply a colon-separated list of cipher names. Names may be either OpenSSL names, or longer descriptive names.</p> <p>For more information, see Specify Cipher Suites.</p>

Parameter	Description
<code>ssl_auth_only</code>	<p>Specifies whether SSL should be used to encrypt all server-client communications, or only client authentication.</p> <p>When enabled, the client requests SSL be used only for authentication. The server then uses TCP communications for further data exchange. When disabled or absent, all communication between the client and server must be SSL encrypted.</p> <p>For an overview of this feature, see SSL Authentication Only.</p>
<code>ssl_rand_egd</code>	<p>The path for the entropy gathering daemon (EGD), if one is installed. This daemon generates random data for the client.</p>

ConnectionFactory SSL parameters

For more information about each parameter, see the description of the equivalent parameter in [tibemsd.conf](#).

Parameter	Description
<code>ssl_vendor</code>	<p>The vendor name of the SSL implementation that the client uses. Since software release 8.4.0, only one vendor (JSSE) is supported for the Java client, so use of this parameter is optional in that context.</p>
<code>ssl_identity</code>	<p>The client's digital certificate.</p> <p>For more information on file types for digital certificates, see File Names for Certificates and Keys.</p>
<code>ssl_issuer</code>	<p>Issuer's certificate chain for the client's certificate. Supply the entire chain, including the CA root certificate. The client reads the certificates in the chain in the order they are presented in this parameter.</p> <p>Example</p> <pre>ssl_issuer = certs\CA_root.pem ssl_issuer = certs\CA_child1.pem ssl_issuer = certs\CA_child2.pem</pre> <p>For more information on file types for digital certificates, see File Names for Certificates and Keys.</p>
<code>ssl_private_key</code>	<p>The client's private key. If the key is included in the digital certificate in <code>ssl_identity</code>, then you may omit this parameter.</p> <p>For more information on file types for digital certificates, see File Names for Certificates and Keys.</p>
<code>ssl_trusted</code>	<p>List of CA certificates to trust as issuers of server certificates. Supply only CA root certificates.</p> <p>For more information on file types for digital certificates, see File Names for Certificates and Keys.</p>

Parameter	Description
<code>ssl_verify_host</code>	<p>Specifies whether the client should verify the server's certificate. The values for this parameter are <code>enabled</code> or <code>disabled</code>. By default, this parameter is <code>enabled</code>, signifying the client should verify the server's certificate.</p> <p>When <code>disabled</code>, the client establishes secure communication with the server, but does not verify the server's identity.</p>
<code>ssl_verify_hostname</code>	<p>Specifies whether the client should verify the name in the CN field of the server's certificate. The values for this parameter are <code>enabled</code> and <code>disabled</code>. By default, this parameter is <code>enabled</code>, signifying the client should verify the name of the connected host or the name specified in the <code>ssl_expected_hostname</code> parameter against the value in the server's certificate. If the names do not match, the client rejects the connection.</p> <p>When <code>disabled</code>, the client establishes secure communication with the server, but does not verify the server's name.</p>
<code>ssl_expected_hostname</code>	<p>The name the client expects in the CN field of the server's certificate. If this parameter is not set, the expected name is the hostname of the server.</p> <p>The value of this parameter is used when the <code>ssl_verify_hostname</code> parameter is <code>enabled</code>.</p>
<code>ssl_ciphers</code>	<p>Specifies the cipher suites that the client can use.</p> <p>Supply a colon-separated list of cipher names. Names may be either OpenSSL names, or longer descriptive names.</p> <p>For more information, see Specify Cipher Suites.</p>
<code>ssl_auth_only</code>	<p>Specifies whether SSL should be used to encrypt all server-client communications, or only client authentication.</p> <p>When <code>enabled</code>, the client requests SSL be used only for authentication. The server then uses TCP communications for further data exchange. When <code>disabled</code> or absent, all communication between the client and server must be SSL encrypted.</p> <p>For an overview of this feature, see SSL Authentication Only.</p>
<code>ssl_rand_egd</code>	<p>The path for the entropy gathering daemon (EGD), if one is installed. This daemon generates random data for the client.</p>

Specify Cipher Suites

On the EMS server, specify cipher suites using the `ssl_server_ciphers` configuration parameter in `tibemsd.conf`.

For more information about server configuration files, see [Configuration Files](#).

For clients connecting with a connection factory, specify cipher suites using the `ssl_ciphers` connection factory parameter. For more information, see [Configure SSL in EMS Clients](#).

Syntax for Cipher Suites

EMS uses OpenSSL for SSL support. Therefore, the cipher suite names can be specified as the OpenSSL name for the cipher suite.

When specifying cipher suites, the usual way to specify more than one cipher suite is to separate each suite name with a colon (:) character. Alternatively, you can use spaces and commas to separate names.

Java Client Syntax

The syntax for specifying the list of cipher suites is different for Java clients than for any other location where cipher suites can be specified. For Java clients, you specify a qualifier (for example, + to add the suite) followed by the cipher suite name. Cipher suite names are case-sensitive. The following table describes the qualifiers you can use when specifying cipher suite names in a ConnectionFactory for Java clients.

Qualifier	Description
+	Add the cipher to the list of ciphers.
-	Remove the cipher from the list of ciphers.
>	Move the cipher to the end of the list.
<	Move the cipher to the beginning of the list.
ALL	<p>All ciphers from the list (except null ciphers). You can use this keyword to add or remove all ciphers.</p> <p>At least one cipher suite must be present, otherwise the SSL connection fails to initialize. So, if you use -ALL, you must subsequently add the desired ciphers to the list.</p>

This example specifies cipher suites in the `ssl_ciphers` connection factory parameter in a Java client:

```
-ALL:+AES128-SHA:+AES256-SHA:<DES-CBC3-SHA
```

This example specifies cipher suites using Java names:

```
-ALL:+TLS_RSA_WITH_AES_128_CBC_SHA:+TLS_RSA_WITH_AES_256_CBC_SHA:<SSL_RSA_WITH_3DES_EDE_CBC_SHA
```

Syntax for All Other Cipher Suite Specifications

For any cipher suite list that is not specified in a connection factory of a Java client, use the OpenSSL syntax. In particular, C clients and the `ssl_server_ciphers` configuration parameter require OpenSSL syntax.

In OpenSSL syntax, specifying a cipher suite name adds that cipher suite to the list. Each cipher suite name can be preceded by a qualifier. Cipher suite names are case-sensitive. The following table describes the qualifiers available using OpenSSL syntax.

Qualifier	Description
/	<p>When entered as the first item in the list, this option causes EMS to begin with an empty list, and add the ciphers that follow the slash.</p> <p>If the / does not prefix the cipher list, then EMS prefixes the cipher list with the OpenSSL cipher string DEFAULT.</p> <p>This modifier can only be used at the beginning of the list. If the / appears elsewhere, the syntax of the cipher suite list will be incorrect and cause an error.</p>
+	<p>Moves the cipher to the end of the list.</p> <p>This qualifier is used to move an existing cipher. It can not be used to add a new cipher to the list.</p>
-	<p>Remove the cipher from the list of ciphers. When this option is used, the cipher can be added later on in the list of ciphers.</p>
!	<p>Permanently disable the cipher within the list of ciphers. Use this option if you wish to remove a cipher and you do not want later items in the list to add the cipher to the list. This qualifier takes precedence over all other qualifiers.</p>
ALL	<p>All ciphers from the list (except null ciphers). You can use this keyword to add or remove all ciphers.</p> <p>At least one cipher suite must be present or the SSL connection fails to initialize. So, after using -ALL, you should add at least one cipher to the list.</p>

This example specifies cipher suites in the `ssl_server_ciphers` configuration parameter.

```
ssl_server_ciphers = -ALL:AES128-SHA:AES256-SHA:DES-CBC3-SHA
```

This example illustrates disabling AES128-SHA, then adding all other ciphers:

```
ssl_server_ciphers = !AES128-SHA:ALL
```

Default Cipher List

The EMS server and C client library use DEFAULT as their default cipher list. For details on the cipher suites corresponding to DEFAULT for a given version of OpenSSL, refer to the OpenSSL documentation.

Supported Cipher Suites

The EMS server and C client library support a subset of the cipher suites that OpenSSL supports. For a complete list, see the output of the `help ciphers` command in the administration tool.

Supported Cipher Suites for Java Clients

Java clients support only the cipher suites listed in the following table. For convenience, the table lists both the Java name and the OpenSSL name for each cipher suite. For Java clients, restrictions apply to some of the newer cipher suites. Using these may require adjustments to some of the following: JVM version, JVM vendor, JCE unlimited strength jurisdiction policy files, the `java.security` properties file, and X509 certificate digital signature algorithms. For details, contact TIBCO Support.

Java Name (OpenSSL Name)	Protocol Version	Key Exch	Auth	Encrypt	Key Size	MAC
SSL_RSA_WITH_RC4_128_SHA (RC4-SHA)						

Java Name (OpenSSL Name)	Protocol Version	Key Exch	Auth	Encrypt	Key Size	MAC
	SSLv3	RSA	RSA	RC4	128	SHA1
SSL_RSA_WITH_3DES_EDE_CBC_SHA (DES-CBC3-SHA)						
	SSLv3	RSA	RSA	3DES	168	SHA1
SSL_DHE_RSA_WITH_3DES_EDE_CBC_SHA (EDH-RSA-DES-CBC3-SHA)						
	SSLv3	DH	RSA	3DES	168	SHA1
SSL_DHE_DSS_WITH_3DES_EDE_CBC_SHA (EDH-DSS-DES-CBC3-SHA)						
	SSLv3	DH	DSS	3DES	168	SHA1
TLS_RSA_WITH_AES_128_CBC_SHA (AES128-SHA)						
	SSLv3	RSA	RSA	AES	128	SHA1
TLS_RSA_WITH_AES_256_CBC_SHA (AES256-SHA)						
	SSLv3	RSA	RSA	AES	256	SHA1
TLS_DHE_DSS_WITH_AES_128_CBC_SHA (DHE-DSS-AES128-SHA)						
	SSLv3	DH	DSS	AES	128	SHA1
TLS_DHE_DSS_WITH_AES_256_CBC_SHA (DHE-DSS-AES256-SHA)						
	SSLv3	DH	DSS	AES	256	SHA1
TLS_DHE_RSA_WITH_AES_128_CBC_SHA (DHE-RSA-AES128-SHA)						
	SSLv3	DH	RSA	AES	128	SHA1
TLS_DHE_RSA_WITH_AES_256_CBC_SHA (DHE-RSA-AES256-SHA)						
	SSLv3	DH	RSA	AES	256	SHA1
TLS_RSA_WITH_AES_128_CBC_SHA256 (AES128-SHA256)						
	TLSv1.2	RSA	RSA	AES	128	SHA256

Java Name (OpenSSL Name)	Protocol Version	Key Exch	Auth	Encrypt	Key Size	MAC
TLS_RSA_WITH_AES_256_CBC_SHA256 (AES256-SHA256)						
	TLSv1.2	RSA	RSA	AES	256	SHA256
TLS_DHE_DSS_WITH_AES_128_CBC_SHA256 (DHE-DSS-AES128-SHA256)						
	TLSv1.2	DH	DSS	AES	128	SHA256
TLS_DHE_RSA_WITH_AES_128_CBC_SHA256 (DHE-RSA-AES128-SHA256)						
	TLSv1.2	DH	RSA	AES	128	SHA256
TLS_DHE_DSS_WITH_AES_256_CBC_SHA256 (DHE-DSS-AES256-SHA256)						
	TLSv1.2	DH	DSS	AES	256	SHA256
TLS_DHE_RSA_WITH_AES_256_CBC_SHA256 (DHE-RSA-AES256-SHA256)						
	TLSv1.2	DH	RSA	AES	256	SHA256
TLS_RSA_WITH_AES_128_GCM_SHA256 (AES128-GCM-SHA256)						
	TLSv1.2	RSA	RSA	AESGCM	128	AEAD
TLS_RSA_WITH_AES_256_GCM_SHA384 (AES256-GCM-SHA384)						
	TLSv1.2	RSA	RSA	AESGCM	256	AEAD
TLS_DHE_RSA_WITH_AES_128_GCM_SHA256 (DHE-RSA-AES128-GCM-SHA256)						
	TLSv1.2	DH	RSA	AESGCM	128	AEAD
TLS_DHE_RSA_WITH_AES_256_GCM_SHA384 (DHE-RSA-AES256-GCM-SHA384)						
	TLSv1.2	DH	RSA	AESGCM	256	AEAD
TLS_DHE_DSS_WITH_AES_128_GCM_SHA256 (DHE-DSS-AES128-GCM-SHA256)						
	TLSv1.2	DH	DSS	AESGCM	128	AEAD

Java Name (OpenSSL Name)	Protocol Version	Key Exch	Auth	Encrypt	Key Size	MAC
TLS_DHE_DSS_WITH_AES_256_GCM_SHA384 (DHE-DSS-AES256-GCM-SHA384)						
	TLSv1.2	DH	DSS	AESGCM	256	AEAD
TLS_ECDHE_ECDSA_WITH_RC4_128_SHA (ECDHE-ECDSA-RC4-SHA)						
	SSLv3	ECDH	ECDSA	RC4	128	SHA1
TLS_ECDHE_ECDSA_WITH_3DES_EDE_CBC_SHA (ECDHE-ECDSA-DES-CBC3-SHA)						
	SSLv3	ECDH	ECDSA	3DES	168	SHA1
TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA (ECDHE-ECDSA-AES128-SHA)						
	SSLv3	ECDH	ECDSA	AES	128	SHA1
TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA (ECDHE-ECDSA-AES256-SHA)						
	SSLv3	ECDH	ECDSA	AES	256	SHA1
TLS_ECDHE_RSA_WITH_RC4_128_SHA (ECDHE-RSA-RC4-SHA)						
	SSLv3	ECDH	RSA	RC4	128	SHA1
TLS_ECDHE_RSA_WITH_3DES_EDE_CBC_SHA (ECDHE-RSA-DES-CBC3-SHA)						
	SSLv3	ECDH	RSA	3DES	168	SHA1
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA (ECDHE-RSA-AES128-SHA)						
	SSLv3	ECDH	RSA	AES	128	SHA1
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA (ECDHE-RSA-AES256-SHA)						
	SSLv3	ECDH	RSA	AES	256	SHA1
TLS_ECDHE_ECDSA_WITH_AES_128_CBC_SHA256 (ECDHE-ECDSA-AES128-SHA256)						
	TLSv1.2	ECDH	ECDSA	AES	128	SHA256

Java Name (OpenSSL Name)	Protocol Version	Key Exch	Auth	Encrypt	Key Size	MAC
TLS_ECDHE_ECDSA_WITH_AES_256_CBC_SHA384 (ECDHE-ECDSA-AES256-SHA384)						
	TLSv1.2	ECDH	ECDSA	AES	256	SHA384
TLS_ECDHE_RSA_WITH_AES_128_CBC_SHA256 (ECDHE-RSA-AES128-SHA256)						
	TLSv1.2	ECDH	RSA	AES	128	SHA256
TLS_ECDHE_RSA_WITH_AES_256_CBC_SHA384 (ECDHE-RSA-AES256-SHA384)						
	TLSv1.2	ECDH	RSA	AES	256	SHA384
TLS_ECDHE_ECDSA_WITH_AES_128_GCM_SHA256 (ECDHE-ECDSA-AES128-GCM-SHA256)						
	TLSv1.2	ECDH	ECDSA	AESGCM	128	AEAD
TLS_ECDHE_ECDSA_WITH_AES_256_GCM_SHA384 (ECDHE-ECDSA-AES256-GCM-SHA384)						
	TLSv1.2	ECDH	ECDSA	AESGCM	256	AEAD
TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 (ECDHE-RSA-AES128-GCM-SHA256)						
	TLSv1.2	ECDH	RSA	AESGCM	128	AEAD
TLS_ECDHE_RSA_WITH_AES_256_GCM_SHA384 (ECDHE-RSA-AES256-GCM-SHA384)						
	TLSv1.2	ECDH	RSA	AESGCM	256	AEAD



Some updates of Java may deactivate compromised cipher suites. If absolutely required, check the Java documentation to reactivate them.

Enterprise Message Service does not support these cipher suites:

- SSL_RSA_WITH_RC4_128_MD5
- SSL_RSA_EXPORT_WITH_RC2_CBC_40_MD5
- SSL_RSA_EXPORT_WITH_RC4_40_MD5
- SSL_RSA_EXPORT_WITH_DES_40_CBC_SHA
- SSL_DHE_RSA_EXPORT_WITH_DES_40_CBC_SHA
- SSL_DHE_DSS_EXPORT_WITH_DES_40_CBC_SHA
- SSL_RSA_WITH_NULL_MD5
- SSL_RSA_WITH_NULL_SHA
- SSL_RSA_WITH_DES_CBC_SHA
- SSL_DHE_DSS_WITH_DES_CBC_SHA
- SSL_DHE_RSA_WITH_DES_CBC_SHA

Although they are not supported, they are included in the interface definition only to allow old programs to compile correctly. Use the SSL authentication only feature in place of these cipher suites. See [SSL Authentication Only](#) below for more information.

Supported Cipher Suites for .NET Clients

In general, the .NET client library supports the cipher suites that .NET supports. Refer to your MSDN documentation or contact Microsoft support for complete details on supported ciphers on specific .NET environments.

SSL Authentication Only

EMS servers can use SSL for secure data exchange (standard usage), or only for client authentication. This section describes the use of SSL for client authentication.

Motivation

Some applications require strong or encrypted authentication, but do not require message encryption.

In this situation, application architects could configure SSL with a null cipher. However, this solution incurs internal overhead costs of SSL calls, decreasing message speed and throughput.

For optimal performance, the preferred solution is to use SSL only to authenticate clients, and then avoid SSL calls thereafter, using ordinary TCP communications for subsequent data exchange. Message performance remains unaffected.

Preconditions

All the following preconditions must be satisfied to use SSL only for authentication:

- The server and clients must both be release 4.2 or later. (If not, EMS behavior reverts to using SSL for all communications throughout the life of the connection.)
- The server must explicitly enable the parameter `ssl_auth_only` in the `tibemsd.conf` configuration file.
- The client program must request a connection that uses SSL for authentication only. Clients can specify this request in factories by enabling the `ssl_auth_only` parameter, or by calling:
 - Java: `TibjmsSSL.setAuthOnly`
 - C: `tibemsSSLParams_SetAuthOnly`
 - C#: `EMSSSL.SetAuthOnly`

See Also

Server parameter `ssl_auth_only`

Client parameter `ssl_auth_only`

Enable FIPS Compliance

You can enable TIBCO Enterprise Message Service to run in compliance with Federal Information Processing Standard (FIPS), Publication 140-2.

Enable the EMS Server



The EMS server supports FIPS compliance only on the Linux, Solaris, and Windows platforms.

To enable FIPS 140-2 operations in the EMS server:

- Set the `fips140-2` parameter in the main configuration file to `true`.
- Ensure that incompatible parameters, listed below, are not included in the server configuration files.
- Ensure that the `ssl_server_ciphers` parameter for the EMS server is configured to use a supported cipher suite. Supported cipher suites are listed below.

When `fips140-2` is enabled, on start-up the EMS server initializes in compliance with FIPS 140-2. If the initialization is successful, the EMS server prints a message indicating that it is operating in this mode. If the initialization fails, the server exits (regardless of the `startup_abort_list` setting).

Incompatible Parameters

In order to operate in FIPS compliant mode, you must not include these parameters in the `tibemsd.conf` file:

- `ssl_dh_size`
- `ssl_server_ciphers`
- `ldap_tls_rand_file`
- `ldap_tls_cipher_suite`
- `ft_ssl_ciphers`

These parameters cannot be included in the `routes.conf` file:

- `ssl_ciphers`

Supported Cipher Suites

Only the following cipher suites are supported by the EMS server when it is started in FIPS mode:

- AES128-SHA
- AES256-SHA
- DES-CBC3-SHA
- DHE-DSS-AES128-SHA
- DHE-DSS-AES256-SHA
- DHE-RSA-AES128-SHA
- DHE-RSA-AES256-SHA
- EDH-DSS-DES-CBC3-SHA
- EDH-RSA-DES-CBC3-SHA

Enable EMS Clients

Java and C client applications can operate in FIPS compliance:

- **Java Clients**

Java clients that use JSSE can operate in FIPS 140-2 compliant mode by using a FIPS 140-2 compliant cryptographic provider that supports the PKCS#11 interface. This interface is described in the Oracle documentation. A good starting point is the *PKCS#11 Reference Guide*. See <https://docs.oracle.com/javase/8/docs/technotes/guides/security/p11guide.html>. You are responsible for procuring and configuring such a provider.

- To enable FIPS 140-2 operations in the Java client:
 - Download and install the Java Cryptography Extension (JCE) Unlimited Strength Jurisdiction Policy Files for your JDK installation. These files are available on the Sun Microsystems website.
 - Install a FIPS 140-2 compliant cryptographic token (hardware or software) that has a PKCS#11 interface, as per the token provider's instructions.
 - You or the token provider should configure the cryptographic token.
 - Modify the `JAVA_HOME/lib/security/java.security` file to include the PKCS#11 provider and the location of the relevant configuration file. Refer to the Java documentation for additional details: <https://docs.oracle.com/javase/8/docs/technotes/guides/security/p11guide.html#Config>.
 - Set the `com.tibco.tibjms.ssl.PKCS11` property to `true` before calling any EMS methods.

- **C Clients**

C clients that link to the dynamic EMS libraries can operate in FIPS 140-2 compliant mode. FIPS compliance is not available with static libraries.

To enable FIPS 140-2 operations in the C client, use compliant OpenSSL libraries, and initialize the libraries to enable FIPS 140-2 operations before calling any EMS functions.



The Java and C clients support FIPS compliance only on the Linux, Solaris, and Windows platforms.

Fault Tolerance

The following sections describe the fault tolerance features of TIBCO Enterprise Message Service.

Fault Tolerance Overview

You can arrange TIBCO Enterprise Message Service servers for fault-tolerant operation by configuring a pair of servers—one primary and one secondary.

Upon startup, the first server to start reaches the active state and the other the standby state. The active server accepts client connections, and interacts with clients to deliver messages. If the active server fails, the standby server becomes active and resumes operation in its place.


Shared State

A pair of fault-tolerant servers can have access to shared state, which consists of information about clients and persistent messages.



You cannot use more than two servers in a fault-tolerant configuration.

This information enables the standby server to properly assume responsibility for those clients and messages. The following image illustrates a fault-tolerant configuration of EMS.



Locking


To prevent the standby server from assuming the role of the active server, the active server locks the shared state during normal operation. If the active server fails, the lock is released, and the standby server can obtain the lock and become active.

Unshared State Failover

You can also include additional servers that do not share state. As with shared state, the clients can automatically reconnect to additional servers.

However, unlike shared state, unshared state is controlled by the EMS client. As a result, it is up to client producers to catch failures on send that may occur during an unshared state failover, and to then resend the affected message. As this may lead to duplicate or out-of-order messages, the corresponding client consumers should be equipped to filter out duplicates and re-order messages if dictated by the application requirements.

The following image illustrates an unshared state fault-tolerant configuration of EMS.



Shared State Failover Process

This section presents details of the shared state failover sequence.


Detection

A standby server detects a failure of the active server in either of the following ways: Heartbeat Failure or Connection Failure.

- *Heartbeat Failure*—The active server sends heartbeat messages to the standby server to indicate that it is still operating. When a network failure stops the servers from communicating with each other, the standby server detects the interruption in the steady stream of heartbeats. For details, see [Heartbeat Parameters](#).
- *Connection Failure*—The standby server can detect the failure of its TCP connection with the active server. When the active server process terminates unexpectedly, the standby server detects the broken connection.

Response

When a standby server (B) detects the failure of the active server (A), then B attempts to assume the role of active server. First, B obtains the lock on the current shared state. When B can access this information, it becomes the new active server.




Lock Unavailable

If B cannot obtain the lock immediately, it alternates between attempting to obtain the lock (and become the active server), and attempting to reconnect to A (and resume as a standby server)—until one of these attempts succeeds.

Role Reversal

When B becomes the new active server, A can restart as a standby server, so that the two servers exchange roles.



Client Transfer

Clients of A that are configured to failover to standby server B automatically transfer to B when it becomes the new active server. B reads the client's current state from the shared storage to deliver any persistent messages to the client.

Client Notification

Client applications can receive notification when shared state failover occurs.

- **Java**
To receive notification, Java client programs set the system property `tibco.tibjms.ft.switch.exception` to any value, and define an `ExceptionListener` to handle failover notification; see the class `com.tibco.tibjms.Tibjms` in *TIBCO Enterprise Message Service Java API Reference*.
- **C**
To receive notification, C client programs call `tibems_setExceptionOnFTSwitch(TIBEMS_TRUE)` and register the exception callback in order to receive the notification that the reconnection was successful.
- **C#**
To receive notification, .NET client programs call `Tibems.SetExceptionOnFTSwitch(true)`, and define an exception listener to handle failover notification; see the method `Tibems.SetExceptionOnFTSwitch` in *TIBCO Enterprise Message Service .NET API Reference*.

Message Redelivery

Qualified messages will be redelivered in a failover situation.

- **Persistent**
When a failure occurs, messages with delivery mode `PERSISTENT`, that were not successfully acknowledged before the failure, are redelivered.
- **Synchronous Mode**
When using durable subscribers, EMS guarantees that a message with `PERSISTENT` delivery mode and written to a `store` with the property `mode=sync`, will not be lost during a failure.

- Delivery Succeeded

Any messages that have been successfully acknowledged or committed are not redelivered, in compliance with the JMS specification.

- Topics

All topic subscribers continue normal operation after a failover.

Transactions

A (non-XA) transaction is considered active when at least one message has been sent or received by the session, and the transaction has not been successfully committed. An XA transaction is considered active when the XA start method is called.

After a failover, attempting to commit the active transaction results in a `javax.jms.TransactionRolledBackException`. Clients that use transactions must handle this exception, and resend any messages sent during the transaction. The standby server, upon becoming active, automatically redelivers any messages that were delivered to the session during the transaction that rolled back.

Queues

For queue receivers, any messages that have been sent to receivers, but have not been acknowledged before the failover, may be sent to other receivers immediately after the failover.

A receiver trying to acknowledge a message after a failover may receive the `javax.jms.IllegalStateException`. This exception signifies that the attempted acknowledgment is for a message that has already been sent to another queue receiver. This exception only occurs in this scenario, or when the session or connection have been closed. This exception cannot occur if there is only one receiver at the time of a failover, but it may occur for exclusive queues if more than one receiver was started for that queue.

When a queue receiver catches a `javax.jms.IllegalStateException`, the best course of action is to call the `Session.recover()` method. Your application program should also be prepared to handle redelivery of messages in this situation. All queue messages that can be redelivered to another queue receiver after a failover always have the header field `JMSRedelivered` set to true; application programs must check this header to avoid duplicate processing of the same message in the case of redelivery.



Acknowledged messages are never redelivered (in compliance with the JMS specification). The case described above occurs when the application cannot acknowledge a message because of a failover.

Heartbeat Parameters

When the active server heartbeat stops, the standby server waits for its activation interval (elapsed time since it detected the most recent heartbeat); then the standby server retrieves information from shared storage and assumes the role of active server.

The default heartbeat interval is 3 seconds, and the default activation interval is 10 seconds. The activation interval must be at least twice the heartbeat interval. Both intervals are specified in seconds. You can set these intervals in the server configuration files. See [Fault Tolerance Parameters](#) for details.

Configuration Files

When an active server fails, its standby server assumes the status of the active server and resumes operation. Before becoming the active server, the standby server re-reads its configuration files.

If the two servers share configuration files, then the administrative changes to an active server carry over to its standby once the latter becomes active.



When fault-tolerant servers share configuration files, you must limit configuration changes to the active server only. Separately reconfiguring the standby server can cause it to overwrite the shared configuration files; unintended misconfiguration can result.

Additionally, when a server that is a member of a fault-tolerant pair requires a restart, both servers must be restarted to activate the change. When the active server is shut down, the standby server does not reinitialize its properties (such as listens, heartbeats, timeouts, and so on) or stores during activation. It does reinitialize objects such as queues, topics, factories, routes, and so on.


Unshared State Failover Process

The following topics detail the unshared state failover sequence of events.

To configure clients, see [Configure Clients for Unshared State Failover Connections](#).

Detection

Unshared state failover is initiated by the EMS client. When a client setup for unshared state detects a lost connection to server (A), it attempts to connect to server (B), as defined in the connection factory.



Unshared state is not limited to two servers. Unlike shared state failover, unshared state is controlled by the EMS client. The client can include more than two URLs in its list of additional servers.

Response

Clients with unshared state connections automatically connect to B after losing the connection to A.

When clients setup for unshared state detect lost connections to server A, they create new connections to server B. All runtime objects from the client's connection are recreated, including sessions, destinations, message producers, and message consumers.

Because unshared state is defined in the connection factory, B remains the current server as long as the connection is active. If the connection to B is lost, clients attempt to connect to another server defined in the connection factory.

Message Loss

Because B does not have access to persistent messages that were not delivered or acknowledged prior to the failover, some messages may be lost or delivered out of order across the failover process. To prevent message loss, use shared state failover.

Unsupported Features

These features and Java classes are not supported with unshared state connections:


- XA transactions

- Durable topic subscribers
- ConnectionConsumer
- ServerSession
- ServerSessionPool
- QueueRequestor
- TopicRequestor

Dual State Failover

An unshared state connection factory can include shared-state server pairs in its list of backup servers. When both shared state and unshared state servers are included, the failover process is a combination of both types of failover.

The following image illustrates the dual state failover process.



In this example, servers A1 and A2 share state. Servers B1 and B2 also share state. However, A1 and A2 do not share state with B1 and B2.

The EMS clients created connections using a connection factory with A1, A2 + B1, B2. The initial server connections were with server A1. When the connection to A1 failed, the failover process proceeded as described in [Shared State Failover Process](#), and the clients connect to A2.

A2 then failed, before A1 restarted. The clients next created connections to B1, recreating all runtime objects from the connection (as described above in [Unshared State Failover Process](#)). B1 is now the active server. Because B1 and B2 share state, If B1 fails, B2 becomes the active server.

Shared State

For the most robust failover protection, the active server and standby server must share the same state.

Shared state includes the following categories of information:

- persistent message data (for queues and topics)
- client connections of the active server
- metadata about message delivery

During a failover, the standby server re-reads all shared state information.

Implement Shared State

We recommend that you implement shared state using shared storage devices. The shared state must be accessible to both the active and standby servers.

Support Criteria

If your stores are file-based, there are several options available for implementing shared storage, using a combination of hardware and software. EMS requires that your storage solution guarantees the following listed criteria.

Note that these criteria are inherently satisfied by database store implementations.



Always consult your shared storage vendor and your operating system vendor to ascertain that the storage solution you select satisfies all four criteria.

Criterion	Description
Write Order	The storage solution must write data blocks to shared storage in the same order as they occur in the data buffer. (Solutions that write data blocks in any other order (for example, to enhance disk efficiency) do <i>not</i> satisfy this requirement.)
Synchronous Write Persistence	Upon return from a synchronous write call, the storage solution guarantees that all the data have been written to durable, persistent storage.
Distributed File Locking	The EMS servers must be able to request and obtain an exclusive lock on the shared storage. The storage solution must <i>not</i> assign the locks to two servers simultaneously. (See Software Options .) EMS servers use this lock to determine the primary server.
Unique Write Ownership	The EMS server process that has the file lock must be the only server process that can write to the file. Once the system transfers the lock to another server, pending writes queued by the previous owner must fail.

Hardware Options

Consider these examples of commonly-sold hardware options for shared storage:

- Dual-Port SCSI device

- Storage Area Network (SAN)
- Network Attached Storage (NAS)

SCSI and SAN

Dual-port SCSI and SAN solutions generally satisfy the [Write Order](#) and [Synchronous Write Persistence](#) criteria. (The clustering software must satisfy the remaining two criteria.) As always, you must confirm all four requirements with your vendors.

NAS

NAS solutions require a CS (rather than a CFS) to satisfy the [Distributed File Locking](#) criterion (see below).

Some NAS solutions satisfy the criteria, and some do not; you must confirm all four requirements with your vendors.

NAS with NFS

When NAS hardware uses NFS as its file system, it is particularly difficult to determine whether the solution meets the criteria. Our research indicates the following conclusions:

- NFS v2 and NFS v3 definitely do *not* satisfy the criteria.
- NFS v4 with TCP *might* satisfy the criteria. Consult with the NAS vendor to verify that the NFS server (in the NAS) satisfies the criteria. Consult with the operating system vendor to verify that the NFS client (in the OS on the server host computer) satisfies the criteria. When both vendors certify that their components cooperate to guarantee the criteria, then the shared storage solution supports EMS.

For more information on how the EMS locks shared store files, see [Managing Access to Shared Store Files](#).

Software Options

Consider these examples of commonly-sold software options:

- Cluster Server (CS)

A cluster server monitors the EMS server processes and their host computers, and ensures that exactly one server process is running at all times. If that server fails, the CS restarts it; if the CS fails to restart it, it starts the other server instead.

- Clustered File System (CFS)

A clustered file system lets the two EMS server processes run simultaneously. It even lets both servers mount the shared file system simultaneously. However, the CFS assigns the lock to only one server process at a time. The CFS also manages operating system caching of file data, so the standby server has an up-to-date view of the file system (instead of a stale cache).

With dual-port SCSI or SAN hardware, either a CS or a CFS might satisfy the [Distributed File Locking](#) criterion. With NAS hardware, only a CS can satisfy this criterion (CFS software generally does not). Of course, you must confirm all four requirements with your vendors.

Messages Stored in Shared State

Messages with PERSISTENT delivery mode are stored, and are available in the event of active server failure. Messages with NON_PERSISTENT delivery mode are not available if the active server fails.

For more information about recovery of messages during failover, see [Message Redelivery](#).

Storage Files

By default, the `tibemsd` server creates three file-based stores to store shared state.

- `$sys.failsafe`—This store holds persistent messages using synchronous I/O calls.
- `$sys.nonfailsafe`—This file stores messages using asynchronous I/O calls.
- `$sys.meta`—This store holds state information about durable subscribers, fault-tolerant connections, and other metadata.

These stores are fully customizable through parameters in the stores configuration file. More information about these files and the default configuration settings are fully described in [stores.conf](#).

To prevent two servers from using the same store file, each server restricts access to its store file for the duration of the server process. For more information on how the EMS manages shared store files, see [Managing Access to Shared Store Files](#).



These default files can be changed or modified. See [Default Store Files](#) for more information.

Storage Parameters

Several configuration parameters apply to EMS storage files (even when fault-tolerant operation is not configured).

For more information, see [Storage File Parameters](#).

Configure Fault-Tolerant Servers

The following topics describe how to configure fault-tolerant servers, for the shared state and the unshared state scenarios.

Shared State

To configure an EMS server as a fault-tolerant secondary, set parameters in its main configuration file (or on the server command line).

- `server` Set this parameter to the same server name in the configuration files of both the primary server and the secondary server.
- `ft_active` In the configuration file of the primary server, set this parameter to the URL of the secondary server. In the configuration file of the secondary server, set this parameter to the URL of the active server.

When a server configured for fault tolerance starts, it attempts to connect to its peer server. If it establishes a connection to its peer, then it enters the standby state. If it cannot establish a connection to its peer, then it becomes the active server.

While a server is in the standby state, it does not accept connections from clients. To administer the standby server, the admin user can connect to it using the administration tool. Standby servers started with a JSON configuration file cannot be administered.

Authorization and Fault-Tolerant Servers

EMS authorization interacts with fault tolerance. If [authorization](#) is enabled and the two EMS Servers are configured for fault tolerance, then both servers in a fault-tolerant pair must be configured.

The following files have to be updated:

- The `tibemsd.conf` file for each server must have the same server name and password (the server and password parameters must be the same on each server).
- The user name and password in the `users.conf` file for each server must match the values of the server and password parameters in the `tibemsd.conf` file.



If the two EMS Servers are not sharing a `users.conf` file, make sure that you create a user with the same name as the EMS Server, and set the user's password with the value of the "server" password.

For example, you have two EMS Servers (Server 1 and Server 2) that are named "EMS-SERVER" and are to use a password of "mySecret", but which do not share a `users.conf` file. To set the user names and passwords, start the EMS Administration Tool on each server, as described in [EMS Administration Tool](#), and do the following.

From the active (Server 1), enter:

```
set server password=mySecret
create user EMS-SERVER password=mySecret
```

From the standby (Server 2), enter:

```
set server password=mySecret
create user EMS-SERVER password=mySecret
```

From the active (Server 1), enter:

```
set server authorization=enabled
```

From the standby (Server 2), enter:

```
set server authorization=enabled
```

SSL

You can use SSL to secure communication between a pair of fault-tolerant servers.

Parameters in the main configuration file (`tibemsd.conf`) affect this behavior. The relevant parameters all begin with the prefix `ft_ssl`.

The server initializing a secure connection to another server uses the `ft_ssl` parameters to determine the properties of its secure connection to the other server. The receiving server validates the incoming connection against its own `ssl_` parameters. For more information about `ft_ssl` parameters, see [Fault Tolerance Parameters](#). For more information about `ssl_` parameters, see [SSL Server Parameters](#).

Also see [SSL Protocol](#).

Reconnect Timeout

When a standby server assumes the role of the active server during failover, clients attempt to reconnect to the standby server (that is, the new active) and continue processing their current message state. Before accepting reconnects from the clients, the new active server reads its message state from the shared state files.

You can instruct the server to clean up state information for clients that do not reconnect before the time limit specified by the `ft_reconnect_timeout` configuration parameter. The `ft_reconnect_timeout` time starts once the server has fully recovered the shared state, so this value does not account for the time it takes to recover the store files. See [ft_reconnect_timeout](#) for details.

Unshared State

When configuring a fault tolerant pair that does not share state, you must ensure that both servers use identical configurations.

This is especially important for these configuration settings:

- **Destinations**
Both servers must support the same destinations.
- **Routes**
Messages must be able to arrive at the endpoints, using equivalent or identical routes across servers.

- **Access Control**

Access control must be setup identically in both servers, so that the `users.conf`, `groups.conf`, and `acl.conf` file settings match.

- **SSL**

When SSL is deployed, both servers must use the same certificate(s).

Fault Tolerance in Central Administration

Central Administration uses the same JSON configuration file to manage both servers in a fault tolerant pair. Primary and secondary server roles are determined when the servers are started.

All but two configuration settings are shared by both EMS servers: the `listen` and `ft_active` parameters are configured separately.

- The primary server, if elected active, listens for client connection on ports defined in the main Server Properties page, in the Primary Listens section. If elected standby, it listens for the secondary server on the Secondary Listens URL that is flagged using the FT Active radio button on the Fault Tolerance properties page.
- Conversely, the secondary server, if elected standby, listens for the primary server using the Primary Listens URL that is flagged with the FT Active radio button on the main Server Properties page. If elected active, it listens for client connections using the Secondary Listen URLs defined on the Fault Tolerance page.

For more information on Central Administration, see *TIBCO Enterprise Message Service Central Administration*.

Configuring Fault Tolerance

To configure a fault tolerant server pair using Central Administration:

Procedure

1. Configure the primary server as usual.
2. On the [Server Properties](#) page, designate the URL on which the secondary server listens for the primary server by clicking the **FT Active** radio button next to the desired Listens URL.
3. On the [Fault Tolerance](#) properties page, configure the Secondary Listens URLs that the secondary server uses to listen for client connections in the event that it becomes the active server.
4. Designate the URL on which the primary server listens for the secondary server, should a failure occur and the secondary server becomes active. Click the **FT Active** radio button next to the desired Secondary Listens URL.
5. Configure the remaining fault tolerance properties on the Fault Tolerance page.
6. Deploy the configuration changes.
7. Start the primary and secondary EMS servers using the method described in [Starting Fault Tolerant Server Pairs](#).

Configuration Errors

When an EMS server is started, the fault tolerance mechanism is triggered by the presence of a URL in the Secondary Listens list of a primary `tibemsd`, or by that of a URL in the Primary Listens list of a secondary `tibemsd`.

Once fault tolerance is triggered, the EMS server generates an error if it finds that the "FT Active" switch was not assigned to any URL in its peer's list. If `CONFIG_ERRORS` is present in the [startup_abort_list](#) parameter, the `tibemsd` aborts startup. Otherwise, the `tibemsd` cancels fault

tolerance and starts without checking its peer. This results in a file lock error for the EMS server that is started second.

Configure Clients for Shared State Failover Connections

When a failover occurs and the standby server takes the active state, clients attempt to reconnect to this server (that is, the new active server). To enable a client to reconnect, you must specify the URLs of both servers when creating a connection.

Specify multiple servers as a comma-separated list of URLs. Both URLs must use the same protocol (either `tcp` or `ssl`). For example, to identify the first server as `tcp://server0:7222`, and the second server as `tcp://server1:7344` (if first server is not available), you can specify:

```
serverUrl=tcp://server0:7222, tcp://server1:7344
```

The client attempts to connect to each URL in the order listed. If a connection to one URL fails, the client tries the next URL in the list. The client tries the URLs in sequence until all URLs have been tried. If the first failed connection was not the first URL in the list, the attempts wrap to the start of the list (so each URL is tried).

For information on how to lookup a fault-tolerance URL in the EMS naming service, see [Perform Fault-Tolerant Lookups](#).



The reconnection logic in the client is triggered by the specifying multiple URLs when connecting to a server. If no secondary server is present, the client must still provide at least two URLs (typically pointing to the same server) in order for it to automatically reconnect to the server when it becomes available after a failure.



When messages are sent in non-persistent or reliable modes, the consumer does not normally wait for a server reply to its acknowledgements. However, a fault tolerant consumer does wait for a server reply (when using an session mode other than `DUPS_OK_ACKNOWLEDGE` or `EXPLICIT_CLIENT_DUPS_OK_ACKNOWLEDGE`). This is true for shared state configurations. Unshared state configurations, which tolerate lost, duplicated, and out-of-order messages during a failover, do not wait for server acknowledgements.

Specify More Than Two URLs

Even though there are only two servers (the primary and secondary servers), clients can specify more than two URLs for the connection.

For example, if each server has more than one listen address, a client can reconnect to the same server at a different address (that is, at a different network interface).

Set Reconnection Failure Parameters

EMS allows you to establish separate parameters for initial connection attempts and reconnection attempts.

How to set the initial connection attempt parameters is described in [Set Connection Attempts, Timeout and Delay Parameters](#). This section describes the parameters you can establish for reconnection attempts following a fault-tolerant failover.

The reason for having separate connect and reconnect attempt parameters is that there is a limit imposed by the operating system to the number of connection attempts the EMS server can handle at any particular time. (For example, in Unix, this limit is adjusted by the `ulimit` setting.) Under normal circumstances, each connect attempt is distributed so it is less likely for the server to exceed its maximum accept queue. However, during a fault-tolerant failover, all of the clients automatically try to reconnect to the new active server at approximately the same time. When the number of connections is large, it may require more time for each client to reconnect than for the initial connect.

By default, a client will attempt reconnection 4 times with a 500 ms delay between each attempt. You can modify these settings in the `factories.conf` file or by means of your client connection factory API, as demonstrated by the examples in this section.

The following examples establish a reconnection count of 10, a delay of 1000 ms and a timeout of 1000 ms.

- Java

Use the `TibjmsConnectionFactory` object's `setReconnAttemptCount()`, `setReconnAttemptDelay()`, and `setReconnAttemptTimeout()` methods to establish new reconnection failure parameters.

```
factory.setReconnAttemptCount(10);
factory.setReconnAttemptDelay(1000);
factory.setReconnAttemptTimeout(1000);
```

- C

Use the `tibemsConnectionFactory_SetReconnectAttemptCount`, `tibemsConnectionFactory_SetReconnectAttemptDelay`, and `tibemsConnectionFactory_SetReconnectAttemptTimeout` functions to establish new reconnection failure parameters.

```
status = tibemsConnectionFactory_SetReconnectAttemptCount(factory, 10);
status = tibemsConnectionFactory_SetReconnectAttemptDelay(factory, 1000);
status = tibemsConnectionFactory_SetReconnectAttemptTimeout(factory, 1000);
```

- C#

Use the `ConnectionFactory.SetReconnAttemptCount`, `ConnectionFactory.SetReconnAttemptDelay`, and `ConnectionFactory.SetReconnAttemptTimeout` methods to establish new reconnection failure parameters:

```
factory.setReconnAttemptCount(10);
factory.setReconnAttemptDelay(1000);
factory.setReconnAttemptTimeout(1000);
```

Configure Clients for Unshared State Failover Connections



Unshared state failover is an extension of the JMS specification. Because state is not shared among servers, messages can be lost, duplicated, or delivered out-of-order across the failover process.

Unshared state connections are created differently from shared state connections in several important ways.

- For Java applications, a JAR file must be present in the environment CLASSPATH of the client.
- For C applications, a header file must be included and clients must link using the unshared state library.
- The connection must be created using an unshared state connection factory.
- The server URLs must be specified using unshared state syntax.

Include the Unshared State Library

- Java Applications

Before creating the connection factory, ensure that the CLASSPATH includes the JAR file:

```
tibjmsufo.jar
```

- C Applications

Include the `tibemsufo.h` header file.

- C# Applications

Include the `TIBCO.EMS.UFO.dll` file.

Create an Unshared State Connection Factory

To create unshared state connections, use the relevant methods:

- Java Applications
java com.tibco.tibems.ufo package.
- C Applications
tibemsufo library and functions.
- C# Applications
TIBCO.EMS.UFO package.

Methods called inside a `MessageListener` callback immediately return an `EMSEException` indicating the connection has been terminated.

Connection Recovery

When an unshared state connection fails, the connection's `ExceptionListener` callback is invoked. To recover the connection—repair it so that it is connected to an active server—the client application calls the connection factory's `recoverConnection` method or `tibemsUFOConnectionFactory_RecoverConnection` function.

This must be performed in the `ExceptionListener` callback. The recover connection method blocks until the connection (and its related objects, including sessions, producers, and consumers) are fully recreated, or until it has failed in all its attempts to recreate these objects.

As long as the unshared state client has a valid connection, the API behaves the same as the standard EMS client. However, when the unshared state client's connection is broken, the API performs as follows:

1. Methods called inside a `MessageListener` callback immediately return a Java exception `ConnectionFactoryException` or C status of `TIBEMS_SERVER_NOT_CONNECTED`.
2. Methods called elsewhere block until the connection is valid again.

Note that the connection is considered broken from the point where the underlying TCP/SSL connection fails, and until `recoverConnection` or `tibemsConnectionFactory_RecoverConnection` successfully returns.

Specify Server URLs

When a server connection is lost during an unshared state failover, clients attempt to reconnect to the second server. To enable a client to reconnect, you must specify the URLs of both servers when creating a connection.

- **Unshared State**

Specify multiple servers as a list of URLs separated by plus (+) signs. For example, to identify the first server as `tcp://server0:7222`, and the second server as `tcp://server1:7344`, you can specify:

```
serverUrl=tcp://server0:7222+tcp://server1:7344
```

- **Dual State**

To combine shared state server pairs with unshared state servers, use commas to separate the servers that share state, and plus (+) signs to separate servers that do not share state. For example, this line specifies server a1 and a2 as a fault-tolerant pair that share state, and servers b1 and b2 as a second pair with shared state:

```
serverUrl=tcp://a1:8222,tcp://a2:8222+tcp://b1:8222,tcp://b2:8222
```


Note that a1 and a2 do not share state with b1 and b2.

The client attempts to connect to each URL in the order listed. If a connection to one URL fails, the client tries the next URL in the list. The client tries the URLs in sequence until all URLs have been tried. If the first failed connection was not the first URL in the list, the attempts wrap to the start of the list (so each URL is tried). If none of the attempts succeed, the connection fails.



Server lookup functions do not permit unshared state syntax. That is, you cannot separate server URLs using the plus (+) symbol during a server lookup.

Set Connect Attempt and Reconnect Attempt Behavior

The effect of setting connect attempt and reconnect attempt properties at the application level is different when applied to unshared state connection factories.

If the EMS client is using a shared state connection factory, then the values specified by way of properties or API calls will be the values used during client connect and reconnect sequences. However, if the client is using an unshared state factory, then the application layer values do not directly override the `connect_attempt_count` and `reconnect_attempt_count` properties set in the unshared state connection factory. Instead, the value specified at the application level is multiplied by the value in the connection factory to determine the resulting count. Also if the `connect_attempt_delay` and/or `reconnect_attempt_delay` are overridden at the application layer, the resulting actual delays can vary significantly from the override value.

For example, if the unshared state connection factory has a `connect_attempt_count` value of 5 and the Java system property `com.tibco.tibjms.connect.attempts` is set to 3 for the Java client, then the effective `connect_attempt_count` will be 15.

See Also

The connection factory connect attempt and reconnect attempt properties are documented in [factories.conf](#).

The sections [Set Connection Attempts, Timeout and Delay Parameters](#) and [Set Reconnection Failure Parameters](#) describe the use of these settings.

Routes

The following sections describe routing of messages among TIBCO Enterprise Message Service servers.

Overview

TIBCO Enterprise Message Service servers can route messages to other servers.

- Topic messages can travel one hop or multiple hops (from the first server).
- Queue messages can travel only one hop to the home queue, and one hop from the home queue.


You can define routes using an administrative interface (that is, configuration files, `tibemsadmin`, or administration APIs).

Route

Basic Operation

- Each *route* connects two TIBCO Enterprise Message Service servers.
- Each route forwards messages between corresponding destinations (that is, global topics with the same name, or explicitly routed queues) on its two servers.
- Routes are bidirectional; that is, each server in the pair forwards messages along the route to the other server.

For example, the compact view at the top of the following image denotes a route between two servers, A and B. The exploded view beneath it illustrates the behavior of the route. Each server has a global topic named T1, and a routed queue Q1; these destinations correspond, so the route forwards messages between them. In addition, server A has a global topic T2, which does not correspond to any topic on server B. The route does not forward messages from T2.



Global Destinations

Routes forward messages only between global destinations—that is, for topics the `global` property must be set on both servers (for queues, see [Routed Queues](#)).

For more information about destination properties, See [Destination Properties](#).

The following image illustrates a route between two servers, C and D, with corresponding destinations T1 and T2. Notice that T1 is global on both C and D, so both servers forward messages across the route to the corresponding destination. However, T2 is not global on C, neither C nor D forward T2 messages to one another.



Unique Routing Path


It is illegal to define a set of routes that permit a message to reach a server by more than one path. TIBCO Enterprise Message Service servers detect illegal duplicate routes and report them as configuration errors.

The following image depicts two sets of routes. On the left, the routes connecting servers A, B, C, D and E form an acyclic graph, with only one route connecting any pair of servers; this configuration is legal (in any zone).

In contrast, the routing configuration on the right is illegal in a multi-hop zone. The graph contains redundant routing paths between servers Q and S (one direct, and one through R and T).



Note that the configuration on the right is illegal only in a multi-hop zone; it is legal in a one-hop zone. For further information, see [Zone](#).



Zone

Zones restrict the behavior of routes, so you can configure complex routing paths. Zones affect topic messages, but not queue messages.

Basic Operation


A *zone* is a named set of routes. Every route belongs to a zone.

A zone affects the forwarding behavior of its routes:

- In a multi-hop (mhop) zone, topic messages travel along all applicable routes to all servers connected by routes within the zone.
- In a one-hop (1hop) zone, topic messages travel only one hop (from the first server).

- Queue messages travel only one hop, even within multi-hop zones.

For example, the following figure depicts a set of servers connected by routes within a multi-hop zone, Z1. If a client sends a message to a global topic on server B, the servers forward the message to A, C, D and E (assuming there are subscribers at each of those servers). In contrast, if Z1 were a one-hop zone, B would forward the message to A, C and D—but D would *not* forward it E.




Eliminate Redundant Paths with a One-Hop Zone

The following image illustrates an enterprise with four servers:

- B1 and B2 serve producers at branch offices of an enterprise.
- M serves consumers at the main office, which process the messages from the branches.
- R serves consumers that record messages for archiving, auditing, and backup.

The goal is to forward messages from B1 and B2 to both M and R. The routing graph *seems* to contain a cycle—the path from B1 to M to B2 to R duplicates the route from B1 to R. However, since these routes belong to the one-hop zone Z2, it is impossible for messages to travel the longer path. Instead, this limitation results in the desired result—forwarding from B1 to M and R, and from B2 to M and R.




Overlapping Zones

A server can have routes that belong to several zones. When zones overlap at a server, the routing behavior within each zone does not limit routing in other zones. That is, when a forwarded message reaches a server with routes in several zones, the message crosses zone boundaries, and its hop count is reset to zero.

The following image illustrates an enterprise with one-hop zones connecting all the servers in each of several cities in a fully-connected graph. Zone TK connects all the servers in Tokyo; zone NY connects all the servers in New York; zone PA connects all the servers in Paris. In addition, the multi-hop zone WO connects one server in each city.

When a client of server TK3 produces a message, it travels one hop to each of the other Tokyo servers. When the message reaches TK1, it crosses into zone WO. TK1 forwards the message to NY1, which in

turn forwards it to PA1. When the message reaches NY1, it crosses into zone NY (with hop count reset to zero); NY1 forwards it one hop to each of the other New York servers. Similarly, when the message reaches PA1, it crosses into zone PA (with hop count reset to zero); PA1 forwards it one hop to each of the other Paris servers.



Active and Passive Routes

A route connects two servers. You may configure a route at either or both of the servers.

Active-Passive Routes

When you configure a route at only one server, this asymmetry results in different perspectives on the route.

- A route is *active* from the perspective of the server where it is configured. This server actively initiates the connection to the other server, so we refer to it as the *active server*, or *initiating server*.
- A route is *passive* from the perspective of the other server. This server passively accepts connection requests from the active server, so we refer to it as the *passive server*.

A server can have both active and passive routes. That is, you can configure server S to initiate routes, and also configure other servers to initiate routes to S.

You can specify and modify the properties of an active route, but not those of a passive route. That is, properties of routes are associated with the server where the route is configured, and which initiates the connection.



Defining a route specifies a zone as well (either implicitly or explicitly). The first route in the zone defines the type of the route; subsequent routes in the same zone must have the same zone type (otherwise, the server reports an error).

Active-Active Routes

Two servers can both configure an active route one to the other. This arrangement is called an *active-active configuration*.

For example, server A specifies a route to server B, and B specifies a route to A. Either server can attempt to initiate the connection. This configuration results in only one connection; it does not result in redundant routes.

You can promote an *active-passive* route to an *active-active* route. To promote a route, use this command on the passive server:

```
create route name url=url
```

The *url* argument is required, so that the server (where the route is being promoted) can connect to the other server if the route becomes disconnected. See [create route](#) for more information.

The promoted route behaves as a statically configured route—that is, it persists messages for durable subscribers, and stores its configuration in [routes.conf](#), and administrators can modify its properties.

Configure Routes and Zones

You can create routes using the administration tool, or the administration APIs (see `com.tibco.tibjms.admin.RouteInfo` in the online documentation).

Syntax

To create a route using the administration tool, first connect to one of the servers, then use the `create route` command with the following syntax:

```
create route name url=URL zone_name=zone_name zone_type=1hop|mhops properties
```

- *name* is the name of the server at the other end of the route; it also becomes the name of the route.
- *URL* specifies the other server by its URL—including protocol and port.

If your environment is configured for fault tolerance, the URL can be a comma-separated list of URLs denoting fault-tolerant servers. For more information about fault tolerance, see [Fault Tolerance](#).

- *zone_name* specifies that the route belongs to the routing zone with this name. When absent, the default value is `default_mhop_zone` (this default yields backward compatibility with configurations from releases earlier than 4.0).
- The zone type is either `1hop` or `mhop`. When omitted, the default value is `mhop`.
- *properties* is a space-separated list of properties for the route. Each property has the syntax:

```
prop_name=value
```

For gating properties that control the flow of topics along the route, see [Selectors for Routing Topic Messages](#).

For properties that configure the Secure Sockets Layer (SSL) protocol for the route, see [Routing and SSL](#).

Example

For example, these commands on server A would create routes to servers B and C. The route to B belongs to the one-hop zone Z1. The route to C belongs to the multi-hop zone ZM.

```
create route B url=tcp://B:7454 zone_name=Z1 zone_type=1hop
create route C url=tcp://C:7455 zone_name=ZM zone_type=mhop
```

Show Routes

You can display these routes using the `show routes` command in the administration tool:

show	routes				
Route	T	ConnID	URL	Zone	T
B	A	3	tcp://B:7454	Z1	1
C	A	-	tcp://C:7455	ZM	m

- The Route column lists the name of the passive server.
- The T column indicates whether the route is active (A) or passive (P), from the perspective of server A.
- The ConnID column contains either an integer connection ID if the route is currently connected, or a dash (-) if the route is not connected.

Routes to Fault-Tolerant Servers

You can configure servers for fault tolerance. Client applications can specify the primary and secondary servers.

Once a client has connected to the active server, if its connection to the server fails, the client can connect to the standby server and resume operation. Similarly, a route specification can specify primary and secondary passive servers, so that if the route to the active-state server fails, the active-route server can connect to the standby-state server and resume routing.

Failover behavior for route connections is similar to that for client connections; see [Configure Clients for Shared State Failover Connections](#).

Example

```
create route B url=tcp://B:7454,tcp://BBackup:7454 zone_name=Z1 zone_type=1hop
```

Routing and SSL

When configuring a route, you can specify SSL parameters for the connection. Although both participants in an SSL connection must specify a similar set of parameters, each server specifies this information in a different place.

- The passive server must specify SSL parameters in its main configuration file, `tibemsd.conf`.
- When a server initiates an SSL connection, it sends the route's SSL parameters to identify and authenticate itself to the passive server. You can specify these parameters when creating the route, or you can specify them in the route configuration file, `routes.conf`.

You can configure the server to require a digital certificate only for SSL connections coming from routes, while not requiring such a certificate for SSL connections coming from clients or from its fault-tolerant peer.

For more information, see [ssl_require_route_cert_only](#).

SSL Parameters for Routes

The following table lists parameters that you can specify in the `routes.conf` configuration file, or on the command line when creating a route. The parameters for configuring SSL between routed servers are similar to the parameters used to configure SSL between server and clients; see [SSL Protocol](#).

Parameter	Description
<code>ssl_identity</code>	<p>The server's digital certificate in PEM, DER, or PKCS#12 format. You can copy the digital certificate into the specification for this parameter, or you can specify the path to a file that contains the certificate in one of the supported formats.</p> <p>For more information, see File Names for Certificates and Keys.</p>
<code>ssl_issuer</code>	<p>Certificate chain member for the server. Supply the entire chain, including the CA root certificate. The server reads the certificates in the chain in the order they are presented in this parameter.</p> <p>The certificates must be in PEM, DER, PKCS#7 or PKCS#12 format.</p> <p>Example</p> <pre>ssl_issuer = certs\CA_root.pem ssl_issuer = certs\CA_child1.pem ssl_issuer = certs\CA_child2.pem</pre> <p>For more information, see File Names for Certificates and Keys.</p>
<code>ssl_private_key</code>	<p>The local server's private key. If the digital certificate in <code>ssl_identity</code> already includes this information, then you may omit this parameter.</p> <p>This parameter accepts private keys in PEM, DER and PKCS#12 formats.</p> <p>You can specify the actual key in this parameter, or you can specify a path to a file that contains the key.</p> <p>For more information, see File Names for Certificates and Keys.</p>
<code>ssl_password</code>	<p>Private key or password for private keys.</p> <p>You can set passwords using the <code>tibemsadmin</code> tool. When passwords are set with this tool, the password is obfuscated in the configuration file. For more information, see Using the EMS Administration Tool.</p>
<code>ssl_trusted</code>	<p>List of certificates that identify trusted certificate authorities.</p> <p>The certificates must be in PEM, DER or PKCS#7 format. You can either provide the actual certificates, or you can specify a path to a file containing the certificate chain.</p> <p>For more information, see File Names for Certificates and Keys.</p>
<code>ssl_verify_host</code>	<p>Specifies whether the server must verify the other server's certificate. The values for this parameter are <code>enabled</code> and <code>disabled</code>.</p> <p>When omitted, the default is <code>enabled</code>, signifying the server must verify the other server's certificate.</p> <p>When this parameter is <code>disabled</code>, the server establishes secure communication with the other server, but does not verify the server's identity.</p>

Parameter	Description
<code>ssl_verify_hostname</code>	<p>Specifies whether the server must verify the name in the CN field of the other server's certificate. The values for this parameter are enabled and disabled.</p> <p>When omitted, the default is enabled, signifying the server must verify the name of the connected host or the name specified in the <code>ssl_expected_hostname</code> parameter against the value in the server's certificate. If the names do not match, the connection is rejected.</p> <p>When this parameter is disabled, the server establishes secure communication with the other server, but does not verify the server's name.</p>
<code>ssl_expected_hostname</code>	<p>Specifies the name expected in the CN field of the other server's certificate. If this parameter is not set, the default is the hostname of the other server.</p> <p>This parameter is relevant only when the <code>ssl_verify_hostname</code> parameter is enabled.</p>
<code>ssl_ciphers</code>	<p>Specifies a list of cipher suites, separated by colons (:).</p> <p>This parameter accepts both the OpenSSL name for cipher suites, or the longer descriptive names.</p> <p>For information about available cipher suites and their names, see Specify Cipher Suites.</p>
<code>ssl_rand_egd</code>	<p>The path for the installed entropy gathering daemon (EGD), if one is installed. This daemon generates random numbers.</p>

Routed Topic Messages

A server forwards topic messages along routes only when the global property is defined for the topic.

Topic messages can traverse multiple hops.

When a route becomes disconnected (for example, because of network problems), the forwarding server stores topic messages. When the route reconnects, the server forwards the stored messages.


Servers connected by routes do exchange messages sent to temporary topics.

For more information, see [addprop topic](#) and [create topic](#).

Registered Interest Propagation

To ensure forwarding of messages along routes, servers propagate their topic subscriptions to other servers.

For example, the top of the following image depicts an enterprise with three servers—A, M and B—connected by routes in a multi-hop zone. The bottom of the figure illustrates the mechanism at work within the servers to route messages from a producer client of server A, through server M, to server B and its subscriber client. Consider this sequence of events.



1. All three servers configure a global topic T1.
2. At bottom right of the above figure, a client of server B creates a subscriber to T1.
3. Server B, registers interest in T1 on behalf of the client by creating an internal subscriber object.
4. Because a route connects servers M and B, server B propagates its interest in T1 to server M. In response, M creates an internal subscriber to T1 on behalf of server B. This subscriber ensures that M forwards (that is, delivers) messages from topic T1 to B. Server B behaves as a client of server M.
5. Similarly, because a route connects servers A and M, server M propagates its interest in T1 to server A. In response, A creates an internal subscriber to T1 on behalf of server M. This subscriber ensures that A forwards messages from topic T1 to M. Server M behaves as a client of server A.
6. When a producer client of server A sends a message to topic T1, A forwards it to M. M accepts the message on its topic T1, and forwards it to B. B accepts the message on its topic T1, and passes it to the client.

Subscriber Client Exit

If the client of server B creates a *non-durable* subscriber to T1, then if the client process exits, the servers delete the entire sequence of internal subscribers. When the client restarts, it generates a new sequence of subscribers; meanwhile, the client might have missed messages.

If the client of server B creates a *durable* subscriber to T1, then if the client process exits, the entire sequence of internal subscribers remains intact; messages continue to flow through the servers in store-and-forward fashion. When the client restarts, it can consume all the messages that B has stored in the interim.

Server Failure

In an active-active route between servers B and M, if B fails, then M retains its internal subscriber and continues to store messages for clients of B. When B reconnects, M forwards the stored messages.

In an active-passive route configured on B, if B fails, then M removes its internal subscriber and does not store messages for clients of B—potentially resulting in a gap in the message stream. When B reconnects, M creates a new internal subscriber and resumes forwarding messages.

In an active-passive route configured on A, if either server fails, then M retains its internal subscriber in the same way as an active-active route. However, B does not retain its internal state which it uses to

suppress duplicate messages from A and can deliver messages to its consumers after they have consumed them. Therefore, if it is desirable to not lose messages and to not have duplicate messages, the route should be active-active.

Network Failure

If an active-passive connection between B and M is disrupted, M displays the same behavior as during a server failure.

maxbytes

Combining durable subscribers with routes creates a potential demand for storage—especially in failure situations. For example, if server B fails, then server M stores messages until B resumes. We recommend that you set the `maxbytes` or `maxmsgs` property of the topic (T1) on each server, to prevent unlimited storage growth (which could further disrupt operation).

Selectors for Routing Topic Messages

A server forwards a global topic message along routes to all servers with subscribers for that topic. When each of those other servers requires only a small subset of the messages, this policy could potentially result in a high volume of unwanted network traffic.


You can specify *message selectors* on routes to narrow the subset of topic messages that traverse each route.



Message selectors on routes are different from message selectors on individual subscribers, which narrow the subset of messages that the server delivers to the subscriber client.

Example

The following figure illustrates an enterprise with a central server for processing customer orders, and separate regional servers for billing those orders. For optimal use of network capacity, we configure topic selectors so that each regional server gets only those orders related to customers within its region.



Specifying Selectors

Specify message selectors for global topics as properties of routes. You can define these properties in two ways:

- Define selectors when creating the route (either in `routes.conf`, or with the administrator command `create route`).
- Manipulate selectors on an existing route (using the `addprop`, `setprop`, or `removeprop` administrator commands).



If you change the message selectors on a route, only incoming messages are evaluated against the new selectors. Messages pending in the server are re-evaluated only if the server is restarted.

Syntax

The message selector properties have the same syntax whether they appear in a command or in a configuration file:

```
incoming_topic=topicName selector="msg-selector"
outgoing_topic=topicName selector="msg-selector"
```

The terms *incoming* and *outgoing* refer to the perspective of the active server—where the route is defined.



topicName is the name of a global topic.

msg-selector is a message selector string. For detailed information about message selector syntax, see the documentation for class `Message` in *TIBCO Enterprise Message Service Java API Reference*.

Example Syntax

As described in [Example](#), an administrator might configure these routes on the central order server:

```
setprop route Canada outgoing_topic="orders" selector="country='Canada' "
setprop route Mexico outgoing_topic="orders" selector "country='Mexico' "
setprop route USA outgoing_topic="orders" selector="country='USA' "
```

Those commands would create these entries in `routes.conf`:

```
[Canada]
url=ssl://canada:7222
outgoing_topic=orders selector="country='Canada' "
...
[Mexico]
url=ssl://mexico:7222
outgoing_topic=orders selector="country='Mexico' "
...
[USA]
url=ssl://usa:7222
outgoing_topic=orders selector="country='USA' "
...
```

Symmetry

`outgoing_topic` and `incoming_topic` are symmetric. Whether A specifies a route to B with `incoming_topic` selectors, or B specifies a route to A with `outgoing_topic` selectors, the effect is the same. That is, B sends only those messages that match the selector over the route.

Active-Active Configuration

In an active-active configuration, you may specify selectors on either or both servers. If you specify `outgoing_topic` selector S1 for topic T on server A, and `incoming_topic` selector S2 for T on server B, then the effective selector for T on the route from A to B is (S1 AND S2).

See also [Active and Passive Routes](#).

Wildcards

You can specify wildcards in topic names. For each actual topic, the server uses logical AND to combine all the selectors that match the topic.

However, routing of topic messages is only reliably supported when the subscriber's topic is a subset (or equal) of the configured global topic. Similarly, intersections are not supported. For example, if `topics.conf` contains `foo.*` and `foo.a*`, the following subscriptions are correct:

```
foo.*
foo.1
bar.a.b
```

The following subscriptions are *not* correct:

```
foo.>
bar.*.b
```


Routed Queues

With respect to routing, queues differ from topics in several respects.

These differences can be summarized as:

- Servers route queue messages between the queue owner and adjacent servers.
- The concept of zones and hops does not apply to queue messages (only to topic messages).

The left side of the following image depicts an enterprise with three servers—P, R and S—connected by routes. The remainder of the image illustrates the mechanisms that routes queue messages among servers (center) and their clients (right side).



Owner and Home

Server R defines a global queue named Q1. R is the *owner* of Q1.

Servers P and S define *routed queues* Q1@R. This designation indicates that these queues depend upon and reflect their *home queue* (that is, Q1 on server R). Notice that the designation Q1@R is only for the purpose of configuration; clients of P refer to the routed queue as Q1.

Example

When J sends a message to Q1, server P forwards the message to the home queue—Q1 on server R.

Now the message is available to receivers on all three servers, P, R and S—although only one client can consume the message. Either Q1 on P receives it on behalf of K; or Q1 on S receives it on behalf of N; or M receives it directly from the home queue.

Producers

From the perspective of producer clients, a routed queue stores messages and forwards them to the home queue. For example, when J sends a message to Q1 on server P, P forwards it to the queue owner, R, which delivers it to Q1 (the home queue).

The message is not available for consumers until it reaches the home queue. That is, client K cannot consume the message directly from server P.

If server R fails, or the route connection from P to R fails, P continues to store messages from K in its queue. When P and R resume communication, P delivers the stored messages to Q1 on R.

Similarly, routed queues do not generate an exception when the `maxbytes` and `maxmsgs` limits are exceeded in the routed server. Clients can continue to send messages to the queue after the limit is reached, and the messages will be stored in the routed server until the error condition is cleared.

Consumers

From the perspective of consumer clients, a routed queue acts as a proxy receiver. For example, when L sends a message to Q1 on server R, Q1 on P can receive it from R on behalf of K, and immediately gives it to K.

If server P fails, or the route connection from P to R fails, K cannot receive messages from Q1 until the servers resume communication. Meanwhile, M and N continue to receive messages from Q1. When P and R resume communication, K can again receive messages through Q1 on P.



Receiving messages from a routed queue using either a small timeout (less than one second) or no wait can cause unexpected behavior. A small timeout value increases the chances that protocol messages may not be processed correctly between the routed servers. For example, queue receivers may not be correctly destroyed.

Configuration

You must explicitly configure each routed queue in `queues.conf`—clients cannot create routed queues dynamically.



Dynamic routed queues are not supported. In a future release, the server will consider a routed queue with a wildcard as a misconfiguration and will fail to start when `startup_abort_list` includes `CONFIG_ERRORS`.

You may use the administration tool or API to configure routed queues; see `addprop queue` and `create queue`.

To configure a routed queue, specify the queue name and the server name of the queue owner; for example, on server P, configure:

```
Q1@R
```



It is legal to use this notation even for the home queue. The queue owner recognizes its own name, and ignores the location designation (@R).

It is illegal to configure a routed queue as `exclusive`.

Browsing

Queue browsers cannot examine routed queues. That is, you can create a browser only on the server that owns the home queue.


Transactions

TIBCO Enterprise Message Service does not support transactional consumers on routed queues (through the use of XA or local transacted sessions).

Routing and Authorization

User & Password

When a server's [authorization](#) parameter is enabled, other servers that actively connect to it must authenticate themselves by name and password, or by X.509 certificate.



In the above image, servers A and B both configure active routes to one another.

- Because A enables authorization, A must configure a user named B.
- However, because B disables authorization, A need not identify itself to B, and B need not configure a user named A.

ACL

When routing a secure topic or queue, servers consult the ACL specification before forwarding each message. The servers must grant one another appropriate permissions to send, receive, publish or subscribe.

For example, in above image, you don't need an ACL for messages to flow from A (where a producer is sending to) to B (where a consumer is consuming from) because B has authorization turned off and messages are being sent to and consumed from queues. However, if messages were to flow from B to A (producer connects to B and consumer connects to A), then server A's ACL should grant user B send permission on the queue Q2.

If we were to use topics in this example, then for messages to flow from A to B, you would need A to grant B the `subscribe` and `durable` permission on the topic ([global](#) on both servers). And for messages to flow from B to A, you would have to grant topic B `publish` permission on the topic.

Also see [Authentication and Permissions](#).

Monitor Messages

This section lists all the topics on which the server publishes messages for system events. The message properties for messages published on each topic are also described.

See [Monitor Server Events](#) for more information about monitor topics and messages.

Description of Monitor Topics

Topic	Message Is Published When...
<code>\$sys.monitor.admin.change</code>	The administrator has made a change to the configuration.
<code>\$sys.monitor.connection.connect</code>	A user attempts to connect to the server.
<code>\$sys.monitor.connection.disconnect</code>	A user connection is disconnected.
<code>\$sys.monitor.connection.error</code>	An error occurs on a user connection.
<code>\$sys.monitor.consumer.create</code>	A consumer is created.
<code>\$sys.monitor.consumer.destroy</code>	A consumer is destroyed.
<code>\$sys.monitor.flow.engaged</code>	Stored messages rise above a destination's limit, engaging the flow control feature.
<code>\$sys.monitor.flow.disengaged</code>	Stored messages fall below a destination's limit, disengaging the flow control feature.
<code>\$sys.monitor.limits.connection</code>	Maximum number of hosts or connections is reached.
<code>\$sys.monitor.limits.queue</code>	Maximum bytes for queue storage is reached.
<code>\$sys.monitor.limits.server</code>	Server memory limit is reached.
<code>\$sys.monitor.limits.topic</code>	Maximum bytes for durable subscriptions is reached.
<code>\$sys.monitor.producer.create</code>	A producer is created.
<code>\$sys.monitor.producer.destroy</code>	A producer is destroyed.
<code>\$sys.monitor.queue.create</code>	A dynamic queue is created.
<code>\$sys.monitor.route.connect</code>	A route connection is attempted.
<code>\$sys.monitor.route.disconnect</code>	A route connection is disconnected.
<code>\$sys.monitor.route.warning</code>	An issue worth warning about occurs on a route connection.
<code>\$sys.monitor.route.error</code>	An error occurs on a route connection.

Topic	Message Is Published When...
<code>\$sys.monitor.route.interest</code>	A change in registered interest occurs on the route.
<code>\$sys.monitor.server.info</code>	The server sends information about an event; for example, a log file is rotated.
<code>\$sys.monitor.server.warning</code>	The active server detects a disconnection from the standby server.
<code>\$sys.monitor.topic.create</code>	A dynamic topic is created.
<code>\$sys.monitor.tx.action</code>	A local transaction commits or rolls back.
<code>\$sys.monitor.xa.action</code>	An XA transaction commits or rolls back.

Topic	Message Is Published When...
<code>\$sys.monitor.D.E.destination</code>	<p>A message is handled by a destination. The name of this monitor topic includes two qualifiers (<i>D</i> and <i>E</i>) and the name of the destination you wish to monitor.</p> <p><i>D</i> signifies the type of destination and whether to include the entire message:</p> <ul style="list-style-type: none"> • T — topic, include full message (as a byte array) into each event • t — topic, do not include full message into each event • Q — queue, include full message (as a byte array) into each event • q — queue, do not include full message into each event <p><i>E</i> signifies the type of event:</p> <ul style="list-style-type: none"> • r for receive • s for send • a for acknowledge • p for premature exit of message • * for all event types <p>For example, <code>\$sys.monitor.T.r.corp.News</code> is the topic for monitoring any received messages to the topic named <code>corp.News</code>. The message body of any received messages is included in monitor messages on this topic. The topic <code>\$sys.monitor.q.*.corp.*</code> monitors all message events (send, receive, acknowledge) for all queues matching the name <code>corp.*</code>. The message body is not included in this topic's messages.</p> <p>The messages sent to this type of monitor topic include a description of the event, information about where the message came from (a producer, route, external system, and so on), and optionally the message body, depending upon the value of <i>D</i>.</p> <p>See Monitor Messages for more information about message monitoring.</p>

Description of Topic Message Properties

Each monitor message can have a different set of these properties.

Property	Contents
<code>conn_connid</code>	Connection ID of the connection that generated the event.
<code>conn_ft</code>	Whether the client connection is a connection to a fault-tolerant server.

Property	Contents
<code>conn_hostname</code>	Hostname of the connection that generated the event.
<code>conn_ssl</code>	Whether the connection uses the SSL protocol.
<code>conn_type</code>	Type of connection that generated the event. This property can have the following values: <ul style="list-style-type: none"> • Admin • Topic • Queue • Generic • Route • FT (connection to fault-tolerant server) • Unknown
<code>conn_username</code>	User name of the connection that generated the event.
<code>conn_xa</code>	Whether the client connection is an XA connection.
<code>event_action</code>	The action that caused the event. This property can have the values listed in Event Action Property Values .
<code>event_class</code>	The type of monitoring event (that is, the last part of the topic name without the <code>\$sys.monitor</code>). For message monitoring, the value of this property is always set to message.
<code>event_description</code>	A text description of the event that has occurred.
<code>event_reason</code>	The reason the event occurred (usually an error). The values this property can have are described in Event Reason Property Values .
<code>event_route</code>	For routing, the route that the event occurred on.
<code>message_bytes</code>	When the full message is to be included for message monitoring, this field contains the message as a byte array. You can use the <code>createFromBytes</code> method (in the various client APIs) to recover the message.
<code>mode</code>	Message delivery mode. This values of this property can be the following: <ul style="list-style-type: none"> • <code>persistent</code> • <code>non_persistent</code> • <code>reliable</code>
<code>msg_correlation_id</code>	JMS correlation ID.

Property	Contents
msg_id	Message ID.
msg_seq	Message sequence number.
msg_size	Message size, in bytes.
msg_timestamp	Message timestamp.
msg_expiration	Message expiration.
replyTo	Message JMSReplyTo.
rv_reply	Message RV reply subject.
source_id	ID of the source object.
source_name	<p>Name of the source object involved with the event. This property can have the following values:</p> <ul style="list-style-type: none"> • XID (global transaction ID) • message_id • connections (number of connections) • unknown (unknown name) • Any server property name • the name of the user, or anonymous

Property	Contents
source_object	<p>Source object that was involved with the event. This property can have the following values:</p> <ul style="list-style-type: none"> • producer • consumer • topic • queue • permissions • durable • server • transaction • user • group • connection • message • jndiname • factory • file • limits (a limit, such as a memory limit) • route • transport
source_value	Value of source object.
stat_msgs	Message count statistic for producer or consumer.
stat_size	Message size statistic for producer or consumer.
target_admin	Whether the target object is the admin connection.
target_created	Time that the consumer was created (in milliseconds since the epoch).
target_dest_name	Name of the target destination
target_dest_type	Type of the target destination.
target_durable	Name of durable subscriber when target is durable subscriber.
target_group	Group name that was target of the event
target_hostname	Hostname of the target object.
target_id	ID of the target object.

Property	Contents
target_name	<p>Name of the object that was the target of the event. This property can have the following values:</p> <ul style="list-style-type: none"> • XID (global transaction ID) • message_id • connections (number of connections) • unknown (unknown name) • Any server property name • the name of the user, or anonymous
target_nolocal	NoLocal flag when target is durable subscriber.
target_object	<p>The general object that was the target of the event. This property can have the following values:</p> <ul style="list-style-type: none"> • producer • consumer • topic • queue • durable • server • transaction • user • group • connection • message • jndiname • factory • file • limits (a limit, such as a memory limit) • route • transport
target_selector	Selector when the target is a consumer.
target_subscription	Subscription of the target object when target is durable subscriber.
target_url	URL of the target object.
target_username	Username of the target object.
target_value	Value of the object that was the target of the event, such as the name of a topic, queue, and so on.

Event Action Property Values

Event Action Value	Description
accept	connection accepted
acknowledge	message is acknowledged
add	user added to a group
admin_commit	administrator manually committed an XA transaction
admin_rollback	administrator manually rolled back an XA transaction
commit	transaction committed
connect	connection attempted
create	something created
delete	something deleted
disconnect	connection disconnected
flow_engaged	stored messages rise above a destination's limit, engaging the flow control feature
flow_disengaged	stored messages fall below a destination's limit, disengaging the flow control feature
interest	registered interest for a route
modify	something changed
grant	permission granted
premature_exit	message prematurely exited
purge	topic, queue, or durable subscriber purged
receive	message posted into destination
remove	user removed from a group
resume	administrator resumed a route
revoke	permission revoked
rollback	transaction rolled back
rotate_log	log file rotated
send	message sent by server to another party

Event Action Value	Description
subscribe	subscription request
suspend	administrator suspended a route
txcommit	administrator manually committed a local transaction
txrollback	administrator manually rolled back a local transaction
xaccommit	an application committed an XA transaction (2-phase)
xaccommit_1phase	an application committed an XA transaction (1-phase)
xastart	an application started a new XA transaction
xastart_join	an application has joined (that is, added) a resource to an existing transaction
xastart_resume	an application resumed a suspended XA transaction
xaend_fail	an application ended an XA transaction, indicating failure
xaend_success	an application ended an XA transaction, indicating success
xaend_suspend	an application suspended an XA transaction
xaprepare	an application prepared an XA transaction
xarecover	an application called recover (to get a list of XA transactions)
xarollback	an application rolled back an XA transaction

Event Reason Property Values

Event Action Value	Description
accept	connection accepted
acknowledge	message is acknowledged
add	user added to a group
admin_commit	administrator manually committed an XA transaction
admin_rollback	administrator manually rolled back an XA transaction
commit	transaction committed
connect	connection attempted
create	something created

Event Action Value	Description
delete	something deleted
disconnect	connection disconnected
flow_engaged	stored messages rise above a destination's limit, engaging the flow control feature
flow_disengaged	stored messages fall below a destination's limit, disengaging the flow control feature
interest	registered interest for a route
modify	something changed
grant	permission granted
premature_exit	message prematurely exited
purge	topic, queue, or durable subscriber purged
receive	message posted into destination
remove	user removed from a group
resume	administrator resumed a route
revoke	permission revoked
rollback	transaction rolled back
rotate_log	log file rotated
send	message sent by server to another party
subscribe	subscription request
suspend	administrator suspended a route
txcommit	administrator manually committed a local transaction
txrollback	administrator manually rolled back a local transaction
xaccommit	an application committed an XA transaction (2-phase)
xaccommit_1phase	an application committed an XA transaction (1-phase)
xastart	an application started a new XA transaction
xastart_join	an application has joined (that is, added) a resource to an existing transaction

Event Action Value	Description
xastart_resume	an application resumed a suspended XA transaction
xaend_fail	an application ended an XA transaction, indicating failure
xaend_success	an application ended an XA transaction, indicating success
xaend_suspend	an application suspended an XA transaction
xaprepare	an application prepared an XA transaction
xarecover	an application called recover (to get a list of XA transactions)
xarollback	an application rolled back an XA transaction

Error and Status Messages

This section lists all possible error messages that the server can output, alphabetized by category.

Key to this section

Category	
The category indicates the general class of error. This section is alphabetized by category.	
Description	The description explains the error category in more detail.
Resolution	The resolution indicates possible recovery actions that administrators should consider.
Errors	These strings represent all instances of the error, as they appear in EMS server code. Some categories have many error instances; others have only one. These strings can include formatting characters.

Error and Status Codes

Admin command failed	
Description	An admin tool or program using the admin API attempted an operation that failed for the given reason.
Resolution	The admin tool or admin API provides the failure reason. The user of the tool or API should examine the error and correct the syntax, parameter or configuration that is causing the failure.
Errors	<p>Attempt by user %s to %s failed due to lack of permissions</p> <p>%s: create %s failed: conflicting zone: existing consumer has a different zone</p> <p>%s: create %s failed: detected duplicate durable subscription [%s] for topic [%s].</p> <p>%s: create %s failed: illegal to use wildcard %s [%s].</p> <p>%s: create %s failed: invalid %s [%s].</p> <p>%s: create %s failed: invalid session id=%d.</p> <p>%s: create %s failed: invalid syntax of %s [%s].</p> <p>%s: create %s failed: invalid temporary %s [%s].</p> <p>%s: create %s failed: not allowed to create dynamic %s [%s].</p> <p>Invalid consumer in recover one msg request.</p> <p>Invalid sequence number in recover one msg request.</p>

Authentication error	
Description	The EMS server failed to authenticate the user or password.

Authentication error	
Resolution	Ensure the user is defined to EMS by one of the methods allowed by the user_auth parameter in the main configuration file. The user is either specified by the application or in the SSL certificate. If the user is defined, reset the password and try again.
Errors	<p>Unable to initialize connection, SSL username error.</p> <p>LDAP authentication failed for user '%s', status = %d - %s</p> <p>LDAP authentication failed for user '%s', LDAP server not found.</p> <p>LDAP authentication failed for user '%s', no password provided</p>

Bad or missing value for command line parameter	
Description	An invalid value was supplied for a command line parameter.
Resolution	Change the value of the named parameter to an acceptable value; for information about tibemsd command line parameters, see EMS documentation.
Errors	<p>'%s' requires an integer argument.</p> <p>'%s' requires a positive integer argument.</p> <p>'%s' requires a string argument.</p> <p>Pathmap is only supported when using a JSON configuration file.</p> <p>Cannot open pathmap file '%s': file not found or permission denied.</p> <p>Invalid pathmap entry '%s'.</p>

Basic initialization failed	
Description	tibemsd was unable to start.
Resolution	Correct the configuration or startup parameters and restart.

Basic initialization failed	
Errors	<p>Unable to add admin user into admin group: error=(%d) %s</p> <p>Fault tolerant activation has to be greater than 2x heartbeat</p> <p>Server heartbeat client should be non-zero and no more than a third of the client timeout server connection</p> <p>Server heartbeat server should be non-zero and no more than a third of the server timeout server connection</p> <p>Client heartbeat server should be non-zero and no more than a third of the server timeout client connection</p> <p>Fault Tolerant configuration error, can't create loop.</p> <p>Fault tolerant connection failed, fault tolerant mode not supported on '%s'.</p> <p>Fault tolerant heartbeat has to be greater than 0</p> <p>Initialization failed due to errors in configuration.</p> <p>Initialization failed due to errors in SSL.</p> <p>Initialization failed due to errors with transports.</p> <p>Initialization failed. Exiting.</p> <p>Initialization has failed. Exiting.</p> <p>Initialization of thread pool failed (%s). Exiting.</p> <p>Startup aborted.</p> <p>Server failed to read configuration.</p> <p>Initialization failed: storage for '%s' not found.</p> <p>Failure initializing storage thread: %s.</p> <p>Ignoring condition %s in startup_abort_list: not supported on this platform.</p> <p>Ignoring condition ALL in startup_abort_list: not supported on this platform. Using condition SSL instead.</p> <p>Initialization failed due to errors with multicast.</p> <p>Configuration error: dbstore_driver_name for store [%s] cannot be empty</p> <p>Configuration error: dbstore_driver_url for store [%s] cannot be empty</p> <p>Configuration error: dbstore_driver_dialect for store [%s] cannot be empty</p> <p>Configuration error: dbstore_driver_username for store [%s] must be specified</p> <p>Configuration error: dbstore_driver_password for store [%s] must be specified</p> <p>Error Loading JVM: %s</p> <p>Unknown Error Loading JVM</p> <p>Trying JVM location: %s</p> <p>Error Loading JVM: %s</p> <p>Unknown Error Loading JVM</p> <p>Unable to create default store '%s': %d - %s</p> <p>\$sys.meta store's type must be 'file' or 'dbstore'.</p>

Basic initialization failed	
	<p>Configuration error: file=%s, line=%d: The parameter '%s' is not supported on this platform</p> <p>Unable to bind network IO thread: %d to Processor Id: %d. Exiting!</p> <p>Unable to bind storage thread for store '%s' to Processor Id: %d. Exiting!</p> <p>Unable to start Network IO Thread(s). Error: %d - %s</p>

Commit failed due to prior failure or after fault-tolerant switch	
Description	A warning message indicating that the commit of a client application's transaction failed either because there were earlier errors when processing this transaction or because the transaction was started on the active server prior to a fault-tolerant failover.
Resolution	The client application should retry the transaction.
Errors	Commit failed due to prior failure or after fault-tolerant switch.

Compaction failed	
Description	Compaction of the store file failed.
Resolution	The most likely cause of this error is running out of memory. Shut down tibemsd and see remedies for Out of memory.
Errors	<p>Compaction of store '%s' failed: %d (%s). Please shutdown and restart tibemsd.</p> <p>Compaction of store '%s' failed: %d (%s).</p> <p>Initialization of file_destination_defrag feature failed for queue '%s' (store '%s') due to an out of memory condition. Feature is disabled.</p> <p>file_destination_defrag of queue '%s' (store '%s') failed: %d (%s).</p>

Configured durable differs from stored one	
Description	The durables configuration file specifies a durable with a given name and client identifier with attributes that are different from the identically named durable found in the meta.db file.
Resolution	Correct the durables configuration file to match the durable defined in the meta.db file or administratively delete the durable and re-define it.
Errors	Configured durable '%s' differs from durable in storage, storage version used.

Create of global routed topic failed: not allowed to create dynamic topic	
Description	A server received an interest notification from another server that does not match the allowed topics in its configuration.

Create of global routed topic failed: not allowed to create dynamic topic	
Resolution	This only is printed when the trace includes ROUTE_DEBUG. If the server's topic definitions are as expected, this statement can be ignored or remove the ROUTE_DEBUG trace specification to prevent printing.
Errors	Create of global routed topic failed: not allowed to create dynamic topic [%s].

Create of routed queue failed: not allowed to create dynamic queue	
Description	A warning indicating that a tibemsd with a route to this daemon has a queue configured to be global but this daemon does not permit the creation of that queue dynamically.
Resolution	Add the specified queue or a pattern that includes it to this daemon if you want the queue to be accessible from this daemon, otherwise the warning can be ignored.
Errors	Create of routed queue failed: not allowed to create dynamic queue [%s].

Database record damaged	
Description	An error occurred reading one of the tibemsd store files.
Resolution	Send details of the error and the situation in which it occurred to TIBCO Support.
Errors	Server failed to recover state.

Database Stores Setup Errors	
Description	In a database stores setup, errors occurring at runtime
Resolution	Check your database server vendor and database administrator for failures occurring during writes, deletes, reads of different records, for failures occurring during database store open check with the database administrator for permissions and the existence of the database. For failures occurring during a FT setup where all the stores are database stores, please check with the database server vendor or database administrator. In the case where both are active, we recommend shutting down both the servers and investigating the problem.

Database Stores Setup Errors	
Errors	<p>Unable to open store [%s]: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to store message record in store [%s]: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to write ack record in store [%s]: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to write txn record in store [%s]: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to update txn record in store [%s]: [ESTATUS = %d, ERRSTR = %s]</p> <p>No memory to create no hold list for valid msgs record</p> <p>No memory to create hold list for valid msgs record</p> <p>No memory to create held list for valid msgs record</p> <p>Failed to write valid msg record in store [%s]: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to update msg record with record id [% PRINTF_LLFMT d] in store [%s]: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to delete %s record id = % PRINTF_LLFMT d : [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to read message with store id = % PRINTF_LLFMT d: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to initialize dbstore [%s]: [ERRSTR = %s]</p> <p>Failed to open store [%s], error = %s</p> <p>Unable to restore %s records from store [%s]: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to delete meta record: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to beginTransaction: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to read message with store id = % PRINTF_LLFMT d: [ESTATUS = %d, ERRSTR = %s]</p> <p>Store [%s] locked by server %s</p> <p>Store [%s] cannot be locked by server %s</p> <p>Failed to store txn record: [txn id = % PRINTF_LLFMT d, ESTATUS = %d]</p> <p>Failed to update txn record: [txn record id = % PRINTF_LLFMT d, ESTATUS = %d]</p> <p>Exception while processing msg from database store [%s], error = %d</p> <p>Failed to write meta record: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to update meta record: [ESTATUS = %d, ERRSTR = %s]</p> <p>Failed to write connection record: error = %d</p> <p>Failed to write session record: error = %d</p> <p>Failed to write consumer record: error = %d</p> <p>Failed to write producer record: error = %d</p> <p>Failed to write zone record: error = %d</p> <p>Failed to update connection record: error = %d</p> <p>Failed to update consumer record: error = %d</p> <p>Failed to write purge record: [ESTATUS = %d, ERRSTR = %s]</p> <p>Commit Transaction Failed [ESTATUS = %d, ERRSTR = %s]</p>

Database Stores Setup Errors

No Memory to create lock manager: Store [%s] cannot be locked by server %s
 Could not find system record for store [%s]

Durable consumer was found in the store file for a route that does not exist

Description	On server startup a durable consumer was found in the store file for a route that is not listed in the routes.conf file. This happens if the routes.conf file is manually edited.
Resolution	Make routing changes via administration tools.
Errors	Discarding durable '%s' for route '%s' because the route does not exist.

Dynamic Module Loading Errors

Description	An error occurred when loading or using a shared library module.
Resolution	Module loading is affected by the presence of shared libraries in the module path. Use the +load tracing flag to get more information about how the server is loading modules. See the section on Starting the EMS Server for more details.
Errors	Problem loading %s: %s Unknown problem loading %s. Loaded %s Problem binding %s: %s Unknown problem binding %s. Unable to locate %s Fatal error: Returned from exec(), errno = %d OpenSSL library version mismatch tibftl_transports not supported

Duplicate message detected

Description	Warning generated when tibemspd receives a message with a message id that matches another message's message id.
Resolution	Only seen when message id tracking is enabled.
Errors	Detected duplicate %s message, messageID='%s'

Destination backlog growth detected

Description	Warning generated when a destination appears to be growing an unwieldy backlog of messages.
-------------	---

Destination backlog growth detected	
Resolution	Consume or purge a large number of messages from that destination.
Errors	<p>Destination growing very large: name=%s type=%s msg_count=%lld dest_size=%lld (bytes) num_consumers=%d inbound_rate=%d (bytes/s) outbound_rate=%d (bytes/s)</p> <p>Destination growing very large: name=%s type=%s msg_count=%lld dest_size=%lld (bytes) num_consumers=%d inbound_rate=statistics_disabled outbound_rate=statistics_disabled</p> <p>The server will attempt to trace warnings about destinations that are growing unbounded above %lld bytes or %lld messages.</p> <p>The server will attempt to trace warnings about destinations that are growing unbounded above %lld %s.</p> <p>Set server properties 'large_destination_memory' and 'large_destination_count' respectively to alter these thresholds.</p> <p>Set server property '%s' to alter this threshold.</p>
Error in configuration file	
Description	The server encountered an invalid configuration statement in the specified configuration file on the specified line.
Resolution	Examine the appropriate configuration file and correct the syntax error.

Error in configuration file	
Errors	<p>Configuration warning: file=%s, line=%d: route '%s' does not have a user configured for authorization.</p> <p>SSL Configuration error: file=%s, line=%d: invalid certificate file name, unknown extension or invalid encoding specification</p> <p>Configuration error: file=%s, line=%d: illegal to specify %s for routed queue</p> <p>Configuration error: file=%s, line=%d: bad destination specification: %s</p> <p>Configuration warning: file=%s, line=%d: illegal to specify prefetch=none for global or routed queue. Prefetch reset to default.</p> <p>Configuration warning: file=%s, line=%d: illegal to specify prefetch=none for topic. Prefetch reset to default.</p> <p>Configuration error: file=%s, line=%d: ignored alias '%s' for %s '%s' because such alias already exists</p> <p>Configuration error: The specified file '%s' is empty or does not exist</p> <p>Configuration error: file=%s, line=%d: both tibrv_export and tibrvcm_export are specified, ignoring tibrv_export</p> <p>Configuration error: file=%s, line=%d: ignoring transport '%s' in %s list, transport not found</p> <p>Configuration error: file=%s, line=%d: multiple bridge entries for the same destination '%s' are not allowed.</p> <p>Configuration error: file=%s, line=%d: Ignoring durable, name cannot start with \$sys.route, use route property instead.</p> <p>Configuration error: file=%s, line=%d: Rendezvous transport not specified for Rendezvous CM transport '%s'</p> <p>Configuration error: file=%s, line=%d: ignoring invalid max connections in the line, reset to %s</p> <p>Configuration error: file=%s, line=%d: ignoring invalid max_client_msg_size in the line, reset to unlimited</p> <p>Configuration error: file=%s, line=%d: value of %s out of range, reset to default</p> <p>Configuration error: max_msg_field_print_size >= max_msg_print_size, resetting both to default</p> <p>Configuration error: file=%s, line=%d: unable to create %s '%s': invalid destination name, invalid parameters or out of memory</p> <p>Configuration error: file=%s, line=%d: value of db_pool_size too big or less than allowed minimum, reset to default value of %d bytes</p> <p>Configuration error: file=%s, line=%d: Ignoring durable, route does not allow clientid, selector or nlocal.</p> <p>Configuration error: file=%s, line=%d: Route '%s' does not exist for configured durable.</p> <p>Configuration error: file=%s, line=%d: unable to process selector in route parameters, error=%s</p> <p>Configuration error: file=%s, line=%d: both tibrv_import and tibrvcm_import are specified, ignoring tibrv_import</p>

Error in configuration file

Configuration error: file=%s, line=%d: ignored route '%s' because route represents route to this server.

Configuration error: file=%s, line=%d: ignoring invalid topic selector specifications in route parameters

Configuration error: file=%s, line=%d: value of max_msg_memory less than allowed, reset to %dMB

Configuration error: file=%s, line=%d: ignored alias '%s' for factory because such alias already exists

Configuration error: file=%s, line=%d: invalid certificate file name, unknown extension or invalid encoding specification

Configuration error: file=%s, line=%d: ignored route '%s' because route has invalid zone information.

Configuration error: file=%s, line=%d: ignored route '%s' because route with such name or URL already exists.

Configuration error: file=%s, line=%d: value of msg_pool_size invalid or too big or less than allowed minimum of %d, reset to default value of %d

SSL Configuration error: file=%s, line=%d: invalid private key file name, unknown extension or invalid encoding specification

Configuration conflict: file=%s, line=%d: value of msg_pool_block_size already set at line=%d. Ignoring msg_pool_size.

Configuration error: file=%s, line=%d: bridge has no targets, unable to process

Configuration error: file=%s, line=%d: Illegal to specify routed queue as a bridge source

Configuration error: file=%s, line=%d: \$TMP\$.> cannot be bridge source or target destination

Configuration error: file=%s, line=%d: A temporary destination cannot be bridge source or target destination

Configuration error: file=%s, line=%d: client_trace error: %s

Configuration error: file=%s, line=%d: %s

Configuration error: %shealth_check_listen is malformed - %s

Configuration error: file=%s, line=%d: duplicate specification of transport type

Configuration error: file=%s, line=%d: duplicate value

Configuration error: file=%s, line=%d: Ignoring durable, duplicate of earlier entry.

Configuration error: file=%s, line=%d: Ignoring durable, name is invalid.

Configuration error: file=%s, line=%d: Ignoring durable, name is missing or invalid.

Configuration error: file=%s, line=%d: Ignoring durable, topic is invalid.

Configuration error: file=%s, line=%d: Ignoring durable, topic is missing or invalid.

Configuration error: file=%s, line=%d: Ignoring durable, durable subscriptions not supported on temporary destination wildcard \$TMP\$.>.

Configuration error: file=%s, line=%d: error in the bridge description, unable to proceed.

Configuration error: file=%s, line=%d: error in permissions

Error in configuration file

Configuration error: file=%s, line=%d: error in the transport description, unable to proceed.

Configuration error: file=%s, line=%d: errors in line, some options may have been ignored

Error: unable to add bridge specified in file=%s, line=%d. Error=%s

Configuration error: file=%s, line=%d: Unable to create destination defined by the bridge source

Unable to create Rendezvous Certified transport '%s' because it references undefined Rendezvous transport '%s'

Configuration error: file=%s, line=%d: failed to create ACL entry, reason=%s

Unable to export message to SmartSockets. error=%s.

Use fsync error: file=%s, line=%d: invalid property value

Use fsync (min disk) error: file=%s, line=%d: invalid property value

exit_on_nonretryable_disk_error: file=%s, line=%d: invalid boolean property value

consumed_msg_hold_time: file=%s, line=%d: invalid property value

active_route_connect_time: file=%s, line=%d: invalid property value

Fault tolerant reread error: file=%s, line=%d: invalid property value

Fault standby lock check error: file=%s, line=%d: invalid property value

Configuration error: file=%s, line=%d: ignored unknown permission '%s'

Configuration error: file=%s, line=%d: ignoring duplicate %s '%s' specified earlier

Configuration error: file=%s, line=%d: ignoring duplicate transport name '%s' in %s list

Configuration error: file=%s, line=%d: ignoring duplicate user

Configuration error: file=%s, line=%d: ignoring errors in permission line

Configuration error: file=%s, line=%d: ignoring invalid connect attempt count

Configuration error: file=%s, line=%d: ignoring invalid connect attempt delay

Configuration error: file=%s, line=%d: ignoring invalid connect attempt timeout

Configuration error: file=%s, line=%d: ignoring invalid disk statistic period

Configuration error: file=%s, line=%d: ignoring invalid entry syntax

Configuration error: file=%s, line=%d: ignoring invalid factory load balancing metric

Configuration error: file=%s, line=%d: ignoring invalid ft activation in the line

Configuration error: file=%s, line=%d: ignoring invalid ft heartbeat in the line

Configuration error: file=%s, line=%d: ignoring invalid ft reconnect timeout in the line

Configuration error: file=%s, line=%d: ignoring invalid line

Configuration error: file=%s, line=%d: ignoring invalid line in factory parameters

Configuration error: file=%s, line=%d: ignoring invalid line in route parameters

Configuration error: file=%s, line=%d: ignoring invalid line: invalid syntax in the line

Configuration error: file=%s, line=%d: ignoring invalid reconnect attempt count

Error in configuration file

Configuration error: file=%s, line=%d: ignoring invalid reconnect attempt delay

Configuration error: file=%s, line=%d: ignoring invalid reconnect attempt timeout

Configuration error: file=%s, line=%d: ignoring invalid value of %s

Configuration error: file=%s, line=%d: ignoring invalid value '%s' for property '%s'

Configuration error: file=%s, line=%d: ignoring unknown property '%s'

Configuration error: file=%s, line=%d: ignoring unrecognized property '%s'

Configuration error: file=%s, line=%d: ignoring user out of group context

Configuration error: file=%s, line=%d: illegal to use predefined name %s

Configuration error: file=%s, line=%d: Invalid clientid value

Configuration error: file=%s, line=%d: invalid value of db_pool_size, reset to default of %d bytes

Configuration error: file=%s, line=%d: invalid line syntax or line out of order

Configuration error: file=%s, line=%d: invalid value of max memory, reset to unlimited

Configuration error: file=%s, line=%d: invalid value of max_msg_memory, reset to unlimited

Configuration error: file=%s, line=%d: invalid property value

Configuration error: file=%s, line=%d: invalid property value, reset to default.

Configuration error: file=%s, line=%d: invalid password

Configuration error: file=%s, line=%d: invalid value of reserve_memory, reset to zero

Configuration error: file=%s, line=%d: invalid value of route_recover_interval, reset to default %d

Configuration error: file=%s, line=%d: invalid value of route_recover_count, line ignored

Configuration error: file=%s, line=%d: Invalid selector value

Configuration error: file=%s, line=%d: invalid syntax of %s, unable to continue.

Configuration error: file=%s, line=%d: invalid transport parameter '%s'

Configuration error: file=%s, line=%d: invalid transport type '%s'

Configuration error: file=%s, line=%d: invalid trace_client_host value

Configuration error: file=%s, line=%d: invalid trace_millisecond value

Configuration error: file=%s, line=%d: invalid value of %s, reset to unlimited

Configuration error: file=%s, line=%d: invalid value '%s'

Configuration error: file=%s, line=%d: invalid value '%s' for parameter '%s'

Configuration error: file=%s, line=%d: invalid value of '%s'

Configuration error: file=%s, line=%d: invalid value of %s

Configuration error: file=%s, line=%d: invalid value of %s, reset to 256MB

Configuration error: file=%s, line=%d: invalid value of %s, reset to default

Configuration error: file=%s, line=%d: line too long, ignoring it

Error in configuration file

Configuration error: file=%s, line=%d: maximum number of listen interfaces reached.

Configuration error: file=%s, line=%d: multiple principals specified, line ignored

Configuration error: file=%s, line=%d: multiple targets specified, line ignored

Configuration error: file=%s, line=%d: out of memory, unable to create Rendezvous transport

Configuration error: file=%s, line=%d: no permissions found in acl entry

Configuration error: file=%s, line=%d: no target found in acl entry

Configuration error: file=%s, line=%d: %s '%s' not found

Configuration error: No topic exists for configured durable '%s%s%s'.

failed to create durable '%s', exception: %s.

Configuration error: file=%s, line=%d: no valid user or group found in acl entry

Configuration conflict: file=%s, line=%d: Overriding value of msg_pool_size already set at line=%d.

Configuration warning: file=%s, line=%d: parameter '%s' is deprecated

Configuration error: file=%s, line=%d: value of reserve_memory too small, reset to 16MB

Configuration error: file=%s, line=%d: ignoring invalid line in route parameters: invalid zone type, too long

Configuration error: file=%s, line=%d: ignoring invalid line in route parameters: invalid topic prefetch

Configuration error: file=%s, line=%d: ignoring invalid line in route parameters: zone name exceeding %d bytes

Routing Configuration error: file=%s, line=%d: invalid property value

Configuration warning: file=%s, line=%d: ignoring rvcmlistener, duplicate

Configuration error: file=%s, line=%d: ignoring rvcmlistener, first token is invalid

Configuration error: file=%s, line=%d: ignoring rvcmlistener, invalid destination

Configuration error: file=%s, line=%d: ignoring rvcmlistener, second token is invalid

Configuration error: file=%s, line=%d: ignoring rvcmlistener, third token is invalid

Configuration error: file=%s, line=%d: ignoring rvcmlistener, wildcards are not permitted

SmartSockets configuration directory name is too long. error=%s.

SmartSockets file '%s' not found.

SSL Configuration error: file=%s, line=%d: duplicate value

SSL Configuration error: file=%s, line=%d: invalid value of DH key size.

SSL Configuration error: file=%s, line=%d: invalid property value

Configuration error: file=%s, line=%d: syntax error in the line, ignoring

Configuration error: file=%s, line=%d: syntax errors in line, line ignored

Topic '%s' not valid in configured durable '%s'.

%s%sNo client ID for%s unshared durable '%s'.

Error in configuration file

Configuration error: file=%s, line=%d: Unrecognized attribute

Configuration error: file=%s, line=%d: user '%s' not found, ignoring

Configuration error: file=%s, line=%d: value is invalid or less than minimum %d, reset to 0

Configuration error: file=%s, line=%d: value less than allowed minimum, reset to 0

Configuration error: file=%s, line=%d: value of %s less than allowed minimum of %dKB, reset to unlimited

Configuration error: file=%s, line=%d: Invalid value or value does not fall between %d and %d

Configuration error: Invalid line: file=%s, line=%d

Configuration error: Missing store header: file=%s, line=%d

Configuration error: Mixed mode configuration: file=%s, line=%d

Configuration error: Invalid store parameter: file=%s, line=%d

Configuration error: Store definition failed

Configuration error: Unrecognized store type requested.

Configuration error: Filename for store '%s' cannot be empty.

Error occurred writing store definition into file.

Configuration error: file=%s, line=%d: ignoring channel '%s' on topic '%s', channel does not exist

Configuration error: file=%s, line=%d: ignoring channel '%s' on topic '%s', overlaps with channel '%s' on topic '%s'

Configuration error: file=%s, line=%d: ignoring channel '%s', duplicate name

Configuration error: file=%s, line=%d: ignoring channel '%s', address of '%s:%d' already defined

Configuration error: file=%s, line=%d: channel '%s', %s

Configuration error: file=%s, line=%d: channel '%s', no address specified.

Configuration error: file=%s, line=%d: channel '%s', invalid address syntax: port not specified.

Configuration error: file=%s, line=%d: channel '%s', invalid address: group must be in the range 224.0.0.0 to 239.255.255.255

Configuration error: file=%s, line=%d: channel '%s', interface must address a valid multicast-capable network interface.

Configuration error: file=%s, line=%d: channel '%s', invalid address: port must be in the range 1 to 65535

Configuration error: file=%s, line=%d: channel '%s', ttl must be in the range 1 to 255

Configuration error: file=%s, line=%d: channel '%s', priority must be in the range -5 to 5

Configuration error: file=%s, line=%d: channel '%s', maxrate must be less than 512MB

Configuration error: file=%s, line=%d: channel '%s', maxtime must be greater than 0

Configuration error: file=%s, line=%d: cannot store messages in: %s

Error in configuration file	
	<p>Configuration error: file=%s, line=%d: cannot find store: %s</p> <p>Required store param 'type' not specified for store '%s'</p> <p>Configuration error: file=%s, line=%d: parameter does not match another parameter that defined store '%s' as 'file' type%s.</p> <p>Configuration error: file=%s, line=%d: parameter does not match another parameter that defined store '%s' as 'dbstore' type%s.</p> <p>Configuration error: file=%s, line=%d: parameter does not match another parameter that defined store '%s' as 'mstore' type%s.</p> <p>Store '%s' already defined</p> <p>Configuration error: Store with similar dbstore_driver_url exists, file=%s, line=%d</p> <p>Configuration error: duplicate file name %s for stores %s and %s</p> <p>Configuration warning: file=%s, line=%d: the discardAmount is too small for the selected RV Queue Limit Policy. It is recommended to have at least 10%% of the maxEvents</p> <p>Configuration error: file=%s, line=%d: the discardAmount is too big compared to the maxEvents value. Defaulting to TIBRVQUEUE_DISCARD_NONE policy</p> <p>Configuration error: file=%s, line=%d: maxEvents and discardAmount values must be strictly positive for an RV Queue Limit Policy other than TIBRVQUEUE_DISCARD_NONE. Defaulting to TIBRVQUEUE_DISCARD_NONE policy</p> <p>Configuration error: file=%s, line=%d: RV Queue Limit Policy '%s' unknown or not supported. Defaulting to TIBRVQUEUE_DISCARD_NONE policy</p> <p>Configuration error: file=%s, line=%d: Error parsing the RV Queue Limit Policy value '%s'. Defaulting to TIBRVQUEUE_DISCARD_NONE policy</p> <p>Configuration warning: file=%s, line=%d: The bridge's source destination '%s' is dynamic but has no parent. The bridge should either be removed or a static parent destination added</p> <p>Changing the type of the existing store '%s' is not permitted</p> <p>Only stores of type 'file' are permitted. Unable to create store '%s' of type '%s'</p>

Error writing commit request, errors already occurred in this transaction	
Description	A client application's attempt to commit a transaction failed because the server encountered an error during an operation associated with the transaction.
Resolution	Examine previous error statements to determine the cause of the operation failure and correct that before attempting the transaction again.
Errors	Error writing commit request, errors already occurred in this transaction.

Error writing configuration file	
Description	tibemspd was unable to update one of its configuration files following a configuration change.
Resolution	Check that the user that started the tibemspd has permission to change the configuration files and that there is sufficient disk space on the device.
Errors	<p>Error occurred saving acl information</p> <p>Error occurred saving bridges information</p> <p>Error occurred saving durables information</p> <p>Error occurred saving factories information</p> <p>Error occurred saving file '%s'</p> <p>Error occurred saving group information</p> <p>Error occurred saving %s information</p> <p>Error occurred saving main configuration file '%s'</p> <p>Error occurred saving routes information</p> <p>Error occurred saving tibrvcm information</p> <p>Error occurred while updating main configuration file '%s'. Configuration has not been saved.</p> <p>Error occurred writing bridges into file.</p> <p>Error occurred writing destination '%s' into file</p> <p>Error occurred writing factory into file.</p> <p>Error occurred writing group '%s' into file</p> <p>Error occurred writing into the file '%s'.</p> <p>Error occurred writing route into file.</p> <p>I/O error occurred saving bridge information</p> <p>I/O error occurred saving group information</p> <p>I/O error occurred saving route information</p> <p>I/O error occurred writing into file '%s'</p> <p>Configuration error: file=%s, line=%d: Ignoring property '%s' which is not supported in EMS Community Edition.</p>

Error writing to store file	
Description	tibemspd was unable to write data to one of its store files.
Resolution	Ensure that the directory containing the store files is mounted and accessible to the tibemspd, and that there is free space available on the device

Error writing to store file	
Errors	<p>A %s I/O error occurred on file descriptor %d: %s - %d</p> <p>A %s I/O error occurred on file %s: %s - %d</p> <p>Failed writing block data to '%s': %s</p> <p>Failed writing message to '%s': I/O error or out of disk space.</p> <p>Failed writing purge state for queue '%s': I/O error or out of disk space.</p> <p>Failed writing purge state for topic consumer: I/O error or out of disk space.</p> <p>Exception trying to create confirm record, %s.</p> <p>Exception trying to create message from store: %s</p> <p>Exception trying to create transaction record.</p> <p>Exception trying to create valid messages record, %s.</p> <p>Exception trying to export message to RV.</p> <p>Failed writing message to '%s': %s.</p> <p>Exception writing transaction commit record: %s.</p> <p>Exception writing transaction rollback record: %s.</p> <p>Exception writing transaction prepare record: %s.</p> <p>Failure deleting old version of transaction record: %s.</p> <p>Failed deleting '%s' record from %s: %s</p>
Exceeded system resources.	
Description	The system resources are inadequate for timely processing of server activities.
Resolution	Increase the specified resource or reduce the workload on this server.

Exceeded system resources.	
Errors	<p>WARNING: Slow clock tick %d seconds, delayed messaging and timeouts may occur. System appears overloaded.</p> <p>WARNING: Connection timeouts delayed around %d seconds.</p> <p>Missed transfer of global lock before a slow operation was reported. Last offender grabbed lock around %d milliseconds ago.</p> <p>WARNING: Slow processing protocol message of type %s, lasted around %d milliseconds.</p> <p>WARNING: Slow completing processing protocol message of type %s, lasted around %d milliseconds.</p> <p>WARNING: Slow removing messages, lasted around %d milliseconds. This may have delayed connection timeouts.</p> <p>WARNING: Slow swapping out messages, lasted around %d milliseconds. This may have delayed connection timeouts.</p> <p>WARNING: Slow processing message (%s%s), lasted around %d milliseconds.</p> <p>WARNING: Slow processing message (%s ac=%d), lasted around %d milliseconds.</p> <p>WARNING: Slow processing event callback (%s), lasted around %d milliseconds.</p> <p>WARNING: Slow write to store (%s) lasted around %d milliseconds.</p> <p>WARNING: A single %s store (%s) lasted around %d seconds.</p>

Failed to open TCP port	
Description	tibemspd was unable to open the tcp port.
Resolution	Shutdown process that is using the port or change the value of the 'listen' parameter in the server's tibemspd.conf file to a port that is not in use.
Errors	Binding connection to TCP port %d failed:%d (%s).

File access error	
Description	tibemspd was unable to properly access the specified file.
Resolution	Check that the path name is correct and the directory exists, the user that started tibemspd has permission to read the specified directory and path, the file exists if it isn't one that the tibemspd can create, the file is not being used by another tibemspd or some other process.

File access error	
Errors	<p>Configuration file '%s' not found.</p> <p>Failed to create file '%s'</p> <p>failed to open file '%s'.</p> <p>failed to open log file '%s'.</p> <p>Failed to read message from store.</p> <p>Failed to rename file %s into %s: %s</p> <p>Unable to open metadata file '%s', error '%s'.</p> <p>Unable to open metadata file '%s', file may be locked.</p> <p>Unable to open store file '%s', error '%s'.</p> <p>Unable to open store file '%s', file may be locked.</p> <p>Unable to preallocate storage file '%s'.</p> <p>I/O error occurred reading from the file '%s'.</p> <p>Exiting on non-retryable disk error: %d</p> <p>Exiting on disk error: %d</p> <p>Exception trying to read message from store.</p> <p>Error during file close of '%s' - %d.</p> <p>Unable to open FT State Replication determination file '%s', error '%s'.</p> <p>Unable to open FT State Replication determination file '%s', file may be locked.</p> <p>Error upon accessing FT State Replication determination file '%s', invalid header CRC.</p> <p>Unable to write to FT State Replication determination file '%s', error '%s'.</p> <p>Exiting due to error while accessing the FT State Replication determination file.</p> <p>Symbolic link '%s' is incorrect: %s.</p>

FIPS 140-2 Mode Errors	
Description	An error occurred while starting or running the server in FIPS 140-2 compliant mode.
Resolution	Check the configuration of SSL related parameters to make sure that no incompatible ciphers or operations are requested.
Errors	<p>Cannot specify ldap_tls_cipher_suite in FIPS 140-2 mode.</p> <p>Cannot specify ldap_tls_rand_file in FIPS 140-2 mode.</p> <p>Cannot specify SSL cipher list in FIPS 140-2 mode.</p> <p>Cannot specify random data source file in FIPS 140-2 mode.</p> <p>Cannot specify ssl_dh_size in FIPS 140-2 mode.</p> <p>Cannot specify ssl_server_ciphers in FIPS 140-2 mode.</p> <p>Cannot specify ssl_rand_file in FIPS 140-2 mode.</p>

FTL Gateway.	
Description	An error occurred when loading or using the FTL Gateway.
Resolution	Correct the FTL transport in the EMS configuration and/or the Application in the FTL realm service.

FTL Gateway.	
Errors	<p>Error setting FTL message constant '%s'.</p> <p>Constants (none).</p> <p>Constant (string) %s: \ %s \</p> <p>Constant (long) %s: %PRINTF_LLFMTd</p> <p>Exception Summary: %s</p> <p>Exception: \n%s</p> <p>The FTL application for this gateway was administratively disabled. Please restart this server to re-enable this FTL gateway.</p> <p>FTL Notification Type=%d: %s\n</p> <p>Failed to process FTL password.</p> <p>Connecting to the realm service.</p> <p>Setting a FTL discard policy is highly recommended.</p> <p>Invalid FTL discard policy. Defaulting to \old\.</p> <p>Global FTL Settings</p> <p>Realm service URL: %s</p> <p>Realm server Secondary URL: %s</p> <p>Username: %s</p> <p>Password: %s</p> <p>Log Level: %s</p> <p>Application Name: %s</p> <p>Discard Policy: %s</p> <p>Discard Amount: %d</p> <p>Discard Max Events: %d</p> <p>Freeing FTL Global resources.</p> <p>FTL Global resources freed.</p> <p>FTL Advisory:</p> <p>Unable to start FTL dispatcher thread.</p> <p>Unable to initialize FTL Transport (%s). For more information, enable FTL tracing.</p> <p>FTL Transport '%s' Ignoring unsupported FTL field type (%s).</p> <p>Error importing FTL message. status = %s.</p> <p>FTL Transport '%s': Skipping message (subscriber removed).</p> <p>Error setting FTL message field '%s'</p> <p>Conversion from EMS bytes message to FTL message failed.</p> <p>Conversion from EMS text message to FTL message failed.</p> <p>Conversion from EMS data message to FTL message failed.</p> <p>Conversion from an EMS Object message to a FTL message is not supported.</p>

FTL Gateway.

Conversion from an EMS Stream message to a FTL message is not supported.

Conversion from EMS message type (%d) to a FTL message is not supported.

Unable to set FTL fields from EMS Properties.

Unable to set FTL fields from EMS header values.

Unable to export message (%s).

FTL Transport Settings

Topic Import Delivery Mode: %s.

Queue Import Delivery Mode: %s.

Endpoint: %s

Import Parameters

Match String: %s

Subscriber Name: %s

Export Parameters

Format: %s

FTL Transport '%s' removed subscriber.

FTL Transport '%s' removing subscriber.

FTL Transport '%s': Error removing subscriber.

Error creating subscriber '%s' on endpoint '%s'

Creating FTL Transport '%s'

Created FTL Transport '%s'

Failed to create FTL transport '%s'

FTL transport '%s' is creating a publisher.

FTL Transport '%s' created a publisher.

FTL transport '%s': Error creating publisher.

Destroyed FTL transport '%s'

Transport '%s' cannot subscribe to %s %s; already subscribed.

FTL Transports cannot be imported on a wildcard destination.

A FTL Transport can be used with only one destination.

FTL Transport '%s' has subscribed to %s %s.

FTL Transport '%s' failed to subscribe to %s %s.

FTL Transport '%s' has unsubscribed from %s %s.

FTL transport '%s' cannot be specified as an import by more than one destination.

%s %s FTL Transport '%s' as an import for destination '%s'.

%s %s FTL Transport '%s' as an export for destination '%s'.

Internal error	
Description	The server detected an internal inconsistency.
Resolution	Send the error statement and a description of the environment to TIBCO Support.

Internal error	
Errors	<p>**Error** unable to process message, error = %s</p> <p>Admin user not found during initialization</p> <p>Error bridging transacted data message, '%s'.</p> <p>Error processing xa commit request, %s. connID=% PRINTF_LLFFMT d %s</p> <p>Error processing xa end - transaction marked ROLLBACKONLY, %s. connID=% PRINTF_LLFFMT d sessID=% PRINTF_LLFFMT d %s</p> <p>Error processing xa prepare request, %s. connID=% PRINTF_LLFFMT d %s</p> <p>Error processing xa rollback request, %s. connID=% PRINTF_LLFFMT d %s</p> <p>Error decoding sequence data in xa rollback request. connID=% PRINTF_LLFFMT d %s</p> <p>Error decoding sequence data in route ack response.</p> <p>Unable to create internal session</p> <p>Problem setting flow stall recover message on route queue:%s: %s</p> <p>Failed to handle connection initialization: %s.</p> <p>Problem trying to recover routed consumer for queue %s: setting recover message. Error: %s</p> <p>Failed to send the flow stall recover request: %s.</p> <p>Unable to handle transacted data message, '%s'.</p> <p>Unable to handoff connection init message: %s.</p> <p>Unable to initialize fault tolerant connection, remote server returned '%s'</p> <p>Unable to process producer message, failed to add sender name, error=%s.</p> <p>Unable to process sequence for message.</p> <p>Unable to send recover ack on flow stall: %s</p> <p>Handling of route flow stall recovery request from %s failed: unable to get message property %s: %s</p> <p>Handling of route flow stall recovery request failed: Unable to get message properties: %s</p> <p>Failed to send acknowledge to the stall recover request of server %s, will try later. Error: %s</p> <p>failed to send recover ack on stalled flow: invalid consumer</p> <p>unable to create recovered connection, status: %s</p> <p>Exception creating purge record.</p> <p>Exception creating zone.</p> <p>Exception creating zone: adding zone to state.</p> <p>Exception in startup, exiting.</p> <p>Exception preparing message for client send (%s): %s</p> <p>Exception sending flow recover acknowledge</p> <p>Exception sending routing information to %s - %s</p>

Internal error	
	<p>Exception sending session init response</p> <p>Exception sending queue acknowledge response to %s: %s</p> <p>Exception trying to initialize connection.</p> <p>Exception trying to initialize connection, can't send response: %s</p> <p>Exception trying to initialize route.</p> <p>Exception trying to initialize route '%s' configured durables: %s</p> <p>Exception trying to process message, '%s'.</p> <p>Exception trying to process message from store.</p> <p>Failure queuing incoming message for processing: %s.</p> <p>Failure queuing message for removal from system: %s.</p> <p>Failure queuing message to add to dead queue: %s.</p> <p>Failure discarding topic overflow: %s.</p> <p>Failure processing system request.</p> <p>Failure processing transaction message.</p> <p>Failure bridging incoming message: %s.</p> <p>Failure verifying uniqueness of routed message: %s.</p> <p>Failure scheduling message hold release: %s.</p> <p>Exception adding message write context: %s.</p> <p>%s: Failure processing multicast request: %s</p> <p>%s: Failure sending multicast request response: %s</p> <p>%s: Failure processing multicast status: %s</p> <p>%s: Failure sending multicast status response: %s</p> <p>%s: Failure sending multicast configuration: %s</p> <p>Failure sending multicast message on channel '%s': %s</p> <p>Failure enqueueing multicast message on channel '%s': %s</p> <p>Failure starting multicast engine: %s</p> <p>Failure starting multicast channel '%s': %s</p> <p>Failure posting multicast channel '%s' wake event: %s</p> <p>Failed preparing message for writing: %s</p> <p>Failed discarding local transaction: %s</p> <p>Abandoning transaction record due to IO failure.</p> <p>Error sending acknowledgment to route '%s': %s</p> <p>Error processing acknowledgments from route '%s': %s</p> <p>Failure starting delivery of delayed message seq = % PRINTF_LLFMtd: %s</p> <p>Failure moving failed delivery delayed message seq = % PRINTF_LLFMtd to dead queue: %s</p>

Invalid connection	
Description	Warning indicating that tibemspd was attempting to reestablish delivery of messages across a route to another tibemspd but was unable to find the connection for that route.
Resolution	Either reduce the tibemspd's memory requirement by consuming messages or removing messages from its queues, or increase the amount of memory available to the tibemspd by shutting down other processes on the machine or increasing the machine's memory.
Errors	Recovery flow stall for destination %s failed: invalid route connection

Invalid destination	
Description	An application is attempting to use a destination name that is not valid.
Resolution	Alter application code to use an acceptable destination name.
Errors	<p>%s: create %s failed: Not permitted to use reserved queue [%s].</p> <p>%s: %s failed: illegal to use wildcard %s [%s].</p> <p>%s: %s failed: %s [%s] not configured.</p> <p>At least one bridge is referencing %s [%s] as a target. This destination does not exist and there is no parent that would allow its dynamic creation. The destination has been forcefully created. To avoid this, the bridge(s) referencing this target should be destroyed.</p> <p>Use of '\$' destination prefix is not supported [%s %s].</p>

Invalid listen specification	
Description	The server could not parse the listen parameter in the tibemspd.conf file
Resolution	Correct the listen parameter to match the form [protocol]://[url] as specified in the manual.
Errors	<p>Invalid listen specification: '%s'.</p> <p>Invalid request to create temporary destination.</p>

Invalid session	
Description	tibemspd received a request that referred to a session that doesn't currently exist.
Resolution	Send details of the error and the situation in which it occurred to TIBCO Support.

Invalid session	
Errors	<p>Cannot find session for ack</p> <p>Cannot find session for ack range</p> <p>%s: destroy %s failed: invalid session id=%d.</p> <p>Unable to destroy session, invalid session.</p> <p>Invalid session in commit request.</p> <p>Invalid commit request.</p> <p>Invalid session trying to update(%d) tx record.</p> <p>Invalid session in commit transaction record.</p> <p>Invalid session in recover request.</p> <p>Invalid session in rollback request.</p> <p>Invalid session in xa end request. connID=% PRINTF_LLFMT d</p> <p>Invalid session in xa start request. connID=% PRINTF_LLFMT d</p>

LDAP error - should always display LDAP error	
Description	An attempt to authenticate a client's userid and password using the external LDAP server failed.
Resolution	Examine the error code printed by the messaging server and consult the manual for the external LDAP server.
Errors	<p>Filter '%s' contains an illegal type substitution character, only %%s is allowed</p> <p>Filter '%s' contains too many occurrences of %%s, max allowed is: %d</p> <p>Filter '%s' too long, max length is %d characters</p> <p>Invalid search scope: %s</p> <p>LDAP Configuration error: file=%s, line=%d: invalid property value</p> <p>LDAP is not present</p> <p>LDAP search resulted %d hits.</p> <p>ldap_url_parse failed, returned: %d</p> <p>Lookup of group '%s' produced incorrect or no results</p> <p>Missing LDAP URL</p> <p>Missing %s parameter</p> <p>Zero entries returned from getting attributes for group '%s':</p> <p>Failed adding user '%s' into LDAP user cache</p>

LICENSE WARNING	
Description	The server detected a violation of its license.

LICENSE WARNING	
Resolution	This error only occurs with the evaluation version of the server or in an embedded form. To correct this error either replace your evaluation version with a production version or contact the vendor who supplied the embedded version.
Errors	License violation: %s.

Missing configuration	
Description	An essential attribute has not been configured.
Resolution	Change the tibemsd.conf file so that a value for the attribute is provided.
Errors	Configuration error with metadata database. Configuration error with storage databases.

Missing transaction	
Description	A client application attempted to change the state of a transaction that the tibemsd does not have in its list of current transactions.
Resolution	Check tibemsd trace logs to see if the transaction had been committed or rolled back by an administrator, if not then check the client code to see if it or its transaction manager are calling the transaction operations in the correct order.
Errors	<p>Cannot find transaction referred to transaction record update(%d) request. connID=% PRINTF_LLFMT d %s</p> <p>Cannot find transaction referred to in xa commit request. connID=% PRINTF_LLFMT d %s</p> <p>Cannot find transaction referred to in xa prepare request. connID=% PRINTF_LLFMT d %s</p> <p>Cannot find transaction referred to in xa rollback request. connID=% PRINTF_LLFMT d %s</p> <p>Received prepare request for transaction already prepared. connID=% PRINTF_LLFMT d %s</p> <p>Cannot find transaction referred to in xa start (resume) request. connID=% PRINTF_LLFMT d sessID=% PRINTF_LLFMT d %s</p> <p>Cannot find transaction referred to in xa start (join) request. connID=% PRINTF_LLFMT d sessID=% PRINTF_LLFMT d %s</p> <p>Cannot find transaction referred to in xa end request. connID=% PRINTF_LLFMT d sessID=% PRINTF_LLFMT d %s</p>

Multicast Channel Allotted Bandwidth Exceeded.	
Description	Indicates that a multicast channel's allotted bandwidth has been exceeded.

Multicast Channel Allotted Bandwidth Exceeded.	
Resolution	Either slow down the publisher(s), enable flow control, or increase the multicast channel's allotted bandwidth by increasing the channel's maxrate property or increasing the server's multicast_reserved_rate property.
Errors	Multicast channel \'%s\' has exceeded its allotted bandwidth

Multicast Daemon Status Codes and Errors	
Description	Errors occurring in the Multicast Daemon.
Resolution	Check the configuration of the Multicast Daemon and Server, as well as the health of the network.

Multicast Daemon Status Codes and Errors	
Errors	<p>Interface IP address: %s</p> <p>[%s] Connection created, connid=% PRINTF_LLFMT d</p> <p>Error: Unable to set channel property \'%s\'=% PRINTF_LLFMT d</p> <p>[%s] Created consumer consid=%PRINTF_LLFMTd connid=%PRINTF_LLFMTd topic=\'%s\'</p> <p>Multicast Daemon Id=%s</p> <p>Statistics enabled on a %d second interval.</p> <p>Statistics disabled.</p> <p>Rotating log from %s to %s</p> <p>Memory allocation error, possible data loss.</p> <p>Unrecoverable PGM error rc=%d, reason=%s</p> <p>Could not parse configuration file \'%s\'</p> <p>Interface IP address: %s</p> <p>Tracing enabled.</p> <p>Tracing disabled.</p> <p>refused new connection with existing ID % PRINTF_LLFMT d</p> <p>[%s] Connection destroyed, connid=%PRINTF_LLFMTd</p> <p>Error sending to consid=%PRINTF_LLFMTd connid=%PRINTF_LLFMTd from channel \'%s\': %s</p> <p>%s, status=%s</p> <p>Attached channel \'%s\' to consumer consid=%PRINTF_LLFMTd connid=%PRINTF_LLFMTd</p> <p>Error attaching channel \'%s\' to consumer consid=%PRINTF_LLFMTd connid=%PRINTF_LLFMTd</p> <p>Detaching channel \'%s\' from consumer consid=%PRINTF_LLFMTd connid=%PRINTF_LLFMTd</p> <p>Destroying consumer consid=%PRINTF_LLFMTd connid=%PRINTF_LLFMTd</p> <p>Channel configuration from server does not match existing channel \'%s\'</p> <p>Ignoring additional PGM receiver created on group \'%s\', dport=%d, sport=%d, channel=%s</p> <p>Created channel: \'%s\'</p> <p>Error: %s is not a valid multicast-capable IP address. Use the -ifc command line parameter to specify a valid interface.</p>

Multicast General Status Codes and Errors	
Description	General multicast errors that can occur in the Server and Multicast Daemon.
Resolution	Check the configuration of the Multicast Daemon and Server, as well as the health of the network.

Multicast General Status Codes and Errors	
Errors	<p>PGM ERROR: %s - %s (%d)</p> <p>PGM ERROR: channel=\ '%s\' - %s (%d)</p> <p>Error setting PGM parameter %s=%u: %s (%d)</p> <p>Error setting PGM parameter %s=\ '%s\': %s (%d)</p> <p>Error getting PGM parameter \ '%s\': %s (%d)</p> <p>Error getting PGM statistic \ '%s\': %s (%d)</p> <p>Received an invalid EMS Message.</p> <p>Received a message spanning multiple fragments.</p> <p>PGM Session was reset for channel \ '%s\', PGM seqno=%PRINTF_LLFMtd, code=%c</p> <p>Stopped receiving on channel \ '%s\'</p> <p>Started receiving on channel \ '%s\'</p> <p>Error receiving on channel \ '%s\'</p> <p>Stopped sending on channel \ '%s\'</p> <p>Started sending on channel \ '%s\'</p> <p>Error creating sender on channel \ '%s\': %s</p>

Mstore errors	
Description	An error occurred using an Mstore database file.
Resolution	

Mstore errors	
Errors	<p>Unable to open store %s: %s: %d (%s).</p> <p>Wrong schema version. Found %d, expected %d.</p> <p>Schema creation failed: '%s' error: %d %s</p> <p>Unable to reset a statement (%s): %s.</p> <p>Unable to step a statement (%s): %s: %d.</p> <p>Store %s: %s: bind fail: %d.</p> <p>Store %s: Fail retrieving consumer interest: %d.</p> <p>Store %s: Fail retrieving msg interest info: %s.</p> <p>Store %s: Fail writing transaction record: %s.</p> <p>Store %s: Fail reading data: %s.</p> <p>Store %s: Fail reading topic message: %s.</p> <p>Store %s: Fail marking topic message non-pending: %s.</p> <p>Store %s: Fail reading next topic message: %s.</p> <p>Store %s: Fail reading queue message: %s.</p> <p>Store %s: Fail getting next queue message: %s.</p> <p>Store %s: Fail marking queue message non-pending: %s.</p> <p>Store %s: Fail writing transaction info: %s.</p> <p>Store %s: Fail deleting transaction acks: %s.</p> <p>Store %s: Fail recording transaction msg: %s.</p> <p>Store %s: Fail recording transaction acks: %s.</p> <p>Store %s: Fail deleting ack: %s.</p> <p>Store %s: Fail completing transaction: %s.</p> <p>Store %s: Too many entries in memory message interest.</p> <p>Store %s: Invalid message interest for destination % PRINTF_LLFMT d.</p> <p>Store %s: Invalid destination read.</p> <p>Store %s: Failure restoring transaction: %s.</p> <p>Store %s: Failure restoring transaction msg: %s.</p> <p>Store %s: Failure restoring transaction ack: %s.</p> <p>Store %s: Failure resetting topic: %s.</p> <p>Store %s: Correct functioning cannot be guaranteed due to mstore failure. Exiting.</p> <p>Failed writing to mstore: I/O error or out of disk space.</p> <p>Failed writing to mstore: I/O error or out of disk space. Exiting on disk error.</p> <p>Ignoring property mstore_truncate=true for [%s] because this mstore is not in a format that allows truncation. Please use the tibemsdbconvert tool.</p> <p>Pragma INCREMENTAL_VACUUM(%d); returned error %d.</p>

Out of memory	
Description	The server failed to allocate memory as it was attempting to perform an operation.
Resolution	Check how much memory the server process is using according to the operating system. Compare this with how much memory and swap space the host actually has. If there are sufficient memory and swap space, check the operating system limits on the server process to determine if this is the cause. If the limits are set to their maximum and this error occurs, reduce the load on this server by moving some topics and queues to another server.

Out of memory	
Errors	<p>%s trying to recreate persistent message.</p> <p>Error during routed queue configuration, can not create routed queue consumer</p> <p>Could not initialize monitor</p> <p>Error: out of memory processing admin request</p> <p>Error during route configuration, can not create routed queue consumer, err=%s</p> <p>Configuration error - duplicate group: file=%s, line=%d: ignoring line</p> <p>Unable to create admin group: out of memory during initialization</p> <p>Error: unable to create alias for %s '%s': no memory</p> <p>Error: unable to create alias: out of memory</p> <p>Unable to create import event for %s '%s' on transport '%s'</p> <p>Unable to create internal connection, error=(%d) %s</p> <p>Unable to create internal connection: out of memory during initialization</p> <p>Error: unable to create %s '%s': no memory</p> <p>Error: unable to create route while parsing file=%s, line=%d.</p> <p>Unable to create SmartSockets subscriber on transport '%s', %s '%s': out of memory</p> <p>Unable to create temporary destination, out of memory</p> <p>Failed to create reserve memory. Exiting.</p> <p>Failed writing message to '%s': No memory for operation.</p> <p>Unable to process message imported on transport '%s'.</p> <p>Fault Tolerant configuration, no memory!</p> <p>Fault Tolerant error, no memory.</p> <p>LDAP initialization failed.</p> <p>No memory.</p> <p>No memory: %s.</p> <p>No memory authenticating user '%s'</p> <p>No memory authenticating via LDAP</p> <p>Out of memory while building admin response message</p> <p>Out of memory while building JNDI response message</p> <p>Out of memory creating global import event on transport '%s'</p> <p>Out of memory creating import event for %s '%s' on transport '%s'</p> <p>Out of memory creating SS transport %s</p> <p>No memory creating stalled flows in destination</p> <p>Out of memory during initialization</p> <p>Could not set replyto destination exporting SS message.</p> <p>Could not set destination exporting SS message.</p> <p>Could not get destination exporting SS message.</p>

Out of memory

Failed to initialize SS message fields exporting SS message.

Out of memory exporting SS message.

Out of memory: unable to process SS message type on export

No memory for creating connection.

No memory generating dynamic route durable.

Out of memory importing SS message. error=%s.

No memory in IO thread to create pool.

Out of memory while parsing bridges file

Out of memory while parsing factories file

Out of memory while parsing routes file

No memory performing routing operation.

Out of memory processing %s on %s '%s'

Out of memory processing administrative request

Out of memory processing message tracing

No memory processing purge record.

No memory while processing route interest

Out of memory processing transports

Out of memory processing transports configuration

Out of memory reading configuration.

Out of memory restoring routed consumer

Out of memory sending monitor message.

No memory sending topic routing information.

%s trying to add message to %s queue.

No memory trying to add message to system.

No memory trying to cleanup route.

No memory to create ack record.

No memory to create client connection

No memory to create configured durable '%s%s%s'.

No memory to create configured durables

No memory to create confirm record.

No memory to create connection.

No memory to create consumer.

No memory trying to create destination.

No memory to create destination for consumer or browser.

No memory trying to create global topic destination.

No memory to create message from store.

Out of memory

No memory trying to create message producer.
 No memory to create producer.
 No memory trying to create queue browser.
 No memory trying to create response message.
 No memory to create routed consumer
 No memory to create routed queue consumers
 No memory trying to create routed queue destination.
 No memory trying to create routed tmp queue destination.
 No memory to create session.
 No memory trying to create tmp destination for consumer.
 No memory trying to create transaction.
 No memory to create valid messages record.
 No memory restoring valid sequence number info.
 No memory to create zone.
 No memory trying to export message to RV.
 No memory trying to export message to SS.
 No memory trying to import message from RV%s.
 No memory trying to import message from RVCN.
 No memory trying to import message from SS. error=%s.
 No memory trying to initialize connection.
 No memory trying to initialize route connection.
 No memory trying to parse configured durable.
 No memory trying to process data message.
 No memory trying to process queue message.
 No memory to process route interest
 No memory trying to process system request.
 No memory trying to process topic consumer.
 No memory trying to process topic message.
 No memory trying to process xa end. connID=% PRINTF_LLFMT d sessID=%
 PRINTF_LLFMT d %s
 No memory trying to read message from store.
 Route down while trying to recover routed consumer.
 No memory trying to recover routed consumer.
 No memory trying to recover one msg for routed consumer.
 No memory trying to recover route stall.
 No memory trying to recover route stall, will try again.

Out of memory

No memory to restore messages.
 No memory to restore prepared transactions.
 No memory trying to retrieve for queue browser.
 No memory trying to send recover/rollback response.
 out of memory trying to send topic interest to routes
 No memory to set clientID for connection.
 No memory trying to setup queue route configuration
 No memory trying to setup route configuration
 No memory trying to setup topic route configuration
 Route recovery of destination %s on route from %s will fail: No memory
 Route recovery of destination %s on route from %s will fail: No memory to create timer
 Route recovery of destination %s on route from %s will fail: %s
 Failed to initialize OpenSSL environment: out of memory
 Out of memory queuing imported message for processing.
 Out of memory gathering consumers for incoming message.
 Out of memory scheduling message delete.
 Out of memory preparing to write message.
 Out of memory assembling list of message to store.
 Out of memory processing route consumer.
 Out of memory preparing message for writing.
 Out of memory creating connection thread list.
 Out of memory creating RV gateway thread list.
 Out of memory creating SmartSockets gateway thread list. error=%s.
 Out of memory delaying bridged flow control response.
 Out of memory preparing to delay flow control response.
 Out of memory delaying one flow control response.
 Out of memory delaying set of flow control responses.
 Out of memory trying to clear message hold.
 Out of memory trying to delete held message.
 Unable to update the valid messages record. Error code: %d - %s.
 No memory scheduling message delete completion, Error code: %d.
 No memory to build msg properties.
 No memory to create prop.
 No memory to set prop.
 No memory getting the list of delivered messages. The JMSXDeliveryCount property of some messages may no longer be accurate.

Out of memory	
	<p>No memory getting the list of delivered messages from session % PRINTF_LL_FMT d. The JMSXDeliveryCount property of messages that were sent to this session may no longer be accurate.</p> <p>No memory getting the list of delivered messages during rollback of transaction with xid: %s. The JMSXDeliveryCount property of messages that were rolled-back may no longer be accurate.</p> <p>Out of memory discarding message.</p> <p>Out of memory advancing queue pending.</p> <p>Out of memory adding message to pending list.</p> <p>Out of memory returning message to pending list.</p> <p>Out of memory trying to re-queue after xa rollback.</p> <p>Out of memory finalizing restored queue: %s.</p> <p>Out of memory restoring queue flush state.</p> <p>Out of memory detaching message during queue purge.</p> <p>Out of memory removing message from queue.</p> <p>Out of memory retrieving message by correlation id.</p> <p>Out of memory scheduling cleanup of transaction ack: %s.</p> <p>Out of memory setting message all acked: %s.</p> <p>Out of memory cleaning up transaction: %s.</p> <p>Out of memory updating sent state on ack.</p> <p>Out of memory updating in-doubt state on ack.</p> <p>Out of memory removing message from system.</p> <p>Out of memory associating ack with data.</p> <p>Out of memory associating ack with transaction.</p> <p>Error setting mstore discard scan: %s.</p> <p>Error setting mstore_truncate timer: %s.</p> <p>Out of memory recording modified topic.</p> <p>Out of memory re-queuing sent messages.</p> <p>No memory trying to resend delivered messages following an xa end NOTA. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d %s</p> <p>No memory to create consumer on %s [%s]</p> <p>Failed to set delivery count in %smessage: status=%s</p> <p>Failure to create per-mstore delayed delivery state: %s.</p>
Protocol error, incorrect XID in XA request	
Description	The tibemspd received an XA End instruction from the third party Transaction Manager which referred to a different transaction from the one currently in use by the session.

Protocol error, incorrect XID in XA request	
Resolution	Report this to the your Transaction Manager vendor.
Errors	Incorrect xid in xa end (0x%x) request. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d %s

Protocol error, transaction in incorrect state	
Description	A client application's attempt to start an XA transaction failed because the transaction already exists and is not in the correct state.
Resolution	This error is most likely caused by an external transaction manager that allowed two separate client applications to use the same XA transaction identifier (XID). Consult the manual for the transaction manager or report this to the transaction manager vendor.
Errors	<p>Cannot process xa start for a session when another transaction is already active on that session. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d %s</p> <p>Cannot process xa start with TMNOFLAGS when the transaction is already active. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d %s</p> <p>All clients participating in the same global transaction must use the same protocol, connID=% PRINTF_LL_FMT d</p> <p>Invalid xa start (resume) request: the session was not previously suspended. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d %s</p> <p>Error processing xa start - transaction marked ROLLBACKONLY. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d %s</p> <p>Error processing xa start request, %s. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d %s</p> <p>Invalid xa end (suspend) request: session already suspended or not started. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d %s</p> <p>Invalid xa end request: the session was neither associated with a transaction nor suspended. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d %s</p> <p>Error processing xa prepare - transaction marked ROLLBACKONLY, %s. connID=% PRINTF_LL_FMT d %s</p>

Protocol message format error	
Description	tibemsd received a message with either missing or incomplete data.
Resolution	Send details of the error and the situation in which it occurred to TIBCO Support.

Protocol message format error	
Errors	<p>Unable to confirm session, invalid request.</p> <p>Unable to create consumer, invalid destination.</p> <p>Unable to init session, invalid request.</p> <p>Unable to process msg for export. error=%s.</p> <p>Unable to recover consumer, invalid request.</p> <p>Unable to recover consumer, invalid session.</p> <p>Unable to recover one msg for consumer, invalid request.</p> <p>Unable to recover one msg for consumer, invalid sequence number.</p> <p>Unable to recover one msg for consumer, invalid session.</p> <p>Unable to serve the flow stall recover request from server %s, invalid request.</p> <p>Unable to start consumer, invalid consumer</p> <p>Unable to server the flow stall recover request from server %s, invalid consumer.</p> <p>Unable to unsubscribe consumer, invalid client request.</p> <p>%s: %s failed: illegal to use %s [%s] in standby state.</p> <p>Invalid flag in xa end request. connID=% PRINTF_LLFFMT d sessID=% PRINTF_LLFFMT d %s</p> <p>Invalid flag in xa start request. connID=% PRINTF_LLFFMT d sessID=% PRINTF_LLFFMT d %s</p> <p>Invalid request to delete temporary destination: %s. connID=% PRINTF_LLFFMT d</p> <p>Invalid request to delete temporary destination: not owner connection.</p> <p>Invalid xid in commit request.</p> <p>Invalid xid in commit transaction record.</p> <p>Invalid xid trying to update(%d) transaction record.</p> <p>Invalid xid in rollback request.</p> <p>Invalid xid in rollback transaction record.</p> <p>Invalid xid in xa commit request. connID=% PRINTF_LLFFMT d</p> <p>Invalid xid in xa end request. connID=% PRINTF_LLFFMT d sessID=% PRINTF_LLFFMT d</p> <p>Invalid xid in xa prepare request. connID=% PRINTF_LLFFMT d</p> <p>Invalid xid in xa rollback request. connID=% PRINTF_LLFFMT d</p> <p>Invalid xid in xa start request. connID=% PRINTF_LLFFMT d sessID=% PRINTF_LLFFMT d</p> <p>Malformed routed message</p> <p>Problem decoding sequence data in confirm: %s.</p> <p>Problem decoding sequence data in rollback.</p> <p>Problem decoding sequence data in xa end. connID=% PRINTF_LLFFMT d sessID=% PRINTF_LLFFMT d %s</p>

Protocol message format error	
	<p>%s:%s queue browser failed: queue name is missing in request message</p> <p>Received admin request with replyTo not set</p> <p>Received JNDI request with replyTo not set.</p> <p>Received unexpected message type %d</p> <p>No destination in incoming data message.</p> <p>Invalid %s message</p>

Protocol Sequence Error	
Description	A non-embedded java client is attempting to connect to a tibemsd that is part of an embedded JMS environment.
Resolution	Reconfigure the client to connect to a fully licensed tibemsd.
Errors	<p>Invalid client connect detected.</p> <p>No closure.</p>

Recovery errors	
Description	An error occurred during the recovery process.
Resolution	<p>If you are not able to fix the problem and need to restart the system, make a backup of the store files and restart the server with the '-forceStart' command line parameter. The server will then attempt to start regardless of errors (expect out-of-memory errors). In this mode, application messages and/or internal records causing problems (due to file corruption or other) will be deleted. Therefore, dataloss is likely to occur, so this command line parameter should be used with extreme caution and only after understanding the consequences. A copy of the store files can be sent to TIBCO Support for post-mortem analysis.</p>

Recovery errors	
Errors	<p>The recovery process stopped while processing a '%s' record (id=% PRINTF_LLFMT d), error: %d - %s. Check the section 'Error Recovery Policy' from chapter 'Running the EMS Server' in the User's Guide before attempting to restart the server</p> <p>The recovery process stopped while processing a '%s' record (id=% PRINTF_LLFMT d) due to an out-of-memory condition. Ensure that the system can allocate sufficient memory to the EMS Server process before restarting it</p> <p>Unable to get the session's context handle for %s record: %d - %s</p> <p>Unable to get the list iterator for %s record</p> <p>Unable to get next element from list for %s record</p> <p>Unable to create %s object, no memory</p> <p>Error occurred while processing %s record id=% PRINTF_LLFMT d (%s) - Unable to reconstruct message: %d - %s</p> <p>Unable to recreate zone '%s': %d - %s</p> <p>Unable to add zone '%s' to the system: %d - %s</p> <p>Zone '%s' is defined as type '%s' in configuration but also is defined as type '%s' in meta.db</p> <p>Unable to recreate connection id=% PRINTF_LLFMT d, client id=%s: %d - %s</p> <p>Discarding session id=% PRINTF_LLFMT d because the connection id=% PRINTF_LLFMT d was not recovered. Recovery continues</p> <p>Unable to recreate session id=% PRINTF_LLFMT d with connection id=% PRINTF_LLFMT d and client id=%s: %d - %s</p> <p>Unable to recreate consumer id=% PRINTF_LLFMT d with connection id=% PRINTF_LLFMT d, session id=% PRINTF_LLFMT d, and client id=%s: invalid destination: %s</p> <p>No memory to create destination for consumer id=% PRINTF_LLFMT d</p> <p>Discarding consumer id=% PRINTF_LLFMT d on destination '%s' because connection id=% PRINTF_LLFMT d with client id=%s was not restored. Recovery continues</p> <p>Discarding consumer id=% PRINTF_LLFMT d on destination '%s' and connection id=% PRINTF_LLFMT d with client id=%s because session id=% PRINTF_LLFMT d was not restored. Recovery continues</p> <p>No memory to recreate consumer id=% PRINTF_LLFMT d</p> <p>Failed to build import selectors for consumer id=% PRINTF_LLFMT d: %d - %s</p> <p>Failed to read import selectors for routed consumer id=% PRINTF_LLFMT d: %d - %s</p> <p>Discarding durable id=% PRINTF_LLFMT d (connection id=% PRINTF_LLFMT d, client id=%s) on destination '%s' because the durable name is not specified. Recovery continues</p> <p>Unable to recreate producer id=% PRINTF_LLFMT d with connection id=% PRINTF_LLFMT d, session id=% PRINTF_LLFMT d, and client id=%s: invalid destination: %s</p> <p>No memory to create destination for producer id=% PRINTF_LLFMT d</p> <p>Discarding producer id=% PRINTF_LLFMT d on destination '%s' because connection id=% PRINTF_LLFMT d was not restored. Recovery continues</p>

Recovery errors	
	<p>Discarding producer id=% PRINTF_LL_FMT d on destination '%s' with connection id=% PRINTF_LL_FMT d and client id=%s because session id=% PRINTF_LL_FMT d was not restored. Recovery continues</p> <p>Unable to recreate purge record: invalid destination: %s</p> <p>Unable to recreate purge record for destination %s: %d - %s</p> <p>Error creating message for transaction record: %d - %s</p> <p>Error creating message's store structure for transaction record: %d - %s</p> <p>Unable to recover transaction record: transaction id missing: %d - %s</p> <p>Unable to recover transaction id=% PRINTF_LL_FMT d: %d - %s</p> <p>Unable to recover ack record (txid=% PRINTF_LL_FMT d, consid=% PRINTF_LL_FMT d, seqid=% PRINTF_LL_FMT d, location=%s): %d - %s</p> <p>Unable to recover ack record, cannot create message: %d - %s</p> <p>Unable to recover sequence numbers from valid record: %s</p> <p>Unable to recover message, can not create lock: %d - %s</p> <p>Unable to restore held message from store, (location=%s) no memory</p> <p>Unable to restore message sequence=% PRINTF_LL_FMT d: (location=%s) %d - %s</p> <p>No memory to create destination for message</p> <p>Inconsistency restoring routed message sequence=% PRINTF_LL_FMT d</p> <p>No memory to restore routed message sequence=% PRINTF_LL_FMT d</p> <p>Persisted message possibly corrupted: %s</p> <p>Error creating message's store structure: %d - %s</p>

Rejected attempt to connect via SSL to TCP port	
Description	A client application attempted to connect to the server's TCP port using the SSL protocol.
Resolution	Change the client application's URL from ssl to tcp or change the server's listen parameter from tcp to ssl. To activate a change of the server listen parameter requires a restart of the server.
Errors	Rejected attempt to connect via SSL to TCP port

Rejected attempt to connect via TCP to SSL port	
Description	A client application attempted to connect to the server's SSL port using the TCP protocol.
Resolution	Change the client application's URL from tcp to ssl or change the server's listen parameter from ssl to tcp. To activate a change of the server listen parameter requires a restart of the server.

Rejected attempt to connect via TCP to SSL port	
Errors	Rejected attempt to connect via TCP to SSL port

Rejected connect from route: invalid cycle in route	
Description	The multi-hop route support of the server does not support configuring a cycle. However, it detected a configuration that would create a cycle.
Resolution	Remove one of the routes that creates the cycle.
Errors	[%s@%s]: rejected connect from route: invalid cycle in route: %s Illegal, route to '%s' creates a cycle. Terminate the connection Illegal, route to '%s' creates a cycle.

Rendezvous transport error	
Description	tibemsd encountered a Rendezvous error.
Resolution	See Rendezvous documentation for details of what the error means and how to remedy it.

Rendezvous transport error	
Errors	<p>Unable to create dispatcher for import event for %s '%s' on transport '%s', error is %s</p> <p>Unable to create inbox for import event for %s '%s' on transport '%s'</p> <p>Unable to create Rendezvous Certified transport '%s': %s</p> <p>Unable to create Rendezvous Certified transport '%s' because unable to create Rendezvous transport '%s'</p> <p>Unable to create Rendezvous transport '%s': %s</p> <p>Unable to create TIBCO Rendezvous Certified Listener for %s '%s' on transport '%s': %s</p> <p>Failed to confirm RVCN message: %d (%s)</p> <p>Failed to confirm RVCN message sequence % PRINTF_LLFMT u from cm sender '%s'. Error: %d (%s)</p> <p>Unable to store trackId % PRINTF_LLFMT d for RVCN message sequence % PRINTF_LLFMTu from cm sender '%s'. Error: %d (%s)</p> <p>Unable to retrieve trackId % PRINTF_LLFMT d. Error: %d (%s)</p> <p>A problem occurred while importing RVCN message sequence % PRINTF_LLFMT u from cm sender '%s'. Expecting a redelivery</p> <p>Unable to queue the request type: %d. Transport '%s', destination '%s', CM Sender '%s', CM Sequence % PRINTF_LLFMT u . Error: %d (%s)</p> <p>Unable to queue the request type: %d. Transport '%s', destination '%s'. Error: %d (%s)</p> <p>Failed to disallow Rendezvous Certified Message listener '%s': %s</p> <p>Unable to export topic message, error=%s.</p> <p>Unable to pre-register certified listener '%s' on transport '%s': %s</p> <p>Rendezvous send failed on transport '%s', error='%s'</p> <p>Unable to restart the CM Listener for %s '%s' (RVCN Transport '%s'). Error code: %d '%s'</p> <p>Unable to create the timer for the restart of the CM Listener for %s '%s' (RVCN Transport '%s'). Error code: %d '%s'</p> <p>Unable to stop the CM Listener for %s '%s' (RVCN Transport '%s'). Error code: %d '%s'</p>

Restoring consumer failed	
Description	Seen when tibemsd starts up and detects that the zone for a route as specified in routes.conf has been changed.
Resolution	Either delete the route or change its zone back and restart the tibemsd.
Errors	Restoring consumer failed: Conflicting zone for route to [%s]: The route was initially zone \ %s\ type %s, but now \ %s\ type %s. Zone change not allowed while there are durable subscribers. Please delete the route first and create new one.

Running on reserve memory	
Description	Warnings indicating that the tibemspd has run out of memory and is now using its reserve memory
Resolution	Either reduce the tibemspd's memory requirement by consuming messages or removing messages from its queues, or increase the amount of memory available to the tibemspd by shutting down other processes on the machine or increasing the machine's memory.
Errors	<p>Running on reserve memory, ignoring new message.</p> <p>Running on reserve memory, no more send requests accepted. Pending msg count = % PRINTF_LLFMT d</p> <p>Pending msg count = % PRINTF_LLFMT d</p>

Runtime Error in Fault-Tolerant Setup	
Description	In a fault-tolerant setup, error occurs at runtime.
Resolution	Check the status of both servers (primary, secondary). In case of both active, the file store data may be corrupted already and we recommend shutting down both servers and investigating the situation.
Errors	<p>Fault-tolerance error: Dual-Active server detected at: '%s'</p> <p>The active EMS server does not hold the lock on meta store</p> <p>The standby EMS server could not find the specified meta store.</p> <p>The active EMS server name is %s while the standby EMS server name is %s. The names must be the same</p> <p>A standby EMS server (%s) is already connected to the active EMS server</p> <p>Fault Tolerant error (%s), can't create connection to '%s'.</p> <p>Cannot determine which server should be active because both servers have been forced to start separately. Please force one of them to start (\forstart\ tibemspdadmin command). The other server will discard its data.</p> <p>This standby server is joining an active server and both have previously been forced to start. This server is discarding its data.</p> <p>Erasing content of store %s</p> <p>Internal error: Identical non-0 FT determination counters</p> <p>Store '%s' not defined on the active server, skipping it</p> <p>Store '%s' on the active server has a different file name than on the standby server</p> <p>Store '%s' is not present in the standby server configuration</p> <p>Error checking active server's configuration: %d - %s</p> <p>The configuration used on startup is incompatible with the one sent by the active server. Exiting!</p>

SmartSockets transport error	
Description	tibemsd encountered a SmartSockets error.
Resolution	See SmartSockets documentation for details of what the error means and how to remedy it.

SmartSockets transport error	
Errors	<p>Unable to create SmartSockets subscriber on transport '%s': failed to convert %s '%s', error=%s</p> <p>Unable to import SmartSockets message on transport %s: failed to convert subject '%s', error=%s</p> <p>Unable to import SmartSockets message on transport %s: failed to tokenize subject '%s'</p> <p>Unable to import SmartSockets message on transport %s: failed to convert reply subject '%s', error=%s</p> <p>Unable to import SmartSockets message on transport %s: no destination found '%s'</p> <p>Unable to export EMS message into SmartSockets on transport '%s'. Failed to convert subject '%s', error=%s.</p> <p>Unable to export EMS message into SmartSockets on transport '%s'. Failed to convert reply subject '%s', error=%s.</p> <p>Error translating EMS message body into SS message. Status=%s</p> <p>Error translating EMS message headers into SS message. Status=%s</p> <p>Error translating EMS message properties into SS message. Status=%s</p> <p>Unable to confirm SS message. %s</p> <p>Unable to connect to SmartSockets RTserver via transport: '%s': %d - %s</p> <p>Unable to register GMD failure callback: '%s': %d - %s</p> <p>Unable to create open callback on transport: '%s': %d - %s</p> <p>Unable to create default callback on transport: '%s': %d - %s</p> <p>Unable to create SS callback for %s '%s' on transport '%s' SS error: %s</p> <p>Unable to create SS message type on export</p> <p>Unable to create SmartSockets subscriber for %s '%s' on transport '%s', error: %s</p> <p>Unable to create SmartSockets transport '%s': %d - %s</p> <p>Failed to confirm SS message. error=%s.</p> <p>Failed to create SmartSockets transport %s</p> <p>Unable to handoff confirm SS message: %s.</p> <p>Unable to import SS message. Error=%d, %s.</p> <p>Unable to import SS message data fields. Error=%d, %s.</p> <p>Unable to import SS message headers. Error=%d, %s.</p> <p>Unable to import SS message, failed to create message destination.</p> <p>Unable to import SS message, failed to create reply destination.</p> <p>Unable to import SS message, error retrieving delivery mode.</p> <p>Unable to import SS message, error setting imported property. error=%s.</p> <p>Unable to import SS message, error setting message extensions property. error=%s.</p> <p>Unable to import SS message, failed to create message wire. error=%s.</p> <p>Unable to import SS message, error retrieving number of fields.</p>

SmartSockets transport error	
	<p>Unable to initialize SmartSockets transport '%s': error=%d: %s</p> <p>Unable to set SmartSockets Dispatcher for transport: '%s': %d - %s</p> <p>Unable to set SS message type on export</p> <p>Unable to set Username/Password for SmartSockets transport '%s': %d - %s</p> <p>Unable to import SmartSockets message on transport %s: failed to retrieve SS subject.</p> <p>SS Subject CB destroy Failed: for '%s' on transport '%s' SS error: %s</p> <p>SS Subject CB lookup Failed: for '%s' on transport '%s' SS error: %s</p> <p>SmartSockets TipcMsgSetDeliveryMode failed, '%s'</p> <p>SmartSockets TipcMsgSetLbMode failed, '%s'</p> <p>SmartSockets TipcSrvConnFlush failed, '%s'</p> <p>SmartSockets TipcSrvConnMsgSend failed, '%s'</p> <p>SS Unsubscribe failed: for '%s' on transport '%s' SS error: %s</p> <p>GMD delivery failed on transport '%s', SS message seq=%d, reason='%s' for process '%s'</p> <p>Unable to process undelivered SS GMD message, can not register EMS message, error='%s', tport='%s', GMD seq=%d</p> <p>Unable to process undelivered SS GMD message, can not add to undelivered EMS queue, error='%s', tport='%s', GMD seq=%d</p> <p>Unable to process undelivered SS GMD message, failed to build EMS message, error='%s', tport='%s', GMD seq=%d</p> <p>Unable to convert undelivered SS GMD message into EMS message, error='%s', tport='%s', GMD seq=%d</p>

SSL initialization failed	
Description	The server failed attempting to initialize the OpenSSL library.
Resolution	Examine the OpenSSL error and the EMS User's Guide chapter describing the use of SSL.

SSL initialization failed	
Errors	<p>Failed to process ft ssl password</p> <p>Failed to process ssl password</p> <p>Ignoring SSL listen port %s</p> <p>Failed to initialize SSL: can not load certificates and/or private key and/or CRL file(s) and/or ciphers.</p> <p>Failed to initialize OpenSSL environment: error=%d, message=%s.</p> <p>Failed to initialize SSL. Error=%s</p> <p>Failed to initialize SSL: unable to obtain password</p> <p>Failed to initialize SSL: server certificate not specified.</p> <p>Failed to initialize SSL: server private key not specified.</p> <p>Using secondary SSL password.</p> <p>Using secondary SSL identity.</p> <p>Using secondary SSL expected host name.</p> <p>Using secondary SSL private key.</p>

Standby server '%s' disconnected	
Description	Lost connection with the standby fault-tolerant server.
Resolution	Determine if the standby server is running. If it is running, check for a network partition.
Errors	Standby server '%s' disconnected.

Store file format mismatch	
Description	The store files specified were created from a different version of EMS that is not supported by this version.
Resolution	Revert to use the version of EMS that created the store file or locate the store file conversion tool and use it to convert the store file to this version.
Errors	Unsupported store format: %s (%d)

System call error, should be errno-driven	
Description	A low-level system function has failed.
Resolution	Report the error to your system administrator and ask them to remedy the problem.

System call error, should be errno-driven	
Errors	<p>Accept() failed: too many open files. Please check per-process and system-wide limits on the number of open files.</p> <p>Accept() failed: %d (%s)</p> <p>Select() failed: %d (%s)</p> <p>%s%se=%p refs=%lld flags=%u type=%u id=%u subtype=%u q=%u cb_count=%u ioType=%u ioSrc=%d ioValid=%d ioVChecked=%d cb=%p free_cb=%p</p> <p>Epoll_wait() failed: %d (%s)</p> <p>Epoll_ctl() %s on fd %d failed: %d (%s)</p> <p>ioctl() on /dev/poll failed: %d (%s)</p> <p>write() %s update /dev/poll on fd %d failed: %d (%s)</p> <p>Cannot retrieve user name of the current process.</p> <p>Client connection not created, %s.</p> <p>Could not obtain hostname</p> <p>Could not resolve hostname '%s'. Possibly default hostname is not configured properly while multiple network interfaces are present.</p> <p>Unable to listen for connections: %d (%s).</p> <p>Unable to open socket for listening: %d (%s).</p> <p>Closing connection from %s due to timeout, exceeded timeout of %d.</p> <p>Could not %s sequential file optimization: %d.</p>

Transaction action while previous action is incomplete.	
Description	State-modifying action is requested on a transaction for which another such action is being processed.
Resolution	Send details of the error and the situation in which it occurred to TIBCO Support.
Errors	<p>Cannot request second state change for transaction while the first request is in progress (%d, %d) %s.</p> <p>Unexpected request to roll xa txn forward with previous operation (%d) incomplete: %s.</p> <p>Unexpected request to roll xa txn back with previous operation (%d) incomplete: %s.</p> <p>Unexpected request to prepare xa txn with previous operation (%d) incomplete: %s.</p> <p>Unexpected request to commit xa txn with previous operation (%d) incomplete: %s.</p> <p>Unexpected request to commit session with previous operation (%d) incomplete.</p>

Transaction timeout.	
Description	Transaction not completed before timeout. Offending transaction is discarded.
Resolution	Most likely, transaction manager error prevented it from advancing this transaction in a timely manner. Verify correct operation of the transaction manner.

Transaction timeout.	
Errors	Rollback due to timeout on unprepared transaction. connID=% PRINTF_LL_FMT d %s

Unnecessary or duplicate message	
Description	tibemsd received a message with either missing or incomplete data.
Resolution	Send details of the error and the situation in which it occurred to TIBCO Support.
Errors	Error processing xa start request, %s. connID=% PRINTF_LL_FMT d sessID=% PRINTF_LL_FMT d Error trying to enter standby for '%s', %s.

Unrecognized option	
Description	The server's command line contains an unrecognized option.
Resolution	Run the server with the -help option and compare it with the command line containing the unrecognized option.
Errors	Unrecognized option: '%s'.

Appliance State Replication Events.	
Description	A transition occurred in the State Replication feature.
Resolution	Refer to the section of the documentation pertaining to State Replication.
Errors	Transitioning to Server State: %s Transitioning to Server State: %s Forced exit to prevent dual-active servers Forced early exit - caught signal during server startup