



TIBCO Flogo®

Release Notes

Version 2.26.5 | June 2026

Contents

Contents	2
New Features	4
Version 2.26.5	4
Version 2.26.4	5
Version 2.26.3	6
Version 2.26.2	7
Version 2.26.1	7
Version 2.26.0	9
Changes in Functionality	11
Deprecated Features	13
Removed Features	14
Migration and Compatibility	15
Closed Issues	16
Known Issues	17
TIBCO Flogo	17
Database Services	42
Flogo Connector for Agentic AI - Tech Preview	42
Flogo Connector for Amazon Kinesis	43
Flogo Connector for Apache Avro	43
Flogo Connector for Apache Kafka	43
Flogo Connector for Apache Pulsar	44
Flogo Connector for Docusign	44
Flogo Connector for EMS	44

Flogo Connector for FTL	45
Flogo Connector for Google Cloud Pub/Sub	45
Flogo Connector for HTTP	45
Flogo Connector for IBM MQ	46
Flogo Connector for Mail	46
Flogo Connector for Microsoft Azure Service Bus	47
Flogo Connector for Microsoft SQL Server	47
Flogo Connector for MongoDB	48
Flogo Connector for OData	49
Flogo Connector for Oracle Database	49
Flogo Connector for Oracle MySQL	50
Flogo Connector for PostgreSQL	50
Flogo Connector for Salesforce.com Einstein Analytics	51
Flogo Connector for TIBCO Cloud Messaging	52
Flogo Connector for TIBCO Data Virtualization	52
Flogo Connector for WebSockets	53
TIBCO Documentation and Support Services	54
Legal and Third-Party Notices	56

New Features

Version 2.26.5

Upgrade Google Connection to Override Service Account Key

You can securely configure Google connections by leveraging enhanced options for the Service Account Key. You can override the key using a Base64-encoded value, a JSON service account key, a file path (starting with `file://`), or a Kubernetes secret, providing greater flexibility in managing your Google connections. For more information, see *TIBCO Flogo® Connectors User Guide*.

TIBCO Flogo® Connector for Agentic AI - Tech Preview

- Azure OpenAI LLM Provider support: A new AzureOpenAI provider option in the LLM Provider Configuration enables direct integration with Azure-hosted OpenAI models using Azure-specific deployment, region, and resource settings.
- Memory Conversation Store in the LLM Client Activity: The LLM Client Activity now supports an in-process memory conversation store, enabling multi-turn conversational interactions.
- Dynamic MCP Server and A2A Server configuration via LLM Client Activity inputs: The LLM Client Activity Input tab now includes `mcpServerConfigs` and `a2aServerConfigs` array fields, allowing MCP servers and A2A remote agents to be configured dynamically at runtime without pre-configured connection resources.

TIBCO Flogo® Connector for Model Context Protocol (MCP)

- Scope-based access control for JWT authentication: A new Required Scope field on MCP Server handlers enables per-tool, per-prompt, and per-resource authorization based on JWT token scopes.
- Structured content support for tool responses: A new Reply Settings tab with Tool Output Schema and a `structuredContent` field in Map from Flow Outputs enable MCP tools to return structured, schema-validated responses alongside text responses.
- Content annotations for tool responses: The MCP Server trigger reply now includes

optional audience and priority fields on the tool response object, enabling MCP content annotations on tool results. For existing apps, you must sync the trigger reply schema to pick up the new audience and priority fields before they can be mapped in the flow.

- **Enhanced tokenInfo claims:** The tokenInfo object in Map to Flow Inputs now exposes additional standard JWT claims (iss, sub, aud, name, email) for richer authorization and audit logging.
- **MCP Client Activity:** A new activity that enables Flogo flows to invoke tools on remote MCP servers as an MCP client, with support for multiple transport types, authentication modes, and structured JSON responses.
- **MCP Client OAuth2 Configuration:** A new connection type that provides OAuth2 authentication for the MCP Client Activity, supporting both Client Credentials and Authorization Code grant types.
- **OpenTelemetry support for MCP Server trigger:** The MCP Server trigger now supports OpenTelemetry for distributed tracing and observability of MCP server operations.

TIBCO Flogo® Connector for Apache Pulsar

- **Trigger-level Flowlimit:** TIBCO Flogo® Connector for Apache Pulsar now supports trigger-level flowlimit.

Version 2.26.4

The following features have been added in this release of TIBCO Flogo®, TIBCO Flogo® Extension for Visual Studio Code, and Flogo® Connectors.

Flow Instance ID now included in Error Object

The flowInstanceId is now included in the data of the Error object, supporting error correlation with specific flow instances.

TIBCO Flogo® Connector for Google Cloud Storage

TIBCO Flogo® Connector for Google Cloud Storage now supports List Activity. For more information, see [Google Cloud Storage List](#).

TIBCO Flogo® Connector for Agentic AI - Tech Preview

- TIBCO Flogo® Connector for Agentic AI – Tech Preview now includes support for

agents to communicate with each other using A2A protocol.

- TIBCO Flogo® Connector for Agentic AI – Tech Preview now includes the LLM Client activity, which allows you to dynamically configure the LLM provider, model, and authentication at runtime, eliminating the need for pre-configured connections.
- TIBCO Flogo® Connector for Agentic AI – Tech Preview now includes a new input field, `filteredToolNames`, in the AI Agent activity, which accepts a string array to limit the tools available during an invocation and enable context reduction.

TIBCO Flogo® Connector for Apache Pulsar

TIBCO Flogo® Connector for Apache Pulsar now supports trigger-level flowlimit.

Version 2.26.3

The following features have been added in this release of TIBCO Flogo®, TIBCO Flogo® Extension for Visual Studio Code, and Flogo® Connectors.

Activity Type in Flogo Metrics

You can now include the activity type as a label in TIBCO Flogo® metrics. This enhancement provides greater clarity and observability by allowing you to associate metrics, such as DB operation latency or REST invoke success rates, directly with their corresponding activity types. For more information, see [OpenTelemetry Collector](#).

Enhanced OpenTelemetry Metrics for Flogo

TIBCO Flogo® now provides additional metrics for OpenTelemetry (OTEL) collectors. You can access `flogo_activity_execution_duration_msec` and `flogo_flow_execution_duration_msec` metrics via OTEL, allowing for more comprehensive monitoring and analysis of your Flogo applications. This eliminates the need to bypass the OTEL collector for these specific metrics. For more information, see [OpenTelemetry Collector](#).

Improved Schema Validation Runtime Error

A new engine variable `FLOGO_SCHEMA_VALIDATION` is added to enforce runtime schema validation. When enabled, the application fails during execution if the engine detects any schema validation issues. For more information, see [Environment Variables](#).

Ability to Specify a Custom Build Name

You can specify a build name in the command `build-tp-deployment` using a flag `-b` or `-build-name` that helps identify the builds with a user given name on TIBCO Control

Plane. For more information, see [Building Flogo App Executable and Docker Image Using Flogo - App Build CLI](#).

Newly Supported Connector

TIBCO Flogo® Connector for Google Cloud Storage is the newly supported connector. For more information, see [Supported Flogo Connectors](#).

TIBCO Flogo® Connector for Model Context Protocol (MCP)

- TIBCO Flogo® Connector for Model Context Protocol (MCP) now supports annotation settings for Tool primitives in the MCP Server Trigger Handler. You can specify whether a tool is ReadOnly, Destructive, Idempotent, or Open World.
- TIBCO Flogo® Connector for Model Context Protocol (MCP) now allows you to configure whether the MCP server operates in stateless or stateful mode.

TIBCO Flogo® Connector for Agentic AI - Tech Preview

TIBCO Flogo® Connector for Agentic AI – Tech Preview now includes support for the Amazon Bedrock Anthropic provider.

Version 2.26.2

Support for Encrypted SSL Fields

To improve security, SSL client and server keys PEM-encoded files get encrypted when they are uploaded in REST triggers and Invoke REST activities. For more information, see [REST Trigger - ReceiveHTTPMessage](#).

Newly Supported Connectors

TIBCO Flogo® Connector for Agentic AI - Tech Preview, TIBCO Flogo® Connector for Mail, and TIBCO Flogo® Connector for TIBCO FTL® are the newly supported connectors. For more information, see [Supported Flogo Connectors](#).

Version 2.26.1

Custom Headers in InvokeRest Activity

You can now add custom headers manually in the InvokeRest activity, even when it is configured with an API specification. This provides consistent header management similar to the REST trigger. For more information, see [InvokeRESTService](#).

Array Duplication in Mapper

The mapper now supports duplicating arrays from multiple sources, allowing you to combine items from different data sources within a single array. Additionally, you can add new items to the duplicated array. For more information, see [Array Merge and Split](#).

Support for Add Item Option in @Merge Node

Users can now add an empty array as a child node to a merge node using the Add Item option. This enhancement also enables you to perform split and merge operations on empty arrays. For more information, see [Array Merge and Split](#).

Circuit Breaker Pattern Support

This release introduces support for the circuit breaker pattern. This prevents cascading failures in distributed systems, improving the stability and fault tolerance of applications. For more information, see [Using the Circuit Breaker in an Activity](#).

Flogo REST Basic Authentication Support

Flogo now supports Basic Authentication for REST triggers. You can configure basic authentication credentials directly within the REST trigger, enabling secure access for incoming webhooks and resolving issues where authorization headers were previously ignored. For more information, see [REST Trigger- ReceiveHTTPMessage](#).

TIBCO Flogo® Connector for TIBCO Enterprise Message Service™

JNDI Naming URLs: TIBCO Flogo® Connector for TIBCO Enterprise Message Service™ now supports using Java Naming and Directory Interface (JNDI) naming URLs when configuring TIBCO EMS connection factories. For more information, see the "EMS Connection Details" topic in *TIBCO Flogo® Connectors User Guide*.

TIBCO Flogo® Connector for Model Context Protocol (MCP)

Support for Elicitation, Sampling, and Logging Activities: TIBCO Flogo® Connector for Model Context Protocol (MCP) now supports Elicitation, Sampling, and Logging Activities. For more information, see the "TIBCO Flogo® Connector for Model Context Protocol" topic in *TIBCO Flogo® Connectors User Guide*.

TIBCO Flogo® Connector for Apache Kafka

KAFKA Connection: Schema Registry Vendor: A new field, **Schema Registry Vendor**, is available on the Kafka Connection. This field allows you to specify a schema registry vendor.

- When you select **None** as the Schema Registry Vendor, messages are produced and

consumed as Avro payloads. This option provides backward compatibility.

- When you select a specific Schema Registry Vendor, the payload follows the vendor-specific wire format that the registry defines.

Schema Registry: One-Way SSL Authentication: You can now use one-way SSL authentication for the Schema Registry. This provides an additional layer of security for your Kafka connections.

Version 2.26.0

Activation

From TIBCO Flogo® 2.26.0, running Flogo apps requires activation via a license to start. Generate a license to activate this product within TIBCO® Software Downloads site at <https://www.tibco.com/downloads>. Only customers with an active entitlement to this release can generate a license. To learn how to configure this product for activation, visit <https://docs.tibco.com/products/tibco-activation-service> and the documentation for this release. For frequently asked questions on TIBCO® Activation, see [FAQs](#). For more information, see [Activation](#).

Support for App Build Debug Logs in Visual Studio Code Extension

You can now create debug logs when building Flogo applications within the Visual Studio Code extension. This feature provides detailed build information, including Go build output and checks for go proxy and speed. For more information, see [Optimizing and Debugging the Flogo App Executable](#).

Support for Build Configuration File

Flogo now supports a build configuration file to optimize the creation of Flogo binaries. This enhancement ensures that your application builds include only necessary dependencies, significantly reducing both download size and build time. For more information, see [Optimizing and Debugging the Flogo App Executable](#).

TIBCO Flogo Design Assistant - Tech preview

The TIBCO Flogo® Design Assistant is an interactive design companion that enables users to create and configure Flogo applications using natural language prompts. For more information, see [TIBCO Flogo® Design Assistant - Tech Preview](#).

License File Option in Flogo - App Build CLI

Flogo - App Build CLI now allows you to include license files directly within build executables, Docker images, and build.zip files. This enhancement streamlines the

distribution of your Flogo applications with the necessary licensing information. For more information, see [Building Flogo App Executable and Docker Image Using Flogo - App Build CLI](#).

Support for Linux ARM Architecture

Flogo now supports the Linux ARM architecture, providing you with the flexibility to deploy and run your Flogo applications on compatible ARM-based systems. For more information, see [Building Flogo App Executable and Docker Image Using Flogo - App Build CLI](#).

Support for \$ref Keyword in JSON Schemas

You can now use the \$ref keyword in JSON schemas to reference definitions. The Mapper correctly resolves and displays these referenced structures, allowing you to perform field-level mapping for inputs and outputs in activities, triggers, and subflows. This feature also supports nested or chained references and provides validation errors if a reference cannot be resolved.

Support for Batching in TIBCO Flogo® Connector for Databricks

TIBCO Flogo® Connector for Databricks now supports batch updates.

TIBCO Flogo® Connector for Model Context Protocol (MCP)

Support for JWT Token Authentication: You can now configure authentication using JWT (JSON Web Token). The connector also provides access to JWT scopes and the token's expiry time as input in your application flow.

Support for Blob Resources: The connector now supports Blob resources, allowing for transmission of non-textual data such as images, PDFs, or compiled binaries. Upgraded SDK: The connector has been updated to use MCP SDK 1.0.0.

Changes in Functionality

The following change has been made in this release of TIBCO Flogo®, TIBCO Flogo® Extension for Visual Studio Code, and Flogo Connectors.

Default Number of Workers

Previously, the default number of workers was set to 5. Now, the default number of workers has increased to 25 to support higher capacity for applications.

TIBCO Flogo® Connector for Model Context Protocol (MCP)

Connection Reference Format Change for MCP Servers in Agentic AI Components (since 2.26.4)

Starting with Flogo 2.26.4, connection references for List of MCP servers in Agentic AI components use a `conn://` prefix internally (for example, `conn://b2c3d4e5-f6a7-8901-bcde-f12345678901`) to support forward compatibility.

Impact: Flogo apps created prior to version 2.26.4 stored MCP server connection references as plain identifiers without the `conn://` prefix. When these apps are opened in Flogo 2.26.4 or later, the **List of MCP Servers** field appears empty even though the connection definitions exist in the app.

This change affects the following Agentic AI components.

Component	Affected Field
Agent Trigger	List of MCP Servers
Agent Activity	List of MCP Servers
LLM Client Activity	List of MCP Servers

Action required: After opening a pre-2.26.4 app, re-select the MCP server connections from the dropdown menu in each affected component.

Procedure

1. Open the **Flogo** app in the IDE.
2. For each affected component (Agent Trigger, Agent Activity, or LLM Client Activity), open its settings.
3. In the **List of MCP Servers** field, re-select the desired MCP server connections from the dropdown menu.
4. Save the app.

Deprecated Features

Deprecation Notice: macOS Installer for TIBCO Flogo® Extension for Visual Studio Code

The installer for the TIBCO Flogo® Extension for Visual Studio Code on macOS (Darwin) is planned to be deprecated starting with the TIBCO Flogo® 3.x release. On macOS, you can continue to use the TIBCO Flogo® Extension for Visual Studio Code Dev Containers, which is the best practice going forward. For more information, see [Using the Extension with Visual Studio Code Dev Containers](#).

Removed Features

No features have been removed this release of TIBCO Flogo®, TIBCO Flogo® Extension for Visual Studio Code, and Flogo Connectors.

Migration and Compatibility

The following information provides migration procedures and a compatibility matrix for this release of TIBCO Flogo®, TIBCO Flogo® Extension for Visual Studio Code, and Flogo Connectors.

Custom Flogo extensions built using APIs from the github.com/TIBCOSoftware/flogo-lib repository are not compatible with TIBCO Flogo® Extension for Visual Studio Code and Flogo® capability on TIBCO® Control Plane. To ensure compatibility, custom extension source code must be migrated to use APIs from the github.com/project-flogo/core repository (<https://github.com/project-flogo/core>).

In case of any issues, reach out to support@tibco.com.

Closed Issues

The following issues have been fixed in this release of TIBCO Flogo®, TIBCO Flogo® Extension for Visual Studio Code, and Flogo Connectors.

TIBCO Flogo® and TIBCO Flogo® Extension for Visual Studio Code

Key	Summary
FLOGO-18471	Flogo mocker generates an ACTIVITY-ERROR instead of an ENGINE-ERROR when configured to return an ENGINE-ERROR.
FLOGO-16325	Code and activityType are missing in error object for ENGINE-ERROR.

Known Issues

The following issues exist in this release of TIBCO Flogo®, TIBCO Flogo® Extension for Visual Studio Code, and Flogo Connectors.

TIBCO Flogo

Key	Summary and Workaround
FLOGO-18399	Summary: When adding request headers in an OData Modify activity, they are not immediately reflected in the Input tab's headers section. Workaround: Navigate to a different tab and then return to the Input tab to see the new changes.
FLOGO-18117	Summary: When using the <code>true()</code> or <code>false()</code> boolean functions, design-time validation errors are not displayed, and the application fails at runtime. Workaround: None.
FLOGO-18077	Summary: Apps created using Flogo Design Assistant set a default <code>conn://</code> value on hidden connection fields, causing runtime failure. Workaround: Modify the app to trigger contribution logic (for example, update the app version), which resets the hidden connection field value.
FLOGO-18036	Summary: When you run the <code>build-tp-deployment</code> command using a default context, the <code>-b (--build-name)</code> flag is ignored, and a warning message <code>The Extension version does not support Build name attribute. Build name will be ignored.</code> appears. Workaround: Pass the context explicitly in the build command using <code>-c</code> flag.
FLOGO-17920	Summary: When you create an application build ZIP file using Flogo App

Key	Summary and Workaround
	Build CLI with the command <code>build-tp-deployment</code> and import this file in a Data Plane in TIBCO Control Plane, the included connectors in the app are not displayed in the builds table. Workaround: None.
FLOGO-17623	Summary: When you add request headers in an OData Modify activity, they are not immediately reflected in the Input tab's headers section. Workaround: Navigate to a different tab and then return to the Input tab to see the new changes.
FLOGO-17614	Summary: When an MCP Server connection used by a Flogo application is deleted, the application fails at runtime. Workaround: None.
FLOGO-17574	Summary: Prompt-driven mapping generates an incorrect expression when mapping one activity output to another activity field. Workaround: None.
FLOGO-17406	Summary: For new primitive array nodes within a Split & Merge wrapper, the Add Item option is initially hidden in the kebab menu. Workaround: In the right-hand configuration pane, click Select under Configure with items. Manually add the first item.
FLOGO-17405	Summary: When you add a new node to a Split & Merge wrapper on a primitive array, the new node displays an incorrect or generic icon. Workaround: Switch tabs and then return to the input tab to update the icon to the correct type-specific primitive array icon.
FLOGO-17395	Summary: On Linux, binary does not build using Local runtime if Go is installed from Install Prerequisites for Flogo Connectors. Workaround: Before building binary using Local runtime on Linux, install or update Go manually.

Key	Summary and Workaround
FLOGO-17385	Summary: If the flow execution starts directly in error handler, then the execution state is not rendered in flow execution instance. Workaround: None.
FLOGO-17345	Summary: Execution path is not highlighted in nested subflow execution in play mode intermittently. Workaround: Review the logs and the test result file for all activity links and execution paths.
FLOGO-17066	Summary: When changing an activity type in Flogo Design Assistant - Tech Preview, the activity name in the UI is not updated. Workaround: None.
FLOGO-17065	Summary: App does not activate if the Tibco Activation service URL does not have a fingerprint ID. Workaround: Fingerprint ID should be appended with the Tibco Activation service URL when using TAS for activation.
FLOGO-17051	Summary: When duplicating inputs from a dereferenced \$ref schema, only root properties are copied, not all inner properties. Workaround: None.
FLOGO-16960	Summary: When the app is running, no warning message is displayed if connectivity to Tibco Activation Server is broken. Workaround: None.
FLOGO-16785	Summary: Duplicating an Array item, using Add Items, which has an active Conditional block, causes the UI to freeze temporarily, and the duplicate node might not appear. Workaround: Navigate away from the activity, then reopen the original activity to resolve the frozen UI.
FLOGO-16784	Summary: When duplicating a Conditional block set on an Array block,

Key	Summary and Workaround
	variables defined inside the Array are not assigned unique names in the duplicate block. Workaround: Manually rename the variable in the duplicated Array block. Switch tabs to refresh the Available Data view, then update the variable name in the mapping.
FLOGO-16750	Summary: Validation errors occur in Mock Outputs and Assert on Outputs due to mismatches between the schema and data for arrays. Workaround: None.
FLOGO-16721	Summary: When a schema contains multiple \$ref errors in Visual Studio Code, only the first error appears in the error message panel. The system does not highlight or log subsequent \$ref errors, making it difficult to debug. Workaround: None.
FLOGO-16597	Summary: Internal variables without assigned values do not save in the app JSON and are only visible in the UI. Workaround: None.
FLOGO-16521	Summary: Newly added properties in the Error object generate a validation error in unit tests. Workaround: None.
FLOGO-16516	Summary: Mappings are not getting auto updated in an error object if the activity name is changed. Workaround: After changing the activity name, update the mappings in the error object manually.
FLOGO-16417	Summary: Inactive Flogo App Execution tabs are not closed when the app is restarted. Workaround: None. Close the Flogo App Execution tabs manually.

Key	Summary and Workaround
FLOGO-16216	Summary: Flogo App Executions do not get deleted when the app is removed from the workspace, resulting in the accumulation of executions on the disk. Workaround: Delete Flogo app executions from the local temp directory under the <code>vscode-debug</code> folder to clear them from Visual Studio Code.
FLOGO-16172	Summary: A design-time validation error occurs when mapping an array variable of a primitive type to input fields, although the application functions correctly at runtime. Workaround: Use the <code>coerce.toArray()</code> function on the source variable instead of direct mapping (for example, <code>coerce.toArray(\$variable [varStrArr])</code>).
FLOGO-16132	Summary: When adding variables within an array whose items are configured using the Add Item option, the activity incorrectly places these variables inside the first array item. This limits the scope of these variables and prevents proper usage across all items. Workaround: None.
FLOGO-16127	Summary: Variable name validation is not implemented. The use of special characters, such as #, @, -, \$, and so on, generates an error when the variable name is referenced in Input activity. Workaround: None.
FLOGO-16124	Summary: A runtime error occurs when utilizing internal variables in triggers. Workaround: None. Avoid internal variables in triggers.
FLOGO-16108	Summary: The activity fails to provide design-time validation for type mismatches when assigning incompatible values to Object and Array internal variables. Workaround: None.
FLOGO-16105	Summary: When mapped from upstream data, connection lines are not

Key	Summary and Workaround
	visible for Object or Array variables. Workaround: None.
FLOGO-16089	Summary: On macOS, the MySQL Connector driver option is missing in the "Install Prerequisites for Flogo Connectors" section, preventing users from installing the necessary driver required for MySQL databases. Workaround: None
FLOGO-16070	Summary: When importing connections, if a connection has the same name but a different type, it overrides the existing connection instead of creating a new one. Workaround: Use unique connection names or ensure that the connection type is the same before importing.
FLOGO-15908	Summary: When the parent array is created using the Add Item option and the nested array is configured with the Iterate from Source option, Flogo Mapper fails to expose the loop variable. Workaround: None.
FLOGO-15898	Summary: When setting Environment Variables through the Configure and Run Action option, the values appear with escaped quotes at the beginning and end. Workaround: Set the Environment Variables directly in the terminal instead of using the Configure and Run Action option.
FLOGO-15872	Summary: The toggle button remains ON when there are no connections in the existing app during the import process. Workaround: None.
FLOGO-15781	Summary: When you paste an activity with an attached app spec, the app spec is not copied even if the Spec Binding toggle is enabled. Workaround: None.

Key	Summary and Workaround
FLOGO-15773	Summary: The Timeout field in Wait for Notification activity does not show the default value immediately after the activity is added to the flow. Workaround: Refresh to see the default value.
FLOGO-15771	Summary: An activity with an app schema attached is copied when the Spec Binding toggle is enabled, but the schema is not present in the App Schemas tab. For app property, even when this toggle is enabled, the properties are not getting created in the App Properties tab. Workaround: None.
FLOGO-15753	Summary: Design-time errors do not display when there are spaces in the connection name, leading to connection failures when scaling apps. Workaround: Use underscores instead of spaces.
FLOGO-15704	Summary: Schema parameters with type or value null or undefined error is observed when the API spec has an object having a property with type in array. This error is not resolved even after changing the type in the API spec and configuring the trigger again. Workaround: Edit the app.flogo file and clear the fe_metadata property on the flow, and then synchronize the Rest trigger.
FLOGO-15585	Summary: Mocking a subflow in unit test play mode does not allow users to navigate into the called flow, which remains unexecuted. Workaround: None
FLOGO-15554	Summary: When the data type of an input schema field in a Mapper activity is changed from Array to Object, the input mapping UI does not refresh and continues to display options suitable for an Array type. Workaround: Clear the existing mapping after changing the schema and save the changes.
FLOGO-15535	Summary: The fe_metadata section in the .flogotest JSON file does not revalidate against the updated schema, as the removed property still exists at the parent level.

Key	Summary and Workaround
	Workaround: Manually delete the removed property from the .flogotest JSON file.
FLOGO-15534	Summary: Changes made to the schema do not auto-reflect in the .flogo app JSON output fields of activity. Workaround: After updating the app schema, open the flow and edit the activities.
FLOGO-15518	Summary: If you do not select the primary checkbox of the schema, it does not show up in the preview. However, it is visible in the app after import. Workaround: None
FLOGO-15502	Summary: Modifying the Flogo app does not stop the execution of the play feature in Unit Test mode. Workaround: Manually stop the test case execution in play mode.
FLOGO-15498	Summary: Any renamed trigger is not displayed on the flow list page after importing the app. Workaround: Open the flow and then navigate to the flow list page to see the renamed trigger.
FLOGO-15467	Summary: When attempting to set an application name that starts with digits or consists solely of digits, an error occurs. Workaround: Start the app name with letters followed by numbers.
FLOGO-15310	Summary: You cannot create a new connection during import, and the changes in the connection of an imported app are not reflected. Workaround: Update the existing connection with the required changes that you want to import, or create a new connection and select the activities and triggers.
FLOGO-15307	Summary: The default blank flow remains in the app when flows are implemented using a Spec.

Key	Summary and Workaround
	Workaround: After implementing flows from a Spec, delete the default flow if it is not required.
FLOGO-15049	Summary: The error icon remains present on the input tab after saving changes related to the Salesforce activity conditions. Workaround: Validate the activity to remove the error icon.
FLOGO-14954	Summary: When you use the ProtobufToJSON activity, the following error message is displayed: Unable to get message descriptor from registry. Workaround: None.
FLOGO-14947	Summary: When an attached spec in a trigger or activity is deleted from the SPECS tab, no error is displayed. Workaround: None. Update the trigger or activity settings manually to use another spec.
FLOGO-14882	Summary: Changes are not reflected in the InvokeRestService activity configuration when the attached app spec is updated. Workaround: Reset the Use app level spec toggle and re-select the same spec. The changes are updated in the activity configuration.
FLOGO-14773	Summary: On the Import specs dialog, specs from the TIBCO Developer Hub display version 0.0.0. Workaround: None. Once a spec is imported, it shows the OpenAPI version of the spec.
FLOGO-14699	Summary: On adding ReplyToTrigger activity in the error handler flow for the first time, the mappings of REST trigger are not reflected. Workaround: Delete the ReplyToTrigger activity and add it again.
FLOGO-14683	Summary: Mapping, where an app property is already mapped, is not updated if the app property is moved from the root level to a group or from a group to the root level.

Key	Summary and Workaround
	Workaround: Update the app property mapping manually.
FLOGO-14602	Summary: Existing Oracle Database connection must be reconnected to server with upgrade of TIBCO Flogo® Extension for Visual Studio Code from version 1.1.1 to 1.2.0, otherwise app fails at runtime. Workaround: After upgrading TIBCO Flogo® Extension for Visual Studio Code, re-establish the Oracle Database connection and then Build and Run the application.
FLOGO-14340	Summary: On collapsing and then re-expanding the activity or trigger configuration, the number of mappings is removed from the right-most configuration panel. The data mappings remain the same. Workaround: Close and reopen the activity or trigger configuration.
FLOGO-13705	Summary: You cannot select oneOf for anyOf schema in the Start a Subflow activity. Workaround: Use schemas with oneOf or anyOf keywords in the main flow.
FLOGO-13404	Summary: Selected oneof schema property is not present in the Trigger Output of the Rest trigger and activities Input after import if the app schema is used. Workaround: Enter the schema directly instead of attaching the app schema when using a schema having a OneOf keyword in the Input settings.
FLOGO-13300	Summary: In TIBCO Flogo® Extension for Visual Studio Code, when you try to connect to an Oracle Database using the Install Prerequisite option, the test connection fails with the message "libsora.so.21.1 file not found" on Ubuntu 24. Workaround: Remove unused or unnecessary Oracle drivers and use the pre-install script to reinstall them.
FLOGO-13284	Summary: If test cases are exported from TIBCO Cloud Integration and run without test suites, the test run fails.

Key	Summary and Workaround
	Workaround: Create a test suite, add the test cases to the test suite, and then run the test.
FLOGO-13093	Summary: After discarding changes in the activity configuration, the Open Subflow icon is still present in the activity tile. Workaround: Navigate out of and then back into the same flow.
FLOGO-13082	Summary: In the activity configuration, when you click the Open Subflow icon, the UI is disabled. Workaround: Save the changes and then click the Open Subflow icon.
FLOGO-13066	Summary: Getting error as Unexpected error while fetching task results in flow tester when you click Start a subflow activity. Workaround: None.
FLOGO-13013	Summary: On selecting the oneOf schema for the enum data is not getting cleared. Workaround: Clear the enum datatype before selecting the other oneOf schema.
FLOGO-12447	Summary: Activities are run but not highlighted in a flow that includes a subflow with detached invocation set to True. Workaround: None.
FLOGO-12345	Summary: The JSON.SET mapper function generates an error for a null value. Workaround: None.
FLOGO-12340	Summary: After saving mapping changes in any tab of an activity configuration window, you cannot switch to another tab without saving even if no new changes are made. Workaround: Save the changes again.
FLOGO-11904	Summary: After a request is complete for an HTTP trigger app with proxy mode, an error is displayed in the logs.

Key	Summary and Workaround
	Workaround: You can ignore the error as the flow execution is complete. You can also change the processing mode to Data and then back to proxy to remove the error.
FLOGO-11902	Summary: The Testing Sandbox environment for Unit Testing fails to start in certain scenarios. Due to this the Unit tests for the Flogo app fails to execute. Workaround: Restart the test again after sometime.
FLOGO-11650	Summary: When dealing with an OSS activity in your Flogo app, you can update the trigger configurations with the Coerce with Schema option. However, when you pick a configured schema, and discard it to close the triggered configuration screen, the UI gets stuck. Workaround: You need to refresh the page or click the apps tab to start again.
FLOGO-11262	Summary: If we try to open the mapper activity, which has an array with large records mapped with an array type, then the browser becomes unresponsive and validation goes into an Infinite loop. Workaround: Instead of using an array with large records directly into the Mapper activity input, map it with the output of some other activity.
FLOGO-11239	Summary: Let us say there is a Flogo app with a large number of flows and activities. Enable the execution history and then, on completion of the execution, go back to the Execution History page. After this, open an execution instance and when we click View Details, we do not see the list of activities that have been executed. Instead, we see a message that says that the Execution History is not enabled for the organization. Workaround: None.
FLOGO-11122	Summary: If you are a Read-Only User, the Navigate to subflow icon is not visible on StartaSubflow activity tile. Workaround: None.
FLOGO-11119	Summary: For Read-Only User and User roles, Open Subflow is not present inside the StartaSubflow activity.

Key	Summary and Workaround
	Workaround: Click the Input or Output tab and click the Settings tab. The Navigate to subflow becomes visible.
FLOGO-11100	Summary: References are not updated for the General category activities and triggers for the existing apps, which are exported after the upgrade from PAPI. Workaround: None
FLOGO-11072	Summary: When mapping unmapped arrays, the Filter by value gets populated in the Configure with Value input mapper after clearing the source mapping and switching to Configure with Value option. Workaround: Select a different non-array node and select the array node again.
FLOGO-10958	Summary: The enum value dropdown is unavailable for the array child elements. Workaround: None.
FLOGO-10888	Summary: Unpushed apps are not copied from tibcli. Workaround: None.
FLOGO-10886	Summary: During mapping of arrays, on double-clicking the source array, the mapping is added in the Filter by field. Workaround: Instead of double-clicking the source node, drag the source node to update the source.
FLOGO-10839	Summary: During mapping of arrays, we are not able to select the Configure with source option after clearing the mappings. Workaround: Close the activity panel. Then, open it again and try to map the node.
FLOGO-10837	Summary: Activities are not aligned linearly when the app is pushed from PAPI or tibcli. Workaround: None.
FLOGO-10834	Summary: References are not auto-updated if a group name is updated in

Key	Summary and Workaround
	the application properties. Workaround: References need to be manually updated after renaming any group of app properties.
FLOGO-10802	Summary: The field with space is not working in the filter expression of the for-each function. Workaround: You must insert an additional identifier ["<loopName>"] in the \$loop expression. For example: <pre data-bbox="446 667 1409 821">array.forEach(\$activity[Mapper].output.data, "data",\$loop{color:#de350b}["data"]{color}["FirstName"]=="Jones")</pre>
FLOGO-10732	Summary: In cases where there is only one successful branch or a branch with one true condition in the flow tester, it results in all the branches getting highlighted. This happens irrespective of whether the other branches include false conditions or error. Workaround: None.
FLOGO-10707	Summary: When trying to execute the branch merging process, Run test from this activity in flow tester does not work. The flow gets blocked due to this. Workaround: None
FLOGO-10628	Summary: When we modify the API specifications, the Refresh icon must pop-up after opening the Trigger Setting. However, there is some delay for the Refresh icon to be visible. Workaround: None.
FLOGO-10620	Summary: The branching mapping window closes directly after clicking the Save. There is no close option. Workaround: None.
FLOGO-10582	Summary: SF Delete activity with loop does not open upon clicking in the flow tester run. Workaround: None.

Key	Summary and Workaround
FLOGO-10576	Summary: The Refresh icon vanishes while performing certain actions. It happens when we discard the changes, close the pop-up on the list flow page and trigger configuration in the flow details page. Workaround: Refresh the page either by reloading or navigating from flow list to flow details.
FLOGO-10572	Summary: If an API specification has some cyclic redundancy, a proper error is not displayed. Workaround: None.
FLOGO-10565	Summary: When we upload an API specification, which has constructs that are not supported in Flogo, like Option method and Common Parameters, a warning is not displayed. Workaround: None.
FLOGO-10529	Summary: When the API specification is renamed, the new name is not reflected when we click the Refresh icon. Instead, it shows the previously used name. Workaround: Manually export the API specification from the TIBCO Cloud™ Integration - API Modeler and re-import it in the Trigger Setting.
FLOGO-10523	Summary: If we make a copy of an app created in TCAM, then we are not able to see its entry in the TIBCO Cloud™ Integration - API Modeler create Flogo app section. Workaround: None.
FLOGO-10499	Summary: When we create apps using the TIBCO Cloud™ Integration - API Modeler platform or the API specification, it displays the error - “xml has type or value wrong”. Workaround: None.
FLOGO-10456	Summary: If an activity is added and not connected to any branch or activity, and later exported and imported back, then this added activity is not seen. Workaround: None.
FLOGO-10356	Summary: The Close icon disappears when there are many activities open

Key	Summary and Workaround
	and we expand one of them. Workaround: Zoom out the panel to find the Close icon.
FLOGO-10300	Summary: When there is a large flow and you want to connect many activities together, then drawing the connection lines must auto scroll the page. Workaround: Zoom out the flow canvas by clicking the zoom in and out button and then connect the activities.
FLOGO-10047	Summary: If the mappings are not correct in the Unit Testing mock feature for an Activity, the Activity is not mocked, and does not fail at run time. Workaround: Correct the mappings in the Mock data.
FLOGO-9905	Summary: When we search for any property, we see the appropriate list of properties as per its name, along with the ones that have no value. Workaround: None.
FLOGO-9586	Summary: On importing a .flogotest file with matching unit test data, a copy of existing test cases and test suites is created with new names. Workaround: Delete the newly added copy of test cases and test suites manually.
FLOGO-9583	Summary: In an activity configuration, when mappings are cleared in the input mapper using "Clear Mappings", the mappings are cleared but the items are still visible. If you close the Activity configuration and return to the input mapper, the items are no longer visible. Workaround: None
FLOGO-9556	Summary: When using the Flow Tester, if a null value is passed in the schema at the object level, a validation error is returned and the test does not run. Workaround: None
FLOGO-9394	Summary: After clearing a mapping and adding an item, the item is not

Key	Summary and Workaround
	added the first time. Workaround: Click Add item multiple times.
FLOGO-9373	Summary: Unit test execution fails if a Flogo app is using a user supplement. Workaround: None.
FLOGO-9370	Summary: A Mapper Activity returns an empty array as output, on mapping multiple items and providing a single array element as input. Workaround: None
FLOGO-9159	Summary: If a REST trigger has an app schema and it is attached to the Request or Response schema and later reconfigured using API spec, a “Bad gateway” error is observed. Workaround: Detach the app schema from the Request or Response schema before configuring the trigger using API spec.
FLOGO-9142	Summary: If an Activity is executed in a loop, on the Execution History tab, the Completed count is more than the Started count. Workaround: None
FLOGO-8988	Summary: Error propagated from the trigger does not trigger the error handler flow. Workaround: None
FLOGO-8933	Summary: If you rename a connection and then select the Create new connection option while importing an app, connection names are not created correctly. Workaround: None
FLOGO-8848	Summary: For a Kafka app with AVRO schema, a validation error symbol is displayed in the consumer trigger. Workaround: None

Key	Summary and Workaround
FLOGO-8778	Summary: Importing an app in an environment where the Execute JavaScript Activity does not exist, an error indicating that the Activity is missing in the error Handler flow is returned. Workaround: None.
FLOG-8740	Summary: In the cron expression builder, the Save and Discard buttons are disabled when you try to change an existing cron expression to default by using one of the following methods: • Switching to cron builder and accepting the pop-up • Switching from timer to cron Workaround: Click a cron expression field and then click outside the cron expression builder. The Save and Discard buttons are enabled.
FLOGO-8535	Summary: When the Coerce with schema option is used, data of type ANY is not converted to OBJECT type on save or sync. Workaround: Switch between the tabs, and the data is converted.
FLOGO-8476	Summary: If a mapping variable has a “-” in the name, the flow fails to run at runtime. Workaround: None
FLOGO-8413	Summary: After adding multiple If/Else conditions in a mapper, the new conditions are not visible on the UI immediately and there is a minor delay before they are available for viewing. Workaround: None
FLOGO-8479	Summary: If you rerun an Activity using Rerun flow from this Activity on the Executions page, the Completed count displayed on the Metrics page > Flow tab > Activity Execution (count) does not include the rerun of the Activity from which the rerun is performed. Workaround: None
FLOGO-8432	Summary: Mapping child elements using <code>\$loop</code> in an <code>array.forEach</code>

Key	Summary and Workaround
	function results in a mapper validation error. No error is reported during runtime. Workaround: None
FLOGO-8350	Summary: When a gRPC Activity is used in an app and the app is started, the following warning is displayed: <pre>WARNING: Package "github.com/golang/protobuf/protoc-gen-go/generator" is deprecated.WARNING: Package "github.com/golang/protobuf/protoc-gen-go/generator" is deprecated. A future release of golang/protobuf deletes this package, which has long been excluded from the compatibility promise.</pre> Workaround: Ignore the warning.
FLOGO-8349	Summary: If an activity has an empty or incorrect input, a validation error is indicated by a red error icon. Even when the erroneous condition is removed, the error icon continues to be displayed. Workaround: Click Validate.
FLOGO-8300	Summary: When a condition is added to the data mapper, the mapper does not automatically open the input mapping field. Workaround: Scroll down to view the newly added condition and then manually open the input field.
FLOGO-8287	Summary: If a root or parent array is not mapped, the Add condition menu is wrongly displayed in the mappings of the array children, and the mapper stops responding. Workaround: Close and reopen the Activity configuration. Map the root or parent array.
FLOGO-8258	Summary: The Protobuf2JSON activity shows a design-time error when you refresh the browser. No error is reported during runtime. Workaround: Click Validate.

Key	Summary and Workaround
FLOGO-7927	Summary: When you specify a filter as the third argument in the <code>array.forEach()</code> function, <code>\$loop</code> is not evaluated automatically when you drag-and-drop a child element. Instead, the whole path is populated. Workaround: Manually edit it and replace the parent path with the <code>\$loop</code> expression.
FLOGO-7868	Summary: [Microsoft Azure] When building an app binary, messages of the build process are not shown on the UI immediately. They are shown only after the build process is completed. Workaround: None
FLOGO-7665	Summary: Instrumentation metrics data is not available for an app and tibagent deployed on AWS Fargate. Workaround: None
FLOGO-7657	Summary: When adding a description for an app, the "This field is required" message is displayed and the cursor moves in front of the message when you start typing the description. The message does not go away until you go inside the flow. Back is also disabled. Workaround: None
FLOGO-7436	Summary: Runtime validation is not enabled for Required Form Params. Workaround: None
FLOGO-7421	Summary: Runtime validation error is observed for <code>filecontent</code> type data when Output Validation is set to <code>true</code> in the REST trigger. Workaround: Do not enable Output Validation when the Request type is <code>multipart/form-data</code> in the REST trigger.
FLOGO-7269	Summary: On the flow list page, a "missing extension" validation error is shown for each flow even after installing the missing extension. Workaround: Validate each flow to remove the validation error for that flow.

Key	Summary and Workaround
FLOGO-6951	Summary: Password type app properties do not support encrypted values during design time. Workaround: None
FLOGO-6933	Summary: When the InvokeRestService Activity is configured with Open API spec, the response headers are converted to JSON Data instead of JSON Schema in the InvokeRest Output settings. Workaround: None.
FLOGO-6904	Summary: When the InvokeRESTService Activity is used with the HTTP Client Authorization Configuration connection and OAuth2 Authorization type, it fails to auto-refresh the token if the expired or invalid token response does not have the status code as 401. Workaround: Use another InvokeRESTService Activity to get the new token and use the new token in the InvokeRESTService Activity.
FLOGO-6847	Summary: If a database connector activity has a design time error, the message incorrectly disappears after clicking the Clear Table link. Workaround: None
FLOGO-6718	Summary: The order of elements in an object in a JSON file is not maintained when the file is processed. Workaround: None.
FLOGO-6586	Summary: The value of the BIGINT data type is converted to an incorrect value. Workaround: If possible, use a STRING data type instead.
FLOGO-6552	Summary: The resource path of a previous specification is shown in the Resource path list even after deleting the specification file and uploading a new specification file. Workaround: Select the resource path from the Resource path list even if it shows paths of previous specifications. Even though the specification

Key	Summary and Workaround
	displayed is incorrect, the new path is loaded.
FLOGO-6542	Summary: If you upload an OpenAPI Specification (OAS) file in the InvokeREST Activity and later upload an updated version of the same OAS, the changes to the schema are not reflected in the associated parameters and request/response schemas. Workaround: Delete the original specification and upload the new OAS again.
FLOGO-5802	Summary: When you close and reopen an application, input mappings containing errors, such as missing index values, convert to string values. This prevents validation from identifying the incorrect mapping. Workaround: Manually remove the double quotes.
FLOGO-5400	Summary: While running an app in a flow tester, if you provide a JSON schema with a nested array, it returns an error at design time. Workaround: None
FLOGO-5267	Summary: The ConfigureHTTPResponse Activity is not updated correctly when reply settings are changed. Workaround: Trigger a save operation by re-doing or undoing some of the mapper mappings on the ConfigureHTTPResponse Activity.
FLOGO-4936	Summary: Boolean data type and null data type are not supported in TIBCO Cloud Messaging. Workaround: None
FLOGO-4717	Summary: When a Swagger specification file of size 2.5 MB or more is used for creating an app or uploaded using the REST trigger configuration, the app is not deployed to TIBCO Cloud. Workaround: Use a Swagger specification file of a smaller size.
FLOGO-4716	Summary: If required elements of a request schema are not provided, the runtime provides a response but the tester returns a validation error.

Key	Summary and Workaround
	Workaround: None
FLOGO-4661	Summary: Single quotes are not supported in mapper variables. Workaround: None
FLOGO-4659	Summary: If you use a field name that contains special characters, the <code>array.foreach</code> mapping fails with the following error: <pre>eval expression failed to resolve Loop: 'field name', ensure that Loop is configured in the application</pre> Workaround: Add a scope name before the field name. For example, manually change <code>\$loop["fieldName"]</code> to <code>\$loop["ScopeName"]</code> <code>["fieldName"]</code>.
FLOGO-4653	Summary: An unsupported data type in the request or response schema is not converted to a supported one. Workaround: In the API Spec, change the type to the supported data type. For example, change <code>Float</code> and <code>long</code> data type to <code>Integer</code>.
FLOGO-4628	Summary: If a Swagger specification file is modified and the file is saved with a different name, the changes are not reflected in the app even if you click Sync Schema. Workaround: None
FLOGO-4387	Summary: An Activity generates a mapper error if the mapped object does not exist, as the <code>FLOGO_MAPPING_SKIP_MISSING</code> environment variable cannot be set in the flow tester. Workaround: None
FLOGO-4363	Summary: When an app with different trigger and handler settings is imported, trigger and handler settings are not replaced after selective import. Workaround: None

Key	Summary and Workaround
FLOGO-4188	Summary: For OpenTracing, even after terminating an app, recurring warnings are displayed in JaegerUI. Workaround: None
FLOGO-4164	Summary: While starting a gRPC app binary that has a gRPC activity using the same proto file, the following error message is displayed: <pre>Duplicate enum registered</pre> Workaround: Change the package name to a different one to make sure gRPC activity use the different package name in the proto file.
FLOGO-4127	Summary: App properties of type INTEGER are not supported. Workaround: None
FLOGO-3906	Summary: After mapping array root nodes, when a child node mapping is updated, only a mapped child node is returned at run time. Workaround: None
FLOGO-3393	Summary: If a Kafka producer produces a JSON string, the Kafka consumer does not receive any data. Workaround: None
FLOGO-2888	Summary: You cannot upload Swagger specification definitions, which have a cyclic dependency. Workaround: None
FLOGO-2886	Summary: Depending on your machine configuration and browser configuration, you might not be able to upload a large Swagger API definition JSON file or the browser might become unresponsive. The following error message is displayed on the Network tab and the file is not uploaded:

Key	Summary and Workaround
	Request entity too large Workaround: None
FLOGO-2861	Summary: When uploading a custom schema for GraphQL, if the custom schema has a cyclic dependency, the following error is returned and the upload fails: Maximum call stack size exceeded for circular reference Workaround: None
FLOGO-1757	Summary: JSON schema with cyclic references is not supported. Workaround: Remove the cyclic references from the schema.
FLOGO-1684	Summary: When accessing the UI, a "502 Bad Gateway" error is returned if the machine is configured with a static IP address. Workaround: Configure the machine IP address as dynamic.
FLOGO-814	Summary: In the flow error handler, <code>\$error.data</code> and <code>\$error.code</code> are not supported in the mapper. Workaround: If you import an open source Project Flogo™ app, manually delete <code>\$error.data</code> and <code>\$error.code</code> from the mappings.
FLOGO-358	Summary: On macOS, if you run the <code>run-studio.sh</code> installer from a directory that is not shared with the Docker container, the installation fails and the following error is displayed: Mounts denied Workaround: Configure the path to the <code>run-studio.sh</code> file in Docker > Preferences > File Sharing before running the <code>run-studio.sh</code> command.
WISNFK-219	Summary: (macOS) An incorrect SQL query does not display any error.

Key	Summary and Workaround
	Workaround: Insert a valid SQL query that provides the metadata.

Database Services

Key	Summary and Workaround
WIDBSV-451	Summary: In a select query with a where clause, if the parameter name is the same as the column name, the return type is incorrect. Workaround: None

Flogo Connector for Agentic AI - Tech Preview

Key	Summary
FGAI-70	Summary: When using MCP connections over HTTP with authentication enabled, tools do not load until the application is reopened. Workaround: Reopen the Flogo application.
FLOGO-17579	Summary: When TIBCO Control Plane MCP server is used by TIBCO Flogo® Connector for Agentic AI - Tech Preview, the application fails at runtime. Workaround: None.

Flogo Connector for Amazon Kinesis

Key	Summary
FGAZKS-54	Summary: Tags object is not supported for CreateDeliveryStream field of Firehose Stream type. Workaround: None.

Flogo Connector for Apache Avro

Key	Summary and Workaround
WIAVRO-65	Summary: For Avro activities, when app-level schemas are used, Avro schemas are not displayed in the list for selecting the schema. Instead, JSON schemas are displayed. Workaround: None

Flogo Connector for Apache Kafka

Key	Summary and Workaround
FGKAFKA-201	Summary: Delay observed in retry attempts on error when network is slow at client side. Workaround: None.

Flogo Connector for Apache Pulsar

Key	Summary and Workaround
FGPUL-389	Summary: When georeplication is set to <code>true</code>, batching does not work as expected. Workaround: None.

Flogo Connector for DocuSign

Key	Summary and Workaround
FGDUSN-85	Summary: When you import any TCI DocuSign existing application in Visual Studio Code and open existing connection tab to edit the connection details after entering any input in the required fields, the connection does not validate the process and it displays a <code>Login successful</code> message. Workaround: Create new DocuSign connection and use it in flow to run the application.
FGDUSN-67	Summary: When editing existing connection with DocuSign in Visual Studio Code, the application does not load the DocuSign Authentication Type and OAuth2 Token fields. Workaround: Close the application and reopen.

Flogo Connector for EMS

Key	Summary and Workaround
FGEMS-27	Summary: The SSL handshake logs are shown on the application startup unexpectedly. Workaround: None.

Flogo Connector for FTL

Key	Summary and Workaround
FGFTL-15	Summary: When the Subscriber Trigger is dragged and dropped into the flow, the Message Schema and Enable Flow Limit fields are not visible initially. Workaround: These fields become visible after the trigger is added to the flow. Users can then configure them as needed.

Flogo Connector for Google Cloud Pub/Sub

Key	Summary and Workaround
FGGCPS-42	Summary: On the Windows operating system, installing the connector and generating the binary and docker images takes a long time. Workaround: None.
FGGCPS-40	Summary: In the Message Publisher activity, an error message is displayed when you leave the Topic ID field blank on the Settings tab and override it on the Input tab. Workaround: None.

Flogo Connector for HTTP

Key	Summary and Workaround
FGHTTP-83	Summary: In Data mode, the app does not go into running state if the context path is not set. Workaround: At least, pass / in the context path for Data mode.

Key	Summary and Workaround
FGHTTP-89	Summary: In Data mode, when a request of type Multipart/form-data or application/x-www-form-urlencoded is made from the HTTP service then a null response is received. Workaround: Use processing mode as Proxy instead of Data for making such a request.

Flogo Connector for IBM MQ

Key	Summary and Workaround
FGIBMQ-142	Summary: The Subscriber in JSON format is not saved if added directly with a JSON value format. Workaround: Add the JSON schema again after adding the Subscriber trigger.
FGIBMQ-141	Summary: The Listener in JSON format is not saved if added directly with a JSON value format. Workaround: Add the JSON schema again after adding the Listener trigger.
FGIBMQ-107	Summary: Connectors activity and trigger input tab fields take time to load the values. Workaround: Wait for some time or refresh Visual Studio Code.

Flogo Connector for Mail

Key	Summary and Workaround
FGMAIL-12	Summary: When using IMAP Fetch Activity for fetching a large number of emails, sometimes the activity may time out. Workaround: Use the Retry on Error feature.

Flogo Connector for Microsoft Azure Service Bus

Key	Summary and Workaround
WIAZSB-54	Summary: If your app contains the QueueReceiver or TopicSubscriber Azure Service Bus trigger, the app crashes if an empty message is published to the Azure Service Bus queue or topic using HTTP POST. Workaround: None.
WIAZSB-49	Summary: When a message that is published to a topic or a queue in the service bus has the 'TimeToLive' broker property set, Microsoft Azure Service Bus Queue Receiver and Microsoft Azure Service Bus Topic Subscriber triggers are not able to process and display its value in the output. Workaround: None.

Flogo Connector for Microsoft SQL Server

Key	Summary and Workaround
WIMSSS-355	Summary: In case of queries combining results from multiple tables, if the tables have identical column names, then the repeated column names are renamed as columnName_<number>. Workaround: For duplicate column names use alias.
WIMSSS-327	Summary: When passing a list of values in the prepared parameter, then query does not return any values. Workaround: Pass multiple prepared parameters such as ?a1,?a2.
WIMSSS-213	Summary: If you export or import from 2.8.1 to the current version, an error is shown on the activities even after establishing a connection. Workaround: Refresh the page or click on the respective activity again.

Key	Summary and Workaround
WIMSSS-92	Summary: The OUTPUT clause in INSERT INTO is not supported. For example, the following INSERT INTO statement does not return the expected value for promotion id: <pre> INSERT INTO promotions (promotion_name, discount, start_date, expired_date) OUTPUT inserted.promotion_id VALUES ('2018 Fall Promotion', 0.15, '20181001', '20181101'); </pre> Workaround: None.

Flogo Connector for MongoDB

Key	Summary and Workaround
FGMGDB-117	Summary: Options such as update, find, and delete do not work when the auto generated '_id' is given in the input criteria. Workaround: With user given ids in the documents, MongoDB activities work. While inserting a document, specify a unique id in the input JSON.
FGMGDB-107	Summary: MongoDB activities time out in 30 seconds even if the Timeout value is set to a higher value. Workaround: None.
FGMGDB-96	Summary: On the MongoDB Connection page, the value entered in the Key Password field is not validated when using SSL.

Key	Summary and Workaround
	Workaround: None.
FGMGDB-93	Summary: MongoDB Trigger is not compatible with Cosmos DB. Workaround: None.
FGMGDB-83	Summary: The MongoDB Insert document activity generates an incorrect output on failure, if the ?Insert Many Documents? option is selected and the ?Continue on Error? field is set to False. Workaround: None.

Flogo Connector for OData

Key	Summary and Workaround
FGOD-50	Summary: The output of content-length response header of OData Query activity is not getting mapped to the Log Message activity. Workaround: None.

Flogo Connector for Oracle Database

Key	Summary and Workaround
WIORA-153	Summary: If the password contains a colon (:), an error occurs while connecting to the database. Workaround: None

Flogo Connector for Oracle MySQL

Key	Summary and Workaround
WIMYSQ-488	Summary: When importing an app's JSON with a MySQL, SQL Server, or Postgres activity, an error marker is shown on the activity even after updating the credentials. Workaround: Refresh the page.
WIMYSQ-464	Summary: For incorrect query, an error message is not showing up in the Insert, Delete, and Update activities. Workaround: None.
WIMYSQ-440	Summary: If there is no SSL server and you configure the connection as an SSL Connection with the TLS Required option selected, no error is generated at design time. An error is generated only at run time. Workaround: None.

Flogo Connector for PostgreSQL

Key	Summary and Workaround
WIPGRS-662	Summary: You cannot fetch Auto suggestion on Windows for PostgreSQL default public schema. Workaround: None.
WIPGRS-538	Summary: When Nullable fields are left empty, an error is generated. Workaround: Remove any fields that are not required from the query to automatically treat those fields as NULL.
WIPGRS-460	Summary: In case of queries combining results from multiple tables, if the tables have identical column names, then the repeated column names are renamed as columnName_<number>.

Key	Summary and Workaround
	Workaround: For duplicate column name use alias.
WIPGRS-429	Summary: In PostgreSQL "rowsAffected" is not showing in the output schema of the INSERT and UPDATE Activity. Workaround: None
WIPGRS-387	Summary: When running the connector with an SSL configuration with incorrect client key and client certificate issues, it results in errors at run time. These issues are not validated at design time. Workaround: None
WIPGRS-327	Summary: If you export or import from 2.8.1 to the current version, an error is shown on the activities even after establishing a connection. Workaround: Refresh the page or click on the respective Activity again.
WIPGRS-88	Summary: When using time datatype, "time without timezone" is not supported. Workaround: None

Flogo Connector for Salesforce.com Einstein Analytics

Key	Summary and Workaround
WISFEI-62	Summary: If Flogo apps using Salesforce Wave activities are run for longer durations, a token refresh error is displayed. Workaround: Reconfigure the Salesforce connection used in the activities and build the app again.

Flogo Connector for TIBCO Cloud Messaging

Key	Summary and Workaround
FGTCM-53	Summary: The subscriber stops receiving the message from the server after the reconnect attempts are exceeded. Workaround: Make sure that the TIBCO Cloud™ Messaging server is running normally and try the following: • Restart the app. • Configure a larger number of AutoReconnectAttempts under the connection to make sure it can try to reconnect more times until the server is up.
FGTCM-18	Summary: Content matcher does not work with INTEGER type for TIBCO Cloud™ Messaging Subscriber. Workaround: None

Flogo Connector for TIBCO Data Virtualization

Key	Summary and Workaround
FGTDV-205	Summary: Additional logs appear when the user stops a running binary. Workaround: None.
FGTDV-151	Summary: Tables are not auto-populated (if you use Ctrl + space) when you open an app after sometime. Workaround: Go to the Settings tab, change the catalog and switch it back. You can see the tables being auto-populated.
FGTDV-46	Summary: With Retry On Error before all retry attempts are completed, if we start the TDV server then the app does not auto connect. Workaround: None.

Key	Summary and Workaround
FGTDV-45	Summary: The delay between retry attempts is more than 2 minutes when the TDV server is unreachable, not honoring connection timeout. Workaround: None.

Flogo Connector for WebSockets

Key	Summary and Workaround
FGWSKT-125	Summary: The TCI exported app does not work in TIBCO Flogo® Connector for WebSockets. Workaround: When you make any change in the app and save it again, the app gets corrected and runs as expected.

TIBCO Documentation and Support Services

For information about this product, you can read the documentation, contact TIBCO Support, and join TIBCO Community.

How to Access TIBCO Documentation

Documentation for TIBCO products is available on the [Product Documentation website](#), mainly in HTML and PDF formats.

The [Product Documentation website](#) is updated frequently and is more current than any other documentation included with the product.

Product-Specific Documentation

The documentation for TIBCO Flogo® is available on the [TIBCO Flogo® Product Documentation](#) page.

How to Contact Support for TIBCO Products

You can contact the Support team in the following ways:

- To access the Support Knowledge Base and getting personalized content about products you are interested in, visit our [product Support website](#).
- To create a Support case, you must have a valid maintenance or support contract with a Cloud Software Group entity. You also need a username and password to log in to the [product Support website](#). If you do not have a username, you can request one by clicking **Register** on the website.
- To submit ideas, suggestions, or feedback for TIBCO products, visit our [product Support website](#).

How to Join TIBCO Community

TIBCO Community is the official channel for TIBCO customers, partners, and employee subject matter experts to share and access their collective experience. TIBCO Community offers access to Q&A forums, product wikis, and best practices. It also offers access to

extensions, adapters, solution accelerators, and tools that extend and enable customers to gain full value from TIBCO products. For a free registration, go to [TIBCO Community](#).

Legal and Third-Party Notices

SOME CLOUD SOFTWARE GROUP, INC. (“CLOUD SG”) SOFTWARE AND CLOUD SERVICES EMBED, BUNDLE, OR OTHERWISE INCLUDE OTHER SOFTWARE, INCLUDING OTHER CLOUD SG SOFTWARE (COLLECTIVELY, “INCLUDED SOFTWARE”). USE OF INCLUDED SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED CLOUD SG SOFTWARE AND/OR CLOUD SERVICES. THE INCLUDED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER CLOUD SG SOFTWARE AND/OR CLOUD SERVICES OR FOR ANY OTHER PURPOSE.

USE OF CLOUD SG SOFTWARE AND CLOUD SERVICES IS SUBJECT TO THE TERMS AND CONDITIONS OF AN AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER AGREEMENT WHICH IS DISPLAYED WHEN ACCESSING, DOWNLOADING, OR INSTALLING THE SOFTWARE OR CLOUD SERVICES (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH LICENSE AGREEMENT OR CLICKWRAP END USER AGREEMENT, THE LICENSE(S) LOCATED IN THE “LICENSE” FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE SAME TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of Cloud Software Group, Inc.

TIBCO, the TIBCO logo, the TIBCO O logo, and Flogo are either registered trademarks or trademarks of Cloud Software Group, Inc. in the United States and/or other countries.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only. You acknowledge that all rights to these third party marks are the exclusive property of their respective owners. Please refer to Cloud SG’s Third Party Trademark Notices (<https://www.cloud.com/legal>) for more information.

This document includes fonts that are licensed under the SIL Open Font License, Version 1.1, which is available at: <https://scripts.sil.org/OFL>

Copyright (c) Paul D. Hunt, with Reserved Font Name Source Sans Pro and Source Code Pro.

Cloud SG software may be available on multiple operating systems. However, not all operating system platforms for a specific software version are released at the same time. See the “readme” file for the availability of a specific version of Cloud SG software on a specific operating system platform.

THIS DOCUMENT IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. CLOUD SG MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S), THE PROGRAM(S), AND/OR THE SERVICES DESCRIBED IN THIS DOCUMENT AT ANY TIME WITHOUT NOTICE.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "README" FILES.

This and other products of Cloud SG may be covered by registered patents. For details, please refer to the Virtual Patent Marking document located at <https://www.cloud.com/legal>.



Copyright © 2016-2026. Cloud Software Group, Inc. All Rights Reserved.