



# **TIBCO iProcess® Engine (Oracle) for Linux**

## **Release Notes**

*Version 11.9.0  
August 2022*



# Contents

---

<b>Contents</b>	<b>2</b>
<b>New Features</b>	<b>4</b>
Release 11.9.0	4
Release 11.8.0	5
Release 11.7.0	7
Release 11.6.1	8
Release 11.6.0	8
Release 11.5.0	9
<b>Changes in Platform Support</b>	<b>15</b>
<b>Changes in Functionality</b>	<b>16</b>
<b>Deprecated and Removed Features</b>	<b>17</b>
Release 11.9.0	17
Release 11.8.0	17
Release 11.7.0	18
Release 11.6.1	18
Release 11.6.0	18
Release 11.5.0	18
<b>Compatibility</b>	<b>19</b>
<b>Change History</b>	<b>20</b>
Release 11.9.0	20
Release 11.8.1	21
Release 11.8.0	22
Release 11.7.0	23

Release 11.6.1 .....	27
Release 11.6.0 .....	34
Release 11.5.0 .....	39
<b>Restrictions .....</b>	<b>48</b>
<b>Known Issues .....</b>	<b>54</b>
<b>Other Information .....</b>	<b>57</b>
Use \$SWDIR/util/plist .....	57
Number of File Descriptors per Process .....	57
Must Normalize Case Data to View Cases .....	58
Upgrading from Earlier Version Might Cause Error Messages in Log File .....	58
<b>TIBCO Documentation and Support Services .....</b>	<b>60</b>
<b>Legal and Third-Party Notices .....</b>	<b>62</b>

# New Features

---

The following new features have been added since release 11.5.0 of this product.

## Release 11.9.0

The following features have been added since the last major release of TIBCO iProcess® Engine (Oracle) for Linux.

### JMX is Now Disabled by Default (For Business Studio Users)

From this release, by default, JMX is disabled in iProcess Engine. Connecting to a background process by using the JMX port is permanently disabled. With an exception, you can enable this feature in the `RPC_TCP_LI` process by setting the process attribute `ENABLE_JMX_LISTENER` to 1. This exception is to support the deployment of procedures especially from the Business Studio. You must set the `ENABLE_JMX_LISTENER` process attribute first and then, restart the iProcess Engine.

### Support for Global Variables

From this release, the Global Variables feature is added with the following functionality:

- User-definable custom fields that can be accessed from within any procedure via the new `GLOBALVARIABLE` expression
- Developers to set configuration data external to the procedure and change it independently of the procedure definition
- `swadm` supports Set, Delete, Import, and Export of Global Variables
- The new iProcess Admin Console page to view, change, import, and export Global Variables

For more information, see *TIBCO iProcess® Engine Administrator's guide* and *TIBCO iProcess® Engine Admin Console Guide*.

## Encryption Improvements

From this release,

- Encryption for the RPC layer between the iProcess Workspace (Windows), Work Queue Server, and Work Item Server processes is improved
- Encryption protocol that is used between iProcess Server Objects and iProcess Objects Server is updated

## Support for Export and Import of iProcess Configuration

From this release, iProcess Engine supports export and import commands to easily replicate iProcess Engine environments. For more information, see *TIBCO iProcess® Engine Administrator's guide*.

# Release 11.8.0

The following new features have been added in this release.

## Support for Java 11

From this release, Java 11 Support for iProcess Engine (Oracle) is provided.

## Support for Platforms

In this release, support for the following platforms have been added:

- Oracle Linux 7.6 (64 Bit)
- Oracle Linux 8.0 (64 Bit)
- Solaris (SPARC) 11.4 (64 Bit)
- Red Hat Enterprise Linux Server 7.6 (64-bit)
- Red Hat Enterprise Linux Server 8.0 (64-bit)
- SUSE Enterprise Linux 15 (64 Bit)
- Centos 7.6 (64 Bit)

## Support for Databases

In this release, support for the following databases has been added.

- Oracle 18c database using Oracle 19c Client
- Oracle 19c database using Oracle 19c Client

## MEMO Efficiency Improvements

From this release,

- USING\_BLOB flag allows a NULL value.
- In-place update of the MEMO is performed, instead of delete and insert.
- Memos are migrated in batches.

## IPAC enhancements

- The performance of Log Viewer Time Based filtering has improved
- Handling of large numbers of Queues, Message Queue Messages and System Events has increased
- Filtering for Queues, Messages, and System Events has enhanced
- New filtering options to swadm and plist for Queues, Messages, and System Events has been added
- Existing Monitoring Graphs can be edited
- Support for more details has been added across all the nodes in a Node Cluster environment
- Support for Pagination from Server

## Customer Written Applications

If you have created any customized applications, such as SAL SDK, UVAPI plug-ins, NPSAL, or JAVA plug-in applications, you must update your applications to 64-bit, for the applications to run seamlessly.

# Release 11.7.0

The following new features have been added in this release.

## TIBCO iProcess® Engine Administration Console

TIBCO iProcess Engine Administration Console is a Graphical User Interface (GUI)-based tool that runs on the web. It can be used to perform the following administrative tasks:

- Control process operations (start, stop, pause, enable/disable, and delete).
- Configure resources like process attributes, MBox queues, databases, port ranges, debug settings, and so on.
- Monitoring information, such as processes, queue information, logs, and so on.
- Monitoring performance based on CPU usage, memory usage, and so on.

For more information, see *TIBCO iProcess Engine Administration Console User's Guide*.

## Support for TIBCO iProcess Engine on Microsoft Azure

iProcess Engine can now be installed on the Microsoft Azure cloud platform. This enables you to host an existing installation or a completely new installation of iProcess Engine on Microsoft Azure.

For more information, see *TIBCO iProcess Engine Configuration Guide for Cloud*.

## swadm METRICS

This is a new swadm utility that enables you to query and export statistical iProcess Engine information. For more information on how to use this utility, see *TIBCO iProcess Engine Administrator's Guide*.

## Monitoring of Undelivered Queue Items

The integration capabilities of TIBCO Hawk have been extended to include a new interface **getUndeliveredCount** which allows monitoring undelivered queue items in iProcess Engine.

## Performance Improvements to Case Data Searching

The case data searching functionality has been enhanced to reduce search time and return search results faster.

## Support Oracle 12c R2 Database 12.2 and DB2 11.1

iProcess Engine now supports Oracle 12c R2 Database 12.2 and DB2 11.1 database servers.

## Release 11.6.1

The following new features have been added in this release.

### Support for Amazon Web Services (AWS) for TIBCO iProcess Engine for cloud

From this release, TIBCO iProcess Engine is now supported on the cloud through Amazon Web Services (AWS).

See *TIBCO iProcess Engine for Configuration Guide for Cloud* for more details.

## Release 11.6.0

The following new features have been added in this release.

### 64-bit Application

From this release, TIBCO iProcess Engine is a 64-bit application and can only be used on 64-bit operating systems against a 64-bit database. The executable process size of the 64-bit iProcess Engine application will increase (when compared to 32-bit versions in earlier releases), which depends on the application and amount of data. In general, the resident memory size of a process will increase by around 30%. Ensure that the machine to install iProcess Engine has sufficient memory to cater for this increase.

**i Note:** To use any existing UVAPI plug-ins with iProcess Engine 11.6.0, you must rebuild the UVAPI package as a 64-bit library.

## Support for Java Version

From this release, Java Standard Edition 8 is supported. See *TIBCO iProcess Engine Installation guide* for details.

# Release 11.5.0

The following new features have been added in this release.

## System Events Management ([IPE-3416](#))

The following new functions have been added to manage system events:

- **Enable System Events Logging**

When installing TIBCO iProcess Engine, you can use the **Enable System Event Logging** configuration item in the **Configuration Options** menu configuration option in the **Configuration** dialog box to specify whether or not you want to log system events information.

For more information about how to use this configuration item , see "Configuration Options Menu" in *TIBCO iProcess Engine Installation*.

The following tables are created to store information about system events logging:

- `system_event`: the table is used to store basic information about the system events.
- `system_event_conf`: the table is used to store system events configuration information.

- **Audit System Events**

You can use the `SYSTEM_EVENT_LOGGIN` process attribute to specify whether or not you want to audit system events after installing or upgrading to TIBCO iProcess Engine 11.5.0.

For more information, see "Activity Monitoring and Work Queue Delta Configuration" in *TIBCO iProcess Engine Administrator's Guide*.

- **Publish System Events**

You can use the `PUBLISH_SYS_EVENT_METHOD` process attribute to specify whether or not you want to publish system events. Before publishing a system event, ensure that the system event has been audited.

You can publish a system event by using Windows Event Viewer, TIBCO Hawk Agent, or the IAPJMS process.

- If you choose to publish a system event by using TIBCO Hawk Agent, you can use the `SE_WORKER_PORTNO` process attribute to specify a port number of the socket that is used for communications between the processes that audit the system events and the "worker" process. The "worker" process finally sends the events information to TIBCO Hawk Agent.
- If you choose to publish a system event by using the IAPJMS process, you can use the `SEJMS_TOPICNAME` attribute to specify the JMS topic name for the JMS destination that is used to publish the system event.

For more information, see "Activity Monitoring and Work Queue Delta Configuration" in *TIBCO iProcess Engine Administrator's Guide*.

- **Query System Events Information**

You can use the `plist -e` command to query information about a single or multiple system events.

For more information, see "System Event Information" in *TIBCO iProcess Engine Administrator's Guide*.

- **Turn Off System Events**

You can delete information about a single or multiple system events or clear information about system events ahead of a specified date from iProcess database by using the `swadm delete_system_event` command.

For more information, see "Removing System Events Information from the iProcess Database" in *TIBCO iProcess Engine Administrator's Guide*.

- **Import and Export System Events Configuration**

You can import a system event configuration file into TIBCO iProcess Engine by using the `swutil IMPEVENTCONF` command and export configuration information of a system event from TIBCO iProcess Engine to a command line by using the `swutil EXPEVENTCONF` command.

For more information, see *TIBCO iProcess swutil and swbatch Reference Guide*.

## Optimize SQL Statements Execution ([IPE-3455](#))

You can use the `sqloptim` file, which is located in the `SWDIR/etc` directory, to optimize execution of SQL statements in the database.

For more information, see "SWDIR\etc\sqloptim" in *TIBCO iProcess Engine Administrator's Guide*.

## Reduce Log in Time ([IPE-3468](#))

The average time for a user to log in to TIBCO iProcess Engine node is now identical no matter how many user groups and users have been created in this TIBCO iProcess Engine node if other system conditions remain unchanged.

For example, the average time for the user to log in to an iProcess Engine node with 500 users registered is the same as the average time for the user to log in to the same iProcess Engine node with 15000 users registered, if the other system conditions remain the same.

## Unlock Work Items ([IPE-3472](#))

You can use the `MN_UNLOCKER` process attribute to specify which iProcess users can have permission to unlock work items.

For more information, see "Process Management Configuration" in *TIBCO iProcess Engine Administrator's Guide*.

## WRITELOG Function Introduced ( [IPE-3473](#))

You can use the `WRITELOG` function to write messages to a log file to trace and debug iProcess scripts issues.

For more information, see "Log Functions" in *TIBCO iProcess Expressions and Functions Reference Guide*.

## Define the Maximum Size of Log Files ([IPE-3476](#))

You can use the `maxsize` parameter in the `DEBUG` process attribute to define the maximum size of log files, except the `sw_error`, `sw_warn`, `SWEntObjSvXX.log`, and `spodirectorXX.log` files.

When the log files reach the maximum size, if the `onfull` parameter in the `DEBUG` process is set to `save`, the log files are archived.

The default value of the `maxsize` parameter is 20 GB, and the default value of the `onfull` parameter is `save`.

For more information, see "Monitoring Log files" in *TIBCO iProcess Engine Administrator's Guide*.

## Define the Maximum Size of the `sw_warn` and `sw_error` Log Files (IPE-3477)

You can use the `WARN_ERROR_LOG_SIZE` process attribute to define the maximum size of the `sw_warn` and `sw_error` log files. The default value of the `WARN_ERROR_LOG_SIZE` process attribute is 2 GB.

For more information, see *TIBCO iProcess Engine Administrator's Guide*.

## Work Items Are Unique to Users (IPE-3480)

Add `requestid` as the unique identifier for each work item so that each work item can only be locked by one user.

## Change Field Data Type (IPE-3513)

The Long Raw data type in the `pm_objects`, `proc_defn`, and `user_setting` tables in the database has been changed to BLOB.

From TIBCO iProcess Engine 11.5.0, all the new case memo data is stored in the `nmemo` and `pack_nmemo` tables and the data type is BLOB.

You can migrate the old case memo data from the `memo` and `pack_memo` tables to the `nmemo` and `pack_nmemo` tables in one of the following ways:

- Use the **Memo Data Migration** menu when upgrading TIBCO iProcess Engine to 11.5 as a root user. For more information, see "Memo Data Migration Menu" in *TIBCO iProcess Engine for UNIX Installation*.
- Using the `swutil MIGRATEMEMOS ALL_CASES|LIVE_CASES|casenumrange` command after upgrading TIBCO iProcess Engine to 11.5. For more information, see "Migrating Old Case Memo Data" in *TIBCO iProcess swutil and swbatch Reference Guide*.

**Note:**

It might take a long time to complete the migration procedure. The time consumption depends on the volume of the memos in the `pack_memo` and `memo` tables.

## Delayed Release Has Been Enhanced ([IPE-3536](#))

The following features have been introduced to enhance the delayed release function:

- Add the `SW_DELAYED_RELEASE_ERR` stored procedure in the iProcess database. TIBCO iProcess BusinessWorks Connector can trigger the `SW_DELAYED_RELEASE_ERR` stored procedure to call and send the error message to the BG process if the iProcess Complete Delayed Release activity fails to complete delayed release of an EAI BusinessWorks step.

For more information, see "Delayed Release" in *TIBCO iProcess BusinessWorks Connector User's Guide*.

- Add the following system-defined message in the audit trail to trace the error message when performing delayed release of an EAI BusinessWorks step has failed:

```
088 StepDescription EAI delayed-release failed (error code (failure_count, BG_action):
error message)
```

For more information, see "Understanding Audit Trails" in *TIBCO iProcess Engine Administrator's Guide*.

## Support for Platforms

In this release, the following platforms are supported:

- Red Hat Enterprise Linux Server 5.10 (32-bit and 64-bit)
- Red Hat Enterprise Linux Advanced Platform 5.10 (32-bit and 64-bit)
- Red Hat Enterprise Linux Server 7.0 and 7.1 (64-bit)



**Note:** Any subsequent service packs release, such as 7.2 would also be supported.

## Support for Database

In this release, you can use one of the following versions of Oracle client to access Oracle 11g and 12c depending on your operating system:

- HP-UX, Solaris, and AIX: 12.1.0.1
- Linux: 12.1.0.2

# Changes in Platform Support

---

The following table lists the features that have been removed in the version 11.9.0 of TIBCO iProcess® Engine (Oracle) for Linux.

## *Platform Support Removed*

Platform	Status	As of Release	Notes
Solaris	Removed	11.9.0	TIBCO iProcess® Engine (Oracle) for Linux no longer supports Solaris platform.
AIX	Removed	11.9.0	TIBCO iProcess® Engine (Oracle) for Linux no longer supports AIX platform.

In line with [TIBCO's Platform Support Policy](#), the 11.8.x release of iProcess (iProcess Engine, iProcess Workspace, and iProcess Developer) is the last release to support the Oracle Solaris and IBM AIX platforms.

The following product components are directly affected by this change:

- TIBCO iProcess Engine (Oracle)
- TIBCO iProcess Engine (DB2)
- TIBCO iProcess Technology plug-ins
- TIBCO iProcess Webservices Server plug-in
- TIBCO iProcess Server Objects (Java)
- TIBCO iProcess Workspace (Browser)

For a complete list of supported platforms, see the Readme file.

## Changes in Functionality

---

The following functionality has been changed in this release of TIBCO iProcess® Engine (Oracle) for Linux.

Key	Version	Summary
IPE-5789	11.9.0	<p>The JMX or RMI dependency from the JMS Admin tool is removed. The JMS Admin tool now directly connects to a database and/or JMS instead of sending requests to the iProcess Engine.</p> <p><b>Note:</b> (For Business Studio only) There is an option to temporarily enable this feature by using the ENABLE_JMX_LISTENER process attribute.</p>

---

# Deprecated and Removed Features

---

This section describes any features that have been deprecated or removed since release 11.5.0 of this product.

For deprecated features, if relevant, useful alternatives to the deprecated features are listed. Any use of a deprecated feature must be discontinued as it might be removed in a future release. You must avoid depending on the deprecated features and become familiar with the suggested alternative features.

## Release 11.9.0

The following feature has been removed as of this release of TIBCO iProcess® Engine (Oracle) for Linux.

### Removed Feature

From this release, the iProcess Server Manager is no longer supported.

## Release 11.8.0

### Deprecated Features

The following features are deprecated in this release:

- iProcess Decisions Server
- iProcess Decisions Studio
- iProcess Decisions Web Services

## Release 11.7.0

No features have been deprecated or removed as of this release of TIBCO iProcess Engine.

## Release 11.6.1

### Deprecated Features

The following features are deprecated in this release:

- TIBCO iProcess Objects (COM)
- TIBCO iProcess Objects (Java)

## Release 11.6.0

### Deprecated Features

The following features are deprecated in this release:

- TIBCO iProcess Client (ASP) and TIBCO iProcess Client (JSP) are deprecated and might be removed from a future release. You can use TIBCO iProcess Workspace (Browser) as an alternative client interface for TIBCO iProcess Suite.
- TIBCO iProcess Objects (C++) is deprecated and might be removed in a future release. You can use TIBCO iProcess Server Objects as an alternative interface for your iProcess applications.

### Removed Features

From this release, 32-bit environments are no longer supported.

## Release 11.5.0

No features are deprecated and removed in this release.

# Compatibility

---

In addition to other versions of TIBCO iProcess® Suite components, the following TIBCO products have been successfully tested for compatibility with release 11.9.0 of TIBCO iProcess Engine.

Product	Version
iProcess Workspace (Browser)	11.9.0
iProcess Workspace Lite	1.2.0
TIBCO iProcess® Web Services Server Plug-in	11.9.0
TIBCO iProcess® Technology Plug-ins	11.9.0
TIBCO iProcess® Server Objects	11.9.0

If you have any queries regarding product compatibility with this version of iProcess Engine, contact TIBCO Support for further assistance.

# Change History

---

The following JIRA issues and Modification Requests (MRs) have been implemented since release 11.5.0 of TIBCO iProcess Engine.

## Release 11.9.0

Defect #	Description
IPE-5802 (Parent JIRA IPE-5763)	When reconnecting to the LDAP server, BG crashes during an LDAP synchronization.
IPE-5742	Unable to set few debug log parameters like log level, trace msg flag and so on for the SPO server via Process Attributes.
IPE-5728	When the SPO server consumes 100% CPU, it does not respond to any requests.
IPE-5689	When importing the configuration file, you cannot import the watcher or worker ports present in the <b>/etc/services</b> location.
IPE-5609 (Parent JIRA IPE-4135)	When a case starts via SSOLITE that contains an SW_ADD_PACK_MEMO call, the memo data gets saved in the main case but, it does not pass that data into a sub-procedure.
IPE-5604	The log4j JAR file is upgraded to 2.17.2 version.
IPE-5593 (Parent JIRA IPE-5579)	When a queue name contains hyphen (-) in it, the swutil CHECKITEM and swutil CLEANITEM commands do not return correct output.

Defect #	Description
IPE-5589	The EncodeToUTF8 function fails to identify the correct char-set when translating from US-ASCII to UTF8.
IPE-5563 (Parent JIRA IPE-5388)	The SPODIRECTOR file crashes when parsing the Client version.
IPE-5384	When you run the swinstall and swconfig files during installation, the segmentation fault occurs.
IPE-5328	The WIS session do not release the lock after publishing the <b>JMS WQD</b> message error.
IPE-5327	When you run the following <b>plist</b> commands in socket mode, dumps are created <div> <pre> plist -Px plist -Px &lt;procname&gt; ALLVERS </pre> </div>
IPE-5152	When you pass the EMPTY_BLOB function in the ReadOciLob function call, you open LOB with the OCILobOpen function but, cannot close it properly.

## Release 11.8.1

Defect #	Description
IPE-5535	Addressed the Apache Log4J vulnerability (CVE-2021-44228).
IPE-5524	When memory consumption increases, user cannot connect to the server and the server must be rebooted.
IPE-5505	When getting the subcase audit message, iProcess Objects Server crashes.
IPE-5494	When you try to reopen a case by selecting a trigger event, TIBCO iProcess

Defect #	Description
	Workspace (Browser) returns an error.
IPE-5485	When a user creates multiple groups via the Staffware Process Objects (SPO) Server, an error occurs.
IPE-5330	IAPJMS to connect with EMS over SSL.

## Release 11.8.0

Defect #	Description
IPE-5153	Line feed in the case description could be a probable cause for an intermittent SPO crash.
IPE-5152	Open LOBs exist at transaction commit - warnings in sw_error
IPE-4816	CLONE - improve performance for writing blob type data into database
IPE-4769	performance improvement for upgrading memo tables
IPE-4996	ldapconf command line to set groupname, rolename, Qsupervisors and Userflags
IPE-15	The CDQP QINFO imports fieldname in lowercase when the control file does not use R at the beginning of the file.
IPE-4987 (Parent JIRA IPSE- 260)	BG memory usage increases whenever LDAP FULL SYNC is performed in LDAPCONF.
IPE-4953 (Parent JIRA IPSE-	WIS crashes while filtering work items if you use an asterisk (*) as a filter string.

Defect #	Description
4952)	
IPE-4936	iProcess Engine startup status message for RPC_UDP_LI is not updated from STARTING to RUNNING.
IPE-4919 (Parent JIRA IPSE- 4512)	In iProcess Workspace Browser, when users filter data with an asterisk (*), relevant records are not filtered and displayed.
IPE-4869 (Parent JIRA IPSE- 4850)	The iProcess database connects times out overnight due to the IDLE_TIME setting. RCP_TCP_LI crashes with a core dump.
IPE-4868 (Parent JIRA IPSE- 4866)	WQS crash caused by socket id corrupted the call stack and impacted the users severely.
IPE-4036	Performance improvement for the fix for losing participants when performing full ldapsync.
IPE-1186	If you perform a non-root installation, the generated rootscript includes switches to the useradd/usermod and groupadd commands instead of the actual commands.

## Release 11.7.0

Defect #	Description
IPE-4526	SW_DELAYED_RELEASE displayed an error on executing a stored procedure with

Defect #	Description
	DelayedReleaseId that has no failed count.
IPE-4525 (Parent JIRA IPE- 4501)	If you tried adding multiple users in TIBCO iProcess Engine version 11.6.1 HF-011 via TIBCO iProcess Objects Server, a SAL system error occurred.
IPE-4485 (Parent JIRA IPE- 4474)	The parsing logic of a major and minor version of a procedure by the iProcess Objects Server was incorrect.
IPE-4443 (Parent JIRA IPE- 4442)	If you performed a full LDAP server synchronization, all participants were lost.
IPE-4429 (Parent JIRA IPE- 4411)	The JumpTo function on a closed case was stopped/restricted.
IPE-4419 (Parent JIRA IPE- 4418)	Background processes were suspended if a sub procedure with a failed withdrawal step was released.
IPE-4410 (Parent JIRA IPE- 4403)	The Unlock Workitem option does not work in a UTF-8 enabled iProcess Engine instance. As a result, the iProcess Objects Server returns the "item not found" error.
IPE-4401	After completing the first step in a case, by using the KEEP option from java clients like the iProcess Workspace (Browser) or iProcess Server Objects, results in

Defect #	Description
(Parent JIRA IPE-4393)	the iProcess Objects Server inserting the data into both pack_data and case_data tables.
IPE-4381 (Parent JIRA IPE-4380)	In cases when the background (BG) failed to process sub-cases, it did not roll back and continued purging cases and committed the transaction.
IPE-4375 (Parent JIRA IPE-4367)	Watcher and worker do not stop during restart as the iProcess Objects Director does not send a shutdown notification to the sentinel.
IPE-4355 (Parent JIRA IPE-4354)	TIBCO iProcess Engine can not fetch a Request ID due to lack of support for an older DelayedReleaseID format. This has been fixed by adding backward support for the older DelayedReleaseID format.
IPE-4306 (Parent JIRA IPE-4224)	The libgcc_s library was missing and the libiconv libraries had issues which resulted in errors during installation. These errors occurred because of the swconfig utility's dependency on these libraries.
IPE-4305 (Parent JIRA IPE-4297)	When recompiling the SAL SDK brokers, the interface to the Work Queue Server did not work returning the following error:  (count is 0 on sal_queues_count) and -11 ER_NOTFOUND
IPE-4287	TIBCO iProcess Engine encountered an error when loading an extremely high number of cases due to insufficient memory allocation to the iProcess Objects Server.
IPE-4244	A new parameter "proc_id" was added to the SW_GETCASE_STATUS stored

Defect #	Description
(Parent JIRA IPE- 4243)	procedure. This did not allow closing cases through SSOLITE.SW_CLOSE procedure on the iProcess Engine upgraded environment.  To fix this, the change to SW_GETCASE_STATUS has been reverted and SW_GETCASE_STATUS_EX that takes proc_id and casenum as input has been added.
IPE-4233  (Parent JIRA IPE- 3360)	The sw_casenum was not available in the first steps of the initial (init) script.
IPE-4232  (Parent JIRA IPE- 3963)	There is a memory leak when freeing the user member list cache.
IPE-4231  (Parent JIRA IPE- 3962)	There is a slight memory leak in the SPO.
IPE-4223  (Parent JIRA IPE- 4189)	For a non-array memo field, the stored procedure was being saved as an array field.
IPE-4210  (Parent JIRA IPE- 4209)	While removing participants from the Work Queue Server, the queue record is locked causing the iProcess Objects Server process to be unresponsive.
IPE-4180  (Parent JIRA IPE-)	Any CASENUM greater than 2G resulted in a "case not found" error.

Defect #	Description
4179)	
IPE-4178	In iProcess Workspace (Browser), if you clicked the Use Default button in the column selector under the View menu, and then logged out from iProcess Workspace (Browser), the iProcess Objects Server crashed.

## Release 11.6.1

Defect #	Description
IPE-4138	When a case data was set by TIBCO iProcess Objects Server, the numeric value got changed to a decimal value.
IPE-4128	An orphaned item is left in the queue until WIS restart.
IPE-4097	If there were any trailing spaces for input values in text and memo fields, TIBCO iProcess Objects Server deleted these spaces automatically.
IPE-3969 (Parent JIRA IPE- 3968)	When an additional user was added to the groupusers/iPrGroupUsers in Active Directory, the output and the LDAP server synchronization returned unreliable data.
IPE-3903	TIBCO iProcess Engine had returned an error when connecting to TIBCO iProcess Objects Server if the hostname was longer than 64 characters.
IPE-3897 (Parent JIRA IPE- 3899)	The Work Item Server (WIS) had a problem with sorting work item lists that contained both very low and very high CASENUMs.
IPE-3895	When upgrading TIBCO iProcess Engine, the upgrade failed when migrating process definition data (proc-defn).

Defect #	Description
IPE-3894	If you performed a swutil PROC RELEASE, and chose to migrate all cases (-m ALL) when there was no released version of the procedure, the cases were not migrated.
IPE-3893 (Parent JIRA IPE- 3879)	<p>The <i>swutil USERINFO</i> - command failed to remove a user from a group. For example, for a user <i>Usr00001</i> and group <i>Grp00002</i>, the command and corresponding error are:</p> <p><b>Command:</b> <i>swutil USERINFO -</i></p> <p><i>M-Usr00001,Grp00002</i></p> <p><b>Error:</b> <i>Line 1: User Usr00001 is not a member of group Grp00002; line ignored</i></p> <p><i>^Z</i></p> <p><i>0 lines successfully processed</i></p>
IPE-3891	TIBCO iProcess Engine did not import queues if there were leading spaces, trailing spaces, and control characters, such as Carriage Return/Line Feed.
IPE-3890	The Work Queue Server crashed if there were leading spaces in the queue names.
IPE-3868 (Parent JIRA IPE- 3876)	<p>If you shut down TIBCO iProcess Engine and migrated cases to a new PROC RELEASE by using swutil, the pstafffc file crashed. The pstafffc01.log file listed the following errors:</p> <p><i>[P=06576][T=01668]160517212511.370102:0001: slist_add (): failed to reallocate object list (70, 4)</i></p> <p><i>[P=06576][T=01668]160517212511.370383:C001: lselect_casenum : Failed to add case number to slist</i></p> <p><i>[P=06576][T=01668]160517212511.370699:0001: slist_add (): failed to reallocate object list (70, 4)</i></p> <p><i>[P=06576][T=01668]160517212511.371000:C001: lselect_casenum : Failed to add case number to slist</i></p>
IPE-3864	The RPCBG crashed when TIBCO iProcess Engine was shut down.

Defect #	Description
(Parent JIRA IPE- 3831)	
IPE-3863  (Parent JIRA IPE- 3857)	Cases that were suspended displayed as active in the work queues.
IPE-3862  (Parent JIRA IPE- 3828)	SQL statement 36 cannot execute successfully when the case number is 2500009010.
IPE-3856  (Parent JIRA IPE- 3858)	The SSOLITE Stored Procedure SW_UNPACKRELEASEID did not get the procedure information by using case number, even when the procedure's version was in delayreleaseid.
IPE-3851	If you tried purging cases with a million sub-cases, the background process returned a memory error.
IPE-3846  (Parent JIRA IPE- 3848, IPE- 3850, IPE- 3854)	If you used the wrong password when you logged in to TIBCO iProcess Workspace (Browser) the first time, and then used the correct password to log in, the following error occasionally occurred:  <i>client connection refused; too many clients</i>
IPE-3845	TIBCO iProcess Engine admin user was not notified when sw_error and sw_warn logs were created.
IPE-3838	When upgrading from TIBCO iProcess Engine 11.5 to 11.6, with "Upgrade files only" selected, the installation failed.

Defect #	Description
IPE-3833 (Parent JIRA IPE- 3920)	The sentinel could not be started by using the <code>swstart -p</code> command when UTF-8 was enabled and UTF-8 database was used.
IPE-3825	The EAI Database (EAI DB) could not build the parameter mapping in case of a numeric input parameter, and an integer value above the default maximum.
IPE-3824	The features of the <code>SE_WORKER_PORTNO</code> parameter could not be disabled when required.
IPE-3821	The <code>move_server</code> command failed when executed from secondary servers.
IPE-3799	The database scripts failed when upgrading TIBCO iProcess Engine to version 11.5.
IPE-3674	When a queue was created with a space in the queue name, the <code>swutil CLEANITEM</code> command failed.
IPE-3670	When you started TIBCO iProcess Engine, it logged the message <i>set param.sticky_sal to 1</i> despite manually setting up <code>STICKY_SAL</code> initially.
IPE-3669	TIBCO iProcess Objects Server crashed when getting the memo data.
IPE-3659	When a background process debug string of <code>ALL=255</code> was enabled, changing the <code>IAPJMS_SIMPLETOPIC</code> flag value in TIBCO iProcess Engine from 1 to 0 and back to 1 caused all background processes with debugging enabled to crash.
IPE-3598	TIBCO iProcess Objects Server's memory allocation increased rapidly and the server crashed when it was scanned for vulnerabilities by a third-party software.
IPE-3360 (Parent JIRA IPE- 4069)	The <code>sw_casenum</code> was not available in the first steps of the initial (init) script.

Defect #	Description
IPE-3275	The default configuration for EAI_MAIL caused the background process (BG) sockets to close and duplicate background processes.
IPE-2782	The Work Item Server (WIS) crashed when publishing the work queue delta message.
IPE-2750	Post upgrade from TIBCO Process Engine version 9.0 to TIBCO iProcess Engine version 11.1, a case could not be closed through the SSOLITE.SW_CLOSE case procedure.
IPE-2680	TIBCO iProcess Objects server set a hard-coded value (7) to the umask.
IPE-2556	The swentobjsv crashed if it received an LV message when the DB_ENABLED configuration parameter was set to 0.
IPE-2374	When trying to fetch the SAL session handle, if the number of SAL sessions went beyond 0xFFFF, the attempt to fetch the handle failed.
IPE-2333	TIBCO iProcess Engine could not be started due to lack of available AQ ports in the aq_port_range table.
IPE-2240	Some Work Item Server (WIS) filter expressions for a range of numerics did not work. For example: <ul style="list-style-type: none"> <li>• <i>NUM2=[50 60 70] - Failed with a SAL System Error</i></li> <li>• <i>NUM2=[50] - Failed with SAL System Error</i></li> <li>• <i>NUM2=["50" - "100"] - Did not return an error but fails to return items as the "100" appears to get truncated as the field length is only 2,0</i></li> </ul>
IPE-2222	When multiple cases were released, some or all deltas did not have the CDQP data.
IPE-2049	If an anonymous user tried to attempt an LQ (list user queue) of a user's queue to which they did not have access, the thread hung in the "acquire_user" stage.
IPE-2005	When the user started a new case, the undelivered work items for the case were

Defect #	Description
	not displayed in the Outstanding tab.
IPE-1965	When upgrading TIBCO iProcess Engine, with the IPEINSTALL user being different from the IPESERVICE user, the engine failed to start as some file permissions were not set correctly.
IPE-1768	When upgrading from TIBCO Process Engine to TIBCO iProcess Engine, the upgrade process ended without any prompt, in case of warnings.
IPE-1657	The SQL statement which cached the case counts blocked the database.
IPE-1611 (Parent JIRA IPE- 4034)	The background process had a memory leak when an event was published.
IPE-1548	In an EAI Database step, when you tried to call a procedure, the step was not executed and the following error was returned.  <i>Invalid Step Definition: No Stored procedure name</i>
IPE-1523	The Work Item Server (WIS) went into a deadlock if the parameter WIS_NEW_ITEM_BATCH_SIZE was not 0 and if a new work item arrived for an undelivered or test queue that did not exist.
IPE-1340	In instances where the Oracle server had to be restarted, some data in the background process was lost. This did not allow the processes to resume normally when the server was restarted.
IPE-1332	User authentication failed due to conflict between TIBCO iProcess Engine APIs and Active Directory APIs.
IPE-1301	When a user was deleted, the user's queue directory under \$SWDIR/queues was not removed.
IPE-1141	In the server manager under section queue management, the failed count/failout value for the messages for any queue were not correct.

Defect #	Description
IPE-1097	If there was a network error when connecting to the LDAP server, TIBCO iProcess Engine did not execute automatic reconnect attempts.
IPE-1085	The change password (chgpwd) process got locked if TIBCO iProcess Objects Server wrote MON at the time of fork.
IPE-1030	swadm and swconfig printed misleading messages on startup.
IPE-1029	The deadline tab for EAI Step Definitions was not disabled for non-delayed releases.
IPE-966	The case description was not updated in the CASE_INFORMATION field when the setCaseData () call was used.
IPE-947	Add Java library path to catalina.sh for the tomcat bundled with TIBCO iProcess Engine.
IPE-903	Work item did not appear in the Test work queue.
IPE-879	When TIBCO iProcess Objects Server was paused or resumed, the swsvrmgr did not show the correct server status until the server received a new TCP package.
IPE-841 (Parent JIRA IPE- 3880)	There was a timing issue between the background (BG) process and the Work Item Server (WIS) process which updated the staffo table. This resulted in the staffo entries with the locker column set but no locked bit set or expired auto-withdraw deadlines which did not let the Work Item Server (WIS) cache when deadlines recalculated.
IPE-797	swinstall failed to identify missing "command not found".
IPE-745	The sal_xpc_list_filter_cases () function did not handle expressions with OR correctly.
IPE-690	The IAP monitor did not fully support the field in which an array was defined.
IPE-232	The port used by ORACLE AQ events could not be set up due to problems in the firewall environment.

Defect #	Description
(Parent JIRA IPE- 884)	
IPE-167	The LDAP configuration or synchronization behavior was inconsistent when a user with an invalid MENU_NAME existed.
IPE-112	<p>If an EAIDB stored procedure returned an output parameter that had a null value, the following error occurred and the EAIDB step failed.</p> <p><i>sw_warn:</i></p> <p>2010/08/25 16:27:08.027943 (BG:2:18413:2:EAIDB1:2552:DB1:pro:/proeai.c:81845:3601): 1869-Procedure:EAIDB1 EAI Step:DB1 Case:2552 EAI plug-in EAIRun_Call() failed, error: SQL_SYS_ERR - MS-SQL error code :-99999 - [IBM][CLI Driver] CLI0110E Invalid output or indicator buffer specified. SQLSTATE=22002</p> <p>2010/08/25 16:27:08.195189 (BG:2:18413:0:EAIDB1:2552:DB1:pro:/cplmain.c:81512:2388): 1631-WARNING: &lt;CPLInstruction - Error&gt; &lt;-2&gt; &lt;RELEASE&gt; &lt;RELEASE^sw111db2a^5:0.7^1^sw111db2a,swadmin,5102,sw111db2a^2552^2552^sw111db2a^swadmin^S1^Step1^3^25/08/2010^16:27^5102^sw111db2a^swadmin^1^&gt;</p> <p>2010/08/25 16:27:08.195243 (BG:2:18413:2:EAIDB1:2552:DB1:pro:/swbgmbd.c:82103:1113): 1864-Transaction failure : Reason code = -2</p>

## Release 11.6.0

Defect #	Description
IPE-621	If only one Case Data Queue Parameter (CDQP) was defined for a queue and the CDQP contained only 1 character, an error occurred when accessing the queue from iProcess Workspace (Browser).

Defect #	Description
IPE-3640 (Parent JIRA IPE-3626)	If you specified a different value for the SW_CP_VALUE property other than the Priority property in the <b>Input</b> tab of the iProcess Complete Delayed Release activity, the message priority was not changed to the value specified in the SW_CP_VALUE property after completing the delayed release.
IPE-3654 (Parent JIRA IPE-3639)	If you had run the manual_uorai11_4_1_5.sql script file first, and then run the manual_uorai11_4_1_9.sql script file, the following error message was displayed: <pre>"PLS-00306:wrong number or type of arguments in call to 'SW_ EVENT_MESSAGE'"</pre>
IPE-3687	TIBCO iProcess Objects Server crashed when multiple threads concurrently called the UVAPI interface.
IPE-3688 (Parent JIRA IPE-3634)	When using SPO to open a disabled queue, an infinite loop error occurred and the error messages were written to the log file continuously.  Corrected.
IPE-3697	When upgrading TIBCO iProcess Engine from an earlier version to 11.5.0 and running the upgrade script to check and drop constraints, if an index was created with a constraint and the index was not removed, the upgrade failed.  Corrected.
IPE-3698	The status of the WISMBD process was not correct when WIS processes were suspended and the WISMBD process was stopped.
IPE-3700 (Parent JIRA IPE-3681)	When the BG process was used to publish audited activity messages to the IAPJMS process, the IAPJMS process spent a lot of time looking up a dynamic JMS topic; therefore, both the IAPJMS process and BG process worked very slowly.
IPE-3701 (Parent	When you use the Case Data Queue Parameter (CDQP) field to filter items, if both the database and the iProcess engine environment used UTF-8, and the CDQP

Defect #	Description
JIRA IPE-3684)	field contained empty values, the filter result was incorrect. Corrected.
IPE-3708 (Parent JIRA IPE-3705)	After processing the sub cases, the Chinese characters in the "step description" section of the audit message were missing or abnormally displayed. Corrected.
IPE-3710 (Parent JIRA IPE-3707)	When you use the <b>swutil EVENT</b> command with an abox file to update field data, if the abox file contained a numeric field and the value of this field contained a leading zero with no decimal point, after updating, the leading zero in the value was removed and replaced with a decimal point behind the value in the database table. For example, if the original value was "09", the value in the database table was updated to "9".
IPE-3720	When starting a case and executing a graft step use an sw_graft stored procedure or an iProcess Server Objects application, if the <b>auto-purge</b> option was enabled for the graft sub procedure, an error was returned to iProcess Workspace (Browser).
IPE-3724	Failed to start the iProcess Engine node after installing iProcess Engine with Hawk 5.1.x. Corrected.
IPE-3727 (Parent JIRA IPE-3726)	The IDX_ATTACHMENT_FK index was missing, which caused database deadlock. Corrected
IPE-3739	When using the <b>SWBATCH</b> command to purge a batch of cases, if one of the specified cases did not exist, the subsequent cases within the specified case range were not purged. Corrected.

Defect #	Description
IPE-3740 (Parent JIRA IPE- 3719)	If the <b>password required</b> option was enabled when installing iProcess Engine, and the first step of a procedure was an EAI step, an error occurred when starting a case.  Corrected.
IPE-3741	The RPC_POOL process crashed when releasing an unreleased procedure that had configured case deadlines.
IPE-3749 (Parent JIRA IPE- 3730)	If the SQL statement was marked as cached, memo searches might look into the incorrect table, resulting in no data being found although a memo being assigned.  This issue affected systems with memo data in both the MEMO and NMEMO tables and either type of memo.  Corrected.
IPE-3750 (Parent JIRA IPE- 3742)	When using TIBCO ActiveMatrix BusinessWorks or SSOLite to start a case with a memo value, if the procedure contained multiple EAI steps and the memo value was set to NULL in one of the EAI steps, the memo value was not NULL after starting the case.  Corrected.
IPE-3751 (Parent JIRA IPE- 3744)	If TIBCO iProcess Workspace (Browser) was used to start cases, unnecessary test logs were added to the SPO SAL logs.  Corrected.
IPE-3752 (Parent JIRA IPE- 3738)	If you upgraded iProcess Engine to version 11.5 without migrating any cases, an error occurred when running a TIBCO ActiveMatrix BusinessWorks process to issue an update event for a case that existed in any previous versions of iProcess Engine.  Corrected.
IPE-3753	When multiple users attempted to log in to TIBCO iProcess Objects Server

Defect #	Description
(Parent JIRA IPE-3692)	through different client applications (.net/java), a "No response from SPO Server" error message was displayed for certain users.
IPE-3754 (Parent JIRA IPE-701)	Failed to upgrade an iProcess Engine node, if multiple iProcess Engine nodes with similar names, such as wx1234,wx12345, and wx12356, were installed on a machine.
IPE-3757 (Parent JIRA IPE-3691)	If TIBCO iProcess Engine client connected to TIBCO iProcess Objects Server that had already exited, and it did not close the connection to TIBCO iProcess Objects Server, TIBCO iProcess Objects Server might crash.
IPE-3758	An error occurred by using the <b>save as &gt; new procedure</b> option to rename a procedure.
IPE-3759	The BG process crashed when running the SSOLITE stored procedure that contained graft steps.
IPE-3760 (Parent JIRA IPE-3748)	The value format of the delayedreleaseID parameter was changed. Certain value parsing functions in TIBCO iProcess Objects Server could not parse the new format; therefore, an error occurred when parsing the values with the new format and failed to release the 'delayed release EAI step'.  Corrected.
IPE-3763	When switching iProcess Engine from one machine to another machine in a cluster environment, a database error like the following occurred:  ORA-02292: integrity constraint violated ORA-02292: integrity constraint violated error  Corrected.
IPE-3765	If you updated the values of memo fields in the subprocedure through the SSOLITE interface, the updated values were not returned to the main procedure.

Defect #	Description
(Parent JIRA IPE- 3706)	Corrected.
IPE-3794 (Parent JIRA IPE- 3785)	The WQS process updated the wqs_index table frequently during the startup of iProcess Engine, the WQS process consumed nearly 100% of the CPU and the WIS process was locked in a STARTING state.  Corrected.
IPE-3795	The standard file descriptor (for example, 0, 1, 2) was used in the RPC depository.

## Release 11.5.0

Defect #	Description
IPE-701	When you used the swstart script located in the <i>SWDIR/bin</i> directory to start all the server processes in a node cluster, if multiple nodes had similar names, the server processes did not start.
IPE-1488	TIBCO iProcess Engine failed to start if one of the following conditions occurred:  ORA-28002: the password will expire within string days  ORA-28011: the account will expire soon; change your password now  Corrected.
IPE-3141	The step_addr column of the predict table displayed NOADDR when a new user was added to TIBCO iProcess Engine.
IPE-3389	When installing TIBCO iProcess Engine, if the name and password of DB Schema Owner were not contained in the passwd file located in the /etc directory, the following error messages were displayed:  Checking DB connectivity and users...  DB2 User (<user_name>) must be a member of the <group_name> group

Defect #	Description
	Press Enter to continue:
IPE-3390 (Parent JIRA IPE- 3326)	After starting TIBCO iProcess Engine, the DBQD process was continually logging entries into the DBQD_1_stdout log file, which was located in the \$SWDIR/logs/process/etc directory.
IPE-3394	When installing iProcess Engine, if you used JBoss EAP 6.1.0 as the JMS provider, the configuration information written to the iapjms_classpath.properties file that was located in the \$SWDIR/etc directory was incorrect.
IPE-3395 (Parent JIRA IPE- 3309)	After importing procedures through the XML Process Definition Language (XPDL) file, the access control on the library containing the imported procedures was reverted to the default settings.
IPE-3396	When calling the triggerEvent() method, TIBCO iProcess Objects Server process did not unlock the procedure cache if an error occurred.
IPE-3399	When you used TIBCO iProcess Objects Server process to cache a specified version of the procedure definition that did not exist in TIBCO iProcess Engine, the following error message was displayed in TIBCO iProcess Objects Server log file:  SPO did not unlock every read/write lock.
IPE-3400	When importing a procedure library by using the swutil IMPORTLIB command for the second time, if the description of the procedure exceeded 24 characters, the importing of the procedure library failed.
IPE-3412 (Parent JIRA IPE- 3013)	After starting cases by using the SSOLite stored procedures, the values in the casenum_gaps table were incorrect.  Implemented.
IPE-3414	When you use the swsvrmgr START_NEW command to start a new instance of the

Defect #	Description
	BG process, the Process Sentinels crashed.
IPE-3416	<p>The following functions are introduced to manage system events:</p> <ul style="list-style-type: none"> <li>• Enable system events logging</li> <li>• Audit system events</li> <li>• Publish system events</li> <li>• Query information about system events</li> <li>• Turn off system events</li> <li>• Import configuration files of system events into iProcess Engine</li> <li>• Export configuration information of system events to a command line</li> </ul> <p>See <a href="#">System Events Management (IPE-3416)</a>.</p>
IPE-3421	When starting a case that contained a numeric field in iProcess Engine 11.4.1, if the NLS_LANG parameter was set to en_US and the decimal separator in the numeric field was set to the period character rather than the comma character, a warning message was displayed in the sw_warn file.
IPE-3424	A closed case was not opened by using SSOLite stored procedures.
IPE-3425	<p>After successfully caching a version of a procedure definition by using iProcess Objects Server process, the following error message was displayed in TIBCO iProcess Objects Server log file:</p> <pre>g_proc_cache_rwlock was read-locked. cache_the_procedure() SEO_node_namefind() failed.</pre>
IPE-3429 (Parent JIRA IPE- 3283)	<p>A deadlock occurred when the m_IndexLock parameter was used in the CIndex::SetDeleted() and CIndex::IsDeleted() functions.</p> <p>Corrected.</p>
IPE-3430	A deadlock occurred which caused all the "worker" threads and the update

Defect #	Description
(Parent JIRA IPE-3348)	thread in the WIS process to suspend when more than one "worker" threads were processing the WIS session simultaneously.  Corrected.
IPE-3432 (Parent JIRA IPE-3346)	More logs have been added to trace the information of the locks in the CIndex_Mutex lock pool used by the WIS process.  Corrected.
IPE-3436	TIBCO iProcess Objects server process unlocked the read and write lock before locking the process cache.
IPE-3437 (Parent JIRA IPE-3380)	When running a script, which called the markfieldchanged function, to release work items, the work items were locked.
IPE-3441 (Parent JIRA IPE-3417)	When calling the GetNextDeltaItem() method to retrieve a new or modified work item from a work queue, the error message "invalid format of delta details from SAL" was recorded in TIBCO iProcess Objects Server log file.
IPE-3444	When reconnecting to an LDAP server that was performing synchronization, the BG process was suspended.  Corrected.
IPE-3445	When deploying a procedure in TIBCO Business Studio, the procedure inherited the access control settings of the deployer, instead of the predefined access control settings from the procedure library.
IPE-3452	When upgrading TIBCO iProcess Engine to 11.4.1, if the value you set for the NLS_TERRITORY parameter contained a space, the following error message was displayed:

Defect #	Description
	<p>WARNING: The NLS_LANG environment setting doesn't match the database's setting.</p> <p>Press Enter key to continue...</p> <p>Corrected.</p>
IPE-3455	<p>Add the sqloptim file, which is located in the SWDIR/etc directory, to optimize SQL statements execution.</p> <p>See <a href="#">Optimize SQL Statements Execution (IPE-3455)</a> .</p>
IPE-3458	<p>After upgrading TIBCO iProcess Engine from 11.1.1 to 11.4.1, the swdefs file was not successfully generated.</p>
IPE-3459	<p>When specifying values for fields in the case_data table, if <b>Support Unicode Encoding</b> was enabled and the length of the values exceeded the predefined size, the values were not truncated before they were stored in the table.</p>
IPE-3460	<p>When upgrading TIBCO iProcess Engine to 11.4.1 from any versions except for 11.4.0, an error occurred during creating indexes because the column name of table_owner in the user_indexes view was mistakenly replaced by the name of the database owner.</p> <p>Corrected.</p>
IPE-3463	<p>When you use the swutil PROC RELEASE command to release a version of a procedure with the -M ALL option, if the required libraries and the EAI plug-in were not loaded because of an EAI failure, the specified version of the procedure was released, but all the active cases were not migrated to the new version.</p>
IPE-3466	<p>When installing TIBCO iProcess Engine 11.4.1, if you used the TNSNames.ora file to connect to the database of which database type was Oracle Real Application Clusters, the following warning message was displayed in the sw_warn log file:</p> <p>Function loci_unsubscribe_event, Error Message OCISubscriptionUnRegister() failed.</p> <p>Corrected.</p>

Defect #	Description
IPE-3467	After forwarding work items to another queue, the Arrival-time attribute was not displayed correctly.
IPE-3468	Reduce the average time for a user to log in to TIBCO iProcess Engine node with many user groups and users created.  See <a href="#">Reduce Log in Time (IPE-3468)</a> .
IPE-3472	Add the MN_UNLOCKER process attribute to define who can have the permission to unlock work items.  See <a href="#">Unlock Work Items (IPE-3472)</a> .
IPE-3473	Add the WRITELOG function to write messages to log files.  See <a href="#">WRITELOG Function Introduced ( IPE-3473)</a> .
IPE-3476	Add support for defining the maximum size of log files.  See <a href="#">Define the Maximum Size of Log Files (IPE-3476)</a> .
IPE-3477	Add the WARN_ERROR_LOG_SIZE process attribute to define the maximum size of the sw_warn and sw_error log files.  See <a href="#">Define the Maximum Size of the sw_warn and sw_error Log Files (IPE-3477)</a> .
IPE-3480	Add the requestid as the unique identifier for each work item.  See <a href="#">Work Items Are Unique to Users (IPE-3480)</a> .
IPE-3486	When triggering a graft step, TIBCO iProcess Objects server crashed.
IPE-3491	When you use the SW_JUMPTO procedure to have a case jumped from its current step to another step in the sub-procedure if the case tag contained the main procedure name and the withdraw list was set to the asterisk (*) wildcard, the transaction failed and an error message was displayed in the sw_error file.
IPE-3496	The participation data within the WQS process was not unlocked after it was

Defect #	Description
	locked.  Monitor logic is added in the WQS process to accurately trace the locations where participation data is locked.
IPE-3497	The <code>sw_partic_unlock_external()</code> method was called to unlock a locker that was not created in the participation data.
IPE-3498	The <code>sw_partic_unlock_external()</code> method was not called to unlock a locker after the locker was created in the participation data.
IPE-3513	Change field data type in the database.  See <a href="#">Change Field Data Type (IPE-3513)</a> .
IPE-3536	Add the <code>W_DELAYED_RELEASE_ERR</code> stored procedure in the database and system-defined error message in the audit trail to trace delayed-release.  See <a href="#">Delayed Release Has Been Enhanced (IPE-3536)</a> .
IPE-3537	When installing TIBCO iProcess Engine, if you specified an incorrect password for the database user, no warning messages were displayed until the installation failed.
IPE-3538	When starting the iProcess Objects Server (SPO) process, the memory was rapidly consumed.
IPE-3539	IAP messages were not generated because the validation of the audit user failed.  Corrected.
IPE-3540	If you set the <code>IAPSCHEMA</code> parameter to 1 in the <code>staffcfg</code> file, the Background (BG) process failed to validate the audit user name for the activity and did not roll back the transaction.  Corrected.
IPE-3544	The <code>plist -M</code> command did not work because the iProcess foreground user ( database user) was used to connect to the database.

Defect #	Description
	Corrected.
IPE-3588	When migrating only live cases from swutil by running the <code>swutil PROC RELEASE -M</code> command, all cases (including close cases) were migrated.
IPE-3615	When the <code>MakeProc</code> function was called to return the minor version of a released procedure, if the major version and minor version parameters were both set to <code>-1</code> in the function, an incorrect procedure version was returned.
IPE-3624	The <code>CNUM_SEQ_CACHE</code> and <code>REQID_SEQ_CACHE</code> process attributes were not added into the upgrade scripts since TIBCO iProcess Engine 11.1.3.  Corrected.
IPE-3627	Upgrade Java 1.7 to new versions on the following platforms of iProcess Engine: <ul style="list-style-type: none"> <li>• Windows, Linux, and Solaris: 1.7.0.75</li> <li>• HP: 1.7.0.11</li> <li>• AIX: 7.0.0.195</li> </ul>
IPE-3629	When you use the <code>trigger</code> event function in a script step to change the value of a memo field, if the new value of the memo field exceeded 4096 characters, the memo data stored in the memo table was incorrect.
IPE-3641	When completing a delayed-release in TIBCO ActiveMatrix BusinessWorks, if the <code>SW_CP_VALUE</code> field was set to a value, the value of the message priority in TIBCO iProcess Engine was not changed.
IPE-3642	TIBCO iProcess Engine failed to insert the outstanding workitems information into the <code>outstanding_addr</code> table.
IPE-3650	Upgrade Tomcat to version 7.0.59.
IPE-3652 (Parent JIRA IPE-	When a dynamic sub-procedure call step started more than 300 sub-cases of the main procedure, the following error message was displayed in the <code>sw_error</code> log file:

Defect #	Description
3663)	write_pprs() Unable to execute statement(non-select) (Statement ID - 298) (ORA-00001: unique constraint (PK_OUTSTANDING_ADDR) violated)  Corrected.

# Restrictions

The table in this section lists known restrictions in this release.

Defect #	Summary/Workaround
IPE-3113	<p><b>Summary</b> An error occurs when loading XPDL for a procedure library with any new functionality into iProcess Workspace (Windows), if the procedure library is saved as XPDL from a later version of TIBCO iProcess Engine, and loaded into an earlier version of TIBCO iProcess Engine.</p> <p><b>Workaround</b> TIBCO does not recommend that you import procedures, which are exported from a later version of TIBCO iProcess Engine to an earlier version of TIBCO iProcess Engine.</p> <p>For more information, see <i>TIBCO iProcess swutil and swbatch Reference Guide</i>.</p>
MR 40988	<p><b>Summary</b> When a procedure is exported to an XPDL file from TIBCO iProcess Workspace (Windows), no list or table information is included.</p> <p><b>Workaround</b> None.</p>
MR 35194	<p><b>Summary</b> The iProcess Server Manager does not support language translation.</p> <p><b>Workaround</b> None.</p>
CR 19010	<p><b>Summary</b> If the WIS process handles an update event (such as, from a <code>\$SWDIR/bin/swutil EVENT -p \bin\swutil EVENT -p</code> command) while a user has a work item open, the <b>Case Description</b> and <b>WQ Parameters</b> revert to the values they had before the update when the work item is kept.</p> <p><b>Workaround</b> None.</p>
CR 18799	<p><b>Summary</b> If lots of MOVESYSINFO operations are being performed by BG processes, then the other processes that must recache the user/group information might fail due to becoming deadlocked.</p>

Defect #	Summary/Workaround
	<p>It is also possible that the caching process might load group membership or attribute values that do not match the attributes or queues loaded. This is because the caching process would first load the queues, then the attributes, and finally the attribute values. If a MOVESYSINFO changed the attribute values before they were loaded then they might not match the attributes that were loaded before the MOVESYSINFO.</p> <p><b>Workaround</b> Once all operations have been completed, modify the user/group area and perform one last MOVESYSINFO.</p>
CR 18631	<p><b>Summary</b> If you have an outstanding test mail item for an unreleased procedure and you delete the step from the procedure that the outstanding mail refers to, the test mail item can no longer be accessed. This is to be expected as the step has been deleted from the procedure. However, if you then purge the case for this inaccessible step the case is purged but the item is never removed from the message queue.</p> <p><b>Workaround</b> Clean up the item by using the <code>swutil CLEANITEM</code> command.</p>
CR 18614	<p><b>Summary</b> When a user logs in to the iProcess Workspace (Windows) test queues are not displayed in Work Queue Manager. This is because the user's personal work queue (from which the test queues are created) has not been cached yet.</p> <p><b>Workaround</b> If a new work item is sent to a test queue this causes the <b>Rebuild List</b> button to appear. Alternatively, the user can select their personal work queue and press <b>F5</b>. This also causes the <b>Rebuild List</b> button to appear. Clicking <b>Rebuild List</b> displays the test queues.</p>
CR 18361	<p><b>Summary</b> Performance on AIX systems can be very slow when opening cases from a queue.</p> <p><b>Workaround</b> If the SERVERRUN function is being used frequently in one or many procedures, the <code>\$SWDIR/lib/fil.so</code> file must be "pinned" into the AIX Shared Memory, by ensuring that all users have read and execute permissions on the file. To do this, use the command</p> <p><b>chmod 555 \$SWDIR/lib/fil.so</b></p>

Defect #	Summary/Workaround
CR 17669	<p><b>Summary</b> If you use iProcess activity monitoring on an iProcess Engine that uses a node cluster architecture, and you enable iProcess activity monitoring on the master node but not on one or more slave nodes, activity monitoring is disabled. (This is because the slave node settings contradict the master node settings.)</p> <p><b>Workaround</b> Make sure that you enable iProcess activity monitoring on <i>both</i> the master node <i>and</i> on each slave node when you install the iProcess Engine. See the <i>iProcess Engine Installation Guide</i> for more information about how to do this.</p>
CR 17603	<p><b>Summary</b> The J2EE standard supports the use of different security credentials (username and password) for JNDI InitialContext and JMS connections.</p> <p>However, in this version of iProcess Engine, you can only define a single username and password for the <b>IAPJMS</b> process. The process uses these credentials for both JNDI InitialContext and JMS connections.</p> <p>Note that the <b>IAPJMSConnect.SecurityPrinciple</b> property defines the username. The <b>IAPJMSConnect.SecurityCredentials</b> property defines the password. Both properties are defined in the <b>iapjms.properties</b> file. See Chapter 9, “Administering Activity Monitoring”, in the TIBCO iProcess Engine Administrator’s Guide for more information.</p> <p><b>Workaround</b> None.</p>
CR 17466	<p><b>Summary</b> If you use iProcess activity monitoring, Monitor Event Detail (MED) messages with <b>ActivityIDs 16, 19, 20, 25, 26, and 28</b> do not display the name of the audit user in the <b>&lt;AuditUser&gt;</b> element. Instead, they display information that depends on the particular message.</p> <p>For example, when a sub-procedure is started a MED message with <b>ActivityID = 16</b> is generated. The <b>&lt;AuditUser&gt;</b> element in this case shows the SubCaseID of the sub-case that has been started, not the name of the audit user, as shown .</p> <pre>&lt;AuditMessage&gt;Sub-Case started from "SUBCALL1"&lt;/AuditMessage&gt; &lt;AuditStep Name="SUBCALL1"&gt;</pre>

Defect #	Summary/Workaround
CR 16946	<div data-bbox="428 312 1336 512"> <pre> &lt;Description&gt;SUBCALL1&lt;/Description&gt; &lt;AuditDate Microseconds="545547"&gt;2005-08- 24T14:57:56&lt;/AuditDate&gt;  &lt;AuditUser&gt;:iPEPublication4:SUBPROC:1:201:201&lt;/AuditUser&gt; &lt;/AuditStep&gt; </pre> </div> <p><b>Workaround</b> None. If you require additional information about the contents of the &lt;AuditUser&gt; element for one of these messages, contact TIBCO Support.</p>
CR 16945	<p><b>Summary</b> The iProcess Engine uses the SHMKEY_ID process attribute value when building the UNIX shared memory key that is allocated when the WQS process is started. If a shared memory conflict occurs, resulting in the WQS process being unable to start, you can change the SHMKEY_ID value to resolve the problem.</p> <p>However, changing the value of the SHMKEY_ID process attribute has no effect in this version of the iProcess Engine. You cannot use SHMKEY_ID to resolve shared memory conflicts.</p> <p><b>Workaround</b> See <a href="#">CR 16945</a> on <a href="#">CR 16945</a> for more information about alternative ways of resolving shared memory conflicts.</p>
CR 16945	<p><b>Summary</b> If the WQS process (or other iProcess Engine process) cannot obtain a shared memory segment when the iProcess Engine attempts to start, startup fails. Error messages <b>1974</b> and <b>1975</b> are written to the \$SWDIR/<b>logs/sw_error</b> file, such as,</p> <div data-bbox="428 1381 1336 1581"> <pre> 2005/02/15 16:51:48 (WQS:1:18218:1:swadmin:/wqsindex.c:7.21:566): 1974-Failed to get shared memory handle for WQSINDEX 2005/02/15 16:51:48 (WQS:1:18218:1:swadmin:/wqsindex.c:7.21:677): 1975-WQS initialize failed, connected to shared memory for </pre> </div> <p><b>Workaround</b> For more information about how to resolve this problem, please see the description of these errors in the <i>iProcess Engine System Messages Guide</i>. Note that:</p>

Defect #	Summary/Workaround
	<ul style="list-style-type: none"> <li>You can force the iProcess Engine to obtain a new shared memory key when it starts up. To do this: Move the <b>/var/tmp/nodename</b> directory (where nodename is the nodename of this iProcess Engine) to another location on the same physical partition of the file system, such as, <b>/var/tmp/old/nodename</b>. Restart the iProcess Engine. The iProcess Engine must obtain a different shared memory key, allowing it to start successfully.</li> <li>If you set debugging for the WQS process, the <b>shmget</b> call returns error code <b>22</b>.</li> <li>Changing the value of the SHMKEY_ID process attribute has no effect in this iProcess Engine version. This is because of a current restriction in the product - see <a href="#">CR 16946</a> on <a href="#">CR 16946</a> for more information.</li> </ul>
CR 16878	<p><b>Summary</b> Filtering a view of a case via TIBCO iProcess Objects Server with a filter expression that uses a Question mark (?) or Asterisk (*) wildcard character to match against SW_CASEREF causes an error. A 'SAL System Error' message is returned to TIBCO iProcess Objects (COM).</p> <p><b>Workaround</b> None.</p>
CR 15531	<p><b>Summary</b> Adding a numeric user attribute with decimal places creates an attribute with 24 Characters and no decimal places.</p> <p>This happens if the attribute is added by using the iProcess Administrator or via \$SWDIR/bin/\bin\swutil <b>USERINFO</b>. For example, if you add a numeric attribute with length 10.2, it is created as a numeric attribute with length 24.0.</p> <p><b>Workaround</b> None.</p>
CR 15311	<p><b>Summary</b> The following fields do not appear in the <b>Available Fields</b> list of fields in the <b>Inputs</b> or <b>Outputs</b> tab for iProcess Engine plug-ins:</p> <ul style="list-style-type: none"> <li>SW_IP* Fields</li> <li>SW_STEPNAME</li> <li>SW_STEPDESC</li> </ul>

Defect #	Summary/Workaround
	<b>Workaround</b> None.
CR 14598	<p><b>Summary</b> When you map sub-procedure output parameters to main procedure fields, you can define a private <b>Output Mapping</b> script that runs after all the mappings have been performed (for example, to perform additional field manipulation). These output mapping scripts are ignored when performing case prediction.</p> <p><b>Workaround</b> None.</p>
CR 14597	<p><b>Summary</b> If a memo field is defined as an input or output parameter for a sub-procedure, it is ignored when performing case prediction - no data is passed for the field.</p> <p><b>Workaround</b> None.</p>
CR 14225	<p><b>Summary</b> When viewing cases, filter criteria that use the Question mark (?) (such as SW_CASENUM ? "2") or regular expressions use the same character (SW_CASENUM ? "1234?") fail.</p> <p><b>Workaround</b> Use one of the following two workarounds:</p> <ul style="list-style-type: none"> <li>• Use the Equal sign (=) instead, such as, SW_CASENUM = "2", or</li> <li>• Use an Asterisk (*) wildcard character in the regular expression, such as "1234*". This succeeds, but produces a wider range of results than the ? character must; any case number that starts with 1234 matches.</li> </ul>
CR 12037	<p><b>Summary</b> You must not use any of the following special characters when naming new groups, roles, lists or tables:</p> <p>" \ / [ ] : ;   = , + * ? &lt; &gt; @ \0 "</p> <p><b>Workaround</b> None.</p>
CR 12024	<p><b>Summary</b> When adding a group into the LDAP directory, if the group name is longer than 11 characters, the following information is displayed in the sw_warn log file:</p> <p>The length of the group name is limited to 15 characters.</p> <p><b>Workaround</b> None.</p>

# Known Issues

---

The following issues exist in this release of TIBCO iProcess Engine.

## Summary

**Summary** The iProcess Administration Console service fails to start if .archive file does not exist in *SWDIR*.

**Workaround** Ensure that you have .archive file in %SWDIR%\logs if the Administration Console service has to start from Windows Services.

**Summary** After installing TIBCO iProcess Engine with the Oracle database 11g, iProcess Engine cannot start, if the Oracle server and client have been installed on an x86 platform and a non-x86 platform respectively.

This is an Oracle defect. See Oracle Documentation 1306192.1 for more information.

**Workaround** Follow these steps:

1. Log in to SQLPlus using the system account.
2. Run the following statement:

```
alter system set events '10867 trace name context forever, level 1';
```

**Summary** On SUSE Enterprise Linux 11, RPC portmapper service is started by rpcbind by default, which causes TIBCO iProcess Engine to fail to start.

**Workaround** Switch to *portmap* to start RPC services by following these steps:

1. Run `/etc/init.d/rpcbind stop` to stop RPC services.
2. Get the portmap RPM installation file from SUSE Enterprise Linux 11 installation disk and install portmap.
3. Run `/etc/init.d/portmap start` to start RPC services.

Then, the iProcess Engine can start successfully.

**Summary** Work items cannot be seen in the work queue when configuring IAPJMS for JBoss.

---

**Summary**

**Workaround** Perform the following steps:

1. Copy `JBOSS_HOME/client/log4j.jar` to `$SWDIR/jar/thirdpart/`
2. Open the `SWDIR/etc/iapjms_classpath.properties` configuration file and replace `classpath.internal.log4j=thirdparty/log4j-1.2.8.jar` with `classpath.internal.log4j=thirdparty/log4j.jar`
3. Restart TIBCO iProcess Engine.

---

**Summary** The `PM_AUTO_BOOT` parameter must not be set in a cluster of the TIBCO iProcess Engine nodes.

**Workaround** Follow these steps to set the `PM_AUTO_BOOT` parameter and start the cluster:

1. Set the `PM_AUTO_BOOT` parameter to `0`.
2. Run `swstart -p` to start the sentinels on all nodes.
3. Run `swstart` to start TIBCO iProcess Engine on any node.

---

**Summary** If you select the option "User must change password at net logon" in Active Directory, and then sync to iProcess Engine, the user cannot log in to iProcess Engine.

**Workaround** None.

---

**Summary** Operating system dates later than 31st December 2037 are not supported.

Although designed to process dates up to the year 3000, the iProcess Suite has been modified - in the interests of data integrity - to shut down if the system date exceeds 31st December 2037.

The iProcess Suite uses the `time()` system call to get the system date and time. This call returns the system date and time as the number of seconds since midnight, 1st January 1970 as a signed integer (32-bits). This means that the `time()` function (which is commonly referred to as UNIX time) is unable to return a time beyond 19th January 2038, 03:14:07 UCT.

To protect the integrity of your iProcess installation, the iProcess Engine creates a file `$SWDIR/logs/sw_error\logs\sw_error` and shuts itself down if the system returns a date beyond 31 December 2037. Do not use operating system dates later than this. Potentially, ALL applications that use the time function are at risk beyond this date.

---

---

**Summary**

---

**Summary** Same user logged on multiple times causes degradation/possible errors.

The same user logging on multiple times to the same iProcess Engine might result in performance degradation. iProcess Engine allows only one transaction to be processed at a time for users that are logged on multiple times to that server, resulting in slower processing.

---

**Summary** Locking work items.

The SAL SDK allows long locking multiple times by the same user name. Consequently, in iProcess Engine, it is possible to lock the same work item from a work queue by using a different login session if there are two or more clients logged in as the same user name.

---

**Summary** Text field attribute lengths stored in multiples of 24.

All attributes except for text fields are set to a length of 24 if a length is not specified or if some length (up to 24) is specified. Decimal places are not stored.

For text fields, length is set to 24 if no length is specified. If a length is specified, the actual length is the next multiple of 24, up to the maximum length of 255. For example, creating a text field 25 characters long results in the field being 48 characters long.

---

**Summary** Audit filtering limitations on sub-cases.

When specifying an audit filter for a sub-case, or a parent case that contains a sub-case, the following limitation applies. If your filter criteria do not match the sub-case started audit entry in the parent case, no audit entries are returned for the sub-case, regardless of whether the filter criteria matches audit entries of the sub-case.

The workaround for this is to specify the following in your AuditFilterExpr filter expression:

```
FILTER_FLAGS=[AF_ALL_SUBSTART]
```

## Other Information

---

### Use \$SWDIR/util/plist

You can use the `$SWDIR/util/plist X\util\plist X` option to provide backward compatibility with Staffware 2000. For example, use `plist -pv` does not report counts, but you can use `plist -pvX` to specify Staffware 2000 compatibility so that counts are derived. Enter `$SWDIR/util/plist\util\plist` at the command line to display a full list of options.

### Number of File Descriptors per Process

The TIBCO iProcess Engine must be started with a sufficient number of available file descriptors per process based on the number of users. This is specified in the iProcess Engine using the NumFiles configuration parameter.

It is very difficult to know exactly how many files per user will be needed for the iProcess Engine since this number will vary depending on a number of factors that are unique to each site's procedures and transactions. The number of files could be as low as 4 files per user, but would not likely go above 12 files per user in a standard configuration. In addition, the iProcess Engine will use up to an additional 50 files independent of the number of users. Based on 1,000 users, the iProcess Engine would open somewhere from 4,050 to 10,150 files.

When the iProcess Engine is started, it attempts to set the number of files from the default number to the maximum number allowed. The default value can be displayed with the `ulimit -n` or `ulimit -Sn` commands ("S" indicating the "soft" or default limit). The maximum value can be displayed with the `ulimit -Hn` command ("H" indicating the "hard" or maximum limit).

The following formula can be used as a guideline to determine the number of file descriptors you need:

$$(12 * \text{Number of users}) + 100$$

For a default configuration, the default number of users is 1024, which means the upper file limit must be 12388  $((12 * 1024) + 100)$ .

The TIBCO iProcess Engine must be started by the background user (which defaults to "pro"), but only the superuser ("root") can increase the maximum ulimits. If the current per process maximum file limit is less than the number needed, either the number of open files per process must be raised for the entire system, or the root user can start a shell, increase the file limits for that shell, and then "su" to the background user. (The name of the background user is listed on the second line of the \$SWDIR/swdefs file.)

It is *highly* recommended that the file limit be set as high as possible since the iProcess Engine will immediately exit if there are no more file descriptors available. Running the command `ulimit -n unlimited` will set the file limit to the operating system design limits. This command will only be successful if the system limits allow this.

## Must Normalize Case Data to View Cases

When you install iProcess Engine, there is a check box in the Configuration window that is used to enable a feature called CaseData Normalization. If you use an application developed with iProcess Objects or iProcess Server Objects, you *must* enable case data normalization. If it is not enabled, cases do not appear in the case list.

Case data normalization can be enabled during the installation or at a later time by using the Case Data Normalization utility, `swnormcd`.

For more information about case data normalization and how to use `swnormcd`, see *TIBCO iProcess Engine Administrator's Guide*.

## Upgrading from Earlier Version Might Cause Error Messages in Log File

Upgrading from an earlier version of iProcess Engine to version i10.0 (0.0) or later might cause error messages similar to the following error messages to appear in the iProcess Engine log file:

```
ERROR|error in sal_pver_audlist procname($EMAIL) err(0) curridx(1)
ERROR|error in sal_pver_audlist procname($SYSTEM) err(0)
curridx(1)
```

```
ERROR|error in sal_pver_audlist procname(CARPOOL) err(0)  
curridx(1)
```

These messages are a result of the upgrade, but an error has not occurred. Disregard the messages.

# TIBCO Documentation and Support Services

---

For information about this product, you can read the documentation, contact TIBCO Support, and join TIBCO Community.

## How to Access TIBCO Documentation

Documentation for TIBCO products is available on the [TIBCO Product Documentation](#) website, mainly in HTML and PDF formats.

The [TIBCO Product Documentation](#) website is updated frequently and is more current than any other documentation included with the product.

## Product-Specific Documentation

Documentation for TIBCO iProcess® Engine is available on the [TIBCO iProcess® Engine Product Documentation](#) page.

To directly access documentation for this product, double-click the following file:

`TIBCO_HOME/release_notes/TIB_ipe_unix_oracle_11.9.0_docinfo.html` where `TIBCO_HOME` is the top-level directory in which TIBCO products are installed. On Windows, the default `TIBCO_HOME` is `C:\tibco`. On UNIX systems, the default `TIBCO_HOME` is `/opt/tibco`.

The following documents for this product can be found in the TIBCO Documentation site:

- *TIBCO iProcess® Engine Architecture Guide*
- *TIBCO iProcess® Engine Configuration Guide for Cloud*
- TIBCO iProcess® Engine Administrator's Guides:
  - *TIBCO iProcess® Engine Administrator's Guide*
  - *TIBCO iProcess® Objects Director Administrator's Guide*
  - *TIBCO iProcess® Objects Server Administrator's Guide*
  - *TIBCO iProcess® Engine Administration Console User Guide*
- TIBCO iProcess® Engine Database Administrator's Guides:
  - *TIBCO iProcess® Engine (DB2) Administrator's Guide*

*TIBCO iProcess® Engine (Oracle) Administrator's Guide*

*TIBCO iProcess® Engine (SQL) Administrator's Guide*

*TIBCO iProcess® swutil and swbatch Reference Guide*

- *TIBCO iProcess® Engine System Messages Guide*
- *TIBCO iProcess® User Validation API User Guide*
- *LDAPCONF Utility User Guide*

## How to Contact TIBCO Support

Get an overview of [TIBCO Support](#). You can contact TIBCO Support in the following ways:

- For accessing the Support Knowledge Base and getting personalized content about products you are interested in, visit the [TIBCO Support](#) website.
- For creating a Support case, you must have a valid maintenance or support contract with TIBCO. You also need a user name and password to log in to [TIBCO Support](#) website. If you do not have a user name, you can request one by clicking **Register** on the website.

## How to Join TIBCO Community

TIBCO Community is the official channel for TIBCO customers, partners, and employee subject matter experts to share and access their collective experience. TIBCO Community offers access to Q&A forums, product wikis, and best practices. It also offers access to extensions, adapters, solution accelerators, and tools that extend and enable customers to gain full value from TIBCO products. In addition, users can submit and vote on feature requests from within the [TIBCO Ideas Portal](#). For a free registration, go to [TIBCO Community](#).

# Legal and Third-Party Notices

---

SOME TIBCO SOFTWARE EMBEDS OR BUNDLES OTHER TIBCO SOFTWARE. USE OF SUCH EMBEDDED OR BUNDLED TIBCO SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED TIBCO SOFTWARE. THE EMBEDDED OR BUNDLED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER TIBCO SOFTWARE OR FOR ANY OTHER PURPOSE.

USE OF TIBCO SOFTWARE AND THIS DOCUMENT IS SUBJECT TO THE TERMS AND CONDITIONS OF A LICENSE AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED SOFTWARE LICENSE AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER LICENSE AGREEMENT WHICH IS DISPLAYED DURING DOWNLOAD OR INSTALLATION OF THE SOFTWARE (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH SOFTWARE LICENSE AGREEMENT OR CLICKWRAP END USER LICENSE AGREEMENT, THE LICENSE(S) LOCATED IN THE “LICENSE” FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of TIBCO Software Inc.

TIBCO, the TIBCO logo, the TIBCO O logo, ActiveMatrix BusinessWorks, Business Studio, Enterprise Message Service, Hawk, iProcess, and Rendezvous are either registered trademarks or trademarks of TIBCO Software Inc. in the United States and/or other countries.

Java and all Java based trademarks and logos are trademarks or registered trademarks of Oracle Corporation and/or its affiliates.

This document includes fonts that are licensed under the SIL Open Font License, Version 1.1, which is available at: <https://scripts.sil.org/OFL>

Copyright (c) Paul D. Hunt, with Reserved Font Name Source Sans Pro and Source Code Pro.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only.

This software may be available on multiple operating systems. However, not all operating system platforms for a specific software version are released at the same time. See the readme file for the availability of this software version on a specific operating system platform.

THIS DOCUMENT IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. TIBCO SOFTWARE INC. MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THIS DOCUMENT AT ANY TIME.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "READ ME" FILES.

This and other products of TIBCO Software Inc. may be covered by registered patents. Please refer to TIBCO's Virtual Patent Marking document (<https://www.tibco.com/patents>) for details.

Copyright © 1994-2022. TIBCO Software Inc. All Rights Reserved.