



TIBCO iProcess® Engine (Oracle)

Administrator's Guide

Version 11.9.1 | March 2024

Contents

Contents	2
The TIBCO iProcess® Engine Node	10
Table Relationships	10
nodes	11
Process Sentinels	15
Table Relationships	15
node_cluster	15
process_config	18
process_event_log	21
process_attributes	24
running_processes	27
active_logins	29
checksums	32
Mbox Sets and Message Queues	34
Table Relationships	34
iqf_queues	35
mbox_set	38
mbox_set_group	40
Oracle AQ Queue Tables and Queues	42
Sequence Numbers	48
About Sequence Numbers	48
Table Relationships	49
sequences	50
Procedures	53

Table Relationships	53
proc_index	54
iap_monitor	58
iap_field	60
iap_activity	62
iap_global	64
proc_version	66
procedure_lock	69
proc_instance	71
proc_audit	74
proc_defn	77
proc_deadline	81
proc_event	84
wqd_delta_subscriptions	87
Procedure Management	89
About Procedure Objects	89
Table Relationships	89
pm_objects	90
pm_objects_lock	93
pmobjects_security	96
proc_mgt_hierarchy	98
Cases	101
Table Relationships	101
case_information	102
outstanding_addr	106
wait	110
wait_step	113
status	115
case_data	118

audit_trail	121
memo	124
nmemo	128
predict	131
predict_lock	135
case_deadline_event	138
case_event	141
casenum_gaps	145
Work Items	148
Table Relationships	148
staffo	148
pack_data	153
pack_memo	156
pack_nmemo	159
qaccess	162
Case Data Queue Parameters	165
Table Relationships	165
cdqp_def	165
cdqp_cfg	167
Queue Participation and Redirection	170
Table Relationships	170
part_defn	170
part_list	173
redir_defn	175
Administrative Tables	178
Table Relationships	178
flag_table	178
version	181

Users and Work Queues	183
About User Tables	183
Table Relationships	183
user_names	184
user_attrib	187
user_setting	190
user_values	191
user_memb	194
leavers	196
tsys_user_names	199
tsys_user_attrib	199
tsys_user_values	200
tsys_user_memb	200
Roles	201
About Roles	201
Table Relationships	201
role_users	202
tsys_role_users	204
TIBCO iProcess Tables	206
About TIBCO iProcess Tables	206
Table Relationships	207
db_names	208
db_fields	210
db_values	213
tsys_db_names	215
tsys_db_fields	216
tsys_db_values	216
str_db_names	217
str_db_fields	217

ttmp_dbs_names	217
ttmp_dbs_fields	218
ttmp_dbs_values	218
Lists	219
About Lists	219
Table Relationships	220
list_names	220
list_values	223
tsys_list_names	225
tsys_list_values	225
ttmp_list_names	226
ttmp_list_values	226
iProcess Server Plug-ins	227
Table Relationships	227
eai_registry	227
Firewall Port Ranges	231
Table Relationships	231
port_range	232
port_range_active	235
port_range_conf	237
port_range_nodes	239
WQS/WIS Shared Memory	242
Table Relationships	242
wqs_index	242
System Event Logging	247
Table Relationships	247
system_event	247
system_event_conf	249

Monitoring	252
Table Relationships	252
stat_gen_mins	253
stat_gen_hours	256
stat_gen_daily	260
stat_mq_mins	264
stat_mq_hours	266
stat_mq_daily	268
stat_rp_mins	270
stat_rp_hours	273
stat_rp_daily	276
stat_vers_daily	279
stat_proc_daily	281
Views	284
STORAGE Configuration Macro Values	285
TABLESIZE	286
TABLEPCTINCREASE	286
INDEXSIZE	287
TABLESPACE	287
INDEXSPACE	287
AQTABLESPACE	288
SSOLite Stored Procedures	289
Overview	289
Using SSOLite Stored Procedures	290
Processing Asynchronous Message	290
Transactional Processing	290
Handling Exceptions	291
Processing Queues	293
Prioritizing Messages	294

Data Procedures	295
SW_ADD_PACK_DATA	295
SW_ADD_PACK_MEMO	297
SW_CLEAR_PACK_CACHE	298
SW_MODIFY_CASEDATA	299
Command Procedures	301
SW_AUDIT	301
SW_CASEREOPEN	303
SW_CASESTART	304
SW_CLOSE	306
SW_CLOSE_WITHOUT_EVENT	308
SW_DELAYED_RELEASE_ERR	309
SW_EVENT	310
SW_EVENT_UPDATE_PACK	312
SW_GETCASE_STATUS	313
SW_GETCASE_STATUS_EX	315
SW_GRAFT	316
SW_GRAFTCOUNT	318
SW_JUMPTO	319
SW_JUMPTO_MULTI	321
SW_PURGE	323
SW_PURGE_WITHOUT_EVENT	324
SW_SUSPEND	326
SW_ACTIVATE	327
Control Procedures	328
SW_ENABLECACHING	329
SW_DISABLECACHING	330
SW_SET_MBOX	330
SW_SET_PRIORITY	332
SW_SET_QUEUE	333
SW_UNSET_MBOX	334
SW_UNSET_PRIORITY	334

SW_UNSET_QUEUE	335
Debug Procedures	335
SW_SET_DEBUG	336
SW_GET_DEBUG	336
SW_CLEAR_DEBUG	337
Database Stored Procedures	338
Overview	338
CASENUM_FIND_GAPS	338
XPC_CREATE_INDEX	341
Unused Tables	344
TIBCO Documentation and Support Services	345
Legal and Third-Party Notices	347


The TIBCO iProcess® Engine Node

This section describes the table that is used to store information about the TIBCO iProcess® Engine node.

Table Relationships

The following diagram shows how the [nodes](#) table is related to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



nodes

The `nodes` table holds information about this iProcess Engine node. A node is a single logical iProcess Engine, which may be installed either on a single computer, or spread across several using a node cluster architecture.

Structure

The `nodes` table has the following structure:

TABLE nodes(

node_id	number(5)	NOT NULL,
node_name	varchar2(24)	NOT NULL,
dir_name	varchar2(28)	NOT NULL,
mail_addr	varchar2(149)	NULL,
mail_cert	varchar2(31)	NULL,
mail_type	number(5)	NOT NULL,
node_public	number(1)	NOT NULL,
node_slave	number(1)	NOT NULL,
node_deleted	number(1)	NOT NULL,
rpc_majvers	number(3)	NOT NULL,
rpc_minvers	number(3)	NOT NULL,
server_majvers	number(3)	NOT NULL,
server_minvers	number(3)	NOT NULL)

Column	Description
node_id	Unique ID of this iProcess node. Note: This value is always 1.
node_name	Logical name for this node.
dir_name	Name of the directory which holds the node's data (<i>SWDIR</i>).

Column	Description
mail_addr	<i>Not used. Reserved for possible future use.</i>
mail_cert	<i>Not used. Reserved for possible future use.</i>
mail_type	<i>Not used. Reserved for possible future use.</i>
node_public	<i>Not used. Reserved for possible future use.</i>
node_slave	<i>Not used. Reserved for possible future use.</i>
node_deleted	<i>Not used. Reserved for possible future use.</i>
rpc_majvers	<i>Not used. Reserved for possible future use.</i>
rpc_minvers	<i>Not used. Reserved for possible future use.</i>
server_majvers	<i>Not used. Reserved for possible future use.</i>
server_minvers	<i>Not used. Reserved for possible future use.</i>

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_nodes	node_id	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The nodes table contains one row, which is the entry for the iProcess Engine.

Rows are added, updated and deleted in the following situations.

Action	Description
added	never.
updated	never.
deleted	never.


Process Sentinels

This section describes the tables that are used to store information used by the Process Sentinels.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



node_cluster

The `node_cluster` table defines the server computers that make up this iProcess Engine node.

Structure

The node_cluster table has the following structure:

```
TABLE node_cluster(
  logical_machine_id          number(5)          NOT NULL,
  physical_machine_name       varchar2(256)       NOT NULL,
  master                      number(1)          NOT NULL,
  check_error_files           number(1)          NOT NULL,
  machine_comment             varchar2(256)       NULL)
```

Column	Description
logical_machine_id	Unique ID for this server.
physical_machine_name	If a UNIX server, the name of this server (as returned by the UNIX uname command). If a Windows server, then the name of this server or the Microsoft Windows cluster network name.
master	Flag that defines whether this computer is acting as the master server (1) or, if a node-cluster architecture is being used, as a slave server (0).
check_error_files	Flag that defines whether the Process Sentinels on this server check (1) or do not check (0) for the creation of <i>SWDIR\logs\sw_error</i> and <i>sw_warn</i> files.
machine_comment	Descriptive comment describing this server.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_node_cluster	logical_machine_id	TINYINDEXSPACE

Unique Key

The following unique key is defined for this table.

Key Name	Column(s)	Index Tablespace
unq_node_cluster	physical_machine_name	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The node_cluster table contains one row for each server computer that is part of the iProcess Engine node.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new server is added to the node, either at installation or by using the <code>SWDIR\util\swadm</code> utility.
updated	a server's details are updated, using the <code>SWDIR\util\swadm</code> utility.
deleted	a server is removed from the node, using the <code>SWDIR\util\swadm</code> utility.

process_config

The `process_config` table stores information about each process *instance* that is defined on the system.

Multiple instances of each server process can be used to optimize iProcess Engine efficiency - for example, to increase the processing capability on one server, or to spread the processing load across multiple servers.

Structure

The `process_config` table has the following structure:

```
TABLE process_config(
```

<code>logical_machine_id</code>	<code>number(5)</code>	<code>NOT NULL,</code>
<code>logical_process_name</code>	<code>varchar2(10)</code>	<code>NOT NULL,</code>
<code>logical_process_instance</code>	<code>number(5)</code>	<code>NOT NULL,</code>
<code>enabled</code>	<code>number(1)</code>	<code>NOT NULL,</code>
<code>persistent</code>	<code>number(1)</code>	<code>NOT NULL,</code>

last_known_status	varchar2(20)	NOT NULL,
status_comment	varchar2(255)	NULL)

Column	Description
logical_machine_id	ID of the server where this process instance runs, as defined in the node_cluster table.
logical_process_name	Logical name of this process instance. Note: For a list of logical process names, see the "Administering iProcess Engine Server Processes" topic in <i>TIBCO iProcess Engine Administrator's Guide</i> .
logical_process_instance	Unique ID for this process instance.
enabled	Flag that defines whether this process instance starts automatically (1) when the iProcess Engine starts, or whether it must be started manually (0).
persistent	Flag that defines whether this process instance is automatically restarted (1) or not (0) when the iProcess Engine is shut down and restarted. Note: Any row in which the persistent value is 0 is deleted when the iProcess Engine starts up.
last_known_status	Last known status of this process instance, as reported to the Process Sentinels by the process. Either: STARTING, RUNNING, PAUSED, SUSPENDED, SHUTTING DOWN or STOPPED. Note: The process_event_log table provides an audit trail of changes to the status of a process instance.
status_comment	Brief explanation of the last_known_status, as reported to the Process Sentinels by the process.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_process_config	logical_machine_id logical_process_name logical_process_instance	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_process_config ¹	logical_machine_id	node_cluster

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_process_config_fk	logical_machine_id	SMALLINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE

¹This key enforces the DELETE CASCADE referential action.

Value	Definition
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `process_config` table contains one row for each instance of each server process defined on the system.

Rows are added, updated, and deleted in the following situations.

A row is...	When...
added	a new process instance is added, either at installation or by using the <code>SWDIR\util\swadm</code> , <code>SWDIR\util\swsvrmgr</code> utilities.
updated	a process instance's settings or status are updated, either by system activity, or by using the <code>SWDIR\util\swadm</code> or <code>SWDIR\util\swsvrmgr</code> utilities.
deleted	a process instance is deleted, either at installation or by using the <code>SWDIR\util\swadm</code> or <code>SWDIR\util\swsvrmgr</code> utilities.

process_event_log

The `process_event_log` table logs all changes in the status of server process instances.

Structure

The `process_event_log` table has the following structure:

TABLE process_event_log

logical_machine_id	number(5)	NOT NULL,
logical_process_name	varchar2(10)	NOT NULL,
logical_process_instance	number(5)	NOT NULL,
process_id	number(10)	NOT NULL,
process_status	number(5)	NOT NULL,
process_status_comment	varchar2(255)	NULL,
timestamp	date	NOT NULL)

Column	Description
logical_machine_id	ID of the server where the process instance that this event applies to is running, as defined in the node_cluster table.
logical_process_name	Logical name of the process that this event applies to. Note: See "Administering iProcess Engine Server Process" in <i>TIBCO iProcess Engine Administrator's Guide</i> for a list of logical process names.
logical_process_instance	ID of the process instance that this event applies to, as defined in the process_config table.
process_id	Process ID (PID) of the process instance that this event applies to.
process_status	Status change event that occurs for the specified process instance. One of the following: <ul style="list-style-type: none"> 3000 - process instance started. 3001 - process instance stopping.

Column	Description
	<ul style="list-style-type: none"> • 3002 - process instance stopped. • 3003 - process instance died. • 3004 - process instance paused. • 3005 - process instance unpaused.
process_status_comment	Description of the process_status entry, as reported to the Process Sentinels by the process.
timestamp	Date and time that this event occurred.

Primary Key

None.

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `process_event_log` table contains one row for each status change event that has occurred to each instance of a server process.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a process starts, receives a shutdown command, or shuts down.
updated	never.
deleted	never.

Note: Because rows are never deleted automatically, TIBCO recommend that you regularly monitor the size of this table and delete or archive rows manually if you need to.

process_attributes

The `process_attributes` table stores process attribute definitions, which provide configuration information for iProcess Engine server processes.

Structure

The `process_attributes` table is structured as follows:

```
TABLE process_attributes (
  logical_machine_id      number(5)      NOT NULL,
  logical_process_name    varchar2(10)   NOT NULL,
  logical_process_instance number(5)      NOT NULL,
```


attribute_name	varchar2(50)	NOT NULL,
attribute_value	varchar2(1024)	NOT NULL,
attribute_type	varchar2(2)	NOT NULL)

Column	Description
logical_machine_id	<p>ID of the server where the process instance that this attribute applies to is running, as defined in the node_cluster table.</p> <p>A value of 0 means that this attribute applies to all servers that are part of this node.</p>
logical_process_name	<p>Logical name of the process that this attribute applies to.</p> <p>A value of ALL means that this attribute applies to all processes on the indicated server.</p> <p>Note: See "Administering iProcess Engine Server Processes" in <i>TIBCO iProcess Engine Administrator's Guide</i> for a list of logical process names.</p>
logical_process_instance	<p>ID of the process instance that this attribute applies to, as defined in the process_config table.</p> <p>A value of 0 means that this attribute applies to all instances of the indicated process.</p>
attribute_name	<p>Name of this process attribute.</p> <p>Note: See "Administering Process Attributes" in <i>TIBCO iProcess Engine Administrator's Guide</i> for a list of the available process attributes.</p>
attribute_values	<p>Value of this process attribute.</p> <p>Note: See "Administering Process Attributes" in <i>TIBCO iProcess Engine Administrator's Guide</i> for a list of the valid values for each process attributes.</p>
attribute_type	<p>Type of this process attribute: either I (Integer), c (Character) or s (String).</p> <p>Note: All attribute_values are stored as strings in this table. This value determines how the value is returned to the <i>SWDIR\bin\swadm</i> interface.</p>

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_process_attributes	logical_machine_id logical_process_name logical_process_instance attribute_name	SMALLINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The process_attribute table contains one row for each unique definition of a process attribute on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new process attribute definition is added, either at installation or by using the <i>SWDIR\util\swadm</i> utility.
updated	a process attribute definition is updated, using the <i>SWDIR\util\swadm</i> utility.
deleted	a process attribute definition is deleted, using the <i>SWDIR\util\swadm</i> utility.

Note	This table can contain orphan rows in which data can exist that does not apply to any process currently being used.
-------------	---

running_processes

The `running_processes` table stores information about each process instance that is currently running on the system.

Structure

The `running_processes` table has the following structure:

```
TABLE running_processes (
  logical_machine_id      number(5)          NOT NULL,
  logical_process_name    varchar2(10)       NOT NULL,
  logical_process_instance number(5)          NOT NULL,
  process_id              number(10)         NOT NULL,
  port_number              number(5)          NOT NULL)
```

Column	Description
<code>logical_machine_id</code>	ID of the server where this process instance is running, as defined in the node_cluster table.
<code>logical_process_name</code>	Logical name of this process instance.

Column	Description
	Note: See "Administering iProcess Engine Server Processes" in <i>TIBCO iProcess Engine Administrator's Guide</i> for a list of logical process names.
logical_process_instance	ID of this process instance, as defined in the process_config table.
process_id	Process ID (PID) of this process instance.
port_number	Port number that this process instance is running on.

Primary Key

None.

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `running_processes` table contains one row for each instance of an iProcess Engine server process that is currently running on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new process instance is started.
updated	a process instance is restarted (<code>process_id</code> and <code>port_number</code> are updated).
deleted	a process instance is stopped.

active_logins

The `active_logins` table stores details of all users who are currently logged in to this iProcess Engine node.

Structure

The `active_logins` table has the following structure:

```
TABLE active_logins(
  logical_machine_id      number(5)          NOT NULL,
  logical_process_name    varchar2(10)       NOT NULL,
  logical_process_instance number(5)          NOT NULL,
  user_name               varchar2(64)       NOT NULL,
  user_id                 varchar2(37)       NOT NULL,
  process_id              number(10)         NOT NULL,
  filsh                   number(5)          NOT NULL,
  windows                 number(2)          NOT NULL,
  station_id              varchar2(32)       NOT NULL)
```

Column	Description
<code>logical_</code>	ID of the server where the process that made the login request is running, as

Column	Description
machine_id	defined in the node_cluster table.
logical_process_name	Logical name of this process instance. Note: See "Administering iProcess Engine Server Processes" in <i>TIBCO iProcess Engine Administrator's Guide</i> for a list of logical process names.
logical_process_instance	ID of this process instance, as defined in the process_config table.
user_name	Name of the user who is logged in, as defined in the user_names table.
user_id	ID of the user who made the login request (for internal use only).
process_id	Process ID (PID) of the process that made the login request.
filsh	FIL session handle (for internal use only).
windows	Flag that defines whether the login request came from TIBCO iProcess Objects (0) or from an TIBCO iProcess® Workspace or other SAL application (1).
station_id	Comment that identifies where a user is logged in.

Primary Key

None.

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_active_logins ¹	logical_machine_id	node_cluster

¹This key enforces the DELETE CASCADE referential action.

Indexes

The following indexes are defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_active_logins_fk	logical_machine_id	SMALLINDEXSPACE
idx_active_logins	user_id	MEDIUMINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The active_logins table contains one row for each user who is currently logged into this iProcess Engine node.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a user is logged in.
updated	never.
deleted	a user is logged out or the iProcess Engine shuts down.

checksums

The checksums table is used internally by the iProcess Engine to provide security checks on the [active_logins](#) and [port_range](#) tables.

Structure

The checksums table has the following structure:

```
TABLE checksums (
```

area_id	number(5)	NOT NULL,
area_name	varchar2(20)	NOT NULL,
check_sum	varchar2(54)	NOT NULL)

Column	Description
area_id	Unique ID of the area using this checksum
area_name	Name of the area using this checksum. Currently this is always PORT RANGING.
check_sum	Encrypted checksum for the indicated area.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_checksums	area_id	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The checksums table contains one row for each checksum used internally by the iProcess Engine.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	the iProcess Engine is started.
updated	a login is performed.
deleted	never.

Mbox Sets and Message Queues


This section describes the tables that are used to control the behavior of the message queuing system.

It also describes the [Oracle AQ Queue Tables and Queues](#), which provide the underlying message queuing system used by the iProcess message queues.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



iqL_queues

The `iqL_queues` table defines each message queue that is available on this iProcess Engine node.

Structure

The `iqL_queues` table has the following structure:

```
TABLE iqL_tables (
  queue_id          number(5)          NOT NULL,
  queue_name        varchar2(24)       NOT NULL,
  queue_type        number(2)          NOT NULL,
  queue_phys_descr  varchar2(100)      NOT NULL)
```

Column	Description
<code>queue_id</code>	Unique identifier for this message queue.
<code>queue_name</code>	Name of this message queue.
<code>queue_type</code>	Message type used by this message queue. This value is always 1, for local messages.
<code>queue_phys_descr</code>	ID of the Oracle AQ queue that is used to hold this message queue. See: Format of the Oracle AQ QueueID for a description of the format used for this value. Oracle AQ Queue Tables and Queues for more information about the required structure of AQ queue tables and queues, and how to create them.

Format of the Oracle AQ QueueID

The ID of the Oracle AQ queue that is used to hold this message queue (in the `queue_phys_descr` column) is specified using the following format:

```
0001:[instance]:queue_table:queue
```

where:

- 0001 indicates that the remainder of the string uses Oracle AQ format.
- *instance* is the Oracle Service Name of the Oracle instance that holds the AQ queue. If this is blank, the default local instance is assumed.
- *queue_table* is the name of the AQ queue table that holds the AQ queue.
- *queue* is the name of the AQ queue used to hold this message queue.

For example, the entry:

```
0001::bgmboxtable1:bgmboxqueue1
```

describes the AQ queue called bgmboxqueue1 contained in queue table bgmboxtable1 on the default Oracle instance.

Default Message Queues and AQ Tables

When the iProcess Engine is installed, the init2Kora.sql (on UNIX, or on Windows init2Kora_tok.sql) script creates the following default set of message queues and AQ queue tables required by the system.

Queue Name	Oracle AQ Queue ID
BGMBOX1	0001::bgmboxtable1:bgmboxqueue1
BGMBOX2	0001::bgmboxtable2:bgmboxqueue2
WISMBBOX1	0001::wismboxtable1:wismboxqueue1
WISMBBOX2	0001::wismboxtable2:wismboxqueue2
PREDICTMBOX1	0001::predictmboxtable1:predictmboxqueue1
PREDICTMBOX2	0001::predictmboxtable2:predictmboxqueue2

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_iql_queues	queue_id	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The iql_queues table contains one row for each message queue that is available on this node.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new message queue is added to the node, either at installation or by using the <i>SWDIR\util\swadm</i> utility.
updated	a message queue's details are updated, using the <i>SWDIR\util\swadm</i> utility.

A row is...	When...
deleted	a message queue is deleted from the node, using the <i>SWDIR\util\swadm</i> utility.

mbox_set

The `mbox_set` table defines the list of Mbox sets that are available on this iProcess Engine node.

Structure

The `mbox_set` table has the following structure:

```
TABLE mbox_set (
  mbox_set_id      number(5)          NOT NULL,
  mbox_set_name    varchar2(32)      NOT NULL,
  mbox_set_msgtype number(2)          NOT NULL)
```

Each row provides the following information about a Mbox set.

Column	Description
<code>mbox_set_id</code>	Unique identifier for this Mbox set.
<code>mbox_set_name</code>	Name of this Mbox set.
<code>mbox_set_msgtype</code>	Message type used by this Mbox set. This value is always 1, for local messages.

Default Mbox Sets and Message Queues

When the iProcess Engine is installed, the `init2Kora.sql` (on UNIX, or on Windows `init2Kora_tok.sql`) script creates the following default Mbox sets that are required by the system. (The [mbox_set_group](#) table defines which message queues are stored in which Mbox set.)

Mbox Set	Contains these message queues
BGMBSET	BGMBBOX1, BGMBBOX2
WMDMBSET	WISMBBOX1, WISMBBOX2
PREDICTMBSET	PREDICTMBOX1, PREDICTMBOX2

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_mbox_set	mbox_set_id	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The `mbox_set` table contains one row for each Mbox set that is available on this iProcess Engine node.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new Mbox set is added to the node, either at installation or by using the <code>SWDIR\util\swadm</code> utility.
updated	an Mbox set's details are updated, using the <code>SWDIR\util\swadm</code> utility.
deleted	an Mbox set is deleted from the node, using the <code>SWDIR\util\swadm</code> utility.

mbox_set_group

The `mbox_set_group` table defines the list of individual message queues that are stored in each Mbox set.

Structure

The `mbox_set_group` table has the following structure:

```
TABLE mbox_set_group (
  mbox_set_id      number(5)          NOT NULL,
  mbox_queue_id    number(5)          NOT NULL)
```

Column	Description
<code>mbox_set_id</code>	Unique identifier of the Mbox set that contains the associated message queue, as defined in the mbox_set table.
<code>mbox_queue_id</code>	Unique identifier of the message queue that is included in the associated Mbox set, as defined in the iql_queues table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_mbox_set_group	mbox_set_id mbox_queue_id	TINYINDEXSPACE

Foreign Keys

The following foreign keys are defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_mbox_set_id ¹	mbox_set_id	mbox_set
fk_mbox_queue_id	queue_id	iql_queues

Indexes

The following indexes are defined for this table.

Index Name	Indexed Column(s)	Tablespace
idx_mbox_set_id_fk	mbox_set_id	TINYINDEXSPACE
idx_mbox_queue_id_fk	mbox_queue_id	TINYINDEXSPACE

Storage

The following STORAGE values are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The `mbox_set_group` table contains one row for each message queue that is available on this node.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new message queue is added to the node, either at installation or by using the <code>SWDIR\util\swadm</code> utility.
updated	never.
deleted	a message queue is deleted from the node, using the <code>SWDIR\util\swadm</code> utility.

Oracle AQ Queue Tables and Queues

Oracle Advanced Queuing (AQ) provides the underlying message queuing system used by the iProcess message queues. Each message queue defined in the [iql_queues](#) table must be mapped to an AQ queue, which in turn must be stored in an AQ table.

When iProcess Engine is installed, the `init2Kora.sql` script (on UNIX, or on Windows `init2Kora_tok.sql`) creates the default set of AQ tables, queues and object types required by the system (see [Default Message Queues and AQ Tables](#).)

i Note: The `init2Kora.sql` script (on UNIX, or `init2Kora_tok.sql` on Windows) also creates a non-persistent Oracle AQ queue called `sw_system_events`. This queue is used to route all iProcess events to the iProcess event manager. (iProcess event management is provided by the Oracle Event Manager on UNIX, and by the iProcess Events COM+ application on Windows.)

If you subsequently decide to add additional message queues, you must use the Oracle DBMS_AQADM package to manually create the Oracle AQ queue tables and queues needed by those message queues. The following sections explain how to do this.

i Note: For a detailed description of the DBMS_AQADM package procedures referred to in this section, see the *Oracle9i Supplied PL/SQL Packages and Types Reference* guide in your Oracle documentation set.

SWLOCALMSG Object Type

An AQ queue table must be associated with one particular message type, which must already exist when you create the AQ queue table.

All AQ queue tables used by the iProcess Engine must use the SWLOCALMSG object type, which is created when the iProcess Engine is installed.

```
CREATE TYPE TABLE_OWNER.SWLOCALMSG AS OBJECT (
  msginfo          VARCHAR2(500),
  node             varchar2(24),
  contenttype      number(2),
  data             VARCHAR2(1000)
);
```

AQ Queue Tables

Use the DBMS_AQADM.CREATE_QUEUE_TABLE procedure to create an AQ queue table. The following parameters are required.

Column	Description
<code>queue_table</code>	Unique name of this queue table.

Column	Description
	This name is used in the <code>queue_phys_descr</code> column of the iql_queues table.
<code>queue_payload_type</code>	Object type of data stored by this queue table. This value must be <code>swlocalmsg</code> .
<code>storage_clause</code>	<p>Tablespace to be used by this queue table.</p> <p>Note: Each queue table can be associated with a different tablespace, which in turn can be associated with a different datafile. Distributing queue tables in this way provides an easy way of reducing I/O contention and optimizing performance. See STORAGE Configuration Macro Values for more information.</p>
<code>sort_list</code>	Sort criteria by which messages are sorted in ascending order and dequeued based on this order.
<code>comment</code>	Description of this queue table.
<code>compatible</code>	Lowest database version that this queue table is compatible with. This value must be 8.1.

The following example, from the `init2Kora.sql` script, shows the SQL used to create one of the default background Mbox tables that is created when the iProcess Engine is installed.

```
DBMS_AQADM.CREATE_QUEUE_TABLE (
  queue_table => 'TABLE_OWNER.bgmboxtable1',
  queue_payload_type => 'TABLE_OWNER.swlocalmsg',
  sort_list => ' priority, enq_time',
  storage_clause => 'tablespace AQTABLESPACE',
  comment => 'default background mbox',
  compatible => '8.1');
```

AQ Queues

Perform the following steps to create a AQ queue and make it available for use as an iProcess message queue:

1. Use the `DBMS_AQADM.CREATE_QUEUE` procedure to create the AQ queue. The following parameters are required.

Column	Description
<i>queue_name</i>	Unique name of this queue. This name is used in the queue_phys_descr column of the iql_queues table.
<i>queue_table</i>	Name of the queue table that holds this queue. This name is used in the queue_phys_descr column of the iql_queues table. Note: Multiple queues can be stored in the same queue table.
<i>retry_delay</i>	Delay time, in seconds, before a message is scheduled for processing again after an application rollback.
<i>max_retries</i>	Number of times that a dequeue with the REMOVE mode can be attempted on a message. The count is incremented when the application issues a rollback after executing the dequeue. The message is moved to the default exception queue when it reaches its max_retries.

The following example, from the `init2Kora.sql` script, shows the SQL used to create one of the default background Mbox queues that is created when the iProcess Engine is installed.

```
DBMS_AQADM.CREATE_QUEUE (queue_name => 'TABLE_OWNER.bgmboxqueue1',
queue_table => 'TABLE_OWNER.bgmboxtable1', retry_delay => 300, max_retries =>
12);
```

2. Use the `DBMS_AQADM.START_QUEUE` procedure to start the queue.
3. Use the `DBMS_AQADM.GRANT_QUEUE_PRIVILEGE` procedure to grant the privileges on the queue. The following parameters are required.

Column	Description
<i>privilege</i>	The AQ queue privilege to grant. This value must be ALL (which means

Column	Description
	both ENQUEUE and DEQUEUE).
<i>queue_name</i>	Name of the queue.
<i>grantee</i>	Grantee. This value must be the name of the iProcess Oracle Foreground user. Note: The Oracle Foreground user is defined in the third entry (after the second backslash character) on line 9 of the <i>SWDIR\etc\staffpms</i> file. For example: 3\swpro\swuser\swpro\staffdb1\10\0
<i>grant_option</i>	Defines whether the access privilege is granted with the GRANT option or not. This value must be false.

The following example, from the `init2Kora.sql` script, shows the SQL used to grant the required privileges on one of the default background Mbox queues that is created when the iProcess Engine is installed.

```
dbms_aqadm.grant_queue_privilege (privilege => 'all', queue_name =>
'TABLE_OWNER.bgmboxqueue1', grantee => 'BACKGROUND_USER', grant_option =>
false )
```

Example

Suppose that the volume of messages handled by your system has increased significantly, and the default messages queues can no longer cope. To deal with the additional load you have decided that you need to add a new BGMBX3 message queue to the BGMBSET Mboxset. This queue requires a new bgmboxqueue3 Oracle AQ queue and bgmboxtable3 queue table.

Note: This example uses UNIX syntax.

To do this:

1. Use SQLPLUS to connect to the Oracle instance.

```
$ORACLE_HOME/bin/sqlplus
connect swpro/staffpro1;
```

2. Create an AQ queue table called bgmboxtable3.

```
EXECUTE DBMS_AQADM.CREATE_QUEUE_TABLE (queue_table =>
'swpro.bgmboxtable3', queue_payload_type => 'swpro.swlocalmsg', comment =>
'3rd background mbox', compatible => 8.1);
```

3. Create an AQ queue called bgmboxqueue3 in this queue table.

```
EXECUTE DBMS_AQADM.CREATE_QUEUE (queue_name => 'swpro.bgmboxqueue3',
queue_table => 'swpro.bgmboxtable3', retry_delay => 300, max_retries => 12);
```

4. Start the bgmboxqueue3 queue.

```
EXECUTE DBMS_AQADM.START_QUEUE (queue_name => 'swpro.bgmboxqueue3');
```

5. Grant the required privileges on the bgmboxqueue3 queue.

```
EXECUTE dbms_aqadm.grant_queue_privilege (privilege => 'all', queue_name =>
'bgmboxqueue3', grantee => 'swuser', grant_option => false );
```

6. Commit the changes, disconnect and exit.

```
commit;
disconnect;
exit;
```

7. Use the `$SWDIR\util\swadm` utility to add a new message queue called BGMBX3, which uses the bgmboxqueue3 queue.

```
cd $SWDIR/util
swadm ADD_QUEUE BGMBX3 Local 0001::bgmboxtable3:bgmboxqueue3
```

8. Add the BGMBX3 queue to the BGMBSET Mbox set.

```
swadm ADD_QUEUE_TO_MBOXSET 1 8
```

1 is the number of the BGMBSET Mboxset (from the `swadm SHOW_MBOXSETS` command) and 8 is the number of the message queue (from the `swadm SHOW_QUEUES` command).

Sequence Numbers

This section describes *sequence numbers* - unique numbers that are used by TIBCO iProcess® Engine server processes, and the table that is used to generate them.

About Sequence Numbers

A *sequence number* is simply a unique identifier for an object. TIBCO iProcess® Engine uses six different types of sequence number, as shown in the following table.

Sequence Number	Stored in table...	Unique identifier for a...
o_reqid	staffo	Work item
casenum	case_information	Case
proc_id	proc_index	Procedure
wait_id	wait	Outstanding Wait
def_id	cdqp_def	CDQP definition
cfg_id	cdqp_cfg	CDQP value
monitor_id	iap_monitor	Procedure that IAP is monitoring
provider_id	eaiws_jms_provider1	JMS provider
destination_id	eaiws_jms_destination2	JMS endpoints for JMS provider

These sequence numbers are generated on an “as required” basis by iProcess Engine, which calls one of the following stored database procedures:

¹Only created if TIBCO iProcess Technology Plug-ins are installed.

²

- `sp_cdqp_cfg_sequence`
- `sp_cdqp_def_sequence`
- `sp_cnum_sequence`
- `sp_procid_sequence`
- `sp_reqid_sequence`
- `sp_waitid_sequence`
- `sp_iap_monitor_id_sequence`
- `sp_eaiws_jms_provider_seq`
- `sp_eaiws_jms_destination_seq`

The procedure accesses the `sequences` table, increments the value of the `seq_val` column for the appropriate row, identified by the `seq_id` column, and returns that value. The returned value is then used as the next sequence number in the appropriate table.



Note: For more information about these stored procedures please see the database creation script (`init2Kora.sql` on UNIX, `init2Kora_tok.sql` on Windows).

However, getting sequence numbers directly from the database in this way can create a performance bottleneck, because while one process is requesting a number it must block any other process from attempting to do so.

To minimize the effect of this bottleneck, you can assign a cache of a block of sequence numbers to a process, by using process attributes. The process gets a sequence number from its cache when it needs one, and only accesses the database to refresh the cache when it has run out of numbers. For more information, see "Sequence Caching" in *TIBCO iProcess Engine Administrator's Guide*.

Table Relationships

The [sequences](#) table has no database-enforced relationships, that is, foreign keys, with other tables.

sequences

The sequences table is used to generate unique sequence numbers for the use of TIBCO iProcess® Engine server processes.

Structure

The sequences table has the following structure:

```
TABLE sequences (
    seq_id          number(5)          NOT NULL,
    seq_val         number(20)         NOT NULL,
    seq_name        varchar2(24)       NOT NULL)
```

Column	Description
seq_id	Sequence ID of the associated seq_val value. One of the following values: 1 (o_reqid) 2 (casenum) 3 (proc_id) 4 (wait_id) 5 (def_id) 6 (cfg_id)
seq_val	Current sequence number value for the sequence defined by seq_id.
seq_name	Name of the associated seq_id column. One of the following values: REQID CNUM PROC WAIT CDQP_DEF CDQP

Column	Description
Note: This value is not currently used by the iProcess Suite.	

Primary Key

None.

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

This table always contains 6 rows—one row for each type of sequence number used by the iProcess Engine server processes. The table is populated when the iProcess Engine is installed.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	never.
updated	when a new sequence number of that type is requested.
deleted	never.


Procedures

This section describes the tables that are used to store information about iProcess procedures, sub-procedures and sub-procedure parameter templates.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships(foreign keys), are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



proc_index

The `proc_index` table holds information that is specific to a procedure (or sub-procedure or sub-procedure parameter template).



Note

Data that can change between versions or instances of a procedure is not held in this table. See the [proc_version](#) and [proc_instance](#) tables instead.

Structure

The `proc_index` table has the following structure:

```
TABLE proc_index (
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  proc_used_count  number(5)          NOT NULL,
  proc_name        varchar2(8)        ,
  proc_desc        varchar2(24)       ,
  proc_owner       varchar2(24)       ,
  dir_name         varchar2(12)       ,
  proc_used        number(1)          NOT NULL,
  work_days        number(1)          NOT NULL,
  auto_purge       number(1)          NOT NULL,
  networked        number(1)          NOT NULL,
  cdesc_type       number(1)          NOT NULL,
  ignore_blanks    number(1)          NOT NULL,
  is_predict       number(1)          NOT NULL,
  normalise_data   number(1)          NOT NULL,
  delay_purge      number(1)          NOT NULL,
  delay_value      varchar(512)       NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this procedure is defined on, as defined in the nodes table.
<code>proc_id</code>	Unique ID of this procedure, generated from the sequences table.
<code>proc_used_count</code>	Not used.

Column	Description
proc_name	Name of this procedure. Note: Internal procedures are prefixed with a dollar sign (\$) character.
proc_desc	Description of this procedure.
proc_owner	Name of the owner of this procedure, as defined in the user_names table.
dir_name	Not used.
proc_used	Flag that defines whether this record is currently free (0) or being used (1).
work_days	Flag that defines whether the procedure uses a 7-day week (0) or a configurable working week (1) in date calculations.
auto_purge	Flag that defines whether (1) or not (0) cases of this procedure are automatically purged when they are closed.
networked	<i>Reserved for possible future use.</i>
cdesc_type	Flag that defines whether a case description is Required (0), Optional (1) or Hidden (2) when a case of this procedure is started.
ignore_blanks	Flag that defines whether or not a blank field is treated as an error when used as an addressee for a step of this procedure: <ul style="list-style-type: none"> 0 means that the field is treated as an error and the step is delivered to the undelivered queue. 1 means that the field is not treated as an error.
is_predict	Flag that defines whether (1) or not (0) case prediction is enabled for this procedure.
normalise_data	Flag that defines whether (1) or not (0) case data normalization is enabled for this procedure.
delay_purge	Flag that defines whether or not to delay the auto-purge operation.

Column	Description
	<ul style="list-style-type: none"> • 0 means that the auto-purge operation is not delayed. • 1 means that the auto-purge operation is delayed.
delay_value	<p>The value of the delay_value column is:</p> <ul style="list-style-type: none"> • If the value of the delay_purge column is 0, then the value of the delay_value column is NULL. • If the value of the delay_purge column is 1, then the value of the delay_value column is specified in one of the following ways: <ul style="list-style-type: none"> — The period of the delay in days. — Delayed date and time expressions: <i>date expression^time expression</i>

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_proc_index	proc_id node_id	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_proc_index ¹	node_id	nodes

¹This key enforces the DELETE CASCADE referential action.

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_proc_index_fk	node_id	SMALLINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `proc_index` table contains one row for each procedure defined on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new procedure is created.
updated	a procedure's details are updated.
deleted	never.

iap_monitor

The `iap_monitor` table holds the monitor ID records for each procedure and node. If a procedure or node has any activity monitoring configured, it is assigned a monitor ID. The monitor ID is then used when correlating between the [iap_activity](#) and [iap_field](#) tables.

Structure

The `iap_monitor` table has the following structure:

```
TABLE iap_monitor(  
    node_id          number(5)          NOT NULL,  
    proc_id          number(5)          NOT NULL,  
    monitor_id       numeric(10)        NOT NULL)
```

Column	Description
node_id	ID of the node that this procedure is defined on, as defined in the nodes table.
proc_id	Unique ID of this procedure, generated from the sequences table.
monitor_id	Unique ID of the record for the procedure or node being monitored.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_iap_monitor	monitor_id	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_iap_monitor ¹	proc_id node_id	proc_index nodes

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_iap_monitor_fk	node_id	SMALLINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The iap_monitor table contains one row for each procedure or node that has activity monitoring configured for it. Rows are added, updated and deleted in the following situations.

¹This key enforces the DELETE CASCADE referential action.

A row is...	When...
added	a new procedure or node has activity monitoring configured.
updated	a procedure or node's activity monitoring configuration is updated.
deleted	never.

iap_field

The `iap_field` table holds the list of fields that will be published for a given monitor ID.

Structure

The `iap_field` table has the following structure:

```
TABLE iap_field (
  monitor_id      number(10)      NOT NULL,
  field_name      varchar2(31)    NOT NULL)
```

Column	Description
<code>monitor_id</code>	Unique ID of the record for the procedure or node being monitored, as defined in the iap_monitor table.
<code>field_name</code>	The name of the iProcess Engine field for which data is to be sent out with the activity event.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
<code>pk_iap_field</code>	<code>monitor_id</code> <code>field_name</code>	MEDIUMINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_iap_field ¹	monitor_id	iap_monitor

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_iap_field_fk	monitor_id	MEDIUMINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `iap_field` table contains one row for each field that will be published for every activity. Rows are added, updated and deleted in the following situations.

¹This key enforces the DELETE CASCADE referential action.

A row is...	When...
added	a new field is created.
updated	a field's details are updated.
deleted	never.

iap_activity

The `iap_activity` table holds the activity and steps which are configured for a given monitor record.

Structure

The `iap_activity` table has the following structure:

```
TABLE iap_activity(
    monitor_id    number(10)    NOT NULL,
    activity_id   number(3)     NOT NULL,
    step_name     varchar2(8)   NOT NULL)
```

Column	Description
<code>monitor_id</code>	Unique ID of the record for the procedure or node being monitored, as defined in the iap_monitor table.
<code>activity_id</code>	Unique ID which represents the activity that is being monitored on the specified iProcess Engine procedure or step.
<code>step_name</code>	The name of the step in the procedure to be monitored. If the name of the step is \$ALL\$, it means every step in the procedure.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_iap_activity	monitor_id activity_id step_name	MEDIUMINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_iap_activity1	monitor_id	iap_monitor

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_iap_activity_fk	proc_id node_id	SMALLINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

¹This key enforces the DELETE CASCADE referential action.

Table Activity

The `iap_activity` table contains one row for each activity that is being monitored on a procedure or node. Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new activity to be monitored has been configured for a procedure or node.
updated	an activity's details have been updated for a procedure or node.
deleted	never.

iap_global

The `iap_global` table holds the fields that have been allocated globally to the specified procedure.

Structure

The `iap_global` table has the following structure:

```
TABLE iap_global(
    node_id          number(5)          NOT NULL,
    proc_id          number(5)          NOT NULL,
    field_name       varchar2(31)       NOT NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this procedure is stored on, as defined in the nodes table.
<code>proc_id</code>	Unique ID of this procedure, generated from the sequences table.
<code>field_name</code>	The name of the iProcess Engine field for which data is to be sent out with the activity event.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_iap_global	proc_id node_id field_name	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_iap_global ¹	proc_id node_id	proc_index nodes

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_iap_global_fk	proc_id node_id	SMALLINDEXSPACE

Storage

The following STORAGE values are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `iap_global` table contains one row for each field that has been allocated globally to the specified procedure. Rows are added, updated and deleted in the following situations.

A row is...	When...
added	A new global field has been allocated to the specified procedure.
updated	A global field's details have been updated.
deleted	Never.

proc_version

The `proc_version` table holds information that is specific to a version of a procedure (or sub-procedure or sub-procedure parameter template).



Note

Data that is specific to a procedure or to an instance of a procedure is not held in this table. See the [proc_index](#) and [proc_instance](#) tables instead.

Structure

The `proc_version` table has the following structure:

```
TABLE proc_version(
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
```

```

major_vers      number(5)          NOT NULL,
minor_vers      number(5)          NOT NULL,
pd_version      number(7)          ,
pv_status       number(2)          ,
pv_user         varchar2(49)       ,
pv_comment      varchar2(128)     NULL,
pv_created      date               ,
pv_modified     date               ,
pv_released     date               ,
pv_withdrawn    date               ,
pv_is_subproc   number(1)         )

```

Column	Description
node_id	ID of the node that this procedure is stored on, as defined in the nodes table.
proc_id	Procedure number of the procedure associated with this version, as defined in the proc_index table.
major_vers	Major version number of this version.
minor_vers	Minor version number of this version.
pd_version	Instance number of the procedure definition that corresponds to this version, as defined in the proc_instance table.
pv_status	Status of this version. Either: Released (0), Incomplete (1), Unreleased (2), Model (3) or Withdrawn (14).
pv_user	Name of the user who created this version, as defined in the user_names table.
pv_comment	The comment that describes this version.
pv_created	Date and time that this version was created.
pv_modified	Date and time that this version was last modified.
pv_released	Date and time that this version was released.

Column	Description
pv_ withdrawn	Date and time that this version was withdrawn.
pv_is_ subproc	Flag that defines whether (1) or not (0) this version is a sub-procedure.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_proc_version	node_id proc_id major_vers minor_vers	BIGINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_proc_version ¹	node_id proc_id	proc_index

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_proc_version_fk	node_id proc_id	BIGINDEXSPACE

¹This key enforces the DELETE CASCADE referential action.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	BIGTABLESIZE
Percentage Increase	BIGTABLEPCTINCREASE
Tablespace	BIGTABLESPACE

Table Activity

The `proc_version` table contains one row for every version of every procedure (or sub-procedure or sub-procedure parameter template) defined on the system.

Rows are added, updated and deleted in the following situations.

- A row is added when a new procedure or version is created
- A row is updated when a version's details are updated
- A row is deleted when a procedure or version is deleted

procedure_lock

The `procedure_lock` table holds the locks that are used to control access to procedures.

Structure

The `procedure_lock` table has the following structure:

```
TABLE procedure_lock (
  node_id          number(5)                NOT NULL,
  proc_id          number(5)                NOT NULL,
  lock_state       number(1)                NOT NULL,
  lock_owner       varchar2(24),
  lock_date        date                     NOT NULL,
  lock_reason      number(1)                NOT NULL)
```

Column	Description
node_id	ID of the node that this procedure is defined on, as defined in the nodes table.
proc_id	ID of this procedure, as defined in the proc_index table.
lock_state	Flag that defines the procedure state: either unlocked (0) or locked (1).
lock_owner	Name of the user who has the procedure definition locked (if lock_state = 1), as defined in the user_names table.
lock_date	Date and time when the procedure lock was created.
lock_reason	Defines why the procedure is locked: <ul style="list-style-type: none"> • 0 not locked. • 1 locked by the TIBCO iProcess Modeler. • 2 locked by <code>SWDIR\bin\swutil IMPORT</code>.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_procedure_lock	proc_id node_id	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The `procedure_lock` table contains one row for each procedure on the system that is currently being edited.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a procedure is opened (for example, in the iProcess Modeler).
updated	Never.
deleted	a procedure is closed (for example, in the iProcess Modeler).

proc_instance

The `proc_instance` table holds information that is specific to an instance of a version of a procedure (or sub-procedure or sub-procedure parameter template).



Note

Data that is specific to a procedure or to a version of a procedure is not held in this table. See the [proc_index](#) and [proc_version](#) tables instead.

Structure

The `proc_instance` table has the following structure:

```
TABLE proc_instance(
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  major_vers       number(5)          NOT NULL,
  minor_vers       number(5)          NOT NULL,
  pd_version       number(7)          NOT NULL,
  pi_first_step    varchar2(8),
  pi_rpa_start     number(1),
  pi_rpa_admin     number(1),
  pi_has_eis_objs  number(1),
  pi_has_subprocs  number(1))
```

Column	Description
<code>node_id</code>	ID of the node that this instance is stored on, as defined in the nodes table.
<code>proc_id</code>	Procedure number of the procedure associated with this instance, as defined in the proc_index table.
<code>major_vers</code>	Major version number of the version associated with this instance, as defined in the proc_version table.
<code>minor_vers</code>	Minor version number of the version associated with this instance, as defined in the proc_version table.
<code>pd_version</code>	Instance number of this procedure definition.
<code>pi_first_step</code>	Start step for this instance of the procedure.
<code>pi_rpa_start</code>	Flag that defines whether (1) or not (0) Remote Procedure Access (RPA) case start restrictions are set in the procedure definition.
<code>pi_rpa_admin</code>	Flag that defines whether (1) or not (0) Remote Procedure Access (RPA) administration restrictions are set in the procedure definition.
<code>pi_has_eis_objs</code>	Flag that defines whether (1) or not (0) the procedure definition contains EIS

Column	Description
	objects.
pi_has_subprocs	Flag that defines whether (1) or not (0) the procedure definition contains sub-procedure steps or graft steps.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_proc_instance	node_id proc_id pd_version	BIGINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_proc_instance ¹	node_id proc_id	proc_index

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_proc_instance_fk	node_id proc_id	BIGINDEXSPACE

¹This key enforces the DELETE CASCADE referential action.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	BIGTABLESIZE
Percentage Increase	BIGTABLEPCTINCREASE
Tablespace	BIGTABLESPACE

Table Activity

The `proc_instance` table contains one row for each instance of each procedure (or sub-procedure or sub-procedure parameter template) defined on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new procedure or version is created, or when an existing procedure definition is edited.
updated	never.
deleted	a procedure or version is deleted.

proc_audit

The `proc_audit` table stores audit events for a version of a procedure (or sub-procedure or sub-procedure parameter template). An audit event occurs whenever:

- a version is created, updated, released or withdrawn,
- the procedure definition instance associated with the version is updated. (For example, when a user makes changes to the procedure definition in the iProcess Modeler but does not change the version number).

Structure

The `proc_audit` table has the following structure:

```
TABLE proc_audit(  
    node_id          number(5)          NOT NULL,  
    proc_id          number(5)          NOT NULL,  
    major_vers       number(5)          NOT NULL,  
    minor_vers       number(5)          NOT NULL,  
    pd_version       number(7),  
    pa_comment       varchar2(128)      NULL,  
    pa_event         number(5),  
    pa_date          date,  
    pa_user          varchar2(24))
```

Column	Description
node_id	ID of the node that this audit event is stored on, as defined in the nodes table.
proc_id	Procedure number of the procedure associated with this audit event, as defined in the proc_index table.
major_vers	Major version number of the version associated with this audit event, as defined in the proc_version table.
minor_vers	Minor version number of the version associated with this audit event, as defined in the proc_version table.
pd_version	Instance number of the procedure definition associated with this audit event, as defined in the proc_instance table.
pa_comment	Comment describing the audit event.
pa_event	The audit event that occurred. Either: Created (0), Updated (1), Released (2) or Withdrawn (3).
pa_date	Date and time that the audit event occurred.
pa_user	Name of the user who performed the audit event, as defined in the user_names table.

Primary Key

None.

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_proc_audit ¹	node_id proc_id pd_version	proc_instance

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_proc_audit_fk	node_id proc_id pd_version	BIGINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	BIGTABLESIZE
Percentage Increase	BIGTABLEPCTINCREASE
Tablespace	BIGTABLESPACE

¹This key enforces the DELETE CASCADE referential action.

Table Activity

The `proc_audit` table contains one row for every audit event for every version of every procedure (or sub-procedure or sub-procedure parameter template) defined on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a version is created, updated, released or withdrawn.
updated	never.
deleted	a procedure or version is deleted.

proc_defn

The `proc_defn` table holds procedure definitions.

Structure

The `proc_defn` table has the following structure:

```
TABLE proc_defn (
  node_id      number(5)          NOT NULL,
  proc_id      number(5)          NOT NULL,
  pd_version   number(5)          NOT NULL,
  pd_type      number(1)          NOT NULL,
  pd_index     number(10)         NOT NULL,
  pd_size      number(10)         NOT NULL,
  pd_directory varchar2(25)       NOT NULL,
  pd_file      varchar2(25)       NOT NULL,
  pd_data      blob              NOT NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this procedure definition is defined on, as defined in the nodes table.

Column	Description
proc_id	ID of the procedure that this procedure definition relates to, as defined in the proc_index table.
pd_version	ID of the procedure instance that this row relates to, as defined in the proc_instance table.
pd_type	Type of procedure definition data stored in this row. Either: <ul style="list-style-type: none"> • 0 <i>pro</i> data (textual procedure definition) • 1 <i>lst</i> data (binary procedure definition) • 2 <i>nod</i> data (not used) • 3 <i>gwd</i> data (iProcess Modeler layout information) • 4 <i>nod</i> data (not used) • 5 VBA project data (VBA project files)
pd_index	<p>Index number into the set of rows that make up this procedure definition.</p> <p>If the procedure definition is longer than 30,000 bytes, multiple rows (in 30,000 byte chunks) are used to store the data. Each segment of the procedure definition data is uniquely identified by its <code>pd_index</code> value.</p> <p>Note:</p> <ul style="list-style-type: none"> • If you have upgraded your system from one of the following versions, existing procedure definitions are divided into 2000 byte chunks: <ul style="list-style-type: none"> — (UNIX Oracle) any Version i9.<i>n</i>-o iProcess Engine, or from a pre-Version 9.0-o(0.15) Process Engine. — (Windows Oracle) any Version 9.0-o Process Engine. • However, if a procedure definition is modified, the new instance is added using 30,000 byte chunks.
pd_size	Size (in bytes) of the procedure definition data for the current row. This is 30,000 bytes (or 2000—see above) for all but the last row of the procedure definition.

Column	Description
pd_directory	<p>If pd_type is 5, contains the sub-directory path (relative to <i>SWDIR\projects</i>) where any VBA project files related to this procedure definition are stored. Filenames are stored in pd_file.</p> <p>If pd_type is 0 to 4, this field contains a hyphen.</p>
pd_file	<p>If pd_type is 5, contains the filename of a VBA project file related to this procedure definition (if there is one). The file is physically stored in the location defined by pd_directory.</p> <p>If pd_type is 0 to 4, this field contains a hyphen.</p>
pd_data	Raw data for this (portion of the) procedure definition.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_proc_defn	proc_id pd_index pd_type node_id pd_version pd_directory pd_file	LARGEINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_proc_defn ¹	node_id	proc_instance

¹This key enforces the DELETE CASCADE referential action.

Key Name	Column(s)	Referenced in Table...
	proc_id pd_version	

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_proc_defn_fk	proc_id node_id pd_version	LARGEINDEXSPACE
idx_proc_defn	proc_id pd_version pd_type node_id	LARGEINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	LARGETABLESIZE
Percentage Increase	LARGETABLEPCTINCREASE
Tablespace	LARGETABLESPACE

Table Activity

The proc_defn table contains one or more rows for each instance of each procedure definition on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a procedure is saved in the iProcess Modeler (thus creating a new instance), or imported.
updated	never.
deleted	a procedure is deleted.

proc_deadline

The `proc_deadline` table stores definitions of procedure deadlines.

Structure

The `proc_deadline` table has the following structure:

```
TABLE proc_deadline(
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  major_vers       number(5)          NOT NULL,
  minor_vers       number(5)          NOT NULL,
  pd_version       number(7)          NOT NULL,
  dead_name        varchar(32)        NOT NULL,
  event_name       varchar(32)        NOT NULL,
  dead_value       varchar(512)       NOT NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this procedure is defined on, as defined in the nodes table.
<code>proc_id</code>	Unique ID of this procedure, generated from the sequences table.
<code>major_vers</code>	The major version number of the procedure that this case belongs to, as defined in the proc_version table.
<code>minor_</code>	The minor version number of the procedure that this case belongs to, as defined

Column	Description
vers	in the proc_version table.
pd_version	Instance number of the procedure definition, as defined in the proc_instance table.
dead_name	The name of the case deadline.
event_name	The name of the event step that is triggered when the case deadline expires.
dead_value	<p>The value of the case deadline. The value is specified in one of the following formats:</p> <ul style="list-style-type: none"> • If the case deadline is specified as a period, then the value is in the: <i>minutes^hours^days^weeks^months^years</i> format. • If the case deadline is specified as an expression, then the value is in the: <i>date expression^time expression</i> format.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_proc_deadline	node_id proc_id pd_version dead_name	BIGINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_proc_deadline ¹	node_id proc_id pd_version	proc_instance

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_proc_dl_fk	node_id proc_id pd_version	BIGINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	BIGTABLESIZE
Percentage Increase	BIGTABLEPCTINCREASE
Tablespace	BIGINDEXSPACE

Table Activity

The `proc_deadline` table contains one or more rows for each instance of each procedure definition on the system. Rows are added, updated, and deleted in the following situations.

¹This key enforces the DELETE CASCADE referential action.

A row is...	When...
added	The deadlines are created.
updated	The deadlines are updated.
deleted	The deadlines are deleted.

proc_event

The `proc_event` table stores definitions of procedure events.

Structure

The `proc_event` table has the following structure:

```
TABLE proc_event(
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  major_vers       number(5)          NOT NULL,
  minor_vers       number(5)          NOT NULL,
  pd_version       number(7)          NOT NULL,
  eventname        varchar(32)        NOT NULL,
  user_event_name  varchar(32)        NOT NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this case is hosted on, as defined in the nodes table.
<code>proc_id</code>	ID of the procedure that this event belongs to, as defined in the proc_index table.
<code>major_vers</code>	Major version number of the procedure version that this case belongs to, as defined in the proc_version table.
<code>minor_vers</code>	Minor version number of the procedure version that this case belongs to, as defined in the proc_version table.

Column	Description
pd_version	Instance number of the procedure definition, as defined in the proc_instance table.
eventname	<p>The name of the procedure event. The value of this column is one of the following:</p> <ul style="list-style-type: none"> • BeforePurge • BeforeClose • AfterClose • BeforeResurrect • AfterResurrect • BeforeSuspend • AfterSuspend • BeforeResume • AfterResume
user_event_name	The name of the event step which you set for the procedure event.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_proc_event	node_id proc_id pd_version eventname	BIGINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_proc_event ¹	node_id proc_id pd_version	proc_instance

Index

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_proc_event_fk	node_id proc_id pd_version	BIGINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	BIGTABLESIZE
Percentage Increase	BIGTABLEPCTINCREASE
Tablespace	BIGINDEXSPACE

Table Activity

The `proc_event` table contains one or more rows for each instance of each procedure definition on the system. Rows are added, updated, and deleted in the following situations.

¹This key enforces the DELETE CASCADE referential action.

A row is...	When...
added	<p>If one of the following conditions occurred:</p> <ul style="list-style-type: none"> • A new procedure event is added. • A procedure event is modified. <p>Note: When updating a procedure event, the record related to this event is deleted and then a new record with the event changes is added in the table.</p> <ul style="list-style-type: none"> • A new version of a procedure is released.
updated	Never.
deleted	<p>If one of the following conditions occurred:</p> <ul style="list-style-type: none"> • A procedure event is deleted. • A procedure event is modified. <p>Note: When updating a procedure event, the record related to this event is deleted and then a new record with the event changes is added in the table.</p> <ul style="list-style-type: none"> • The version of this procedure is deleted.

wqd_delta_subscriptions

The `wqd_delta_subscriptions` table holds a list of the work queues, JMS topics and WQDIDs that are currently in use for Work Queue Delta subscriptions published via JMS. It provides a permanent store of subscription details if a WIS process is restarted. See *TIBCO iProcess Engine Administrator's Guide* for details of Work Queue Delta publication via JMS.

Structure

The `wqd_delta_subscriptions` table has the following structure:

```
TABLE wqd_delta_subscriptions(
  wis_process_instance    number(5)           NOT NULL,
  queue_name              varchar(51)        NOT NULL,
```

wqdid	varchar(36)	NOT NULL
jms_topic_name	varchar(1024)	

Column	Description
wis_process_instance	The instance of the WIS process that is responding to Work Queue Delta publication requests.
queue_name	The name of the work queue being monitored.
wqdid	The unique ID of the subscription.
jms_topic_name	The name of the JMS topic being used for publication.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_wqd_delta_subscription	wqdid	MEDIUMINDEXSPACE

Foreign Keys

None.

Indexes

None.


Procedure Management

This section describes the tables that are used to store information about the iProcess procedure objects that are stored in the Procedure Management library.

About Procedure Objects

Information is stored in these tables about the following types of procedure objects:

- libraries
- procedures
- sub-procedures
- sub-procedure parameter templates
- shortcuts.


 **Note:** Shortcuts are not real procedure objects. They are simply placeholders that allow you to access a procedure object from different locations in the Procedure Management library. Data on shortcuts is only stored in the [proc_mgt_hierarchy](#) table.

Information about procedure versions is stored in other tables - for more information, see [Procedures](#).

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



pm_objects

The `pm_objects` stores information about each procedure object (except shortcuts) in the Procedure Management library.

Structure

The `pm_objects` table has the following structure:

```

TABLE pm_objects (
  object_guid          varchar2(36)          NOT NULL,
  object_type          number(5)              NOT NULL,
  object_name          varchar2(64)          NOT NULL,
  version_major        number(5),
  version_minor        number(5),
  icon_mod_time        date                  NOT NULL,
  icon_binary          blob,
  icon_size            number(8)             NOT NULL,
  object_url           varchar2(1000),
  author              varchar2(64),
  object_create_time   date                  NOT NULL,
  object_mod_time      date                  NOT NULL,
  release_id          varchar2(64),
  security_all         number(1)             NOT NULL,
  proc_id             number(5)             NOT NULL,
  proc_status         number(5))
  
```

Column	Description
object_guid	Globally unique, system-generated identifier for this procedure object. The row defining the Procedure Management library root has the value ROOT_LIBRARY_GUID.
object_type	Procedure object type. Either: library (0), procedure (1), sub-procedure (2) or sub-procedure parameter template (3).
object_name	Name of this procedure object. Note: The object's description (if defined) is also included as part of this field, in brackets following the name.
version_major	Major version number of the version associated with this procedure object, as defined in the proc_version table. This value is always 0 if the object is a library.
version_minor	Minor version number of the version associated with this procedure object, as defined in the proc_version table. This value is always 0 if the object is a library.
icon_mod_time	Time that the icon associated with this procedure object was last modified.
icon_binary	Binary form of the icon associated with this procedure object.
icon_size	Size (in bytes) of the icon associated with this procedure object.
object_url	Usage URL associated with this procedure object.
author	Value of the <code>Author</code> extended property for this procedure object.
object_create_time	Value of the <code>Date Created</code> extended property for this procedure object, showing the time that this object was created.
object_mod_time	Value of the <code>Date Modified</code> extended property for this procedure object, showing the time that this procedure object was last modified.

Column	Description
release_id	Value of the Release Identification extended property for this procedure object.
security_all	Flag that defines whether (1) or not (0) the OEM lock is set for this procedure object.
proc_id	Procedure number of the procedure associated with this procedure object, as defined in the proc_index table. This value is always -1 if the object is a library.
proc_status	For internal use only.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_pm_objects	object_guid	SMALLINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `pm_objects` table contains one row for each procedure object (except shortcuts) in the Procedure Management library.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a procedure object is created.
updated	a procedure object is modified.
deleted	a procedure object is deleted.

pm_objects_lock

The `pm_objects_lock` table stores information about every procedure object that is currently locked.

Structure

The `pm_objects_lock` table has the following structure:

```
TABLE pm_objects_lock (
  object_guid    varchar2(36)    NOT NULL,
  lck_state      number(5),
  lck_owner      varchar2(24),
  lck_time       date)
```

Column	Description
object_guid	ID for this procedure object, as defined in the pm_objects table.
lck_state	Flag that defines (1) that this procedure object is locked.
lck_owner	Name of the user who has this procedure object locked, as defined in the user_names table.
lck_time	Time that the lock was set on this procedure object.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_pm_objects_lock	object_guid	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_pm_objects_lock1	object_guid	pm_objects

Indexes

None.

Storage

The following STORAGE values are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `pm_objects_lock` table contains one row for each procedure object that is currently locked.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a procedure object is locked.
updated	never.
deleted	a procedure object is unlocked.

Unlocking Incorrectly Locked Procedure Objects

A procedure object is normally shown as locked in the Procedure Manager when it is open in the TIBCO iProcess Modeler. However, an object may also be locked if it was not closed properly from a previous TIBCO iProcess Modeler session - for example, if the system failed while the procedure was open.

If this happens the object cannot be accessed again until the locks in the [proc_index](#) and [pm_objects](#) tables are released. To do this:

1. Log in to Oracle as the background user.
2. In SQL*Plus, use the following query to delete all locks associated with the locked procedure (where *procedure_name* is the name of the locked procedure):

```
delete procedure_lock where proc_id = (select proc_id from proc_index
where proc_name = 'procedure_name')
delete pm_objects_lock where object_guid = (select object_guid from pm_
objects where object_name like 'proc_name%')
```

3. Commit the transaction.

The object should now appear unlocked in Procedure Manager. (You can refresh the display first.)



Note

The like statement requires a % sign prefixed or suffixed to the *procedure_name*. However, this will select similarly-named procedures - for example, 'TEST%' would select procedures named TEST1, TEST2, TEST3, even if only TEST4 needed to be cleared.

Ensure that the procedure name is complete - in the case in the previous paragraph, specify 'TEST4%' - so that the % character only covers the option procedure description.

Ensure that you are connected to the correct database and table.

pmobjects_security

The pmobjects_security table stores the encrypted security settings for every procedure object (except shortcuts) in the Procedure Management library.

Structure

The pmobjects_security table has the following structure:

```
TABLE pmobjects_security (
  object_guid    varchar2(36)          NOT NULL,
  security_id    number(5)              NOT NULL,
  attrib_expr    varchar2(260)         NOT NULL,
  security_level varchar2(8)            NOT NULL)
```


Column	Description
object_guid	ID for this procedure object, as defined in the pm_objects table.
security_id	Internal identifier for this procedure object.
attrib_expr	Encrypted security attribute expression for this procedure object.
security_level	Encrypted security level for this procedure object.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_pobjects_security	object_guid security_id	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_pobjects_security1	object_guid	pm_objects

Indexes

None.

Storage

The following STORAGE values are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `pmobjects_security` table contains one row for each procedure object (except shortcuts) in the Procedure Management library.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a procedure object is created.
updated	a procedure object's security settings are modified.
deleted	a procedure object is deleted.

proc_mgt_hierarchy

The `proc_mgt_hierarchy` table stores a set of hierarchy records, which define the hierarchical structure of the Procedure Management library. Each record defines the location of a procedure object in the library.

Structure

The `proc_mgt_hierarchy` table has the following structure:

```
TABLE proc_mgt_hierarchy(
  parent_guid          varchar2(36)          NOT NULL,
  object_guid          varchar2(36)          NOT NULL,
  is_shortcut          number(1)              NOT NULL)
```

Column	Description
parent_guid	ID for the parent library, as defined in the pm_objects table.
object_guid	ID for this procedure object, as defined in the pm_objects table. Note: If is_shortcut is 1, this value is the identifier of the procedure object pointed to by the shortcut.
is_shortcut	Flag that defines whether this hierarchy record is for a real procedure object (0) or for a shortcut (1).

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_proc_mgt_hierarchy	parent_guid object_guid	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_proc_mgt_hierarchy ¹	object_guid	pm_objects

Indexes

None.

¹This key enforces the DELETE CASCADE referential action.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `proc_mgt_hierarchy` table contains one row for every procedure object in the Procedure Management library (except for the root Procedure Management library).

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a procedure object is created, copied or moved.
updated	never.
deleted	a procedure object is deleted or moved.


Cases

This section describes the tables that are used to store information about iProcess cases.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



case_information

The `case_information` table holds information about every case and sub-case that has been started and not yet purged on the system.

Structure

The `case_information` table has the following structure:

```
TABLE case_information (
  node_id          number(5)          NOT NULL,
```

```

proc_id          number(5)          NOT NULL,
casenum          number(20)         NOT NULL,
starter          varchar2(49)       NOT NULL,
casedesc         varchar2(24)       NULL,
procflags        number(5)          NOT NULL,
next_deadline    date,
is_subcase       number(1)          NOT NULL,
is_dead          number(1)          NOT NULL,
is_suspended     number(1)          NOT NULL,
major_vers       number(5)          NOT NULL,
minor_vers       number(5)          NOT NULL,
proc_precedence  number(5)          NOT NULL,
started          date               NOT NULL,
started_usecs    number(6)          NOT NULL)
using_blob       number(1)          )

```

Column	Description
node_id	ID of the node that this case is hosted on, as defined in the nodes table.
proc_id	ID of the procedure that this case belongs to, as defined in the proc_index table.
casenum	<p>Unique case number for this case, generated from the sequences table.</p> <p>Note: If the system has been upgraded from a Version 9 Process Engine, any cases that were started before the upgrade do not have a unique case number. (They have a number that is unique to that procedure.)</p>
starter	Name of the user who started this case, as defined in the user_names table.
casedesc	Case description supplied when the case was started.
procflags	<p>The procedure flags that were set at the time the case was started. For internal use only.</p> <p>Note: These flags are stored to allow consistent operation of the case if the procedure changes status during the lifetime of the case. For example, if the procedure is unreleased when the case is started, but changes to released before the case completes, the case can continue using the original procedure flags.</p>

Column	Description
next_deadline	Date and time that the next deadline expires on this case. If no deadline is set this value appears as 12/31/3000 11:15:00 PM.
is_subcase	Flag that defines whether this case is a main case (0) or a sub-case (1).
is_dead	Flag that defines whether (1) or not (0) this case has completed.
is_suspended	Flag that defines whether (1) or not (0) the case is currently suspended (from a TIBCO iProcess Objects or SAL application).
major_vers	Major version number of the version of the procedure that this case belongs to, as defined in the proc_version table.
minor_vers	Minor version number of the version of the procedure that this case belongs to, as defined in the proc_version table.
proc_precedence	Stores the procedure precedence settings for opening sub-cases. One of: <ul style="list-style-type: none"> • 32 - Released only. • 64 - Unreleased > Released. • 96 - Model > Released. • 128 - Unreleased > Model > Released. • 160 - Model > Unreleased > Released.
started	Date and time that the case was started, to the resolution of a second. Note: The started_usecs column can be combined with this column to provide resolution to a microsecond.
started_usecs	Number of microseconds since the start of the <i>seconds</i> value specified in the started column.
using_blob	Decides to use the old memo data table or the new one.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_case_information	casenum proc_id node_id	LARGEINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_case_information1	proc_id node_id	proc_index

Indexes

The following indexes are defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_case_information_fk	proc_id node_id	LARGEINDEXSPACE
idx_ci_casedesc_UC2	UPPER(casedesc) casenum proc_id	LARGEINDEXSPACE

Storage

The following STORAGE values are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

²Oracle function-based index, to facilitate case insensitive searches.

Value	Definition
Initial	LARGETABLESIZE
Percentage Increase	LARGETABLEPCTINCREASE
Tablespace	LARGETABLESPACE

Table Activity

The `case_information` table contains one row for every open and closed case and sub-case on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new case or sub-case is started.
updated	any of the following occur: <ul style="list-style-type: none"> a case or sub-case is closed. a deadline on a case or sub-case is set or expires. a case or sub-case is suspended or re-opened. a new version of a procedure is released and the option is chosen to migrate cases (and sub-cases) that use the previously released version to the new version.
deleted	a case is purged.

outstanding_addr

The `outstanding_addr` table holds information about each outstanding step on the system.

Structure

The outstanding_addr table has the following structure:

```
TABLE outstanding_addr (
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  casenum          number(20)         NOT NULL,
  sentdate         date              NOT NULL,
  deadline         number(1)         NOT NULL,
  deadline_expired number(1)         NOT NULL,
  sub_procedure    number(1)         NOT NULL,
  deaddate         date              NOT NULL,
  stepname         varchar2(8)       NOT NULL,
  user_name        varchar2(64)      NOT NULL,
  reqid           number(20)         NOT NULL,
  item_suspended  number(1)         NOT NULL,
  item_withdrawn  number(1)         NOT NULL,
  array_idx       number(5)         NOT NULL)
```

Column	Description
rowid	Unique identifier for this row
node_id	ID of the node that this outstanding step is hosted on, as defined in the nodes table.
proc_id	ID of the procedure that this outstanding step belongs to, as defined in the proc_index table.
casenum	Number of the case that this outstanding step belongs to, as defined in the case_information table.
sentdate	Date and time that this outstanding step was sent to the user_name queue.
deadline	Flag that defines whether (1) or not (0) this outstanding step has a deadline defined.
deadline_expired	Flag that defines whether (1) or not (0) the deadline (if defined) has expired and been processed.

Column	Description
sub_ procedure	Flag that defines whether (1) or not (0) this outstanding step is a sub-procedure call.
deaddate	Date and time that the deadline (if defined) expires on this outstanding step. If no deadline is set, this value appears as 12/31/3000 11:15:00 PM.
stepname	Stepname of this outstanding step.
user_name	Name of the queue that this outstanding step has been sent to, as defined in the user_names table.
reqid	Unique ID for this work item, generated from the sequences table.
item_ suspended	Flag that defines whether (1) or not (0) this outstanding step is currently suspended. Note: item_suspended is only set if the case is suspended <i>and</i> the ignore suspend attribute is <i>not</i> set on the step.
item_ withdrawn	Flag that defines whether (1) or not (0) this outstanding step is withdrawn.
array_idx	Either: <ul style="list-style-type: none"> The array element index number of the sub-procedure that generated this outstanding step, if the sub-procedure was called from either a graft step or a dynamic sub-procedure call step. -1, otherwise.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_outstanding_addr	reqid node_id	LARGEINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_outstand_addr ¹	casenum proc_id node_id	case_information

Indexes

The following indexes are defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_outstanding_addr_fk	casenum proc_id node_id	LARGEINDEXSPACE
idx_deadline_date	deaddate	LARGEINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	LARGETABLESIZE
Percentage Increase	LARGETABLEPCTINCREASE
Tablespace	LARGETABLESPACE

¹This key enforces the DELETE CASCADE referential action.

Table Activity

The `outstanding_addr` table contains one row for each outstanding step on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	<p>a new step is sent out.</p> <p>Note:</p> <ul style="list-style-type: none"> • if a step has multiple addressees one row is added per addressee. • for a dynamic sub-procedure, one row is added per called sub-procedure. • for a graft step, one row is added per grafted sub-procedure or external step.
updated	<p>any of the following occur:</p> <ul style="list-style-type: none"> • a deadline on an outstanding step expires. • a case is suspended or re-opened. • an outstanding step is withdrawn.
deleted	<p>the background processes a release, withdraw, close or purge operation that affects an outstanding step.</p>

wait

The `wait` table holds information about each outstanding wait on the system.

Structure

The `wait` table has the following structure:

```
TABLE wait (
  wait_id      number(10)      NOT NULL,
  node_id      number(5)        NOT NULL,
  proc_id      number(5)        NOT NULL,
  casenum      number(20)       NOT NULL,
```

parentstep	varchar2(8)	NULL,
expression	varchar2(200)	NULL,
type	number(1)	NOT NULL)

Column	Description
wait_id	Unique ID for the wait table is generated from the sequences table.
node_id	ID of the node that the wait table is hosted on, as defined in the nodes table.
proc_id	ID of the procedure that the wait table belongs to, as defined in the proc_index table.
casenum	Case number that the wait wait belongs to, as defined in the case_information table.
parentstep	Step name of the parent step for this wait.
expression	<i>Not used. Reserved for possible future use.</i>
type	Wait type. Currently the only supported type is a Step wait (1), that is, the step is waiting for one or more other steps to be released.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_wait	wait_id node_id	BIGINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_wait1 ¹	node_id proc_id casenum	case_information

Indexes

The following indexes are defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_wait_fk	casenum proc_id node_id	BIGINDEXSPACE
idx_wait	casenum proc_id	BIGINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	BIGTABLESIZE
Percentage Increase	BIGTABLEPCTINCREASE
Tablespace	BIGTABLESPACE

Table Activity

The wait table contains one row for each outstanding wait on the system. An associated record exists in the [wait_step](#) table for each step being waited for.

Rows are added, updated and deleted in the following situations.

¹This key enforces the DELETE CASCADE referential action.

A row is...	When...
added	a new wait is triggered.
updated	never.
deleted	a wait is processed.

wait_step

The `wait_step` table holds information about each step that is currently being waited for by a wait defined in the [wait](#) table.

Structure

The `wait_step` table has the following structure:

```
TABLE wait_step (
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  wait_id          number(10)         NOT NULL,
  step_id          number(9)          NOT NULL)
```

Column	Description
<code>node_id</code>	ID of the node that the wait is hosted on, as defined in the nodes table.
<code>proc_id</code>	ID of the procedure that the wait belongs to, as defined in the proc_index table.
<code>wait_id</code>	ID of the wait, as defined in the wait_step table.
<code>step_id</code>	Number of the step that is being waited for, as defined (by the <code>step_num</code> column) in the status table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_wait_step	wait_id step_id	BIGINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_wait_step ¹	node_id wait_id	wait

Indexes

The following indexes are defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_wait_step_fk	wait_id node_id	BIGINDEXSPACE
idx_wait_step	wait_id proc_id	BIGINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	BIGTABLESIZE

¹This key enforces the DELETE CASCADE referential action.

Value	Definition
Percentage Increase	BIGTABLEPCTINCREASE
Tablespace	BIGTABLESPACE

Table Activity

The wait_step table contains one row for each for each step currently being waited for.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new wait is triggered.
updated	never.
deleted	a step that is being waited for is released or withdrawn.

status

The status table holds the current status of each step of each case on the system.

Structure

The status table has the following structure:

```
TABLE status (
  node_id      number(5)      NOT NULL,
  proc_id      number(5)      NOT NULL,
  casenum      number(20)     NOT NULL,
  step_num     number(4)      NOT NULL,
  step_status  number(1)      NOT NULL)
```

Column	Description
node_id	ID of the node that this step is hosted on, as defined in the nodes table.
proc_id	ID of the procedure that this step belongs to, as defined in the proc_index table.
casenum	Case number that this step belongs to, as defined in the case_information table.
step_num	Place number for this step (a unique ID that does not change between edits of a procedure). For internal use only.
step_status	Step status. Either: Not processed (0), Released (1), Outstanding (2) or Withdrawn (3).

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_status	casenum proc_id step_num node_id	HUGETABLESPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_status ¹	node_id proc_id casenum	case_information

¹This key enforces the DELETE CASCADE referential action.

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_status_fk	casenum proc_id node_id	HUGEINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	HUGETABLESIZE
Percentage Increase	HUGETABLEPCTINCREASE
Tablespace	HUGETABLESPACE

Table Activity

The `status` table contains one row for each step of each case (open or closed) on the system. Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a step is sent out, or a case is started.
updated	a step's status changes.
deleted	a case is purged.

case_data

The `case_data` table holds the central copy of the field name and value of each assigned field in each case on the system.

When a work item is sent out to a queue, field data is copied from the `case_data` table to the `pack_data` table. The client uses the field values in the `pack_data` table to fill out the form correctly. When the form is kept any changed fields are updated in the `pack_data` table. When a work item is released field data is moved from the `pack_data` table to the `case_data` table.

Structure

The `case_data` table has the following structure:

```
TABLE case_data (
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  casenum          number(20)         NOT NULL,
  field_name       varchar2(31)       NOT NULL,
  field_value      varchar2(255)      NULL,
  field_value_N    varchar2(255)      NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this field is hosted on, as defined in the nodes table.
<code>proc_id</code>	ID of the procedure that this field belongs to, as defined in the proc_index table.
<code>casenum</code>	Case number that this field belongs to, as defined in the case_information table.
<code>field_name</code>	Name of this field.
<code>field_value</code>	Value of this field.
<code>field_value_N</code>	“Normalized” value of the <code>field_value</code> value. That is: <ul style="list-style-type: none"> • Date values are stored as YYYY-MM-DD.

Column	Description
	<ul style="list-style-type: none"> Numeric values are stored as padded strings. Time and String values are not changed. <p>Note: This value is stored to make case data searching easier, so that the database can do simple string comparisons, instead of having to do type conversions.</p> <p>Case data can be normalized either when installing/upgrading the iProcess Engine, or by using the Case Data Normalization Utility - see <i>TIBCO iProcess Engine Administrator's Guide</i>.</p>

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_case_data	casenum proc_id node_id field_name	MASSIVEINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_case_data ¹	node_id proc_id casenum	case_information

Indexes

The following indexes are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Index Name	Column(s) Indexed	Tablespace
idx_case_data_fk	casenum proc_id node_id	MASSIVEINDEXSPACE
idx_case_data_cnum_ procid_fnfv ¹	field_name field_value_N casenum proc_id	MASSIVEINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MASSIVETABLESIZE
Percentage Increase	MASSIVETABLEPCTINCREASE
Tablespace	MASSIVETABLESPACE

Table Activity

The case_data table contains n rows for each open case on the system, where n is the number of fields in the case that have assigned data values. Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a field has a value assigned to it.

¹This index can impact purge performance. If a large number of purges are being made at the same time TIBCO recommends that you delete this index before performing the purge, then recreate it when the purge has completed.

A row is...	When...
updated	a field's value is changed.
deleted	a field becomes unassigned (blank) or when the parent case is purged.

audit_trail

The `audit_trail` table holds information about each event that has happened to each case on the system.

Structure

The `audit_trail` table has the following structure:

```
TABLE audit_trail (
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  casenum          number(20)         NOT NULL,
  type_id          number(3)          NOT NULL,
  audit_date       date               NOT NULL,
  stepdesc         varchar2(24)       NULL,
  user_name        varchar2(64)       NULL,
  stepname         varchar2(8)        NULL,
  audit_usecs      number(6)          NOT NULL,
  major_vers       number(5)          NOT NULL,
  minor_vers       number(5)          NOT NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this audit event is hosted on, as defined in the nodes table.
<code>proc_id</code>	ID of the procedure that this audit event belongs to, as defined in the proc_index table.
<code>casenum</code>	Case number that this audit event belongs to, as defined in the case_information table.

Column	Description
type_id	<p>ID of the audit event that occurred. Either:</p> <ul style="list-style-type: none"> • a system-defined audit event (≤ 255), as defined in the <code>SWDIR\etc\language.lng\audit.mes</code> file. • a custom, application-defined event (256-999), as defined in the <code>SWDIR\etc\language.lng\auditusr.mes</code> file. <p>Note: See "Defining Audit Trail Entries" in <i>TIBCO iProcess swutil and swbatch Reference Guide</i> for more information about system-defined and application-defined audit trail entries.</p>
audit_date	<p>Date and time that this audit event occurred.</p> <p>Note: The <code>audit_usecs</code> column can be combined with this column to provide resolution to a microsecond.</p>
stepdesc	<p>If <code>type_id</code> is:</p> <ul style="list-style-type: none"> • ≤ 255, the step description of the step that this audit event occurred to. • $\Rightarrow 256$, a user-defined string, containing for example the description of this audit event.
user_name	<p>If <code>type_id</code> is:</p> <ul style="list-style-type: none"> • ≤ 255, the name of the user who performed this audit event, as defined in the user_names table. • $\Rightarrow 256$, a user-defined string, containing for example the name of the user who performed this audit event.
stepname	<p>Name of the step that this audit event occurred for.</p> <p>For internal use only.</p>
audit_usecs	<p>Number of microseconds since the start of the <i>seconds</i> value specified in the <code>audit_date</code> column.</p> <p>Note: On systems that have been upgraded from Version 9, for any existing cases the 6 least significant digits of the <code>at_id</code> column are copied into this column to ensure that audit trail entries remain in the correct order.</p>

Column	Description
major_vers	Major version number of the version of the procedure that this audit event belongs to, as defined in the proc_version table.
minor_vers	Minor version number of the version of the procedure that this audit event belongs to, as defined in the proc_version table.

Primary Key

None.

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_audit_trail ¹	node_id proc_id casenum	case_information

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_audit_trail_fk	casenum proc_id node_id	MASSIVEINDEXSPACE

Storage

The following STORAGE values are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Value	Definition
Initial	MASSIVETABLESIZE
Percentage Increase	MASSIVETABLEPCTINCREASE
Tablespace	MASSIVETABLESPACE

Table Activity

The `audit_trail` table contains one or more rows for each step of each case on the system. Rows are added, updated and deleted in the following situations.

A row is...	When...
added	an audit event occurs.
updated	never.
deleted	a case is purged.

memo

The `memo` table stores the case memo data before upgrading to iProcess Engine 11.6. Since iProcess Engine 11.6, all the new case memo data is stored in the `BLOB` data type in the [nmemo](#) table.

You can migrate case memo data in the `memo` table to the [nmemo](#) table when upgrading to iProcess Engine 11.6 or migrate them by using the `swutil MIGRATEMEMOS` command after the upgrades.



Note: A copy of a memo is saved in the [pack_memo](#) table if the memo is marked on an outstanding form.

Structure

The memo table has the following structure:

```
TABLE memo (
  node_id      number(5)                NOT NULL,
  proc_id      number(5)                NOT NULL,
  casenum      number(20)               NOT NULL,
  memo_id      number(4)                NOT NULL,
  memo_index   number(10)               NOT NULL,
  memo_size    number(10)               NOT NULL,
  memo_data    blob NOT NULL,
  array_idx    number(6)                NOT NULL)
```

Column	Description
node_id	ID of the node that this memo is hosted on, as defined in the nodes table.
proc_id	ID of the procedure that this memo belongs to, as defined in the proc_index table.
casenum	Case number that this memo belongs to, as defined in the case_information table.
memo_id	Unique (for this case) ID of this memo.
memo_index	<p>Index number into the set of rows that make up this memo.</p> <p>If a memo is longer than 30,000 bytes multiple rows (in 30,000 byte chunks) are used to store the memo data. Each segment of the memo data is uniquely identified by its memo_index value.</p>

Note: If you have upgraded your system from iProcess Engine one of the following versions, existing memos are divided into 2,000 byte chunks:

- (UNIX Oracle) any Version i9.n-o iProcess Engine, or from a pre-Version 9.0-o(0.15) Process Engine.
- (Windows Oracle) any Version 9.0-o Process Engine.

However, if a memo is modified, the existing rows are deleted and then re-added using 30,000 byte chunks.

Column	Description
memo_size	Size (in bytes) of the memo data for this row.
memo_data	Memo data.
array_idx	Either: <ul style="list-style-type: none"> • The array element index number of the memo. • -1, if the memo is not an array memo field.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_memo	casenum memo_id memo_index proc_id node_id array_idx	HUGEINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_memo ¹	node_id proc_id casenum	case_information

Indexes

The following index is defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Index Name	Column(s) Indexed	Tablespace
idx_memo_fk	casenum proc_id node_id	HUGEINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	HUGETABLESIZE
Percentage Increase	HUGETABLEPCTINCREASE
Tablespace	HUGETABLESPACE

Table Activity

The memo table contains one or more rows for each memo on the system. Rows are added, updated and deleted in the following situations.

A row is...	When...
added	either: <ul style="list-style-type: none"> a memo field is first assigned. a memo field is modified. (All rows for the memo are deleted and then re-added.)
updated	never.
deleted	either: <ul style="list-style-type: none"> a memo field is modified. (All rows for the memo are deleted and then re-added.) a case is purged.

nmemo

The `nmemo` table stores the case memo data after upgrading to iProcess Engine 11.6. Since iProcess Engine 11.6, all the new case memo data is stored in the `blob` data type in the `nmemo` table.

You can migrate case memo data in the `memo` table to the `nmemo` table when upgrading to iProcess Engine 11.6 or migrate them by using the `swutil MIGRATEMEMOS` command after the upgrades.

Note: A copy of a memo is kept in the `pack_nmemo` table if the memo is marked on an outstanding form.

Structure

The `nmemo` table has the following structure:

```
TABLE nmemo (
  node_id      number(5)          NOT NULL,
  proc_id      number(5)          NOT NULL,
  casenum      number(20)         NOT NULL,
  memo_id      number(4)          NOT NULL,
  memo_index   number(10)         NOT NULL,
  memo_size    number(10)         NOT NULL,
  memo_data    blob              NOT NULL ,
  array_idx    number(6)          NOT NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this memo is hosted on, as defined in the nodes table.
<code>proc_id</code>	ID of the procedure that this memo belongs to, as defined in the proc_index table.
<code>casenum</code>	Case number that this memo belongs to, as defined in the case_information table.
<code>memo_id</code>	Unique (for this case) ID of this memo.

Column	Description
memo_index	Index number into the set of rows that make up this memo. This value is always 1.
memo_size	Size (in bytes) of the memo data for this row.
memo_data	Memo data.
array_idx	Either: <ul style="list-style-type: none"> The array element index number of the memo. -1, if the memo is not an array memo field.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_nmemo	casenum memo_id memo_index proc_id node_id array_idx	HUGEINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_nmemo1	node_id proc_id casenum	case_information

¹This key enforces the DELETE CASCADE referential action.

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_nmemo_fk	casenum proc_id node_id	HUGEINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	HUGETABLESIZE
Percentage Increase	HUGETABLEPCTINCREASE
Tablespace	HUGETABLESPACE

Table Activity

The nmemo table contains one row for each memo on the system. Rows are added, updated and deleted in the following situations.

A row is...	When...
added	either: <ul style="list-style-type: none"> a memo field is first assigned. a memo field is modified.
updated	never.
deleted	either:

A row is...	When...
	<ul style="list-style-type: none"> a memo field is modified. a case is purged.

predict

The predict table stores the prediction data for all expected work items currently defined on the system.

Structure

The predict table has the following structure:

```
TABLE predict (
  node_id          number(5)          NOT NULL,
  proc_num         number(5)          NOT NULL,
  case_num         number(20)         NOT NULL,
  parent_proc_num  number(5)          NOT NULL,
  parent_case_num  number(20)         NOT NULL,
  main_proc_num    number(5)          NOT NULL,
  main_case_num    number(20)         NOT NULL,
  step_name        varchar2(8)        NOT NULL,
  step_desc        varchar2(24)        NULL,
  step_desc2       varchar2(24)        NULL,
  step_addr        varchar2(49)       NOT NULL,
  step_durn_secs   number(10)          NULL,
  step_durn_usecs  number(10)          NULL,
  step_start       date               NOT NULL,
  step_start_usecs number(10)          NOT NULL,
  step_end         date               NOT NULL,
  step_end_usecs   number(10)          NOT NULL,
  field_name       varchar2(31)        NULL,
  field_value      varchar2(255)       NULL)
```

Column	Description
node_id	ID of the node that this predicted work item is hosted on, as defined in the

Column	Description
	nodes table.
proc_num	ID of the procedure associated with this predicted work item, as defined in the proc_index table.
case_num	Either: <ul style="list-style-type: none"> Case number of the case associated with this predicted work item, as defined in the case_information table. 0, if this is a predicted work item in a future sub-case, rather than in a currently outstanding sub-case.
parent_proc_num	ID of the parent procedure associated with this predicted work item, as defined in the proc_index table, if proc_num is a sub-procedure.
parent_case_num	Either: <ul style="list-style-type: none"> ID of the parent case associated with this predicted work item, as defined in the case_information table, if case_num is a sub-case. 0, if this is a predicted work item in a future sub-case, rather than a currently outstanding sub-case, that was itself started from a predicted future sub-case.
main_proc_num	ID of the procedure associated with the main case that generated this predicted work item, as defined in the proc_index table.
main_case_num	ID of the main case that generated this predicted work item, as defined in the case_information table.
step_name	Stepname of the step associated with this predicted work item.
step_desc	Step description of the step associated with this predicted work item.
step_desc2	Additional description of the step associated with this predicted work item.
step_addr	Queue name that this predicted work item will be delivered to.

Column	Description
step_durn_secs	Expected duration (in seconds) between this predicted work item being delivered to and released from the step_addr queue. Note: The step_durn_usecs column can be combined with this column to provide resolution to a microsecond.
step_durn_usecs	Number of microseconds to be added to the value specified in the step_durn_secs column.
step_start	Date and time that this predicted work item is expected to arrive in the step_addr queue, to the resolution of a second. Note: The step_start_usecs column can be combined with this column to provide resolution to a microsecond.
step_start_usecs	Number of microseconds since the start of the <i>seconds</i> value specified in the step_start column.
step_end	Date and time that this predicted work item is expected to be released from the step_addr queue, to the resolution of a second. Note: The step_end_usecs column can be combined with this column to provide resolution to a microsecond.
step_end_usecs	Number of microseconds since the start of the <i>seconds</i> value specified in the step_end column.
field_name	Name of the field that has a CDQP assigned to it for this predicted work item.
field_value	Value of the CDQP assigned to the field_name field for this predicted work item.

Primary Key

None.

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...	Column(s)
fk_predict ¹	main_case_num main_proc_num node_id	predict_lock	case_num proc_num node_id

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE



Note

By default, the predict and predict_lock tables use the SMALL macro values. If you intend to enable case prediction on your system, TIBCO recommends that you change these tables to use a larger value in line with the level of prediction activity you expect.


Table Activity

The predict table contains one or more rows for each predicted work item generated by each step of each case of each procedure that currently has prediction data defined for it.

¹This key enforces the DELETE CASCADE referential action.

If a predicted work item contains one or more fields that have CDQPs assigned to them, duplicate rows are added for each CDQP. In the first row, the `field_name` and `field_value` columns are blank. Each subsequent row contains the `field_name` and `field_value` entries for one assigned CDQP. For example, if a predicted work item contains 5 fields that have CDQPs assigned to them, it will have 6 rows in this table.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	<p>background prediction is enabled on the iProcess Engine, and anything occurs that causes prediction data for a case to be calculated or recalculated. For example, when a case is started, a work item is kept or released, a deadline expires or an event occurs.</p> <p>Note: One row is added for each step in the procedure that can occur on the currently predicted path(s).</p>
updated	never.
deleted	<p>background prediction is enabled on the iProcess Engine, when prediction data for a case is to be recalculated. For example, when a work item is kept or released, a deadline expires or an event occurs.</p> <p>Note: All rows for a given main case number are deleted for each step in the procedure that can no longer occur on the currently predicted path(s).</p>
 Note	Case prediction can be enabled and disabled using the <code>ENABLE_CASE_PREDICTION</code> process attribute. See <i>TIBCO iProcess Engine Administrator's Guide</i> for more information.

predict_lock

The `predict_lock` table stores the locks that are used to control access to the `predict` table.

Structure

The predict_lock table has the following structure:

```
TABLE predict_lock (
  node_id          number(5)          NOT NULL,
  proc_num         number(5)          NOT NULL,
  case_num         number(20)         NOT NULL)
```

Column	Description
node_id	ID of the node that this prediction lock is hosted on, as defined in the nodes table.
proc_num	ID of the procedure that this prediction lock applies to, as defined in the proc_index table.
case_num	Case number of the main case that this prediction lock applies to, as defined in the case_information table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_predict_lock	node_id proc_num case_num	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...	Column(s)
fk_predict_lock ¹	node_id proc_num case_num	case_information	node_id proc_id casenum

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE



Note

By default, the `predict` and `predict_lock` tables use the `SMALL` macro values. If you intend to enable case prediction on your system, TIBCO recommends that you change these tables to use a larger value in line with the level of prediction activity you expect.

Table Activity

The `predict_lock` table contains one row for every main case on the system that currently has prediction data defined in the [predict](#) table. Rows are added, updated and deleted in the following situations.

¹This key enforces the DELETE CASCADE referential action.

A row is...	When...
added	background prediction is enabled on the iProcess Engine, and a case that has prediction enabled is started. Note: Case prediction can be enabled and disabled using the ENABLE_CASE_PREDICTION process attribute. See <i>TIBCO iProcess Engine Administrator's Guide</i> for more information.
updated	never.
deleted	a case that has prediction enabled is purged.

case_deadline_event

The case_deadline_event table stores information about case deadlines when the case is running.

Structure

The case_deadline_event table has the following structure:

```
TABLE case_deadline_event (
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  casenum          numeric(20)        NOT NULL,
  dead_id          varchar(32)        NOT NULL,
  dead_name        varchar(32)        NOT NULL,
  event_name       varchar(32)        NOT NULL,
  dead_value       varchar(512)       NOT NULL)
```

Column	Description
node_id	ID of the node that this procedure is defined on, as defined in the nodes table.
proc_id	Unique ID of this procedure, generated from the sequences table.

Column	Description
casenum	The number of the case that this case deadline belongs to, as defined in the case_information table.
dead_id	For internal use only. This column is referenced from the stepname column in the outstanding_addr table.
dead_name	The name of the case deadline.
event_name	The name of the event step.
dead_value	<p>The value of the case deadline when the case is running. The value is specified in one of the following formats:</p> <ul style="list-style-type: none"> If the case deadline is specified as a period, then the value is in the format: <i>minutes^hours^days^weeks^months^years</i> If the case deadline is specified as an expression, then the value is in the format: <i>date expression^time expression</i>

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_case_dl_event	node_id proc_id casenum dead_id	BIGINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_case_dl_event ¹	casenum proc_id node_id	case_information

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_case_dl_fk	casenum proc_id node_id	BIGINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	LARGETABLESIZE
Percentage Increase	LARGETABLEPCTINCREASE
Tablespace	LARGETABLESPACE

Table Activity

The `case_deadline_event` table contains one or more rows for each instance of each procedure definition on the system. Rows are added, updated, and deleted in the following situations.

¹This key enforces the DELETE CASCADE referential action.

A row is...	When...
added	If one of the following conditions occurs: <ul style="list-style-type: none"> • A case is starting and its deadline is defined in the procedure. • The CreateCaseDeadline expression is called in the EAI step.
updated	The UpdateCaseDeadline expression is called in the EAI step.
deleted	If one of the following conditions occurs: <ul style="list-style-type: none"> • The DeleteCaseDeadline expression is called in the EAI step. • The case deadline expired and an event is triggered. • The case is closed.

case_event

The `case_event` table stores information about cases that are interrupted by triggered events when processing the purge, close, resurrect, suspend, or resume operation. The case information is recorded in this table only when the BG process is handling the delayed release EAI steps, which are defined in the triggered event. After finishing the event, the case resumes execution and fetches the temporary case data from the `case_eventtable`.

Structure

The `case_event` table has the following structure:

```
TABLE case_event(
  node_id          number(5)          NOT NULL,
  proc_id          number(5)          NOT NULL,
  major_vers       number(5)          NOT NULL,
  minor_vers       number(5)          NOT NULL,
  eventname        varchar(32)        NOT NULL,
  user_event_name  varchar(32)        NOT NULL,
  casenum          numeric(20)        NOT NULL,
  state            integer            NOT NULL,
  actionparameter  varchar(256)      )
```

Column	Description
node_id	ID of the node that this case is hosted on, as defined in the nodes table.
proc_id	ID of the procedure that this procedure event belongs to, as defined in the proc_index table.
major_vers	Major version number of the procedure version that this case belongs to, as defined in the proc_version table.
minor_vers	Minor version number of the procedure version that this case belongs to, as defined in the proc_version table.
eventname	<p>The name of the procedure event. The value of this column is one of the following:</p> <ul style="list-style-type: none"> • BeforePurge • BeforeClose • AfterClose • BeforeResurrect • AfterResurrect • BeforeSuspend • AfterSuspend • BeforeResume • AfterResume
user_event_name	The name of the event step which you set for the procedure event.
casenum	ID of the case that this event belongs to, as defined in the case_information table.
state	<p>Flag that defines the state of the procedure event after the event is triggered. The meaning for each flag is:</p> <ul style="list-style-type: none"> • 2 the triggered event is in the processing state.

Column	Description
	<ul style="list-style-type: none"> • 3 the triggered event is finished. • 4 the triggered event is canceled. • -1 the triggered event failed.
actionparameter	When an event is triggered, the processing purge, close, resurrect, suspend, or resume operation is interrupted. This column saves case data of the processing operation when the BG process is handling the delayed release EAI steps, which are defined in the triggered event. After finishing the event, the case resumes execution of the operation and fetches the temporary case data from this column.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_case_event	node_id proc_id casenum eventname	LARGETABLESPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_case_event ¹	casenum proc_id node_id	case_information

¹This key enforces the DELETE CASCADE referential action.

Index

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_case_event_fk	casenum proc_id node_id	LARGETABLESPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	LARGETABLESIZE
Percentage Increase	LARGETABLEPCTINCREASE
Tablespace	LARGETABLESPACE

Table Activity

The case_event table contains one or more rows for each instance of each procedure definition on the system. Rows are added, updated, and deleted in the following situations.

A row is...	When...
added	The procedure event enters the processing state.
updated	The procedure event changes from processing to failed or to canceled.
deleted	If one of the following conditions occurred: <ul style="list-style-type: none"> The case is purged. The procedure event is finished.

A row is...	When...
	<ul style="list-style-type: none"> The procedure event failed. The procedure event is canceled.

casenum_gaps

The casenum_gaps table holds the free case number gaps.

If the case number or the subcase number generated from the sequence table reaches the maximum case number, 4294967295, then the following cases cannot be started. This table is used to create more available case numbers by reusing previous blocks of case numbers, which no longer exist. The free case numbers are available either because the case numbers have never been used or from the original cases that have been purged.

TIBCO iProcess Engine checks the casenum_gaps table to find out whether any free case numbers are available for reuse before allocating a sequence from the end of the case numbers.

The CASENUM_FIND_GAPS stored procedure adds a list of free case number gaps to the casenum_gaps table, it scans a range of case numbers and create available blocks of free case numbers for reuse. For more information, see [CASENUM_FIND_GAPS](#).



Note: This table is not populated by the system and it remains empty unless the CASENUM_FIND_GAPS stored procedure is running to populate it.

Structure

The casenum_gaps table has the following structure:

```
TABLE casenum_gaps(
  casenum_min    number(20)    NOT NULL,
  casenum_max    number(20)    NOT NULL)
```

Column	Description
casenum_min	The minimum case number in a gap.
casenum_max	The maximum case number in a gap.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_casenum_gaps	casenum_min	MASSIVETABLESPACE

Foreign Keys

None.

Triggers

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MASSIVETABLESIZE
Percentage Increase	MASSIVETABLEPCTINCREASE
Tablespace	MASSIVETABLESPACE

Table Activity

The `casenum_gaps` table contains one or more rows for each instance of each procedure definition on the system. Rows are added, updated, and deleted in the following situations.

A row is...	When...
added	running the <code>CASENUM_FIND_GAPS</code> stored procedure.
updated	running TIBCO iProcess Engine.
deleted	running TIBCO iProcess Engine.

See Also

[CASENUM_FIND_GAPS](#)

Work Items

This section describes the tables that are used to store information about work item data - the combination of fields and their values that are held in iProcess forms (also known as “pack data”).

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



staffo

The **staffo** table holds information about *outstanding steps*, that is, steps that have been delivered to work queues but not yet released (or otherwise removed).

Structure

The staffo table is structured as follows:

```
TABLE staffo(
    o_flags                number(5)                NULL,
    o_queueename            varchar2(24)              NULL,
    o_locker                varchar2(24)              NULL,
    o_username              varchar2(49)              NULL,
    o_startname             varchar2(49)              NULL,
    o_dirname               varchar2(12)              NOT NULL,
    o_dirdesc               varchar2(24)              NULL,
    o_procname              varchar2(8)               NOT NULL,
    o_procdesc              varchar2(24)              NULL,
    o_casedesc              varchar2(24)              NULL,
    o_casenum               number(20)                NULL,
    o_placeno               number(5)                 NULL,
    o_dirflags              number(5)                 NULL,
    o_procflags             number(5)                 NULL,
    o_host                  varchar2(24)              NOT NULL,
    o_pnum                  number(5)                 NOT NULL,
    o_pnumcount             number(5)                 NOT NULL,
    o_caseptr               number(15)                NULL,
    o_reqidhost             number(24)                NOT NULL,
    o_reqid                 number(20)                NOT NULL,
    o_deadline              date                     NULL,
    o_reqstamp              date                     NULL,
    o_qparam1               varchar2(24)              NULL,
    o_qparam2               varchar2(24)              NULL,
    o_qparam3               varchar2(12)              NULL,
    o_qparam4               varchar2(12)              NULL,
    o_itempriority           varchar2(24)              NULL,
    o_priority_changed       date                     NULL,
    o_majorvers             number(5)                 NOT NULL,
    o_minorvers             number(5)                 NOT NULL)
```

Column	Description
o_flags	Flags associated with this work item. For internal use only.
o_queueename	Queue name of the user or group queue that contains this work item, as defined in the user_names table.
o_locker	Name of the user who has locked the queue (if it is locked), as defined in

Column	Description
	the user_names table. Note: This column is not written to or updated unless the <code>WIS_WRITELOCKS</code> parameter in the <code>SWDIR\etc\staffcfg</code> file is set.
<code>o_username</code>	Queue name of the user or group queue that contains this work item, as defined in the user_names table.
<code>o_startname</code>	Username of the user who started the case that this work item belongs to, as defined in the user_names table.
<code>o_dirname</code>	Step name of the step that generated this work item.
<code>o_dirdesc</code>	Step description of the step that generated this work item.
<code>o_procname</code>	Procedure name of the procedure that generated this work item, as defined in the proc_index table.
<code>o_procdesc</code>	Procedure description of the procedure that generated this work item, as defined in the proc_index table.
<code>o_casedesc</code>	Case description of the case that this work item belongs to, as defined in the case_information table.
<code>o_casenum</code>	Case number of the case that this work item belongs to, as defined in the case_information table.
<code>o_placeno</code>	Step mark number. For internal use only.
<code>o_dirflags</code>	Step flags. For internal use only.
<code>o_procflags</code>	Procedure flags. For internal use only.
<code>o_host</code>	ID of the node that this work item is associated with, as defined in the nodes table.
<code>o_pnum</code>	Procedure number of the procedure that generated this work item, as

Column	Description
	defined in the proc_index table.
o_pnumcount	Version count of procedure. For internal use only.
o_caseptr	Case control record number. For internal use only.
o_reqidhost	Nodename of the node where the o_reqid is generated, as defined in the nodes table.
o_reqid	Unique ID for this work item, generated from the sequences table.
o_deadline	Date and time that the deadline (if defined) expires on this work item. If no deadline is set this value appears as 12/31/3000 11:15:00 PM.
o_reqstamp	Timestamp when this work item was delivered to the queue.
o_qparam1	Value of work queue parameter 1 for this work item.
o_qparam2	Value of work queue parameter 2 for this work item.
o_qparam3	Value of work queue parameter 3 for this work item.
o_qparam4	Value of work queue parameter 4 for this work item.
o_itempriority	<p>Priority definition for this work item, in the format:</p> <p><i>base:increment:number:period:type</i></p> <p>where:</p> <ul style="list-style-type: none"> <i>base</i> is the base priority value for this work item. <i>increment</i> is the amount that will be added to the item's priority value whenever the <i>period</i> expires. <i>number</i> is the number of increments that will be added to the item's priority value. <i>period</i> is the time period, in the units specified in <i>type</i>, which must expire before the item's priority value is incremented.

Column	Description
	<ul style="list-style-type: none"> <i>type</i> is the unit of measure of the <i>period</i>, either “M” or “m” for minutes, “H” or “h” for hours or “D” or “d” for days.
o_priority_changed	Timestamp when the priority value for this work item was last changed.
o_majorvers	Major version number of the procedure that generated this work item, as defined in the proc_version table.
o_minorsvers	Minor version number of the procedure that generated this work item, as defined in the proc_version table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_staffo	o_reqid o_reqidhost	HUGEINDEXSPACE

Foreign Keys

None.

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_staffo	o_queueename	HUGEINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	HUGETABLESIZE
Percentage Increase	HUGETABLEPCTINCREASE
Tablespace	HUGETABLESPACE

Table Activity

The `staffo` table contains one row for every outstanding step on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a work item is sent out to a queue.
updated	any of the following occur: <ul style="list-style-type: none"> a work item is kept and any changes have been made. a work item's priority value changes. a work item is opened and the <code>WIS_WRITELOCKS</code> parameter in the <code>SWDIR\etc\staffcfg</code> file is set.
deleted	either: <ul style="list-style-type: none"> a work item is released or withdrawn. a case is closed or purged.

pack_data

The `pack_data` table holds the field name and value of every assigned field in every outstanding step on the system.

When a work item is sent out to a queue, field data is copied from the [case_data](#) table to the [pack_data](#) table. The client uses the field values in the [pack_data](#) table to fill out the form correctly. When the form is kept any changed fields are updated in the [pack_data](#)

table. When a work item is released, field data is moved from the [pack_data](#) table to the [case_data](#) table.

Structure

The `pack_data` table has the following structure:

```
TABLE pack_data (
  reqid          number(20)      NOT NULL,
  node_id        number(5)       NOT NULL,
  proc_id        number(5)       NOT NULL,
  casenum        number(20)      NOT NULL,
  field_name     varchar2(31)    NOT NULL,
  field_value    varchar2(255)   NULL,
  field_flags    number(5)       NOT NULL)
```

Column	Description
<code>reqid</code>	ID of the work item that this field belongs to, as defined in the staffo table.
<code>node_id</code>	ID of the node that this field is associated with, as defined in the nodes table.
<code>proc_id</code>	Number of the procedure that this field belongs to, as defined in the proc_index table.
<code>casenum</code>	Case number that this field belongs to, as defined in the case_information table.
<code>field_name</code>	Name of the field, as defined in the case_data table.
<code>field_value</code>	Value of the field. Note: A memo field has a value of 1. The associated memo data is stored in the pack_memo table.
<code>field_flags</code>	Status of the field. For internal use only.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_pack_data	reqid node_id field_name	HUGEINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	HUGETABLESIZE
Percentage Increase	HUGETABLEPCTINCREASE
Tablespace	HUGETABLESPACE

Table Activity

The pack_data table contains one record for every assigned field that contains data has a value other than SW_NA) in every outstanding step on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Either: <ul style="list-style-type: none"> a step is sent out.

A row is...	When...
	<ul style="list-style-type: none"> a field is assigned a value on a keep or release.
updated	An assigned field has its value changed on a keep or release.
deleted	any of the following occur: <ul style="list-style-type: none"> a release instruction for a work item is processed by the background process. a work item is withdrawn. a case is purged.

pack_memo

The `pack_memo` table stores memo data associated with memo fields in the `pack_data` table before upgrading to iProcess Engine 11.6.

Since iProcess Engine version 11.6, all the new memo data associated with the memo fields is stored in the `BLOB` data type in the `pack_nmemo` table.

11.6 You can migrate case memo data in the `pack_memo` table to the `pack_nmemo` table when upgrading to iProcess Engine or migrate them by using the `swutil MIGRATEMEMOS` command after the upgrades.

When a work item is sent out to a queue, memo data is copied from the `memo` table to the `pack_memo` table. The client uses the memo data in the `pack_memo` table to fill out the form correctly. When the form is kept any changed memo data is updated in the `pack_memo` table. When a work item is released memo data is moved from the `pack_memo` table to the `memo` table.

Structure

The `pack_memo` table is structured as follows:

```
TABLE pack_memo (
  reqid          number(20)          NOT NULL,
  node_id        number(5)           NOT NULL,
  proc_id        number(5)           NOT NULL,
```

casenum	number(20)	NOT NULL,
memo_id	number(4)	NOT NULL,
memo_index	number(10)	NOT NULL,
memo_size	number(10)	NOT NULL,
memo_data	blob	NOT NULL,
array_idx	number(6)	NOT NULL)

Column	Description
reqid	ID of the work item that this memo belongs to, as defined in the staffo table.
node_id	ID of the node that this memo is associated with, as defined in the nodes table.
proc_id	Number of the procedure that this memo belongs to, as defined in the proc_index table.
casenum	Case number that this memo belongs to, as defined in the case_information table.
memo_id	Unique (for this case) ID of this memo.
memo_index	<p>Index number in the set of rows that make up this memo.</p> <p>If a memo is longer than 30,000 bytes multiple rows (in 30,000 byte chunks) are used to store the memo data. Each segment of the memo data is uniquely identified by its memo_index value.</p> <p>Note:</p> <ul style="list-style-type: none"> If you have upgraded your system from one of the following versions, existing memos are divided into 2000 byte chunks: <ul style="list-style-type: none"> (UNIX Oracle) any Version i9.n-o iProcess Engine, or from a pre-Version 9.0-o(0.15) Process Engine. (Windows Oracle) any Version 9.0-o Process Engine. However, if a memo is modified, the existing rows are deleted and then re-added using 30,000 byte chunks.
memo_size	Size (in bytes) of the memo data for this row.

Column	Description
memo_data	Memo data.
array_idx	Either: <ul style="list-style-type: none"> • The array element index number of the memo. • -1, if the memo is not an array memo field.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_pack_memo	reqid node_id casenum memo_id memo_index array_idx	HUGEINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	HUGETABLESIZE

Value	Definition
Percentage Increase	HUGETABLEPCTINCREASE
Tablespace	HUGETABLESPACE

Table Activity

The `pack_memo` table contains one or more rows for every assigned memo field that contains data (i.e. that has a value other than `SW_NA`) in every outstanding step on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Either: <ul style="list-style-type: none"> a step containing memo data is sent out. a memo field is assigned a value on a keep or release.
updated	An assigned memo field has its data changed on a keep or release.
deleted	any of the following occur: <ul style="list-style-type: none"> a release instruction for a work item containing memo data is processed by the background process. a work item containing memo data is withdrawn. a case containing memo data is purged.

pack_nmemo

The `pack_nmemo` table stores memo data associated with memo fields in the [pack_data](#) table after upgrading to iProcess Engine 11.6.

Since iProcess Engine version 11.6, all the new memo data associated with the memo fields is stored in the `BLOB` data type in the `pack_nmemo` table.

You can migrate case memo data in the [pack_memo](#) table to the `pack_nmemo` table when upgrading to iProcess Engine 11.6 or migrate them by using the `swutil MIGRATEMEMOS` command after the upgrades.

When a work item is sent out to a queue, memo data is copied from the `nmemo` table to the `pack_nmemo` table. The client uses the memo data in the `pack_nmemo` table to fill out the form correctly. When the form is kept any changed memo data is updated in the `pack_nmemo` table. When a work item is released memo data is moved from the `pack_nmemo` table to the `nmemo` table.

Structure

The `pack_nmemo` table is structured as follows:

```
TABLE pack_nmemo (
  reqid          number(20)          NOT NULL,
  node_id        number(5)           NOT NULL,
  proc_id        number(5)           NOT NULL,
  casenum        number(20)          NOT NULL,
  memo_id        number(4)           NOT NULL,
  memo_index     number(10)          NOT NULL,
  memo_size      number(10)          NOT NULL,
  memo_data      blob                NOT NULL,
  array_idx      number(6)           NOT NULL)
```

Column	Description
<code>reqid</code>	ID of the work item that this memo belongs to, as defined in the staffo table.
<code>node_id</code>	ID of the node that this memo is associated with, as defined in the nodes table.
<code>proc_id</code>	Number of the procedure that this memo belongs to, as defined in the proc_index table.
<code>casenum</code>	Case number that this memo belongs to, as defined in the case_information table.
<code>memo_id</code>	Unique (for this case) ID of this memo.
<code>memo_index</code>	Index number into the set of rows that make up this memo.

Column	Description
	This value is always 1.
memo_size	Size (in bytes) of the memo data for this row.
memo_data	Memo data.
array_idx	Either: <ul style="list-style-type: none"> • The array element index number of the memo. • -1, if the memo is not an array memo field.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_pack_nmemo	reqid node_id casenum memo_id memo_index array_idx	HUGEINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	HUGETABLESIZE
Percentage Increase	HUGETABLEPCTINCREASE
Tablespace	HUGETABLESPACE

Table Activity

The `pack_nmemo` table contains one row for every assigned memo field that contains data (for example, that has a value other than `SW_NA`) in every outstanding step on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Either: <ul style="list-style-type: none"> • a step containing memo data is sent out. • a memo field is assigned a value on a keep or release.
updated	An assigned memo field has its data changed on a keep or release.
deleted	any of the following occur: <ul style="list-style-type: none"> • a release instruction for a work item containing memo data is processed by the background process. • a work item containing memo data is withdrawn. • a case containing memo data is purged.

qaccess

The `qaccess` table stores details of any non-default sort, filter and display criteria used by iProcess users to access their iProcess queues.

Structure

The qaccess table has the following structure:

```
TABLE qaccess (
  user_name      varchar2(64)    NOT NULL,
  access_type    varchar2(8)     NOT NULL,
  queue_name     varchar2(51)    NOT NULL,
  access_str     varchar2(1024)  NULL)
```

Column	Description
user_name	Name of the user that this row applies to, as defined in the user_names table.
access_type	Type of access criteria defined in this row. Any of the following: <ul style="list-style-type: none"> • SORT defines how work items in the specified queue are sorted. • FILTER defines how work items in the specified queue are filtered. • DISPLAY defines how work items in the specified queue are displayed. • QVERS defines when the queue was last accessed. For internal use only.
queue_name	Name of the (user or group) queue that this row applies to, as defined in the proc_version table. Note: Test queues have the suffix /t.
access_str	Access criteria. For internal use only.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_qaccess	user_name queue_name access_type	MEDIUMINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `qaccess` table contains one row per set of non-default access criteria defined per user per queue.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a set of non-default access criteria is saved for a user.
updated	a set of non-default access criteria is updated for a user.
deleted	a user reverts to using the default criteria.


Case Data Queue Parameters

This section describes the tables that are used to store information about Case Data Queue Parameters (CDQPs).

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



cdqp_def

The `cdqp_def` table holds information about each field that is defined as a Case Data Queue Parameter (CDQP).

Structure

The `cdqp_def` table has the following structure:

```
TABLE cdqp_def (
  def_id          number(10)      NOT NULL,
  field_name      varchar2(31)    NOT NULL,
  data_size       number(5)       NOT NULL,
  description     varchar2(40)    NOT NULL,
  is_predict      number(1)       NOT NULL)
```

Column	Description
def_id	Unique identifier for this CDQP, generated from the sequences table.
field_name	Name of the iProcess field assigned to this CDQP, as defined in the case_data table.
data_size	Maximum size, in characters, of this CDQP.
description	Name used to represent this CDQP in Work Queue Manager dialogs.
is_predict	Flag that defines whether (1) or not (0) this CDQP is used for case prediction.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_cdqp_def	def_id	MEDIUMINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `cdqp_def` table contains one row for each field on the system that is currently defined as a CDQP.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a field is first defined as a CDQP.
updated	an existing CDQP definition is updated.
deleted	an existing CDQP definition is deleted.

cdqp_cfg

The `cdqp_cfg` table holds the details of each mapping of a CDQP to a queue.

Structure

The `cdqp_cfg` table has the following structure:

```
TABLE cdqp_cfg (
  cfg_id          number(10)      NOT NULL,
```

def_id	number(10)	NOT NULL,
queue_name	varchar2(48)	NOT NULL)

Column	Description
cfg_id	Unique ID for this CDQP/queue mapping generated from the sequences table.
def_id	ID of the CDQP that is mapped to the queue_name queue, as defined in the cdqp_def table.
queue_name	Name of the iProcess queue that the CDQP defined in def_id is mapped to, as defined in the user_names table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_cdqp_cfg	cfg_id	MEDIUMINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_cdqp_cfg ¹	def_id	cdqp_def

Indexes

The following index is defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Index Name	Column(s) Indexed	Tablespace
idx_cdqp_cfg_fk	def_id	MEDIUMINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `cdqp_cfg` table contains one row for each mapping of a CDQP to a queue that is defined on the system. For example, if CDQP1 is mapped to 6 queues, and CDQP2 is mapped to 4 queues, the `cdqp_cfg` table contains 10 rows.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a field (that is already defined as a CDQP) is mapped to a queue.
updated	never.
deleted	an existing CDQP mapping is deleted.


Queue Participation and Redirection

This section describes the tables that are used to store information about iProcess participation and redirection records.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



part_defn

The `part_defn` table holds all the *participation records* defined on the system. A participation record defines the dates and times that users are allowed to participate in a particular queue. (The [part_list](#) table defines what users are allowed to use a particular participation record.)

Structure

The part_defn table has the following structure:

```
TABLE part_defn (  
    part_id          number(5)          NOT NULL,  
    queue_name       varchar2(24)       NOT NULL,  
    days_mask        varchar2(7)        NOT NULL,  
    start_time       number(4)          NOT NULL,  
    end_time         number(4)          NOT NULL,  
    style            varchar2(24)       NULL,  
    start_date       number(7)          NOT NULL,  
    end_date         number(7)          NOT NULL)
```

Column	Description
part_id	Unique ID for this participation record.
queue_name	Name of the queue that this participation record allows users to participate in, as defined in the user_names table.
days_mask	Days of the week that users can participate in the specified queue_name. For example, -TWT-SS indicates every day except Monday or Friday.
start_time	Time of day when participation starts.
end_time	Time of day when participation ends.
style	<i>Not used. Reserved for possible future use.</i>
start_date	Date on which participation starts.
end_date	Date on which participation ends.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_part_defn	part_id	MEDIUMINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The part_defn table contains one row for each participation record defined on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a new participation record is added.
updated	an existing participation record is updated.
deleted	an existing participation record is deleted.

part_list

The `part_list` table holds the names of all users who are currently allowed to participate in other queues.

Structure

The `part_list` table has the following structure:

```
TABLE part_list (
  part_id          number(5)          NOT NULL,
  user_name        varchar2(64)      NOT NULL)
```

Column	Description
<code>part_id</code>	ID of the participation record that this participant is a member of, as defined in the part_defn table.
<code>user_name</code>	Name of the user who is allowed to participate (according to the participation definition identified by the <code>part_id</code> value), as defined in the user_names table.

Primary Key

None.

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
<code>fk_part_list¹</code>	<code>part_id</code>	part_defn

¹This key enforces the DELETE CASCADE referential action.

Indexes

The following index is defined for this table.

Index Name	Column(s) indexed	Tablespace
idx_part_list_fk	part_id	MEDIUMINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `part_list` table contains one record for each user designated as a participant in each participation record on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Either: <ul style="list-style-type: none"> a new participation record is added. an existing participation record is updated (if a user is added as part of the update).
updated	never.
deleted	Either:

A row is...	When...
-------------	---------

- | | |
|--|---|
| | <ul style="list-style-type: none"> an existing participation record is deleted. an existing participation record is updated (if a user is deleted as part of the update). |
|--|---|

redir_defn

The `redir_defn` table holds information about which queues are being redirected and which queues they are being redirected to.

Structure

The `redir_defn` table has the following structure:

```
TABLE redir_defn (
  redir_id          number(5)          NOT NULL,
  start_time        number(4)          NOT NULL,
  start_date        number(7)          NOT NULL,
  end_time          number(4)          NOT NULL,
  end_date          number(7)          NOT NULL,
  queue_name        varchar2(24)      NOT NULL,
  destination       varchar2(49)      NOT NULL)
```

Column	Description
<code>redir_id</code>	Unique ID for this redirection record.
<code>start_time</code>	Time that this queue redirection starts.
<code>start_date</code>	Date that this queue redirection starts.
<code>end_time</code>	Time that this queue redirection ends.
<code>end_date</code>	Date that this queue redirection ends.

Column	Description
queue_name	Name of the queue from which work items are to be redirected, as defined in the user_names table.
destination	Name of the queue to which work items are to be redirected, as defined in the user_names table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_redir_defn	redir_id	MEDIUMINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `redir_defn` table contains one record for each redirection record defined on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a queue is redirected.
updated	the details of an existing redirection are updated.
deleted	redirection for a queue is turned off.

Administrative Tables

This section describes the tables that are used to store administrative information about the iProcess system.

Table Relationships

The [flag_table](#) and [version](#) tables have no database-enforced relationships with each other or with any other tables.

flag_table

The `flag_table` table provides a locking mechanism which controls access to the four areas of iProcess administrative data - users, lists, roles and TIBCO iProcess® Engine tables. iProcess administrative data is maintained in two sets of tables:

- The main system data, which iProcess references during normal operation, is stored in tables without a prefix (for example, [user_names](#) or [dbs_fields](#)).
- A copy of this data, containing users' edits that have not yet been released for use by the system, is stored in identical tables which have the same name prefixed by `tsys_` (for example, [tsys_user_names](#) or [tsys_dbs_fields](#)).

The `flag_table` table contains a row for each area of iProcess administrative data, and is used to prevent multiple users from editing the same data at the same time.

When a user edits the data in a particular row (for example, using User Manager to edit user data), the `area_locked` flag is set while editing takes place. On completion of the edit, the `area_locked` flag is cleared. If changes have been made, the `area_changed` flag is set.

When a user requests a Move System Information, the `move_req` flag is set on any rows that have the `area_changed` flag set. When the background process sees a row with `move_req` flagged that is not locked, it locks the area and updates the main system data tables from the `tsys_` tables. When the Move System Information operation completes, all the flags are cleared.

Structure

The flag_table table has the following structure:

```
TABLE flag_table (
  area_id          number(5)          NOT NULL,
  area_locked      number(1)          NOT NULL,
  area_changed     number(1)          NOT NULL,
  move_req         number(1)          NOT NULL,
  user_name        varchar2(64)       NULL)
```

Column	Description
area_id	Unique ID of this area of iProcess administrative data: Either Users (1), iProcess Tables (2), Lists (3) or Roles (4).
area_locked	Flag that defines whether (1) or not (0) the specified area_id is locked. The flag is set by: <ul style="list-style-type: none"> an editor (for example, User Manager) when a user is editing the specified area, to prevent other users from editing the same data. the background process while it is updating the system data, to prevent any users from editing the same data.
area_changed	Flag that defines whether (1) or not (0) the tsys_ tables for the specified area_id contain modified data.
move_req	Flag that defines whether (1) or not (0) the specified area_id needs to be updated by a Move System Information operation.
user_name	Name of the user currently altering data in the given area, as defined in the user_names table. This is either: <ul style="list-style-type: none"> the name of the user doing the editing, or swpro if the background process has the area locked.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_flag_table	area_id	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The flag_table table always contains 4 rows - one row for each area of iProcess administrative data (users, lists, roles and TIBCO iProcess® Engine tables).

The table is populated when the iProcess Engine is installed.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	never.

A row is...	When...
updated	either: <ul style="list-style-type: none"> a Move System Information operation either starts or completes. an edit of a data area either starts or completes.
deleted	never.

version

The `version` table contains version information on system data: currently either CDQP or user data. Processes that hold user details query this table to determine if their internal cache is up to date or not.

Structure

The `version` table has the following structure:

```
TABLE version (
    version_type    varchar2(20)    NOT NULL,
    version_value    number(6)      NOT NULL)
```

Column	Description
<code>version_type</code>	Data type: either <code>cdqp</code> or <code>user</code> .
<code>version_value</code>	Number that is incremented whenever the data is changed.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
<code>pk_version</code>	<code>version_type</code>	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The version table always contains a single row. The table is populated when the iProcess Engine is installed.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	never.
updated	a Move System Information operation is performed and data for users, groups or attributes has been modified (that is, if the <code>move_req</code> flag for the Users data area in the flag_table is set to 1).
deleted	never.

Users and Work Queues

This section describes the tables that are used to store information about iProcess user and group queues.

About User Tables

Note that there are two sets of user tables:

- The tables prefixed with `user_` hold the main system data, which TIBCO iProcess® Engine references during normal operation.
- The tables prefixed with `tsys_user_` hold a copy of this data, containing users' edits that have not yet been released for use by the system.

The `tsys_user_` tables are purged and rewritten whenever a user edits user data (either by saving changes made in the User Manager utility in the TIBCO iProcess Administrator, importing data with `SWDIR\bin\swutil USERINFO`, or by using TIBCO iProcess Objects).


The `user_` tables are purged and rewritten with the updated information from the `tsys_user_` tables when a Move System Information is performed - *if* the [flag_table](#) indicates that the appropriate data area has been modified.

Access to the `user_` and `tsys_user_` tables is controlled by a locking mechanism provided by the [flag_table](#) table.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



user_names

The `user_names` table holds the names of all iProcess user and group queues registered on the system.

Structure

The `user_names` table has the following structure:

```
TABLE user_names (  
    node_id          number(5)          NOT NULL,  
    user_id          number(6)          NOT NULL,  
    user_name        varchar2(64)       NOT NULL,  
    user_type        varchar2(1)       NOT NULL)
```

Column	Description
node_id	ID of the node that this (user or group) queue is registered on, as defined in the

Column	Description
	nodes table.
user_id	Unique ID for this (user or group) queue. Note: Users and groups have separate ID sequences, as defined in the user_type column, so both a user and a group can have the same user_id value.
user_name	Name of this (user or group) queue.
user_type	Queue type: user (U) or group (G).

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_user_names	user_id user_type node_id	MEDIUMINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_user_names ¹	node_id	nodes

Indexes

The following indexes are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Index Name	Column(s) Indexed	Tablespace
idx_user_names_fk	node_id	MEDIUMINDEXSPACE
idx_user_names	user_name	MEDIUMINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The user_names table contains one row for each user or group queue defined on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	<p>a Move System Information is performed, if the flag_table indicates that the Users data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_user_names table.</p>
updated	never.
deleted	a Move System Information is performed, if the flag_table indicates that the Users data area has been modified.

A row is...	When...
-------------	---------

Note: The table is purged and rewritten using the values from the [tsys_user_names](#) table.

user_attrib

The user_attrib table holds the definitions of all iProcess attributes defined on the system.

Structure

The user_attrib table has the following structure:

```
TABLE user_attrib (
  node_id          number(5)          NOT NULL,
  attribute_id     number(5)          NOT NULL,
  attribute_name   varchar2(15)      NOT NULL,
  attribute_type   varchar2(1)       NOT NULL)
```

Column	Description
node_id	ID of the node that this attribute is defined on, as defined in the nodes table.
attribute_id	Unique ID for this attribute.
attribute_name	Name of this attribute.
attribute_type	Attribute type: Either ASCII (A), Numeric (R), Date (D) or Time (T).

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_user_attrib	attribute_id node_id	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_user_attrib ¹	node_id	nodes

Indexes

The following indexes are defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_user_attrib_fk	node_id	SMALLINDEXSPACE
idx_user_attrib	attribute_name	SMALLINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

¹This key enforces the DELETE CASCADE referential action.

Table Activity

The `user_attr` table contains one or more rows for each iProcess attribute defined on the system. The following action takes place if an attribute's maximum length is defined as follows:

- 24 characters or less, one row is created for the attribute.
- 25 characters or more, one row is created for each 24 characters of the attribute's maximum length, and a number is appended to the `attribute_name` entry for each row.

The following example illustrates this:

- `DESCRIPTION` is a system-defined attribute of type ASCII with a maximum length of 24 characters; one row is therefore added to the table.
- `QSUPERVISORS` is a system-defined attribute of type ASCII with a maximum length of 48 characters; two rows are therefore added to the table - `QSUPERVISORS_01` and `QSUPERVISORS_02`, each with a unique `attribute_id`.
- `JOBDESC` is a user-defined attribute of type ASCII with a maximum length of 60 characters; two rows are therefore added to the table - `JOBDESC_01` and `JOBDESC_02`, each with a unique `attribute_id`.

<code>node_id</code>	<code>attribute_id</code>	<code>attribute_name</code>	<code>attribute_type</code>
1	1	DESCRIPTION	A
1	2	LANGUAGE	A
1	3	MENUNAME	A
1	4	SORTMAIL	A
1	5	USERFLAGS	A
1	6	QSUPERVISORS_01	A
1	7	QSUPERVISORS_02	A
1	9	JOBDESC_01	A
1	10	JOBDESC_02	A

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a Move System Information is performed, if the flag_table indicates that the Users data area has been modified. Note: The table is purged and rewritten using the values from the tsys_user_names table.
updated	never.
deleted	a Move System Information is performed, if the flag_table indicates that the Users data area has been modified. Note: The table is purged and rewritten using the values from the tsys_user_names table.

user_setting

The `user_setting` table holds the settings that a given user has defined in the iProcess Workspace (Browser). This enables a user to keep the same settings when working on any machine.

Structure

The `user_setting` table has the following structure:

```
TABLE user_setting (
  username      varchar2(32 char)      NOT NULL,
  userkey       varchar2(128 char)     NOT NULL
  valindex      number(10)              NOT NULL,
  vallen        number(10)              NOT NULL
  uservalue     blobNULL
```

Column	Description
username	The name of the user whose preferences are defined in the user_names table.

Column	Description
userkey	The key of the user.
valindex	<p>The index number into the set of rows that make up the user value.</p> <p>If the user value is larger than 30,000 bytes, multiple rows (in 30,000 byte chunks) are used to store the user value. Each segment of the user value is uniquely identified by its valindex value.</p> <p>Note: Since iProcess Engine 11.6, the volume of a row is upgraded. The value of valindex might always be 1.</p>
vallen	The size (in bytes) of the memo data for this row.
uservalue	The value of the particular user identified by userkey.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_user_setting	username userkey valindex	BIGINDEXSPACE

user_values

The **user_values** table holds the values for all attributes defined for all users and groups on the system.

Structure

The user_values table has the following structure:

```
TABLE user_values (
  node_id          number(5)          NOT NULL,
```

user_id	number(6)	NOT NULL,
attribute_id	number(5)	NOT NULL,
attribute_value	varchar2(24) NULL,	
user_type	varchar2(1)	NOT NULL)

Column	Description
node_id	ID of the node that this attribute is defined on, as defined in the nodes table.
user_id	ID of the (user or group) queue that this attribute value is associated with, as defined in the user_names table.
attribute_id	ID of the attribute that this attribute value is associated with, as defined in the user_attrib table.
attribute_value	Value of this attribute. Note: If an attribute value is longer than 24 characters multiple rows are used to store the value. Each segment of the value is uniquely identified by its attribute_id value, as defined in the user_attrib table.
user_type	Type of the (user or group) queue that this attribute value is associated with, as defined in the user_names table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_user_values	user_id attribute_id user_type node_id	BIGINDEXSPACE

Foreign Keys

The following foreign keys are defined for this table.

Key Name ¹	Column(s)	Referenced in Table...
fk_user_values1	node_id user_id user_type	user_names
fk_user_values2	attribute_id node_id	user_attrib

Indexes

The following indexes are defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_user_values_fk1	node_id user_id user_type	BIGINDEXSPACE
idx_user_values_fk2	attribute_id node_id	BIGINDEXSPACE
idx_user_values	attribute_id	BIGINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	BIGTABLESIZE
Percentage Increase	BIGTABLEPCTINCREASE
Tablespace	BIGTABLESPACE

¹These keys enforce the DELETE CASCADE referential action.

Table Activity

The `user_values` table contains one or more rows per assigned attribute per (user or group) queue on the system. If an attribute value's length is:

- 24 characters or less, one row is created for the attribute value.
- more than 24 characters, one row is created for each 24 characters of the attribute value.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	<p>a Move System Information is performed, if the flag_table indicates that the Users data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_user_names table.</p>
updated	never.
deleted	<p>a Move System Information is performed, if the flag_table indicates that the Users data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_user_names table.</p>

user_memb

The `user_memb` table defines users' membership of groups.

Structure

The `user_memb` table has the following structure:

```
TABLE user_memb (
  node_id          number(5)          NOT NULL,
  user_id          number(6)          NOT NULL,
  group_id         number(6)          NOT NULL)
```

Column	Description
node_id	ID of the node that this user/group combination is defined on, as defined in the nodes table.
user_id	ID of the user who belongs to the group, as defined in the user_names table.
group_id	ID of the group that the user belongs to, as defined in the user_names table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_user_memb	user_id node_id group_id	BIGINDEXSPACE

Foreign Keys

None.

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_user_memb	user_id group_id	BIGINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	BIGTABLESIZE
Percentage Increase	BIGTABLEPCTINCREASE
Tablespace	BIGTABLESPACE

Table Activity

The `user_memb` table contains one row for every user/group member relationship defined on the system. For example, if a user is a member of three different groups, there are three rows for that user in this table.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	<p>a Move System Information is performed, if the flag_table indicates that the Users data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_user_names table.</p>
updated	never.
deleted	<p>a Move System Information is performed, if the flag_table indicates that the Users data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_user_names table.</p>

leavers

The `leavers` table stores information about the recently deleted users.

Structure

The leavers table has the following structure:

```
TABLE leavers (
  node_id          number(5)                NOT NULL,
  user_name        varchar2(64)             NOT NULL,
  destination      varchar2(64)             NOT NULL,
  timestamp        number(20)               NOT NULL,
  status           number(2)                NOT NULL)
```

Column	Description
node_id	ID of the node that this (user or group) queue is registered on, as defined in the nodes table.
user_name	Name of this deleted user.
destination	Description of this deleted user.
timestamp	When the current status is set.
status	Status of the redirection performed on the leaver. One of the following values: <ul style="list-style-type: none"> 0 (LEAVER_WILL_BE_REDIRECTED) The leaver will be redirected. 1 (LEAVER_IS_BEING_REDIRECTED) The leaver is being redirected. 2 (LEAVER_FINISH_REDIRECTION) The leaver has been redirected.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_leavers	user_name node_id	MEDIUMINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `leavers` table contains one row for each recently deleted user.

Rows are added, updated, and deleted in the following situations.

A row is...	When...
added	a user is deleted.
updated	one of the following conditions is met: <ul style="list-style-type: none"> the iProcess Engine is started, the status of the deleted user is changed.
deleted	all of the following conditions are met: <ul style="list-style-type: none"> the status field is set to 2 (<code>LEAVER_FINISH_REDIRECTION</code>),

A row is...	When...
	<ul style="list-style-type: none"> the time length defined by the WQS_LEAVER_PERIOD process attribute has passed since the status field was set to 2, the iProcess Engine is shut down, or a Move System Information operation is performed.

tsys_user_names

The `tsys_user_names` table is a copy of the [user_names](#) table. It is identical to the [user_names](#) table except for the following conditions:

- The primary key name is `pk_tsys_user_names`.
- No foreign keys or indexes are defined.
- The table is purged and rewritten when a user edits user data, either by saving changes made in the User Manager utility in the TIBCO iProcess Administrator, importing data with `SWDIR\bin\swutil USERINFO`, or by using TIBCO iProcess Objects. (The [flag_table](#) is also updated to indicate that the Users data area has been modified.)

tsys_user_attrb

The `tsys_user_attrb` table is a copy of the [user_attrb](#) table. It is identical to the [user_attrb](#) table except for the following:

- The primary key name is `pk_tsys_user_attrb`.
- No foreign keys or indexes are defined.
- The table is purged and rewritten when a user edits user data, either by saving changes made in the User Manager utility in the TIBCO iProcess Administrator, importing data with `SWDIR\bin\swutil USERINFO`, or by using TIBCO iProcess Objects. (The [flag_table](#) is also updated to indicate that the Users data area has been modified.)

tsys_user_values

The `tsys_user_values` table is a copy of the `user_values` table. It is identical to the `user_values` table except for the following:

- The primary key name is `pk_tsys_user_values`.
- The foreign key names are `fk_tsys_user_values1` and `fk_tsys_user_values2`.
- The index names are `idx_tsys_user_values_fk1` and `idx_tsys_user_values_fk2`.
- The table is purged and rewritten when a user edits user data, either by saving changes made in the User Manager utility in the TIBCO iProcess Administrator, importing data with `SWDIR\bin\swutil USERINFO`, or by using TIBCO iProcess Objects. (The `flag_table` is also updated to indicate that the Users data area has been modified.)

tsys_user_memb

The `tsys_user_memb` table is a copy of the `user_memb` table. It is identical to the `user_memb` table except for the following:

- The primary key name is `pk_tsys_user_memb`.
- The index name is `idx_tsys_user_memb`.
- The table is purged and rewritten when a user edits user data, either by saving changes made in the User Manager utility in the TIBCO iProcess Administrator, importing data with `SWDIR\bin\swutil USERINFO`, or by using TIBCO iProcess Objects. (The `flag_table` is also updated to indicate that the Users data area has been modified.)

Roles

This section describes the tables that are used to store information about iProcess roles.

About Roles

Note that:

- The [role_users](#) table holds the main system data, which TIBCO iProcess® Engine references during normal operation.
- The [tsys_role_users](#) holds a copy of this data, containing users' edits that have not yet been released for use by the system.

The [tsys_role_users](#) table is purged and rewritten whenever a user edits role data (either by saving changes made in the User Manager utility in the TIBCO iProcess Administrator, importing data with `SWDIR\bin\swutil ROLEINFO`, or by using TIBCO iProcess Objects).


When a Move System Information is performed, if the [tsys_role_users](#) table has been changed, the [role_users](#) table is purged and rewritten with the updated information from the [tsys_role_users](#) table.

Access to the [role_users](#) and [tsys_role_users](#) tables is controlled by a locking mechanism provided by the [flag_table](#) table.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



role_users

The `role_users` table holds information about which roles are defined on the system, and which queues are assigned to them.

Structure

The `role_users` table has the following structure:

```
TABLE role_users (  
    node_id          number(5)          NOT NULL,  
    role_id          number(5)          NOT NULL,  
    role_name        varchar2(15)       NOT NULL,  
    usernode_name    varchar2(49)       NOT NULL)
```

Column	Description
node_id	ID of the node that this role is registered on, as defined in the nodes table.
role_id	Unique ID for this role.
role_name	Name of this role.
usernode_name	Name of the (user or group) queue that the role is assigned to, as defined in the user_names table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_role_users	role_id node_id	MEDIUMINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_role_users ¹	node_id	nodes

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_role_users_fk	node_id	MEDIUMINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE

¹This key enforces the DELETE CASCADE referential action.

Value	Definition
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `role_users` table contains one row for each role defined on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	<p>a Move System Information is performed, if the flag_table indicates that the Roles data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_role_users table.</p>
updated	never.
deleted	<p>a Move System Information is performed, if the flag_table indicates that the Roles data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_role_users table.</p>

tsys_role_users

The `tsys_role_users` table is a copy of the [role_users](#) table. It is identical to the [role_users](#) table except for the following:

- The primary key name is `pk_tsys_role_users`.
- The foreign key name is `fk_tsys_role_users_fk`.
- The index name is `idx_tsys_role_users_fk`.
- The table is purged and rewritten when a user edits role data, either by saving changes made in the User Manager utility in the TIBCO iProcess Administrator,

importing data with `SWDIR\bin\swutil ROLEINFO`, or by using TIBCO iProcess Objects. (The `flag_table` is also updated to indicate that the Roles data area has been modified.)

TIBCO iProcess Tables

This section describes the tables that are used to store information about TIBCO iProcess tables.

**Note**

This section uses the term *TIBCO iProcess table* to mean an iProcess table, and *table* to mean an Oracle table.

About TIBCO iProcess Tables

Note that there are four sets of related tables, as follows:

Prefix	Description
db_	Hold the main system data on <i>installed</i> TIBCO iProcess tables, which iProcess references during normal operation.
str_ db_	Hold the main system data on <i>uninstalled</i> TIBCO iProcess tables, which iProcess references during normal operation. Note: There is no str_db_values table, because no data is associated with uninstalled TIBCO iProcess tables.
tsys_ db_	Hold a copy of the main (db_ and str_db_) system data, containing users' edits that have not yet been released for use by the system.
tmp_ db_	Temporary tables used only when importing TIBCO iProcess® Engine tables (using <code>SWDIR\bin\swutil IMPORT</code>).

The tsys_db_ tables are purged and rewritten whenever a user edits TIBCO iProcess® Engine table data (either by saving changes made in the Table Manager utility in the TIBCO iProcess Administrator, modifying data with `SWDIR\bin\swutil IMPORT` or `DELTAB`, or by using TIBCO iProcess Objects).


When a Move System Information is performed, if the `tsys_dbs_` tables have been changed, the `dbs_` and/or `str_dbs_` tables are purged and rewritten with the updated information from the `tsys_dbs_` tables.

Access to the `dbs_` and `tsys_dbs_` tables is controlled by a locking mechanism provided by the [flag_table](#) table.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



dbnames

The dbnames table holds the names of all *installed* TIBCO iProcess® Engine tables.

Structure

The dbnames table has the following structure:

```
TABLE dbnames (  
    node_id          number(5)          NOT NULL,  
    db_id            number(5)          NOT NULL,  
    db_name          varchar2(15)      NOT NULL)
```

Column	Description
node_id	ID of the node that this iProcess Engine table is defined on, as defined in the nodes table.
db_id	Unique ID for this iProcess Engine table.
db_name	Name of this iProcess Engine table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_dbnames	db_id node_id	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_dbs_names ¹	node_id	nodes

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_dbs_names_fk	node_id	SMALLINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `dbs_names` table contains one row for each installed TIBCO iProcess table on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a Move System Information is performed, if the flag_table indicates that the

¹This key enforces the DELETE CASCADE referential action.

A row is...	When...
	<p>Tables data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_dbs_names table.</p>
updated	never.
deleted	<p>a Move System Information is performed, if the flag_table indicates that the Tables data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_dbs_names table.</p>

dbfs_fields

The `dbfs_fields` table holds the field definitions for every field in every *installed* iProcess table.

Structure

The `dbfs_fields` table has the following structure:

```
TABLE dbfs_fields (
  node_id      number(5)           NOT NULL,
  dbfs_id      number(5)           NOT NULL,
  field_id     number(5)           NOT NULL,
  field_name   varchar2(15)        NOT NULL,
  field_type   varchar2(1)         NOT NULL,
  field_length number(5)           NOT NULL,
  field_decimals number(5)         NOT NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this field is defined on, as defined in the nodes table.
<code>dbfs_id</code>	ID of the table that this field is defined in, as defined in the dbfs_names table.

Column	Description
field_id	Unique ID for the field in this TIBCO iProcess® Engine table.
field_name	Name of this field.
field_type	Field type: Either ASCII (A), Numeric (R), Date (D) or Time (T).
field_length	Length of this field, in characters.
field_decimals	Number of characters after the decimal place in this field (relevant only for Numeric fields).

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_dbs_fields	dbs_id field_id node_id	MEDIUMINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_dbs_fields ¹	node_id dbs_id	dbs_names

Indexes

The following indexes are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Index Name	Column(s) Indexed	Tablespace
idx_dbs_fields_fk	dbs_id node_id	MEDIUMINDEXSPACE
idx_dbs_fields	field_id dbs_id	MEDIUMINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `dbs_fields` table contains one row for each field in each installed TIBCO iProcess table.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	<p>a Move System Information is performed, if the flag_table indicates that the Tables data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_dbs_fields table.</p>
updated	never.
deleted	a Move System Information is performed, if the flag_table indicates that the Tables data area has been modified.

A row is...	When...
-------------	---------

Note: The table is purged and rewritten using the values from the [tsys_dbs_fields](#) table.

dbvalues

The `dbvalues` table holds all field values for all *installed* TIBCO iProcess® Engine tables.

Structure

The `dbvalues` table has the following structure:

```
TABLE dbvalues (
  node_id          number(5)          NOT NULL,
  dbs_id           number(5)          NOT NULL,
  record_id        number(5)          NOT NULL,
  field_id         number(5)          NOT NULL,
  field_value      varchar2(30)       NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this field value is stored on, as defined in the nodes table.
<code>dbs_id</code>	ID of the table that this field value is stored in, as defined in the dbs_names table.
<code>record_id</code>	Unique ID for this record in the iProcess Engine table.
<code>field_id</code>	ID of the field held in this record, as defined in the dbs_fields table.
<code>field_value</code>	Value of the field in this record.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_dbs_values	dbs_id record_id field_id node_id	MEDIUMINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_dbs_values ¹	dbs_id field_id node_id	dbs_fields

Indexes

The following indexes are defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_dbs_values_fk	dbs_id field_id node_id	MEDIUMINDEXSPACE
idx_dbs_values	record_id field_id dbs_id	MEDIUMINDEXSPACE

Storage

The following STORAGE values are defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `db_values` table contains one row for each field of each record in each installed TIBCO iProcess table on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	<p>a Move System Information is performed, if the flag_table indicates that the Tables data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_dbs_values table.</p>
updated	never.
deleted	<p>a Move System Information is performed, if the flag_table indicates that the Tables data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_dbs_values table.</p>

tsys_dbs_names

The `tsys_dbs_names` table is a copy of the [dbs_names](#) table. It is identical to the [dbs_names](#) table except for the following:

- The primary key name is `pk_tsys_dbs_names`.
- The foreign key name is `fk_tsys_dbs_names`.

- The index name is `idx_tsys_dbs_names_fk`.
- The table is purged and rewritten when a user edits iProcess Engine table data, either by saving changes made in the Table Manager utility in the TIBCO iProcess Administrator, modifying data with `SWDIR\bin\swutil IMPORT` or `DELTAB`, or by using TIBCO iProcess Objects. (The [flag_table](#) is also updated to indicate that the Tables data area has been modified.)

tsys_dbs_fields

The `tsys_dbs_fields` table is a copy of the [dbs_fields](#) table. It is identical to the [dbs_fields](#) table except for the following:

- The primary key name is `pk_tsys_dbs_fields`.
- The foreign key name is `fk_tsys_dbs_fields`.
- The index names are `idx_tsys_dbs_fields_fk` and `idx_tsys_dbs_fields`.
- The table is purged and rewritten when a user edits iProcess Engine table data, either by saving changes made in the Table Manager utility in the TIBCO iProcess Administrator, modifying data with `SWDIR\bin\swutil IMPORT` or `DELTAB`, or by using TIBCO iProcess Objects. (The [flag_table](#) is also updated to indicate that the Tables data area has been modified.)

tsys_dbs_values

The `tsys_dbs_values` table is a copy of the [dbs_values](#) table. It is identical to the [dbs_values](#) table except for the following:

- The primary key name is `pk_tsys_dbs_values`.
- The foreign key name is `fk_tsys_dbs_values`.
- The index names are `idx_tsys_dbs_values_fk` and `idx_tsys_dbs_values`.
- The table is purged and rewritten when a user edits iProcess Engine table data, either by saving changes made in the Table Manager utility in the TIBCO iProcess Administrator, modifying data with `SWDIR\bin\swutil IMPORT` or `DELTAB`, or by using TIBCO iProcess Objects. (The [flag_table](#) is also updated to indicate that the Tables data area has been modified.)

str_dbs_names

The `str_dbs_names` table is a copy of the `dbs_names` table. It is identical to the `dbs_names` table except for the following:

- It holds the names of all *uninstalled* TIBCO iProcess® Engine tables.
- The primary key name is `pk_str_dbs_names`.
- No foreign keys or indexes are defined.
- It contains one row for each uninstalled TIBCO iProcess table on the system.

str_dbs_fields

The `str_dbs_fields` table is a copy of the `dbs_fields` table. It is identical to the `dbs_fields` table except for the following:

- It holds the field definitions for every field in every *uninstalled* TIBCO iProcess table.
- The primary key name is `pk_str_dbs_fields`.
- No foreign keys are defined.
- The index name is `idx_str_dbs_fields`.
- It contains one row for each field in each uninstalled TIBCO iProcess table on the system.

ttmp_dbs_names

The `ttmp_dbs_names` table is a temporary copy of the `dbs_names` table. It is identical to the `dbs_names` table except for the following:

- The primary key name is `pk_ttmp_dbs_names`.
- No foreign keys or indexes are defined.
- In most situations the number of rows in the table should be zero.

ttmp_dbs_fields

The ttmp_dbs_fields table is a temporary copy of the [dbs_fields](#) table. It is identical to the [dbs_fields](#) table except for the following:

- The primary key name is pk_ttmp_dbs_fields.
- No foreign keys or indexes are defined.
- In most situations the number of rows in the table should be zero.

ttmp_dbs_values

The ttmp_dbs_values table is a temporary copy of the [dbs_values](#) table. It is identical to the [dbs_values](#) table except for the following:

- The primary key name is pk_ttmp_dbs_values.
- No foreign keys or indexes are defined.
- In most situations the number of rows in the table should be zero.

Lists

This section describes the tables that are used to store information about iProcess lists.

About Lists

Note that there are three sets of related tables, as follows:

Prefix	Description
list_	Hold the main system data on iProcess lists, which iProcess Engine references during normal operation.
tsys_ list_	Hold a copy of the main system data, containing users' edits that have not yet been released for use by the system.
ttmp_ list_	Temporary tables used only when importing iProcess lists (using <code>SWDIR\bin\swutil IMPORT</code>).

The `tsys_list_` tables are purged and rewritten whenever a user edits iProcess lists data (either by saving changes made in the List Manager utility in the TIBCO iProcess Administrator, modifying data with `SWDIR\bin\swutil IMPORT`, or by using TIBCO iProcess Objects).


The `list_` tables are purged and rewritten with the updated information from the `tsys_list_` tables when a Move System Information is performed - *if* the [flag_table](#) indicates that the Lists data area has been modified

Access to the `list_` and `tsys_list_` tables is controlled by a locking mechanism provided by the [flag_table](#) table.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



list_names

The `list_names` table holds the names and definitions of all iProcess lists defined on the system.

Structure

The `list_names` table has the following structure:

```

TABLE list_names (
  node_id      number(5)          NOT NULL,
  list_id      number(5)          NOT NULL,
  list_name    varchar2(15)      NOT NULL,
  list_type    varchar2(1)       NOT NULL,
  list_length  number(5)          NOT NULL,
  list_decimals number(5)          NOT NULL)
  
```

Column	Description
node_id	ID of the node that this list is stored on, as defined in the nodes table.
list_id	Unique ID for this list.
list_name	Name of this list.
list_type	List type: Either ASCII (A), Numeric (R), Date (D) or Time (T).
list_length	Length of this list, in characters.
list_decimals	Number of characters after the decimal place in this list (relevant only for Numeric lists).

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_list_names	list_id node_id	SMALLINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_list_names ¹	node_id	nodes

Indexes

The following index is defined for this table.

¹This key enforces the DELETE CASCADE referential action.

Index Name	Column(s) Indexed	Tablespace
idx_list_names_fk	node_id	SMALLINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	SMALLTABLESIZE
Percentage Increase	SMALLTABLEPCTINCREASE
Tablespace	SMALLTABLESPACE

Table Activity

The `list_names` table contains one row for each iProcess list on the system.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	<p>a Move System Information is performed, if the flag_table indicates that the Lists data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_list_names table.</p>
updated	never.
deleted	<p>a Move System Information is performed, if the flag_table indicates that the Lists data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_list_names table.</p>

list_values

The `list_values` table holds the value of every item in every iProcess list on the system.

Structure

The `list_values` table has the following structure:

```
TABLE list_values (
  node_id      number(5)          NOT NULL,
  list_id      number(5)          NOT NULL,
  record_id    number(5)          NOT NULL,
  list_value   varchar2(30)      NULL)
```

Column	Description
<code>node_id</code>	ID of the node that this list item is stored on, as defined in the nodes table.
<code>list_id</code>	ID of the list that this list item is stored in, as defined in the list_names table.
<code>record_id</code>	Unique ID for this list item.
<code>list_value</code>	Value of this list item.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
<code>pk_list_values</code>	<code>list_id</code> <code>record_id</code> <code>node_id</code>	MEDIUMINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_list_values ¹	node_id list_id	list_names

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_list_values_fk	list_id node_id	MEDIUMINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `list_values` table contains one row for each iProcess list item defined on the system.

Rows are added, updated and deleted in the following situations.

¹This key enforces the DELETE CASCADE referential action.

A row is...	When...
added	<p>a Move System Information is performed, if the flag_table indicates that the Lists data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_list_values table.</p>
updated	never.
deleted	<p>a Move System Information is performed, if the flag_table indicates that the Lists data area has been modified.</p> <p>Note: The table is purged and rewritten using the values from the tsys_list_values table.</p>

tsys_list_names

The `tsys_list_names` table is a copy of the [list_names](#) table. It is identical to the [list_names](#) table except for the following:

- The primary key name is `pk_tsys_list_names`.
- The foreign key name is `fk_tsys_list_names`.
- The index name is `idx_tsys_list_names_fk`.
- The table is purged and rewritten when a user edits iProcess list data, either by saving changes made in the List Manager utility in the TIBCO iProcess Administrator, modifying data with `SWDIR\bin\swutil IMPORT`, or by using TIBCO iProcess Objects. (The [flag_table](#) is also updated to indicate that the Lists data area has been modified.)

tsys_list_values

The `tsys_list_values` table is a copy of the [list_values](#) table. It is identical to the [list_values](#) table except for the following:

- The primary key name is `pk_tsys_list_values`.

- The foreign key name is `fk_tsys_list_values`.
- The index name is `idx_tsys_list_values_fk`.
- The table is purged and rewritten when a user edits iProcess list data, either by saving changes made in the List Manager utility in the TIBCO iProcess Administrator, modifying data with `SWDIR\bin\swutil IMPORT`, or by using TIBCO iProcess Objects. (The [flag_table](#) is also updated to indicate that the Lists data area has been modified.)

ttmp_list_names

The `ttmp_list_names` table is a temporary copy of the [list_names](#) table. It is identical to the [list_names](#) table except for the following:

- The primary key name is `pk_ttmp_list_names`.
- The foreign key name is `fk_ttmp_list_names`.
- The index name is `idx_ttmp_list_names_fk`.
- In most situations the number of rows in the table should be zero.

ttmp_list_values

The `ttmp_list_values` table is a temporary copy of the [list_values](#) table. It is identical to the [list_values](#) table except for the following:

- The primary key name is `pk_ttmp_list_values`.
- The foreign key name is `fk_ttmp_list_values`.
- The index name is `idx_ttmp_list_values_fk`.
- In most situations the number of rows in the table should be zero.


iProcess Server Plug-ins

This section describes the table that is used to store information about iProcess server plug-ins that are installed on this iProcess Engine.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



eai_registry

The `eai_registry` table stores information about each iProcess server plug-in that is installed on this iProcess Engine. The background process reads this table to determine which iProcess server plug-ins to start.

Structure

The eai_registry table has the following structure:

```
TABLE eai_registry(
  eai_type          varchar2(20)      NOT NULL,
  logical_machine_id number(5)        NOT NULL,
  release_version   varchar2(32)     NOT NULL,
  plugin_library    varchar2(256)    NOT NULL,
  init_params       varchar2(1024) NULL)
```

Column	Description
eai_type	Short name for the EAI Step type that this iProcess server plug-in supports. For example, one of the following: <ul style="list-style-type: none"> EAIDB EAI Database EAISCR EAI Script EAIWEBSERVICES EAI Web Services
logical_machine_id	ID of the computer that this iProcess server plug-in is installed on, as defined in the node_cluster table. <p>Note: If a node cluster architecture is in use, the iProcess server plug-in must be installed on each server in the cluster that is configured to run a background process.</p>
release_version	Version number of this iProcess server plug-in (for example, i10.0-o(3.0)).
plugin_library	Pathname (on this logical_machine_id) where this EAI server plug-in is installed.
init_params	Startup parameters used by this iProcess server plug-in.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_eai_registry	eai_type logical_machine_id	TINYINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_eai_registry ¹	logical_machine_id	node_cluster

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed	Tablespace
idx_eai_registry_fk	logical_machine_id	TINYINDEXSPACE

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

¹This key enforces the DELETE CASCADE referential action.

Table Activity

The `eai_registry` table contains one row for each iProcess server plug-in that is installed on each server in this iProcess Engine node.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	an iProcess server plug-in is installed.
updated	an iProcess server plug-in is upgraded or amended.
deleted	an iProcess server plug-in is deleted.

Firewall Port Ranges

This section describes the tables that store the port range data that is used when iProcess Engine is used in a firewalled environment.

**Note:**


For more information, see:

- the "Using iProcess Engine in a Firewalled Environment" topic in *TIBCO iProcess Engine Architecture Guide*.
- the "Administering Firewall Port Ranges" topic in *TIBCO iProcess Engine Administrator's Guide*.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



port_range

The `port_range` table contains the firewall data about individual port/RPC numbers that lie within port range configurations defined on this iProcess Engine.

Structure

The `port_range` table has the following structure:

```
TABLE port_range (
  port_range_id          number(10)      NOT NULL,
  slot_number            number(10)      NOT NULL,
  rpc_number             number(10)      NOT NULL,
  port_number            number(10)      NOT NULL,
  status                 number(10)      NOT NULL,
  logical_machine_id     number(10)      NULL,
  logical_process_name   varchar2(10)   NULL,
  logical_process_instance number(10)    NULL)
```

Column	Description
<code>port_range_id</code>	Unique ID of the port range configuration that this port/RPC number belongs to, as defined in the port_range_conf table.
<code>slot_number</code>	Internal slot in memory used by this port/RPC number.
<code>rpc_number</code>	RPC number.
<code>port_number</code>	Port number.
<code>status</code>	<p>Defines whether this port/RPC number is available or in use by a process. One of the following values:</p> <ul style="list-style-type: none"> • -2 Reserved for future use. • -1 Unobtainable. (A process tried to use the port but found that it was already in use.) • 0 Unallocated. • 1 Allocated to the process defined by the

Column	Description
	logical_machine_id, logical_process_name and logical_process_instance columns.
logical_machine_id	Either: <ul style="list-style-type: none"> ID of the server where the process instance that this port/RPC number has been allocated to runs, as defined in the node_cluster table. 0, if the port/RPC number has not been allocated to a process.
logical_process_name	Logical name of the process instance that this port/RPC number has been allocated to.
logical_process_instance	Unique ID of the process instance that this port/RPC number has been allocated to.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_port_range	port_range_id, slot_number	TINYINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_port_range	port_range_id	port_range_conf

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The `port_range` table contains one row per port/RPC number used by the iProcess Engine (if you are using iProcess on a network with a firewall and using port range filtering or RPC filtering).

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a user defines a new port range configuration, that is, a new record in the port_range_conf table, or modifies the range of an existing port range configuration, using the <code>SWDIR\util\swadm</code> utility.
updated	a process is assigned a slot, or frees up a slot.
deleted	a user deletes a port range configuration, that is, a record in the port_range_conf table, using the <code>SWDIR\util\swadm</code> utility.

port_range_active

The `port_range_active` table lists what port/RPC numbers are being actively used to provide RPC services by iProcess Engine processes.



Note

The table only lists processes that provide RPC services. These processes are RPC_TCP_LI, RPC_UDP_LI, RPC_POOL, RPC_SWIP, WQS and WIS.

Structure

The `port_range_active` table has the following structure:

```
TABLE port_range_active (
  logical_machine_id      integer      NOT NULL,
  logical_process_name    varchar2(10)  NOT NULL,
  logical_process_instance integer      NOT NULL,
  process_id              integer      NOT NULL,
  port_number              integer      NOT NULL,
  rpc_number              integer      NOT NULL)
```

Column	Description
<code>logical_machine_id</code>	ID of the server where this process instance runs, as defined in the node_cluster table.
<code>logical_process_name</code>	Logical name of this process instance. Note: See "Administering iProcess Engine Server Processes" in <i>TIBCO iProcess Engine Administrator's Guide</i> for a list of logical process names.
<code>logical_process_instance</code>	Unique ID for this process instance.
<code>process_id</code>	Operating system process ID of this process instance.
<code>port_number</code>	Port number being used by this process instance.
<code>rpc_number</code>	RPC number being used by this process instance.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_port_range_active	logical_machine_id, logical_process_name, logical_process_instance	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The port_range_active table contains one row per port/RPC number that is being actively used by the iProcess Engine.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	an iProcess Engine process allocates itself a port/RPC number from either the port_range table or the operating system.
updated	never.
deleted	an iProcess Engine process stops using its assigned port/RPC number, that is, is shut down.

port_range_conf

The `port_range_conf` table defines the available port range configuration(s) for this iProcess Engine, for use with a firewall.



Note

In pre-10.4 iProcess Engine versions this information was defined in the `RNGMODE` parameter of the `$WDIR\etc\staffcfg` file.

Structure

The `port_range_conf` table has the following structure:

```
TABLE port_range_conf (
  port_range_id  integer      NOT NULL,
  range_mode     smallint     NOT NULL,
  range_size     integer      NOT NULL,
  port_start     integer      NOT NULL,
  rpc_start      integer      NOT NULL)
```

Column	Description
<code>port_range_id</code>	Unique ID of this particular port range configuration.
<code>range_mode</code>	Mode used by this port range configuration. One of the following values:

Column	Description
	<ul style="list-style-type: none"> • 0 No Port or RPC ranging. A process uses the next available port number assigned by the operating system, and an RPC number based on the process ID. • 1 Port ranging. A process uses a port number allocated from within the defined range, and an RPC number based on the process ID. • 2 RPC ranging. A process uses the next available port number assigned by the operating system, and an RPC number allocated from within the defined range. • 3 Port and RPC ranging. A process uses both a port number and an RPC number allocated from within the defined ranges.
range_size	The number of port and RPC numbers allowed in the port number and RPC number ranges.
port_start	The first number in the defined range of port numbers. (The last number = port_start + range_size.)
rpc_start	The first number in the defined range of RPC numbers. (The last number = rpc_start + range_size.)

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_port_range_conf	port_range_id	TINYINDEXSPACE

Foreign Keys

None.

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The `port_range_conf` table contains one row per defined port range configuration.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a user defines a new port range configuration using the <code>SWDIR\util\swadm</code> utility.
updated	a user changes an existing port range configuration, that is, either mode, range size or starting port/RPC number is changed, using the <code>SWDIR\util\swadm</code> utility.
deleted	a user deletes an existing port range configuration using the <code>SWDIR\util\swadm</code> utility.

port_range_nodes

The `port_range_nodes` table lists which port range configurations (as defined in the [port_range_conf](#) table) are being used by which machines in the iProcess Engine node (as defined in the [node_cluster](#) table).

**Note**

It is not mandatory for each machine in an iProcess Engine node to have to sit behind the same firewall. Different machines may use different firewalls, or no firewall.

Structure

The port_range_nodes table has the following structure:

```
TABLE port_range_nodes (  
    port_range_id          integer          NOT NULL,  
    logical_machine_id     integer          NOT NULL)
```

Column	Description
port_range_id	ID of a particular port range configuration, as defined in the port_range_conf table.
logical_machine_id	ID of the server using this port range configuration, as defined in the node_cluster table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_port_range_nodes	port_range_id, logical_machine_id	TINYINDEXSPACE

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_port_range_nodes	port_range_id	port_range_conf

Indexes

None.

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	TINYTABLESIZE
Percentage Increase	TINYTABLEPCTINCREASE
Tablespace	TINYTABLESPACE

Table Activity

The `port_range_nodes` table contains one row per server that sits behind a firewall (port range configuration) defined in the [port_range](#) table.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	a user adds a machine to the list of servers that sit behind a particular port range configuration, using the <code>SWDIR\util\swadm</code> utility.
updated	a user moves a machine from sitting behind one particular port range configuration to another, using the <code>SWDIR\util\swadm</code> utility.
deleted	a user removes a machine from the list of servers that sit behind a particular port range configuration, using the <code>SWDIR\util\swadm</code> utility.

WQS/WIS Shared Memory

This section describes the [wqs_index](#) table.

Table Relationships

The [wqs_index](#) table has no database-enforced relationships with other tables.

wqs_index

The `wqs_index` table holds the information about each work queue on the system that is stored in shared memory by the WQS/WIS processes.

Structure

The `wqs_index` table has the following structure:

```
TABLE wqs_index(
    logical_machine_id          number(5)          NOT NULL,
    logical_process_instance    number(5)          NOT NULL,
    queue_name                  varchar(24)        NOT NULL,
    total_items                 number(20)         NULL,
    last_cache_time             number(20)         NULL,
    new_items                   number(20)         NULL,
    deadline_items              number(20)         NULL,
    urgent_items                number(20)         NULL,
    redir_queue_name            varchar(24)        NULL,
    is_cached                   number(1)          NOT NULL,
    is_group                    number(1)          NOT NULL,
    is_test                     number(1)          NOT NULL,
    is_redirected               number(1)          NOT NULL,
    is_disabled                 number(1)          NOT NULL)
```

Column Name	Description
logical_machine_id	ID of the server where the WIS process that is handling this work queue is running, as defined in the node_cluster table.
logical_process_instance	ID of the instance of the WIS process that is handling this work queue, as defined in the process_config table.
queue_name	Name of the work queue.
total_items	<p>Total number of items in this work queue.</p> <p>Note: When the iProcess Engine starts up the WIS processes use this value to determine whether or not each work queue should be cached. See "Configuring When WIS Processes Cache Their Queues" in <i>TIBCO iProcess Engine Administrator's Guide</i> for more information.</p>
last_cache_time	<p>Either:</p> <ul style="list-style-type: none"> Time taken to cache the work queue (in milliseconds) when it was last cached, either when the WIS process first started up or when the work queue was first accessed. -1, if the work queue has not yet been cached.
new_items	Number of new, unopened items in this work queue.
deadline_items	Number of items in this work queue that have deadlines.
urgent_items	Number of items in this work queue that have an urgent priority.
redir_queue_name	<p>Indicates the following status if a work queue is being redirected:</p> <ul style="list-style-type: none"> the name of the work queue that this queue is currently being redirected to, if the queue is currently being redirected (<code>is_redirected = 1</code>). empty, if the queue is currently not being redirected (<code>is_redirected = 0</code>).

Column Name	Description
is_cached	Indicates whether the queue is currently cached by the WIS process and displays the following values: <ul style="list-style-type: none"> • 1, if the queue is cached. • 0, if the queue is not cached.
is_group	Indicates whether the queue is a Group queue and displays the following values: <ul style="list-style-type: none"> • 1, if the queue is a Group queue. • 0, if the queue is a User queue.
is_test	Indicates whether the queue is a Test queue and displays the following values : <ul style="list-style-type: none"> • 1, if the queue is a Test queue. • 0, otherwise.
is_redirected	Indicates whether the queue is currently being redirected to <code>redir_queue_name</code> and displays the following values: <ul style="list-style-type: none"> • 1, if the queue is currently redirected. • 0, otherwise.
is_disabled	Indicates whether the queue is disabled and displays the following values : <ul style="list-style-type: none"> • 1, if the queue is currently disabled. • 0, otherwise.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)	Index Tablespace
pk_wqs_index	queue_name is_test	MEDIUMINDEXSPACE

Foreign Keys

None

Indexes

None

Storage

The following STORAGE values are defined for this table.

Value	Definition
Initial	MEDIUMTABLESIZE
Percentage Increase	MEDIUMTABLEPCTINCREASE
Tablespace	MEDIUMTABLESPACE

Table Activity

The `wqs_index` table contains one row for each work queue on the system that is handled by a WIS process.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	A new work queue is allocated to a WIS process by the WQS process.
updated	<ul style="list-style-type: none"> An existing work queue is re-allocated to a different WIS process by the WQS process. A <code>MOVESYSINFO</code> has been processed by the WQS process. The update thread in the WQS process writes the contents of the WQS/WIS shared memory to the database. This update occurs every <code>WQS_PERSIST_SHMEM</code> seconds.

A row is...	When...
	See "Administering Process Attributes" in <i>TIBCO iProcess Engine Administrator's Guide</i> for more information about the WQS_PERSIST_SHMEM process attribute.
deleted	A WIS is started as the first time the WIS persists the current shared memory to the database it clears out all existing rows and then writes the shared memory to the database table.


System Event Logging

This section describes the tables that are used to store information about system event logging.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



system_event

The `system_event` table contains information about system events.

Structure

The `system_event` table has the following structure:

TABLE system_event			
type_id	number(5)	NOT NULL,	
user_name	varchar(255)	NOT NULL,	
audit_date	date	NOT NULL,	
audit_usecs	number(6)	NOT NULL,	
details	varchar(512)	NOT NULL,	

Column	Description
type_id	IID of an audit event. It is defined in the <code>SWDIR\etc\language.lng\sysevents.cfg</code> file.
user_name	Name of the user who performed the audit event, as defined in the <code>user_names</code> table.
audit_date	Date and time when the event occurred. Note: The <code>audit_usecs</code> column can be combined with this column to provide resolution to a microsecond.
audit_usecs	Number of microseconds since the start of the seconds value specified in the <code>audit_date</code> column.
details	Extra details of the event.

Primary Key

None.

Foreign Keys

None.

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_sys_event_fk	type_id user_name audit_date

Table Activity

The `system_event` table contains one row for each system event that is audited.

Rows are added and deleted in the following situations:

A row is...	When...
added	a new system event is audited.
deleted	using the <code>swadm delete_system_event</code> command to delete system event information or clean system event information that is earlier than a specified period. See <i>TIBCO iProcess Engine Administrator's Guide</i> for more information about the <code>swadm delete_system_event</code> command.

system_event_conf

The `system_event_conf` table holds the configuration information of system events. The information specifies which system event will be audited and published.

Structure

The `system_event_conf` table has the following structure:

TABLE system_event_conf

type_id	number(5)	NOT NULL,
audited	number(5)	NOT NULL,
published	number(5)	NOT NULL,
event_desc	varchar(256)	NOT NULL,

Column	Description
type_id	IID of an audit event. It is defined in the SWDIR\etc\language.lng\sysevents.cfg file.
audited	Whether to audit the system event.
published	Whether to publish the system event.
event_desc	Description of the system event.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)
pk_event_conf	type_id

Foreign Keys

None.

Indexes

None.

Table Activity

The `system_event_conf` table contains one row for the configuration of each system event.

Rows are added and deleted in the following situations:

A row is...	When...
added	a new system event configuration is imported to iProcess Engine by using the IMPEVENTCONF command. See <i>TIBCO iProcess swutil and swbatch Reference Guide</i> for more information about the IMPEVENTCONF command.
updated	a system event is updated in the configuration file imported by the IMPEVENTCONF command.
deleted	a system event is deleted from the configuration file imported by the IMPEVENTCONF command.


Monitoring

This section describes the database METRICS tables that are used to store information required to monitor system or iProcess Engine performance.

Table Relationships

The following diagram shows how the tables described in this section are related to each other and to other tables in the schema. Note that:

- Only database-enforced relationships, that is, foreign keys, are shown.
- Logical relationships, that is, those used by iProcess, are not shown.



stat_gen_mins

The stat_gen_mins table contains general metrics information on work item server, queues, logins and machine at the minute resolution level.

Structure

The stat_gen_mins table has the following structure:

TABLE stat_gen_mins(
seq_id	INT	,	
cap_date	DATE	,	
active_login_count	INT	,	
wis_most_que	INT	,	
wis_most_que_items	INT	,	
most_que_sum	INT	,	
wis_most_item	INT	,	
wis_item_sum	INT	,	
wis_mi_que_sum	INT	,	
wis_lg_queue	INT	,	
lg_queueename	VARCHAR2(32)	,	
lg_queuesize	INT)	

Column	Description
seq_id	Generated sequence number to maintain uniqueness. This is also the primary key.
cap_date	Date and time when these details were captured/recorded.

Column	Description
active_login_count	Number of logins active for that minute.
wis_most_que	WIS that is processing the most number of Queues.
wis_most_que_items	Work Items count on WIS that is processing most number of Queues.
most_que_sum	Work Items count on WIS that is processing most number of Work Items.
wis_most_item	WIS that is processing most number of Work Items.
wis_item_sum	Work Items count on WIS that is processing most number of Work Items.
wis_lg_queue	WIS that is processing largest Queue
lg_queueename	Name of largest Queue
lg_queuesize	Size of largest Queue

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)
pk_stat_mins_seqid	seq_id

Foreign Keys

None

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_gen_m	cap_date

Table Activity

The stat_gen_mins table contains one record for every minute the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every minute.
updated	Never
deleted	After the configured retention period defined by process attribute (value is in days). METRICS_DATA_MINS_KEEP

stat_gen_hours

The stat_gen_hours table contains general metrics information on work item server, cases, users and database at the hour resolution level.

Structure

The stat_gen_hours table has the following structure:

TABLE stat_gen_hours(
seq_id	INT	,

cap_date	DATE	,
max_log_count	INT	,
avg_log_count	INT	,
user_count	INT	,
group_count	INT	,
queue_count	INT	,
wis_most_que	INT	,
wis_most_que_items	INT	,
most_que_sum	INT	,
wis_most_item	INT	,
wis_item_sum	INT	,
wis_mi_que_sum	INT	,
wis_lg_queue	INT	,
lg_queue_name	VARCHAR2(32)	,
lg_queue_size	INT	,
outstanding_item_count	INT	,
Dbtiming	INT	,
event_test	VARCHAR2(128))

Column	Description
seq_id	Generated sequence number to maintain uniqueness. This is also the

Column	Description
	Primary Key.
cap_date	Date and time when these details were captured/recorded.
max_log_count	Maximum active logins for that hour.
avg_log_count	Average number of logins active for that hour.
user_count	Number of users in iProcess.
group_count	Number of groups in iProcess.
queue_count	Number of queues configured in iProcess.
wis_most_que	WIS that is processing most number of Queues.
wis_most_que_items	Work Items count on WIS that is processing most number of Queues.
most_que_sum	Work Items count on WIS that is processing most number of Work Items.
wis_most_item	WIS that is processing most number of Work Items.
wis_item_sum	Work Items count on WIS that is processing most number of Work Items.
wis_mi_que_sum	Queue count on WIS that is processing most number of Work Items.
wis_lg_queue	WIS that is processing the largest Queue
lg_queue_name	Name of largest Queue
lg_queuesize	Size of largest Queue
outstanding_item_count	Number of Work Items pending processing.

Column	Description
Dbtiming	Round trip time to reach or connect to a database.
event_test	Status of event loopback test.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)
pk_stat_hour_seqid	seq_id

Foreign Keys

None

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_gen_h	cap_date

Table Activity

The stat_gen_hours table contains one record for every hour the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every hour.
updated	Never
deleted	After the configured retention period defined by process attributes (value is in days). METRICS_DATA_HOURS_KEEP

stat_gen_daily

The stat_gen_daily table contains general metrics information on procedures, cases, users, queues and machine at the daily resolution level.

Structure

The stat_gen_daily table has the following structure:

TABLE stat_gen_daily(
seq_id	INT	,	
cap_date	DATE	,	
proc_sum	INT	,	
proc_ver_sum	INT	,	
proc_id	INT	,	
proc_name	VARCHAR(32)	,	
proc_most_ver	INT	,	
max_casenum	NUMBER(20)	,	

max_reqid	NUMBER(20)	,
case_information_size	NUMBER(20)	,
case_data_size	NUMBER(20)	,
audit_trail_size	NUMBER(20)	,
user_sum	INT	,
group_sum	INT	,
queues_sum	INT	,
max_log_count	INT	,
avg_log_count	INT	,
max_outstanding_count	INT	,
min_outstanding_count	INT	,
avg_outstanding_count	INT	,
max_dbtming	INT	,
min_dbtming	INT	,
avg_dbtming	INT	,
ci_stats_update	DATE	,
at_stats_update	DATE	,
cd_stats_update	DATE)

Column	Description
seq_id	Generated sequence number to maintain uniqueness. This is also the

Column	Description
	Primary Key.
cap_date	Date and time when these details were captured/recorded.
proc_sum	Total number of procedures.
proc_ver_sum	Total number of versions of all procedures.
proc_id	Id of the procedure with most versions.
proc_name	Name of the procedure with most versions.
proc_most_ver	Number of versions on that procedure with most versions.
max_casenum	Max CASENUM in the system.
max_reqid	Maximum REQID in the system.
case_information_size	Number of rows in Case Information database table
case_data_size	Number of rows in Case Data database table.
audit_trail_size	Number of rows in Audit Trail database table.
user_sum	Number of Users in the system at the start of the day.
group_sum	Number of Groups in the system at the start of the day.
queues_sum	Number of Queues in the system at the start of the day.
max_log_count	Maximum active logins in the last 24 hours.
avg_log_count	Average active logins in the last 24 hours.
max_outstanding_count	Maximum of <i>Outstanding_Addr</i> count in the last 24 hours.

Column	Description
min_outstanding_count	Minimum of <i>Outstanding_Addr</i> count in the last 24 hours.
avg_outstanding_count	Average of <i>Outstanding_Addr</i> count in the last 24 hours.
max_dbtming	Maximum database connection time in the last 24 hours.
min_dbtming	Minimum database connection time in the last 24 hours.
avg_dbtming	Average database connection time in the last 24 hours.
ci_stats_update	Last status update on Case Information table.
at_stats_update	Last status update on Audit Trail table.
cd_stats_update	Last status update on Case Data table.

Primary Key

The following primary key is defined for this table.

Key Name	Column(s)
pk_stat_day_seqid	seq_id

Foreign Keys

None

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_gen_d	cap_date

Table Activity

The stat_gen_daily table contains one record for every minute the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every day.
updated	Never
deleted	After the configured retention period defined by process attributes (value is in days). METRICS_DATA_DAILY_KEEP

stat_mq_mins

The stat_mq_mins table contains general metrics information on total messages in each message queue at the minute resolution level.

Structure

The stat_mq_mins table has the following structure:

TABLE stat_mq_mins(
seq_id	INT	,
cap_date	DATE	,
queue_id	INT	,
queue_name	VARCHAR2 (32)	,
msg_count	INT)

Column	Description
seq_id	Generated sequence number.
cap_date	Date and time when these details were captured/ recorded.
queue_id	Id of the Message Queue.
queue_name	Name of the Message Queue.
msg_count	Number of Messages in the Queue.

Primary Key

None

Foreign Keys

None

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_mq_m	cap_date

Table Activity

The stat_mq_mins table contains one record for every minute the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every minute, one for every Message Queue.
updated	Never
deleted	After the configured retention period defined by process attribute (value is in days). METRICS_DATA_MINS_KEEP

stat_mq_hours

The stat_mq_hours table contains general metrics information on minimum/maximum and average messages in each message queue along with the number of expired messages at the hour resolution level.

Structure

The stat_mq_hours table has the following structure:

TABLE stat_mq_hours(
seq_id	INT	,
cap_date	DATE	,
queue_id	INT	,
queue_name	VARCHAR2(32)	,
max_count	INT	,
min_count	INT	,
avg_count	INT	,
exp_msg_count	INT)

Column	Description
seq_id	Generated sequence number.
cap_date	Date and time when these details were captured/ recorded.
queue_id	ID of the Message Queue.
queue_name	Name of the Message Queue.
max_count	Maximum of the messages count in last hour.
min_count	Minimum of the messages count in last hour.
avg_count	Average of the messages count in last hour.
exp_msg_count	Number of Dead messages in this Message Queue.

Primary Key

None

Foreign Keys

None

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_mq_h	cap_date

Table Activity

The stat_mq_hours table contains one record for every hour the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every hour, one per each Message Queue.
updated	Never
deleted	After the configured retention period defined by process attribute (value is in hours). METRICS_DATA_HOURS_KEEP

stat_mq_daily

The stat_mq_daily table contains general metrics information on min/max and average messages in each message queue and the number of expired messages at the day resolution level.

Structure

The stat_mq_daily table has the following structure:

TABLE stat_mq_daily(
seq_id	INT	,	
cap_date	DATE	,	
queue_id	INT	,	
queue_name	VARCHAR2 (32)	,	
max_count	INT	,	
min_count	INT	,	

avg_count	INT	,
exp_msg_count	INT)

Column	Description
seq_id	Generated sequence number.
cap_date	Date and time when these details were captured or recorded.
queue_id	Id of the Message Queue
queue_name	Name of the Message Queue
max_count	Maximum of the messages count in 24 hours.
min_count	Minimum of the messages count in 24 hours.
avg_count	Average of the messages count in 24 hours.
exp_msg_count	Number of Dead messages in this Message Queue.

Primary Key

None

Foreign Keys

None

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_mq_d	cap_date

Table Activity

The stat_mq_daily table contains one record for every minute the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every day, one for each Message Queue.
updated	Never
deleted	After the configured retention period defined by process attribute (value is in days). METRICS_DATA_DAILY_KEEP

stat_rp_mins

The stat_rp_mins table contains general metrics information on running processes on Process ID, CPU and memory usage, total threads and process start command at the minute resolution level.

Structure

The stat_rp_mins table has the following structure:

TABLE stat_rp_mins(
seq_id	INT		,
cap_date	DATE		,
machine_id	INT		,
instance_id	INT		,

process_name	VARCHAR2 (32)	,
pid	INT	,
cputime	VARCHAR2 (32)	,
cpu	INT	,
memory	INT	,
threads	INT	,
starttime	DATE	,
command	VARCHAR (512))

Column	Description
seq_id	Generated sequence number
cap_date	Date and time when these details were captured/ recorded
machine_id	Machine ID
instance_id	Instance Number of the Process
process_name	Name of the Process
pid	System generated Process ID
cputime	Calculated average CPU usage between two (data collection) intervals.
cpu	CPU Percentage
memory	Memory Usage
threads	Number of threads

Column	Description
starttime	Start time of the process
command	Process start command

Primary Key

None

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_stat_pmin_mid	machine_id	node_cluster

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_rp_m	cap_date

Table Activity

The stat_rp_mins table contains one record for every minute the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every minute, one per each Running Process.
updated	Never
deleted	After the configured retention period defined by process attribute (value is in days). METRICS_DATA_MINUTES_KEEP

stat_rp_hours

The stat_rp_hours table contains general metrics information on running processes on min/max and average for CPU and memory usage, total threads and process start command at the hour resolution level.

Structure

The stat_rp_hours table has the following structure:

TABLE stat_rp_hours(
seq_id	INT		,
cap_date	DATE		,
machine_id	INT		,
instance_id	INT		,
process_name	VARCHAR2(32)		,
max_cpu	INT		,
max_mem	INT		,

max_threads	INT	,
avg_cpu	INT	,
avg_mem	INT	,
avg_threads	INT	,
min_cpu	INT	,
min_mem	INT	,
min_threads	INT)

Column	Description
seq_id	Generated sequence number
cap_date	Date and time when these details were captured/recorded
machine_id	Machine ID
instance_id	Instance Number of the Process
process_name	Name of the Process
max_cpu	Maximum CPU usage in the last hour
max_mem	Maximum memory usage in the last hour
max_threads	Maximum threads count in the last hour
avg_cpu	Average CPU usage in the last hour
avg_mem	Average memory usage in the last hour
avg_threads	Average threads count in the last hour

Column	Description
min_cpu	Minimum CPU usage in the last hour
min_mem	Minimum memory usage in the last hour
min_threads	Minimum threads count in the last hour

Primary Key

None

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_stat_phour_mid	machine_id	node_cluster

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_rp_h	cap_date

Table Activity

The stat_rp_hours table contains one record for every hour the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every hour, one per each Running Process.
updated	Never
deleted	After the configured retention period defined by process attribute (value is in days). METRICS_DATA_HOURS_KEEP

stat_rp_daily

The stat_rp_daily table contains general metrics information on running processes on min/max and average for CPU and memory usage, total threads and process start command at the daily resolution level.

Structure

The stat_rp_daily table has the following structure:

TABLE stat_rp_daily(
seq_id	INT	,
cap_date	DATE	,
machine_id	INT	,
instance_id	INT	,
process_name	VARCHAR2(32)	,
max_cpu	INT	,
max_mem	INT	,

	max_threads	INT	,
	avg_cpu	INT	,
	avg_mem	INT	,
	avg_threads	INT	,
	min_cpu	INT	,
	min_mem	INT	,
	min_threads	INT)

Column	Description
seq_id	Generated sequence number
cap_date	Date and time when these details were captured/recorded
machine_id	Machine ID
instance_id	Instance Number of the Process
process_name	Name of the Process
max_cpu	Maximum CPU usage in the last 24 hours
max_mem	Maximum memory usage in the last 24 hours
max_threads	Maximum threads count in the last 24 hours
avg_cpu	Average CPU usage in the last 24 hours
avg_mem	Average memory usage in the last 24 hours
avg_threads	Average threads count in the last 24 hours

Column	Description
min_cpu	Minimum CPU usage in the last 24 hours
min_mem	Minimum memory usage in the last 24 hours
min_threads	Minimum threads count in the last 24 hours

Primary Key

None

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_stat_pday_mid	machine_id	node_cluster

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_rp_d	cap_date

Table Activity

The stat_rp_daily table contains one record for every minute the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every day, one per each Running Process
updated	Never
deleted	After the configured retention period defined by process attribute (value is in days). METRICS_DATA_DAILY_KEEP

stat_vers_daily

The stat_vers_daily table contains daily metrics information on iProcess and Object Server version details.

Structure

The stat_vers_daily table has the following structure:

TABLE stat_vers_daily(
seq_id	INT	,	
cap_date	DATE	,	
machine_id	INT	,	
machine_name	VARCHAR2(256)	,	
iPE_ver	VARCHAR2(32)	,	
SPO_ver	VARCHAR2(64)	,	
operating_sys_ver	VARCHAR2(256))	

Column	Description
seq_id	Generated sequence number
cap_date	Date and time when these details were captured/ recorded.
machine_id	Machine ID
machine_name	Name of the Machine
iPE_ver	iProcess Engine version
SPO_ver	iProcess Objects Server version
operating_sys_ver	OS version details

Primary Key

None

Foreign Keys

The following foreign key is defined for this table.

Key Name	Column(s)	Referenced in Table...
fk_stat_ver_mid	machine_id	node_cluster

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_vers_d	cap_date

Table Activity

The stat_vers_daily table contains one record for every minute the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every day
updated	Never
deleted	After the configured retention period defined by process attribute (value is in days). METRICS_DATA_DAILY_KEEP

stat_proc_daily

The stat_proc_daily table contains daily metrics information on procedures and total live and closed cases.

Structure

The stat_proc_daily table has the following structure:

TABLE stat_proc_daily(
seq_id	INT	,	
cap_date	DATE	,	
proc_name	VARCHAR2(32)	,	
flags	VARCHAR2(32)	,	

maj_ver	INT	,
min_ver	INT	,
start_step	VARCHAR2(32)	,
directory	VARCHAR2(32)	,
max_casenum	number(20)	,
total_cases	INT	,
dead_cases	INT)

Column	Description
seq_id	Generated sequence number.
cap_date	Date and time when these details were captured/recorded.
proc_name	Name of the Procedure
flags	Flags to represent status
maj_ver	Major number in the Procedure version
min_ver	Minor number in the Procedure version
start_step	First step of the Procedure
directory	Procedure directory name
max_casenum	Largest case number of the case created associated to this Procedure
total_cases	Total Number of cases on this Procedure
dead_cases	Number of dead cases on this Procedure

Primary Key

None

Foreign Keys

None

Indexes

The following index is defined for this table.

Index Name	Column(s) Indexed
idx_stat_proc_d	cap_date

Table Activity

The stat_proc_daily table contains one record for every hour the server is running and recording data.

Rows are added, updated and deleted in the following situations.

A row is...	When...
added	Rows are added every day
updated	Never
deleted	After the configured retention period defined by process attribute (value is in days). METRICS_DATA_DAILY_KEEP

Views

The following database views are defined for internal use:

- `dbs_nm_fld`
- `tsys_dbs_nm_fld`
- `ttmp_dbs_nm_fld`
- `str_dbs_nm_fld`
- `lst_nm_val`
- `tsys_lst_nm_val`
- `ttmp_lst_nm_val`

**Note**

For more information about these views please see the database creation script (`init2Kora.sql` on UNIX, and `init2Kora_tok.sql` on Windows).

STORAGE Configuration Macro Values

i Note: STORAGE values are only defined if the database is *created* when installing a Version i10.0-o(2.0) or later iProcess Engine. They are not defined if the database is created for an earlier version and subsequently upgraded to Version i10.0-o(2.0) or later.

This appendix describes the real values that are assigned to the STORAGE configuration macros defined for each table in the iProcess database schema.

The real values are defined in the following tablesizes files:

- *Default* values are defined in the tablesizes file. Using this file creates a small database (approximately 50Mb) that is suitable for benchmarking or development purposes
- *Medium* values are defined in the tablesizes `tablesizes.med` file. Using this file creates a medium database.
- *Large* values are defined in the tablesizes `tablesizes.large` file. Using this file creates a large database.

When you install the iProcess Engine, you choose which one of these tablesizes files to use. The installer (`swinstall`) replaces the configuration macros with the appropriate values in the `init2Kora.sql` script, which is used to create the iProcess database schema.

For more detailed information about this process, and how you can customize it to your particular requirements, see "Configure the Initial Size and Layout of the iProcess Schema" in *TIBCO iProcess Engine Installation Guide*.

The tables in the following sections define the real values that are assigned to each STORAGE configuration macro, according to:

- the *SIZE* value assigned to the specific table, as defined earlier in this guide.
- the tablesizes file used during installation.

TABLESIZE

The *SIZETABLESIZE* macros define the initial size (in extents) of iProcess schema tables.

Macro	Default	Medium	Large
TINYTABLESIZE	1K	1K	1K
SMALLTABLESIZE	2K	10K	20K
MEDIUMTABLESIZE	40K	90K	90K
BIGTABLESIZE	200K	1200K	4000K
LARGETABLESIZE	500K	15000K	150000K
HUGETABLESIZE	500K	50000K	1100000K
MASSIVETABLESIZE	1M	600000K	1500000K

TABLEPCTINCREASE

The *SIZEPCTINCREASE* macros define the percentage increase to be applied when growing iProcess schema tables.

Macro	Default	Medium	Large
TINYTABLEPCTINCREASE	0	0	0
SMALLTABLEPCTINCREASE	20	20	20
MEDIUMTABLEPCTINCREASE	50	50	50
BIGTABLEPCTINCREASE	50	50	50
LARGETABLEPCTINCREASE	50	100	50

Macro	Default	Medium	Large
HUGETABLEPCTINCREASE	50	100	50
MASSIVETABLEPCTINCREASE	50	100	50

INDEXSIZE

This macro is not currently used. It is reserved for possible future use.

TABLESPACE

The *SIZE*TABLESPACE macros define the tablespaces used by iProcess schema tables.

Macro	Default	Medium	Large
TINYTABLESPACE	staffwar	staffwar	staffwar
SMALLTABLESPACE	staffwar	staffwar	staffwar
MEDIUMTABLESPACE	staffwar	staffwar	staffwar
BIGTABLESPACE	staffwar	staffwar	staffwar
LARGETABLESPACE	staffwar	staffwar	staffwar
HUGETABLESPACE	staffwar	staffwar	staffwar
MASSIVETABLESPACE	staffwar	staffwar	staffwar

INDEXSPACE

The *SIZE*INDEXSPACE macros define the tablespaces used by iProcess schema primary keys and indexes.

Macro	Default	Medium	Large
TINYINDEXSPACE	staffwar	staffwar	staffwar
SMALLINDEXSPACE	staffwar	staffwar	staffwar
MEDIUMINDEXSPACE	staffwar	staffwar	staffwar
BIGINDEXSPACE	staffwar	staffwar	staffwar
LARGEINDEXSPACE	staffwar	staffwar	staffwar
HUGEINDEXSPACE	staffwar	staffwar	staffwar
MASSIVEINDEXSPACE	staffwar	staffwar	staffwar

AQTABLESPACE

The AQTABLESPACE macro defines the tablespace used by the AQ tables that provide the underlying message queuing system used by the iProcess message queues. See [Oracle AQ Queue Tables and Queues](#) for more information.

Macro	Default	Medium	Large
AQTABLESPACE	staffwar	staffwar	staffwar

SSOLite Stored Procedures

This appendix describes the SSOLite stored procedures package.

Overview

The SSOLite package is a set of stored procedures, available in the iProcess database, that provide applications with direct access to a limited subset of iProcess functionality.

An application can use SSOLite stored procedures to issue instructions directly to the iProcess background processes (by inserting messages into the iProcess message queues) to perform the following iProcess operations:

- start a case.
- trigger an event.
- graft a sub-procedure to a procedure (at run-time).
- jump a case to a different point in the procedure.
- suspend a case.
- re-activate a suspended case.

There are four different categories of SSOLite procedure:

- [Data Procedures](#) are used to create (or clear) any pack data that is required for a particular operation.
- [Command Procedures](#) are used to perform the iProcess operations described above.
- [Control Procedures](#) can be used to control the operation of the other SSOLite procedures. Their use is optional.
- [Debug Procedures](#) can be used to provide debug information about the operation of data and command procedures, if required.

Using SSOLite Stored Procedures

The following sections discuss some general issues that you need to be aware of when designing an application to use SSOLite stored procedures:

- [Processing Asynchronous Message](#)
- [Transactional Processing](#)
- [Handling Exceptions](#)
- [Processing Queues](#)
- [Prioritizing Messages](#)

Processing Asynchronous Message

SSOLite stored procedures work by sending a message to a database queue, which is processed by one or more background (BG) processes. This means that:

- there is a short delay between an SSOLite stored procedure completing and the BG process processing the instruction.
- even if an SSOLite procedure has completed successfully, the instruction that is processed by the BG may still fail.

Transactional Processing

The BG process does not process any instructions issued by SSOLite stored procedures until the SSOLite transaction has been committed. You can therefore scope transactions according to the requirements of your particular application:

- A transaction can be defined as a single instruction, such as a case start. (If the call to [SW_CASESTART](#) succeeds then a commit is immediately performed.)
- Several instructions can be processed as part of a single transaction. For example, a transaction can add pack data, issue an event, add more pack data and then start several cases, and is only committed if all these operations complete successfully.

Handling Exceptions

SSOLite stored procedures raise an Oracle error in the range -20000 to -20020 if any procedure fails. Note that:

- The error text is always preceded by the string (SWERROR).
- Each error has a unique ID, which is displayed at the end of the error text.

It is the application's responsibility to handle any such database exceptions, and issue a rollback if appropriate.

The following table describes the different errors (and their unique IDs) that may be returned by the SSOLite stored procedures.

Note: Some of the stored procedures listed in the table are not described in this section. These are lower level stored procedures that may be called by some or all of the stored procedures that are described in this section.

Stored Procedure	Oracle Error	Error Text
SW_GET_NODE_DETAILS	-20001	Node details not found in database (ID:001007)
SW_SET_QUEUE_NAME	20002	MBox Queue Name(s) not found in database (ID:001008)
SW_GET_PROCEDURE	-20003	Procedure details not found in database for procedure name= <i>proc_name</i> (ID:001010)
	-20000	Procedure version not found in database for procedure name= <i>proc_name</i> , Case Num= <i>case_num</i> (ID:001011)
	-20004	Latest Released or Unreleased Procedure version not found in database for procedure name= <i>proc_name</i> (ID:001012)
	-20005	Procedure version not found in database for procedure name= <i>proc_name</i> <i>major_version</i> <i>minor_version</i>

Stored Procedure	Oracle Error	Error Text
		(ID:001013)
SW_SUSPEND	-20000	Suspend type (<i>suspend_type</i>) is invalid, expected 2 (suspend) or 0 (activate) (ID:001014)
	-20000	Case (<i>case_num</i>) is already active (ID:001036)
	-20000	Case (<i>case_num</i>) is dead (ID:001037)
	-20000	Case (<i>case_num</i>) is already suspended (ID:001038)
SW_GET_SUBPROC_DETAILS	-20000	Sub-Proc casenum not found in database for Procedure <i>proc_name</i> , Case Number <i>case_num</i> , Step Name <i>step_name</i> , Sub-proc <i>sub_proc_name</i> (ID:001018)
SW_GETCASE_STATUS_EX	-20006	Failed to find case information for case: <i>case_num</i> (ID:001019)
SW_UNPACKDELAYRELEASEID	-20000	Unexpected inconsistency between node name <i>nodename</i> and delayed release id procedure node name <i>nodename</i> (ID:001020)
	-20000	Unexpected inconsistency between node name <i>nodename</i> and delayed release id queue node name <i>nodename</i> (ID:001021)
SW_DELAYED_RELEASE_ERR	-20000	Failed to get node ID (ID:001022)
SW_PURGE	-20006	Case (<i>case_num</i>) is dead (ID:001037)
	-20006	Procedure and case information does not match (ID:001041)
SW_CLOSE	-20006	Case (<i>case_num</i>) is dead (ID:001037)

Stored Procedure	Oracle Error	Error Text
	-20006	Procedure and case information does not match (ID:001042)

Processing Queues

SSOLite stored procedures write messages to the BG processes using the default background message queues, using a round-robin allocation on a per-session basis. This means that every time a new database session is started the first defined queue (BGMB0X1) is used first. As a result, BGMB0X1 can become overloaded if database sessions are not persisted.

You can override this default behavior for specific transactions by using the [SW_SET_QUEUE](#) and [SW_UNSET_QUEUE](#) control procedures.

Alternatively, you can dedicate specific message queues to handling requests from your SSOLite stored procedure calls. To do this:

1. Create a new Mbox set named SSOLITE. (The Mbox set can use either existing message queues or new ones.)
2. Set the MBSET_WRITE_BG process attribute for your application to assign the SSOLITE1 queue to it. All messages posted to a BG process by the SSOLite stored procedures will now use the SSOLITE Mbox set.

The following example shows a series of commands that you could use to do this.

```
# Add a new SSOLITEQ1 message queue. (Remember to create the
# table ssolitemboxtable and the ssolitemboxqueue AQ first.)
#
swadm add_queue SSOLITEQ1 Local 0001::ssolitemboxtable:ssolitemboxqueue
# Add a new SSOLITE Mbox set.
#
swadm add_mboxset SSOLITE Local

# Add the SSOLITEQ1 message queue to the SSOLITE Mbox set (6 is the
# Mboxset ID of the SSOLITE Mbox set).
#
swadm add_queue_to_mboxset 6 7
# Set MBSET_WRITE_BG so that calls from the application's SSOLITE
#stored procedures use the SSOLITE Mbox set to write messages to the
```

```
#BG processes.
#
swadm set_attribute1 SSOLITE 0 MBSET_WRITE_BG 6
#
#Set background processes to read from the queue
#
swadm add_process 1 BG Y
swadm set_attribute 1 BG 5 MBSET_READ_BG 6
```

**Note**

The SSOLite stored procedures cache queue information. Therefore, you *must* shut down and restart all database connections if you change your message queue configuration in this way.

For more information about message queue configuration, see:

- [Mbox Sets and Message Queues](#).
- "Administering Message Queues and Mbox Sets" in *TIBCO iProcess Engine Administrator's Guide*.

Prioritizing Messages

You can now set priorities ranging from 1 to 999 (where 1 is the highest priority) for internal message queues when passing messages between iProcess processes such as from the background and the WISes, or from SSOLite to the BG processes. The default message queue priority is 50.

Use the [SW_SET_PRIORITY](#) control procedure to set the internal message queue priorities and the [SW_UNSET_PRIORITY](#) control procedure to restore the default message queue priorities.

The messages with higher internal message queue priorities are processed earlier than those with lower priorities, and the message with the highest priority is automatically the next message processed, even if there is a backlog in the queue.

If the internal message queue priorities are not set, the messages will be processed in the order of SW_CP_VALUE or SW_IP_VALUE when using iProcess Workspace (Windows) to process work items.

**Note**

When using SSOLite stored procedures to start a case or to trigger an event, the following rules determine which message queue priority settings should be used for processing messages:

- If the value of the SW_CP_VALUE field is set, the message will be processed in the order of SW_CP_VALUE regardless of the message queue priority that is set by using the SW_SET_PRIORITY control procedure.
- If the SW_CP_VALUE field is not set, the message will be processed in the order of the message queue priority that is set using the SW_SET_PRIORITY control procedure.
- If both the SW_CP_VALUE field and the SW_SET_PRIORITY control procedure are not set for the message priority, the message priority will be set to the default value of the SW_CP_VALUE field, 50.

See *TIBCO iProcess Modeler Advanced Design* for more information about the SW_CP_VALUE field.

Data Procedures

The following data procedures are available:

- [SW_ADD_PACK_DATA](#)
- [SW_ADD_PACK_MEMO](#)
- [SW_CLEAR_PACK_CACHE](#)
- [SW_MODIFY_CASEDATA](#)

SW_ADD_PACK_DATA

The SW_ADD_PACK_DATA procedure defines an item of pack data (a field name/value pair) that will be passed to iProcess with the next command procedure that is called.

Syntax

```
SW_ADD_PACK_DATA (
    field_name          in varchar2(31),
    field_value         in varchar2(255))
```

where:

- `field_name` is a string that specifies the name of the iProcess field that is to be set.
- `field_value` is a string that specifies the value to be set for *field_name*.



Note

Although the value is always passed as a string, it must be in the correct format for the type of field. No validation is performed on either the field name or field value.

Notes

`SW_ADD_PACK_DATA` allows pack data to be passed to iProcess when a command procedure is called:

- You must call `SW_ADD_PACK_DATA` to specify the pack data immediately before calling the desired command procedure.
- A call to `SW_ADD_PACK_DATA` defines a single item of pack data. If you want to define multiple items of pack data, you must make a `SW_ADD_PACK_DATA` call for each piece of data before calling the desired command procedure.
- The pack data is only valid for the next command procedure that is called.

Examples

In the following example, two `SW_ADD_PACK_DATA` calls are used to define data values for the F1 and F2 fields, which are passed to iProcess when Case1 is started (using [SW_CASESTART](#)). The second `SW_CASESTART` call, starting Case2, does not have any data values.

```
begin
SSOLITE_DATA.SW_ADD_PACK_DATA ('F1', 'DataItem1');
SSOLITE_DATA.SW_ADD_PACK_DATA ('F2', 'DataItem2');
```



```

SSOLITE.SW_CASESTART ('CUSTREQ', -1, -1, 'Case1', 'user35', '', casenum,
reqid);
SSOLITE.SW_CASESTART ('CUSTREQ', -1, -1, 'Case2', 'user35', '', casenum,
reqid);
end;
/
commit;

```

If you want to specify pack data for the F1 and F2 fields for Case2 as well, you must call SW_ADD_PACK_DATA again before calling SW_CASESTART, as shown .

```

begin
SSOLITE_DATA.SW_ADD_PACK_DATA ('F1', 'DataItem1');
SSOLITE_DATA.SW_ADD_PACK_DATA ('F2', 'DataItem2');
SSOLITE.SW_CASESTART ('CUSTREQ', -1, -1, 'Case1', 'user35', '', casenum,
reqid);
SSOLITE_DATA.SW_ADD_PACK_DATA ('F1', 'DataItem1');
SSOLITE_DATA.SW_ADD_PACK_DATA ('F2', 'DataItem2');
SSOLITE.SW_CASESTART ('CUSTREQ', -1, -1, 'Case2', 'user35', '', casenum,
reqid);
end;
/
commit;

```

SW_ADD_PACK_MEMO

The SW_ADD_PACK_MEMO procedure defines an item of pack memo data (a field name/value pair) that will be passed to iProcess with the next command procedure that is called.

Syntax

```
SW_ADD_PACK_MEMO (
```

memo_name	in varchar2(31),
-----------	------------------

memo_length	in integer,
-------------	-------------

memo_data	in blob,
-----------	----------

array_idx	in integer default 0)
-----------	-----------------------

where:

- memo_name is the name of the iProcess memo field (or memo array field).
- memo_length is the number of bytes contained in the memo data.
- memo_data is a raw data field that holds the actual memo data.
- array_idx (optional) can be specified if memo_name is a memo array field; it identifies the specific element in the memo array to be used. If array_idx is not explicitly set, it defaults to a value of 0.

If memo_name is not a memo array field, you should either not set *array_idx*, or set it to 0. (If array_idx contains any other value, no memo data will be found; an error message will be written to the *SWDIR\logs\sw_warn* file.)

Notes

SW_ADD_PACK_MEMO allows pack memo data to be passed to iProcess when a command procedure is called:

- You must call SW_ADD_PACK_MEMO to specify the pack memo data immediately before calling the desired command procedure.
- A call to SW_ADD_PACK_MEMO defines a single item of pack memo data. If you want to define multiple items of pack memo data, you must make a SW_ADD_PACK_MEMO call for each piece of memo data before calling the desired command procedure.
- The pack memo data is only valid for the next command procedure that is called.

SW_CLEAR_PACK_CACHE

The SW_CLEAR_PACK_CACHE procedure clears any items of pack data or pack memo data that have been added using [SW_ADD_PACK_DATA](#) or [SW_ADD_PACK_MEMO](#) calls, prior to calling a command procedure.

Syntax

```
SW_CLEAR_PACK_CACHE ()
```

Notes

Use SW_CLEAR_PACK_CACHE if added data is no longer required.

SW_MODIFY_CASEDATA

By using the SW_MODIFY_CASEDATA procedure, you can modify the data of an existing case. Use an [SW_ADD_PACK_DATA](#) procedure to specify the data to be modified. Then, an immediately following SW_MODIFY_CASEDATA posts an instruction to the BG process to carry out the change. You can use the SW_MODIFY_CASEDATA procedure to set case data for main procedures and sub-procedures.

This event is audited, using audit message 058. See *TIBCO iProcess Engine Administrator's Guide* for details of audit messages.

Syntax

```
SW_MODIFY_CASEDATA (
```

proc_name	in varchar2(8),
proc_maj_ver	in number(5),
proc_min_ver	in number(5),
case_number	in integer,
reason	in varchar(2),
user_id	in varchar2(24))

where:

- `proc_name` is the name of the procedure that you want to modify a case of.
- `proc_maj_ver` is either the major version number of the `proc_name` procedure, or `-1`. See the notes .
- `proc_min_ver` is either the minor version number of the `proc_name` procedure, or `-1`. See the notes .
- `case_number` is the case number of the main procedure for which the data is to be modified.
- `reason` is a reason for the case data modification, used in the audit trail.
- `user_id` is the name of the iProcess user who is performing the modification.

Notes

Instead of using the specific major and/or minor version number of the procedure, you can specify both the `proc_maj_ver` and `proc_min_ver` parameters as `-1`. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).

**Note**

If you specify one version number parameter as `-1`, you must specify the other one as `-1` as well.

Example

This example modifies data for case 876 of the `Transfer` procedure. The `SW_ADD_PACK_DATA` statement changes the value of the `TEXT1` field to "New customer name". The `SW_MODIFY_CASEDATA` call then identifies the procedure and case to be changed, and provides the "Modified For Graft" message which will be displayed in the audit trail.

```
EXEC ssolite_data.SW_ADD_PACK_DATA('TEXT1', 'New customer name');  
EXEC ssolite.SW_MODIFY_CASEDATA('Transfer', -1, -1, 876, 'Modified For  
Graft', 'swadmin');
```

Command Procedures

The following command procedures are available:

- [SW_AUDIT](#)
- [SW_CASEREOPEN](#)
- [SW_CASESTART](#)
- [SW_CLOSE](#)
- [SW_CLOSE_WITHOUT_EVENT](#)
- [SW_DELAYED_RELEASE_ERR](#)
- [SW_EVENT](#)
- [SW_EVENT_UPDATE_PACK](#)
- [SW_GETCASE_STATUS_EX](#)
- [SW_GETCASE_STATUS](#)
- [SW_GRAFT](#)
- [SW_GRAFTCOUNT](#)
- [SW_JUMPTO](#)
- [SW_JUMPTO_MULTI](#)
- [SW_PURGE](#)
- [SW_PURGE_WITHOUT_EVENT](#)
- [SW_SUSPEND](#)
- [SW_ACTIVATE](#)

SW_AUDIT

The `SW_AUDIT` procedure instructs the iProcess Engine background (BG) process to create the specified audit trail message for the specified case.

Syntax

SW_AUDIT (

<i>proc_name</i>	in varchar2(8),
<i>proc_maj_ver</i>	in number(5),
<i>proc_min_ver</i>	in number(5),
<i>case_num</i>	in integer,
<i>Audit_id</i>	in integer,
<i>Audit_step</i>	in varchar2(8),
<i>Audit_desc</i>	in varchar2(24),
<i>User_id</i>	in varchar2(255))

where:

- *proc_name* is the name of the procedure that you want to create an audit message for.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *case_num* (input) is the name of a variable, defined in the calling program, into which SW_AUDIT will return the case number of the started case.
- *Audit_id* is the numeric value of the audit message required. User audit messages will be values greater than 256, as listed in the *SWDIR/etc/english.lng/auditusr.mes* file. See "Understanding Audit Trails" in *TIBCO iProcess Engine Administrator's Guide* for details.
- *Audit_step* is the stepname of this audit. If the step is not required for this audit message, specify this parameter as a null string (") instead.
- *Audit_desc* is the description to be added to the audit message.

- *User_id* is the username that will be added to the audit trail entry.

Notes

Instead of using the specific major and/or minor version number of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).



Note

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

Example

This example creates an audit message 131 for the CARPOOL procedure.

```
EXEC SSOLITE.SW_AUDIT('CARPOOL', -1, -1, 51, 131, 'REFUSED', 'BW
Activity', 'BW User');
```

SW_CASEREOPEN

The SW_CASEREOPEN procedure resurrects a case.

Syntax

```
SW_CASEREOPEN (
  proc_name          in varchar2(8),
  user_id            in varchar2(24),
  step_name          in varchar2(8),
  case_num           in integer)
```

where:

- *proc_name* is the name of the procedure that you want to resurrect.
- *user_id* is the name of the iProcess user who is resurrecting the case.

- *step_name* is the name of the case step that you want to resurrect.
- *case_num* is the number of the case that you want to resurrect.

Notes

After a case is closed, all the deadlines of the case are removed. If the case is reopened, you can reset the deadlines by running the `CreateCaseDeadline` function. For more information about the `CreateCaseDeadline` function, see *TIBCO iProcess Expressions and Functions Reference Guide*.

Example

This example resurrects step STEP1 of case 101 of procedure CUSTREQ.

```
EXEC ssolite.SW_CASEREOPEN ('CUSTREQ', 'user35','STEP1',101);
```

SW_CASESTART

The `SW_CASESTART` procedure starts a case of a procedure.

Syntax

`SW_CASESTART (`

<i>proc_name</i>	<code>in varchar2(8),</code>
------------------	------------------------------

<i>proc_maj_ver</i>	<code>in number(5),</code>
---------------------	----------------------------

<i>proc_min_ver</i>	<code>in number(5),</code>
---------------------	----------------------------

<i>case_desc</i>	<code>in varchar2(24),</code>
------------------	-------------------------------

<i>user_id</i>	<code>in varchar2(24),</code>
----------------	-------------------------------

<i>step_name</i>	<code>in varchar2(8),</code>
------------------	------------------------------

<i>case_num</i>	out integer,
<i>request_id</i>	out integer)

where:

- *proc_name* is the name of the procedure that you want to start a case of.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *case_desc* is a suitable description for this case.
- *user_id* is the name of the iProcess user who is starting the case.
- *step_name* is the name of the step at which the case should start. If you want to use the default start step, specify this parameter as a null string ('').
- *case_num* (output) is the name of a variable, defined in the calling program, into which SW_CASESTART will return the case number of the started case.
- *request_id* (output) is the name of a variable, defined in the calling program, into which SW_CASESTART will return the REQ ID of the work item that is sent out when the case is started.

Notes

Instead of using the specific major and/or minor version number of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will determine which version of the procedure to use according to the following rules:

1. the latest released version of the procedure or, if no released version exists,
2. the latest unreleased version of the procedure.



Note

If you specify one version number parameter as -1, you must also specify the other one as -1 .

Example

This example starts a case of the CUSTREQ procedure. Note that pack data values for the CustName and CustID fields are provided by separate calls to [SW_ADD_PACK_DATA](#) immediately before the SW_CASESTART call.

```
declare
casenum numeric(20);
reqid numeric(20);
begin
SSOLITE_DATA.SW_ADD_PACK_DATA ('CustName', 'Allsop, J.A. ');
SSOLITE_DATA.SW_ADD_PACK_DATA ('CustID', '478163 ');
SSOLITE.SW_CASESTART ('CUSTREQ', -1, -1, 'Refund request', 'user35', '',
casenum, reqid);

end;
/
commit;
```

SW_CLOSE

The SW_CLOSE procedure closes an active case of a procedure.

If an event is set for the OnBeforeClose event, the event is triggered when the case is about to close but before the case is actually closed. If an event is set for the OnAfterClose event, the event is triggered after closing the case.

Syntax

SW_CLOSE (
<i>proc_name</i>	in varchar2(8),
<i>proc_maj_ver</i>	in number(5),
<i>proc_min_ver</i>	in number(5),

<i>case_number</i>	in integer,
<i>user_id</i>	in varchar2(24))

where:

- *proc_name* is the name of the procedure that you want to close a case of.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *case_num* is the number of the case that is to be closed.
- *user_id* is the name of the iProcess user who is closing the case.

Notes

Instead of using the specific major and/or minor version number of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).

i Note: If you specify one version number parameter as -1, you must specify the other one as -1 as well.



Note

Example

This example closes the 103 case of the CUSTREQ procedure without triggering an event.

```
EXEC SSOLITE.SW_CLOSE ('CUSTREQ', -1, -1, 103, 'swadmin')
```

SW_CLOSE_WITHOUT_EVENT

The `SW_CLOSE_WITHOUT_EVENT` procedure closes an active case of a procedure without triggering the events that are set for the `OnBeforeClose` event or the `OnAfterClose` event.

Syntax

```
SW_CLOSE_WITHOUT_EVENT (
```

<i>proc_name</i>	in varchar2(8),
<i>proc_maj_ver</i>	in number(5),
<i>proc_min_ver</i>	in number(5),
<i>case_number</i>	in integer,
<i>user_id</i>	in varchar2(24))

where:

- *proc_name* is the name of the procedure that you want to close a case of.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *case_num* is the number of the case that is to be closed.
- *user_id* is the name of the iProcess user who is closing the case.

Notes

Instead of using the specific major and/or minor version number of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).

**Note**

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

Example

This example closes the 103 case of the CUSTREQ procedure without triggering an event.

```
EXEC SSOLITE.SW_CLOSE ('CUSTREQ', -1, -1, 103, 'swadmin')
```

SW_DELAYED_RELEASE_ERR

The SW_DELAYED_RELEASE_ERR procedure takes a BG action when a delayed release error occurs.

Syntax

```
SW_DELAYED_RELEASE_ERR (
```

<i>delayed_release_id</i>	in varchar2,
---------------------------	--------------

<i>audit_desc</i>	in varchar2,
-------------------	--------------

<i>user_id</i>	in varchar2,
----------------	--------------

<i>err_code</i>	in varchar2,
-----------------	--------------

<i>err_message</i>	in varchar2,
--------------------	--------------

<i>bg_action</i>	in integer)
------------------	-------------

where:

- *delayed_release_id* is the ID of the delayed release.
- *audit_desc* is the description of the delayed release audit.
- *user_id* is the user ID.

- *err_code* is the error code.
- *err_message* is the error message.
- *bg_action* is the BG action to handle the delayed release error.

Notes

If a delayed release error occurs, TIBCO BusinessWorks returns an error code, an error message, and a BG action to TIBCO iProcess Engine. The BG process take the following actions according to BG action:

- Just log the error and do nothing.
- Log the error and requeue the transaction again.
- Log the error and progress the iProcess case, as if it has been released.

See *TIBCO iProcess Connector for ActiveMatrix BusinessWorks User's Guide* for more information about the delayed release error.

SW_EVENT

The SW_EVENT procedure triggers a specific event on the case of a procedure.

Syntax

```
SW_EVENT (  
  
    proc_name           in varchar2(8),  
  
    proc_maj_ver        in number(5),  
  
    proc_min_ver        in number(5),  
  
    step_name           in varchar2(8),  
  
    case_num            in integer,  
  
    user_id             in varchar2(24))
```

where:

- *proc_name* is the name of the procedure that you want to trigger the event on.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *step_name* is the name of the event step that you want to trigger.
- *case_num* is the number of the case that you want to trigger the event on.
- *user_id* is the name of the iProcess user who is triggering the event.

Notes

Instead of using the specific major or minor version number or both of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).



Note

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

For more information about events and how to use them, see *TIBCO iProcess Modeler Integration Techniques*.

Example

This example issues an event, as user *swadmin*, on *STEP1* of case 101 of the *CUSTREQ* procedure.

```
EXEC SSOLITE.SW_EVENT ('CUSTREQ', -1, -1, 'STEP1', 101, 'swadmin');
```

SW_EVENT_UPDATE_PACK

The SW_EVENT_UPDATE_PACK procedure is the same as [SW_DELAYED_RELEASE_ERR](#), but when it triggers a specific event on a case of a procedure it refreshes the data of any work items that are outstanding for that case.

Syntax

SW_EVENT_UPDATE_PACK (

<i>proc_name</i>	in varchar2(8),
<i>proc_maj_ver</i>	in number(5),
<i>proc_min_ver</i>	in number(5),
<i>step_name</i>	in varchar2(8),
<i>case_num</i>	in integer,
<i>user_id</i>	in varchar2(24))

where:

- *proc_name* is the name of the procedure that you want to trigger the event on.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *step_name* is the name of the event step that you want to trigger.
- *case_num* is the number of the case that you want to trigger the event on.
- *user_id* is the name of the iProcess user who is triggering the event.

Notes

Instead of using the specific major or minor version number or both of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).



Note

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

For more information about events and how to use them, see *TIBCO iProcess Modeler Integration Techniques*.

Example

This example issues an event, as user *swadmin*, on step *STEP1* of case 101 of the *CUSTREQ* procedure, and refreshes outstanding work items.

```
EXEC SSOLITE.SW_EVENT_UPDATE_PACK ('CUSTREQ', -1, -1, 'STEP1', 101,
'swadmin')
```

SW_GETCASE_STATUS

The *SW_GETCASE_STATUS* procedure returns the status of a case of a procedure.

Syntax

```
SW_GETCASE_STATUS (
    case_num          in integer,
    case_status       out varchar(10),
```

<i>proc_type</i>	out varchar(10) ,
<i>case_started</i>	out date)

where:

- *case_num* is the number of the case that you want to get the status of.
- *case_status* (output) is the name of a variable, defined in the calling program, into which SW_GETCASE_STATUS will return the status of the specified case.
- *proc_type* (output) is the name of a variable, defined in the calling program, into which SW_GETCASE_STATUS will return the procedure type of the specified case (for example, Main or Sub).
- *case_started* (output) is the name of a variable, defined in the calling program, into which SW_GETCASE_STATUS will return the date that the case was started.

Example

This example displays the status of case 8.

```

Declare
case_status varchar(10);
proc_type varchar(10);
case_started date;
begin
    SSOLITE.SW_GETCASE_STATUS (8, case_status, proc_type, case_started);
    DBMS_OUTPUT.PUT_LINE('Case status is ' || case_status);
    DBMS_OUTPUT.PUT_LINE('Proc type is ' || proc_type);
    DBMS_OUTPUT.PUT_LINE('Case started at ' || case_started);
end;
/

```

This results in output displaying the status of the case. For example:

```

Case status is Active
Proc type is Sub
Case started at 31-MAY-05

```

SW_GETCASE_STATUS_EX

The SW_GETCASE_STATUS_EX procedure retrieves the case status of a procedure.

Syntax

SW_GETCASE_STATUS_EX (

IN	<i>proc_num</i>	integer,
IN	<i>case_num</i>	integer,
OUT	<i>case_status</i>	varchar 2)
OUT	<i>proc_type</i>	varchar 2,
OUT	<i>case_started</i>	date,

where:

- *proc_num* is the procedure id for which the status needs to be retrieved.
- *case_number* is the number of the case for which status needs to be retrieved.
- *case_status* is the return value for case status. It can be one of the three values: Active, Suspended, or Dead.
- *proc_type* defines the process type. The value is either Sub, or Main.
- *case_started* returns the date and time when the case started.



Note

SW_GETCASE_STATUS_EX is similar to SW_GETCASE_STATUS except that it takes an extra parameter *proc_num* as one of the input parameters.



Note

In Process Engine versions prior to 10, case numbers were unique only under a given Procedure, but become duplicate at the Engine level. Since Procedures are always identified by *proc_num*, in such situations, a *proc_num* is mandatory, to uniquely identify a case. SW_GETCASE_STATUS_EX is used in such a situation instead of SW_GETCASE_STATUS as it takes *proc_num* and *case_num* as inputs.

SW_GRAFT

The SW_GRAFT procedure grafts a sub procedure onto a graft step in the main procedure. The case data is added to the sub-procedure.

Syntax

SW_GRAFT (

<i>proc_name</i>	in varchar2(8),
<i>proc_maj_ver</i>	in number(5),
<i>proc_min_ver</i>	in number(5),
<i>case_number</i>	in integer,
<i>graft_step_name</i>	in varchar2(8),
<i>graft_proc_name</i>	in varchar2(8),
<i>graft_proc_maj_ver</i>	in number(5),
<i>graft_proc_min_ver</i>	in number(5),
<i>graft_id</i>	in varchar(2))

where:

- *proc_name* is the name of the parent procedure that you want to graft a sub-procedure to.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *case_number* is the number of the case that you want to graft a sub-procedure to.
- *graft_step_name* is the name of the graft step in the *proc_name* procedure that the sub-procedure is to be grafted to.

- *graft_proc_name* is the name of the sub-procedure that is to be grafted to the *proc_name* parent procedure.
- *graft_proc_maj_ver* is either the major version number of the *graft_proc_name* procedure, or -1. See the notes
- *graft_proc_min_ver* is either the minor version number of the *graft_proc_name* procedure, or -1. See the notes
- *graft_id* is a unique identifier for this instance of the *graft_step_name* graft step.

Notes

Instead of using the specific major and/or minor version number of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).



Note

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

For more information about graft steps and how to use them, see *TIBCO iProcess Modeler Integration Techniques*.

Example

This example uses SW_GRAFT to graft the SUBPROC1 sub-procedure to step GRAFT01 of case 101 of the CUSTREQ procedure. It then uses SW_GRAFTCOUNT to specify that a single item is to be grafted to the UNIQUEID instance of the graft step.

```
EXEC SSOLITE.SW_GRAFT ('CUSTREQ', -1, -1, 101, 'GRAFT01', 'SUBPROC1', -
1, -1, 'UNIQUEID')
EXEC SSOLITE.SW_GRAFTCOUNT ('CUSTREQ', -1, -1, 101, 'GRAFT01',
'UNIQUEID', 1)
/
commit;
```

SW_GRAFTCOUNT

The SW_GRAFTCOUNT procedure specifies how many items are to be grafted to the specified instance of the graft step.

Syntax

SW_GRAFTCOUNT (

<i>proc_name</i>	in varchar2(8),
------------------	-----------------

<i>proc_maj_ver</i>	in number(5),
---------------------	---------------

<i>proc_min_ver</i>	in number(5),
---------------------	---------------

<i>case_number</i>	in integer,
--------------------	-------------

<i>graft_step_name</i>	in varchar2(8),
------------------------	-----------------

<i>graft_id</i>	in varchar2,
-----------------	--------------

<i>graft_count</i>	in integer)
--------------------	-------------

where:

- *proc_name* is the name of the parent procedure that you want to graft a sub-procedure to.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *case_number* is the case number of the main procedure that the sub-procedure is to be grafted to.
- *graft_step_name* is the name of the graft step in the *proc_name* procedure that the sub-procedure is to be grafted to.
- *graft_id* is a unique identifier for this instance of the *graft_step_name* graft step.

- *graft_count* is the number of items that are to be grafted to the *graft_step_name* graft step.

Notes

Instead of using the specific major or minor version number or both of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).



Note

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

For more information about graft steps and how to use them, see *TIBCO iProcess Modeler Integration Techniques*.

Example

See [SW_GRAFT](#).

SW_JUMPTO

The SW_JUMPTO procedure jumps a case from its current step to another step in the procedure, ignoring the procedure logic.

Syntax

```
SW_JUMPTO (
```

```
    proc_name                                in varchar2(8),
```

```
    proc_maj_ver                             in number(5),
```

<i>proc_min_ver</i>	in number(5) ,
<i>jump_step</i>	in varchar2(8) ,
<i>case_number</i>	in integer ,
<i>jump_reason</i>	in varchar(2) ,
<i>user_id</i>	in varchar2(24)
<i>failurecount</i>	in integer,)

where:

- *proc_name* is the name of the procedure that you want to jump a case of.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *jump_step* is the name of the step that the case is to jump to.
- *case_number* is the case number of the main procedure that is to jump.
- *jump_reason* is a reason for this jump, used in the audit trail
- *user_id* is the name of the iProcess user who is performing the jump.
- *failurecount* is an optional parameter. If passed, is used internally to pass it on to BusinessWorks and to wait for some time before retrying.

Notes

Instead of using the specific major or minor version number or both of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).

**Note**

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

If a SW_JUMPTO procedure specifies an invalid *jump_step*, the transaction is rolled back. A warning message is generated and an Invalid Step message is written to the audit trail.

For more information about jumps and how to use them, please see the TIBCO iProcess Objects and TIBCO iProcess Server Objects programmer guides.

Example

This example jumps case 102 of the CUSTREQ procedure from its current position in the workflow to STEP5. The reason for the jump will be displayed in the audit trail as “Administrator-initiated Jump”.

```
EXEC SSOLITE.SW_JUMPTO ('CUSTREQ', -1, -1, 'STEP5', 102, 'Administrator-  
initiated Jump', 'swadmin')
```

SW_JUMPTO_MULTI

The SW_JUMPTO_MULTI procedure is similar to [SW_JUMPTO](#) except that it can process, that is, jump to, more than one step. It allows the withdrawal of either a single step or all steps. In addition it allows setting of case data using the existing [SW_ADD_PACK_DATA](#) interface.

Syntax

```
SW_JUMPTO_MULTI (
```

<i>tgt_proc_name</i>	in varchar2(8),
<i>tgt_proc_maj_ver</i>	in number(5),
<i>tgt_proc_min_ver</i>	in number(5),
<i>src_step_name</i>	in varchar2(8),

<i>tgt_step_name</i>	in varchar2,
<i>case_number</i>	in integer,
<i>jump_reason</i>	in varchar(2),
<i>user_id</i>	in varchar2(24))

where:

- *tgt_proc_name* is the name of the procedure that you want to jump a case of.
- *tgt_proc_maj_ver* is either the major version number of the *tgt_proc_name* procedure, or -1. See the notes .
- *tgt_proc_min_ver* is either the minor version number of the *tgt_proc_name* procedure, or -1. See the notes .
- *src_step_name* is the name of the step to be withdrawn. Specifying * withdraws all outstanding steps.
- *tgt_step_name* is the name of the step that the case is to jump to. Use a comma-separated list of step names to jump to more than one step.
- *case_number* is the case number of the main procedure that is to jump.
- *jump_reason* is a reason for this jump, used in the audit trail.
- *user_id* is the name of the iProcess user who is performing the jump.

Notes

Instead of using the specific major or minor version number or both of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).



Note

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

If a `SW_JUMPTO_MULTI` procedure specifies an invalid *jump_step*, the transaction is rolled back. A warning message is generated and an Invalid Step message is written to the audit trail.

For more information about jumps and how to use them, please see the TIBCO iProcess Objects and TIBCO iProcess Server Objects programmer guides.

Example

This example jumps case 110 of the CARPOOL procedure to the `ALLOCATE` steps and `REFUSED`. The `REQUEST` step is withdrawn. The reason for the jump will be displayed in the audit trail as “Request Refused”.

```
EXEC SSOLITE.SW_JUMPTO_MULTI ('CARPOOL', -1, -1, 'REQUEST',
'ALLOCATE,REFUSED', 110, 'Request Refused', 'swadmin')
```

SW_PURGE

The `SW_PURGE` procedure purges the specified case of a procedure (permanently deleting it from the system). If events are set for the `OnBeforePurge` event, the events will be triggered when the case is about to purge but before the case is actually purged.

Syntax

SW_PURGE (
<i>proc_name</i>	in varchar2(8),
<i>proc_maj_ver</i>	in number(5),
<i>proc_min_ver</i>	in number(5),
<i>case_number</i>	in integer)

where:

- *proc_name* is the name of the procedure that you want to purge a case of. The case must be either active or closed.

- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *case_num* is the number of the case that is to be purged.

Notes

Instead of using the specific major or minor version number or both of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).



Note

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

Example

This example purges case 103 of the CUSTREQ procedure.

```
EXEC SSOLITE.SW_PURGE ('CUSTREQ', -1, -1, 103)
```

SW_PURGE_WITHOUT_EVENT

The SW_PURGE_WITHOUT_EVENT procedure purges the specified case of a procedure (permanently deleting it from the system) without triggering the events that are set for the OnBeforePurge event.

Syntax

```
SW_PURGE_WITHOUT_EVENT (
```

<i>proc_name</i>	in varchar2(8),
<i>proc_maj_ver</i>	in number(5),
<i>proc_min_ver</i>	in number(5),
<i>case_number</i>	in integer)

where:

- *proc_name* is the name of the procedure that you want to purge a case of. The case must be either active or closed.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *case_num* is the number of the case that is to be purged.

Notes

Instead of using the specific major or minor version number of the procedure, or both, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess uses the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).



Note

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

SW_SUSPEND

The SW_SUSPEND procedure suspends a case of a procedure.

Syntax

SW_SUSPEND (

<i>proc_name</i>	in varchar2(8),
------------------	-----------------

<i>proc_maj_ver</i>	in number(5),
---------------------	---------------

<i>proc_min_ver</i>	in number(5),
---------------------	---------------

<i>case_number</i>	in integer,
--------------------	-------------

<i>user_id</i>	in varchar2(24),
----------------	------------------

<i>suspend_type</i>	in integer)
---------------------	-------------

where:

- *proc_name* is the name of the procedure that you want to suspend a case of.
- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes.
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes.
- *case_number* is the number of the case that is to be suspended.
- *user_id* is the name of the iProcess user who is suspending the case.
- *suspend_type* defines the type of suspend action. This is an optional parameter that defaults to 2.

Notes

Instead of using the specific major or minor version number or both of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or,

that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).

**Note**

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

For more information about how to suspend and re-activate a case, please see the TIBCO iProcess Objects and TIBCO iProcess Server Objects programmer guide.

Example

This example suspends case 103 of the CUSTREQ procedure.

```
EXEC SSOLITE.SW_SUSPEND ('CUSTREQ', -1, -1, 103, 'swadmin', 2)
```

SW_ACTIVATE

The SW_ACTIVATE procedure re-activates a previously suspended case of a procedure.

Syntax

SW_ACTIVATE (

<i>proc_name</i>	in varchar2(8),
<i>proc_maj_ver</i>	in number(5),
<i>proc_min_ver</i>	in number(5),
<i>case_number</i>	in integer,
<i>user_id</i>	in varchar2(24))

where:

- *proc_name* is the name of the procedure that you want to reactivate a case of.

- *proc_maj_ver* is either the major version number of the *proc_name* procedure, or -1. See the notes .
- *proc_min_ver* is either the minor version number of the *proc_name* procedure, or -1. See the notes .
- *case_number* is the number of the suspended case that is to be reactivated.
- *user_id* is the name of the iProcess user who is re-activating the case.

Notes

Instead of using the specific major or minor version number, or both, of the procedure, you can specify both the *proc_maj_ver* and *proc_min_ver* parameters as -1. If you do this, iProcess will use the version number of the procedure that the case was originally started with or, that it has subsequently been migrated to (if a subsequent version has been released while the case is still in progress).



Note

If you specify one version number parameter as -1, you must specify the other one as -1 as well.

For more information about how to suspend and reactivate a case, please see the TIBCO iProcess Objects and TIBCO iProcess Server Objects programmer guide.

Example

This example re-activates case 103 of the CUSTREQ procedure.

```
EXEC SSOLITE.SW_ACTIVATE ('CUSTREQ', -1, -1, 103, 'swadmin')
```

Control Procedures

The following control procedures are available:

- [SW_ENABLECACHING](#)
- [SW_DISABLECACHING](#)
- [SW_SET_MBOX](#)

- [SW_SET_PRIORITY](#)
- [SW_SET_QUEUE](#)
- [SW_UNSET_MBOX](#)
- [SW_UNSET_PRIORITY](#)
- [SW_UNSET_QUEUE](#)

SW_ENABLECACHING

The `SW_ENABLECACHING` procedure enables the caching of work item (`reqid`) and case number (`casenum`) sequence numbers for the current database session.

Syntax

```
SW_ENABLECACHING ( )
```

Notes

Caching `reqid` and `casenum` sequence numbers can be done to enhance batch SQL performance in appropriate situations.

When sequence number caching is enabled, the first transaction in the session retrieves its sequence numbers from the database, but subsequent transactions in the same session retrieve their sequences from the cache. (The size of the cache is determined by the value of the `CNUM_SEQ_CACHE` and `REQID_SEQ_CACHE` process attributes).

Unused sequence numbers in the cache are discarded when the database session terminates. This can result in gaps in the value of the sequence numbers if caching is used inappropriately. For example, if you enable caching for a session that simply starts a single case, all the unused `iProcess` case numbers will be lost.

Sequence number caching is enabled by default when a database session is started. Use the [SW_DISABLECACHING](#) procedure to disable sequence number caching.

For more information about sequence number caching, see "Sequence Number Caching" in *TIBCO iProcess Engine Administrator's Guide*.



The SW_ENABLECACHING procedure is part of the SSOLITE_MSG package.

Note

SW_DISABLECACHING

The SW_DISABLECACHING procedure disables the caching of work item (reqid) and case number (casenum) sequence numbers for the current database session.

Syntax

```
SW_DISABLECACHING ( )
```

Notes

Sequence number caching is enabled by default when a database session is started.

See the [SW_ENABLECACHING](#) procedure for more information about the use of sequence number caching, and when you should enable or disable it.



The SW_DISABLECACHING procedure is part of the SSOLITE_MSG package.

Note

SW_SET_MBOX

The SW_SET_MBOX procedure tells the current SSOLite session to use a different Mbox set from the default one.

Syntax

```
SW_SET_MBOX (   
    mbox_set_id                in number(5) )
```

where:

- *mbox_set_id* is a unique identifier for the Mbox set you want to use.

Notes

This procedure is useful to partition messages for the purpose of performance or service levels. The procedure can be used in many ways, including separating out bulk operations, such as purging or starting cases. Other sessions will still use the default Mbox set for operations such as delayed releases.

Use the [SW_UNSET_MBOX](#) procedure to restore using the default Mbox set for all operations.

Example

The following example shows how to set another Mbox set BGMBSETB for bulk operations. You must create the `sw_db_bgqueue_4` physical queues `bgmboxtable3` and `bgmboxtable4` tables, and the `bgmboxqueue3` and `bgmboxqueue4` AQ first. For more information about queue processing and Mbox set creation, see [Processing Queues](#).

```
# Step 1. Add two new message queues.
#
swadm add_queue BGMBBOX3 Local 0001::bgmboxtable3:bgmboxqueue3
swadm add_queue BGMBBOX4 Local 0001::bgmboxtable4:bgmboxqueue4

# Step 2. Add a new Mbox set.
#
swadm add_mboxset BGMGSETB Local

# Step 3. View Mbox and queue IDs.
#
swadm show_mboxsets v
swadm show_queues

# Step 4. Add the BGMBBOX3 and BGMBBOX4 message queues to the BGMGSETB Mbox
set (
6 is the Mboxset ID of the BGMGSETB Mbox set,
8 is the queue ID of the BGMBBOX3 message queue, and
9 is the queue ID of the BGMBBOX4 message queue.)
#
swadm add_queue_to_mboxset 6 8
swadm add_queue_to_mboxset 6 9

# Step 5. Set the BGMGSETB Mbox set for bulk case starts.
#
EXEC ssolite.SW_SET_MBOX(6);
```

```

# Step 6. Start the bulk cases.
#
declare
casenum numeric(20);
reqid numeric(20);
begin
    ssolite_data.SW_ADD_PACK_DATA ('CustName', 'Allsop, J.A. ');
    ssolite_data.SW_ADD_PACK_DATA ('CustID', '478163 ');
    ssolite.SW_CASESTART ('CUSTREQ', -1, -1, 'Refund request', 'user35',
'', casenum, reqid);

end;
/
commit;

# Step 7. Restore using the default Mbox set.
#
EXEC ssolite.SW_UNSET_MBOX();

```

SW_SET_PRIORITY

The `SW_SET_PRIORITY` procedure sets the internal message queue priorities. The procedure *only* changes the priority of the messages that SSOLite sends. It does not change the `SW_CP_VALUE` and `SW_IP_VALUE`. So any subsequent messages for that case will remain at the default level or will be processed in the order of `SW_CP_VALUE` or `SW_IP_VALUE` when using iProcess Workspace (Windows) to process work items.

Syntax

```

SW_SET_PRIORITY (
    message_priority    in integer)

```

where:

- *message_priority* is the priority value.

You can set priorities ranging from 1 to 999, where 1 is the highest priority, for internal message queues when passing messages between iProcess processes such as from the Background process to WIS processes, or from SSOLite to the Background process. Its default value is 50. See [Prioritizing Messages](#) for more information.

Notes

Use the [SW_UNSET_PRIORITY](#) procedure to restore the default message queue priorities.

Example

The following example sets the SW_CASESTART priority of Case1 and Case2 to 70, Case3 and Case4 to 100, and Case5 to the default priority.

```
begin
ssolite.SW_SET_PRIORITY (70);
ssolite.SW_CASESTART ('CUSTREQ', -1, -1, 'Case1', 'user35', '', 0, 0);
ssolite.SW_CASESTART ('CUSTREQ', -1, -1, 'Case2', 'user35', '', 0, 0);
ssolite.SW_SET_PRIORITY (100);
ssolite.SW_CASESTART ('CUSTREQ', -1, -1, 'Case3', 'user35', '', 0, 0);
ssolite.SW_CASESTART ('CUSTREQ', -1, -1, 'Case4', 'user35', '', 0, 0);
ssolite.SW_UNSET_PRIORITY ();
ssolite.SW_CASESTART ('CUSTREQ', -1, -1, 'Case5', 'user35', '', 0, 0);
end;
/
commit;
```

SW_SET_QUEUE

The SW_SET_QUEUE procedure forces all messages posted in the current database session to use the same background queue.

Syntax

```
SW_SET_QUEUE ( )
```

Notes

By default, SSOLite stored procedures write messages to the BG processes using the default background message queues, using a round-robin allocation on a per-session basis. This allows the message load to be spread evenly across all of the available background queues. (See [Processing Queues](#) for more information.)

If required, you can use the `SW_SET_QUEUE` procedure to force all messages that are subsequently posted in the current session to use the same background queue.

After the `SW_SET_QUEUE` procedure has been called, the next message that is posted uses the next available background queue (as per normal round-robin allocation). Subsequent messages are then posted to the same queue, until either:

- the [SW_UNSET_QUEUE](#) procedure is called, after which messages are again allocated on the default round-robin basis, or
- the database session is terminated.

SW_UNSET_MBOX

The `SW_UNSET_MBOX` procedure restores using the default Mbox set for all operations.

Syntax

```
SW_UNSET_MBOX ()
```

Notes

Use the [SW_SET_MBOX](#) procedure to tell SSOLite to use a different Mbox set for bulk purges or bulk case starts.

Example

See the example of [SW_SET_MBOX](#).

SW_UNSET_PRIORITY

The `SW_SET_PRIORITY` procedure restores the default message queue priorities.

Syntax

```
SW_UNSET_PRIORITY ()
```

Note

You can set priorities for internal message queues when passing messages between iProcess processes such as from SSOLite to the BG process. See [Prioritizing Messages](#) for more information.

Use the [SW_SET_PRIORITY](#) procedure to set the internal message queue priorities.

SW_UNSET_QUEUE

The `SW_UNSET_QUEUE` procedure forces the use of round-robin queue allocation for messages posted in the current database session.

Syntax

```
SW_UNSET_QUEUE ( )
```

Notes

The `SW_UNSET_QUEUE` procedure cancels the effect of a previous [SW_SET_QUEUE](#) procedure call. See the [SW_SET_QUEUE](#) procedure for more information.

Debug Procedures

The following debug procedures are available:

- [SW_SET_DEBUG](#)
- [SW_GET_DEBUG](#)
- [SW_CLEAR_DEBUG](#)

Debug output data is stored in the following temporary table:

```
TEMPORARY TABLE SSOLITE_DEBUG_DATA (  
  message varchar(256));
```

The table simply holds the debug message text in inserted order. If an application has enabled debugging, a simple `select * from SSOLITE_DEBUG_DATA` statement can be used to display the debug data.

SW_SET_DEBUG

The `SW_SET_DEBUG` procedure turns debugging on or off.

Syntax

```
SW_SET_DEBUG(  
    enable                in integer)
```

where *enable* is a flag that turns debugging on or off. Specify the following conditions:

- 1 to enable debugging (and create the `SSOLITE_DEBUG_DATA` temporary table).
- 0 to disable debugging. Note that any existing debug information written to the `SSOLITE_DEBUG_DATA` temporary table for the current transaction is still available.

SW_GET_DEBUG

`SW_GET_DEBUG` returns the number of rows of debug data that are available in the `SSOLITE_DEBUG_DATA` table, or -1 if debugging is not enabled.

Syntax

```
SW_GET_DEBUG() returns integer
```

Notes

You must call `SW_GET_DEBUG` to populate the `SSOLITE_DEBUG_DATA` table. Calling the procedure copies data from the Oracle `DBMS_OUTPUT` package to SSOLite's own data type.

SW_CLEAR_DEBUG

Calling SW_CLEAR_DEBUG clears all existing debug data and resets the SSOLITE_DEBUG_DATA temporary table.

Syntax

```
SW_CLEAR_DEBUG()
```

Notes

Use of this procedure is optional, as the use of temporary tables to hold debug data ensures that data is cleared anyway.

Database Stored Procedures

This appendix describes the package of database-stored procedures.

Overview

Database stored procedures are available in the iProcess database and you can find them in the Oracle script file, `init2Kora_tok.sql`.

Sequence numbers can be generated by calling the stored procedures. See [Sequence Numbers](#) for more information.

The database stored procedures include:

- `sp_cdqp_cfg_sequence`
- `sp_cdqp_def_sequence`
- `sp_cnum_sequence`
- `sp_procid_sequence`
- `sp_reqid_sequence`
- `sp_waitid_sequence`
- `sp_iap_monitor_id_sequence`
- `sp_eaiws_jms_provider_seq`
- `sp_eaiws_jms_destination_seq`
- `casenum_find_gaps`

CASENUM_FIND_GAPS

The `CASENUM_FIND_GAPS` stored procedure adds a list of free case number gaps to the `casenum_gaps` table.

If the case number or the subcase number generated from the sequence table reaches the maximum case number, 4294967295, then the following cases cannot be started. This stored procedure is used to scan a range of case numbers and create available blocks of free case numbers for reuse. It operates across a case range and only allocates free case numbers. The free case numbers are available either because the case numbers have never been used or from the original cases that have been purged.

The `casenum_gaps` table holds the free case number gaps that are created by the `CASENUM_FIND_GAPS` stored procedure. See [casenum_gaps](#) for more information.

Syntax

```
CASENUM_FIND_GAPS (
    v_casenum_min    IN NUMBER,
    v_casenum_max    IN NUMBER,
    v_gap_size       IN NUMBER)
```

where:

- `v_casenum_min` specifies the minimum case number of the range.
- `v_casenum_max` specifies the maximum case number of the range.
- `v_gap_size` specifies the minimum size of a gap that contains only free case numbers.

How to Reuse Free Case Numbers

Perform the following steps to reuse the free case numbers:

i Note: TIBCO recommends that you shut down iProcess Engine before running `CASENUM_FIND_GAPS`. If you want to run the procedure against a running system, you must ensure that the case range supplied does not overlap with the ranges currently being used, as there is the possibility of overlapping gaps with duplicate case numbers being created.

1. Shut down TIBCO iProcess Engine.
2. Periodically run the `CASENUM_FIND_GAPS` stored procedure as the database administrator.

To do this, you can create a SQL script as shown in the following example, and use SQL*Plus to run the script.

```

conn swpro_11309/swpro_11309@ORCL;
set serveroutput on
BEGIN
CASENUM_FIND_GAPS ( 100, 500, 20);
END;
/
quit;

```

In the example, CASENUM_FIND_GAPS (100, 500, 20) looks for the gaps of at least 20 free case numbers from 100 to 500. If the range has three gaps: 130 - 140, 240 - 270, and 430 - 480, only the last two gaps will be listed in the casenum_gaps table for iProcess Engine to allocate case numbers.

3. Restart TIBCO iProcess Engine.

When TIBCO iProcess Engine wants to cache a new batch of sequences, it will first use the case numbers in the casenum_gaps table that are listed by the CASENUM_FIND_GAPS stored procedure and then allocate the unused new case numbers when the case numbers in the table are used up.

Notes

Before running the stored procedure, note that:

- Running the CASENUM_FIND_GAPS stored procedure may take a long time. It is only of benefit in the areas where the density of the occupied case numbers is low enough to have many gaps in between. This is typically in the lower range of case numbers, as these are older cases and more likely to have been closed and purged. The area close to the most recently started cases is likely to be densely populated, because all these cases are new and less likely to be closed and purged.
- Ensure that there are enough available case numbers for reuse by creating a sound purge strategy.
- TIBCO recommends that you do not run CASENUM_FIND_GAPS repeatedly on the same case number range. Check the values in the casenum_gaps table for the listed gaps and run the procedure on a range outside of the highest and lowest figures in the table.
- The performance of CASENUM_FIND_GAPS is proportional not to the size of the range, but to the number of actual cases in the range. For instance, when running it on a range from 0 to 100 million, if there are only 5000 cases in that range, it will be very fast and might only take a few seconds. While running it on a range from 100 million to 105 million, if there are close to 5 million cases in that range, it will take

considerably longer. To find how many cases are in the intended range, run the following SQL:

- `SELECT COUNT(*) FROM CASE_INFORMATION WHERE CASENUM > v_casenum_min AND CASENUM < v_casenum_max`
- Based on previous runs and recorded timings, you might be able to predict the time `CASENUM_FIND_GAPS` will take for any given range with a reasonable amount of accuracy.

See Also

- [casenum_gaps](#)

XPC_CREATE_INDEX

`XPC_CREATE_INDEX` is used for creating a custom index on a given table-based on the user's needs.

Syntax

```
XPC_CREATE_INDEX (
    idx_xpc_name    VARCHAR(32))
```

The valid values for `idx_xpc_name` are:

- `idx_xpc_status`: Creates an index on the case information table with columns `is_dead`, `casenum`, and `proc_id`.
- `idx_xpc_ended`: Creates an index on the case information table with columns `next_deadline`, `casenum`, and `proc_id`.
- `idx_xpc_started`: Creates an index on the case information table with columns `started`, `casenum`, and `proc_id`.
- `idx_xpc_starter`: Creates an index on the case information table with columns `starter`, `casenum`, and `proc_id`.
- `idx_xpc_tid`: Creates an index on the case information table with columns `type_id`, and `casenum`.

- **idx_xpc_date:** Creates an index on the case information table with columns audit_date, and casenum.
- **idx_xpc_desc:** Creates an index on the case information table with columns stepdesc, and casenum.
- **idx_xpc_step:** Creates an index on the case information table with columns stepname, and casenum.
- **idx_xpc_user:** Creates an index on the case information table with columns user_name, and casenum.

This stored procedure addresses any performance issues while searching millions of cases in the database. With the help of this logic, iProcess Engine checks the filter and the tables involved. In the search, if there is no proper index created, the system throws a suggestion in sw_warn and system event to create index to improve the performance. iProcess Engine checks for the index on the following fields, with the corresponding database table and database columns.

SYSTEM FIELD	INDEX INPUT	DB TABLE	DB COLUMN
SW_STATUS	idx_xpc_status	case_information	is_dead
SW_TERMINATED	idx_xpc_ended	case_information	next_deadline
SW_TERMINATEDDATE	idx_xpc_ended	case_information	next_deadline
SW_STARTED	idx_xpc_started	case_information	started
SW_STARTEDDATE	idx_xpc_started	case_information	started
SW_STARTER	idx_xpc_starter	case_information	starter
SW_AUD_TYPE	idx_xpc_tid	audit_trail	type_id
SW_AUD_DATE	idx_xpc_date	audit_trail	audit_date
SW_AUD_USER	idx_xpc_user	audit_trail	user_name
SW_AUD_STEP	idx_xpc_step	audit_trail	stepname
SW_AUD_DESC	idx_xpc_desc	audit_trail	stepdesc

This is primarily used when working with "Filtering Work Items and Cases" (Ref: TIBCO iProcess® Server Objects (Java) or (.NET) Programmer's Guide)

Unused Tables

The following tables are created by the database creation script (`init2Kora.sql` on UNIX, `init2Kora_tok.sql` on Windows), but are not currently used by iProcess Engine:

- `pack_attach`
- `process_invqueue`
- `prounqid`
- `attachment`

**Warning**

Do not delete these tables. They are reserved for possible future use.

TIBCO Documentation and Support Services

For information about this product, you can read the documentation, contact TIBCO Support, and join TIBCO Community.

How to Access TIBCO Documentation

Documentation for TIBCO products is available on the [Product Documentation website](#), mainly in HTML and PDF formats.

The [Product Documentation website](#) is updated frequently and is more current than any other documentation included with the product.

Product-Specific Documentation

The documentation for this product is available on the [TIBCO iProcess® Engine Product Documentation](#) page.

How to Contact Support for TIBCO Products

You can contact the Support team in the following ways:

- To access the Support Knowledge Base and getting personalized content about products you are interested in, visit our [product Support website](#).
- To create a Support case, you must have a valid maintenance or support contract with a Cloud Software Group entity. You also need a username and password to log in to the [product Support website](#). If you do not have a username, you can request one by clicking **Register** on the website.

How to Join TIBCO Community

TIBCO Community is the official channel for TIBCO customers, partners, and employee subject matter experts to share and access their collective experience. TIBCO Community offers access to Q&A forums, product wikis, and best practices. It also offers access to extensions, adapters, solution accelerators, and tools that extend and enable customers to gain full value from TIBCO products. In addition, users can submit and vote on feature

requests from within the [TIBCO Ideas Portal](#). For a free registration, go to [TIBCO Community](#).

Legal and Third-Party Notices

SOME CLOUD SOFTWARE GROUP, INC. (“CLOUD SG”) SOFTWARE AND CLOUD SERVICES EMBED, BUNDLE, OR OTHERWISE INCLUDE OTHER SOFTWARE, INCLUDING OTHER CLOUD SG SOFTWARE (COLLECTIVELY, “INCLUDED SOFTWARE”). USE OF INCLUDED SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED CLOUD SG SOFTWARE AND/OR CLOUD SERVICES. THE INCLUDED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER CLOUD SG SOFTWARE AND/OR CLOUD SERVICES OR FOR ANY OTHER PURPOSE.

USE OF CLOUD SG SOFTWARE AND CLOUD SERVICES IS SUBJECT TO THE TERMS AND CONDITIONS OF AN AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER AGREEMENT WHICH IS DISPLAYED WHEN ACCESSING, DOWNLOADING, OR INSTALLING THE SOFTWARE OR CLOUD SERVICES (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH LICENSE AGREEMENT OR CLICKWRAP END USER AGREEMENT, THE LICENSE(S) LOCATED IN THE “LICENSE” FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE SAME TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

This document is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of Cloud Software Group, Inc.

TIBCO, the TIBCO logo, the TIBCO O logo, ActiveMatrix BusinessWorks, Business Studio, Enterprise Message Service, Hawk, iProcess, and Rendezvous are either registered trademarks or trademarks of Cloud Software Group, Inc. in the United States and/or other countries.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only. You acknowledge that all rights to these third party marks are the exclusive property of their respective owners. Please refer to Cloud SG’s Third Party Trademark Notices (<https://www.cloud.com/legal>) for more information.

This document includes fonts that are licensed under the SIL Open Font License, Version 1.1, which is available at: <https://scripts.sil.org/OFL>

Copyright (c) Paul D. Hunt, with Reserved Font Name Source Sans Pro and Source Code Pro.

Cloud SG software may be available on multiple operating systems. However, not all operating system platforms for a specific software version are released at the same time. See the “readme” file for the availability of a specific version of Cloud SG software on a specific operating system platform.

THIS DOCUMENT IS PROVIDED “AS IS” WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. CLOUD SG MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S), THE PROGRAM(S), AND/OR THE SERVICES DESCRIBED IN THIS DOCUMENT AT ANY TIME WITHOUT NOTICE.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "README" FILES.

This and other products of Cloud SG may be covered by registered patents. For details, please refer to the Virtual Patent Marking document located at <https://www.tibco.com/patents>.

Copyright © 1994-2024. Cloud Software Group, Inc. All Rights Reserved.